

M14 Rifle History and Development

Text Only Edition

Lee Emerson

Copyright 2009 - 2013 by Lee Emerson

All rights reserved. No part of this book may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying, recording, or by any information storage and retrieval system, without permission in writing from the copyright owner.

Front Cover: September 01, 1987 - Armed with a M14A1 rifle, a U. S. Navy Sea-Air-Land (SEAL) team member hides in the foliage at the edge of a river while providing cover for fellow team members during a tactical warfare training exercise. Photo by Journalist First Class Lynn Jenkins, U. S. Navy.

Back Cover: Photo by the author.

“Sincere and strong love is greatly gratified and delighted in the prosperity of the beloved object; and if the love be perfect, the greater the prosperity of the beloved is, the more is the lover pleased and delighted; for the prosperity of the beloved is, as it were, the food of love, and therefore the greater that prosperity, the more richly is love feasted.” – Jonathan Edwards, *Heaven, A World of Charity Or Love*, Northampton, England, 1738.

This book is dedicated to those who love and to those who love liberty.

Table of Contents

Preface	9
Part 1: The Military M14	11
Introduction	11
Engineering Material	12
Engineering Definitions	12
AISI 4100 and 8600 Series Alloy Steels	15
M14 Rifle Preservation	15
M14 Rifle Lubrication	20
M14 Receiver Material	33
AISI 8620 Alloy Steel	36
How was the U. S. Government Issue M14 receiver made?	37
Receiver Heat Treatment	38
Development of Magnetic Particle Inspection	40
USGI Receiver Geometry	40
Intervening Rifle Models: M2 through M13	44
M14 Rifle Development Highlights	45
M14 Rifle Factory Inspection	55
M14 Production at Springfield Armory	57
M14 Production at Winchester	58
M14 Production at Harrington & Richardson	60
M14 Production at TRW	67
The TRW Mystique	69
Raritan Arsenal	71
Experimental Items for the USGI M14 Rifle	72
The Issue M14 Rifle	79
The M14 Rifle in Overhaul	86
M14 in Service with the U. S. Army and U. S. Marine Corps	87
The M14 in the U. S. Navy	98
The M14 in Other Service	99
The M14 in the Arts and Entertainment	102

Museum Collections	111
Israel Defense Forces	111
Other Foreign Hostile Action	112
Taiwan	114
Destruction and Export of USGI M14 Rifles	116
Foreign Sales of USGI M14 Rifles	121
M14E1	123
M14E2 and M14A1	124
M14 Grenadier	127
M14 M	128
M14 NM	129
M15	132
U. S. Army Snipers and the XM21 and M21	133
M14 Product Improved Rifle	139
XM25 and M25	140
M14 SMUD	142
M14 DMR	143
M39 EMR	145
U. S. Marine Corps Scout-Snipers and the M14 Rifle	146
M14 Enhanced Battle Rifle	147
M14SE, Mk 14 SEI and M80 SDM	153
Semi-automatic Only USGI M14 Rifles	158
Hahn Machine Company and Pearl Manufacturing	159
U. S. Civilian Ownership of Select Fire USGI and Chinese M14 Rifles	160
Ignore the Petition to Sell the M14!	163
Select Fire M14 Rifle Rate of Fire Modification	163
Military versus Civilian Use	164
Part 2: The Commercial M14	169
U. S. Commercial Production of the M14 Type Rifle	169
Characteristics of Commercial Receivers	169
Commercial Receiver Geometry	171
U. S. Commercial Manufacture Select Fire M14 Type Rifles	174

Camp Perry Military Reservation	175
Civilian and Military Marksmanship Awards	176
Springfield Armory, Inc.	179
Texas Production	179
M1A Receiver Shipments from 1971 to 1975	185
The Texas M1A	186
Transition from Texas to Illinois	188
Illinois Production	189
Illinois M1A Models	191
Gray-Syracuse, Inc., Valley Ordnance Co. and Hillside Manufacturing	198
Springfield Armory, Inc. and Glenn Nelson	207
Rock Island Armory, Inc.	209
Karl Maunz	209
H & R Gun Co. and Smith Ltd.	213
A. R. Sales Co., National Ordnance, Inc. and Federal Ordnance, Inc.	215
Armscorp	222
Fulton Armory	225
Western Ordnance/Smith Enterprise, Inc.	227
Smith Enterprise, Inc. Receiver Design, Manufacture and Testing	229
Smith Enterprise, Inc. Receiver Identification	231
Smith Enterprise, Inc. M14 Services	232
M14K	233
AWC Systems Technology	234
Hesse, Ltd. and Sarco, Inc.	235
Entreprise Arms, Inc.	235
Troy Industries, Inc.	236
LRB of Long Island, Inc.	238
7.62mm Firearms	242
James River Armory	243
Origin of Chinese M14 Rifles	243
Norinco and Poly Technologies Corporation	246
Production and Export of Chinese M14 Rifles	247
Chinese M14 Rifle Export to the United States	249

Keng's Firearms Specialty, Incorporated	250
Century Arms International	251
IDE USA and CJA	252
Chinese M14 Rifle Export to Canada	253
Chinese Receivers	254
Markings of Exported Chinese M14 Rifles	254
United States Firearms Laws	256
U. S. Law and the Chinese M14 Rifle	258
1994 Assault Weapons Ban	262
Canada Firearms Laws	263
Part 3: All Things Small and Wonderful	265
M14 Barrel Material	265
General Information on AISI 4140 Alloy Steel	265
General Information on AISI 416 Stainless Steel	266
The Barrel Making Process	267
M14 Barrel Length	268
USGI M14 Rack Grade Barrels	268
USGI M14 National Match Barrels	270
Chinese M14 Barrels	273
U. S. Commercial M14 Barrels	273
USGI M14 Stock Designs	276
USGI M14 Wood Stocks	276
USGI M14 Synthetic Stocks	282
USGI M14E2 Stocks	285
Commercial Synthetic Match Grade Stocks	286
Commercial Folding and Telescoping Stocks	287
Other Stocks	301
Hand Guards	311
USGI Sights	314
Commercial Sights	317
Muzzle Attachments	319
Military Sound Suppressors	327

Commercial Sound Suppressors	330
USGI M14 Technical and Training Documents	333
Timeline of U. S. Army M14 Field Manuals	335
Timeline of U. S. Army M14 Technical Manuals	335
USGI Parts	338
USGI Parts Sales	358
Parts Interchangeability with the M1 Garand Rifle	359
M1 Garand Parts on M14 Type Rifles	360
USGI Parts Packaging	361
Notes on Commercial Parts	362
Notes on Chinese Parts	372
Commercial Parts Identification	374
USGI Magazines	376
Foreign Manufacture Magazines	379
U. S. Commercial Magazines	380
Miscellaneous Notes on Scope Mounts	382
Side Single Point Scope Mounts	383
Side Two Point Scope Mounts	385
Side Three Point Scope Mounts	386
Side Three Point Scope Mount Fitting on Commercial M14 Receivers	394
Scope Mounts Secured to the Rear Sight Pocket	395
Rail System Mounts	397
Barrel Rail Mounts	399
Cleaning Kit	402
USGI Tools	404
Commercially Available Tools	406
USGI Accessories	407
Commercial Accessories	414
M2 Type Bipods	417
Other Bipods	419
Ammunition	420
Other Calibers	425
M14 Problems	427

1987 Springfield Armory, Inc. Recall Notice	431
Accurizing Tips	432
Miscellaneous Tips	433
Your Relationship with M14 Gunsmiths and Firearms Dealers	435
Appendix A: The Military M14	437
Table 1: Elements of Alloy Steels	437
Table 2: Composition of AISI 8620, AISI 4140 and AISI 416 Steels	438
Table 3: Properties of AISI 8620, AISI 4140 and AISI 416 Steels	438
Table 4: Suppliers of USGI Rifle Grease	439
Table 5: Select Properties of Some Military Greases	440
Table 6: Select Properties of Some Military Lubricating Oils	441
Table 7: Coefficient of Static Friction for Select Materials	442
Table 8: Harrington & Richardson X Series Rifles	442
Table 9: M14 Rifle on Television	443
Table 10: Springfield Armory National Historic Site M14 Rifles	450
Table 11: U. S. Government Exports of M14 Rifles to Foreign Nations	451
Table 12: M14E1 Rifle Types	451
Table 13: M14 Type Rifle Headspace Dimensions	452
Table 14: 7.62x51 mm NATO Ammunition	453
Table 15: Significant Military Tests Involving the USGI M14 Rifle	455
Table 16: United States Patents	458
Appendix B: The Commercial M14	465
Table 17: Production of Commercial M14 Rifles	465
Table 18: Commercial M14 Production and Export Data	467
Table 19: Norinco M14 Rifles Imported Into the United States	468
Table 20: Poly Technologies M14 Rifles Imported Into the United States	469
Table 21: Chinese M14 Rifles Imported Into Canada	469
Table 22: U. S. Federal Firearms Licenses	470
Table 23: M14 Magazine Capacity Restrictions in the USA	471
Table 24: Retail Suppliers of USGI M14 Related Items - 1970 and 1971	472
Table 25: Springfield Armory, Inc.	474
Table 26: Smith Enterprise, Inc.	491

Table 27: Federal Ordnance, Inc.	493
Table 28: Enterprise Arms, Inc.	494
Table 29: Armscorp	495
Table 30: Fulton Armory	496
Table 31: LRB Arms	497
Table 32: 7.62mm Firearms	502
Table 33: Springfield Armory, Inc. M1A Rifle Stock Numbers	503
Table 34: Springfield Armory, Inc. M1A Related Items Stock Numbers	513
Appendix C: All Things Small and Wonderful	527
Table 35: M14 Type Rifle Barrel Lengths	527
Table 36: Composition of USGI Barrels	531
Table 37: Properties of Walnut, Birch and Cherry	531
Table 38: U. S. Military M14 Publications	531
Table 39: U. S. Military Publications for M14 Related Items	534
Table 40: U. S. Military Publications for M14 Optical Sights	535
Table 41: Material Selection for USGI M14 Parts	537
Table 42: Observed Manufacture Dates for USGI M14 Rifle Items	542
Table 43: Subcontractors to USGI Contractors	545
Table 44: USGI Contractors for M14 Rifle Items	555
Table 45: USGI M14 Rifle Items with Part Number Markings	572
Table 46: USGI M14 Rifle Parts and Accessories Packaging	573
Table 47: Chinese M14 Rifle Part Markings	576
Table 48: Timeline of USGI Magazine Contractors	577
Table 49: Barrel and Receiver Group Items	578
Table 50: Bolt Assembly Items	591
Table 51: Operating Rod Group Items	593
Table 52: Firing Mechanism Items	594
Table 53: M14 Stock and Hand Guard Items	597
Table 54: M14 Stock Butt Plate Assembly Items	603
Table 55: M14E2/M14A1 Stock Assembly Items	605
Table 56: M14 DMR Stock Assembly Items	610
Table 57: Sage International Stock Assembly Items	611

Table 58: Twenty Round Magazine Items	619
Table 59: M2 Bipod Items	620
Table 60: Organizational Maintenance Items	624
Table 61: Direct Support Maintenance Items	628
Table 62: General Support (Depot) Maintenance Items	630
Table 63: Procurement Substitutions - Interchangeable Items	634
Table 64: Accessories for Various USGI M14 Rifles	638
Table 65: Comparison of USGI Multi-tools	651
Table 66: Repair Items	652
Table 67: T44E4 Rifle Parts and Recommended Spare Parts	653
Table 68: T12 Bayonet Parts	659
Table 69: T140 and M76 Grenade Launcher Parts	660
Table 70: T6 Auxiliary Winter Trigger Parts	661
Table 71: T44E5 Rifle Parts and Recommended Spare Parts	661
Table 72: M14 Rifle Spare Parts Allowance for 100 Rifles	668
Table 73: M14 Rifle Parts Replacement	672
Table 74: M14E2 Rifle Parts Replacement	674
Bibliography	677

Preface

This work is an honest and reasonable attempt at capturing the history and development of the M14 rifle. The reader is encouraged to check the facts for himself. The M14 rifle story is still very much in progress.

Thank you to members of the www.makereadyforum.com, www.m14tfl.com, and www.warrifles.com Internet discussion boards for their support and helpful suggestions. Special thanks go to LAW483 Enterprises, Sadlak Industries, Smith Enterprise, SparrowHawk Stocks, Troy Industries, Warbirds Custom Guns, and William J. Ricca Surplus for their generous assistance. The author thanks those who have contributed to this work but wish to remain anonymous. Other Sources # 12, # 18 and # 27 made significant contributions to this volume.

The copy editing chore for the First Edition was freely and graciously donated by Brent A. Blanchard, Attorney and Counselor at Law. Mr. Blanchard learned to shoot from his dad as a child. He shot smallbore rifle as a teenager and was a member of the Brigham Young University Army ROTC Rifle Team. He competed in High Power competition matches in the 1980s while the M14 rifle was king of competition shooting. After he learned that careers in public relations, marketing, and financial planning were not to his liking, Mr. Blanchard went to law school. He was admitted to the bar in the State of Nevada after graduation and later accepted a position at a law firm in Las Vegas, NV.

William Cook Richards generously gave his time to the task of copy editing for the Second Edition. Additionally, his thoughtful suggestions regarding the use of publishing software resulted in a better layout with the Second Edition.

There are no double quotes before and after specific alphanumeric characters used to identify equipment and rifle parts. The substantial number of rifle part identifying marks and dimensional measurements included in the narrow focus of this volume renders those conventions distracting. In this work, "Springfield Armory" refers to the U. S. government installation. The name "Springfield Armory, Inc." belongs to the commercial firearms manufacturer.

Due to the nature of the Internet, web site addresses listed in the Bibliography were active at the time research was conducted but may not work thereafter. Some rifle models, parts or accessories discussed in this work may not be available due to the limited number made or because the manufacturer is no longer in business.

Always handle all firearms in a safe manner. There are four basic rules of firearms safety: 1) **Treat every gun as if it was loaded** 2) **Never point the muzzle at anything you are not willing to destroy** 3) **Keep your finger off the trigger until the sights are on the target** and 4) **Always be sure of your target and what is behind and to the sides of it.** Metal targets present a ricochet hazard. Ricochets can come back to the firing line from which they originated. Wear proper attire, e.g., no tank tops, and personal protective equipment (ear muffs or plugs and shooting glasses) when shooting.

LEE EMERSON

Always read and follow product safety warnings and instructions. This includes all firearms, ammunition, accessories, and gun care products. Use hand and portable tools safely and in the manner for which they are designed. Consult with law enforcement officials or an attorney if you are unsure of the law where you live.

I trust you will find this work helpful in your pursuit of happiness.

Lee Emerson
December 2013
Las Vegas, NV

Part 1

The Military M14

Introduction

The U.S. Rifle 7.62 mm M14 was adopted for military service by the United States on May 01, 1957. The announcement was made by William H. Brucker, Secretary of the Army. The rifle was officially designated M14 in the U. S. Army Ordnance Technical Committee document OTCM 36558 on June 05, 1957. The M14 rifle was developed to replace four types of military small arms: M1 Rifle, M1 and M2 Carbines, M1918 Browning Automatic Rifle and M3A1 submachine gun. This was an ambitious goal reflecting the long-standing traditions of economy and marksmanship in the U. S. Army. The technology of the time was unable to overcome the laws of nature. The result was a rifle with a heavy hitting cartridge that was tough to manage in automatic fire and too heavy and too long in the minds of its critics and some of its operators. Regardless, the M14 has performed superbly in its primary role, battle rifle.

The M in M14 stands for Model. The M14 rifle is a rotating bolt, gas operated, air cooled, magazine fed, shoulder fired weapon. The M14 is 44.28 " long with the hinged butt plate in the closed position and weighs 8.8 pounds. With a full magazine, cleaning kit and sling, it weighs approximately 11.2 pounds. The maximum effective range is 460 meters (503 yards). The M14 has seen hostile service with the American military from the 1963 Cuban missile crisis to the Global War on Terrorism. The M14 rifle has been employed as a battle rifle, squad automatic weapon, competition match rifle, grenade launcher, sniper weapon system and ceremonial rifle.

Between 1958 and 1963, the U. S. government ordered 1,380,358 M14 rifles from four entities. These were the U. S. Army's Springfield Armory in Springfield, MA; Winchester (Olin Mathieson Chemical Corporation) in New Haven, CT; Harrington & Richardson Arms Company in Worcester, MA; and Thompson-Ramo-Wooldridge, Inc. in Cleveland, OH. A total of 1,376,031 M14 rifles were delivered between 1959 and 1964. In December 1962, just before Secretary of Defense Robert McNamara announced cancellation of the project, the U. S. Army had planned a procurement schedule totaling 2,500,000 M14 rifles by June 30, 1969.

From 1945 to June 30, 1957, the U. S. government spent \$10,927,523 to research, develop, test and evaluate the M14. Total cumulative investment cost for the M14 project was \$207,017,000. The total cumulative operating, maintenance and ammunition costs up to July 01, 1968 was \$295,290,000. The average production cost was \$105.15 per rifle with TRW being the most affordable of the four manufacturers. During rifle production, five magazines were packed with each rifle. The cost of the five magazines was \$4.20. The production learning curve slope was 92 percent. This means as

production quantities doubled, the time to produce each rifle decreased by 8 percent. The production cost per rifle continued to increase for each of the three commercial manufacturers until each had produced 100,000 rifles. After that point, production cost per rifle decreased as more rifles were completed. In 1968, the annual operating (parts, maintenance, and ammunition) cost for each rifle was \$50.52. The cost of the M14 project production equipment was as follows: Olin Mathieson Chemical Corporation - \$7,593,460, Harrington & Richardson - \$6,330,726 and TRW - \$6,824,559. The cost of the production equipment at Springfield Armory was not available when researched for a 1968 U. S. Army Materiel Command report.

In October 1968, the U. S. Army Materiel Command reported the following reliability figures for the M14 rifle in Technical Report 68-4 *M14 Rifle Cost Analysis Report*:

Mean Time To Overhaul (average time to overhaul a M14 rifle) - 1.5 hours
Time Between Overhaul (TBO) - 5 years
Mean Time Between Failure (MTBF or average time between any failure requiring repair) - 270 days
Mean Time To Repair (MTTR) - 0.6 hours
Average annual ammunition usage as of November 1965 - 810 cartridges (610 rounds ball, 50 rounds tracer and 150 rounds blank).

Engineering Material

There are three important factors which influence the quality of the M14 type rifle receiver and parts. These factors are material selection, heat treatment, and dimensional geometry. Selection of an engineering material is based upon the design, application and manufacturing feasibility of an object. With that in mind, if the proper material is not used, the specified (and desired) values for each mechanical property (hardness, strength, toughness, etc.) may not be achieved for a given part, regardless of whether heat treatment is performed well or done at all. If the incorrect material is used to make the part, the part may yield a shorter service life, or may even catastrophically fail with resulting personal injury or death. The same goes when heat treatment of parts is not performed according to design specifications and procedures. Whether a receiver is initially formed by forging, machining or casting, the finish machining operations are performed before carburizing, quenching and tempering. If dimensional geometry is incorrect, even a properly heat-treated part made of the correct material will either function poorly or it will not last as long as it should.

Engineering Definitions

A₁ temperature – This is the minimum threshold temperature to create austenite molecular structure in steel. The A₁ temperature is 1341 degrees Fahrenheit for steel with less than 6.67 % carbon content. All of the steel used in the M14 rifle contains less than 1.00 % carbon.

A₃ temperature – The temperature at which ferrite forms as the steel begins cooling. This is about 1528 degrees Fahrenheit for AISI 8620 steel.

Alloy steel – Alloy steel is steel that contains trace percentages of other elements.

Annealing - This is a method of heat treatment performed by heating steel to a temperature that transforms all of the molecules to austenite structure, followed by slow furnace cooling. This method produces a coarse pearlite molecular structure in the steel. Annealing is done to produce lower strength and higher ductility steel—performance characteristics opposite of high strength and brittleness.

Austenite – Austenite is the Face Centered Cubic molecular structure of iron. The maximum solubility of carbon in austenite is 2.11 %.

Carburizing – Carburizing is a group of techniques for heat treating the surface of steel. It is used when the alloy steel has insufficient carbon to attain the desired surface properties through conventional heating methods. Carburizing alters the chemistry of the surface of the steel. The first part of the process is the diffusion of carbon into the part's surface at an elevated temperature. This creates a high carbon content at the surface which increases the hardness. When the part is then rapidly cooled and tempered the surface remains hard and strong while the core (or center) remains softer and tougher.

Case depth – The depth below the surface of a steel part to which hardening occurs by surface heat treatment techniques.

Cementite – This is a hard and brittle compound of three iron atoms and one carbon atom. It contains 6.67 % carbon. It is used to strengthen steel when it is dispersed evenly. The chemical formula is Fe₃C.

Ferrite – Ferrite is the Body Centered Cubic form of iron. The maximum solubility of carbon in (alpha) ferrite is 0.0218 %. Alpha ferrite is one structure of several that can form upon slow cooling from the molten phase.

Hardness – Hardness can be thought of as resistance to permanent indentation. Hardness is measured using various tests with their own number scales, such as Brinell, Knoop, Rockwell, and Vickers.

Heat treatment – Heat treatment is the controlled heating and cooling of metals for the purpose of changing their physical properties. It is one of many methods that can be used to change the mechanical properties of metals.

Hypoeutectoid steel – This is steel with less than 0.77 % carbon content. If hypoeutectoid alloy steel is heated above the A₁ temperature, 100 % austenite structure can be formed. This is desired for making hardened steel parts by heat treatment.

Magnetic particle inspection – Magnetic particle inspection is a method of non-destructive examination that detects surface and subsurface flaws in ferromagnetic metals (iron, steel, nickel and cobalt alloys).

Martensite - The Body Centered Tetragonal molecular structure of steel with 0.2 % or greater carbon content. It is the hardest, strongest and most brittle molecular structure of steel. It can be as hard as 65 HRC.

M_s – The temperature at which steel begins to form martensite molecules upon rapid cooling. This temperature differs for each alloy steel.

M_{90} – The temperature at which steel is composed of 90 % martensite upon rapid cooling. This temperature differs for each alloy steel.

Normalizing – This is a method of heat treatment that is performed by heating steel to a temperature that transforms all of the molecules to austenite structure followed by air cooling or oil quenching and tempering. This treatment produces a fine pearlite molecular structure in steel. Normalizing is done to control dispersion-strengthening of the steel.

Pearlite – A form of steel that contains two solid molecular structures of steel, ferrite and cementite. It is created when steel is slowly cooled.

Rockwell hardness test – This hardness tester uses a small diameter steel ball or diamond cone depending on the material to be sampled. The depth of penetration of the ball or cone is automatically measured and converted to a Rockwell hardness number, expressed with “HRC” or “HRD” after the number. HRC means the hardness value on the Rockwell C scale. HRD stands for the hardness value on the Rockwell D scale. The Rockwell C and D scales are used to measure the hardness of high strength steels. A diamond cone indenter is used for these hardness scales.

Stress – Applied force divided by the original material cross-section area.

Surface hardening - Surface hardening is a process which increases the wear resistance of a steel part while it retains its softer and tougher interior. There are three methods for raising surface hardness of steel: 1) diffusion 2) applied energy and 3) surface finish. Carburizing and nitrocarburizing are examples of surface hardening by the diffusion method. Applied energy techniques for hardening steel surfaces include flame hardening and induction hardening. Chromium plating and physical vapor deposition are popular types of surface finishes for steel parts.

Tempering – Tempering is the heating of martensite steel below the A_1 or eutectoid temperature. This heating redistributes the cementite within the martensite. Redistribution or dispersion of the cementite is called dispersion-strengthening.

Tempering relieves residual stresses caused by the transformation of austenite into martensite upon rapid cooling. Tempering reduces the strength and hardness but increases the ductility and toughness of steel. However, the hardness is also dependent upon the carbon content of the steel. The higher the carbon content the higher the hardness of the martensite.

Tensile strength – The strength of a material can be determined by measuring the stress it takes to cause deformation. The yield strength is the stress needed to begin permanent deformation (elongation) of a material. The ultimate tensile strength is the maximum applied stress before the material breaks.

Toughness – Mathematically, it is often measured as the total area under the stress versus strain curve for a given material. In layman's terms, toughness is the resistance of a material to failure by impact.

AISI 4100 and 8600 Series Alloy Steels

In the United States, types of steel are commonly identified by the American Iron and Steel Institute (AISI) classification system. Carbon and alloy steels are given unique four digit numbers. The first digit of each number indicates the major alloying element or elements. The second digit represents a subgroup of the major alloy element or elements. The third and fourth digits denote the amount of carbon in the steel. For example, AISI 4140 is a molybdenum-chromium alloy steel with 0.40 % carbon content. AISI 4100 and 8600 series alloy and AISI 416 stainless steels are commonly used in the manufacture of M14 rifle parts.

M14 Rifle Preservation

Corrosion – In layman's terms, corrosion is the wasting away of a material. This is not desirable but the M14 type rifle must be expected to perform in harsh environments. Thus, corrosion is an issue of concern in its design and application. Corrosion of metal parts can occur from contact from various sources such as chemicals, water immersion, humid air, human body sweat, salt water spray or microbes. Fine grain dust that is high in salts and carbonates, such as that found in Iraq, can corrode metal parts. Alloy aluminum, carbon steel and alloy steel surfaces will oxidize (rust) in moist air but at varying rates. Carbon and low alloy steels have similar poor corrosion resistance in aerated neutral pH water and sea water. Rubber and plastic materials are not immune from corrosion either. Corrosion of rubber and plastic can cause cracking or softening of rifle parts.

Stainless steels have good resistance in mild environments but are susceptible to localized chloride pitting corrosion from sources like salt water or body sweat. This susceptibility to chloride pitting corrosion is at its greatest when stainless steel is heated to a temperature around 195 degrees Fahrenheit, e.g., the M14 gas cylinder after firing.

Martensitic stainless steels are used to manufacture some M14 type rifle parts. Martensitic stainless steels have the least corrosion resistance of the five types of stainless steels. In sea water or in water near neutral pH, martensitic AISI 416 stainless steel will suffer general surface corrosion at a faster rate than carbon steel or low alloy steel. Martensitic stainless steels are also susceptible to hydrogen embrittlement cracking corrosion but this is not an issue when in service as a M14 type rifle part.

Preservation – Carbon and alloy steels can be preserved with coating or plating. Most M14 type rifle parts are made from alloy steels. Alloy steel parts are almost always coated with manganese phosphate or zinc phosphate for corrosion protection. Both methods of coating have been used for decades. An exception to phosphate coating is the bolt in semi-automatic M14 type rifles built by McMillan Firearms Manufacturing, LLC (Phoenix, AZ). Those bolts were given an electroless nickel and polytetrafluoroethylene (PTFE) coating for enhanced abrasion and corrosion resistance and lubricity.

Thomas Coslett developed and patented iron phosphate coating in 1907. Six years later, Frank Richards of the United Kingdom patented the process of manganese phosphate coating. In 1915, Clark Parker obtained the rights to both patents and formed the Parker Rust-Proof Phosphating Company of America. Zinc phosphate coating was developed by the Parker Rust Proof Company as an inexpensive alternative to manganese phosphate coating. The U. S. Patent for the zinc phosphate coating method was issued in 1942 to Van M. Darsey, an employee of the Parker Rust Proof Company.

Phosphate coatings can and do wear off of M14 rifle parts from normal use and handling. Many gunsmiths are equipped to refresh or replace the phosphate coating on parts with a worn finish. The color of phosphate coating on USGI M14 parts varies from light gray to green-gray to charcoal gray. Manganese phosphate produces darker shades of gray color finish. Zinc phosphate coats the parts with lighter shades of gray. M14 parts were phosphate coated in batches and by many companies for the U. S. government. As an example, the finish on the butt plate assembly was allowed to vary among shades from gray (FED-STD-595 color 36118) to black (FED-STD-595 color 37038). Consequently, the M14 enthusiast should not expect new-in-wrap or used USGI M14 parts to match in color when assembling a M14 type rifle.

Government contractors and military small arms technicians were required to finish M14 parts with a phosphate coating per the government drawings. However, there was at least one exception to this rule. In 1967, the U. S. Marine Corps 3rd Force Service Regiment serviced several thousand M14 rifles. The unit was stationed on Okinawa where there was no capability for phosphate coating. M14 rifles were disassembled, chemically cleaned, finished with a hot vat black oxide coating, and then reassembled for shipment back to the United States.

The USGI rack grade barrel bore, gas piston, spindle valve, gas cylinder plug, operating rod front end, gas cylinder bore and commercial stainless steel barrels are not coated.

The bolt roller was not coated at the factory but left bare. Some bolt rollers on stripped bolts were phosphate coated during arsenal or depot inspection, recoating and rewrap. Some alloy steel barrels are blued, such as the commercial barrels and the early 1980s military barrels made by Gene Barnett. Gun bluing and phosphate coatings will not adhere to stainless steel. Consequently, USGI M14 gas cylinders, spindle valves and gas cylinder plugs were blackened with molten sodium dichromate oxide coating. Commercial reproduction gas cylinders are protected with paint that will adhere to stainless steel. Alternately, the gas cylinder, spindle valve, front band and gas cylinder plug exterior surfaces can be preserved with a ceramic coating as is done by Jeffrey Shapiro (NY) as part of his National Match modification.

The M14 rack grade barrel bore is chromium plated for corrosion protection among other benefits. The process of chromium plating a rifle barrel was patented in 1932 by John M. Olin and Alfons G. Schuricht. John M. Olin was a chemical engineer at Western Cartridge Company when he and Mr. Schuricht developed the plating process. The two gentlemen developed the process as a means to minimize corrosion and erosion in gun barrels caused by the use of ammunition. Mr. Olin went on to become President of Olin Industries in 1944. In 1954, he was elected Chairman of the Board at the newly formed Olin Mathieson Chemical Corporation. Mr. Olin retired in 1957. He was awarded, solely or jointly, twenty-four patents for items related to firearms and ammunition. He passed away in 1982. Between 1953 and 2005, the John M. Olin Foundation distributed more than \$370,000,000 to politically conservative academic institutions.

Parts such as scope mounts and gas cylinder lock wrenches made from alloy aluminum are typically anodized to prevent oxidation. All of these metal surface finishes serve to preserve M14 type rifle parts and accessories from the harmful effects of corrosion.

Wood Stock Preservation - Linseed oil, tung oil and a number of commercial wood finishes have been used with great success to bring out the natural beauty of M14 rifle stocks. Well-preserved wood M14 stocks command a collector premium.

There are four categories of surface finishes for preservation of wood gun stocks: 1) raw or pure oils 2) boiled oils 3) polymerized or bodied oils and 4) varnishes. When applied to a wood surface, these liquids harden into a solid film to form a protective seal. Oil and varnish finishes are susceptible to deterioration from mildew and fungus and generally do not offer ultraviolet light protection.

The first three categories, pure, boiled and polymerized oils, are known as drying oil finishes. Drying oils cure over time by forming a network of long chain molecules (polymerization) while reacting to the presence of oxygen (oxidation). Drying oils offer good, affordable moisture resistance and are easy to apply. Drying oil finishes soak into the wood thereby enhancing the natural appearance of the grain.

Raw or pure oils are obtained from plants. Raw oils that have been used at one time or another include linseed, tung, walnut, poppy seed, perilla and walnut oil. Raw oils take weeks to fully cure when applied to wood. All environmental factors and the applied oil film thicknesses being equal, tung oil will dry faster than linseed oil because it absorbs less oxygen. Among raw oils, linseed and tung oils are the universal choices for gun stock preservation. Linseed oil is an extract of the seed of the flax plant (*Linum usitatissimum*). Tung oil is made from tung tree nuts (*Aleurites fordii*). Tung oil is also known as chinawood oil. With age, linseed oil will turn yellow and may flake on a wood surface but tung oil is very resistant to yellowing and will not flake.

Until 1942, the U. S. Army used raw linseed oil to preserve wood gun stocks. From M1 rifle production in 1942 until at least 1963 when the last M14 rifles were assembled with wood stocks, tung oil was the preservative used in the factory. Tung oil gives a more durable finish than linseed oil. For maintenance purposes, raw linseed oil was the preservative specified in U. S. Army M14 rifle technical manuals. The M14A1 stock drawing specifies boiled linseed oil or tung oil as the protective finish. U. S. Army manual FM 23-8 cautions against getting linseed oil on the metal parts. The reason for this is that a sticky gum can form on the metal parts from dried linseed oil.

Long curing time for wood finishes is not always desirable. Boiled oils have additives known as siccatives. A siccative is an oil soluble organic acid metal salt. Adding siccatives to raw drying oil reduces the cure time from weeks to less than two days. The presence of drying additives, siccatives, is what classifies it as boiled oil. Siccatives may contribute to yellowing of an oil finish but do not affect the water moisture content of the wood. Boiled linseed oil is a popular choice among civilian collectors. It gives the wood stock a military appearance without the long cure time.

There are two common polymerized or bodied oils, linseed and tung. Bodied oils are made by heating raw oil sufficiently in an oxygen-free atmosphere to complete polymerization. Thus, oil viscosity, or resistance to flow, of the polymerized or bodied oil is significantly increased. Bodied oil then only has to react with oxygen to fully cure. This results in a much faster cure time and a more durable film as compared to the raw oil. Bodied oils generally "set" after a day. Polymerized tung oil produces a smooth gloss appearance as compared to the matte finish of pure tung oil.

A varnish is typically a combination of drying oil, resin and a solvent. A varnish will form a hard surface on the wood stock as the solvent evaporates. Turpentine and turpentine substitutes, e.g., mineral spirits, are used as varnish solvents. Varnishes are sold in glossy, semi-gloss or satin finish. Varnishes have little or no color. There are several types of varnishes: acrylic, alkyd, drying oil, epoxy, lacquer, marine, polyurethane, resin, shellac, and violin. Polymerized linseed oil varnish is commonly sold as Danish oil. Varnishes dry faster and harder than drying oils and provide excellent water resistance but often lack aesthetic appeal. Some varnishes have additives for ultraviolet light protection.

Normal Climate Care – FM 23-8 (May 1965 edition) specified a daily inspection of the M14 rifle to check for any corrosion when in use. For preservation, the same manual requires a light film of lubricating oil to be applied on all metal parts except the inside of the gas cylinder, the gas piston and the gas cylinder plug. Alternately, USGI rifle bore cleaner could be applied to metal surfaces as a short term (one day) protectant. Note: **The barrel bore and chamber should be cleaned, dried and checked clear of obstructions before firing.** Lubricant or bore cleaner left in the barrel can affect rifle accuracy. More significantly, foreign material may adversely increase chamber pressure. Above freezing, corrosion becomes a problem if not properly addressed by the rifle owner.

Cold Climate Care - For temperatures below freezing, all moisture and excess lubricant must be removed to keep the rifle working properly. In extensive arctic testing in the winter of 1968, the U. S. Army found the M14 malfunctioned 137 times out of 30,000 rounds fired (0.5 %) using five unlubricated rifles in ambient temperature ranging from 35 degrees Fahrenheit to - 58 degrees Fahrenheit. Among this set of five rifles, the most common malfunction was the failure of the bolt to lock open (44 of 137 instances). When LSA lubricant (then MIL-L-46000A) was used in the same test, the malfunction rate dropped to 23 malfunctions in 30,000 rounds fired (0.07 %) with another set of five M14 rifles. Each rifle was field stripped and cleaned every 1000 rounds during the test. LSA lubricant is no longer available in the military supply system.

The U. S. Navy prescribes a light coat of the synthetic blend, Cleaner Lubricant Preservative (CLP), in subzero temperature. The Mk 14 Mod 0 operator manual states CLP will provide adequate lubrication between 0 and - 35 degrees Fahrenheit in areas where grease is normally applied with the exception of the bolt roller. Regardless, it is best to keep the rifle outside in the cold air in such conditions. Without risking loss of life or limb, cover the rifle with cover (poncho, blanket, tarp, etc.) to protect it from snow or ice. If the rifle is brought into a heated space, do not clean it until the rifle has reached room temperature at which time it can be thoroughly cleaned of all moisture.

Hot and Humid or Ocean Climate Care – Wipe metal surfaces dry and lightly coat with CLP or other preservative oil. This maintenance will help protect the rifle from the effects of perspiration or saltwater. If the rifle is submerged in saltwater, clean all metal surfaces with fresh water as soon as possible before drying and lubricating. Frequently apply raw or boiled linseed oil to the wood stock to keep it from swelling.

Desert Climate Care – Clean the rifle daily or more often to keep sand and dust from accumulating in the bore and on the moving parts. Keep the rifle dry and the muzzle and receiver covered when dust or sand is in the air. It is better to keep the rifle dry of soft lubricants in sandy areas. If not, oil or grease will collect dust and sand. The debris-laden lubricant then becomes abrasive when the rifle is employed. The U. S. Army has determined that moving vehicles in the desert, and firearms stowed inside them, are dust traps. This lesson also has application for ranchers and outdoorsmen who stow firearms

in their vehicles. In sandy, dusty areas, the M14 rifle should be periodically wiped down with a clean soft cloth to keep down the dust build up. The M14 wood stock should be hand rubbed with raw or boiled linseed oil to keep it from drying out.

Muddy Area Climate Care - Clean, thoroughly dry and then lubricate the rifle as soon as possible.

M14 Rifle Lubrication

A comprehensive discourse of tribology is beyond the scope of this work. The reader is referred to U. S. Army manual EM 1110-2-1424 *Lubricants and Hydraulic Fluids* for an excellent introduction to the subject. The following information is intended to familiarize the reader with the topic of lubrication for the M14 type rifle. The M14 rifle needs lubrication under normal climate conditions to operate as designed while minimizing wear of the parts in sliding contact. The engineering materials used as lubricants in the M14 rifle can be divided into two categories, soft and hard.

Soft Lubricants – Oils, greases and sprays are used to lubricate moving parts within a firearm to facilitate proper function and minimize parts wear. Soft lubricants also provide modest protection against corrosion where applied. They are economical and readily available. Most soft lubricants do not perform well in cold weather. Soft lubricants break down over time with use of the rifle and due to exposure to air and moisture. Greases do not dissipate heat well and small quantities are not easily dispensed. As a rule of thumb, more is not better for soft lubricants. The minimum amount of lubricant should be applied to the M14 rifle in its care.

Some ingredients and properties of grease are defined as follows:

Anti-wear (AW) additive - Solid lubricant particles are dispersed in grease to prevent metal-to-metal contact of lubricated surfaces. These solid particles are known as anti-wear additives. Phosphorus and zinc compounds and suspended PTFE are common AW additives. Anti-wear additives are useful up to about 465 to 480 degrees Fahrenheit. Above that temperature range, anti-wear compounds begin to break down. Anti-wear additives will reduce the oxidation resistance of grease. Consequently, grease containing anti-wear additives will need to be reapplied much more often than grease without AW or oxidation inhibitor additives.

Apparent viscosity - Viscosity is the resistance of a fluid to flow. Oil has a consistent viscosity for a given temperature. The viscosity of grease decreases as the shear rate (speed of metal surfaces sliding against each other) increases. Thus, the apparent viscosity of a grease is its resistance to flow for a given shear rate at a given temperature.

Bleeding - Bleeding is the separation of the lubricant from the thickening agent in a grease.

Boiling point - The boiling point is the temperature at which the grease will begin to vaporize at atmospheric pressure.

Consistency - Consistency is the hardness of grease. It is a primary factor in selecting suitable grease for a given application, e.g., lubrication of the M14 rifle.

Corrosion inhibitor - A corrosion inhibitor protects the lubricated metal surfaces from corrosion attack by moisture or other foreign contaminants.

Dropping Point - The dropping point is the temperature at which a grease will drop from a standard test orifice.

Evaporation - Evaporation is the loss of the lubricant component of grease as it is heated.

Extreme pressure (EP) additive - An EP additive in grease prevents seizing of the sliding metal surfaces under very high pressure. Graphite and molybdenum disulfide are common EP additives and may be used for service above 600 degrees Fahrenheit.

Flash point - The vapor from the grease may ignite from an open flame above this temperature.

NLGI (National Lubricating Grease Institute) Number - The NLGI number is a comparative scale number to indicate the hardness of grease as tested at 77 degrees Fahrenheit. The higher the NLGI number, the harder the grease. NLGI number 000 is the lowest rating (semi-fluid) and 6 is the highest (solid). The NLGI number for military specification rifle grease is equivalent to 2.5.

Oxidation inhibitor - An oxidation inhibitor is an additive that minimizes oxygen attack of the grease. Oxygen attack, or oxidation, will increase apparent viscosity. An oxidation inhibitor, or anti-oxidant, will extend the useful life of a soft lubricant. Oxidation inhibitors are consumed over time as the grease is exposed to the open air. Oxidation of grease also increases as its temperature increases. The higher the service temperature the sooner the grease will need replacement.

Penetration - Penetration is a test for measuring the hardness or consistency of grease.

Pour point - The pour point is lowest temperature at which a grease or oil will flow under standardized test conditions.

Shear rate - The shear rate is the relative rate of sliding between molecules of the grease as it flows.

Water resistance - Water resistance is the ability of grease to lubricate the surface to which it is applied in the presence of water.

Most firearms lubricants available today are petroleum based oils and greases. As of 2007, over 98 % of lubricating oils and greases were made with petroleum (mineral) oil. Lithium complex grease containing mineral oil is generally considered true multipurpose grease. Due to its versatility, lithium-based grease accounted for 72 % of the commercial market in 2007. Lithium-based greases have been available since 1942.

Military instructions on how to use oil and grease to lubricate the M14 varied slightly depending on the document:

Springfield Armory Report SA-NM11-2612 (June 1955) - A light coat of oil should be applied to all metal surfaces except the bore, chamber and other parts that contact ammunition. Extra care should be taken to lubricate specified areas of the receiver, bolt, operating rod, and operating rod spring. After firing and cleaning, the interior of the gas system (gas piston, gas cylinder and gas cylinder plug) was to be left lightly oiled.

FM 23-8 (December 1959, May 1965 and April 1974) - Lubricate the rifle with PL Special lubricating oil in normal temperatures and Lubricating Oil, Weapons (LAW) in subzero temperatures. A light film of oil should be applied to all metal surfaces except for surfaces coming in contact with ammunition and the interior of the gas cylinder, gas piston and gas cylinder plug. Rifle grease was to be applied to specified areas of the receiver, bolt and operating rod. If the rifle was to be exposed to very cold temperature or sand or dust, grease was not applied.

MIL-G-46003 (August 1961) and MIL-G-46003A (December 1976) - Rifle grease was designed to lubricate rifles and other small arms in conditions of sustained rain within the temperature range of 35 to 100 degrees Fahrenheit.

TM 9-1005-223-10 (March 1972) - Lubricate the rifle with PL Special lubricating oil in normal temperatures or LAW in subzero temperatures. Apply rifle grease to specified areas of the receiver, bolt and operating rod.

Military Specification MIL-G-46003A lists the performance requirements for rifle grease:

Material - a mixture of mineral or synthetic oil and a thickening agent that may or may not have additives but able to meet the requirements of MIL-G-46003A

Work penetration - The consistency of the grease must be 220 to 270 per ASTM D217.

Dropping point - The grease must possess a dropping point of at least 190 degrees Fahrenheit per ASTM D566.

Mineral oil viscosity - The viscosity must be 108 to 172.6 centiStokes at 100 degrees Fahrenheit per ASTM D445.

Water resistance - Not more than 4 % per ASTM D1264

Rust prevention - A rating of 2 or less per ASTM D1743

Corrosion resistance - No evidence of green color, pitting or etching and no black or brown stain after the test strip is washed with normal hexane per FED-STD-791 method 5309.

Storage stability - The grease is able to meet the specified requirements after sealed storage at 100 degrees Fahrenheit for six months.

Performance test - Grease stored for six months is applied to five M14 rifles for testing. Each rifle is fired in a series of semi-automatic and automatic cycles for a total of 500 rounds. During the entire test, the rifle is subjected to water spray. If there is more than one freeze up of a bolt or more than six malfunctions due to operation of the bolt amongst the entire 2,500 rounds shot, the lot of grease is rejected.

Workmanship - The rifle grease must have smooth texture and free of abrasives, lumps, granular particles, entrapped air and any odor.

Aside from military specification rifle grease, there are a number of commercially formulated greases that provide adequate lubrication for the M14 type rifle in all but the most severe service conditions.

As a general rule, different greases should not be mixed together or applied one over another. If a new type of grease is to be used, the M14 type rifle should first be disassembled and thoroughly cleaned of all grease. Combining greases may result in a mixture that is too hard or too soft or the maximum useful temperature may be lowered too far or the enhanced performance of the additives may be diminished. As an example, a grease manufacturer, Henkel KGaA, notes on its specification sheet that Plastilube will lose its heat resistance if mixed with a grease containing a soap thickening agent.

SAE 10 engine oil or automatic transmission fluid can be used in a combat or other life threatening situation to lubricate a M14 rifle. Automobile engine oil *may* have corrosion inhibitor and anti-wear additives and/or *may* contain benzene. Some automobile engine oils do, some do not. Automobile engine oil should be used as a last-ditch option for lubricating the M14. A better choice for a field expedient lubricant is automatic transmission fluid. Automatic transmission fluid does contain corrosion and oxidation inhibitors and does not break down until about 220 degrees Fahrenheit.

Grease is an emulsion of a fluid lubricant and a thickening agent. It may have additives for enhanced performance. *Typically*, the fluid lubricant is oil and the thickener is soap. The oil can be made from petroleum or a vegetable or a man-made synthetic composition. Aluminum-, calcium-, lithium- and sodium-based soaps are common

thickening agents in greases. Complex grease will have a second thickening agent. The second thickener is added to increase the useful service temperature of the grease. All three parts, lubricant, thickener and additives, influence the properties and performance of grease. The lubricant portion of the grease can be from 50 % to 95 % by weight. The thickening agent(s) are generally 5 % to 20 % of the grease recipe and additives can be 0 % to 15 % of the composition by weight. Cost and the intended application (customer or end user requirements or specifications) for a grease influence what ingredients and how much of each make up a manufacturer's "recipe."

The M14 rifle, like other firearms, is usually subject to short periods of use bracketed by long periods of inactivity. The M14 rifle has sliding contact of parts under an applied force, e.g., bolt-to-receiver, operating rod-to-receiver, hammer-to-bolt, etc. Lubricating oil will run or migrate from where it is needed with time so it is not well-suited for the M14. If a grease with too hard a consistency is applied to sliding surfaces, it may not flow to parts surfaces where needed during operation. The ideal M14 lubricant will be a multipurpose grease instead of oil.

The ideal M14 rifle grease should have: 1) the consistency of paste 2) good or better temperature resistance with minimal bleeding 3) good or better water resistance and 4) contain anti-wear, corrosion and oxidation inhibitors. Such properties are desirable because the M14 rifle is likely to perform in intemperate weather. Military specification MIL-PRF-63460 prohibits the use of graphite as an ingredient for Cleaner, Lubricant and Preservative. Since CLP is authorized for use in the Mk 14 Mod 0, and other military weapons subject to combat use, lubricant with graphite additive is not recommended.

Operating temperature has a significant effect on the performance of grease. As the operating temperature decreases, the apparent viscosity of grease increases to the point that it can cause the M14 to malfunction in its operating cycle. Generally, the low temperature operating limit for grease is its pour point. As operating temperature increases, softening and then bleeding will occur. As the temperature is further increased the lubricant in the grease will evaporate. The higher the operating temperature of the lubricated surface, the more frequent the grease will need to be reapplied. At even higher temperatures, the thickening agent and any additives will boil and break down chemically forming harmful solid deposits and off-gases. An industry rule of thumb is the service life of grease is halved for every 59 degrees Fahrenheit over 158 degrees Fahrenheit.

Over the years, Lubriplate and Plastilube grease have been issued to U. S. military troops for lubrication of the M14 rifle. Both greases serve well as lubricants for the M14 type rifle. Both contain mineral oil but the major difference is in the thickening agent. Lubriplate 130-A uses calcium-based soap and Plastilube is made with an inorganic clay thickener. The trademark, LUBRIPLATE, was registered to the Lubriplate Corporation (New York, NY) on October 06, 1931. The name LUBRIPLATE was later registered by Fiske Brothers Refining Co. (Newark, NJ) on October 19, 1948. The trademark registration has since expired. Lubriplate 130-A grease was developed for the M1

Garand rifle during World War II. It is pale yellow in color. Lubriplate 130-A is water resistant and contains anti-wear, oxidation, and corrosion additives. Lubriplate 130-A has a kinematic viscosity of 135 centiStokes at 104 degrees Fahrenheit. Greases with a base oil viscosity over 100 centiStokes at 104 degrees Fahrenheit are classified as high viscosity greases. The viscosity of the base lubricant is designed to meet the intended application. The sliding surfaces in the M14 rifle are not heavily loaded but do move at a fast *cyclic rate* of 750 times per minute. A high viscosity grease approximating the kinematic viscosity of Lubriplate 130-A and with consistency of children's paste, is then appropriate for the M14.

Plastilube grease was developed in January 1950 by Warren Refining & Chemical Company Corporation (Cleveland, OH). The name, PLASTILUBE, was registered to Warren Refining & Chemical on February 20, 1951. The trademark registration has expired. Plastilube is reddish-brown in color. It is thicker in consistency than Lubriplate.

The Military Qualified Products List for military specification rifle grease was last updated on March 02, 1992. The sole entry on the latest list is Lubriplate RG-62-A (equivalent to Lubriplate 130-A) made by Fiske Brothers Refining Company.

U. S. Army FM 23-8 (May 1965 edition) specified the application of rifle grease to a number of surfaces on the rifle before firing: bolt locking recesses, the bolt camming lug on the hammer, operating rod camming surfaces, and the lip of the receiver that contacts the rear top edge of the bolt. As part of normal maintenance, M14 gunsmiths may also recommend a light film of rifle grease in: 1) the operating rod channel 2) the operating rod saddle that contacts the barrel 3) the bolt roller 4) the receiver bolt raceway 5) between the top of the lip of the front band and the bottom of the stock ferrule 6) the inside of the cylindrical portion of the operating rod 7) the inside diameter of the operating rod guide 8) the operating rod spring guide 9) the bottom of the rear sight base and 10) sides of the rear sight aperture. U. S. Army armorers applied MIL-G-10924 specification grease to M14 NM rifles. The official name of this grease is "Grease, automotive and artillery" and is commonly referred to as "GAA."

The U. S. Navy cleaning regimen for the Mk 14 Mod 0 rifle is as follows:

Every 250 rounds - clean the bore and chamber

Every 500 rounds - clean the gas piston and gas cylinder

Every 1000 rounds - 1) clean the rifle including the bolt, operating rod and connector 2) apply rifle grease to bolt lugs, receiver bolt raceways and recesses, bolt roller, receiver operating rod channel and operating rod camming surfaces and 3) clean and preserve other metal parts.

Grease should be removed and reapplied yearly to prevent solidification. Grease stored in containers deteriorates over a long period of time. The lubricant will typically separate from the thickener. In this condition, the grease may or may not still meet its design

specifications. Tests for penetration, dropping point and oil separation are needed to determine if the grease is still usable.

Cleaner, Lubricant, Preservative - The all-purpose weapons liquid Cleaner, Lubricant and Preservative (CLP) was adopted by the U. S. Department of Defense some time before July 1979 with promulgation of military specification MIL-L-63460. CLP replaced several different small and large caliber weapons cleaners, lubricants and preservatives in the U. S. military supply system. Where allowed by the operations and maintenance manual, e.g., Mk 14 Mod 0, CLP is authorized for use in lieu of rifle bore cleaner (MIL-PRF-372), medium preservative and lubricating oil (MIL-PRF-3150), low temperature weapons lubricant (MIL-PRF-14107), automatic weapons lubricant (MIL-L-46000) and rifle grease (MIL-G-46003). For normal climate care, CLP is the specified lubricant for the M14 DMR and the Mk 14 Mod 0 per the operator level manuals published by the U. S. Marine Corps and U. S. Navy.

Because MIL-L-63460 (now MIL-PRF-63460) was a performance specification and not a required list of recipe ingredients, the CLP formula composition was left to the USGI contractor to develop. CLP does tend to dry out after about one month after application on the rifle. If the particular brand of CLP has PTFE additive, the container should be shaken immediately prior to application as the PTFE tends to settle within minutes inside its container. Additionally, CLP with PTFE additive left in the bore will cause erratic accuracy for as many as twenty shots out of the rifle until blown out of the muzzle.

As of early 2007, military approved vendors and associated product designations for CLP included Sentinel Canada (SENT-CLP and CLP 22), Anderol, Inc. (ROYCO-634), Arpol Petroleum Co. (ARPOLUBE 63460), Shell International (Aeroshell Fluid 634), and LHB Industries (Pro CLP). In the commercial market, the CLP formula made by Royal Lubricants (marketed by Remington Arms) does not contain PTFE additive. The CLP liquid supplied by Armor Holdings contains PTFE additive.

Operating Temperature - The U. S. military has tested the M14 and M16 type rifles to determine the temperatures at which various parts are subject to during heavy use. Cookoff is a condition where ammunition is heated sufficiently from its surrounding environment to explode. Automatic rifles and machine guns are susceptible to this condition during heavy use. If the weapon is air cooled, has a thin contour barrel and is fired from a closed bolt, e.g., M14, the rate of fire needed for cookoff is substantially lowered. The rate of cooling of the M14 barrel limits its sustained rate of fire. The ambient temperature, length and contour of the barrel, the styles of hand guard and stock, and the attachment of a sound suppressor all affect the rate at which the barrel cools off. As the M14 rifle is fired, the temperature along the barrel will vary substantially. The chamber area will heat up the least. The barrel forward of the chamber up to the gas port will be the hottest section. As some of the gas flows into the gas cylinder, the barrel muzzle will not be quite as hot. Regardless, the temperature in each portion of the barrel will increase with the number of rounds and/or the rate of fire.

Most lubricants and cleaners left inside the bore will boil off as the barrel heats up before cookoff occurs. Each lubricant or cleaner will have its own boiling point. The commercial and military firearms lubricants researched all had boiling points in excess of 400 degrees Fahrenheit. For general comparison, butter in a heated frying pan will smoke at about 395 degrees Fahrenheit. The bore should be swabbed clean and dry before firing to avoid loss of accuracy or any ill effects to the operator. Sliding surfaces of the M14 rifle will be less than 400 degrees Fahrenheit. Thus, firearms lubricants applied to sliding surfaces of the M14 should not boil off.

While not an evaluation of the M14, the following summary illustrates the approximate range of temperatures extant in a centerfire rifle barrel at cookoff. The U. S. Army conducted substantial testing of the M16A1 and M16A1E1 (later adopted as the M16A2) in 1982. Part of this testing included a thorough evaluation of the barrel temperatures under cookoff and sustained firing conditions. The profile of the M16A2 barrel approximates that of the M14 standard contour barrel. Thus it serves to illustrate the effects of sustained firing conditions in the M14 rifle barrel.

In the cookoff test, the U. S. Army determined that the M16A1 could be fired at a rate of 85 rounds per minute for 150 rounds without cookoff. The maximum barrel temperature measured was 849 degrees Fahrenheit at a point 12.9 " from the muzzle end. Likewise, the M16A1E1 was able to fire 170 rounds at the same rate without experiencing cookoff. The maximum barrel temperature for the M16A1E1 was 903 degrees Fahrenheit at a point 12.8 " from the muzzle end. In the testing of the two rifles, the lowest recorded temperatures at which cookoff occurred was 847 degrees Fahrenheit on the barrel surface at 12.8 " from the muzzle end and 338 degrees Fahrenheit on the chamber, both on the M16A1E1. Cookoff occurred at much higher chamber and mid-barrel surface temperatures in the sustained rate of fire test. It occurred at 564 degrees Fahrenheit and above at the chamber and 1,018 degrees Fahrenheit and above in the middle portion of the barrel. Cookoff occurred as soon as fifteen minutes of firing at 30 rounds per minute in the thinner barrel M16A1.

During development of the Mk 14 Mod 0, the Naval Surface Warfare Center (Crane, IN) found that cookoff could occur in as little as 150 rounds of continuous semi-automatic fire with a wood stock M14 on a hot sunny day. The Naval Surface Warfare Center (NSWC), in later testing conducted in September 2006, obtained the following temperature readings on a Mk 14 rifle fitted with a Smith Enterprise, Inc. M14DC sound suppressor and a third generation Sage International, Ltd. M14 EBR stock:

Mk 14 rifle fired in semi-automatic mode for 160 rounds at a rate of one per second then allowed to cool -

Chamber temperature - 178 degrees Fahrenheit
Gas cylinder temperature - 496 degrees Fahrenheit
Sound suppressor temperature - 734 degrees Fahrenheit

Cookoff - no cookoff after ten minutes

Mk 14 rifle fired in automatic mode for 200 rounds in twenty round bursts -

Chamber temperature - 250 degrees Fahrenheit

Gas cylinder temperature - 525 degrees Fahrenheit

Sound suppressor temperature - 1107 degrees Fahrenheit

Cookoff - cookoff occurred at sixty seconds

PTFE Additive in Firearms Lubricants under High Temperature - The following is not meant to be a comprehensive discussion on polytetrafluoroethylene (PTFE), its use and its limitations. However, the use of PTFE as an additive for firearms lubricants is a matter of some curiosity. It is beyond the scope of this work to fully address this topic but some information is presented here as the basis for further inquiry on the part of the reader.

PTFE was discovered on April 06, 1938 by Dr. Roy J. Plunkett, a chemist at the Jackson Laboratory of E. I. du Pont de Nemours and Company, Inc. while working on a new air conditioning refrigerant. Kinetic Chemicals, Inc. (DuPont) patented PTFE in 1941. DuPont is the sole supplier of PTFE in the United States.

At room temperature, PTFE is a white wax-like substance. PTFE has very low friction resistance, excellent dielectric strength and high heat resistance. The first PTFE resin coated cooking pan was created in 1954 by Marc Gregoire (France). PTFE resin is a common coating for non-stick cookware. PTFE is used as an insulator in electrical cables, an ingredient in printed circuit boards and as a stain repellent on fabrics.

Due to its very low coefficient of friction, PTFE is used for applications where sliding action of parts is needed such as bearings, bushings, gears, slide plates and firearms. For these applications, PTFE particles are mixed with mineral oil as an anti-wear additive.

PTFE is chemically inert below 464 degrees Fahrenheit. If left unattended on a hot stove burner, PTFE resin cookware can reach temperatures high enough to release toxic byproducts into the immediate atmosphere. These toxic byproducts can be lethal to birds and can cause temporary flu-like symptoms in human beings. In a 1973 study of PTFE resin coated cookware, pet birds were found to die from the toxic fumes of PTFE when the PTFE resin coated cookware reached 536 degrees Fahrenheit. Such a temperature exceeds what is needed for cooking food and is an obvious abuse of the cookware.

As PTFE is heated above food cooking temperature, it begins to emit ultra fine particulate matter at 464 degrees Fahrenheit. It melts at 621 degrees Fahrenheit. Further heating of PTFE to extreme temperatures, which should not be done, results in the release of several toxic gases:

M14 RIFLE HISTORY AND DEVELOPMENT

At 680 degrees Fahrenheit - difluoroacetic acid (DFA), hexafluoropropene (HFP), monofluoroacetic acid (MFA), perfluorooctanoic acid (PFOA), tetrafluoroethylene (TFE) and trifluoroacetic acid (TFA)

At 878 degrees Fahrenheit - silicon tetrafluoride (SiF₄)

At 887 degrees Fahrenheit - perfluoroisobutene (PFIB)

At 932 degrees Fahrenheit - carbonyl fluoride (CFO₂) and hydrofluoric acid (HF)

At 1112 degrees Fahrenheit - octafluorocyclobutane (OFCB), perfluorobutane (PFB) and trifluoroacetic acid fluoride (CF₃COF)

At 1202 degrees Fahrenheit - carbon tetrafluoride (CF₄)

Firearms cleaner, lubricant or preservative oil or grease containing PTFE additive applied to sliding surfaces of the M14 rifle will not reach a temperature of 464 degrees Fahrenheit or higher with the possible exception of the cylindrical portion of the operating rod and the operating rod guide. Thus, firearms cleaner, lubricant or preservative with PTFE additive will remain chemically inert when applied to the saddle portion of the operating rod and areas to the rear. Application of any cleaner, lubricant or preservative oil or grease containing PTFE additive forward of the chamber may result in deterioration of the PTFE additive.

Experience of the U. S. Marine Corps found that when CLP containing PTFE additive was left in the bore of a M14 rifle it would shoot erratically until the CLP had been blown out after the first fifteen to twenty rounds of fire. The accuracy would return indicating the washing out of the CLP with its PTFE additive. Even with automatic fire, it's unlikely any portion of the barrel surface would reach 464 degrees Fahrenheit or higher in no more than twenty rounds. If the M14 rifle was fitted with a sound suppressor, the propellant gases and any residual bore cleaner or preservative will blow back into the shooter's face each time the rifle is fired. If the bore cleaner or preservative contained PTFE additive then it is conceivable that some PTFE high temperature particulate or off-gas could be blown on to the shooter.

An Aberdeen Proving Ground experiment in 1987 found that propellant gas temperature, as measured 5.2 " past the end of the M14 rifle flash suppressor exceeded 2000 degrees Fahrenheit in the first millisecond after bullet exit from the rifle. The temperature excursion was found to be very short-lived as the gas temperature dropped to less than 500 degrees Fahrenheit in less than 2 milliseconds after the bullet exited the flash suppressor. The APG study used ammunition loaded with WC-846 gunpowder.

For civilian use, what cleaner, lubricant or preservative should be used for the M14 type rifle? No one product will perform all three functions in a superior manner. The M14 owner should choose a different product for each need.

Cleaner - Commercial brand bore cleaner that is suitable for removing gunpowder residue and copper fouling.

Lubricant - Commercial NLGI # 2 grease made of mineral oil, a calcium complex or lithium complex soap, and additives. Both types of thickeners possess good to excellent water resistance. Sodium-based greases have poor water resistance. Grease containing synthetic oil serves just as well as those with mineral oil as a firearms lubricant but typically at additional retail cost.

For NLGI # 2 greases, lithium-based soap grease will remain fluid to a point between - 20 and 0 degrees Fahrenheit depending on the formulation. In comparison, a calcium-based soap grease with a NLGI # 2 rating is typically useable to a temperature between 0 and + 10 degrees Fahrenheit depending on its recipe. Generally, lithium complex grease can be used up to 350 degrees Fahrenheit while its dropping point exceeds 500 degrees Fahrenheit. Calcium-based greases are usually more affordable than lithium-based greases.

The following list is a few of the more common grease additives and their uses:

Antimony dialkyldithiocarbamate - antioxidant, anti-scuff, anti-wear, corrosion inhibitor, extreme pressure additive, friction reducer

Methylene-bis-dibutyldithiocarbamate - antioxidant and anti-wear

Potassium triborate - antioxidant and anti-wear

Zinc dialkyldithiocarbamate - anti-wear, corrosion inhibitor, and oxidation inhibitor

Zinc dialkyldithiophosphate - anti-wear, corrosion inhibitor

Zinc oxide - corrosion inhibitor

The civilian M14 type rifle owner will not likely need the high temperature or extreme pressure protection afforded by solid anti-wear additives such as graphite, molybdenum disulfide or PTFE. Grease with a service temperature up to 350 degrees Fahrenheit should suffice for civilian use.

Preservative - Commercial brand of Cleaner, Lubricant and Preservative (CLP) without PTFE additive due to the possible release of off-gases from elevated barrel temperature

Each chemical product on the market should have a Material Safety Data Sheet (MSDS) available. If the MSDS cannot be found through an online search, the manufacturer or distributor should be contacted to obtain one. The MSDS is very helpful because it will give the reader the product physical data, any handling precautions to be aware of and it will usually disclose some, if not all, of the product ingredients. Undoubtedly, the amount and type of ingredients in a firearms care product will vary from manufacturer to manufacturer for a similar product.

Disclaimer: The user of any firearms care product is responsible for following all manufacturer instructions and precautions. Follow all product instructions and warnings on the container. Some products should be used in well ventilated areas and/or may require skin protection. Never use these products in a manner other than what is

intended by the product manufacturer.

Hard Lubricants – It may seem detrimental for very hard surfaces to be in bare sliding contact with each other but friction and wear can be significantly reduced with some hard surface finishes. In other words, a solid material can be a lubricant. In the M14 rifle, this is not only possible but has already been achieved. The benefit of applying a hard smooth finish to the M14 barrel bore was realized in 1956. The all chromium plated firing pin has proven itself enduring and lubricious since the mid-1960s. The XM25, M25, M14SE and Mk 14 SEI rifles employ gas pistons with very hard finishes in combat conditions. Some commercial M14 type receivers and parts have been nitrocarburized since 1985. As part of a custom rifle project, Century Arms International imported Norinco M14 Sporter receiver serial number C08610 has been dense chromium plated. Unique in the history of Springfield Armory, Inc., all metal parts for M1A serial number 020000 were completely chromium plated and then assembled together with a wood laminate stock. M1A serial number 020000 left the Geneseo, Illinois factory in this condition. Proper selection and application of hard, smooth finishes does enhance the service life of M14 rifle parts.

Ceramic coatings have been applied to metal cutting tools for decades. Titanium carbide coated cutting tools were introduced to the industry in 1969 and titanium nitride coated gear cutters were first used in 1980. Ceramic coatings are used on metal cutting tools because they are abrasion resistant, very hard, and chemically inert and have a low coefficient of friction. The benefits are longer tool life, higher cutting speed, higher feed rate and less machine tool down time. Ceramic coatings are also used to coat steel molds in plastic injection molding machines. The ceramic coating provides improved wear resistance for the mold. One such ceramic coating is titanium nitride.

Titanium nitride is applied to clean metal parts by the physical vapor deposition method. Briefly, this process entails evaporating a very thin layer of titanium on to the part inside a nitrogen gas chamber. The titanium nitride layer is typically 0.0001 " to 0.0002 " thick. This process is done at a temperature low enough (400 to 900 degrees Fahrenheit) so that the metallurgy of the part being coated is not affected. Depending on the ingredient composition, the color of titanium nitride coatings can be any of several hues of brown or gold. If the coating appears to be worn on a used piston, it is because the silica in the primer residue has attacked the relatively softer substrate metal, stainless steel.

Titanium nitride coated gas pistons became part of the build specification for XM25 rifles by 1988. The M14 SE Semi-automatic Sniper System is built with a dense chromium plated gas piston. The USGI M14 gas piston material specification is heat treated AISI 420 stainless steel. Typical USGI gas piston surface hardness ranges between 74.5 and 77 HRA (approximately 42 HRC). A gas piston coated with titanium nitride results in a surface hardness ranging from 80 to 85 HRC. Thin dense chromium plated gas pistons have a surface hardness ranging from 70 to 78 HRC. The advantages of a hard and smooth finish gas piston are as follows:

1) Anti-galling and anti-seizing properties – Galling is the welding of two metals together as they slide against each other. Galling and seizing are not desirable in the M14 rifle gas system. Titanium nitride and dense chromium coatings are harder but have lower coefficients of friction than stainless steel. These characteristics result in a slicker surface than the bare stainless steel gas piston. In effect, the hard finish is a solid lubricant in this application. Consequently, there is less gunpowder and primer residue buildup. Gunpowder and primer residue buildup does cause a very minute amount of seizing between the gas cylinder and gas piston.

2) Corrosion protection – Titanium nitride and thin dense chromium finishes have better pitting corrosion resistance than martensitic stainless steel.

3) Thermal protection – Thin layers of titanium nitride and dense chromium give the substrate metal, AISI 420 stainless steel in this case, better resistance to the effects of heat. The higher resistance to heat extends the service life of the gas piston much like titanium nitride coated metal cutting tools last longer than those that are not coated.

4) Better compression – The hard finish extends the life of the piston grooves. A sharper groove edge will provide compression for a longer amount of time plus it removes more of the gunpowder and primer residue from the cylinder wall than a bare gas piston.

5) Easier cleaning – Cleaning the piston is made easier since the gunpowder and primer residue does not adhere as well as it would on bare gas pistons.

Nitrocarburizing is a thermochemical process that improves the surface properties of iron or steel parts. It increases surface hardness to 60 HRC, reduces the coefficient of friction, improves wear resistance and enhances corrosion resistance of the metal treated. M14 type receivers, gas cylinders, gas cylinder locks, gas cylinder plugs, operating rods, front bands, hammers, triggers and scope mounts have received the benefits of nitrocarburizing treatment.

Nitrocarburizing produces two or three very thin layers of structurally altered steel by diffusing nitrogen and carbon into, not on, the surface of the steel part. Depending on the material composition and the treatment time, the depth of each layer will vary. Total depth of the nitrogen and carbon layers is normally 0.008 " to 0.040 ". The higher the alloy content of the part, the thinner the total depth of the nitrocarburizing layers for the same treatment time. A layer of epsilon iron nitride (6 to 9 % nitrogen and 1 % carbon) is created in the surface to a depth of less than 0.001 ". The epsilon iron nitride layer improves wear and corrosion resistance and lowers the coefficient of friction. A deeper layer of nitrogen under the epsilon iron nitride is produced among the steel molecules. This layer of nitrogen improves fatigue strength of the part. Depending on the treatment selected, a third very thin layer of passive Fe₃O₄ oxide is formed on the epsilon iron nitride layer for improved corrosion resistance. Application of this passive oxide layer is not suitable for stainless steel.

The passive Fe_3O_4 oxide layer enhances the corrosion resistance of the substrate metal, which is AISI 8620 alloy steel for the M14 type receiver. Burlington Engineering, Inc. (Orange, CA) performed a salt spray test (DIN 50 021 SS procedure) to compare the corrosion resistance of various surface finishes. The base metal was a medium carbon steel, AISI 1045. The number of hours until the first spot of oxidation was observed was as follows: 1) untreated AISI 1045 steel – 8 hours 2) hard chromium plating – 70 hours 3) double chromium plating – 100 hours 4) nickel plating – 120 hours 5) nitrocarburized AISI 1045 steel – 380 hours.

M14 Receiver Material

Military and commercial M14 type receivers are made of AISI 8620 or equivalent low carbon molybdenum-chromium alloy steel for the most part. However, there were some exceptions. At least twenty receivers were made of stainless steel by Armcorp USA in the late 1990s. These were identified by the letter S preceding the serial number. At least some of these receivers experienced premature wear of the elevation serrations. Poly Technologies M14S receiver serial numbers 000001 through 000005 were made of AISI 4140 alloy steel and hardened to 60 HRC. Other commercial receivers have been made of the same material but hardened to only 45 to 49 HRC. These receivers also exhibited accelerated wear of the elevation serrations.

The material requirement has always been AISI 8620H alloy steel for USGI M14 receivers. However, there were unintentional exceptions. At least ten Harrington & Richardson M14 receivers were made from AISI 1330 carbon steel and yet another Harrington & Richardson M14 receiver was made of high nickel alloy steel.

The M14 receiver (and bolt) should possess a hard and strong surface and a tough core. The surface hardness and strength provides outstanding wear and fatigue resistance while the soft core gives excellent resistance to failure from impact. It is a hypoeutectoid steel. It is not age-hardenable. That is, it not will increase in strength below 500 degrees Fahrenheit over time. AISI 8620 alloy steel can be hardened and strengthened at the surface and made softer at the core by properly heat treating the surface. It is free machining steel which means it forms small chips when cut. AISI 8620 alloy steel is the choice of material for the M14 receiver and bolt.

Theory of AISI 8620 Steel Heat Treatment – The goal is to produce a part, e.g., M14 receiver, with a hard and strong surface and a tough core. AISI 8620 is a low carbon alloy steel. There is not sufficient carbon content to raise the surface hardness to what is desired (52 to 60 HRC) by simply heating the exterior. The part made from AISI 8620 steel can be made as hard and strong as AISI 4140 steel surface heating by carburizing. The part is placed in a carbon rich medium and then heated above the A_3 temperature. High carbon content (0.8 to 1.0 %) is created to a shallow depth from the surface by the diffusion of carbon into the austenite molecules present. The part is then quenched and tempered for at least one hour within a specified temperature range. The result is a hard,

strong, and uniform depth martensite surface depth with a softer core of martensite and free ferrite. The thickness of the martensite layer, the case depth, is much less than a steel heat treated by surface heating such as is done with medium carbon alloy steels like AISI 4140. The result is that the softer core has a larger and consistent volume than it would have by surface heating. Thus, the carburized receiver has greater toughness. This is the chief advantage of AISI 8620 steel as the material of choice for the lightweight and reliable automatic M14 rifle receiver.

USGI M14 receivers were required to meet these hardness requirements until August 1961: surface hardness of 61 to 69 HRD (47 to 58 HRC), core hardness of 31 to 42 HRC, and a case depth of 0.012 " to 0.018 ". Due to the testing as a result of the December 1960 receiver and bolt failures, the receiver drawing hardness requirements were changed in August 1961 to 61 to 71 HRD (47 to 60 HRC) for surface hardness, 28 to 42 HRC for core hardness and the case depth remained the same, 0.012 " to 0.018 ".

During testing in 1961 at Springfield Armory and Winchester, it was found that Harrington & Richardson, Springfield Armory and Winchester receivers did not always comply with the drawing hardness requirements. These receivers measured out-of-specification low for core hardness in the barrel ring: 1) Harrington & Richardson serial numbers 50925, 73345, 76335, 76716, 76940, 77655, 78556, 79258, 79972 2) Springfield Armory serial numbers 107548, 11314 and 3) Winchester serial numbers 31962, 34300, 34870, 35474, 35563, 35847, 35973, 36187, 36324. Each receiver was tested in five or more spots for core hardness after cutting the barrel ring radially. All of the measurements taken were less than 28 HRC.

USGI M14 receivers that measured out-of-specification high for core hardness in the barrel ring were Winchester serial numbers 28305, 28308, 28259 and 28293. All of the readings (six readings per receiver barrel ring) in the barrel ring were greater than 42 HRC. Other USGI M14 receivers measured out-of-specification low for core hardness in the receiver lug area were Harrington & Richardson serial numbers 275109, 368915, 369006. All of the readings in the receiver lug area (two readings per receiver) measured less than 28 HRC.

Chinese and U. S. commercial M14 receivers are not always heat treated to the same procedure as was done for USGI M14 receivers. Armscorp USA receiver serial number 17371 and Federal Ordnance, Inc. receiver serial number 60223 were destructively tested for elemental composition, surface and core hardness, and case depth. Each receiver was cut just behind the bolt lugs and behind the rear sight pocket. Several readings were taken to determine the average hardness in the front and rear portions of the receiver. The material for both receivers was found to be consistent with the composition of AISI 8620 alloy steel. Results obtained for the Armscorp USA receiver were as follows: a) surface hardness - 55 HRC front, 53 HRC rear b) core hardness - 46 HRC front and rear c) case depth - 0.031 " front, 0.030 " rear. The Federal Ordnance receiver results were as follows: a) surface hardness - 39 HRC front, 40 HRC rear b) core

hardness - 23 HRC front and rear c) case depth - no case depth measured but the highest hardness readings were 46 HRC, front and rear, at 0.005 " below the surface. The surface hardness of a few Chinese receivers imported into the United States has tested substantially less than USGI drawing specification. Commercial receivers can often be brought to suitable surface and core hardness through proper heat treatment.

Assessment of AISI 9310 Alloy Steel - A 1961 Watertown Arsenal Laboratories study on the applicability of AISI 8620H steel for M14 receivers and bolts found that its heat treatment procedure required very strict control in order to meet the specified surface and core hardness requirements. As a follow up to the 1961 study, Watertown Arsenal Laboratories evaluated the hardness suitability of AISI 9310 for M14 receivers and bolts.

AISI 9310 is a nickel-chromium-molybdenum low carbon high alloy steel. The elemental composition of AISI 9310 steel obtained from Springfield Armory and tested by Watertown Arsenal Laboratories was as follows:

Carbon - 0.11 %
Manganese - 0.60 %
Silicon - 0.32 %
Nickel - 3.21 %
Chromium - 1.24 %
Molybdenum - 0.11 %
Phosphorus - 0.010 %
Sulphur - 0.009 %

The AISI 9310 steel was tested for hardenability and impact and its molecular structure examined under microscope. It was carburized at 1600 degrees Fahrenheit for 100 minutes, quenched in agitated oil at 150 degrees Fahrenheit then tempered for 60 minutes at 400 degrees Fahrenheit. This heat treatment resulted in a case depth of 0.014 ", a surface hardness of 56 HRC and core hardness of 39.5 HRC. The core had a 100 % martensite structure. The case was 75 % austenite and 25 % martensite. The high amount of austenite in the outer surface of the case reduced the surface hardness to a depth of about 0.005 ". The lower surface hardness could result in accelerated wear or fatigue of the M14 receiver or bolt. The solution was to subject the AISI 9310 steel to cooling at - 100 degrees Fahrenheit for two hours. The cooling treatment decreased the austenite concentration to less than 10 % and increased the surface hardness to 62 to 65 HRC.

The impact resistance of AISI 9310 steel was compared to that of AISI 8620H steel at - 40 degrees Fahrenheit. In Charpy V-notch impact testing, the AISI 9310 steel was able to absorb much more energy than 8620H steel. For example, when both steels were carburized then quenched at 400 degrees Fahrenheit in agitated oil, AISI 9310 steel absorbed 21.5 ft-lbf of energy while the AISI 8620H steel absorbed 3.4 ft-lbf of energy.

AISI 8620H steel contains a higher amount of sulphur which should make it easier to machine than AISI 9310 steel. However, the 1962 Watertown Arsenal study was optimistic regarding AISI 9310 alloy steel. Based on limited experience with machining both steels and the complex geometry of the M14 receiver and bolt, the Watertown Arsenal report surmised that AISI 9310 steel would be the easier of the two materials to machine.

The Watertown Arsenal Laboratories assessment of AISI 9310 concluded: 1) the core toughness of AISI 9310 was superior to that of AISI 8620H steel when both were carburized and heat treated 2) uniform case and core hardness could be obtained with AISI 9310 steel over a wide range of tempering temperature 3) the high austenite structure of carburized and heat treated AISI 9310 steel could be changed into martensite by a period of deep freezing and 4) the Charpy V-notch impact test was a valid test for small carburized steel parts requiring high toughness.

AISI 8620 Alloy Steel

As of 2010, there are at least four steel mills in the United States producing AISI 8620 alloy steel. The following is presented as background information on AISI 8620 alloy steel. It is a low carbon nickel-chromium-molybdenum alloy steel. The description is as follows:

Typical Uses – AISI 8620 alloy steel is the most widely used carburizing alloy. It is used for gears, shafts and other applications where high wear resistance and a tough core are desirable.

Features – It is noted for a good combination of fatigue and wear resistance, hardness, strength and toughness when properly heat treated and carburized.

Shear Strength – Ultimate shear strength is about 70 % of ultimate tensile strength.

Machinability – The machinability rating is 68 % of AISI 1112 in the annealed condition. It is machined prior to carburizing so that the case depth is not reduced. It polishes well. Average surface cutting speed is 110 feet per minute.

Forming – Forming is good in the annealed condition.

Normalizing – This alloy is typically heated to 1675 degrees F for sufficient time to ensure thorough heating then it is allowed to air cool.

Hardening – This alloy can be hardened by 1) normalizing by heating to 1500 F then water quenching then tempering or 2) annealing then cold working.

Carburizing – Carburizing is typically accomplished by heating to 1650 to 1700 degrees F in a carburizing medium then quenching the steel in oil.

Annealing – Anneal by heating to 1550 degrees F followed by furnace cooling at no more than 50 degrees F per hour down to 850 degrees F. Below 850 degrees F, it can be air cooled.

Forging – Forging is done from 2200 degrees to 1750 degrees F.

Tempering – The steel is heated at temperatures ranges from 400 to 1200 degrees F depending on the hardness wanted. The lower the tempering temperature the higher the hardness and tensile strength.

How was the U. S. Government Issue M14 receiver made?

1. A slug of AISI 8620 steel was cut off from 1 3/4 " diameter bar stock.
2. The steel slug was heated to forging temperature using automatic instrumentation. The temperature range for forging AISI 8620 steel is 1750 to 2200 degrees Fahrenheit.
3. The steel slug was placed into the impression-die drop hammer forging press and formed to make the raw forging.
4. The hot receiver forging was removed by hand and held while trimmed by machine.
5. The 2 pound 7 ounce raw forging was then heat treated. It was normalized by heating 130 to 140 degrees Fahrenheit above the A₁ temperature. This ensured the core exceeded the A₁ temperature which changed the molecular structure of the steel from ferrite and cementite to 100 % austenite. The raw forging was then air cooled or oil quenched and tempered at not less than 450 degrees Fahrenheit. Normalizing produced a fine pearlite structure with a minimal amount of free ferrite. The raw forging was normalized instead of annealed because it was faster and extreme softness was not needed for the receiver. Normalizing also produced greater strength and toughness than annealing. The forgings were checked within a specified hardness range before machining. This helped minimize tool wear.
6. The receiver went through broaching operations. Broaching is a simple and rapid means of removing metal. Typical tolerances that are obtained by broaching are + or - 0.0005 " to 0.0010 ". Broaching is usually more accurate and leaves a better finish than reaming or milling.
7. The receiver was machined to produce the final shape. The rifle model, manufacturer and serial number was then stamped on the receiver heel.

8. After all machining operations, the receiver was carburized, quenched and tempered. The receiver was placed in a carbon rich environment and heated to 1550 to 1600 degrees Fahrenheit. It was left in this condition long enough to obtain a case depth of 0.012 " to 0.018 ". For comparison, the thickness of Boise Cascade 20 pound bond copier paper is 0.0035 " (catalog number OX9001). The carbon surrounding the receiver diffused into the austenite structure surface. After a specified time, the receiver was immediately quenched in oil. The receiver temperature was reduced to well below the M_{90} temperature, 650 degrees Fahrenheit, in less than two seconds. This produced a minimum of 90 % martensite structure throughout the receiver. However, martensite lacks the toughness desired for the M14 receiver. So, the receiver was tempered at 350 to 450 degrees Fahrenheit for at least one hour. The martensite in the core decomposed gradually to a softer mixture of ferrite and cementite as temperature and time were increased. This change in the core increased the toughness of the core. The procedure was controlled to limit the free ferrite to 10 % of the core composition. By specifying and adhering to the temper temperature range and time restrictions, the amount of free ferrite was controlled. The resulting hardness, strength and toughness was achieved within the desired values.

9. The receiver was air gauged for compliance to blueprint dimensional tolerances. At Springfield Armory, non-compliant receivers were stamped with the letter S and discarded as scrap.

10. The receiver was inspected for defects by magnetic particle inspection.

11. The receiver was phosphate coated.

12. The receiver and other M14 parts were assembled together.

Receiver Heat Treatment

The heat treatment procedure for the M14 receiver as of the last drawing revision is as follows:

1. Recommended Heat Treatment - Normalize before machining (oil quenching followed by tempering at not less than 450 degrees Fahrenheit may be used in lieu of air cooling). Carburize at 1550 to 1600 degrees Fahrenheit to specified case depth. Oil quench from 1550 to 1600 degrees Fahrenheit. Temper to hardness specified.

2. Mandatory Requirements:

- a. Normalize before machining.
- b. Carburize to case depth 0.012 " to 0.018 ".
- c. Temper one hour minimum at 350 to 450 degrees Fahrenheit.
- d. Core hardness 28 to 42 HRC. Surface hardness 61 to 71 HRD.
- e. Microstructure of core shall not contain more than 10 % free ferrite after heat

treatment.

f. The use of a straight cyanide bath or gas processes shall not be permitted.

3. Inspection after Heat Treatment - After heat treatment each receiver shall be free from cracks, seams and other injurious defects as determined by magnetic particle inspection using a standard five turn magnetizing coil with a current of 400 to 500 Amperes.

The USGI specification for M14 receiver surface hardness is 48 to 60 HRC (61 to 71 HRD). A receiver core hardness of 35 HRC is the optimum value. In 1961, Springfield Armory tested forty-seven of its M14 receivers to see if a mathematical relationship could be established between the surface hardness of the barrel ring and core hardness in the receiver lugs. The receiver serial numbers tested ranged between 107548 and 119853. An additional 123 Springfield Armory M14 receivers were subsequently tested to verify the preliminary findings of the first forty-seven receivers. Using the empirically derived formula, the core hardness of 168 of 170 receivers was able to be predicted within + or - 3 HRC. The Springfield Armory formula was

$$\text{Core hardness} = 2 (\text{barrel ring surface HRC} + k - \text{barrel ring surface HRD})$$

where factor k was dependent on the area of the receiver cross-section being examined and the quench rate of the heat lot. Note: This formula is presented for educational purposes only. Do not use this formula to predict the core hardness in a commercial manufacture M14 type receiver.

The USGI M14 receiver was required to meet 139 quality assurance specifications. All M14 receivers were examined by magnetic particle inspection. The government drawing required the receiver to be marked with the letter M if no injurious defects were found. Otherwise, a percentage (0.65 % to 2.5 %) of receivers in a given production lot were examined for dozens of dimensional requirements, proper markings, and acceptable surface roughness. Three sample receivers were examined from each day's production for proper core hardness and case hardness depth. Sample receivers were also tested for proper surface hardness. Additionally, five sample receivers from each lot were subjected to a salt spray test. Failure of any one sample tested for adequate protective finish, surface hardness, case hardness depth or core hardness resulted in rejection of the entire lot.

The terms, part number and drawing number, are used interchangeably when discussing USGI M14 (and other small arms) parts. For the most part, these two terms are synonymous. The exception to this rule was when a drawing was made for an assembly, e.g., drawing number C7790187 for the M14 bolt assembly. In the strict sense, the drawing number is preceded by the drawing sheet size, A being the smallest and F the largest. Example, the flash suppressor drawing number is F7791053.

Development of Magnetic Particle Inspection

According to an American Society of Nondestructive Testing Level III certified individual who audits U. S. DOD aerospace parts contractors for compliance with government specifications, the procedure for magnetic particle inspection has changed since the late 1950s. Regarding the M14 receiver blueprint, he states [minor spelling errors corrected]:

The listed procedure would only detect flaws oriented in the transverse direction of the receiver. On a forged or billet receiver, it would only detect flaws perpendicular to the grain flow of the metal. Most often, flaws will run in the direction of grain flow, not perpendicular to it. If the receiver was made from a casting, the procedure would, at best, only detect 50% of the possible flaws.

The amperage values listed are also below the requirements of MIL-STD-1949A and ASTM E 1444. The formula for determining coil shot requirements in the coil described is: $NI = 45000/(L/D)$, where I is the required amperage, N is the number of turns in the coil, L is the length of the part, and D is the diameter (or major outside dimension). However, L/D (called the length to diameter ratio) can never exceed 15. If L/D exceeds 15, then 15 must be substituted for L/D. What this means is, when working the formula, the applied amperage through a five-turn coil should never be less than 600 Amps. The length to diameter ratio can never exceed 15, if it does, then 15 must be used. It is impossible to use the prescribed formula and come up with 400 to 500 Amps. By today's standards, the proper inspection might include a couple of coil shots (by shots I mean applications of electric current) plus a couple of direct contact shots and probably a central conductor shot. Any qualified magnetic particle inspector would most probably look at an M14 receiver and say at least two shots were required, and possibly as many as five. If I were inspecting it for myself, I would say five shots.

The magnetic particle inspection applied amperage requirement was changed to 800 to 1200 Amperes by no later than June 21, 1966 as shown on M14 Rifle drawing F7267000. Disclaimer: The above information is for educational purposes. Machining, heat treat or inspection of any firearm receiver or frame should be performed by an experienced firearm manufacturing FFL/SOT. The author is not responsible for any consequence resulting from any attempt by anyone to manufacture, heat treat or inspect a firearm or parts thereof. Such activities should only be performed by businesses licensed and credentials to do so.

USGI Receiver Geometry

USGI M14 and Taiwanese Type 57 receivers are drop forged. The raw receivers were formed by the impression-die drop forging method. The flashing was removed and the finish machining completed on special broaching, milling and drilling machines. Storms Drop Forging Co. (Springfield, MA) was the subcontractor that made the M1 Garand and M14 receiver and component forgings for Harrington & Richardson. The H&R,

Springfield Armory and Winchester receivers would last 400,000 rounds and the TRW receivers were good for 450,000 rounds. ¹

Comparison of the T20E2, the T44 and the M14 Rifles – John C. Garand, father of the M1 Rifle, designed the T20E1 and T20E2 rifles between September 1944 and June 1945 while working at Springfield Armory. At least one T20E2 rifle, serial number 57, was assembled by March 1945. The T20E2 and the M14 both fire from a closed bolt in semi-automatic and automatic, mask muzzle flash with an attachment, accept a bayonet and bipod, launch rifle grenades and have provision for installing a receiver scope mount. T20E2 muzzle velocity is 2,760 feet per second and the cyclic rate of fire is 700 rounds per minute. The select fire components of the M14 rifle are essentially copied from the T20E2 .30-06 caliber rifle. The M14 firing mechanism was borrowed from Garand's 1944 T20E1 design. Nineteen T20E2 rifles were produced by Springfield Armory between May and August 1945 and a number of them remain in the inventory of the Springfield Armory National Historic Site. The T20E2 rifle did not go into production due to the end of hostilities in August 1945. The U. S. Army did produce an operator's manual for this rifle. The T20E2 project ended in March 1948.

The significant differences between the T20E2 and M14 rifle select fire mechanisms are as follows: 1) the M14 rifle has an operating rod dismount notch in the center of the operating rod rail but the T20E2 rifle operating rod is removed through the notch at the rear top edge of the operating rod channel, similar to what is found on commercial manufacture M14 type rifles 2) the T20E2 rifle connector assembly has no operating rod rail "nub" 3) the T20E2 connector assembly is longer than the M14 connector assembly due to the greater length of the T20E2 receiver 4) there is no underside groove on the forward end of the T20E2 operating rod rail and 5) the forward end of the T20E2 connector assembly is anchored around the connector lock and not on top of it as is the case with the M14 late style connector. The original drawing for the late style M14 connector is dated April 01, 1959.

The T44 rifle was developed from the T20E2 receiver. Between August 1951 and March 1952 the T44 receiver got an operating rod dismount notch in the center of the operating rod rail and the corresponding "nub" was added to the T44 connector assembly. In January 1954, the United States and other North Atlantic Treaty Organization (NATO) nation members adopted the 7.62 x 51 mm cartridge as the standard for rifle ammunition. The new cartridge necessitated redesign of the T44 rifle. Colonel Rayle, Springfield Armory Head of Research and Development, sanctioned a contract with Mathewson Tool Company (New Haven, CT) to produce the drawings for and delivery of twelve shorter length receiver T44 rifles. The first such rifle was delivered to the U. S. Army in June 1954 on schedule. Dave Mathewson modified the receiver design shortly thereafter to more easily facilitate bolt removal during disassembly. This rifle with the shorter length receiver was officially designated as the T44E4 by October 1954.

A January 1955 Springfield Armory photograph of a T44E4 rifle and associated select fire parts shows a shorter T44 style connector assembly in response to adoption of the 7.62 x 51 mm NATO cartridge. However, this means that the forward underside groove for the operating rod rail was not part of the 1954 T44E4 receiver design (drawing F7267056). The operating rod rail forward underside groove was part of the M14 receiver design when drawn in July 1958 (drawing F7790189).

All three designs, T20E2, T44E4 and the M14, had a hole drilled radially through the right receiver leg. Contrary to popular belief, this hole was not used as a fixture alignment hole to machine the receiver. Instead, the hole allowed workers to use hooks to dip receivers into and out of phosphate coating tanks.

Comparison of Select Fire and Semi-Automatic Receivers - The functional differences between USGI and commercial M14 type semi-automatic receivers are slight but important. The USGI M14 receiver has a notch cut in the center of the receiver rail. This allows for dismounting of the operating rod during disassembly. The forward end of the USGI receiver rail has a groove cut into it on the underside to secure the connector assembly from drifting to the right and losing contact with the operating rod as it moves forward to initiate automatic firing sear release function. The USGI receiver is also manufactured with a selector lug on the rear right hand bottom side. The selector and connector assemblies are attached to the rifle by this selector lug.

The select fire M14 type receiver requires a USGI M14 design sear to allow automatic fire when the selector switch is placed in the automatic fire position. If a commercial reproduction M14 type sear or a M1 Garand sear is installed in the firing mechanism, the rifle will not fire in automatic mode even with all select fire components installed and the selector switch placed in the automatic position. This is because the commercial reproduction and M1 Garand sears are not wide enough to contact the sear release no matter the position of the selector switch. The USGI M14 sear is approximately 5/32 " wider than the M1 Garand and commercial reproduction sear designs.

The operating rod rail center dismount notch and forward end underside groove in and of themselves do not facilitate automatic fire but serve as convenient anchor points for reliable operation of the connector assembly. Nonetheless, law enforcement agencies have thought otherwise and enforced their interpretation of the law accordingly. The reader is strongly encouraged to stay out of trouble with law enforcement agencies and the judicial system. Warning: DO NOT alter any M14 type rifle operating rod rail and DO NOT purchase or possess a M14 type receiver in the United States with these two machining cuts or a selector lug unless it is listed in the National Firearms Act Registry.

USGI Receiver Common Traits – USGI receivers have a distinct machined flat surface with a longitudinal edge on the top of the barrel ring. Springfield Armory, Winchester, Harrington & Richardson and TRW used the upper case letters MM to denote millimeter in their receiver heel stamping.

USGI Receiver Functions - The receiver is the heart of the M14 rifle. The USGI M14 receiver performs the following functions: 1) correctly aligns and securely holds the barrel 2) supports, guides and locks the bolt 3) guides the operating rod 4) aligns and holds the firing mechanism 5) acts as an attachment point for the cartridge clip guide 6) receives the magazine for feeding ammunition into the barrel 7) houses the rear sight and serves as the reference for adjustment 8) holds the bolt lock 9) holds the selector shaft and sear release 10) guides the connector assembly 11) holds the connector lock which secures the operating rod spring guide at the rear end and 12) serves as the means of attaching a mounting platform for optical sights.

The following is a collection of thoughts from Mr. Charles T. Green, a degreed mechanical engineer with over twenty years experience. He is also an expert in the use of CAD software and has created "solid" CAD models of the of the M14 Receiver and other components.

The first glance at the M14 drawing set can be an intimidating experience. For example, the receiver drawing is a large, four page wilderness of views, text and dimensions. And, every inch appears to be covered with cryptic information. These documents represent classic, 'old world' conventions from an earlier industrial era. And, they were typically made by real craftsmen who learned their trade in formal drafting schools. Sadly, they also represent a lost art form displaced by modern CAD computers. And, since drafting conventions change with time, correctly interpreting these documents can be challenging, even for experienced draftsmen and engineers. For example, the Geometric Tolerance system employed predates this engineer's experience by many decades.

Of course, the M14 is a revised version of the M1 Garand rifle. And, the M14 drawings appear heavily influenced by the conventions of the original 1937 Garand drawings. Many of their drawings and individual views appear identical. And, it is possible the M14 draftsmen traced views directly from the M1 drawings to save time and labor. As a young engineer, I personally used this method to create many "board drawings" of turbine engine components while working in the turbomachinery industry. It is a widely used technique. And, it is still used today in companies that have not yet converted to CAD. So, it's not surprising the M14 drawings drafted in 1958 follow the same drafting conventions of the earlier 1937 M1 Garand drawings.

However, the greatest difficulty in understanding these drawings has to do with the rifle's design. Several of the M14's components are extremely complex. And, its receiver is one of the most difficult to machine parts I have ever examined. It easily requires more than 240 machine "set-ups" to manufacture it. Most machinists would probably charge well over \$10,000 just to make a prototype. But, it would take a very experienced machinist to do it correctly. And, much of the cost would be for the time spent interpreting the drawing, not to mention making all the tools, jigs and fixtures. I say this because an enormous amount of time was spent studying the receiver drawing while creating a CAD model of it. And, it's understandable why some manufacturers charge over a thousand

dollars for their M14 receivers.

This is also why many manufacturers "lost wax" cast M14 receivers before machining their critical surfaces. The noncritical surfaces are left "as-cast." And, this saves significant machine time and cost. The original "Mil-Spec" receivers were forged before machining for principally the same reason. That is, to get a part to "near net-shape" as possible before machining to also reduce cost. Unfortunately, hot forging is often not as accurate or precise as lost wax casting. So, nearly all hot forged surfaces must be machined or otherwise finished. But, forging does have another advantage: it improves strength by refining the steel's grain structure and forcing the grain to flow with the geometry of the part. Cast parts are sometimes heat treated to greater (internal) hardnesses to compensate for this shortcoming. Or, a superior alloy of steel may also be selected. As a rule of thumb, metallurgists and engineers consider forged parts superior to cast. But, cast M14 receivers can have excellent strength. And, the case hardened surfaces of cast receivers are typically just as hard and wear resistant as the forged. Most cast receivers today are considered to be very good. And, this is due in part to the overall strength of the M14 design. - Charles T. Green

Intervening Rifle Models: M2 through M13

Until the M1 Rifle was adopted, small arms were designated by date, e.g., M1903. By some time in the 1930s the U. S. Army changed to designating weapons by model number. The M1 Garand was the first rifle. The M1 Carbine was the first carbine. The M1 Thompson was the first submachine gun and so forth. Some of the intervening rifle models between the M1 and M14 are identified as follows:

M2: The M2 was a Springfield Armory .22LR caliber magazine fed bolt action rifle. It was 43.66 " long and weighed 8.87 pounds.

M4: The M4 (T38) was a magazine fed .22 Hornet caliber bolt action survival rifle. Harrington & Richardson made 29,344 M4 rifles in 1949. The M4 weighed 4 pounds and was 32 ½ " long with the telescoping wire stock extended. The M4 had a 14 " barrel and a magazine capacity of five rounds. Earlier models had a leaf rear sight but later models were fitted with an adjustable rear peep sight.

M5: The M5 was a combination .22 Hornet caliber rifle and .410 gauge shotgun. Harrington & Richardson produced fifty M5 rifles in 1950.

M6: The M6 was similar to the M5. It too was a combination .22 Hornet caliber rifle and .410 gauge shotgun. The M6 was developed by the U. S. Army Ordnance Command and produced by Ithaca around 1951. The M6 weighed 3 pounds 12 ounces. It had an overall length of 28 ¼ " and a folded length of 15 ". This model was reproduced by Springfield Armory, Inc. for a time.

M8 and M8C: These were spotting rifles for the 105 mm and 106 mm recoilless rifles, respectively.

M9: This may be a sub caliber device for the 106 mm recoilless rifle but this has not been confirmed.

M10: This model number was not used by the U. S. Army.

M11: This model number was not used by the U. S. Army.

M12: This model designation was assigned to three .22LR caliber bolt action training rifles: 1) Winchester Model 52 Heavy Barrel 2) Remington Model 40X-S1 3) Harrington & Richardson M12. Remington Model 40X-S1 M12 rifles were in the inventory of Marine Corps Junior ROTC units in the 1970s for smallbore rifle marksmanship training and competition. The Harrington & Richardson M12 was a single shot heavy barrel heavy wood stock rifle fitted with Redfield globe front sight and Palma rear sight. It weighed about 13 pounds. The Civilian Marksmanship Program sold this rifle to civilians as late as March 2005.

M13: Likewise, this model number was given to two .22LR caliber training rifles, the Remington Model 513T Targetmaster and the Winchester Model 75 Target. Remington Model 513T Targetmaster M13 rifles were also in the inventory of Marine Corps Junior ROTC units in the 1970s.

The M14 rifle was designated as such in 1957 since that number was the next available model number for a rifle.

M14 Rifle Development Highlights

The M14 rifle incorporates a number of designs borrowed from developmental rifles dating between 1944 and 1954. Essentially, the M14 as known today is a slightly improved version of the T44E4 rifle design of 1954. The T44E4/M14 rifle incorporated the following component designs from other rifles:

M1 - hand guard and rear sight

M1E3 - bolt roller

T20E2 - bolt, connector lock, firing mechanism, magazine latching system, operating rod, operating rod spring, operating rod spring guide, select fire components and stock

T25 - gas system and combination front sight, castle nut, setscrew and muzzle attachment assembly

T31 - magazine

T44 series - bolt lock (T44 and T44E1), cartridge clip guide (T44E1) and receiver (T44E4)

The T25 rifle, including the improved Joseph White gas system, was designed by Earle M. Harvey. Remington Arms Co. developed the T44 and T44E1 bolt locks. On the T44, the bolt lock was part of a detachable plate assembly that mounted to the left side of the receiver. By 1953, the bolt lock was held captive by a pin to the receiver itself in the T44E1 rifle. The T44E1 also featured a cartridge clip guide. Otherwise, the component parts listed were the ideas of John C. Garand. He patented the extractor, hammer, magazine, magazine latching system, and rear sight parts. The rear sight assembly was designed for easy one-hand adjustment and reliable keeping of elevation and windage settings even under automatic fire.

Denied his wish for a magazine fed rifle in the M1, John Garand's T31 magazine was further improved by him for the T44E4 (M14). The magazine fed T44E4 (M14) required reloading less often than the M1. In combat, this can be a great advantage. The sheet metal used for the magazine tube, follower and floor plate make it economical to manufacture yet rugged enough to endure combat use. The magazine spring was designed to avoid any tilting of the follower inside the magazine tube or body. Should a follower tilt inside the magazine body it may jam and render the rifle temporarily out of service. In a combat situation, this can be a fatal flaw for the operator. The relative alignment of the M14 receiver with the parts of a magazine work together to feed every cartridge at a slightly upward angle for reliable chambering. A rear side latch plate was added to the magazine tube. The T31 magazine front side rectangular hole was retained. The two features, the latch plate and the rectangular hole, established the means for locking the magazine to the T44E4 (M14) rifle. The latch plate is held securely by the magazine latch. The rectangular hole is retained by the operating rod spring guide. The follower was designed to hold the bolt open after the last cartridge had been ejected from the magazine. The front side of the magazine tube was given a welded lap joint to provide extra resistance to deformation from inertial contact with the cartridges. The double-stack arrangement of the cartridges increases capacity for the same length over a single-stack magazine. The M14 magazine can be disassembled and parts easily replaced in the field though it has proven itself durable. The M14 magazine can be recharged easily whether it is inserted into the rifle or not. Mr. Garand designed the T20 magazine latching system to 1) allow positive retention of the magazine 2) rapid one-hand insertion of a magazine into the rifle and 3) easy one-hand removal of the magazine by simultaneously pressing on the magazine release and pushing the magazine forward and downward away from the stock. A magazine may be inserted either by pushing straight up into the magazine well or reversing the path taken for removal.

Much of the documentation of the development of the M14 rifle from 1952 until 1959 remains inaccessible for public inspection. This documentation is in classified material storage at the National Archives in Washington, DC. During the 1950s, the United States

M14 RIFLE HISTORY AND DEVELOPMENT

Department of Defense produced an immense quantity of classified documents related to the development of thermonuclear weapons. U. S. government documents related to M14 rifle development are stored along with the information on nuclear weapons. With the passage of time, the M14 project documents will become available for public inspection. Some highlights of the M14 rifle project are listed below:

July 01, 1957 to December 31, 1957 - Springfield Armory begins development on aluminum M14 magazines. Mathewson Tool Company produces the first experimental aluminum M14 magazines.

December 1957 - The unlocking cycle of the M1 Garand and M14 rifles was tested by Springfield Armory. The purpose of the test was to determine the average time, in milliseconds, from firing pin contact to: a) bullet passing the gas port b) bullet exit c) initiation of operating rod recoil d) end of operating rod dwell e) completion of bolt unlocking f) position of bullet at initiation of operating rod dwell g) position of bullet at end of operating rod dwell and h) position of bullet at completion of bolt unlocking. Three single rounds were fired from each of three M1 and three M14 (T44E4) rifles. The ammunition used was M2 armor piercing for the M1 and T93E1 or T93E2 armor piercing for the M14. Each rifle was fully loaded for each series of three shots. High speed motion picture cameras (operating at 6,000 to 7,000 frames per second) and flash strobes were used to record hammer fall, bullet exit, operating rod movement and bolt unlocking during each firing sequence. Lumiline screens were used to record average bullet velocity at a distance of 53 feet forward of the muzzle. The film was analyzed and average values calculated to obtain the following values for the M14 rifle: a) hammer fall - 0 milliseconds b) bullet passes gas port - 1.01 milliseconds c) bullet clears muzzle - 1.25 milliseconds d) initiation of operating rod recoil - 1.53 milliseconds e) end of operating rod dwell - 3.57 milliseconds f) completion of bolt unlocking - 5.00 milliseconds g) amount of bullet travel at start of operating rod recoil - 9.2 " past the muzzle h) position of bullet at end of operating rod dwell - 76.1 " past the muzzle i) position of bullet at completion of bolt unlocking - 123.0 " past the muzzle and j) bullet velocity - 2,733 feet per second.

1958 - A modified five round Mauser K98 cartridge clip and a magazine filler were developed and adopted. General Tire & Rubber Company delivers fifty T44E6 and M14 reinforced fiberglass stocks under contract from Springfield Armory. Development work was done on the receiver scope mount and improvement of bolt roller durability.

March 18, 1958 – The U. S. Army Ordnance Command awards a contract to Springfield Armory for a pilot production lot of 15,000 M14 rifles.

July 01, 1958 to December 31, 1958 - The M14 Technical Data Package is completed.

October 1958 - The work needed to calibrate the rear sight elevation knob in meters is completed. Aberdeen Proving Ground and Springfield Armory participated in this project. Master Sergeant Otto Hanel was one of the soldiers involved in the testing and

development of the M14 rifle at Aberdeen Proving Ground during this time.

December 1958 – Springfield Armory begins making production M14 parts.

January 01, 1959 to June 30, 1959 - Several improvements were made to the M14 rifle including: 1) a longer connector lock pin for ease of disassembly 2) modification of the gas cylinder plug and gas piston to make assembly easier 3) modified barrel, gas cylinder and flash suppressor splines to prevent incorrect assembly 4) modification of the barrel diameter to prevent cross-threading of the gas cylinder lock and 5) gas cylinder plug design improvement to prevent cross-threading and thread stripping. Development work continued on the reinforced fiberglass M14 stock.

February 21, 1959 - The Arctic Test Board recommends adoption of the Colley type winter trigger for the M14 rifle.

March 16, 1959 to March 23, 1959 - Two T44E4 bipod designs were tested at Fort Benning, GA for the M14 rifle. Borrowing from John C. Garand's patented M1 rifle bipod, both bipods attached to the bayonet lug. One version did not have any height adjustment. The second bipod model had three height adjustments, weighed 1.28 pounds and could be folded against the stock. Eventually, neither design was adopted. As part of the same test, the M14 rifles were fitted with aluminum butt plates and steel butt plate flappers. Additionally, three types of fiberglass hand guards were tested: Type A - solid, Type B - hand guard with thirty-eight round holes and Type C - hand guard with fourteen slotted holes.

April 10, 1959 - The U. S. Army Infantry Board published the Project Number 2839 report that recommended the adoption of the Type C hand guard and the hinged butt plate for the M14 rifle. The Army Infantry Board report also recommended the M14 rifle with the Type III bipod (referred to as the Type II bipod in other references) as a substitute for the M15 rifle.

July 01, 1959 to December 31, 1959 - Six T140 grenade launchers were made by Springfield Armory. Four of the T140 launchers were sent to the U. S. Marine Corps for testing. Springfield Armory also manufactured twenty-four M6 bayonets of which eighteen were sent to the U. S. Army Infantry Board and the U. S. Marine Corps for testing. A number of fiberglass reinforced M14 stocks were manufactured and sent to the U. S. Army in Alaska for testing. The U. S. Army Continental Army Command standardized the ventilated fiberglass reinforced plastic hand guard and hinged butt plate for the M14 rifle.

July 1959 – The first fifty Springfield Armory M14 rifles were assembled. The stocks and hand guards were made of black walnut.

M14 RIFLE HISTORY AND DEVELOPMENT

August 1959 – Ten of the first fifty M14 rifles were shipped to Fort Benning, GA for testing. All shipment of production M14 rifles was suspended pending test results. The Type IV bipod (referred to as Type III in other references) was tested successfully at Fort Benning. It was later adopted and designated M2 Bipod.

September 1959 – M14 rifle testing is completed with satisfactory performance. The M14 hinged butt plate drawings are completed. The first nineteen M14 rifles are assembled and tested at Springfield Armory.

October 1959 – The first Springfield Armory production M14 rifle is presented to Master Sergeant George C. Ferguson by Secretary of the Army Wilbur C. Brucker at Aberdeen Proving Ground, MD.

March 04, 1960 - U. S. Army Chief of Staff General Lyman L. Lemnitzer presented the first M14 rifle to Commandant of the Marine Corps General David M. Shoup in a ceremony in General Shoup's office. The rifle had a highly polished walnut stock, walnut hand guard, operating rod and magazine.

May 03, 1960 - The U. S. Army Infantry Board concluded its first evaluation of experimental synthetic stocks for the M14 rifle.

June 30, 1960 - A total of 9,471 M14 rifles had been delivered to the U. S. Army.

July 01, 1960 to December 31, 1960 – Aberdeen Proving Ground (MD) successfully develops and tests the XM12 blank firing attachment and a breech shield for the M14. Engineering tests on the reinforced fiberglass stock and hand guard were completed at Aberdeen Proving Ground. The reinforced fiberglass plastic slotted hand guard was found to be superior to the wood hand guard in the testing. Additionally, it was slightly less expensive to manufacture than the walnut hand guard. The fiberglass stocks successfully passed testing as well but the grenade firing test resulted in further development work for improved durability. Development of the M14 National Match rear sight was performed by Springfield Armory including preliminary drawings and manufacture of a prototype rear sight.

October 1960 - Springfield Armory delivers the last rifles from its pilot production order of 15,600 M14 rifles to the U. S. Army.

December 1960 - The first use of hinged butt plates and slotted fiberglass hand guards in the assembly of M14 rifles occurs at Springfield Armory.

December 15, 1960 – A number of Harrington & Richardson (H&R) M14 receivers and bolts failed during range firing at Fort Benning, GA.

January 01, 1961 to June 30, 1961 – Springfield Armory makes the first production birch M14 stocks. Walnut became the alternate standard for the M14 stock. The blank firing attachment and breech shield are tested at Fort Benning, GA. Springfield Armory took the initial steps to produce M14 barrels with a 1:10 twist for anticipated testing with 172 grain match grade ammunition.

January 11, 1961 – Ordnance Weapons Command releases Engineering Order No. 164. This document provided additional quality assurance provisions for the bolt, receiver, barrel and rifle. This Engineering Order was the result of investigations conducted by Springfield Armory, Watertown Arsenal, Rock Island Arsenal, Frankford Arsenal and Aberdeen Proving Ground into the H&R M14 rifle failures of December 1960.

April 1961 – Fiberglass hand guards are produced at Springfield Armory.

April 27, 1961 - The U. S. Army Infantry Board received synthetic material M14 stocks for testing and evaluation.

July 1961 - Brigadier General Elmer J. Gibson is appointed as the M14 Rifle Project Manager by the U. S. Army Chief of Ordnance. Two years later, Major General Gibson is the Army Materiel Command Director of Procurement and Production.

July 01, 1961 to December 31, 1961 - U. S. Army soldiers in Europe reported difficulty in stowing and accessing the butt stock cleaning kit. Springfield Armory determined the butt stock storage compartment holes were not correctly located. The affected stocks were repaired and the stock drawing was revised. Springfield Armory conducts limited testing in the M14 National Match project. Springfield Armory was experimenting with the chromium plating process for M14 National Match barrels.

September 21, 1961 – The M12 blank firing attachment, M3 breech shield and M82 blank cartridge were officially classified as Standard A.

September 29, 1961 - The U. S. Army Infantry Board concludes service testing of pre-production synthetic M14 stocks. The synthetic material stock was recommended for adoption with further development requested to improve durability of the bonded seam.

October 02, 1961 - The Preparedness Investigating Subcommittee of the United States Senate Armed Services Committee issued a report on the slow pace of development and implementation of the M14 rifle project. Starting with developmental work of the T20 rifle in 1945, the first M14 rifle did not reach the U. S. Army until October 1959. The Senate subcommittee placed the principal fault on the inability of the U. S. Army to procure sufficient funding from the Department of Defense even though Congress had appropriated more funding than had been requested. The report stated that the large number of M1 Garand rifles in inventory likely contributed to the delay in producing the M14.

M14 RIFLE HISTORY AND DEVELOPMENT

October 23, 1961 - The United States Continental Army Command agreed with the September 29, 1961 recommendations of the Army Infantry Board regarding adoption and development of the synthetic M14 stock.

January 01, 1962 to June 30, 1962 – The preservation procedure for birch stocks was developed and adopted. It required only one dip in tung oil whereas the walnut stocks had been dipped twice.

January 10, 1962 - Secretary of Defense Robert S. McNamara reorganizes the U. S. Army pending Congressional approval. The Technical Services commands now fall under the authority of the Secretary of the Army.

February 1962 - Congress approves the organizational changes made by Secretary McNamara.

March 1962 - Springfield Armory received the final shipment of 200 aluminum M14 magazines from Mathewson Tool Company per Army Ordnance Command contract ORD-5115.

July 01, 1962 to June 30, 1963 - Work was begun on the Technical Data Package for the M14 NM rifle.

July 1962 - The Mathewson Tool company aluminum M14 magazines were tested with favorable results.

August 01, 1962 - The Ordnance Weapons Command, one of several commands in the U. S. Army Ordnance Corps, becomes the Army Weapons Command (AWC later WECOM) under the newly formed Army Materiel Command (AMC). The Continental Army Command (CONARC), the Combat Developments Command (CDC) and the AMC emerge as the three major commands of the U. S. Army.

December 20, 1962 - Lieutenant General John P. Daley, Commanding General of the U. S. Army Combat Developments Command (CDC) issues the classified report Rifle Evaluation Study. The report consisted of an assessment of the rifles, a conclusion and recommendations regarding the future of the tested rifles. The rifles considered were the M14, M14 (USAIB), the commercial version of the rifle later adopted as the M16, the AK47 and the Special Purpose Individual Weapon (SPIW). The Rifle Evaluation Study summed up the primary purpose of the rifle as being an individual infantry weapon capable of engaging direct fire targets out to 400 meters with a selective capability for automatic fire. The report listed the following desirable characteristics for the military rifle: 1) reliability 2) durability 3) lightweight 4) simple 5) accurate 6) flexible 7) lethal 8) acceptable ergonomics and 9) minimal position disclosing effects.

The SPIW was assessed as being the weapon best able to meet all the desired characteristics once fully developed. The commercial version of the rifle later adopted as the M16 was judged second best. That rifle was judged to be a "marked improvement over the M14 rifle primarily because of lower weapon and ammunition weight." The 1962 reports listed the weight of the M14 (Modified) rifle at 9.84 pounds and its loaded magazine at 1.5 pounds. The commercial rifle later adopted as the M16 was listed with a weight of 6.55 pounds and a loaded twenty round magazine weight of 0.75 pounds. This was the turning point for retention of the M14 rifle as the primary infantry rifle in the U. S. Army. General Daley concluded that the commercial rifle later adopted as the M16 was his preferred choice as long as its shortcomings, reliability and poor night firing ability, were rectified. He acknowledged in his report that there was "wide disagreement at all levels" regarding the military value of the commercial rifle later adopted as the M16. The controversy was eventually settled within the U. S. military but it remains a lively topic of debate among civilian firearms owners to the present day.

January 21, 1963 – In light of the December 1962 CDC Rifle Evaluation Study, Secretary of Defense Robert S. McNamara announced the end of M14 rifle procurement with that fiscal year's contracts.

Winter 1963 - A congressional delegation from Massachusetts consisting of U. S. Senator Edward M. Kennedy, U. S. Senator Leverett A. Saltonstall, ranking Republican of the U. S. Senate Armed Services Committee, and U.S. House of Representatives Speaker John William McCormack met with Secretary of Defense Robert S. McNamara. The legislators attempted to persuade Secretary McNamara to award new government contracts to Harrington & Richardson for the M14 rifle. They were unsuccessful in garnering new M14 rifle contracts for Harrington & Richardson but Secretary McNamara said that an effort would be made to see what other military contracts the Massachusetts firm might be able to qualify for.

February 1963 - Harrington & Richardson received a contract for research and development of the SPIW.

April 1963 - The U. S. Marine Corps had removed all defective Harrington & Richardson M14 bolts from its inventory.

July 01, 1963 to June 30, 1964 - A thorough revision was made of the M14 Technical Data Package. The wood M14 stock was redesigned to increase service life.

October 01, 1963 - Springfield Armory completed the Technical Data Package for the M14 (USAIB).

October 1963 – Per request of the U. S. Army Weapons Command, Springfield Armory fabricated and tested four prototype M14E2 rifles. Springfield Armory delivered its last batch of M14 rifles to the U. S. Army.

M14 RIFLE HISTORY AND DEVELOPMENT

November 1963 – The U. S. Army officially designated the October 1963 revised design of the M14 (USAIB) as the M14E2. Authority was given to Springfield Armory for 8,350 M14E2 conversions.

June 30, 1964 – Official end of new M14 rifle production. TRW made its only production run of M14 NM rifles in 1964.

July 1964 – Thompson-Ramo-Wooldridge, Inc. delivered the last 200 M14 rifles to the U. S. Army.

December 1964 – Springfield Armory completes delivery of 8,350 M14E2 rifles to the U. S. Army.

July 01, 1965 to June 30, 1966 - Springfield Armory converted 4,489 M14 rifles into M14 NM rifles, 2,094 in 1965 and 2,395 in 1966. Springfield Armory conducted a study to evaluate different heat treatment processes and long term storage effects on M14 magazine springs. Work was begun at the Armory to fill spare parts orders for 64,000 bolts with rollers, 35,000 operating rods and 12,000 stocks. The following decisions were made related to M14 rifle design or production:

- 1) These M14E2 design improvements were incorporated into the procurement system: M2 bipod, winter trigger assembly, muzzle stabilizer with positive locking mechanism, stock back plate, better hand grip, and improved bipod jaws.
- 2) Design improvements were completed on a synthetic rubber stock pad to smooth out automatic fire under all environmental conditions.
- 3) Rock Island Arsenal personnel were trained as M14 NM rifle armorers as part of the planned shutdown of Springfield Armory.
- 4) A study was conducted to determine if increasing the flash suppressor inside diameter would improve accuracy. As a result of the study, Springfield Armory recommended no change in the flash suppressor design.
- 5) Springfield Armory and Frankford Arsenal conducted a test of ammunition. Springfield Armory recommended adoption of the extractor design part number 7791578.
- 6) An improved elevation knob and pinion assembly, part number 11010363, was adopted.

December 1965 – The final revision drawings for the firing pin and synthetic M14 stock were issued.

LEE EMERSON

February 1966 - Harrington & Richardson was awarded a contract to manufacture M14 gas cylinder locks.

March 1966 - Harrington & Richardson was awarded a contract to manufacture M14 bolt locks.

May 1966 - Harrington & Richardson was awarded a contract to manufacture M14 gas pistons.

July 01, 1966 to June 30, 1967 – Rock Island Arsenal rebuilt 2,462 rack grade rifles into M14 NM rifles.

July 1966 - Harrington & Richardson was awarded a contract to manufacture M14 selector switches.

August 1966 - Springfield Armory and Rock Island Arsenal armorers worked together at the 1966 National Matches to service M14 NM rifles.

October 1966 - Winchester was awarded a contract to manufacture M14 gas cylinders.

December 1966 – Springfield Armory completed a rebuild program on 24,000 M14 rifles. Harrington & Richardson performed the targeting of these assembled rifles under contract from Springfield Armory.

1967 - Springfield Armory was given an order to deliver 52,780 M14 barrels. Barrel production ran from June into October. Delivery of the barrels was completed by the end of the year.

January 1967 - Springfield Armory transfers responsibility for the National Match Weapons program to Rock Island Arsenal.

May 1967 - Harrington & Richardson was awarded a contract to manufacture M14 connector assemblies.

July 01, 1967 to June 30, 1968 - The technical data was updated and completed for M14 NM rifle barrels.

January 1968 - M14 rifles were used as the test control specimens for evaluation of M16A1 rifles at Fort Sherman in Panama.

April 1968 - TRW was awarded a contract to manufacture M14 bolts.

April 30, 1968 - Springfield Armory was closed. Less than twenty of the 480 Armory employees agree to transfer to Rock Island Arsenal. The majority of the employees went

to work at Smith & Wesson, Inc. (Worcester, MA) and other private industry jobs in the local area. The M14 production equipment had been crated up and shipped to Rock Island Arsenal. The M14 manufacturing records, drawings and other documents were shipped to the U. S. Army Weapons Command at Rock Island Arsenal and to a federal records center in St. Louis, MO.

August 1969 - Three M14 NM rifles were used as test control specimens in M16 rifle accuracy testing conducted by the U. S. Army Marksmanship Training Unit. The M14 NM rifles shot an average 6.4 " group at 300 meters.

M14 Rifle Factory Inspection

Every M14 rifle had to pass several tests before it could be shipped to the military. The M14 rifle was tested by first firing a high pressure 67,500 psi proof round. The rifle and spent cartridge case were examined for any signs of broken parts and overpressure. If the test was successful, the proof P marks were immediately applied to the barrel (P), bolt (a punch mark), stock (P inside a circle or serif P inside a circle) and receiver (punch mark). Winchester M14 barrels have been observed with the letters P and W inside an oval for the proof marking.

The proof test was followed by function tests in semi-automatic, burst automatic, and sustained automatic fire. The rate of fire in automatic had to be within a specified range, 650 to 780 rounds per minute. Each rifle was required to deliver its center of impact within a specified limited area around the point of aim at 100 yards with the rear sight set at eight clicks up from bottom and at zero windage. Every rifle had to group within 5.6 " at 100 yards with five rounds of M80 ball ammunition. Additionally, M14 rifles were tested for tightness of barrel draw, acceptable headspace, firing pin indentation and trigger pull force. The military specification for the amount of trigger pull force was 5.5 to 7.5 pounds for the M14 and 4.5 to 6 pounds for the M14 NM. If the rifle failed, it was tagged to record what the particular problems were. The manufacturer replaced the parts and sent it through the entire inspection process again. Most rifles passed the testing the second time around. The information noted on the tags was recorded and used to analyze the manufacturing process to determine what needed correction.

While a five shot group of 5.6 " at 100 yards may not seem terribly accurate, this includes the inaccuracy of the M80 ball ammunition factored in. The Boston Ordnance District was responsible for final acceptance of M14 rifles manufactured by Harrington & Richardson and Winchester. By Fiscal Year 1962, it had conducted a study into the factory accuracy testing rejection rate of M14 rifles. The Boston Ordnance District discovered that the M80 ball ammunition of itself had an average spread of 3.57 " at 100 yards within every ninety rounds fired. Ammunition inconsistency aside, a rack grade M14 type rifle is accurate for a battle rifle when properly assembled.

In addition to test firing, which every rifle went through, M14 rifles were pulled out at given intervals and subjected to endurance firing for 6000 rounds. One M14 rifle and twelve magazines were selected by a U. S. government representative out of each of the first five lots of 500 rifles at the factory. If each of the five selected rifles passed the endurance test, then the endurance test samples were selected at a rate of one for 2500 rifles produced. This endurance test sampling rate was performed for five lots of 2500 rifles. If these next five rifles all passed the 6000 round endurance test then the endurance sampling rate was upped to one test rifle every 5000 rifles produced.

The 6000 round endurance test was conducted as follows. The rifle was fired first in semi-automatic for 100 rounds followed by five round bursts for another 100 rounds. Then five full magazines were each emptied in automatic with one pull of the trigger for each magazine. The magazines were rotated for even use and the rate of fire was measured during one of the twenty round bursts. The barrel was allowed to cool to ambient after each 100 rounds. The rifle was cleaned and lubricated every 1000 rounds. No cleaning of the gas system was allowed. This procedure was repeated until 6000 rounds had been fired.

Only a small number of any kind of failure was allowed in the 6000 round endurance test. The endurance test allowed no more than twelve malfunctions and no more than two unserviceable parts. The allowable malfunctions and associated instances were as follows: 1) bolt failed to lock into battery – three 2) bolt lock failed to hold the bolt open – one 3) cartridge case failed to eject – one 4) a cartridge that was visible failed to feed – four 5) a cartridge not visible failed to feed – three 5) failure to fire in semi-automatic – three 6) light primer strike – three and 7) punctured primer – one. If any one malfunction occurred more than the allowed number of times or if the total number of malfunctions was more than twelve, the rifle did not pass the endurance test.

No unserviceable parts were allowed in the first 3000 rounds. The allowable unserviceable parts and associated instances for the second 3000 rounds of testing were as follows: 1) ejector – one 2) ejector spring – one 3) extractor – one 4) extractor spring – one 5) firing pin – one. If any one part broke more than once or if there were more than two unserviceable parts, the rifle failed the endurance test. Some of the M14 rifles completed the 6000 round endurance with no malfunctions or unserviceable parts.

Ten M14 rifles selected by a U. S. government representative from each inspection lot were also tested for parts interchangeability. If more than one contractor was producing M14 rifles at the same time, each contractor submitted six specimens each month for parts interchangeability with parts made by the other contractor.

After completion of all firing tests, each bolt assembly was examined by magnetic particle inspection for cracks, seams and other injurious defects. If the bolt passed examination, the bolt was marked with the letter M. The bolt assembly was then cleaned, the roller repacked with grease and the rifle reassembled. Every rifle was given a final and

thorough visual examination before preservation and packaging. Sample M14 rifles were tested for cleanliness before packing and the packaging tested for vacuum retention.

M14 Production at Springfield Armory

The Springfield Armory was built during the American Revolutionary War. The plot of land it was situated on had been used since the 1600s to train colonial militia units. The site was established as an ammunition depot in 1777 by General George Washington. President George Washington selected Springfield Armory in 1789 to be the first government arsenal. Springfield Armory was officially established in 1794 by an Act of Congress. From 1794 to 1968 the Springfield Armory was the center of military small arms development and production in the United States. The armory tested and manufactured several muskets in the eighteenth and nineteenth centuries for the U. S. Army. It also produced the Krag-Jorgenson, M1903 and M1 Garand rifles prior to the M14 project. The Department of the Army announced plans to close Springfield Armory on November 19, 1964 and did so on April 30, 1968.

Springfield Technical Institute was established by the City of Springfield, Massachusetts in 1964. It operated under the jurisdiction of the City of Springfield, Massachusetts and the Commonwealth of Massachusetts Department of Health, Education and Welfare. Springfield Technical Institute later moved into three buildings inside the Springfield Armory during the summer of 1967 and began operating under the authority of the Commonwealth of Massachusetts Board of Community Colleges beginning in September 1967. The fifty-five acre site formerly known as the Springfield Armory was renamed Springfield Technical Community College in August 1968. The college continues to serve the people of the Commonwealth of Massachusetts to the present day.

The Springfield Armory National Historic Site was created by an Act of Congress in 1974 and opened in 1978 under the administration of the U. S. Department of Interior National Park Service. Twenty of the fifty-five acres of land were set aside for the National Historic Site. The Springfield Armory National Historic Site has two buildings, the Main Arsenal which is now the Museum, and the Commanding Officer's Quarters which are now National Park Service administrative offices. The Main Arsenal was built in 1850 and the Commanding Officer's Quarters built from 1845 to 1846. The Springfield Armory National Historic Site houses the largest firearms collection in the United States and the second largest in the world.

Springfield Armory was the first of four M14 rifle manufacturers for the U. S. government. It was tasked with setting up a pilot production line in April 1958. Startup of parts production began in December 1958. The first five parts made were the receiver, the bolt, the gas cylinder, the operating rod handle and the trigger housing. M14 production problems at the Armory included obtaining satisfactory precision castings for the flash suppressors, proper welding techniques for the operating rods, and achieving satisfactory heat treatment for the receivers. Except for TRW, USGI M14 operating rods were welded

together near the rear end of the cylindrical portion as specified by the drawing.

Springfield Armory made the least number of USGI M14 rifles, 167,107. The first M14 rifles were delivered to the U. S. Army in August 1959 by Springfield Armory. The serial number of the first rifle ever stamped M14 was 2000. M14 production orders were given on March 26, 1958, October 07, 1959, September 1960 and August 1961. Springfield Armory had 400 of 3100 employees involved with development and production of the M14 rifle in August 1961. Springfield Armory also made M14 NM rifles. During Fiscal Year 1964, Springfield Armory developed a dry fire device for the M14 rifle. It appears few, if any, of the rubber hammer bumpers were ever made.

Springfield Armory manufactured two M14 rifles for President Eisenhower in November 1959. Two rifles were made in case one was flawed. Both rifles were given a blued finish. As it turned out, close examination revealed M14 serial number D.D.E. 1 to be flawed but D.D.E. 2 was flawless. M14 serial number D.D.E. 2, with the selector lock, was presented to President Eisenhower. M14 serial number D.D.E. 1 was tested as an endurance test rifle then transferred to the Springfield Armory Museum on October 18, 1960 where it remains on public display. Springfield Armory made a number of other presentation grade M14 rifles in 1959 and 1960. These M14 rifles have four digit serial numbers starting with the numeral 0.

Springfield Armory Machine Tools - In 1968, some M14 project equipment was auctioned off. The remainder was shipped to Rock Island Arsenal for storage. One complete set of fixtures and inspection gages from Springfield Armory was sold to the Government of Taiwan for its T57 project. In 1994, Rock Island Arsenal auctioned off to the public a large quantity of M14 project equipment. The auction records were only kept for five years. This equipment had been used at Springfield Armory. The following describes some of the machine tools in use by Springfield Armory in August 1961:

1. The barrel installation machine screwed the barrel and receiver together with the exact prescribed torque in seconds.
2. Broaching machines were used for high speed removal of metal from the receiver forging.
3. A grinder was used to grind the rear faces of the M14 bolt lugs.
4. A special machine tool was made to make the receiver left bolt camming recess. This is the most difficult machining cut on the rifle.

M14 Production at Winchester

Oliver F. Winchester began his business venture into firearms in 1855. Eleven years later, he founded the Winchester Repeating Arms Company in New Haven, CT. He

manufactured the first successful repeating rifle in the world in 1866. By 1872, the firm began making ammunition. In 1931, Olin Industries purchased Winchester Repeating Arms Company and combined it with the Western Cartridge Company to form Winchester-Western. During World War II, Winchester-Western manufactured M1 Garand rifles. In 1954, Olin Industries and Mathieson Chemical Corporation merged to form the Olin Mathieson Chemical Corporation. Its name was simplified to Olin Corporation in 1969.

In 1981, the shotgun and rifle manufacturing operation was sold to U. S. Repeating Arms Company, Inc. U. S. Repeating Arms, a subsidiary of Herstal Group, continued the tradition of manufacturing quality shotguns and bolt and lever action rifles under a licensing agreement from the Olin Corporation until 2006. On March 29, 2006 the manufacture of Winchester brand firearms in New Haven, CT came to a halt after 140 years of operation. The U. S. Repeating Arms facility had been manufacturing Winchester Model 94 and Model 70 rifles and the Model 1300 shotgun. The Winchester named operation remains a leading manufacturer of small arms ammunition. The ammunition plants are located in East Alton, IL and Geelong, Australia.

On February 17, 1959, Winchester was the first of three commercial firms to be awarded a M14 rifle contract. Subsequent M14 contracts were awarded on November 30, 1960, April 13, 1962, and October 08, 1962. To win a second contract, the firm agreed to dedicate all of its manufacturing and assembly operations to manufacturing the M14. Winchester executives and officers from the U. S. Army Ordnance Corps held a dinner and ceremony on September 12, 1960 at its New Haven, CT plant in anticipation of a second M14 rifle contract. The guest list included U. S. Senator Prescott Bush (R - CT), U. S. Representatives Frank Kowalski (D - CT) and Robert N. Giaimo (D - CT), Mayor Richard C. Lee (New Haven, CT), Secretary of the Army Wilber M. Brucker, Brigadier General Oren E. Hurlburt (Commanding General, U. S. Army Ordnance Weapons Command), and state and local business leaders. The festivities included a firepower demonstration of the M14 rifle at the Blue Trail Range (Wallingford, CT). The shooting range demonstration was followed with presentation of a M14 rifle to General Hurlburt by W. Miller Hurley, Vice President of Olin Mathieson Chemical Corporation and General Manager of the Winchester-Western Division. A commemorative 8 3/4 " wide ash tray was made by T. R. Mintz Sales Co. (then 286 Blake Street New Haven, CT) for the dedication ceremony. Mr. Hurley was later interviewed by *Ordnance* magazine in 1961 regarding production of the M14 rifle for the U. S. Army. Sometime during its production, Winchester also had M14 playing cards printed up with an image of the M14 rifle on the front side of each Ace. The first Winchester M14 rifles were delivered to the U. S. Army in April 1961.

Winchester Machine Tools - Winchester designed special milling machines to make the M14 receivers and wood stocks. The company was delayed several months getting the bugs worked out of the receiver making machine tools but was successful in meeting its required monthly production rate by August 1961. The other three rifle manufacturers

formed their receivers by extensive broaching. Winchester had the most automated stock making machinery of the four manufacturers. It was successful from the beginning of operation. Winchester produced the second largest number of USGI M14 rifles, 356,501. The following describes three of more than 600 machine tools used by Winchester to produce the M14 rifle:

1. The barrel drilling installation consisted of eight machines of six spindles each for drilling barrel bores.
2. The Gorton straight-line transfer machine performed thirty-two high precision machining operations on the receiver automatically. This was a unique machine tool specifically made for M14 receiver production at Winchester. It was designed, manufactured, assembled, and tested by the George Gorton Machine Company (Racine, WI) between June 1959 and the spring of 1960. The Gorton transfer machine cost \$600,000.00. It took thirteen weeks to put together. Once assembled, Gorton personnel performed a test run of 1,000 receivers to ensure it worked properly. After it was assembled at the Winchester plant, another test of 1,000 receivers was planned to check for proper operation. Machine cycle time was 45 seconds or eighty receivers per hour. Machining operations performed by it included angular cutting, undercutting, horizontal and vertical milling, automatic duplicating, drilling and automatic profiling. Between the various metalworking operations, fourteen inspection gaging stations checked each work piece for proper dimensions. Each work piece measured 7 7/8 " x 1 11/16 " x 2 5/8 ". After machining, the semi-finished receiver weighed 1 pound 6 ounces. The Gorton transfer machine held dimensional tolerances to within 0.001 " of the specification and only took two employees to run.
3. The sixteen station stock inletting machine replaced sixteen single purpose woodworking machines in making wood stocks.

M14 Production at Harrington & Richardson

Harrington & Richardson Arms Company began manufacturing firearms in 1874 and produced double action revolvers as early as the 1880s. During World War I, the firm manufactured flare guns and sword scabbards for American troops fighting in Europe. Through the years Harrington & Richardson produced reliable and affordable rifles and revolvers. The company produced more than 400,000 M1 Garand rifles from 1952 to 1956 for the U. S. government. In 1964, along with Aircraft Armaments, Inc., Springfield Armory and Winchester, Harrington & Richardson submitted prototype Special Purpose Individual Weapon rifles to Aberdeen Proving Ground for evaluation. Harrington & Richardson M1 Garand rifles are sought after by collectors. The firm also manufactured and sold a product line of gun barrel drills. The company went out of business in 1986.

The main plant for Harrington & Richardson was located at Park Avenue and Chandler Street Worcester, MA 06109. In the early 1960s, it had three other manufacturing

facilities, Gardner and Rochdale, Massachusetts and Elm Grove, West Virginia. Four M14 parts were made at the Gardner location. The West Virginia operation opened in late 1962 to manufacture M14 operating rods. It initially employed up to fifty people.

Retired FBI Agent Leo Laughlin was hired in 1962 as President of the company. Harrie J. Rowe, Jr., Vice President and General Manager, managed the M14 rifle project from the Worcester plant. He was assisted by Wendell Phillips and Vern Brusseau, Chief Engineer for Harrington & Richardson Arms. Mr. Brusseau was in charge of sixty manufacturing engineers supporting M14 rifle production. The Harrington & Richardson Arms M14 receiver was produced by more than 300 employees at its Rochdale plant. The management team there included Ed George, Division Manager, Alfred Thiboeau, Chief Process Engineer, John Sullivan, Production Superintendent, Kenneth Thomas, Chief Inspector, and Donald Walker, Office Manager. The Worcester plant manufactured M14 barrels and was responsible for the assembly, inspection and testing of M14 rifles. Chromium plating of M14 barrels was performed at the Abbott Street facility in Worcester. Edward Flagg was the engineer in charge of the plating department.

Harrington & Richardson received its first M14 contract on April 29, 1959. Subsequent contracts were awarded on April 07, 1960, May 10, 1961, February 15, 1962 and October 12, 1962. The first Harrington & Richardson M14 rifles were delivered to the U. S. Army in December 1960. The company was shipping 20,000 M14 rifles per month in May 1961 to the U. S. Army. In the summer of 1961, the company ran two production shifts at the Worcester and Rochdale plants and one at the Gardner location. The delivery rate increased to 25,000 M14 rifles per month by the end of 1962 but had capacity to produce 40,000 per month. The rifle serial numbers was stamped on the receiver heel after final government inspection and approval of each production lot.

In August 1961 there were about 1,000 employees working on the M14 project at Harrington & Richardson. By 1963, there were over 1,500 employees involved with the M14 project company wide. There were 116 subcontractors to Harrington & Richardson Arms for the M14 rifle project. More than forty-five smaller companies supplied component parts for the M14 rifle. These subcontractors employed 6,000 personnel throughout sixteen states. Harrington & Richardson performed 289 operations, of which more than half were machining operations, to produce each M14 receiver. The company produced the largest number of USGI M14 rifles, 537,625. It returned the M14 rifle project documents and equipment to the U. S. government at some point before 1968.

H&R Machine Tools – Horizontal internal rifle broach cutting was a specialty of Harrington & Richardson, Inc. The following machine tools, among others, were in use at the Harrington & Richardson plant in August 1961:

1. The Cincinnati special milling machine was a multi-station mill for finish machining operations on the receiver.

2. The crush grinder was used to grind gas cylinder threads on the M14 barrel.
3. The Motch & Merryweather Machinery Company (Cleveland, OH) cutoff machine was used to cut and machine M14 bolt locks from roll formed bar stock.

Receiver and Bolt Failures – Two receivers, serial numbers 19478 and 19656, and four bolts from three manufacturers failed during range firing at Fort Benning, GA in December 1960. Later that month, receiver serial number 73293 fractured during proof firing at the Harrington & Richardson factory in Worcester, MA. The bolt in rifle serial number 73293 suffered abnormal peening on the bottom of the right hand lug and severe indentation on the face of the left lug. Receiver serial numbers 19478 and 73293 were made of incorrect material, AISI 1330 steel, instead of AISI 8620 steel. Receiver serial number 19478 was stamped Winchester but it was one of 850 M14 receivers Winchester had purchased from Harrington & Richardson for initial production. Receiver serial numbers 19478 and 73293 each failed completely in both sides just forward of the receiver lugs.

Subsequent testing of 554 Harrington & Richardson receivers in January 1961 found eight more made from AISI 1330 steel and one made of 4 % nickel alloy steel. The serial numbers of Harrington & Richardson M14 receivers found through testing to be made of AISI 1330 carbon steel were: 69121, 71244, 71927, 71974, 72929, 73761, 74238 and 74486. The high nickel alloy steel receiver serial number was 71408.

The use of the wrong material was an unintentional mishap on the part of Harrington & Richardson. When the receivers made of the incorrect steel were heat treated the result was unsafe. These AISI 1330 steel receivers were weak and brittle. The receivers made of the improper material were destroyed but Harrington & Richardson had to produce the contracted number of receivers. It is not known if the serial numbers from the defective receivers were reused or if new serial numbers were issued for the replacement receivers.

One of the four bolts to fail at Fort Benning was from rifle serial number 19453. It had a completely sheared right lug and a severely cracked left lug. The failed bolt was made by Textile Machine Works, a subcontractor to Harrington & Richardson. A thorough metallurgical investigation of the M14 bolt was performed by government, Ipsen Furnace Company and Armour Research Foundation metallurgists between January and May 1961. The failed bolt was cut into sections and examined using microscope photography. The major fault was the failure to strictly adhere to the written heat treatment procedure even though the correct steel was used. The procedure requires the bolts to be heated to a narrow temperature range then immediately cooled by oil immersion. If the bolts are not brought up to the required temperature or if they are allowed to cool before oil quenching, an excessive amount of free ferrite is formed. Ferrite is soft and weak iron. Ferrite does not bond with carbon atoms so the freed up carbon atoms moved into the rest of the bolt. This condition in the HRT bolt created a very hard and brittle martensite molecular structure. Under repeated impact loading from the rifle being shot, cracks

formed and grew in the lugs, resulting in catastrophic bolt failure.

A task force of about forty Army Ordnance Command representatives met on December 28 and 29, 1960 to determine the causes of failure and to implement a plan of action to prevent any more such failures. After the meeting, a combined team from Springfield Armory and Boston Ordnance District visited the following contractors and subcontractors to review M14 component manufacturing procedures and obtain samples for evaluation: Winchester in New Haven, the Rochdale and Worcester H&R plants, Storms Drop Forge, and Textile Machine Works. The following deficiencies were noted by the team:

- 1) M14 bolts at the Winchester plant were not quenched according to good engineering practice for 8620 steel. Additionally, there was no magnetic particle inspection of Winchester M14 bolts after proof firing.
- 2) Receivers that missed steps in the machining process were reworked by spot annealing and hand grinding at Harrington & Richardson.
- 3) Winchester was unable to meet the minimum core hardness limit for bolt heat treatment.
- 4) Textile Machine Works was unable to meet the maximum core hardness limit for bolt heat treatment.

Further, a Lackland Air Force Base report dated December 1960 revealed oversize chambers in H&R M14 barrels. The M14 barrel inspection gage measured chamber diameter at 0.5 " from the breech but the excessive diameter was located at 0.4 " from the breech. Thus, the oversized chamber in H&R M14 barrels had gone undetected. During testing of H&R M14 rifles with oversized barrel chambers in March 1961 at Aberdeen Proving Ground (MD), one early production Winchester bolt failed after 3,100 rounds in the cold room test due to excessive free ferrite.

Springfield Armory test rifle bolts which had gone thousands of rounds were examined for similarities and differences with the failed HRT bolt. The test rifle bolts demonstrated that minor cracks may start in the hardened surface but they do not grow through the bolt core if the heat treatment is correctly performed. Properly heat treated bolts were found generally to have less than 10 % free ferrite but the bolt from receiver serial number 19453 had as much as 50 % free ferrite. The end result was additional quality assurance provisions as required by Ordnance Weapons Command Engineering Order No. 164 released on January 11, 1961. This Engineering Order applied to the first and second Winchester contracts and the first Harrington & Richardson contract. These new requirements included a revised inspection procedure for the barrel, bolt and receiver, installation of new heat treatment equipment and a magnetic analyzer to check receiver material. The revised inspection procedure included two separate magnetic particle inspections of each receiver and bolt, before and after heat treatment. The magnetic

analyzer was developed by Springfield Armory with assistance from Watertown Arsenal.

On April 23, 1961, Ordnance Weapons Command issued instructions to Raritan Arsenal to inspect, segregate and reassemble approximately 35,000 Harrington & Richardson and 850 Winchester M14 rifles manufactured before the issuance of Engineering Order No. 164. The instructions required inspection of the barrels, bolts and receivers for compliance with material, hardness and dimension specifications. Springfield Armory provided technical assistance, training and inspection equipment for this work at Raritan Arsenal. The relevant portion of the May 08, 1961 Springfield Armory report is reproduced here:

“Regarding cracks in bolt locking lugs, numerous firing tests at Springfield Armory have proved minute cracks in bolt lugs do not cause early failure if metallurgical structure of bolts is correct and bolts and receivers are dimensionally correct.

On 23 April 1961, instructions were issued from Hq. OWC on the inspection criteria to be observed at Raritan Arsenal for the inspection segregation and reassembly of M14 rifles. The instructions are as follows:

After careful evaluation of available tests and performance data, and with due consideration to the urgent requirements for M14 rifles, the following are effective immediately:

(a) M14 bolts manufactured prior to the implementation of OWC EO 164 except HRT lots A01 and A1980, and those 850 OMCC bolts in weapons at Raritan Arsenal returned from the field are acceptable for immediate assembly provided the following 100 % reinspection is conducted:

- (1) Check for compliance with surface hardness requirements.
- (2) Inspect for cracks at lug area using 600 amperage on Magnaglow inspection. No cracks are permissible
- (3) Inspect for compliance with the 0.028 minus .008 radius and toll marks in lug area in 4 locations.
- (4) These bolts will not be used for repair parts.
- (5) All bolts in the above category will be marked or etched below the part number or serial number with a small identifiable star or asterisk.

(b) Receivers meeting all other contract requirements are 100% acceptable provided inspection is conducted to insure:

- (1) Compliance with specified surface hardness requirements.
- (2) That proper steel was used in manufacture as determined by use of a magnetic analysis comparator. Receivers exceeding plus 40 reading shall be rejected. Receivers exceeding minus 40 may be accepted but will be marked or etched with a small

identifiable star or asterisk.

(c) Dimensional requirements for both components remain unchanged.

(d) Boston Ordnance District was authorized to approve RDA's for bolts meeting the criteria previously stated.

(e) In addition, instructions have been established to accept oversized chambers in weapons at Raritan Arsenal up to .005["] maximum over the drawing tolerance."

Random sample USGI M14 bolts that had passed all required government inspection and testing measured 52 HRC (HRT marked bolt) and 54 HRC (TRW marked bolt) for surface hardness. Springfield Armory and Winchester carburized M14 bolts by the salt bath method whereas Textile Machine Works used the ammoniated gas method for bolt carburizing.

The bolt is the second hardest part to manufacture on the M14, the receiver being the most challenging. The drawing requirements for the M14 bolt were revised a lot as the M14 project developed. The bolt drawings were originally created in July 1958 and last revised in December 1992 (Revision Y). No other M14 rifle part drawing went through as many revisions.

Due to the bolt failures in late 1960, a lot of research was performed by the U. S. Army into the design and manufacturing process of the M14 bolt. There were bolt failures in five USGI M14 rifles: Harrington & Richardson serial number 73293, Springfield Armory serial number 19656, and Winchester serial numbers 19453, 19478 and 19391.

Three of these bolts had excessive free ferrite but two did not. As a result of the bolt failures, the U. S. Army inspected 33,808 bolts from rifles under serial number 90000. 26,848 of the 33,808 bolts were reused. The inspection tests done on the M14 bolts included magnetic permeability comparisons, measurement of basic magnetic properties, oscilloscope wave form pattern studies, hardness testing, and impact testing at ambient and cold temperatures. The 6,960 bolts pulled from service were due to: 1) surface hardness outside the specification 2) high temper or retemper 3) core hardness greater than 45 HRC 4) core hardness less than 35 HRC 5) core with excessive free ferrite or 6) other unfavorable conditions. The bolts tested had core hardness as high as 46 HRC and as low as 31 HRC. Within a single bolt, it was not unusual to have the core hardness vary up to 4 HRC. Surface hardness was usually within 1 HRC for any point sampled on a given bolt. The bolts sampled ranged from 52 to 62 HRC on the surface.

As of January 1962 (drawing F7790185 Revision H would have been in effect), the heat treat requirements for the M14 bolt were:

Surface - 54 to 59 HRC

Core - 35 to 42 HRC
Case depth - 0.015 " to 0.020 "
Temper temperature - 425 degrees F maximum
Core structure - 10 % free ferrite maximum

With the exception of the five failed bolts from USGI rifles under serial number 75000 and the 6,960 USGI bolts pulled from service, new manufacture USGI M14 bolts have been found acceptable for use by the U. S. Army. USGI M14 bolts made under the final set of heat treatment requirements (drawing F7790185 Revision L and later) were made by Winchester (rifles) and TRW (rifles and spare bolts).

The final heat treatment and hardness requirements for the USGI M14 bolt were established in November 1963:

1) Rockwell hardness readings shall be taken on the top surface of the locking lugs and at the vertical surface of the rear end.

2) Bolt material - 8620H alloy steel except resulphurized content at 0.035 % to 0.50 % that is gun quality specification per ASTM A304, A322, or A331. Hardenability of steel shall be controlled as required to suit manufacturer's heat treatment process and to assure that the specified mandatory physical properties are met. Austenitic grain size is 5 to 8.

3) Heat treatment recommended process - normalize before machining (oil quenching followed by tempering at not more than 450 degrees Fahrenheit may be used in lieu of air cooling). Carburize at 1550 degrees Fahrenheit to 1600 degrees Fahrenheit to the specified case depth. Without reheating, quench in oil or neutral salt bath from 1500 degrees Fahrenheit to 1600 degrees Fahrenheit. If reheated, quench from 1550 degrees Fahrenheit to 1600 degrees Fahrenheit. Temper to the specified hardness.

4) Heat treating mandatory requirements -

A. Normalize before machining.

B. Carburize to a case depth of 0.012 " to 0.018 ".

C. Temper for one hour minimum at 350 degrees Fahrenheit to 450 degrees Fahrenheit.

D. Core hardness is 33 HRC to 42 HRC. Surface hardness is 66 HRD to 71 HRD (54 HRC to 60 HRC).

E. Microstructure of the core shall not contain more than 10 % free ferrite after heat treatment per AMS 2315.

F. The use of a straight cyanide bath or carbonitriding shall not be permitted.

G. When gas carburizing is used the carbon content shall not exceed 0.84 % at the surface of the bolt per AMS 2762.

A 1961 Watertown Arsenal study of the M14 bolt found its tensile strength to vary, as expected, from 275,000 psi at the case hardened surface to 200,000 psi at the inner edge of the case depth to 138,000 psi in the core. The rear inside corner of the left lug is the point of maximum stress for the M14 bolt when a perfectly machined receiver is mated to a perfectly machined bolt.

The M14 bolt lugs are subject to shear stress when the operating rod pushes the bolt back against the receiver lugs. The bearing surface of the bolt lug and the radius of the inside corner of the rear side of each bolt lug influence the magnitude of stress experienced by the bolt. The rear side of the left bolt lug has a smaller bearing surface than the right side lug so it experiences a higher shear stress.

The sharper, or more perpendicular, the inside corner of the rear side is cut the more severe the stress on the bolt lug. Consequently, the USGI drawing F7790185 specifies a minimum radius of 0.028 " - 0.008 " for the inside corner on the rear side of both bolt lugs. This dimension is absolutely critical to limit the maximum shear stress on the bolt. For example, the Watertown Arsenal study indicates that the maximum shear stress at the left lug rear side inside corner would increase by 28 % (assuming full bearing surface contact) by changing the radius dimension from 0.020 " to 0.011 ".

M14 Production at TRW

Thompson-Ramo-Wooldridge, Inc. was the fourth and last of the USGI M14 rifle manufacturers. It is referred to as TRW throughout this work. The earliest origin of TRW was in the 1901 founding of the Cleveland Cap Screw Company. Cleveland Cap Screw made bicycle parts. Eventually, this business was renamed Thompson Products and expanded into manufacturing automobile and aircraft engine parts. In 1958, Thompson Products merged with Ramo-Wooldridge to form Thompson-Ramo-Wooldridge Corporation. Ramo-Wooldridge, Inc. was formed in Los Angeles, CA on September 16, 1953 by Dr. Simon Ramo and Dr. Dean Wooldridge. Ramo and Wooldridge were featured on the cover of the April 19, 1957 issue of *Time* magazine. Dr. Wooldridge retired in 1962 and went on to involve himself in the study of neurology. The five major business groups of TRW in 1962 were Automotive, Electro-Mechanical, Electronics, Space Technologies Laboratories and TRW International. The corporate name was changed to TRW, Inc. in 1965. Four years later, TRW sold off its Space Technology Laboratories group. This spin off enterprise was known as Bunker-Ramo. Simon Ramo was the President of Bunker-Ramo. By no later than 1970, the Systems Group (Redondo Beach, CA) worked on ordnance and automotive projects for TRW.

In 1999, there were two principal divisions, TRW Automotive and TRW Aerospace & Information Systems. The same year TRW Automotive bought the British aerospace and automotive parts manufacturer LucasVarity. In 2002, TRW employed 100,000 workers. In December of the same year, its defense business was purchased by Northrop Grumman. The automotive portion of the business became a separate company for a

short time but was then bought by The Blackstone Group. Goodrich Corporation took over the TRW aerospace business.

Management at TRW in 1961 decided to bid on the M14 rifle contract along with forty-one other firms. Orders for jet engines made at its Cleveland plant were in decline. TRW spent \$200,000.00 of its own funds in preparing the bid. TRW received its first M14 contract on October 02, 1961. TRW received \$6,500,000.00 for necessary machinery and equipment and \$8,500,000 for 100,000 rifles. The second M14 contract was let on October 08, 1962 and a M14 NM contract in Fiscal Year 1964. In late 1961 and the first half of 1962, its Jet & Ordnance Division plant (23555 Euclid Avenue Cleveland, OH 44117) was remodeled and set up for M14 production. This plant was known as the Ordnance Works of the Electro-Mechanical Group within TRW. Until August 1963, its director was William H. Goldbach. In October 1962, J. Wright was the Chairman of the Board at TRW. TRW intentionally underbid on its sales price to the government, \$72.00 and \$80.00 per rifle for its first and second contracts. Management at the Jet & Ordnance Division correctly anticipated that the experimental SPIW would be not fielded in the hope the firm would secure additional M14 contracts. By the end of its second contract, TRW was making a profit on each rifle. Unfortunately for TRW and the M14, the M16 was quickly adopted in place of the SPIW. Thus, follow on contracts never materialized except for one production run of 1,235 M14 NM rifles. Government contract production of M14 rifles ended at TRW in July 1964. TRW manufactured the third largest number of USGI M14 rifles, 314,789. TRW went on to be awarded a U. S. government contract in Fiscal Year 1966 for M79 grenade launchers and M14 bolts and gas cylinders in Fiscal Years 1968 and 1971. Some of the TRW M14 manufacturing operation is briefly described.

The principal stages of TRW M14 receiver manufacture were: 1) steel slug cut off from bar stock 2) drop forging after warm size 3) chain broaching and qualification broaching 4) machining through three dimensional mills 5) additional broaching and 6) phosphate coating.

The principal stages of TRW M14 bolt manufacture were: 1) cut off steel slug 2) extrusion 3) warm-coining 4) thirty machining operations on the Krueger lateral transfer machine 5) ten machining operations on two five station special milling machines and 6) phosphate coating.

The principal stages of TRW M14 operating rod manufacture were: 1) cut off steel slug 2) bump up and roll 3) warm sizing 4) finish machining and 5) phosphate coating.

TRW Machine Tools - The following describes some of the machine tools in use by TRW in November 1962:

1. The Allen multi-station drilling machine drilled all the small holes in the receiver.

2. The bolt assembly fixture completely assembled the bolt except for the roller.
3. The Colonial fifteen station pull-type broach cut the receiver magazine slot.
4. The Footburt 144 " chain broach was used for the first stage in receiver machining.
5. The Krueger lateral transfer machine performed thirty machining operations on two bolts at the same time including precision boring, reaming, gun drilling, hollow milling, and automatic gauging and inspection.
6. The Seneca Falls tracer lathe completed barrel exterior contour turning in two passes.

The TRW Mystique

TRW rifles and parts have a long-standing reputation as better made than those from the other three M14 manufacturers. This was obvious as early as late 1962 from facts described below. The first TRW rifles were delivered in October 1962, one month ahead of schedule. TRW's production record and the quality of its rifles brought enthusiastic praise from the Department of Defense and from the press.

TRW was ahead of Winchester and Harrington & Richardson in a number of ways. Because of its background, TRW had a broader and more sophisticated production experience. TRW considered itself to be highly skilled in the manufacturing techniques of precision forging and chain broaching. Because of its jet engine work, TRW possessed state-of-the-art knowledge of metallurgy and heat treatment. The company was adept at making small batches of custom order aircraft parts.

This knowledge and manufacturing flexibility served TRW well when setting up the M14 project. TRW made only eleven parts during its M14 rifle production. Those parts (receiver, trigger housing, hammer, bolt, operating rod, barrel, rear sight base, connector, gas piston, gas cylinder, and flash suppressor) amounted to less than 65 % of the cost to the government. Only the first six parts in the list were marked TRW. TRW manufactured firing mechanism safeties which were likely replacement parts made after rifle production.

In 1962, Stanley C. Pace was the Electro-Mechanical Group Vice President for TRW. Mr. Pace was a Class of 1943 West Point graduate, World War II bomber pilot and Prisoner of War. After the war, he rose to the rank of Colonel in the U. S. Air Force. He left the Air Force in 1954 to join Thompson Products in Los Angeles, CA. He demonstrated superb leadership and management skills at TRW. Consequently, he was transferred to the TRW Jet Engine plant in Cleveland, OH to turn around that struggling facility. Mr. Pace went on to concurrently manage both the Electro-Mechanical and Space Technologies Laboratories Groups. By no later than 1979, he was President of TRW. He was set to retire in 1985 but was persuaded to take the helm as Chairman and Chief Executive Officer at General Dynamics Corporation which suffered from a poor reputation at the

time. Under his leadership including establishment of uncompromising ethical standards, General Dynamics reestablished itself as an ethical defense contractor and expanded its line of defense products. Mr. Pace eventually retired. In 2001, he was honored by the Association of Graduates at the United States Military Academy with the Distinguished Graduate Award for his lifetime of service.

The expertise of TRW is borne out by the 1962 *American Rifleman* interview of Stanley C. Pace. Mr. Pace explained how TRW applied its jet engine manufacturing experience to the production of M14 rifles. TRW settled on making what parts it could make economically well (based on its expertise), and subcontracted out the remaining parts which were easily manufactured from conventional methods. TRW machined single piece operating rods from forgings. Barrel interiors were formed by German design hammer forging. Barrel exterior contours were formed in two turning passes by using a Seneca Falls tracer lathe. The Seneca Falls tracer lathe replaced six conventional machine tools. The same barrel operation required four turning passes at Winchester. The TRW automatic barrel installation machine was similar to the other makers but it had some changes based on the experiences of the other manufacturers. As previously mentioned, TRW receivers gave about 6 % longer service life than others. TRW did assemble, test and ship all completed M14 rifles stamped with its logo on the receiver heel. Later on, TRW became the only commercial contractor to ever produce the USGI M14 NM rifle.

The M14 failure rate was 5 % to 12 % from all causes among Springfield Armory, Winchester and Harrington & Richardson as of August 1961. TRW had assembled and tested its first M14 rifle on August 23, 1962, three months ahead of the contract schedule. By November 1962 TRW M14 production was 100 per day and it had no rejections to date. The largest five shot group of any TRW rifle up to November 1962 was 5.5 " out of a maximum allowable 6.1 " at 100 meters. The average five shot group size for TRW rifles until November 1962 was 2.5 " to 3.0 " in factory testing. The M14 NM contract was completed and the rifles delivered to the U. S. Army in time for the 1964 National Matches at Camp Perry.

The Department of Defense Project Manager's weekly action report for the second week of February 1965 stated the following:

Marine Corp units in Hawaii submitted Equipment Improvement Reports pertaining to surface defects noted in M14 Rifles manufactured by Thompson Ramo Woolridge [sic]. Similar defects were noted in rifles in the 25th Infantry Division. Sample rifles were flown to WECOM for preliminary inspection and tests, and were subsequently flown to Springfield Armory for thorough evaluation. Investigation to date indicates that there is no unsafe condition, only surface roughness, and there are no known barrel failures. Records of manufacturing inspections reveal that there was some surface etching of barrels being used by TRW, and that after adequate special testing, the barrels were accepted for

production. Interim reports of findings have been made to the Marine Corps and a final report of findings by Springfield Armory, expected late next week, will be promptly forwarded to the Marines. Rifles in question have been suspended from firing pending outcome of the investigation. General Greene has reportedly indicated a feeling that this matter should be treated as sensitive.

With few exceptions, all four manufacturers were required to use the same material and meet the same specifications in making M14 rifles. Known exceptions include some early production chromium-molybdenum-vanadium alloy steel barrels and some Harrington & Richardson operating rods made from AISI 8655 alloy steel. One such Harrington & Richardson operating rod was sampled for hardness in 1995. It measured 32 HRC. The TRW mystique was further strengthened by the growing pains suffered by Winchester and Harrington & Richardson in 1960 and 1961. Overall, it is fair to say that TRW had the most trouble-free production record of the four manufacturers. Sometimes it pays to be last but it always pays to plan well and learn from others.

In a last hurrah for its involvement with small arms programs, the TRW Systems Group (Redondo Beach, CA) was awarded a contract in February 1971 by the Defense Advanced Research Project Agency and the U. S. Army Small Arms Systems Agency to develop the Low Maintenance Rifle (LMR). Designed by TRW employee Don Stoehr, the LMR consisted of a 5.56 mm caliber gas operated roller-locked bolt automatic firing only rifle that used M16 magazines fed from the left hand side. The rifle featured a 19.4 " barrel, a pistol grip for the firing hand, a M60 machine gun trigger mechanism, 300 meter and 500 meter flip-up rear sight apertures, and a post front sight. An adjustment tool was needed to zero the front sight. The LMR was designed to accept a detachable light, M2 bipod or M6 bayonet. The TRW LMR weighed 8.0 pounds with a loaded magazine and had an overall length of 34.25 ". It was made from corrosion resistant materials and had dry lubricant surface finishes that minimized the need for cleaning. No tools were necessary for disassembly or assembly. The TRW LMR fired from an open bolt at a cyclic rate of 450 rounds per minute. TRW had completed its development on the LMR by March 1973 with a number of sample rifles delivered to the U. S. Army for evaluation. Funding for the LMR ceased in 1973 because American involvement in southeast Asia had ended and the Army was satisfied with the M16A1 by that point.

Raritan Arsenal

Some changes in the design of the M14 rifle occurred after the earliest rifles had been shipped to the Army. This included adoption of a slotted fiberglass hand guard and hinged steel butt plate and altering the upper butt plate screw in 1960. The earliest production M14 rifles were inspected and reworked as needed, and modified to incorporate the latest changes. These changes were published as Modification Work Orders issued by the U. S. Army Ordnance Command. This work was being done at Raritan Arsenal (Metuchen, NJ) as of August 1961. Raritan Arsenal also had the responsibility of managing the inventory of small arms training aids until it was

decommissioned by the U. S. Army in 1963.

Experimental Items for the USGI M14 Rifle

M14 Simulator Rifle - Harrington & Richardson, Inc. developed and produced the Simulator, M14, .22 Caliber Mark 1 select fire rifle in 1959. The blowback-operated M14 Simulator weighed 8.7 pounds and was 44 " long with a 22 " barrel. The cyclic rate of fire was 780 rounds per minute and muzzle velocity was 1,100 feet per second. The Simulator rifle was fed from a ten round .22LR caliber box magazine inserted into an empty M14 magazine body. It was based on the Harrington & Richardson Reising Model 65 semi-automatic .22 LR rifle. Mr. Eugene G. Reising, an employee of Harrington & Richardson, invented many firearms including the Model 50 submachine gun. Harrington & Richardson took this project on because of a conversation in March 1959 with Dr. Frederick H. Carten, Chief of Small Arms Research and Development in the U. S. Army Ordnance Corps.

The purpose of the M14 Simulator rifle was to provide an economical training rifle to complement the M14. Harrington & Richardson employee, Les Mulno, had finished building the M14 Simulator by May 1959. One of the M14 Simulator rifles was submitted to Springfield Armory in December 1959 for evaluation purposes. Rifle serial numbers X-26 and X-31 were semi-automatic operation only. The serial number for one of the select fire models was XX1. Harrington & Richardson kept a small number of M14 Simulator rifles until 1986 when they were auctioned off due to going out of business.

M14 Trainer Rifle - The only officially adopted .22 caliber rifle for the M14 rifle was the Harrington & Richardson, Inc. MC-58. Like the M14 Simulator above, it was a modified Model 65. It included a trigger guard safety similar to the M14. The MC-58 rifles were marked on the barrel USMC PROPERTY, MODEL MC-58 or U.S. PROPERTY MODEL MC-58. About 3,500 MC-58 rifles were produced in the late 1950s.

Remington Arms Company built one prototype .22 LR caliber M14 training rifle on a Nylon 66 action. It had a 25 " barrel, M14 front and rear sights and flash suppressor, and a functional bolt lock. The two halves of the caramel color fiberglass stock were held together by ten bolts. The factory-built magazine had an oversized black plastic body to simulate the size of a M14 magazine.

Winter Triggers - Martin H. Colley patented his winter trigger for the M1 Garand rifle in 1952. It was tested by the U. S. Army on the T44 in 1953 and 1954 at Big Delta, Alaska. There were at least two winter trigger devices specifically designed for the T44E4, one made by Mathewson Tool Company and the other crafted at Springfield Armory. Mathewson Tool Company experimented with the Eugene Bourquin patented trigger actuator as a winter trigger. Mr. Bourquin had designed his trigger actuator for rifles fitted with grenade launchers. Springfield Armory had developed the T6 Auxiliary Winter Trigger for the T44E4 by no later than June 1955.

Picatinny Arsenal (Morris County, NJ) designed a winter trigger with safety for the M14 in 1959. The Picatinny Arsenal winter trigger was adapted for the M14 based on the patented design of Andrew J. Marhefka and Irving L. Kintish. When adopted in September 1960 as the M5, the production winter trigger kit included a winter safety.

In 1962, Springfield Armory employee Giulio Savioli designed two M14 rifle auxiliary triggers for use with cold weather mittens. The same year, he invented an improved bolt lock for the M14 rifle. His design provided more positive retention of the open bolt with the magazine removed. The bolt could be released by tapping the bolt lock. These designs were patented in 1963 and 1964. The XM152 winter trigger was developed for the M14A1. It was tested in the Arctic in 1965. The XM152 still retained its experimental designation as of July 2006 as an item in the Equipment List of the M14A1 Technical Data Package. Mr. Savioli also designed a M14 combination tool based on the M3A1 tool used for the M1 Garand. Two of the experimental combination tools were made and submitted to the Army Infantry Board. The experimental combination tool was not accepted because it was deemed too complicated for field use.

There was at least one other experimental design T44 series rifle cartridge clip guide made aside from the T44E6 aluminum cartridge clip guide. In 1961, Springfield Armory produced an extended bolt lock (Springfield Armory part number 27907) for the M14 rifle but it was not approved for use by the U. S. Army.

Magazine Loading Devices - In the mid-1950s, several magazine charging devices were experimented with for the T44 series rifles. These included various wire frame chargers and a semi-expendable magazine classified as the T16 magazine charger. At least two 10 round frame charger designs were patented in the 1950s for the T44/M14. The ten round cartridge clips were found unsatisfactory due to twisting and bending when loading a magazine through the top of the receiver. By 1958, a five round modified Mauser K98 design cartridge clip (stripper clip) had been developed, tested and adopted for the M14. The force necessary to strip a cartridge from either end of a fully loaded cartridge clip was required to be not less than 1.8 pounds and no more than 4.7 pounds. The early version M14 magazine filler was also developed at the same time.

Magazines - Two hundred aluminum M14 magazines were produced by Mathewson Tool Company and tested by Springfield Armory in 1962. Whether or not they were made by Mathewson Tool Company, some aluminum M14 magazines did get issued in the 1960s. These aluminum magazines had an anodized finish. They varied from the steel production magazines in that the seam of the front side is reversed and there is only one weld "dimple" on the latch plate. An aluminum M14 magazine weighs approximately 4.25 ounces as compared to 8.25 to 9.00 ounces for the standard (carbon steel) twenty round M14 magazine.

Springfield Armory assembled some T44E4 stocks with experimental aluminum butt plates with a bright metal upper screw. Springfield Armory produced some mostly plastic

twenty round M14 magazines that had a small “fence” of sheet metal at the top end to which the plastic body was molded. The plastic M14 magazines were made in an attempt to reduce cost. The experimental plastic M14 magazines did not hold up well in testing and were thus discarded. Springfield Armory experimented with black, brown, gray, olive drab, tan and white colored stocks in the first half of the 1960s during development of the synthetic M14 stock. The Armory created a M14 front band with an integral sling swivel at its bottom edge. Rock Island Arsenal designed and made an XM21 experimental two point scope mount in 1970.

The U. S. Army experimented in the second half of the 1960s and the early 1970s with twenty round plastic magazines for the M16 and M14 rifles in the Expendable Magazine Project. At least some of the plastic M14 magazines were sent to Fort Benning by November 1972. Two credible eyewitnesses, both U. S. Army veterans who carried the M14 rifle in the Republic of Viet Nam, report seeing or using USGI thirty round M14 magazines issued to them or other soldiers in their units while in the Republic of Viet Nam. One veteran was a member of the 2nd Battalion 8th Cavalry Regiment 1st Cavalry Division and the other was assigned to the 2nd Battalion 94th Field Artillery 108th Artillery Group. Some disposable plastic pre-filled thirty round M14 magazines were reportedly made and tested by Rock Island Arsenal in the early 1970s as part of this project but this has not been confirmed.

Dr. Carten became Chief of Small Arms Research and Development in August 1953 when Colonel Rene Studler retired from the U. S. Army. Dr. Carten watched over the T44 project at Springfield Armory. He became the Chief of Technical Evaluation Branch for the Research Development & Equipment Directorate when the Army Materiel Command was formed in August 1962 and remained there until at least 1970. Dr. Carten used his position and influence to delay adoption of a smaller caliber cartridge by several years within the U. S. Army. He was a firm believer in the suitability of the 7.62 x 51 mm NATO cartridge for military purposes.

Iron night sights - The design of a night sight for the M1 and M14 rifles was developed by Jack F. Kettler of Fort Leavenworth, KS by no later than May 1959. Springfield Armory referred to this weapon night sight as multilite sights.

The multilite sights consisted of two flip-up metal posts, one just aft of the front sight and one just forward of the rear sight. Each flip-up post was made integral to its standard iron sight counterpart. Both flip-up posts contained two sighting elements, one luminous and the other highly reflective. From no light to half-moon light, the luminous elements provided sufficient light for aiming. The reflective points were used for aiming the rifle in low light conditions better than half-moon light. The Kettler patent suggested either steel or plastic material for the structural portions of the multilite sights, commercial grade radium-activated phosphorus compound for the front and rear luminous elements and plated or stainless steel spheres for the highly reflective elements.

The luminescent sight material actually used in the multilite sights was promethium-147. Promethium is number sixty-one on the periodic table of elements. It is classified as a rare earth element and is produced from nuclear fission. It is radioactive. One isotope, promethium-147, can be made phosphorescent. Promethium-147 has a half-life of 2.64 years. It has been used in analog dial watches and in early M16A1 rifle sights. The promethium-147 was captured in ceramic microspheres and sealed with phosphor inside glass ampoules for the M16A1.

Using prototype sights supplied by the Infantry School at Fort Benning, Springfield Armory designed and fabricated in late 1959, two versions of weapon night sights. In 1960, these sights were tested on the M14 rifle in the field at Fort Benning and in Alaska. Barrel heat created from firing caused the luminescent material to loosen from the night sight posts during the testing at Fort Benning. The adhesive employed for attaching the luminescent material to the sight posts did not last at elevated temperature. Arctic testing of the night sights revealed cracks in the luminescent sight material after ten minutes of sustained firing.

Subsequent to this, Springfield Armory improved the design of the experimental M14 rifle night sight. The improved design resulted in use of an appropriate adhesive to secure the luminescent material to the night sight posts. The newer design also allowed the night sights to be zeroed at a distance of 100 to 150 yards by first zeroing the standard iron sights at the same distance.

Reflex-Collimator Optical Sight - More than 102,000 M1 Garand rifles were exported by the U. S. government through military assistance programs to the Republic of Viet Nam. The M1 rifles were issued to local Civilian Irregular Defense Group (CIDG) units in the Republic of Viet Nam. Among many other duties, U. S. Army Special Forces advisors trained CIDG troops in the use and care of the M1 rifles. By no later than February 1965, the U. S. Army Test and Evaluation Command (Aberdeen Proving Ground, MD) was aware that the Special Forces advisors had difficulty teaching CIDG personnel how to use the M1 rifle sights. Consequently, the U. S. Army Limited Warfare Laboratory developed a reflex-collimator optical sight that would replace the issue iron sights on the M1 and M14 rifles for short and medium distance shooting.

The Limited Warfare Laboratory reflex-collimator optical sight consisted of horizontal and vertical cross hairs inside a sighting tube mounted to the rear sight pocket of the rifle. The advantages were ease of training and operation and much less weight and bulk than a traditional rifle telescope sight. The Limited Warfare Laboratory had published a set of operating and maintenance instructions for this sight in November 1965. Nine reflex-collimator optical sights, eight of the original design and one of an improved design, were tested at Aberdeen Proving Ground from January 24 to June 14, 1966. The original design sights were installed on M1 and M14 rifles. The optical sights were then put through a gauntlet of tests totalling 1,559 rounds fired per rifle - accuracy, protracted firing, cold weather, hot weather and water spray. The accuracy tests compared the shot

dispersion using the reflex-collimator sight at 50 meters, 250 meters and 500 meters. The same accuracy test was repeated with the same shooter using issue iron sights. The reflex-collimator optical sight produced a 40 % greater dispersion of shot placement than the issue iron sights. The reflex-collimator optical sights were lacking in durability. All nine of the sights had cracked or loosened parts caused by the shock of firing the rifle. The sights also exhibited significant parallax. Parallax is where the sight aiming reference point, e.g., cross hairs or red dot, seems to move away from the target when the shooter changes his cheek weld. For these reasons, there was no further development of the idea by Aberdeen Proving Ground.

The Farrand Optical Company (Bronx, NY) developed a collimated sight in 1967 for the M14 rifle. The sight attached to the left side of the M14 receiver while retaining the issue iron sights. Presumably, this sight was intended for military use. Although the U. S. Army project did not produce a viable firearms optical sight, the dot sight concept was developed for commercial use by Aimpoint AB (Sweden) in 1973. First used by game hunters, firearm reflex dot sights have been in use by military forces since the mid-1980s.

In 1971, AAI Corporation (Baltimore, MD) developed a camera system for the M14 rifle. It was used in the testing of tracer ammunition the spring of that year at Fort Benning, GA. Three M14 rifles were outfitted with this camera system for this testing conducted by the U. S. Army Human Engineering Laboratory (Aberdeen Proving Ground, MD). The purpose of the gun-camera system, known as the Miss Distance Indicator (MDI), was to photograph where a projectile hit down range so that the distance and direction from the shooter's point of aim could be measured.

The MDI consisted of a stripped Minolta model 16MGS camera housed inside an aluminum box suspended from the barrel between the gas cylinder plug and the front sight. The Minolta camera was modified by adding a 75 mm lens, a cross hair reticle and a spring to counter the effects of recoil. The MDI weighed about 14 ounces and used 16 mm film. The shutter speed was set at 1/500 of a second. The F-stop (focal length divided by the lens diameter) had settings of F/8, F/11 or F/16. The camera was aligned with the rifle bore. The camera was operated by movement of an actuating rod mounted to the left side of the stock. The actuating rod was secured to the stock by brackets and a lever mounted under the bolt lock. When the rifleman pulled the trigger, the lever moved the rod forward depressing the shutter button. The camera took a photograph of the target area about 2 milliseconds before the hammer struck the firing pin. The film then advanced to the next frame in preparation for the next shot to be fired. Using the photographs, the miss distance and direction of each round was estimated by mathematical procedure. Unfortunately, the MDI system experienced two significant problems. The 75 mm lens created a focal length (distance from the film to the camera lens) too short making it hard to detect the 300 meter and 500 meter targets in the photographs. The MDI was not stable. In more than half of the shots fired, the camera moved in relation to the bore.

The effort to develop a lighter and shorter version of the M14 began in the summer of 1961. Laotian government troops fighting the Pathet Lao in that nation's civil war had difficulty handling full size U. S. made battle rifles. This military need was the impetus for Harrington & Richardson Arms to develop, build, and test several prototype M14 rifles known as "Guerilla guns." The project was headed by Donald L. Hennan at the company's Worcester, MA plant.

The Guerilla gun had a combination perforated conical flash suppressor and gas cylinder secured to the rifle by the flash suppressor nut and setscrew. Its barrel was a USGI M14 chromium plated barrel shortened to 15.5 ". The flash suppressor reduced felt recoil by more than 12 percent. The exterior contour of the barrel chamber was turned down and the receiver was further machined to remove as much steel as possible. The Guerilla gun project had reached an intermediate stage of development by December 1962. By then, the Guerilla gun was 2 pounds lighter and 5.5 " shorter than the M14 rifle. The weight of the Guerilla barrel and flash suppressor assembly was 2.6 pounds and the overall length was 20.5 ". Earl N. Sample, head of research and development at Harrington & Richardson Arms, Donald Hennan, and David L. Hall, weapons designer at Harrington & Richardson Arms, were working on reducing overall weight of the Guerilla gun by an additional 1.5 pounds.

David Hall fired a Guerilla gun for accuracy. It grouped 8 " at 250 yards. The Guerilla gun was considered combat effective out to 300 yards, sufficient for the jungles of southeast Asia. Its manufacturing cost was expected to be more than a M14 rifle due to additional machining operations. The Guerilla gun was tested and demonstrated at more than a dozen military bases by December 1962 but no contracts were awarded for it. The Guerilla gun gas cylinder had a dovetail base welded to it for mounting the front sight. Except for the barrel, flash suppressor and gas cylinder, Guerilla gun parts were interchangeable with the M14 rifle.

The Guerilla guns and other experimental M14 type rifles had serial numbers beginning with the letter X. The M14 Guerilla rifle was never adopted by the U. S. Army. At least two M14 Guerilla rifles, X-42 and X-45, were submitted to Springfield Armory in the second half of 1962 and subsequently transferred to the Springfield Armory Historical Museum on January 07, 1965. Springfield Armory tested this M14 Guerilla rifle for flash suppression in January 1963. M14 Guerilla rifle serial number X-40 was fitted with a custom made prototype Harrington & Richardson underfolding stock. Harrington & Richardson R14 serial number X-81 and M14 serial number X-40 were made with lightening cuts on the bottom of the receiver. R14 serial numbers X-81 and X-82 were made without any provision for mounting a scope.

Harrington & Richardson kept a number of the M14 Guerilla rifles until auctioned off in 1986 at the close of operations. One two digit X series serial number Harrington & Richardson Guerilla rifle, X-35, was also fitted with an underside folding stock but appears to be an M14E1 Type III folding stock. The receiver of this rifle

has no scope mount boss or threaded bolt hole.

Harrington & Richardson developed a 7.62 mm NATO caliber rifle that was a hybrid between the M14 rifle and a Reising submachine gun style receiver. It weighed 8.9 pounds and had an overall length of about 41 ". Only one copy is known to exist, serial number X26. It was fitted with a modified M14 slotted fiberglass hand guard. This rifle was likely created between 1960 and 1962. The 7.62 mm NATO Reising uses the M14 gas cylinder, M14 magazine, M14 butt plate, a modified M14 flash suppressor, and a 20 " M14 modified barrel. However, the receiver, firing mechanism, select fire components and the operating rod were of totally different design from the M14.

The U. S. Army Marksmanship Training Unit (USAMTU) was created on March 01, 1956 by direction of President Eisenhower. The unit was formed to raise marksmanship proficiency in the U. S. Army. Sometime between 1966 and 1970, the U. S. Army Marksmanship Training Unit came up with the idea of adding a rear lug to the M14 receiver as part of their effort to improve the accuracy of the M14 rifle. A U-shaped piece of steel, known as a lug, was welded onto the receiver underneath the heel. The stock was inletted and drilled to accept the lug and screw. A hex head screw secured the lug to the stock through its underside when the rifle was assembled. The U. S. Army Weapons Command at Rock Island Arsenal did not accept this modification out of concern from the effects of welding the receiver. Nonetheless, M1 Garand rifles with welded rear receiver lugs appeared at Camp Perry as early as 1968. M14 rifles with welded rear receiver lugs were shot competitively at Camp Perry shortly thereafter.

The U. S. AMTU also experimented with gas cylinders, operating rod guides, operating rods, and operating rod spring guides for the M14 rifle. The experimental operating rod spring guides included prototypes with hollow shafts, conical shafts and a pivoting magazine catch. One experimental operating rod spring guide was about one-half inch longer than the nominal length. It worked very well in competition matches but it was difficult to install and remove for maintenance.

Other experimental AMTU items included sleeves inserted into the operating rod guide to help dampen the vibration from the movement of the operating rod. Due to drawing tolerances, the outside diameter of the operating rod can be as much as 0.012 " less than the inside diameter of the operating rod hole in the operating rod guide. The looser the fit between the two parts, the more the operating rod moves up and down as it travels back and forth. Another short-lived modification was the machining of a U-shaped cut at six o'clock on the rear opening of the cylindrical portion of the operating rod.

TRW altered at least two M14 flash suppressors into a design very similar to the T37 open prong flash hider used on M1 Garand rifles. These experimental tool room TRW M14 flash suppressors were available in the surplus market in November 1972. TRW also fabricated a mock up Special Purpose Individual Weapon (SPIW) that was built around a modified M14 receiver using SPIW cartridges. The TRW mock up SPIW

included an integral 40 mm grenade launcher that held three grenades. The SPIW magazine and grenade launcher subassembly were made from wood. The butt stock had a telescoping pad. The rear end of the receiver was fitted with a folding leaf sight and there was a pronged flash suppressor. The TRW mock up was sold at a January 1974 Ohio gun show to a private individual from Michigan.

The Issue M14 Rifle

Factory Packaging - After final testing at the factory, each M14 rifle was disassembled, cleaned, dried, lubricated and assembled according to government packaging specifications. M14 rifles were lubricated by completely dipping in lubricating oil since that was the most economical means. Originally, a sling was not included with each rifle. At some point before 1980, the packaging requirements were changed to include placing a small arms sling inside a heat-sealed bag for each of the two rifles inside the shipping box. Each rifle had a volatile corrosion inhibitor tube placed in the bore with the front of the tube bent around the muzzle to hook it into place. White polyethylene protectors for the front sight and muzzle, rear sight, and operating rod handle were placed on each rifle. A white plastic indicator placed in the chamber signified the rifle was empty of ammunition. Each M14 was then placed in a volatile corrosion inhibitor treated bag, the excess air squeezed out and the open end of the bag heat-sealed. The end of the bag was folded over the butt end of the rifle. Additionally, every shipping box contained ten in-the-wrap twenty round M14 magazines and two Basic Initial Issue (BII) kits if it contained two M14 rifles. A shipping box either contained two M14, two M14 M, two M14 NM, one M21, or one M14A1 rifle. The BII kit contained the following items: four M3 cleaning rod sections, cleaning rod carrying case, lubricant case, patch tip, bore brush, chamber brush and combination tool. Prior to 1980, the packaging instructions were revised to remove the BII kits. The packaging instructions specified thirty shipping boxes per shipping container. Each shipping container was required to have a packing list that contained the serial numbers of the rifles contained inside.

There was an exception to the standard M14 BII list of items. BII kits made up at Letterkenny Army Depot (PA) in 1968 included the selector switch and selector spring. These special M14A1 BII kits, along with some M14, M1 Garand, and M16 BII kits, were placed into M79 grenade launcher accessory pouches. These BII kits were to be shipped to the Army of the Republic of Viet Nam. About 2400 of these kits were never shipped but released as surplus to the public in 1979. Letterkenny Army Depot packaged numerous small lots of small ordnance parts during the Viet Nam War due to its well-deserved performance in such projects.

USGI M14 Rifle Costs - As of June 2007, the U. S. government unit price for each of the various M14 rifle models was as follows:

M14 JROTC (NSN 1005-00-283-7695) - \$97.35

M14 M with equipment (NSN 1005-00-678-9829) - \$128.00

M14 with equipment (NSN 1005-00-589-1271) - \$138.00
M14 Honor Guard Semi (NSN 1005-01-494-4169) - \$138.00
M14A1 with equipment (NSN 1005-00-072-5011) - \$206.00
M14 NM (NSN 1005-00-678-9828) - \$316.00
M14 SMUD (NSN 1005-01-255-3311) - \$579.00
M14 DMR (NSN 1005-01-458-6235) - \$1495.00
XM21 and M21 (NSN 1005-00-179-0300) - \$1278.00
Mk 14 Mod 0 (NSN 1005-01-525-7718) - \$2400.00
Mk 14 Mod 0 (NSN 1005-01-531-7324) - \$3361.30

The M39 EMR (NSN 1005-01-553-5196) unit price in October 2008 was \$3,930.17.

Receiving the M14 - When the new-in-box M14 rifles were received by the Army and Marine Corps, oil was present in the gas cylinders because of the factory lubrication. Thus, the U. S. Marine Corps issued Technical Instruction TI-02648A-15/6 to deal with the problem. This Technical Instruction references U. S. Army TM 9-1005-223-12 which requires that each M14 rifle to be field stripped, cleaned, and lubricated prior to firing. The gas cylinder, gas piston and gas cylinder plug should be thoroughly cleaned and dried the first time the rifle is cleaned.

In the U. S. military, the selector shaft lock was installed on most M14 rifles so that only semi-automatic fire could be employed. However, the Table of Organization for the U. S. Marine Corps required three automatic riflemen per rifle squad when the M14 was the issue rifle. In Viet Nam, the 1st Marine Division 1st Reconnaissance Battalion and the Combined Action Platoons (CAP) were equipped with selector switches on their M14 rifles. CAP Marines fielded the M14 from 1965 until at least 1970. Automatic fire was used in ambush situations and by the patrol point man when making enemy contact.

Reliability - Reliability of a weapons system is a timeless characteristic of paramount importance. Military personnel engaged in combat will not trade the reliability of a weapon for anything, including weight. The weight of the rifle is not considered a burden but a life sustaining tool. That tool must function when needed. The M14 rifle has proven itself trustworthy in many places and in many climates.

The M14 rifle was tested for sustained fire in 1960 at Fort Benning, GA. In particular, one M14 rifle was fired continuously at a rate of sixty rounds per minute for 3080 rounds. The test ended when the chambered rounds started pre-igniting because of the hot barrel. The barrel never failed to stabilize the exiting bullets. The front end of the stock and the hand guard eventually burst into flames but the rifle continued to fire. At Fort Benning, the M14 rifle was found capable of firing 600 rounds in heavy rainfall without any malfunctions.

The U. S. Army Infantry Board conducted an extensive small arms comparison test from June to November 1965 at Fort Benning, GA. The study examined all aspects of the

operation and maintenance of several rifles, carbines, automatic rifles and machine guns including the M14, M14E2, M60, HK33, AR18, Stoner 63 and two M16 type models.

In the comparison study, 100 M14 rifles were fired for a total of 445,268 rounds but there were only a total of 313 malfunctions. That is an average of one malfunction per 1,423 rounds. The most common malfunction experienced was a failure to feed which occurred 200 times or once every 2,221 rounds. The next most frequent malfunction was a failure of the bolt to close, 29 times or once every 15,354 rounds fired. These 100 M14 rifles had the following parts fail, collectively: extractor left the bolt - 4, bolt roller broke or cracked - 8, extractor spring plunger broke - 1, extractor broke - 3, ejector broke - 1, firing pin broke - 3, gas cylinder cracked - 2, operating rod spring broke - 1, gas piston burred - 1, M62 cartridge case rupture - 4, hand guard assembly cracked - 1, stock cracked and charred - 6, gas cylinder plug cracked - 1, connector lock pin lost - 2, rear sight cover cracked - 1, front sight guard cracked - 1, flash suppressor setscrew loosened or lost - 4, rear sight pinion assembly stripped - 2. Adding together all malfunctions and instances of damaged parts, the M14 rifles experienced a problem once every 1,345 rounds on average. Out of a total of 331 instances of malfunctions and damaged parts, immediate action by the operator solved the problem 261 times. Only 50 times out of the trigger being pulled 445,268 times, an average of once every 8,905 rounds, did a M14 go down for repair. During the testing, each weapon was field stripped, cleaned and lubricated on a daily basis. A weekly detail cleaning was performed as the testing permitted. Of the seven rifles and carbines tested, the M14 had the lowest rate of malfunctions and damaged parts.

The M14E2 experienced a similar rate of malfunction, 74 instances over a total of 107,287 rounds fired for an average of one per 1,450 rounds. The most common type of failure for the M14E2 was failure to extract. This occurred at a rate of once every 5,109 rounds. During assault exercises, soldiers with the M14E2 occasionally observed the front bottom side of the M14E2 stock burst into flames after firing 200 rounds in three round bursts. The soldiers were still able to operate the weapon by grasping the vertical fore grip but it caused some distraction. Among the fifteen M14E2 rifles tested, the following parts failures were noted: operating rod spring broke - 1, cartridge broke off in chamber during extraction - 2, broken jaws on M2 bipod - 3, burnt stocks - 3, cracked stock - 1, shoulder rest spring broke - 1, muzzle stabilizer fell off - 5, and vertical fore grip snapped off while trying to free the muzzle stabilizer - 1.

In January 1968, the U. S. Department of Defense Weapon Systems Evaluation Group (WSEG) tested the reliability of the M14 and M16A1 rifles at Fort Sherman in Panama under field conditions designed to simulate the environment faced by American troops in the Republic of Viet Nam at the time. Both rifles were tested in beach, swamp, rain forest and dry climate conditions by a total of 302 U. S. Marines divided into four platoons. The M14 rifles and M62 tracer and M80 ball ammunition were included in the test as a control against three versions of the M16A1 and various 5.56 mm ammunition compositions. The M14 rifles were shot alternately in semi-automatic and automatic mode. Each M14

rifle was shot with magazines loaded to twenty cartridges except for one in each of the sixteen squads was fired with magazines filled with eighteen rounds. Each of the M14 rifles used in the test was shot approximately 5,700 rounds with only cleaning at noon each of the twelve days of firing.

The WSEG test recorded the following Mean Rounds to First Malfunction for the M14 rifle in each of the four field environments: 1) 1,039 for salt water, spray and sand 2) 1,248 for swamp water and mud 3) 707 for rain forest and 4) 952 for uplands and dust. When the M14 rifle did malfunction, 42 % of the time it was on the first or second round of the magazine. The likelihood of malfunction is highest with the first two rounds in either magazine loading, eighteen or twenty cartridges. This is due to the slightly lower cyclic rate of fire with a full or nearly-full magazine. The M14 gas system does not exhaust propellant gas and carbon residue into the receiver and bolt. This lends to the reliability of the M14 design.

Safety - Designed as a military weapon, the M14 type rifle has a number of safety features that protect the operator or unintended targets from injury. Some of these features are common to other firearms while the remainder are M14 specific. In order to fire, the USGI M14 rifle must be assembled, the magazine loaded with at least one cartridge and inserted into the rifle, the hammer cocked by pulling the operating rod to the rear with at least 15.31 pounds of force, the bolt stripping a cartridge from the magazine and fully closing into battery, the safety disengaged and the operator pulling the trigger to the rear with sufficient force, typically 5.5 to 7.5 pounds, before the bullet will exit the barrel. Several *deliberate* acts by a human operator must be taken to cause the M14 type rifle to discharge a bullet.

The receiver bridge with its camming surface and cutout work together with the tang of the firing pin to: 1) mechanically retract the firing pin when the bolt rotates to unlock after firing, preventing a "sticky", rusted or gummed-up firing pin from remaining in the forward position during the rest of the cycle of operation and 2) prevent the firing pin from slamming forward when the round being loaded stops in the chamber, preventing a "slam fire" while the bolt is still unlocked. The firing pin can travel forward through the bridge cutout only after the bolt has fully closed and locked. Additionally, the hammer cocking machining cut on the rear end of the bolt prevents the hammer from striking the firing pin until the bolt lugs have rotated into locked position.

The sear engages the hammer to prevent firing until sufficient force is applied to the trigger by the operator. The hammer spring and hammer work together to prevent the primer from blowing out of the cartridge case once the gunpowder has ignited. An easily operated safety can be engaged to prevent any rearward movement of the trigger and any forward motion of the hammer whatsoever. With the safety engaged, the trigger is disengaged from the hammer and the trigger is limited in its rearward travel. The engaged safety rests on top of the hammer left side ridge, positively preventing a strike on the firing pin. The position of the safety can be easily discerned by touch alone. This

is especially useful in the dark. The trigger guard aids in unintended discharge of the rifle by limiting access to the trigger. The two stage trigger pull gives the operator sufficient pause for getting the sights on target or for choosing not to engage at the last twinkling.

When the gunpowder inside the cartridge case ignites, the hot propellant gas generates a chamber pressure of 50,000 psi or more. The chamber pressure is prevented from venting into the operator's face by the locking action of the bolt and receiver lugs. As the gas pressure acts on the gas system, the operating rod will move about 5/64 " to the rear before engaging the bolt to rotate and unlock. This allows sufficient time for propellant gas pressure inside the barrel to drop to ambient pressure. The cutoff and expansion gas system of the M14 develops less gas cylinder pressure than the impingement gas system of the M1. From a safety standpoint, this results in less force acting on the operating rod as it moves to the rear. Less force pushing on the operating rod means softer impact on the receiver by the bolt. The "hump" of the operating rod, located just in front of the handle, serves to knock the ejected cartridge case to the right and forward of the shooter, typically one o'clock to two o'clock as viewed looking down range along the barrel. This ejection pattern minimizes the risk from hot cartridge brass to the operator and adjacent shooters. The bolt lock will engage the bolt holding it to the rear after the last cartridge has been ejected from the rifle. This feature is a visual indicator that the rifle is out of ammunition.

Should several things go terribly wrong and the rifle fires before the bolt lugs have engaged the receiver, the propellant gas will vent forward through the barrel and downward into the magazine well and outward through the gap between the receiver and the stock. The rearward movement of the bolt is controlled by the force of the operating rod spring and the receiver safety lug. As the bolt moves rearward it is forced downward by the slope of the receiver heel. Some commercial M14 type receivers have well defined bolt raceways aft of the receiver bridge which further aids the downward movement of the bolt upon opening.

The hand guard prevents operator injury from the hot barrel. The noise of the muzzle blast is transmitted through the air but also by vibration to the skull through the shooter's cheek weld. This is known as bone conduction of sound waves. The operator's skull receives lesser bone conduction because of the foam filled USGI M14 synthetic stock. Note that this is no substitute though for proper hearing protection. Although the peak sound pressure level lasts less than 2.5 milliseconds, it reaches 159 dB as measured at the operator's ear when the M14 is fired. Automatic fire is only possible with M14 rifles built with functional select fire components and then only when the selector switch has been turned to the automatic fire position. Otherwise, the rifle will only discharge once for each rearward pull of the trigger. The operator can confirm the mode of fire by observing the letter A on one side of the selector switch or feeling the projection on one end of it.

Storage Racks - When not in use, the M14 rifle was securely stowed in a small arms storage rack. There were two types of locked storage racks for the M14 rifle, floor

mounted and wall mounted. Two floor mounted rack models were available, the M1A1 (FSN 1095-776-0043) and the M3A1 (FSN 1095-776-0044). Both models were built from wood and could store twenty M14 or M1 Garand rifles. Floor mounted storage racks were installed in barracks. The M11 wall mounted storage rack was made of 6061 T6 alloy aluminum, painted green and held twenty M14 rifles. The manual for the M1A1 and M11 storage racks was TM 9-1095-200-15P with Change 1 dated 22 September 1965.

Weapons Cards - Troops issued M14 rifles were given a wallet-sized "weapons card." The card was known as a Weapon Custody Receipt (Form 4430) in the U. S. Navy and U. S. Marine Corps. Form 4430 was created in June 1961 and later revised in March 1976. The original Form 4430 contained the following information: organization, person to whom the weapon was issued to and his Service Number, signature and grade of the Commanding Officer, weapon description, weapon serial number and the storage rack number. The March 1976 revision replaced the Service Number with the serviceman's Social Security Number and added a Privacy Act Statement on one side. Accordingly, "THIS FORM IS USED TO DETERMINE WHO HAS CUSTODY OF WEAPON AND TO ESTABLISH RESPONSIBILITY FOR CONTROL, CARE AND SAFEKEEPING."

The weapons card in the U. S. Army was DA Form 3749 Equipment Receipt. The DA Form 3749 was promulgated on August 01, 1971 and later revised in January 1982. The DA Form 3749 was still in use by the U. S. Army 1st Infantry Division as late as May 2005 for issuance of small arms. When a serviceman went to retrieve his M14 rifle he gave the Weapon Custody Receipt or "weapons card" to the armorer. The armorer issued the rifle to the serviceman and placed his "weapons card" in the bottom of the rack where the individual's rifle was stored. Upon return of the M14 rifle to the arms storage room, the service member was given back his weapons card.

Firing Data Cards - A small form, a firing data card, was often pasted by individual soldiers to the inside surface of the butt plate flapper. This card was used to record the battle sight zero at 100 yard increments out to 500 yards for the soldier's M14 rifle. This card was obtained by cutting out from a page of FM 23-71 Rifle Marksmanship Course Trainfire 1. FM 23-71 was published by the U. S. Army in September 1957.

Training Aids – As with other small arms, the U. S. Army and U. S. Marine Corps used training aids to instruct servicemen in the operation and maintenance of the M14 rifle. These training aids were most often used in U. S. Marine Corps recruit and U. S. Army basic and advanced training. U. S. Marine Corps Junior ROTC Units have also used some of the training aids discussed below. After Raritan Arsenal closed in 1963, training aids were stored, issued and maintained by regional facilities such as Fort Jackson (SC) and Fort Benning.

The U. S. Army produced training film T.F. 9 2970 in 1960 on the operation and cycle of functioning of the M14 Rifle. The twenty-seven minute black and white film was titled *U. S. RIFLE, CAL. 7.62 MM M-14*. The M14 and M14A1 were featured in *Weapons of the*

M14 RIFLE HISTORY AND DEVELOPMENT

Infantry, a twenty minute training film in color produced in 1967 by the U. S. Army. This film consisted of live fire demonstrations of the infantry weapons of time, including the M14 and M14A1. The narrator states the capabilities for each weapon throughout the film. The U. S. Marine Corps produced a thirty minute color training film, *The Rifle Basic Marksmanship Series*, for classroom instruction of recruits. It was filmed in 1970 at MCRD Parris Island (SC). The film covered the principles of marksmanship, shooting positions and zeroing of the M14 rifle. It also featured short clips of combat footage of the M14 in use in the Republic of Viet Nam at the beginning of the film.

Cardboard M15 sighting devices were used in classroom instruction to teach soldiers and Marines proper M14 rifle sight alignment and sight picture. The U. S. Army had a chart (GTA 21-2-10 dated June 1971) to instruct soldiers on how lay out the individual combat equipment, including the M14 or M16 rifle, for inspection in the field.

Cloth and heavy paper training mats with the outlines of M14 parts printed with contrasting color were used as well to teach field stripping and assembly. The U. S. Marine Corps used a cloth training mat that had a green color background and yellow print outlines of M14 parts in recruit classrooms at MCRD San Diego in 1971. Fort Benning produced a M14 parts disassembly chart in July 1963.

A two-to-one scale training mock up of the M14 was produced by two different contractors with some slight differences between the two models. The mock up M14 had its own carrying case that doubled as a presentation stand. A disassembly mat, thirty mock up ammunition rounds, a wire basket and a rubber catch mat were included as part of this training aid. The wire basket and rubber mat were used to catch the mock rounds of ammunition as the cycle of operation was demonstrated. Classified as Device 3F44, the mock M14 rifle had exterior areas cut away in places to illustrate the function of the moving parts. The 3F44 device could be field stripped and the mock cartridges cycled in both semi-automatic and automatic modes just like a M14 rifle. The 3F44 device was required to be built well enough to withstand disassembly and assembly twenty times a week for a period of five years and not be adversely affected in temperatures ranging from - 65 degrees to 165 degrees Fahrenheit or relative humidity as high as 95 %. One mock double size M14 rifle is on display at the Stone Bay Ranges Armory inside Marine Corps Base Camp Lejeune (NC).

In 1962, American Research and Manufacturing Corporation produced a pair of animated transparencies that demonstrated the gas system, bolt and firing mechanism operation of the M14 rifle. The Federal Stock Numbers for these two devices were 6910-708-2379 for the Gas System transparency and 6910-708-9720 for the Operating Group transparency. These transparencies were used by the U. S. Marine Corps.

The November 24, 1972 issue of *Life* magazine ran a story on Marine Corps boot camp at Parris Island, SC. In the story, are photographs of Marine recruits training with skeletal metal castings shaped in the form of M14 rifles. The *Life* article refers to these training

aids as mock weapons.

Mr. Banford R. Hill (then of Portland, OR) in 1990 patented a video target training apparatus for the M14 rifle. A simulator device resembling the physical appearance of a M14 rifle was connected to a computer, a camera and two video monitor. The target image, as viewed by the user, was reflected by optical lenses to the camera and then fed to the computer and to two video monitors. The computer processed the target image as viewed by the trainee and the theoretical impact of the round(s) fired. One monitor displayed the target image as seen by the trainee and the other monitor gave a graphical display of where the "shot" landed on the target. The operator could make windage and elevation adjustments on the simulator rifle resulting in change of "bullet" impact on the target image. The training simulator was activated by a trainee pushing it against a target image. The trainee lined up the sights with the target, hopefully using proper sight alignment and sight picture, and pulled the trigger. When the trigger was pulled, a plunger connected to the target pushed back against the simulator rifle to replicate rifle recoil and recock the trigger. The trainee also heard recorded gunfire noise when he pulled the trigger.

The M14 Rifle in Overhaul

As deemed by appropriate authority, the U. S. Army overhauled rack grade M14 rifles at depot facilities, e.g., Anniston Army Depot from 1983 to 1984. If a USGI M14 rifle has been through overhaul, the Army depot performing the work and the month and date it was done will be identified on the right side of the receiver under the operating rod rail, e.g., ANAD 12-83.

The engraved circle or letter O found on some M14 receiver heels means that rifles so marked went through depot level overhaul by the U. S. Marine Corps. Depot armorers at the Marine Corps Logistics Bases (then Depots of Supplies) Barstow, CA and Albany, GA marked overhauled M1 Garand rifles on the flat surface behind the rear sight with O-65, O-66, and O-67. The two digit number in the marking referred to the calendar year of the overhaul, e.g., 67 meant 1967. The practice was continued with depot overhaul of M14 rifles. M14 rifles overhauled by the U. S. Marine Corps were marked O-69 in 1969. By at least 1970, the marking was changed to a four alphanumeric character code, e.g., OB-70. The second letter in the code stood for the depot which performed the work. By similarly marking the M14 receiver heel with the letter O, the rifle would not require disassembly to identify it as an overhauled unit.

Some of the testing for overhauled M14 rifles is briefly described as follows:

Functioning – With a full twenty round magazine, each rifle was fired with five rounds in semi-automatic then one burst of three to five rounds and finished by emptying the magazine with one last pull of the trigger. During the last pull of the trigger, the cyclic rate of the rifle was measured. The cyclic rate requirement was within the range of 650 to 780

rounds per minute. After 100 consecutive rifles passed the cyclic rate of fire test, then every tenth rifle was tested to determine the cyclic rate.

Targeting and Accuracy – Sample M14 rifles were placed into a test stand, loaded with M59 or M80 ball ammunition and five shots were fired at targets at a distance of 1000 inches (27.78 yards). The five shots had to group within a 1.8 " diameter circle.

Endurance – One of every 500 rifles was subjected to a 1000 round endurance test. The first series of 100 rounds was shot in semi-automatic. The second series was fired in five rounds bursts in automatic. The third series was a full magazine dump. The barrel was allowed to cool to ambient after each series of 100 rounds. This set of series was repeated three times then the last 100 rounds were fired by emptying each of five fully loaded magazines with one pull of the trigger for each magazine. No cleaning of the gas system was allowed during the endurance test. No more than four malfunctions total were allowed for passing the endurance test. Also, there were limits on the number of specific types of malfunction: 1) failure to feed – two 2) bolt failed to lock – one 3) failure to fire – one 4) pierced primer – zero 5) failure to extract – two 6) failure to eject – three 7) failure to fire semi-automatic – zero 8) selector operation caused firing – zero and 9) firing not in accordance with the selector switch setting – zero.

Additional Testing – All parts were examined for proper fit, function, condition, and finish. The minimum headspace was 1.6355 " and the maximum, 1.6415 ". However, the overhaul procedure specified that every effort be made to keep the maximum headspace to no more than 1.6375 " to maximize barrel life (with 7.62 x 51 mm NATO ammunition). The trigger pull had to be free from creep and greater than 4 ½ pounds but no more than 7 ½ pounds. The following parts were replaced without regard to condition: ejector, ejector spring, extractor spring and plunger, magazine latch spring, operating rod spring, hammer spring and bolt lock spring. Wood or slotted fiberglass hand guards were replaced with solid fiberglass hand guards. Non-plated firing pins were replaced with chromium plated firing pins. Early style extractors were replaced with late (1965 design) style extractors. Any part marked with N M was removed and replaced. Both styles of operating rod spring guides and gas cylinders were acceptable for service. Barrels with throat erosion readings greater than 5 required replacement. The gas cylinder plug on factory built M14 NM and overhauled M14 rifles was torqued to 13 to 17 foot-pounds force. Failure to fall within specified limits resulted in rejection and subsequent rework of the rifle.

M14 in Service with the U. S. Army and U. S. Marine Corps

U. S. Army - In the U. S. Army infantry squad of the early 1960s, the M14 rifle was standard issue. Each infantry squad had two automatic riflemen, two grenadiers and six riflemen. The 101st Airborne Division was the first Army division to be equipped with the M14 rifle. Delivery of the M14 rifle to this unit began in January 1960. U. S. Army troops in Berlin, West Germany were armed with the M14 rifle by no later than early September

1961. The M14 rifle was issued to all U. S. combat units in western Europe by October 01, 1961. By 1963, the M14 had been issued to all U. S. Army, Navy and Marine Corps units so authorized.

In the 1960s, U. S. Army infantry recruits spent much of their time in basic training with the M14 rifle. The Army recruit used the M14 in drill and ceremonies, marksmanship training, field marches, bivouac, bayonet training, infiltration and obstacle courses, guard duty and small unit tactics training.

In 1960, the U. S. Army infantry rifle squad consisted of twelve soldiers equipped with the M14. In 1962, the Table of Organization and Equipment (TOE) for the rifle squad was changed to 10 soldiers and then a year later to 11 men. In all three cases, the rifle squad was authorized two automatic riflemen. The automatic rifleman was issued the M14 (Modified) rifle until the M14E2 was fielded in 1964. The 1963 TOE remained in effect until 1967 when the U. S. Army adopted the M16A1 rifle.

There were U. S. Army infantry units that used the M14 rifle in the Republic of Viet Nam. For instance, the U. S. Army 1st Infantry Division deployed to the Republic of Viet Nam in July 1965 with its soldiers bearing the M14. The 1st Infantry Division was equipped with M14 rifles on November 19, 1965 during combat operations at Lai Khe in Binh Duong province.

The soldier of the 1960s period carried his M14 magazines using M1956 Lightweight Load Carrying Equipment (LCE). This equipment was introduced in 1956 except the small arms ammunition case came out a year later. The M1956 LCE replaced the M1910 wire hook fasteners with slide clip fasteners and metal canteen with a polyethylene model. The slide clip fastener was patented in 1959. It would later be known as the ALICE clip although it was introduced with the M1956 LCE system. The slide clip fastener was a lightweight, strong, quiet, reliable and durable means of attaching equipment pouches and packs to a load bearing belt. The slide clip fastener could be operated with one hand and it was inexpensive to manufacture. The standard M1956 components consisted of canvas material equipment belt, load bearing suspenders, butt pack, ammunition cases, one quart canteen with cover, shovel carrier, sleeping bag carrier, and small pouches for first aid items and compass.

Development of night vision rifle scopes for military purposes was underway by 1960. Raytheon produced the T-1 infrared rifle scope that year. Two contractors supplied the AN/PAS-4 to the U. S. Army, Polan Industries (220 Eighth Street Huntington, WV) and Varo, Inc. (Garland, TX). About 4,000 units were made in 1962. The AN/PAS-4 weighed about 6 pounds and the belt carried battery for it weighed about 7 pounds. The BB-429/U sintered-plate nickel-cadmium 6 Volt battery was made by Sonotone Corporation (Elmsford, NY). The AN/PAS-4 infrared scope was mounted on a M14 rifle in 1964 and 1965 for orientation of U. S. Army recruits in basic training at Fort Dix (NJ) and Fort Jackson (SC). The AN/PAS-4 equipped M14 rifle also saw service in the Republic of Viet

Nam with U. S. and South Vietnamese troops but primarily in a training role. It had an effective range of 300 yards. The AN/PAS-4 scope was in service until about 1970.

Ammunition cases are commonly referred to as magazine pouches. The M1956 LCE had at least four variations of the small arm ammunition case (FSN 8465-647-0852).

Beginning by September 1959, three versions were made before 1968 and the fourth kind was produced in 1968. A 1960 vintage example was marked as follows inside the flap, top to bottom: first line - POUCH, SMALL ARMS, AMMUNITION, UNIVERSAL second line FSN 8465-647-0852 third line DA 36 243 QM (CTM) 5558-E-61 fourth line AUG 1960. Another M14 magazine pouch made after 1960 was marked as follows inside the flap: top line - CASE, SMALL ARMS, AMMUNITION middle line - DSA-1-8682 bottom line - 8465-647-0852.

The M1956 small arms ammunition cases made before 1968 could hold two M14 twenty round magazines or four M1 Carbine thirty round magazines or six M1 Rifle enbloc clips. The 1968 production M1956 ammunition cases were designed to hold M16 twenty round magazines. The cases were secured with a canvas tab and metal loop arrangement. Only the first of the four versions of the M1956 pouch were made with a front side steel plate inside the fabric. Magazines were inserted top down into the pouches for a number of reasons: 1) faster reloading 2) to help keep dirt and water from collecting in the magazine and 3) minimize the potential for bending of the magazine feed lips.

The U. S. Army upgraded to the M1967 Modernized Load Carrying Equipment (MLCE) system in 1968 to better resist the effects of jungle warfare. The MLCE components were made from nylon. The equipment belt and magazine pouches were given quick release plastic buckles. The M1967 all-metal construction shovel folded into three parts and was stowed inside a plastic case. The M1967 magazine pouches were designed for the M16 rifle and were produced from 1970 to 1972, possibly later. However, in 1970, some M1967 nylon M14 magazine pouches with quick release plastic buckles were produced. These magazine pouches also held two M14 twenty round magazines. Individual load carrying equipment was further modernized in 1974 with the introduction of All Purpose Lightweight Individual Carrying Equipment (ALICE).

In 1957, the U. S. Air Force was the only military branch that did not welcome the M14 rifle. The U. S. Air Force retained its Army supplied M2 carbines in lieu of the heavier M14 rifle. In April 1961, Dr. Carten, the U. S. Army Chief of Small Arms Research and Development recommended the Air Force consider the folding stock M14E1 rifle for its needs. Instead, U. S. Air Force Deputy Chief of Staff General Curtis LeMay continued to lobby for congressional funding to purchase civilian models of the yet-to-be adopted M16 rifle. His lobbying included a personal meeting with President John F. Kennedy in December 1961 then as U. S. Air Force Chief of Staff. His request was denied.

On his third request, General Curtis LeMay was able to obtain funds in May 1962 for the first of several Air Force orders for civilian manufacture M16 type rifles. The U. S. Air

Force adopted the .223 Remington caliber rifle in May 1962 as the M16 to replace its M2 Carbines which the Army no longer stocked parts for. Later, the U. S. Air Force would use the match conditioned M14 rifle for competition matches. Eventually, the U. S. Air Force equipped Explosives Ordnance Disposal and Special Operations personnel with the M14 SMUD rifle.

Although the U. S. Army Ordnance Corps had originally intended to replace the M14 with the Special Purpose Individual Weapon (SPIW), the M16 rifle was brought into service as the standard infantry rifle for the U. S. Army and U. S. Marine Corps by the mid-1960s. Consequently, the M14 rifle was phased out among Army and Marine Corps infantry units as M16 rifles were received. For example, the M14 rifle was replaced by June 1966 in the 22nd Infantry Regiment 4th Infantry Division of the U. S. Army. Yet, Artillery Forward Observers in the Army's 3rd Howitzer Battalion 6th Artillery Regiment carried M14 rifles in the field through at least the end of October 1966. U. S. Army Military Police on duty in the streets of Saigon, Republic of Viet Nam during the November 01, 1966 National Day Parade carried M14 rifles. U. S. Army Chief of Staff General Harold K. Johnson recommended in correspondence to Secretary of Defense Robert McNamara in December 1966 that the M14 rifle should be replaced and only the XM16E1 (later classified as M16A1) should be purchased for infantry rifles. The M16A1 officially replaced the M14 as the Standard A rifle in the U. S. Army on February 28, 1967.

However, the transition was not quickly implemented. The U. S. Army was still using the M14 rifle in combat as late as January 1968 in the Republic of Viet Nam. Soldiers of the Army 40th Signal Battalion stationed around Phu Tai, Binh Dinh defended themselves with the M14 rifle when attacked by the Viet Cong during the Tet Offensive, which began the night of January 30-31, 1968. The soldiers of the U. S. Army 2nd Battalion 94th Field Artillery 108th Artillery Group at Camp J. J. Carroll, near Cam Lo, Quang Tri Province, did not exchange their M14 rifles for the M16 until May 1968. Signal Corps and Aviation units typically carried M14 rifles into combat in 1968 and 1969. M14 rifles were mixed in with M16A1 rifles among troops of the U. S. Army 1st Cavalry Division in the Republic of Viet Nam as late as August 1970.

The U. S. Army reported a total loss of 14,470 M14 and three M16A1 rifles in the Republic of Viet Nam between July 01, 1967 and June 30, 1970. Of that number, 1,038 M14 rifles and the three M16A1 rifles were losses due to combat action. M14 rifles were lost in battle as late as May 1970, if not later, according to available U. S. Army records. For example, two M14 rifles, serial numbers 1239005 and 1299813, were destroyed by direct fire in daylight when the members of the 1st Battalion 5th Infantry Regiment (Mechanized) 25th Infantry Division, were engaged in heavy contact with the enemy in jungle terrain on May 09, 1970 in Operation Bold Lancer.

These equipment loss records, declassified in 1977, include the unit name, date of loss, cause of loss, the rifle serial number and situation details such as visibility, weather, type

of mission, level of enemy contact, terrain, etc. A report was submitted for each M14 rifle lost no matter the cause. In a lot of cases, the weather and terrain information is omitted but the unit names, type of mission, date of loss and rifle serial numbers confirm that the M14 rifle was very much in use in combat until 1970. U. S. Army equipment loss reports for the fiscal years 1968, 1969 and 1970 show that the following major commands lost M14 rifles due to combat action in the Republic of Viet Nam: 1st Aviation Brigade, 1st Cavalry Division, 1st Infantry Division, 9th Infantry Division, 12th Aviation Group, 17th Aviation Group, 23rd Artillery Group, 23rd Infantry Division, 25th Infantry Division, 18th Engineering Brigade, 18th Military Police Brigade, 20th Engineering Brigade, 101st Airborne Division, 108th Artillery Group, 164th Aviation Group and the 199th Infantry Brigade.

Even the M14A1 was carried into combat as late as 1968 in the Republic of Viet Nam. M14A1 rifle serial number 1274598, a Winchester, was lost in combat on May 07, 1968 due to direct fire. The Cavalry unit involved, Troop D 17th Troop 199th Infantry Brigade, was on a Recon in Force mission that day. The M14A1 was lost during heavy contact with the enemy in jungle terrain in the III Corps Tactical Zone.

The weekend of October 21 and 22, 1967 was an ugly scene in Washington, DC. Over 70,000 anti-war protestors gathered to demonstrate against American military involvement in the war in the Republic of Viet Nam. The U. S. government called up 6,000 federal police and U. S. Army Military Police to maintain order in the capitol. On Saturday, the initial rally at the Lincoln Memorial was held peacefully. Towards the evening though, chaos erupted. Nearly 5,000 demonstrators left the rally and marched towards the Pentagon. The demonstrators arrived to find barricades and U. S. Army Military Police armed with fixed bayonets on M14 rifles but no magazines inserted into them. For the next twelve hours, a full blown riot raged outside the Pentagon. In a twist of historic irony, Secretary of Defense Robert S. McNamara observed the bedlam first hand through a window inside the Pentagon. The rifle he thought not worthy of funding four years earlier was the soldiers' tool that his safety depended upon that night. At about midnight on Saturday, the Military Police counterattacked against the American citizens surrounding the Pentagon. Many of the demonstrators were beaten and arrested. By the next evening, the protest was over.

On April 04, 1968, Rev. Dr. Martin Luther King, Jr. was murdered. Following this tragic event, there were many protests, marches, rallies and riots during the spring and summer of 1968. For example, the downtown areas of several major U. S. cities sustained major damage in August 1968 from fires set by rioters protesting the death of Dr. King. U. S. Army National Guard troops armed with M14 rifles were called into control the riots in these cities. The U. S. Army 2nd and 7th Infantry Divisions stationed in the Republic of Korea were still armed with the M14 rifle in 1968. The 2nd Infantry Division converted from the M14 to the M16A1 starting in late 1968 and finishing in May 1970. During this period, the 2nd Division inspected, packaged and turned in over 7,000 M14 rifles. The

M16A1 rifle was shipped to U. S. Army units in Europe beginning in May 1970 to effect replacement of the M14.

On October 03, 1993, U. S. military forces executed Operation Gothic Serpent in Mogadishu, Somalia. During the mission, U. S. Army Special Forces Delta operators Master Sergeant Gary Gordon and Sergeant First Class Randall Shughart volunteered to leave the relative safety of the helicopter they were aboard to provide security for the crew of the second downed Black Hawk UH-60 helicopter, *Super Six-Four*, of Task Force Ranger. Gordon and Shughart fended off the hostile Somalis until all small arms ammunition had been expended and they were fatally wounded. Their selfless actions saved the life of the pilot, Chief Warrant Officer Four Michael J. Durant. Both men were awarded the Medal Of Honor posthumously.

Sergeant First Class Shughart routinely carried the M14 in Somalia. On October 03, 1993, his M14 rifle was equipped with a leather sling and an Aimpoint red dot reflex sight. The stock was painted with a desert camouflage pattern. Before landing on the ground to assist *Super Six-Four*, Sergeant First Class Shughart had provided fire from his M14 rifle on the target building and at both helicopter crash sites. The mission plan called for the two Delta operators to remain airborne. Consequently, Gordon and Shughart, did not bring extra quantities of ammunition. Shughart boarded the helicopter that afternoon with only seven twenty round M14 magazines for the M14 and a Colt Firearms M1911 as a secondary weapon. When Gordon and Shughart touched the ground at the second crash site, there was less than 140 rounds left for the M14 rifle. Nonetheless, Sergeant First Class Shughart put the M14 and the other weapons on the scene to good use. Chief Warrant Officer Four Durant reported hearing a continuous discharge of firearms for about two minutes immediately before Sergeant First Class Shughart was fatally wounded. The weapons of both heroes were never recovered.

U. S. Marine Corps - The M14 rifle was issued to the first Marine Corps units in 1961. The conversion from the M1 Garand rifle to the M14 had been completed for the Fleet Marine Forces by no later than November 1962. Thomas Bailey, son of Harrington & Richardson Arms employee Mary Bailey, was the first U. S. Marine to be issued the M14 rifle. In the 1960s, the U. S. Marine Corps infantry rifle squad consisted of a squad leader and three four man fire teams. Each fire team assigned one M14 with a selector switch to the Automatic Rifleman. The U. S. Marine Corps developed its own Load Carrying Equipment in 1961.

The M1961 LCE had an equipment belt with metal snap "button" fasteners for securing ammunition pouches. The markings on one M1961 web belt read as follows: top line is the item description - BELT, INDIVIDUAL EQUIPMENT middle line is the contract number - DSA100-67-C-1041 bottom line is the Federal Stock Number 8465-823-6937. To the right of this information is the letter M signifying Medium Size. Under the letter M is the marking -2-.

The ammunition pouches were slid on to the belt then secured by snapping the “male” half of the fastener on the pouch to the “female” half of the fastener on the belt. Each M1961 magazine pouch carried one M14 twenty round magazine. In 1964, the second version of the M1961 magazine pouch was introduced. The pouch compartment and flap were made slightly longer than the original. The thought behind the M1961 LCE was that it allowed for a lower prone position. U. S. Army and U. S. Marine Corps infantry Rifleman were issued five M14 magazines and Automatic Rifleman were given eight M14 magazines. Marines carried additional ammunition in sixty round M2 bandoleers. The M1961 LCE also had a butt pack. M1956 canteen covers and shovel carriers were used by the Marines.

The U. S. Marine Corps experimented with two M14 magazine pouches known as M14H and M14-V, H for horizontal carry and V for vertical carry. These olive drab nylon pouches attached by ALICE clips held two magazines. The M14-V pouch was manufactured at some point before 1973. It was marked U.S.M.C. on the flap on the outside and POUCH M14-V on the inside. The magazines were accessed by undoing the flap and pulling vertically out of the pouch. Likewise, a single magazine was removed from the M14H pouch by pulling up on the pouch flap. The M14H pouch was marked U.S.M.C. on the outside of the pouch flap. These magazine pouches were not issued.

While the number of combat operations in the Republic of Viet Nam are too numerous to list, one frightful night in 1966 will serve as witness to the value of the M14. Led by Gunnery Sergeant Jimmie E. Howard, sixteen Marines and two Navy corpsmen (medics) from First Platoon C Company 1st Battalion 5th Marines 1st Marine Division formed up as a reconnaissance patrol on June 13, 1966. They were delivered by helicopter to Hill 488 in the Que Son Valley of Quang Tin Province, Republic of Viet Nam that evening. The Marines and sailors set up an observation post at the top of the hill. During the next two days, the unit called in artillery strikes and aerial bombing runs on Viet Cong units in Que Son Valley. The Marines were equipped with select fire capable M14 rifles, one M79 40 mm grenade launcher and a total load of about 3,000 rounds of 7.62x51 mm NATO ammunition. The two Navy corpsmen carried .45 ACP pistols. Each man also carried a minimum of four fragmentation hand grenades.

By the third evening, June 15, 1966, the enemy had figured out where the source of their trouble was located and had determined to do something about it. A battalion sized force of 450 North Vietnamese Army and Viet Cong soldiers began the attack of Hill 488 at about 11:00 PM in an all-out attempt to annihilate the eighteen Americans. When hostilities had ended at about 9:30 AM the next morning, this small unit of Marines and sailors had become the most highly decorated military unit in American history. The unit had expended all hand grenades and 40 mm projectiles and had less than an estimated 200 rounds of M14 rifle ammunition left by 4:00 AM on June 16. Six of the eighteen men were killed in action that night with another later dying of wounds sustained in the battle. Another five Marines were killed the morning of June 16 as part of the reaction force. The following medals were awarded to the members of Gunnery Sergeant Howard's unit as a

result of the bravery shown and wounds received that night: one Medal of Honor, four Navy Crosses, thirteen Silver Stars, and eighteen Purple Hearts.

Lieutenant General Victor H. Krulak, Commanding General of Fleet Marine Force, Pacific, stated on January 02, 1967 that the Marines in the Republic of Viet Nam were switching to the M16A1 rifle. The change to the M16A1 was pushed in 1966 by Lieutenant General (later General) Lewis W. Walt, then Commanding General of the III Marine Amphibious Force and Senior Advisor for I Corps in the Republic of Viet Nam. General Walt had intended for both the M14 and the M16A1 to remain in use throughout the Corps. Marines would be trained on both rifles. The needs of the specific combat operation would determine which rifle would be fielded. However, it did not work out this way.

By February 1967, Marine Corps Base Camp Lejeune (NC), Marine Corps Schools Quantico (VA) and the Staging Battalion at Marine Corps Base Camp Pendelton (CA) had received the XM16E1 rifle for testing. The M16A1, for the most part, replaced the M14 in U. S. Marine infantry units within the Republic of Viet Nam during March, April and May 1967. The Marine 3rd Reconnaissance Battalion had exchanged its M14 rifles for the M16A1 by November 1967. However, the transition period took quite a bit of time.

Apparently, not all M14 rifles had been turned in by infantry units of the U. S. Marine Corps even as late as 1968. U. S. Marine Corps film footage of the battle for Hue, Thua Thien, Republic of Viet Nam reveals Marines engaging the enemy with M14 rifles between the beginning of the Tet Offensive and the liberation of Hue four weeks later on February 26, 1968. Some U. S. Marines relied on the M14 rifle during one of the most infamous battles of the second half of the twentieth century at Khe Sanh, Quang Tri, Republic of Viet Nam. In that battle, the 26th Marine Regiment 5th Marine Division at Khe Sanh was laid siege to from January 21 to April 14, 1968 by as many as 20,000 North Vietnamese Army soldiers. The 1st Battalion 3rd Marines 3rd Marine Division used M14 rifles alongside the M16A1 against a North Vietnamese Army Ranger Battalion north of Dong Ha, Quang Tri, Republic of Viet Nam during Operation Thor in July 1968 in a fierce five day battle leaving over 1,000 enemy dead and only five taken prisoner.

Marines assigned to Air Wing helicopter squadrons in Viet Nam held on to the M14 rifle later into the war than the rifle battalions. The M14 was still carried by Marines of UH-1 helicopter squadron VMO-3 of the 1st Marine Air Wing at Phu Bai, Thua Thien in November 1967 and the Marine Aircraft Group 13 at Chu Lai, Quang Tin in 1969. U. S. Army Signal Corps soldiers carried M14 rifles in the Republic of Viet Nam near Hue until at least May 1970 while constructing radio relay sites. The soldiers constructing the hill top sites were subject to frequent North Vietnamese Army and Viet Cong sniper fire and so needed a magazine fed rifle with sufficient range to counter the threat.

The M14 in Training and Garrison - After the war in Viet Nam, the M14 remained in use for training and barracks duty. The U. S. Army took the step in February 1968 to fully convert small arms training from the M14 to the M16A1 as supplies became available.

The phase out of the M14 rifle began in Army Basic Training by no later than August 1968, e.g., Fort Dix (NJ), but was not completed until December 1969. All U. S. Army infantry training had changed over to the M16A1 rifle by March 1970. The 1st Marine Division, based at Camp Pendelton (CA), exchanged its M14 rifles for M16A1 rifles in the summer of 1972. Recruits were issued the M14 at Marine Corps Recruit Depot (MCRD) Parris Island (SC) until at least June 1973 and at MCRD San Diego (CA) until at least September 1973. U. S. Marines qualified with the M14 rifle each year as late as 1974, e.g., Camp Pendelton and Marine Barracks Roosevelt Roads (PR).

The 2nd Brigade 112th Armor 49th Armored Division of the Army National Guard during the second half of 1972 exchanged its M14 rifles for M16A1 rifles. Marine Corps Office Candidate School classes trained with the M14 as late as June 1975. The M14 rifle was issue equipment for Marines assigned to the 32nd Street Naval Station (San Diego, CA) until the first half of 1978. As of August 2002, the M14 rifle was still in use by aggressor forces at the U. S. Army Ranger School.

Close Order Drill and The M14 - In the 1700s, armies developed instructions for troops to handle and load weapons while in formation in the field or on the parade ground. These instructions were known as manuals of arms. Some examples are the 1764 British Army manual and the Von Steuben manual adopted by the Continental Army in 1777. Until the American Civil War, soldiers were organized in close-knit formations on the battlefield. Hence, the organized movement of troops with or without weapons came to be known as close order drill. Today, close order drill is rarely used for purposes other than or ceremonies and parade functions. However, the manual of arms command, "Fix Bayonets!", was used on occasion by American forces in combat in the twentieth century.

In 1907, the U. S. Navy published the Landing-Force and Small Arms Instructions manual for sailors and Marines. This set of instructions covered amphibious landing operations as well as close order drill movements, use of the sword and guidon, color guard movements, and parade formations. This manual was revised in 1927 as the Landing Force Manual and yet again in November 1960 as the Landing Party Manual OPNAV P34-03. The 1960 Landing Party Manual had extensive photographs in Chapter 2 Drill and Chapter 3 Ceremonies to illustrate proper execution of close order drill movements with the M14 rifle. On May 26, 1981, the Department of the Navy issued SECNAVINST 5060.22. That instruction replaced the 1960 Landing Party Manual with the Marine Corps Drill and Ceremonies Manual NAVMC 2691 for close order drill purposes. NAVMC 2691 gave instruction on close order drill using the M16 rifle instead of the M14. On May 05, 2003, the U. S. Marine Corps issued a new manual for close order drill and ceremonies, MCO P5060.20. That order contains the manual of arms for the M14 rifle.

U. S. Army field manual FM 22-5 Infantry Drill Regulations was published in 1939. The title of the manual changed to Drill and Ceremonies with the June 1950 edition. It was published six more times until it was superseded by FM 3-21.5 in July 2003. The Manual of Arms for the M14A1 rifle was in the last (1986) edition of FM 22-5 but was removed

with the supersession to FM 3-21.5. The M14 Manual of Arms can be found in Appendix C of the Army field manual FM 3-21.5. U. S. Marine Corps MCO 1500.15 dated 1 February 1961 was a reprint of FM 22-5.

The M14 after 2000 - The U. S. Army and Marine Corps have put the M14 rifle to combat use in Afghanistan, Kuwait and Iraq in support of the War on Terrorism. Program Executive Office Soldier (Fort Belvoir, VA), a subordinate agency of Department of Army Systems Coordinator, fielded a total of 5,353 M14 rifles to Army combat units between August 2002 and April 2007. In March 2003, the Fox television network news department showed video footage of a U. S. Army soldier shooting a M14 rifle using automatic fire into the window of a building during the opening days of Operation Iraqi Freedom. Select members of the following units used the M14 rifle in those countries: U. S. Army 1st Cavalry Division, 1st Infantry Division, 2nd Infantry Division, 10th Mountain Division, 25th Infantry Division, 42nd Infantry Division, 82nd Airborne Division, 101st Airborne Division and the 5th and 7th Special Forces Groups, and the U. S. Marine Corps 1st Marine Division. For example, the 1st Battalion 26th Infantry Regiment 1st Infantry Division used the M14 rifle during Operation Baton Rouge in Samarra, Iraq from September 30 to October 2, 2004. In 2005, U. S. Army Sergeant First Class Dillard "CJ" Johnson racked up 121 enemy kills in Iraq with his scoped M14 rifle. His longest hit exceeded 850 meters. On August 17, 2007, U. S. Army soldiers from the 2nd Battalion 14th Field Artillery Regiment 2nd Brigade Combat Team 10th Mountain Division employed the M14 rifle while providing security cover during a medical civic action program in Mahmudiyah, Baghdad, Iraq. The M14 rifle offers greater range and punch than M16 variant rifles and carbines. A carbine is normally defined as a long gun with a rifled barrel that is less than 20 " long. As of May 2008, 17,062 M14 rifles were issued to U. S. military units. That number is aside from the inventory kept at Rock Island Arsenal and other depot level facilities and those rifles issued on loan to law enforcement agencies.

Modern M14 Rifle Optics - Some 82nd Airborne soldiers in 2002 had Trijicon, Inc. TA01-NSN 4x32 scopes mounted to their M14 rifles while on combat patrol in Afghanistan. U. S. Army and Army National Guard soldiers in Iraq with M14 rifles have purchased and installed a variety of optics at their individual discretion. Optics from Aimpoint, Inc., EOTech, Inc., Leupold & Stevens, Inc., Schmidt and Bender, Inc. and Trijicon, Inc. are in use by U. S. soldiers in Iraq. The U. S. Army has issued AN/PEQ-2A and AN/PEQ-5 optics for use on M14 and Mk 14 Mod 0 rifles in Afghanistan and Iraq. The AN/PEQ-2A consists of an infrared laser and an infrared illuminator. The AN/PEQ-2A laser is effective to more than 600 meters. The AN/PEQ-5 is the visible light laser counterpart. The AN/PEQ-2A and AN/PEQ-5 optics are typically used on Mk 14 type rifles. Individual soldiers have purchased and installed Sadlak Industries, Smith Enterprise, Inc. and Springfield Armory, Inc. scope mounts on issued M14 rifles. Additionally, U. S. Army and Army National Guard battalion and company sized units being deployed to Iraq have purchased M14 accessories such as scopes, scope rings, and scope mounts with unit MPAC credit cards. For example, C Company 3rd Battalion 112th Armor Regiment 56th Brigade

Combat Team 36th Infantry Division purchased and installed scope rings, Springfield Armory, Inc. scope mounts and Tasco rifle scopes on its two M14 rifles before deployment to Iraq in 2005.

Load bearing equipment in use in combat zones today is often a mixture of the government issue MOLLE system and privately purchased civilian market tactical load bearing components. Soldiers with combat service in Iraq report that it was common practice to carry an individual load of seven twenty round magazines for the M14. Ammunition resupply in these areas was often from delinking belted M240 machine gun ammunition.

In 2003, the U. S. Army added the M14 rifle to the weapons inventory of the Stryker brigades. The Designated Marksman (DM) for each squad was outfitted with a scoped M14 rifle. The choice of optics was a Leupold & Stevens, Inc. tactical rifle scope. This gave each squad the ability to cover a larger field of fire.

To help support this new infantry role the U. S. Army established a new school in February 2004 called the Squad Designated Marksman School at Camp Bullis (San Antonio, TX). The U.S. Army issued orders to a group of civilian shooters to serve as the faculty for this school for a period of two weeks. Designated as Volunteer Military Instructors, these civilians were all distinguished competition shooters and members of the Texas State Rifle Association. Two groups of forty soldiers from the U. S. Army First Cavalry Division (Fort Hood, TX) were put through a one week course on operating and maintaining the M14 rifle as the Squad Designated Marksman. The Squad Designated Marksman School at Camp Bullis was such a success that it was hosted by the 5th Army Small Arms Readiness Group in December 2004 at Fort Hood for soldiers of the 3rd Infantry Division. Starting in 2005, the Civilian Marksmanship Program provided volunteers to assist Army Marksmanship Unit instructors in presenting a four day Squad Designated Marksman course. The course was given seventy-two times to a total of 2,658 service members at thirteen military bases by May 2010.

In 2004, the U. S. Army National Guard 1st Battalion 69th Infantry Regiment, based in New York, teamed up with the Army National Guard 1st Battalion 156th Infantry Regiment from Louisiana to form the 256th Brigade Combat Team (BCT). The 256th BCT was deployed in Baghdad, Iraq from October 2004 to September 2005. During this deployment, the 1st Battalion 69th Infantry Regiment equipped one soldier from each ten man squad with a M14 rifle fitted with a Springfield Armory, Inc. Third Generation scope mount and Tasco rifle scope but no bayonet or USGI cleaning kit. Towards the end of the its deployment, the 1st Battalion 69th Infantry Regiment was receiving new production Check-Mate Industries twenty round magazines for its M14 rifles. Staff Sergeant John Chalker of the 1st Battalion 69th Infantry Regiment used his USGI Winchester M14 rifle with iron sights to engage the enemy while serving as the turret gunner aboard a Humvee providing security for Airport Road. Airport Road in Baghdad was dubbed the most

dangerous road in the world because of the heavy number of improvised explosive devices planted and detonated by the enemy on this road. Staff Sergeant Chalker preferred to use his M14 rifle in lieu of the turret mounted M240 belt fed machine gun because he could respond faster to ambushes.

During the late summer and early fall of 2004, two U. S. Army armorers rebuilt and upgraded a batch of M14 rifles into Squad Designated Marksman rifles for the U. S. Army 10th Mountain Division. This accurizing work included unitizing the gas systems, reaming the flash suppressors, tuning the triggers, bedding the stocks and fitting the receivers with Tasco (Overland Park, KS) 10 X 40 mm scopes. In the fall of the same year, the U. S. Army National Guard 42nd Division upgraded its 108 M14 rifles in preparation for deployment to Iraq. The M14 rifles were upgraded with Sadlak Industries (Coventry, CT) steel scope mounts, Tasco 10 X 40 mm scopes, Badger Ordnance (North Kansas City, MO) scope rings, Harris bipods, Butler Creek scope covers, and BlackHawk Products Group (Norfolk, VA) cheek pads. Sadlak Industries, LLC provided instruction to the 42nd Division soldiers on installing the scope mounts. The 42nd Division, along with its M14 rifles, deployed to Iraq in early 2005. The M14 rifles are used in the 42nd Division's Long Range Surveillance detachment.

Staff Sergeant Scott Lawson carried and put to good use a scoped M14 rifle during heavy combat in Fallujah, Iraq in November 2004 as a member of the weapons platoon in A Company 2nd Battalion 2nd Infantry Regiment 1st Infantry Division. A Company 1st Battalion 22nd Infantry Regiment of the U. S. Army 4th Infantry Division left Fort Hood, TX left in November 2005 for deployment to Iraq. Sergeant Cody Hoefer of A Company was issued a M14 rifle in a wood stock along with his M16 style carbine for duty in Iraq. In January 2007, the U. S. Army National Guard 128th Military Police Company employed M14 rifles in countersniper duty in Muqdadiyah, Iraq. The M14 rifle is still very much a useful tool on the modern battlefield and is far from obsolescence.

The M14 in the U. S. Navy

U. S. Navy ships inventory the M14 rifle for several purposes. M14 rifles are maintained by Gunner's Mates on surface ships and Missile Technicians or Fire Control Technicians on submarines. The M14 rifle is used to shoot a line (rope for landlubbers) from one ship to another during underway replenishment, to arm the Shark Watch during swim call, to repel boarders, for use in burial-at-sea ceremonies, and to arm the security detail during loading and off loading of nuclear weapons on submarines.

Navy SEAL Team 1 operating out of the Rung Sat Special Zone in the Republic of Viet Nam was equipped with the M14 rifle until November 1967. Since the American involvement in the Republic of Viet Nam, U. S. Navy SEAL Teams have equipped themselves with the M14, M14 Sniper Security Rifle (SSR) or the Mk 14 as the needs of the mission dictated. Chuck Pfarrer led an eight man SEAL Team in 1983 in Beirut as

part of the multi-national force that attempted to maintain peace during the Lebanese Civil War. Two of the SEALs in his squad were armed with M14 rifles. U. S. Navy sailors, presumably SEALs, operating with Kilo Company 3rd Battalion 8th Marines used a Mk 14 Mod 0 rifle to engage insurgents near Ramadi, Al Anbar Province, Iraq on May 13, 2006.

There are times when use of the M14 rifle is totally unexpected but very useful. One such instance occurred while the ballistic missile submarine *USS Nathan Hale* SSBN 623 was on deterrent patrol in 1985. As a Lafayette Class SSBN, the *USS Nathan Hale* was equipped with a device known as the "towed array." The towed array could be described as a black steel box about the size of an automobile. It contained an assortment of radio and sonar equipment. The towed array was attached to a steel cable that could be reeled in or out from its compartment within the steel decking just aft of the missile tube hatches. With the towed array deployed, the submarine was limited to the speed, depth and dive angle it could do to prevent breaking the cable and losing the towed array. The benefit was that the submarine could remain submerged but continuously receive radio messages. While on deterrent patrol one day somewhere in the Atlantic Ocean, the Officer of the Deck forgot that the towed array was reeled out. He ordered a bell (order to change speed) too fast for the steel cable attached to the towed array. The towed array detached from the boat (submariner term for submarine) and was quickly floating on the ocean surface.

Considering the tactical situation and the sensitive nature of the equipment lost, the Captain ordered the boat to surface. After the ship had ventilated, the ship's Captain, Commander J. W. Hamburg, and Missile Technician Second Class MacPherson armed with a M14 rifle laid (hurried quickly) to the bridge. The Captain ordered the Missile Technician to sink the towed array. After cycling 134 times, the M14 rifle had put enough holes in the towed array casing to make it sink to the bottom of the Atlantic Ocean. The boat quickly submerged immediately thereafter and carried on its deterrent patrol without further incident.

In May 2007, the U. S. Navy held a total of 4,354 M14 rifles aboard its ships. In the summer of the same year, the U. S. Navy transitioned to the M16A3 for boarding parties and force protection. About 2,000 M14 rifles aboard its ships were replaced with the M16A3. The *USS Vandegriff* FFG 48 was scheduled in September 2007 to be the last ship to turn in the M14 rifle. However, two M14 rifles were retained on each ship for line throwing duty. In 2009, the U. S. Navy turned in 30,000 M14 rifles to Rock Island Arsenal, most likely from its storage facilities. Rock Island Arsenal disassembled 1000 of these rifles to support combat operations of the U. S. Army.

The M14 in Other Service

The M14 rifle remains in use today with U. S. Air Force pararescue jumpers and combat controllers, at the U. S. Air Force, Military and Naval Academies, Virginia Military Institute (VA), The Citadel (SC), North Georgia College & State University (GA), Norwich

University (VT), and university ROTC units. As of mid-2007, the U. S. Air Force had about 3,500 M14 rifles in its inventory. M14 rifles are used for shipboard security and line throwing aboard U. S. Navy Military Sealift Command and U. S. Department of Transportation Maritime Administration ships based in Saipan, Commonwealth of the Northern Mariana Islands. The U. S. Customs and Border Protection Office of Air and Marine uses M14 rifles fitted with Sage International, Ltd. stocks to protect the United States against terrorists and drug smugglers.

The National Defense Act of 1916 provided for reserve military forces of the United States. This law also established the Reserve Officer Training Corps (ROTC) and Army Junior ROTC to train civilian college and high school students in military science. ROTC programs were established to supplement the military service academies of the time, West Point and Annapolis. The firing pins are removed from M14 rifles at the service academies and ROTC units. In October 1963, Congress and President Kennedy expanded the Army JROTC program and extended it to the Navy and Air Force. This action was in response to the public outcry over Secretary McNamara's plan to defund JROTC units. Marine Corps JROTC units were issued M14 rifles by no later than 1970. The Marine Corps JROTC program expanded from fifty-seven high schools in 1979 to 220 by 2007. M14 JROTC rifles were demilitarized by plugging the barrel and welding it to the receiver, removing the firing pin and welding over the bolt firing pin front hole. In 2008 and 2009, JROTC M14 rifles were replaced with M1903 rifles. The parts from the JROTC M14 rifles, minus barrels and bolts, were sold by CMP to the surplus market in 2009 and 2010.

As an aside, Mitch Mateiko, owner of Brookfield Precision Tool, rebuilt a batch of M14 rifles at Fort Devens, MA for the U. S. Air Force within days prior to the start of Operation Desert Storm. The BATF attempted to confiscate the M14 rifles from Mr. Mateiko because he did not possess a Federal Firearms License. However, the BATF backed off when it became clear to the BATF Special Agents that the U. S. military would not stand for loss of its equipment.

In August 2004, the U. S. Army Tank Automotive Command at Rock Island Arsenal published a notice of intent to purchase 350 M14 chromium plated parade rifles with accessories from Springfield Armory, Inc. under a sole source contract. A 2005 purchase order by the same Army command required delivery of eight M1A parade rifles by August 2005. The eight M1A rifles were supplied by Springfield Armory, Inc. These were non-functioning standard model M1A rifles. Each of the eight M1A parade rifles had a wood stock, a twenty round magazine, and bayonet and scabbard. All rifle metal parts were chromium plated. The M14 rifle is frequently used as a ceremonial rifle by drill teams and color guards and at Arlington National Cemetery. The Afghanistan Army uses chromium plated M14 rifles for ceremonial purposes, e.g., the funeral for former King Mohammed Zahir Shah on July 24, 2007.

Arlington National Cemetery became a military burial ground in May 1864 for the Union Army during the Civil War. The land had been previously owned by Confederate Army General Robert E. Lee but it was illegally seized by the Federal government in 1862. In 1882, the U. S. Supreme Court declared the government guilty of trespassing and ordered the return of the land to the Lee family. With more than 10,000 soldiers buried on the property, George Washington Custis Lee, oldest son of Robert E. and Mary Lee, sold the land to the U. S. government for \$150,000.00. Arlington National Cemetery is one of two cemeteries administered by the U. S. Army. The Tombs of the Unknown at Arlington National Cemetery contain the bodies of three unknown soldiers, one each from World Wars I and II and the Korean War. The Tombs of the Unknown are guarded around the clock by U. S. Army soldiers in E Company of the 3rd Infantry Regiment, also known as The Old Guard. The Old Guard has guarded the Tombs of the Unknown since April 06, 1948 without interruption. The M14 rifle has been in service with the 3rd Infantry Regiment continuously since the early 1960s. The Tomb Guard uses M14 rifles with wood stocks modified to streamline the grip area.

In 1972, Watervliet Arsenal destructively tested chromium plated M14 rifle barrels to predict useful life of 175 mm M113A1 artillery barrels. M14 rifle barrels were chosen as test specimens because it was more affordable than firing large artillery pieces to barrel failure. At least thirty-two modified M14 barrels were tested to failure by hydraulic pressure, cartridge firing or both. The M14 barrels were machined on a lathe to reduce the outside diameter to produce early failure. Some of the barrels were hydraulically cycled seven times per minute to a pressure of 44,300 psi. Other barrels were fired six times per minute using M80 cartridges. The testing of M14 barrels proved useful in determining service life for artillery cannon barrels. Warning: Under no circumstances, do not attempt this testing. The information is presented for educational purposes only.

Some federal, state and local law enforcement agencies in the United States have M14 rifles and magazines in inventory on loan from the U. S. Army through the Section 1033 program. The authority for this federal program is found in Section 1033 of the National Defense Authorization Act for Fiscal Year 1997. It is codified at Title 10 United States Code Part IV Chapter 153 Section 2576 (a). The Secretary of Defense may transfer excess personal property to law enforcement agencies with officers empowered to arrest and apprehend. The Section 1033 program is administered by the Defense Logistics Agency Law Enforcement Support Office (DLA LESO). Since 1995, the Law Enforcement Support Office has transferred excess DOD equipment such as aircraft, vehicles, cameras, computers, electric generators, military clothing, boots, night vision goggles and weapons to law enforcement agencies. Before October 01, 1996, this program was known as the Section 1208 program. As part of the lengthy paperwork process, a 1033 program M14 rifle will be registered with the BATFE NFA Branch by completed ATF Form 10.

A few police departments have replaced the selector locks with selector switches in M14 rifles obtained through the 1033 program. In June 2005, loaning of M14 rifles was

temporarily suspended to law enforcement agencies through the 1033 program while the XM110 rifle trials were held. In July 2006, the DLA LESO instituted a mandatory inventory check of all firearms on loan through the 1208 and 1033 programs in order to verify its records. Pending requests for firearms were placed on hold until each state had completed the inventory check. Firearms obtained through the 1208 and 1033 programs are on loan from the U. S. Army and cannot be sold under any circumstances. After proper approval, the law enforcement agency can transfer the firearms to another law enforcement agency participating in the 1033 program or return them to Rock Island Arsenal. As of May 2008, 3,638 M14 rifles were on loan from the U. S. Army.

Accurized and scoped M14 rifles are also employed by a number of U. S. federal agencies such as the Bureau of Indian Affairs, the Diplomatic Security Service, and the Department of Energy Office of Secure Transportation (OST). The OST is the agency responsible for the safe transport of nuclear weapons and associated components and special nuclear materials. National Park Service Park Rangers have used M14 rifles in armed overwatch of tourists visiting the Organ Pipe Cactus National Monument. In 2012, U. S. Border Patrol agents in southern Arizona fielded 1033 program M14 rifles. Designated as the M14E by the Border Patrol Office of Training Development, it met the need for a weapon with barrier penetration superior to the 5.56 mm NATO cartridge.

Following the tragic end of the Branch Davidian community in Waco, TX on April 19, 1995, five semi-automatic only M14 type rifles, seventy-two M14 magazines, ten M14 magazine springs and one M14 trigger component were among the firearms and related items pulled from the ashes by the Texas Department of Public Safety.

The M14 in the Arts and Entertainment

While not related to military service or law enforcement the M14 type rifle has been used dramatically in entertainment media such as films, fine art, photography, television shows and video games over the years. A photograph of a pre-teen boy and U. S. Marines firing the M14 rifle even made its way into a children's book, *Do You Know What I Am Going To Do Next Saturday?* The first book with a M14 rifle on its cover was the sixth edition of *Small Arms of the World*.

Films - The M14 rifle was prominently featured in the 1966 U. S. Marine Corps recruiting film *Your First Eighty Days* (MH-10143). A list of big screen and television films with the M14 type rifle includes over 100 titles:

1960s - *Goldfinger* (1964), *Follow Me, Boys* (1966), *The Green Berets* (1968)

1970s - *Tribes* (1970), *White Lightning* (1973), *The Omen* (1976), *Billy Jack Goes To Washington* (1977), *Black Sunday* (1977), *Slap Shot* (1977)

1980s - *A Rumor of War* (1980), *Uncommon Valor* (1983), *Hard Knox* (1984), *Missing In Action* (1984), *Purple Hearts* (1984), *Crocodile Dundee 2* (1986), *Raw Deal* (1986), *The Manhattan Project* (1986), *Full Metal Jacket* (1987), *Gardens of Stone* (1987), the director's cut edition of *Lethal Weapon* (1987), *Saigon Commandos* (1987), *The Living Daylights* (1987), *Dear America: Letters Home from Vietnam* (1988 theatrical release), *Distant Thunder* (1988), *Empire of Ash* (1988), *The Siege of Firebase Gloria* (1988), *84 Charlie Mopic* (1989), *Counterforce* (1989), *Born On The Fourth Of July* (1989)

1990s - *Bullet in the Head* (1990), *NAVY SEALS* (1990), *The Hunt for Red October* (1990), *The Prisoner* (1990), *Dogfight* (1991), *Flight of the Intruder* (1991), *Highlander II: The Quickening* (1991), *Hot Shots!* (1991), *South Central* (1992), *A Perfect World* (1993), *Demolition Man* (1993), *Hot Shots! Part Deux* (1993), *Clear and Present Danger* (1994), *Forrest Gump* (1994), *On Deadly Ground* (1994), *The Shawshank Redemption* (1994), *Congo* (1995), *Panther* (1995), *Star Hunter* (1995), *Mars Attacks!* (1996), *My Fellow Americans* (1996), *Tremors 2* (1996), *Money Talks* (1997), *The Postman* (1997), *A Bright Shining Lie* (1998), *Rogue Force* (1998), *The Negotiator* (1998), *True Story of The Big Red One* (1998), *Dick* (1999), *Dogma* (1999), *The General's Daughter* (1999)

2000s - *A Better Way To Die* (2000), *Thirteen Days* (2000), *Black Hawk Down* (2001), *Spy Game* (2001), *The Believer* (2001), *Path To War* (2002), *Tears Of The Sun* (2003), *The Fog of War* (2003), *The Rundown* (2003), *Resident Evil: Apocalypse* (2004), *The Punisher* (2004), *Alien Apocalypse* (2005), *Mr. & Mrs. Smith* (2005), *Munich* (2005), *State of the Union* (2005), *Stealth* (2005), *The Island* (2005), *xXx: State of the Union* (2005), *Ghetto* (2006), *Ghosts of Cite Soliel* (2006), *Love Comes to the Executioner* (2006), *Skinwalkers* (2006), *US vs John Lennon* (2006), *28 Weeks Later* (2007), *Across The Universe* (2007), *Beaufort* (2007), *Big Stan* (2007), *Hot Fuzz* (2007), *My Name Is Bruce* (2007), *Postal* (2007), *Shooter* (2007), *The Devil Came On Horseback* (2007), *We Own The Night* (2007), *Body of Lies* (2008), *The Objective* (2008), *Black Dynamite* (2009), *The Messenger* (2009), and *X-Men Origins: Wolverine* (2009)

2010s - *Kick-Ass* (2010), *Red* (2010), *Restrepo* (2010), *Storm In An Hour Glass* (2010), *The Objective* (2010), *Winter's Bone* (2010), *Abduction* (2011), *Fast Five* (2011), *Act of Valor* (2012), *Battleground* (2012), *Jack Reacher* (2012), *Osombie* (2012), *Savages* (2012), *The Hunger Games* (2012), *Muhammad Ali's Greatest Fight* (2013), *Olympus Has Fallen* (2013), *Pain & Gain* (2013), *The Butler* (2013), *The Last Stand* (2013), and *Daylight's End* (2014)

The original 1980 three hour twenty minute unedited version of *A Rumor of War* and *Born On The Fourth Of July* are the only two full-length entertainment films known to contain a scene of the M14 type rifle in automatic fire. In 1987, *A Rumor of War* was re-released as a three part mini-series without the scene of the M14E2 in action. *Forrest Gump* is the only commercial film known to show the disassembly of the M14 rifle. Two Rock SOPMOD M14 rifles were built for and used in the film *Mr. & Mrs. Smith*.

Fine Art – The M14 rifle was sculpted into two statues at Fort Dix (NJ). The statues pay tribute to the U. S. Army infantryman. Both statues are the same but have different inscriptions. Known as *The Ultimate Weapon*, both statues depict a 1950s era U. S. Army infantryman charging forward in battle as he gives a war cry with a M14 rifle at the ready. The base commander, Lieutenant General Bruce C. Clarke, ordered a statue to be built to symbolize the Army infantryman. With no budget at all, the original statue was built over an eighteen month period from 1957 to 1958 using railroad track and other scrounged material by Army Specialist 4 Steven Goodman and Private Stuart Scherr.

Over time, weather had adversely affected the statue even though some repairs had been made. The sling of the M14 rifle on the original statue is partially missing from damage incurred at some point. In 1988, private funds were raised to build a new copy of the original. By a coincidental sequence of events in 1989, Mr. Goodman learned of the effort to recast the statue and became involved in the restoration effort. The new statue was cast in bronze at a foundry near Princeton, NJ using molds made from the original. The new statue, 14 feet tall and weighing over 300 pounds, was unveiled in August 1989. Today, the original statue is situated behind a review stand adjacent to Sharpe Field while the newer statue is prominently located in Infantry Park at the center of the base.

Fort Dix was an Army training center between 1917 and 1997. At various times, Fort Dix was also home to various Army infantry divisions. On October 01, 1997, Fort Dix was transferred to the U. S. Army Reserve Command. Since then, it has been a training center for Army Reserve and Army National Guard troops.

Around 1960, the Rainlap Company printed a U. S. Army recruiting advertisement (item number 15-150) for outdoor billboards. The advertisement was made of twelve thick sheets of paper that measured about 8 ½ feet by 19 ½ feet when posted together. The color illustration advertisement showed an Army paratrooper rushing forward, head on, with his M14 rifle at port arms. The top of the poster read ALL MAN . . . ALL ARMY! In August 1963, the U. S. Government Printing Office produced a full color life-sized stand up poster for recruiting offices (catalog number RPI 251). It featured a U. S. Army soldier charging forward with a M14 at the ready.

Max D. Crace was stationed in the Republic of Viet Nam in 1971 while serving in the U. S. Air Force. As an artist, he captured the life of the serviceman in Viet Nam in his illustrations. His drawings are known for their accurate detail of the uniforms and equipment worn and carried in the war.

Mr. Crace's color drawing, "One Shot One Kill" depicts a U. S. Army sniper team poised to take on the enemy with an XM21 rifle. A black and white illustration from Mr. Crace depicts a Marine readying to fire his M14 with commercial telescope and improvised mount from a kneeling position. The U. S. Army sniper equipped with a suppressed XM21 fitted with an AN/PVS-2 scope aiming for a shot is another well illustrated item of Mr. Crace's artistic talent.

The Max Crace drawing, "BOOM BOOM ROCK", depicts an American soldier with a M14 rifle leaning against a large boulder at a lookout point on Monkey Mountain. This spot on the mountain provided a panoramic view of the water and white sands of China Beach. The boulder was marked BOOM-BOOM ROCK MONKEY MOUNTAIN VIETNAM by no later than 1968. Son Tra Mountain, or Monkey Mountain, was an American military base at the north end of China Beach. Bac My An Beach, or China Beach, was located about four miles southeast of Da Nang, Quang Nam, Republic of Viet Nam. It was home to a U. S. Army medical hospital and a Rest and Recreation facility during the war. Presumably, the large boulder was so inscribed because it was a popular location for romantic interludes. Mr. Crace later drew an illustration of a U. S. Navy SEAL employing a M14 SSR rifle in Kuwait in February 1991 during the First Gulf War. As he did with his Viet Nam era illustrations, this drawing was accurate down to the last detail including the rubber pads on the Harris bipod legs. Artist Andre Tracol (Montpellier, France) has created several series of technical posters illustrating the external and internal views of over 400 firearms, including the M14.

Though the M14 rifle doesn't appear in the film, it is a part of the DVD cover art for the 2006 television movie *The Veteran*. Harold Chrismon has created a work of art out of the M14 itself by burning combat images into wood M14 stocks. Graphic artist and illustrator Phil Nguyen (Dogfight Ink) has added his creative flair and attention to detail to turn an exploded view of M14 parts diagram into a fine art lithograph print. Mr. Nguyen has also illustrated different M14 variations in color: M14 DMR, M14, M14A1, Springfield Armory, Inc. M1A-A1 Bush with folding stock, commercial M14 with a McMillan MFS-14 stock and scope, M14 SE, M14 SSR, M21, M39 EMR, Mk 14 Mod 0, Mk 14 Mod 1, and the M14 with a Knight's Armament Company RAS-14 and scope.

From 1987 to 1990, Springfield Armory, Inc. sold two jewelry items, a tie clasp and a hat / jacket pin. The clasp and the pin were both of a miniature M14 made of rhodium and polished gold. After the M14SE rifle was introduced in 2004, Ron Smith of Smith Enterprise, Inc. made a silver ring to commemorate it. It was made of sterling silver. The lettering, CRAZY HORSE M14, was soldered on by hand. A five pointed star was added above M14 to denote active duty military service or veteran or law enforcement status. He also made a similar silver medallion. In 2010, Northwest Territorial Mint (Federal Way, WA) offered a Marine Veteran bookmark with a miniature antique brass likeness of a M14 rifle at one end of the scarlet and gold ribbon (Item 60570).

Photography – Still photographs of the M14 rifle and its end users can be divided into three forms, media news journalism snapshots, combat photographs, and photographic art. It is the author's contention that examples of all three forms of photography exist of the M14 rifle. *Nam A Photographic History* has some splendid examples of each photographic form. Actress Cathy Rankin adds grace and beauty to a folding stock 18 " barreled M14 rifle in one of the monthly photos for the Dillon Aero 2006 Calendar.

There is one photograph including the M14 rifle that stands out as a representative example of all three forms of photography. While not central to the subject, the photo does record the M14 as the rifle carried by those affected by the tragic event. Dickey Chapelle was a war correspondent who traveled with U. S. Marines in combat during World War II. She filed stories with and submitted photographs to publications such as *National Geographic*, *Life*, and *Reader's Digest*. After the war, she photographed combat from the vantage point of rebel groups in Algeria, Cuba and Hungary. Later, she was the first female member of the press to parachute jump with American troops into combat while on assignment in the Republic of Viet Nam, and in her forties at that. Working for the *National Observer*, she returned to the Republic of Viet Nam in the fall of 1965 to photograph and write again of the true story of the U. S. Marine Corps in action. She was so well respected by the U. S. Marine Corps that the Commandant, General Wallace M. Greene, Jr., in 1965 presented her with the Marine Corps eagle, globe and anchor device from his own uniform.

On the fateful morning of November 04, 1965, Dickey Chapelle went on patrol near Chu Lai, Quang Tin with a platoon of U. S. Marines. She was walking second in the column behind the platoon leader, Lieutenant Mauriski. The platoon had just left camp when the platoon leader tripped on a wire. This mishap set off a booby trapped mine. The resulting explosion injured four U. S. Marines and threw Dickey Chapelle twenty feet while a piece of shrapnel punctured her carotid artery. She passed away minutes later on the way to the hospital inside a helicopter. In her last minutes, U. S. Marine Corps Chaplain John Monamara prayed over her and administered last rites as the blood flowed from her neck. Behind the Chaplain, three U. S. Marines watched intently, each armed with a M14 rifle.

This tragedy was captured on black and white film by *Associated Press* photographer Henri Huet. Dickey Chapelle was the first American journalist to be killed during the war in Viet Nam. She once informed a General, "When my time comes, I want it to be on a patrol with the Marines." Henri Huet and three other combat photographers were killed on February 10, 1971 when the helicopter transporting them was shot down by the enemy over Laos.

Philip Jones Griffiths spent three years in the Republic of Viet Nam, 1968 through 1970, photographing all aspects of the war. Griffiths captured the human suffering in war as well as anyone in the 1971 volume, *Vietnam Inc.* The majority of the photographs of this book should be considered photographic art while others are worthy of a headline story or a magazine cover. Included in this collection of war time black and white still photos are three which contain the M14 rifle: Limits of Friendship, Wounded VC Suspect and Forced Urbanization. In each of the three photographs, the M14 rifle is carried by an American soldier or Marine as he deals with the Vietnamese people. These three photographs speak clearly about the human condition at the artistic level.

Larry Burrows was another combat photographer that captured historical events and gut wrenching scenes on film, both black and white and in color. He photographed the first American troops, the 3rd Battalion 9th Marines, carrying M14 rifles, to come ashore on March 08, 1965 in the Republic of Viet Nam at Red Beach 2, ten miles north of Da Nang, Quang Nam. His photographs of the war in Viet Nam were showcased in a number of issues of *Life* magazine in 1963, 1965 and 1966. Larry Burrows was known to consistently put himself at the front of the action. The day before he was killed, he pulled an Army of the Republic of Viet Nam (ARVN) soldier from a burning armored personnel carrier. The next day, he was aboard the fatal helicopter flight with Henri Huet over Laos.

Perhaps the most artistic combat photograph ever taken of the M14 rifle was one by Larry Burrows on October 05, 1966, or very shortly thereafter, during Operation Prairie atop Hill 484 in Quang Tri province, Republic of Viet Nam. In that action, 1,397 North Vietnamese Army soldiers were killed and twenty-seven were taken prisoner while 239 Americans were killed and 1,214 wounded in action. The color photograph is a hill top view overlooking a valley and distant mountain range with cloudy skies in the background. In the fore ground is a fallen and defoliated tree trunk lying next to a Marine helmet and a M14 rifle with inserted magazine pointed away from the camera. This photograph graces the front cover of *Requiem*, a book about combat photographers who were killed during the war in Viet Nam.

Broadcast Network Television - The M14 rifle made its entertainment debut on the NBC broadcast television drama series *The Lieutenant* starring Gary Lockwood and Robert Vaughn. The series depicted a U. S. Marine infantry unit stationed at Camp Pendleton (CA). The series received strong support from the U. S. Marine Corps. The M14 was next featured in the credits scenes of the hit CBS broadcast television situation comedy *Gomer Pyle, USMC* starring Jim Nabors and Frank Sutton.

The M14 rifle was first animated for entertainment on October 23, 1964 during the "Treasure of the Temple" episode in the ABC network series *Jonny Quest*. In the teleplay by Walter Black, Race Bannon (voice by Mike Road) carries an M14 rifle.

The CBS broadcast television weekly series *Tour of Duty* first aired on September 24, 1987. The show was a fictional account of the struggles of a U. S. Army infantry platoon in the Republic of Viet Nam between October 1967 and January 1969. The firearms, including the M14 rifles, and military vehicles used in taping *Tour of Duty* were as historically accurate as possible. The third season had two episodes depicting use of the M14 rifle. In one episode, a Central Intelligence Agency (CIA) employee is attached to an Army squad of soldiers. The CIA employee successfully engages a Viet Cong Lieutenant with the M14 rifle he is carrying. The result is a firefight that involves the infantry squad. The CIA employee uses the M14 rifle during the firefight. The other episode from the last season involves a helicopter pilot that tires of a persistent sniper outside the Special Forces "A" Camp. Armed with a scoped M14 rifle, he takes it upon himself to hunt down the sniper. He is able to finally silence the sniper who turns out to be a woman. The M14

type rifle was seen in scenes of fictional 1960s Viet Nam combat on the NBC broadcast television drama *American Dreams*.

Cable Television - The M14 rifle was shown in the "Flashpoint Vietnam" and "Terror in Paradise" episodes in the Fox News Channel cable television weekly documentary *War Stories* hosted by Oliver North. *War Stories* first aired in May 2001 and ran for sixty-four sixty minute episodes through four seasons. The M14 type rifle has also been featured at several times on the History Channel cable television weekly programs *Mail Call* and *Lock N' Load* hosted by former U. S. Marine, Viet Nam veteran, actor and M14 fan R. Lee Ermev.

Music Video - The M14 rifle is carried by American troops in back drop film footage of three country music videos, *Whiskey Lullaby* by Brad Paisley and Alison Krauss (2004 Arista Nashville), *8th of November* by Big & Rich (2005 Warner Bros.) and *Arlington* by Trace Adkins (2005 EMI).

Video Games – Several M14 rifle variants are equipment options for players in these video games: *America's Army: Proving Grounds*, *ArmA II*, *ArmA III*, *Armed Assault*, *Army of Two*, *Battlefield Bad Company 2*, *Battlefield 3*, *Battlefield 4*, *Battlefield Vietnam*, *Call of Duty: Black Ops 1 and 2*, *Call of Duty: Ghosts*, *Call of Duty: Modern Warfare 1, 2 and 3*, *Call of Duty 4: Modern Combat*, *Combat Arms*, *Counter-Strike Online*, *Dark Sector*, *Delta Force - Army of Two*, *Delta Force - Black Hawk Down: Team Force Sabre*, *Far Cry 3*, *Ghost Recon: Future Soldier*, *Ghost Recon 2*, *Ghost Recon 2: Summit Strike*, *Ghost Recon Advanced Warfighter 2*, *Grand Theft Auto Vice City Stories*, *Hitman Blood Money*, *Insurgency: Modern Infantry Combat*, *Jagged Alliance 2*, *Jagged Alliance: Back In Action*, *Killing Floor*, *MAG*, *Medal of Honor*, *Medal of Honor: Warfighter*, *Men of Valor*, *Metal Gear Solid 4: Guns of the Patriots*, *Operation 7*, *Operation Arrowhead*, *Operation Flashpoint: Cold War Crisis*, *Operation Flashpoint 2: Dragon Rising*, *Operation Flashpoint: Red River*, *Payday 2*, *Project Reality*, *Rainbow 6 Raven Shield*, *Rainbow 6 Rogue Spear*, *Resistance: Fall of Man*, *Resistance: Fall of Man 2*, *Shellshock: Nam '67*, *Shellshock 2: Blood Trails*, *Silent Hill: Homecoming*, *SOCOM: Confrontation*, *SOCOM II*, *SOCOM 3*, *SOCOM US Navy SEALs Combined Assault*, *SOCOM 4: U.S. Navy SEALs*, *State of Decay*, *Stubbs the Zombie*, *Tom Clancy's The Division*, *Vietcong 2*, *Vietcong: Fist Alpha*, *Vietcong: Purple Haze*, *Vietnam: Line of Sight*, and *X-COM*.

Toy M14 - Louis Marx and Company was started by Louis and David Marx of New York City in 1919. The company made and sold Marx Toys brand toys in the United States and overseas for several decades. By the 1950s, Louis Marx and Company was the largest toy company in the world. Marx toys could be found in local dime stores and in Sears, Roebuck & Co. and Montgomery Ward shopping catalogs.

During the 1950s, the company manufactured and sold a toy M14 rifle. The black and brown color molded plastic M14 was 34.5 " long. It had a battery compartment in the butt stock that was accessed through a hinged plastic door. When the trigger was pulled, the

toy emitted an electrically generated gun firing sound through perforations in the integral "magazine." The "magazine" was marked USARMYM-14 on the right hand side. Louis Marx retired in 1972 and sold out to Quaker Oats Company. Unfortunately, the Marx Toys brand did not fare well due to changing market conditions of the 1970s. Quaker Oats sold the Marx Toys business in 1976 to a British toy manufacturer, Dunbee-Combrex-Marx. The new owner struggled in the sagging British economy of the late 1970s. The Marx Toys brand was no longer by 1978. Dunbee-Combrex-Marx went bankrupt in 1980. Today, original Marx Toys brand items are sought after by collectors.

Deluxe Reading (Elizabeth, NJ) was a toy manufacturer from the 1950s to the 1970s. Its most popular product line, Topper Toys, was the brand for a series of full size replica plastic toy guns in the 1960s. Two of these were the Johnny Eagle Lieutenant M14 rifle and M1911 pistol sold in 1965 as a set for boys wishing to "play Army." The Johnny Eagle series play guns were very realistic in appearance and function. The Johnny Eagle M14 magazine could be loaded with plastic bullets. It could fire caps or plastic bullets and eject shells upon firing. The toy M14 had an adjustable sling and its rear sight knobs could be turned to simulate setting of the "iron sights."

A miniature model M14 kit was produced by Model Weapons, Inc. (then P. O. Box 581 Oceanside, CA) in 1959. The Majix series M-14 Rifle kit included a leather sling, walnut stock and several die cast parts for the model hobbyist to assemble. Fifty years later, Dragon Models USA brought to market a one-third scale model M14 rifle. Three choices of plastic stock were offered for the pre-assembled plastic model, black, camouflage (Item # DRA1304) and simulated wood (Item # DRG76010). The Dragon model had an overall length of 14.5 " and its magazine was detachable.

Todd McFarlane was an accomplished comic book writer and artist for Marvel/Epic Comics when he and other co-workers formed their own publishing company in 1992. In May of that year, he debuted the *Spawn* comic series. Mr. McFarlane's *Spawn* comics sold so well that he established McFarlane Toys in 1994 to produce the story characters as toy action figures. By 2006, McFarlane Toys had become the fifth largest action figure manufacturer in the United States. The Arizona based company produces many different series of action figures including sports and military professionals. The McFarlane's Military Series toys are 6 " scale action figures painted in very accurate detail to depict present-day U. S. military men in combat. The Military Series' figures are suitable for ages 13 and older. The Military Series 3 Army Ranger Sniper figure was released for sale in April 2006. It is an Army Ranger equipped with a M21 rifle while a M16 style carbine is slung off the back and a 9 mm pistol is holstered. The figure's head, arms and hands can be moved to change its pose. Hot Toys Limited released its 12 " action figure, U. S. Army 10th Mountain Division Sniper, in April 2008 to the public. This toy was outfitted with uniform, more than twenty accessories, a pistol and a M14 EBR.

The Hudson brand M14 toy rifle is a very realistic model for those who cannot own a military firearm or for use as a film or theatrical prop. The Hudson MG-HD-M14M toy rifle

is made in Japan. The Hudson toy M14 uses a blowback action to feed, extract and eject cycle dummy non-firing cartridges from its twenty round magazine. The Hudson toy is a 1:1 scale replica made of metal and wood. It weighs 8.6 pounds and can be field stripped and assembled just like a M14 rifle. The rear sight, safety, selector switch and butt stock storage compartment door are functional. The Hudson toy M14 is supplied with a factory manual and ten dummy cartridges. Extra magazines and cartridges are factory options.

Replica and Airsoft M14 - In 2005, Vietnam War Guns (Tokyo, Japan) marketed a non-firing full size replica M14 made from metal and wood. The replica M14 could cycle non-firing replica cartridges and be disassembled just like the genuine article. AGM, G&G, G&P, Leapers, Inc., The Kapowwe Company, and Tokyo Marui produced airsoft M14 rifles. These were full scale electrically operated replicas that fire 6 mm pellets. In the United States, an airsoft M14 could be identified by the orange color of the muzzle.

The AGM TSD M14 electric rifle was offered in black color. It was built with a metal outer barrel, metal internal parts and metal cocking handle. The Tokyo Marui M14 had a traditional wood stock appearance. G&G offered the airsoft enthusiast a choice of the full size M14 or the shorter SOCOM 16. Both G&G models used a magazine with a capacity of 470 pellets. The G&G M14 replicas fired pellets at a velocity of 330 feet per second. The G&G SOCOM 16 model could be fitted with a scope mount and optical sight. G&P introduced six airsoft M14 models in 2008 and 2009: M14 DMR, Mk 14 Crane Proto in sand and olive drab, and EBR Mk 14 Mod 0 in black, silver and Navy Seal. G&P airsoft models were made with metal parts and high impact plastic stocks. The magazine capacity was 160 rounds of 6 mm pellets. The muzzle velocity was 335 to 350 feet per second. The Kapowwe M14 had a plastic stock and metal parts such as the charging handle, barrel and 400 round magazine. It fired pellets at 329 feet per second in either semi-automatic or automatic mode. Daisy Outdoor Products (Rogers, AR) produced the .177 caliber CO₂ powered semi-automatic only Model 14 rifle. The length was 43.5 " and it weighed 4 pounds. The magazine capacity was sixteen pellets or BBs. The muzzle velocity was 700 feet per second.

The Leapers, Inc. Special Ops M14 Sniper model featured a metal receiver and barrel. It was available in green, black, Army digital and walnut color stocks. Leapers, Inc. made one barrel and two side three point scope mounts for its airsoft M14. The Leapers, Inc. side three point scope mounts utilized a Weaver rail. The rail lengths were 5.5 " for item number LP-MNT-914 and 6 " for item number LP-MNT-914V2. The Tactical Tri-rail Metal Handguard Mounting System, item number LP-MNT-HGM14TR, had three, six and twelve o'clock M1913 Picatinny rails. The twelve o'clock rail was the same length as the hand guard it replaced. The iron sights could be used with any of the three models. The Leapers, Inc. scope mounts were made from aircraft grade alloy aluminum. In late 2009, Fabsports Canada (Montreal, PQ) began marketing a steel Canadian made single slot Picatinny rail base that replaced the cartridge clip guide (catalog number FS-M14-RM). By May 2010, the steel single slot rail base was eclipsed by the Leapers UTG matte anodized alloy aluminum two slot rail base (catalog number MNT-M14-R02). Both rail

bases were supplied with a spacer, locking screw and hex head wrench for installation. Both cartridge clip guide rail bases were designed to be used in conjunction with the LP-MNT-HGM14TR mount.

Museum Collections

A number of Springfield Armory and Harrington & Richardson M14 rifles were transferred from the U. S. Army to the Springfield Armory Historical Museum (Springfield, MA). For the most part, these transfers occurred between September 14, 1959 and May 9, 1967. M14 rifle receiver serial number 2085 was transferred to the Museum on January 22, 1986 from Rock Island Arsenal. Some of the M14 rifles at the Springfield Armory Museum were transferred back to the U. S. Army (Rock Island Arsenal (IL), Watervliet Arsenal (NY), and Fort Lee (NJ)) between April 26, 1966 and May 18, 1972.

USGI T44 series and M14 variant rifles are displayed at a number of museums around the United States:

Infantry Museum (Fort Benning, GA) - M14 serial number 0001

MCRD Command Museum (San Diego, CA) - M14 serial number 622634

National Firearms Museum (Fairfax, VA) - M14 serial number 0006 and T44E4 serial number 1200

National Museum of the Marine Corps (Triangle, VA) - M14 serial numbers 28760, 368097, 882802 and 1077631

Ordnance Museum (Aberdeen Proving Ground, MD) - M14 serial number 907782

Rock Island Arsenal Museum (Rock Island, IL) - several M14 rifles including serial numbers 0013 and 0017

Springfield Armory National Historic Site (Springfield, MA) - see table in Appendix plus others too numerous to list

Watervliet Arsenal Museum (Watervliet, NY) - M14 serial number 9635 and others

West Point Museum (West Point, NY) - XM21 donated by Company D 2/5 Cavalry 1st Cavalry Division

Israel Defense Forces

The Israel Defense Forces (IDF) used the M14 as a sniper weapon system (SWS) from 1973 to 1997 when it was replaced by the M24 SWS. Israeli Military Industries built 10,000 sniper weapon systems out of the 35,000 rifles given to them by the United States in 1973 as a result of the Yom Kippur War. The remaining M14 rifles were disassembled for spare parts. The Israeli Defense Forces used M14 SWS rifles for fire support during the 1982 invasion of Lebanon. Optics on the Israeli M14 SWS rifles was either the EI-Op Nimrod 6X40 mm daylight scope or the Litton AN/PVS-2 night vision scope. In 1994, the EI-Op Nimrod day scope was replaced with the Swarovski Futonic 6X42 mm scope. As of 2005, the M14 SWS was still in use by the IDF Reserve.

The Israeli firearms designer Dr. Nehemiah Sirkis worked at Sardius in Israel in the 1970s and 1980s. He designed the 7.62 mm NATO caliber M26 sniper rifle based on the AK47. He also designed the bullpup conversion of the M14 type rifle known as the M36 while working in the 1980s for Sardius in Israel. Years later, Dr. Sirkis improved the Swartz firing pin lock on the M1911 type pistol and upgraded the Model 82 .22 LR rifle for Kimber Mfg., Inc. (Yonkers, NY).

The M36 appeared in Israel in the mid-1980s as the Sardius M36 SWS. Arms Corporation of America, Inc. made approximately ten units of the M36 in 1989 using Armscorp of America receivers. The M36 has high profile flip up iron sights. The M36 SWS was intended as a replacement for the M14 SWS. The Israel Defense Forces placed an order in the late 1980s for 1,300 M36 rifles, but Sardius only delivered fifty units. The company lacked the financial and technical resources to fill the order. Sardius went out of business in the early 1990s. Sardius was bought out by a company called Technical Consulting International (TCI) in Israel. TCI obtained a license from the government to produce the M36. Using surplus U. S. M14 rifles, TCI upgraded the M36 design, including installation of a carbon fiber stock. Dr. Sirkis worked on the M36 design improvements as an employee of TCI. TCI reintroduced the rifle as the M89 in the early 1990s.

There were two models, the M89AR with iron sights and the M89SR with a Leupold & Stevens, Inc. or Zeiss scope and no iron sights. The suppressed model was designated M89SR-SP. The overall length for the M89 was approximately 33.5 " for standard models or 40.5 " with the sound suppressor. The M89 had a 22 " fully floated barrel and a modified operating rod handle. The handle at the rear end of the operating rod was ground flat and a circular knob attached to the front end of the rectangular portion of the operating rod. Fully loaded with a twenty round magazine, the M89 weighed 13.8 pounds, while the M89SR-SP weighed 15.5 pounds with its sound suppressor mounted. M89 series rifles were built with Harris bipods. The M89SR-SP was used as a sniper weapon system for units concerned with concealment. It was issued mostly to two IDF Special Forces undercover units, Sayeret Duvedevan and Sayeret Shimshon. Sayeret Shimshon operated in the Gaza Strip until it was disbanded in 1994. The M89 was also exported for sale to other Special Forces units. Subsequent to TCI, Technical Equipment International, Ltd. (Tel Aviv, Israel) produced the M89SR.

Other Foreign Hostile Action

Latin America - The Argentine Army used M14 rifles in the Falklands War with the United Kingdom. Argentine soldiers of C Company, Regimento (Especial) de Infanteria 25 made very effective use of M14 NM rifles equipped with AN/PVS-2 night optics against British forces in the battles for San Carlos and Goose Green in May 1982. The Colombian Army has used the M14 and M14K rifles in action in the 1980s against Fuerzas Armadas Revolucionarias de Colombia (FARC), a very powerful drug trafficking organization. M14 rifles were turned in by rebels to the government of Honduras at La Ceiba during the

summer of 2003.

Philippines - The Philippine Army, Marines, Civilian Auxiliary Forces Geographical Unit (CAFGU), and the rebel New People's Army (NPA) have used American and Chinese M14 rifles against each other in hostile action. For example, on September 24, 2005, the NPA conducted a raid on a platoon of Philippine Army soldiers at rest in Barangay San Carlos, Isabela. In this action, five Philippine Army soldiers were killed and one M60 machine gun and one M14 rifle were captured by the NPA. The Philippine Womens Auxiliary Corps conducts close order drill with M14 rifles. The Philippine Government has issued M14 rifles to civilian volunteer organizations as well.

The Philippine Marines Reserve Marksmanship and Sniper Unit established its scout sniper school in 1969. The first Commanding Officer of the school was Lieutenant Commander Adolfo S. Feliciano. The school was in operation until 1994. The Philippine Marines scout snipers used M1D Garand rifles with M84 scopes and iron-sighted M14 rifles until 1996. The Philippine Marines scout snipers converted to an accurized M16A1 weapons system in 1996 and re-established the scout sniper school in July 2001. One squad of scout snipers is allotted per Marine Battalion Landing Team (MBLT).

The Philippine Marines continued to use the M14 rifle until at least February 2003.

Philippine MBLT 8 was deployed to central Mindanao to join with the 602nd Brigade of the Philippine Army 6th Infantry Division in the February 11, 2003 attack on the Moro Islamic Liberation Front (MILF) Central Command headquarters in the 494 acre Buliok Complex at Pikit, North Cotabato. The Buliok Complex encompasses several towns in the North Cotabato and Maguindanao provinces. After five days of continuously strong resistance by the MILF, the Armed Forces of Philippines succeeded in taking the headquarters complex on February 16, 2003. As part of this operation, Philippine Marines from MBLT 8 were sent to the Liguasan Marsh in rubber rafts to search out and destroy the MILF resistance. The Buliok complex is adjacent to the Liguasan Marsh. During this combat action in the Liguasan Marsh, at least two M14 rifles can be seen in video along with M16 type rifles carried by the Philippine Marines.

Other Areas - On May 17, 1983, a peace agreement was signed between Israel and Lebanon. As Israel drew down its forces in Lebanon over the succeeding months, Syria continued to foment the ongoing civil war. Lebanese Forces (Christian militia) used M14 rifles to defend villages in the Aley and Chouf districts from mid-June to late September 1983 against the Syrian Army and the Lebanese Druze Progressive Socialist Party militia. These M14 rifles were likely acquired from Israel. M14 rifles were in use by both Haitian government forces and insurgents during the February 2004 uprising. In November 2004, at least one M14 rifle was in the hands of the rebel Sudanese People's Liberation Army. Later, in May 2006, Fur tribesmen of the Sudanese People's Liberation Army in Darfur were seen on *ABC World News Tonight* equipped with M14 rifles shortly after the Sudanese government had offered a peace agreement. A company of Estonian Army soldiers stationed in Afghanistan successfully engaged enemy combatants out to 1000

meters with its accurized M14 rifles.

Corporal Ben Roberts-Smith of the Australian Special Air Service Regiment was awarded that nation's highest military honor, the Victoria Cross, for action in combat in Shah Wali Kot, Kandahar, Afghanistan on June 11, 2010. He and three other SAS soldiers were sent into a firefight to support an Australian unit and Afghan National Police personnel taking fire from three Taliban machine guns. Corporal Roberts-Smith destroyed one machine gun nest with a grenade and then charged the other two machine gun positions. He killed two Taliban manning the machine guns with a Mk 14 Mod 0 rifle. The rifle was on loan from the U. S. Special Operations Command. He and three other SAS soldiers ended the threat by next eliminating several other Taliban fighters in a nearby mud hut.

Taiwan

The Taiwanese government had decided to manufacture the M14 rifle and M60 machine gun for its military by no later than April 1966. In May of that year, the Taiwanese Ambassador requested the sale of ten M14 rifles and ten M60 machine guns from the United States to his country. The Combined Service Forces supplies the ordnance, communications and administrative needs of Taiwan's armed services. Under this command headed by General Lai Ming-tang, the M14 and M60 was to be manufactured.

The Military Assistance and Advisory Group (MAAG) China attempted to dissuade General Ming-tang from producing the M14 and M60. General Ming-tang was advised by MAAG China that it would be difficult to produce the M14 rifle based on the experience of American manufacturers. He was informed that the M14 receiver and bolt was made of material very sensitive to heat treatment. MAAG China estimated that it would take fifteen years for the Combined Service Forces to produce a sufficient quantity of M14 rifles for its infantry units. Nevertheless, the U. S. Secretary of State approved the Taiwanese Ambassador's request on June 02, 1966.

In October of the same year, MAAG China sent along two Taiwanese requests. The first was to obtain permission for a team headed by General Ming-tang to tour United States facilities associated with the M14 and M60. The Taiwanese also wanted technical data related to the M14 and M60. The Department of the Army approved the requests. The visits were conducted the same month and the technical data provided to Taiwanese representatives at that time.

The Taiwanese government sent a letter in December 1966 to the U. S. Deputy Assistant Secretary of Defense stating its desire to establish the capability to manufacture M14 rifles and M60 machine guns within the following two years. The Taiwanese planned to produce only 6,000 M14 rifles and 1,200 M60 machine guns. The December 1966 letter requested consent of the U. S. government so Taiwan could begin production and it also asked for additional technical data related to the effort. To this end, a formal Memorandum of Understanding between Taiwan and the United States was signed on

January 23, 1967.

The Memorandum of Understanding grants license to the Government of Taiwan to produce M14 rifles known as the Type 57. The January 23, 1967 memorandum states that Taiwan will purchase tools, components, material, documentation, technical assistance and assemblies from Fiscal Year 1967 through Fiscal Year 1969. As agreed to in the Memorandum of Understanding, the U. S. government sold some of the M14 rifle production machinery used by Harrington & Richardson to Taiwan in 1968. One complete set of fixtures and inspection gages was supplied to the Government of Taiwan by Springfield Armory. By November 1968, nineteen machine tools had been accepted by the Government of Taiwan out of 150 offered by the U. S. government. Shipment of the M14 project equipment previously used by Harrington & Richardson Arms to Taiwan was completed in 1969. This assistance effort was coordinated by MAAG China. The Memorandum of Understanding also required that the Taiwanese T57 items produced would be interchangeable logistically with USGI M14 items.

On January 07, 1969 MAAG China made a recommendation to Admiral John S. McCain, Jr., Commander In Chief Pacific (and father of American POW and later U. S. Senator John S. McCain, III from Arizona) to provide Taiwan with any excess M14 rifles in U. S. inventory up to a total quantity of 380,000 at either no cost (Military Assistance Program) or low cost (Foreign Military Sales). The commanding officer of MAAG China made this recommendation because Taiwan had decided to equip its armed forces with the M14 but was only capable of an annual production rate of 15,000. Admiral McCain followed up a week later on the request by asking the commander of U. S. Army forces in the Pacific and the Department of the Army itself as to availability of excess M14 rifles in inventory. Admiral McCain also requested MAAG China advise him on what funds could be provided by the Taiwanese government for the purchase of spare parts, basic issue items and ammunition needed to support any excess M14 rifles that could be transferred. The Army determined that no serviceable M14 rifles were available as many Army and Army Reserve commands had yet not converted to the M16A1 plus it was still unknown as to which new rifle the Republic of Korea armed services would adopt, M14 or M16A1. The Department of the Army informed Commander In Chief Pacific on July 14, 1969 that it would release 8,000 unserviceable M14 rifles to Taiwan under the Military Assistance Program at no cost except for packing, handling and transportation charges. These charges, approximately \$20,000, were borne by MAAG China. These 8,000 unserviceable M14 rifles were delivered to the Taiwanese government by the end of 1969.

The Republic of China (Taiwan) made approximately 1,000,000 Type 57 rifles from 1969 until at least 1980. Due to start up difficulties, only 200 Type 57 rifles were produced by July 01, 1969. Some, if not all, Type 57 rifles were made at the 60th Arsenal in Kaoshiung, Taiwan. There are two models of Type 57 rifles. Both the first and second model receiver heels are marked in Chinese with the exception that the serial numbers use Arabic numerals. First model Type 57 rifles were assembled with many USGI parts

including stocks, flash suppressors and magazines. The Taiwanese government did not receive the tooling to make flash suppressors and magazines when it received the H&R production machinery. Thus, the Taiwanese government had to make the tooling to manufacture these parts to continue production. The first models had serial numbers 000001 to 048655. The second model began with serial number 048666. The Taiwanese developed a simplified rear sight for the second model Type 57 rifle and the receiver heel information was rearranged. The flat surface immediately behind the rear sight on Type 57 receivers is very distinct in comparison to a USGI M14 receiver. There has not been any collaboration whatsoever of any kind between the People's Republic of China and Taiwan on M14 type rifle design or manufacture.

Like the United States, Taiwan eventually adopted the M16 platform as its standard infantry rifle. The T57 rifle was replaced with the T65 in 1976. The T65 series rifles were Taiwanese designed and manufactured variations of the M16A1 rifle. Due to the large number of T57 rifles produced and M14 rifles purchased from the United States, T57 and M14 rifles are still in the inventory of the Republic of China Army. In August 2011, the Military Combined Logistics Command displayed its prototype XT98 rifle at the Taipei Aerospace & Defense Technology Exhibition. The XT98 was a T57 rifle fitted with a metal chassis stock sporting six and twelve o'clock accessory rails. The twelve o'clock rail extended from about an inch behind the front band to the end of the receiver. The XT98 was made at the 205th Arsenal.

Destruction and Export of USGI M14 Rifles

M14 rifles have been given or sold to foreign governments under U. S. military aid programs since 1967. As of June 30, 1973, the U. S. Army had over 940,000 M14 rifles remaining in its inventory. In late 1973, U. S. Army Director of Material Acquisition, Major General Peter G. Olenchuk, testified before a U. S. House of Representatives subcommittee that the Army planned to remove the M14 rifle from its inventory "except for war contingency purposes." Major General Olenchuk retired from active duty in 1975 and passed away on October 06, 2000.

As of 1996, at least 450,000 M14 rifles had been transferred to foreign armies while another 750,000 were destroyed by the United States. The Naval Surface Warfare Center (Crane, IN) and Anniston Army Depot (Anniston, AL) were two facilities used to demilitarize M14 rifles in the 1990s. The destruction of small arms began in August 1993 at Anniston Army Depot. The machine used to demilitarize M14 rifles was not very discriminate. After the stock, sling, hand guard some of the parts were removed, the M14 was fed into the machine for destruction. This machine was referred to as Captain Crunch. Captain Crunch sheared the rifle about every four to six inches along its length. Typically, Captain Crunch took "bites" at the middle of the receiver, at the front end of the barrel chamber, near the operating rod guide, through the gas cylinder, and through the flash suppressor. Captain Crunch was destroying 3,000 small arms per day at a unit price of \$3.52. Between August 1993 and March 1994, 50,000 M14 rifles were destroyed

at Anniston Army Depot alone. Unfortunately, the demilitarization of small arms continued until 1996.

Some parts were retrieved, set aside and sold through a bid process to surplus parts dealers. These parts were typically the stock, hand guard, sling, rear sight assembly, bolt lock, extractor, operating rod guide and pin, gas cylinder lock, gas cylinder plug, flash suppressor nut and setscrew, front sight, and front sight screw. Parts such as operating rods, firing mechanisms and gas cylinders were also salvaged and sent to the DCM Repair Parts Program at Port Clinton, OH for sale to the public. After each rifle was destroyed, a certificate recording the receiver serial number was signed, dated and kept indefinitely. Destroyed M14 receiver halves have been sold to collectors and to those who work on M14 stocks and make M14 type rifle accessories.

Destruction of M14 Rifles in the Philippines - Over time, the Armed Forces of the Philippines have collected captured and surrendered weapons, serviceable and unserviceable, from the New People's Army and the Moro Islamic Liberation Front. In 2002, the destruction of these weapons began at Camp Aguinaldo in Quezon City, east of Manila. This was done to reduce the cost of storage. The United States government contributed \$300,000.00 towards this destruction effort. By September 2007, 20,000 of an inventory of 32,000 weapons had been demilitarized.

On September 12, 2007, the Philippine military beefed up its presence in metro Manila in response to a renewed attempt to destabilize the administration of Philippine President Gloria Macapagal-Arroyo. An additional 643 troops from the Army's 5th Infantry Division and the Air Force's 760th Combat Group were brought in and housed at Camp Aguinaldo as a precautionary measure. This action reinforced the existing 3,000 troops in the capitol area. On September 20, 2007, Armed Forces of the Philippines Chief of Staff General Hermogenes Esperon, Jr. publicly confirmed the existence of a new plot to destabilize the government.

As part of the government response to this threat, a ceremony was held on September 21, 2007 at Camp Aguinaldo to publicize the destruction of the remaining 12,000 captured and surrendered weapons. General Esperon attended the ceremony covered by the media. General Esperon stated that it was necessary to demilitarize the weapons to reduce the number of "loose" firearms. The destruction procedure including shearing, torch cutting and sawing rifles and machine guns into scrap metal. Amongst the remaining 12,000 firearms collected for destruction were M1 Carbines, M1 and M16 rifles, and at least four M14 rifles. The proceeds from sale of the scrap metal, an estimated P4,000,000 (\$88,000), was to be added to the modernization fund of the Armed Forces of the Philippines.

The M14 Rifle in Foreign Assistance - A partial list of foreign governments that have received M14 rifles from the United States includes Afghanistan, Argentina, Belize, Chad, Chile, Colombia, Denmark, Dominican Republic, Estonia, Greece, Haiti, Israel, Jordan,

Latvia, Lithuania, Niger, Philippines, Republic of Korea, Taiwan, Tunisia, Turkey and Zaire. The Greek Navy has used M14 rifles for guard duty at its bases. The Royal Danish Navy Frogmen Corps inventories the M14 rifle.

In 1968, the government of the Republic of Korea (ROK) was considering a small arms plant on its own soil for the purpose of providing its military with a replacement for the M1 Garand rifle and M1 Carbine. ROK Minister of Defense Choi hoped for a joint venture with the U. S. government to produce the M16A1 rifle for the Korean armed services. Representatives from the ROK Ministry of National Defense and the U. S. Department of Defense met in late May 1968 to discuss the matter. U. S. Deputy Secretary of Defense Paul H. Nitze was agreeable to the idea. However, the U. S. Department of State questioned whether or not it was the best interests of the United States for South Korea to produce its own rifle. The Secretary of State requested an assessment from the Joint Chiefs of Staff and the Commander In Chief Pacific as to what rifle would be best for the ROK military. The U. S. Secretary of State held out the carrot of surplus M14 rifles being available in the near future. The Commander In Chief Pacific stated in his recommendation to the Joint Chiefs of Staff on August 06, 1968:

In summary, the M-14 is an excellent weapon for conventional warfare at the extremely long combat ranges found on the relatively barren Korean terrain, while the M-16 provided an effective weapon for internal defense operations. As the threat indicates a requirement to conduct both types of operations, there are excellent argument [sic] to arm the ROKF with a mix of the weapons.

In early November 1968, the Commander In Chief Pacific (CINCPAC) tried to determine the availability of surplus M14 rifles as an alternate means of replacing the M1 Garand rifle then in use by the ROK military services. The Department of the Army replied to CINCPAC on November 07, 1968 that a study was being conducted to determine if the U. S. Army should retain both the M14 and the M16A1 as standard rifles or just the M16A1 alone. The Department of the Army further advised that if the Department of Defense decided in favor of the M16A1 alone, it would inform CINCPAC of any surplus inventory of M14 rifles. Subsequently, the Commander In Chief of U. S. Army forces in the Pacific notified CINCPAC on December 13, 1968 that there would be no surplus M14 rifles from the conversion to the M16A1 in the Republic of Viet Nam. M14 rifles pulled from units in Viet Nam were being sent back to training commands in the continental United States.

At the beginning of 1969, CINCPAC believed there were two worthwhile means of replacing the ROK military shoulder weapons: 1) construction of a small arms plant in Korea dedicated to producing 600,000 M16A1 rifles or 2) the United States would supply 250,000 M14 rifles to the Republic of Korea for its Army combat units and M16A1 rifles for ROK internal defense operations. The Joint Chiefs of Staff proposed a third alternative to CINCPAC on January 03, 1969, U. S. sources would provide 255,000 M16A1 rifles for ROK Army combat units and 360,000 M14 rifles, once available and depending on cost, to ROK combat support units. At the time, the Department of the Army was not able to

provide the cost of surplus M14 rifles to CINCPAC. Admiral McCain responded on January 18, 1969 to the Department of the Army as follows:

. . . both the M-14 and M-16 rifles provide significant military advantages for use by ROKF, none of which are overriding in CINCPAC's view. Therefore, the relative cost of equipping ROKF with various rifle systems is a key factor in reaching a decision on which alternative to implement and must be determined before the alternatives . . . can be properly evaluated and the facts concerning these alternative methods can be placed before the ROKG

The Department of the Army replied to Admiral McCain on February 06, 1969. The Army was not able to provide firm pricing and availability of surplus M14 rifles because the Secretary of Defense had not yet decided to make the M16A1 rifle the sole standard rifle for the entire U. S. Army. Admiral McCain then recommended to the Joint Chiefs of Staff on February 19, 1969 that a decision to build a small arms plant in Korea be postponed and that the DOD study on rifle standardization be completed without delay.

By March 1969, CINCPAC was evaluating two options for a new ROK military rifle: 1) the United States would provide 40,000 M16A1 rifles to ROK combat units and build a small arms plant in Korea to produce 570,000 M16A1 rifles or 2) the United States could supply 20,000 M16A1 and 230,000 M14 rifles to ROK combat units and ROK combat support units would keep the M1 Garand and M1 Carbine. These alternatives did not bear fruit in 1969 because the estimated cost to produce the M16A1 rifle in Korea was in excess of what the Republic of Korea government could bear and the cost and quantity of surplus M14 rifles was unknown. The U. S. government eventually supplied a number of M14 rifles to the ROK Army by no later than 1978.

Under Fiscal Year 1966 funding for the Military Assistance Program, 908 M14 rifles were delivered to the Philippine government in early 1967 to help equip a Constabulary Battalion Combat Team. The Philippine Marines, Naval Infantry and Army Airborne soldiers had M14 rifles in their weapons inventories before Mount Pinatubo erupted in June 1991.

124,815 M14 rifles were exported under the EDA program between 1995 and 1998. Some were given at no cost under the EDA and MAP programs while other M14 rifles were sold under the FMS program. The Excess Defense Articles program is authorized under the Federal Assistance Act of 1961. Other M14 rifles were transferred to foreign nations under Military Assistance Programs. Some M14 rifles were given to the Nicaraguan Contras by the U. S. government in 1981 or 1982. Accessories were often given away or sold with the rifles as part of the assistance program. For example, M6 bayonets and M8A1 scabbards were sent along with M14 rifles transferred to Ethiopia.

The destruction of M14 rifles began as early as 1970. Rock Island Arsenal personnel replaced the 250 M14 rifles in inventory at the Loyola University (Chicago, IL) Army

ROTC program that year with 250 M16 rifles. The M16 rifles were fitted with devices to inhibit automatic fire. Prior to leaving the university campus, Rock Island Arsenal personnel disassembled and destroyed all 250 M14 rifles. These 250 M14 rifles were cut through the barrels and the receiver barrel rings and the parts discarded as trash.

Initially, the U. S. Department of Defense destroyed large quantities of these newly surplus weapons, including 479,367 M14 rifles in 1993 and 1994 and roughly 350,000 M16A1 rifles in 1996. But under increasing pressure from gun advocates in Congress, an amendment was passed to the Defense Authorization Act in 1996 to prohibit the Army from destroying these surplus weapons. The amendment was passed in subsequent years creating a stockpile of surplus weapons that civilian collectors hoped would be made available for sale at a later date.

In a change of policy in 1995, the Army began to transfer its surplus stocks to foreign governments. Between 1995 and early 1998, 321,905 surplus small arms were exported to foreign militaries under the Excess Defense Articles program. The main recipients were Estonia, Latvia and Lithuania, Israel, Philippines and Taiwan.

From the perspective of the U. S. government, this policy of exporting defense articles to friendly governments has the twin benefit of strengthening vulnerable allies while simultaneously reducing the surplus stockpile. The blanket prohibition on the re-transfer of U. S. military equipment without prior approval from the U. S. government is also said to prevent the weapons from being diverted to third countries.

The reader may be puzzled regarding why M14 rifles (and other small arms) should be destroyed or exported by the United States. During the Cold War, the United States military inventoried a huge stockpile of weapons that would enable it to fight two wars simultaneously. From World War II to the late 1980s, this equated to about 2.3 small arms for each member of the Armed Forces. The shift during the 1990s towards flexible, high-tech rapid-reaction forces meant that a large reserve of small arms was thought to be no longer required.

A Total Army Assets database query performed during the first half of 2001 found a total U. S. Army inventory of 120,021 M14 rifles. This included M14 rifles in each classification of readiness condition. This query did not account for M14A1, M14M and M14 NM (National Match) rifles in the possession of the U. S. Army or any M14 rifles in the inventory of the U. S. Navy, Marine Corps or Air Force. As of mid-2003, the U. S. Army inventory was approximately 96,000 M14 rifles in Condition A readiness. The U. S. Army reported in July 2007 that it had 22,660 M14 rifles in use and 87,462 M14 rifles, serviceable and unserviceable, in depot storage.

The Estonian Defense Forces have two designated marksman M14 models, TP and TP2. The M14 TP was designed around 2000. It has an Estonian manufactured medium green color plywood stock with adjustable cheek rest. The stock was intended to allow

the operator emergency use of iron sights without removing the Chinese made scope. Unfortunately, the cheek rest doesn't raise high enough for a proper cheek weld when using issue the scope mount, rings and scope. The plywood stock also throws the balance of the rifle off towards the muzzle.

In 2008, several hundred of the M14 rifles in Estonia were built into Designated Marksman models for use at the squad and platoon level in the Estonian Defense Forces. These are known as the M14 TP2 model. They were fitted with Knight's Armament RAS-14 rail mounts and Schmidt and Bender, Inc. 3-12x50 mil dot reticle day scopes. As of early 2008, the M14 TP2 model utilized the USGI synthetic stock with a six o'clock M1913 Picatinny rail and strap on cheek rest. An Eberlestock aluminum chassis stock was being considered for it though. The M14 TP2 prototype was made in 2007. The final production version was expected for unveiling by the fall of 2008.

By 2002, Lithuania had developed its own version of the designated marksman M14, the M14L1. The modification of USGI M14 rifles was done in Lithuania by Koncernas Pergale. The M14L1 sports a thumbhole stock with the front end only extending to the front side of the operating rod guide. This leaves the gas cylinder and cylinder portion of the operating rod exposed. A scope mount, rings and scope were included as part of the conversion.

G. A. Precision (North Kansas City, MO) built over 200 M14 rifles into M62-R1 rifles for the Jordan Armed Forces in 2004 and 2005. The M14 rifles are owned by the government of Jordan through a military assistance program of the U. S. government. The build specification included a 22 " Badger Barrels, Inc. match grade heavyweight stainless steel barrel, McMillan M3A bedded fiberglass stock, shimmed gas system, match tuned firing mechanism, Smith Enterprise, Inc. direct connect flash hider and extended bolt lock, Turner Saddlery biothane sling and Harris model HBRM-S bipod. The optics configuration included a Smith Enterprise, Inc. part number 2006 scope mount, Leupold & Stevens, Inc. 3.5-10X day scope, Badger Ordnance M62 single-piece ring mount, and Thales brand night scope. With the exception of the cheek rest, scope and rings, the M62R-1 was given a desert tan finish. The M62-R1 rifle was built with the iron sights removed and the headspace set to 1.632 " + or - 0.001 ".

Foreign Sales of USGI M14 Rifles

Israel has exported USGI M14 rifles to Canada, Germany and New Zealand for commercial sale and to Italy for government use. Some of the exported M14 rifles had been captured in Lebanon by Israel Defense Forces during its 1982 Operation Peace for Galilee. In 1987, at least 3000 M14 rifles were imported into Canada from Israel. Lever Arms Service Ltd. (Vancouver, BC) was one of the importers. These rifles had the selector lug cut off in order to comply with Canadian law. Fifty of these rifles were sold and shipped to the United Kingdom for use in the filming of the 1987 Stanley Kubrick film classic, *Full Metal Jacket*. European Union M14 and M1A owners may buy small parts,

accessories, and Viet Nam era load bearing equipment from Arsenal Military Sales (Rouveroy, Belgium).

During 1988 and 1989, two licensed gun dealers in Germany imported USGI M14 rifles into that country from Israel. The two dealers imported the rifles one at a time per customer request. Initially, there was not much interest in these rifles. Then the German firearms magazine, *Deutsches Waffen Journal*, printed a story on the Springfield Armory, Inc. M1A and Norinco M305 rifles in its July 1988 issue. The article generated some interest in the M14 type rifles among the gun buying public. In the May 1989 issue of *Deutsches Waffen Journal*, one of the gun dealers, Stefan Harlacher, advertised the USGI M14 rifle for a price range of 1,585 Deutsche Marks to 1,685 Deutsche Marks.

Subsequently, a large firearms importer, Interimport, and a large firearms distributor, Frankonia, sensed a business opportunity. Frankonia placed an advertisement in the June 1989 issue of *Deutsches Waffen Journal* for USGI M14 rifles at the substantially lower price of 1,099 Deutsche Marks. These rifles were sold without the selector lug and no select fire components. Shortly after the Frankonia sale began, the Bundeskriminalamt (the German equivalent of the U. S. Federal Bureau of Investigation) declared the imported M14 to be a military small arm. All further importation was halted. The USGI M14 rifles that had been imported were allowed to remain in private hands but had to be permitted by the Bundeskriminalamt. All transfers, sales and repairs regarding the USGI M14 rifles had to be documented. There were a total of about eighty USGI M14 rifles imported and sold in Germany. With a new firearms law effective April 2003, these M14 rifles can be transferred without restriction in Germany among those with gun permits.

A resident of Isle of Jersey, United Kingdom is the legal owner of USGI Winchester M14 rifle serial number 22263. Private individuals in Barbados and Denmark legally own Harrington & Richardson USGI M14 rifles. A small number of M14 rifles remain in the Socialist Republic of Viet Nam. At least one M14 and one M14A1 are on display in the War Remnants Museum at 28 Vo Van Tan District 3 Ho Chi Minh City. M14 serial number 820520 is one of many captured weapons displayed at the Army Museum on Pho Dien Bien Phu in Hanoi. Some M14 rifles have been exported from Viet Nam to the Netherlands, Finland, Luxembourg, and Norway. M14 rifles are available for sale to private individuals in those countries. For example, Mr. van Veen of Amsterdam imported M14 (and M1 Garand and Carbine) rifles into the Netherlands during the 1980s.

Private individuals in Queensland, Australia with a valid state license owned USGI and Chinese M14 rifles from at least 1991 until 1996. In 1996, the Australian government banned private ownership of semi-automatic firearms except for a few private individuals possessing pest control licenses. The 1996 legislation included a buy back program for semi-automatic firearms including M14 rifles.

In 2006, the Queensland Department of Fisheries and Wildlife had at least fifty USGI M14 rifles in its equipment inventory. This agency has at times employed a sharpshooter

equipped with the M14 rifle to kill wild pigs, wild horses and buffalo from a helicopter. The selective hunting is conducted as part of the government's wildlife conservation program.

The Cape York Weeds and Feral Animals Program in Queensland was still ongoing in early 2007. Firearms and firearms parts imported for the use by state law enforcement agencies in Australia must be approved by the Attorney General of Australia.

Unfortunately, as of April 2007, obtaining federal approval to import spare parts or new M14 type rifles was extremely difficult even though the purpose of such was to support official state government conservation efforts.

Countries that allow the commercial importation of USGI M14 rifles generally do not allow owners to have automatic fire capability so the rifles and / or parts are regulated to prohibit select fire. For example, M14 rifles are legal for civilians to own in Germany but the selector lug is milled off and the USGI flash suppressor is replaced with a faux suppressor. Private owners of USGI M14 rifles in Finland must have the selector lug cut off to comply with the law. In the Netherlands, it is illegal for all of the select fire parts to be installed on civilian owned M14 rifles. A M14 type rifle owner in Japan may install the select fire components but must render the parts incapable of automatic fire. One M1A rifle owner in Japan removed enough material from the bottom edge of the sear release to prevent contact with the sear with the switch in the Automatic position. This modification prevents automatic fire and makes his M1A compliant with the law in Japan.

M14E1

Between September 1961 and January 1963, Springfield Armory developed five versions of a folding stock designated as the M14E1. The folding stock M14 was developed at the request of the U. S. Army. Such a rifle was to be carried by paratroopers, tank crews and vehicle drivers. The designs included both under-folding and side-folding stocks for the M14 rifle.

The M14E1 Type IV was outfitted with a clip on muzzle stabilizer that was also capable of mounting a bayonet. One M14E1 Type V rifle was made in January 1963. The Type V stock had an aluminum bar stock arm, aluminum butt plate and swivel bracket. However, the difficulties encountered in producing forged aluminum stock arms were not resolved due to a lack of funding. The M14E1 Type V was shown to the Army and Marines at Fort Belvoir, Fort Knox, Fort Campbell, Fort Benning and Marine Corps Base Quantico by representatives of Springfield Armory during the first six months of 1963. Fort Benning recommended that the Type V stock be changed to a right side folder and that the front pistol grip fold to the rear instead of to the front. The Marines Test Center recommended acceptance of the M14E1 but it was not meant to be. There is a M14E1 Type V rifle on display at the Rock Island Arsenal Museum (Moline, IL).

M14E2 and M14A1

The M14E2, later M14A1, rifle assigned to the automatic rifleman had an M14E2 stock and sling, stabilizer assembly and M2 bipod with sling swivel. His rifle would have a selector switch and selector shaft spring installed in place of the selector lock. Initially though, the automatic rifleman was equipped with a M2 bipod attached to his M14 rifle with or without the sling swivel. This configuration was known as the M14 (Modified) rifle, not to be confused with the M14 M with welded select fire components.

The M14 (Modified) suffered from excessive bullet dispersion, heavy recoil and severe muzzle rise in testing done during the spring of 1961 at Fort Benning. Thus, the U. S. Army Infantry Board was given the task later that year of improving the performance of the M14 (Modified) rifle. This development effort was known as the M14 (USAIB). Captain Durward Dean Gosney, a native of Phoenix, AZ and an Army Infantry Board test officer, developed three major changes to the M14 (Modified) rifle by no later than March 1962. The December 1962 CDC Rifle Evaluation Study declared the M14 (USAIB) "a definite improvement over the M14(M) in the automatic rifle role." Captain Gosney was recognized as the creator of the design officially classified in late 1963 as the M14E2. Major Gosney was later killed while serving in the Republic of Viet Nam.

The M14 (USAIB) design differed significantly from the M14 (Modified) in three ways: 1) attachment of a muzzle stabilizer over the flash suppressor 2) a straight-line stock with a rubber butt pad and 3) dual hand grips. Whether by design or not, the muzzle stabilizer and the flash suppressor work in conjunction to reduce lateral bullet dispersion and reduce recoil by 25 %. Unfortunately, the muzzle stabilizer did not suppress the flash signature. The prototype M14 (USAIB) stock was made by Master Sergeant Raymond Behnay at the U. S. Army MTU and those used in testing were manufactured by Reinhart Fajen. The prototype straight-line stock included a pistol grip, butt pad and butt plate flapper. It reduced muzzle rise and further reduced recoil.

On October 02, 1963, the U. S. Army Weapons Command made a request to Springfield Armory to make some changes in the M14 (USAIB). These changes included redesign of the fore hand grip and the butt stock sling swivel. The differences between the M14 (USAIB) and the M14E2 were as follows:

1) Stock fabrication - The M14 (USAIB) stock was made by cementing several pieces of wood together. A standard M14 stock was used for the front end of the assembly. The M14E2 stock was made from two pieces of wood. The standard M14 stock blank was cut to form the M14E2 stock except for the pistol grip. The pistol grip was formed from a second piece of wood and then secured to the stock body by a dowel and adhesive. The front end bottom and sides of the M14E2 stock was left thicker than the M14 stock to better withstand heat generated by automatic fire. The butt end and the pistol grip were reshaped for better accuracy and operator comfort.

2) Recoil pad - The recoil pad was added to the M14 (USAIB) to reduce operator fatigue. The M14 (USAIB) recoil pad was of commercial manufacture. It was modified to accept the shoulder rest and had to be hand fitted to the stock. The recoil pad had ribbing on the sides allowing debris to collect. The material of the commercial recoil pad had poor resistance to cold weather, abrasion and oil. Consequently, the recoil pad required replacement more often than desired. The M14E2 recoil pad was molded from rubber with excellent resistance to cold weather, abrasion and oil. It was smooth on all sides so that no foreign material would be collected by it. It was designed with an integral steel shoe for strength and a tight fit with the stock. The M14E2 recoil pad was secured to the stock with two screws. Two rubber plugs filled the cavities in the recoil pad over the screws as a means of keeping out snow and other debris. The M14E2 recoil pad was interchangeable from stock to stock.

3) Shoulder rest assembly (butt plate assembly) - The M14 (USAIB) was put together with a standard M14 stock shoulder rest (butt plate flapper) mounted on a block. The shoulder rest helped the rifleman to control muzzle rise. A stop plate was screwed to the top of the block. The stop plate sat above and extended over the sides of the butt end of the stock. There was no detent to keep the shoulder rest in the open or closed position. The shoulder rest for the M14E2 was simplified from the M14 (USAIB). It had only one moving part, the shoulder rest plate (butt plate flapper) itself. The M14E2 stock shoulder rest used a detent to hold the rest plate either open or closed. Additionally, the obtrusive stop plate was eliminated.

4) Muzzle stabilizer - The muzzle stabilizer for the M14 (USAIB) consisted of a steel cylinder drilled with holes and then welded to the flash suppressor at the front sight dove tail base. The M14E2 muzzle stabilizer was a slip-on assembly that was secured to the bayonet lug by a screw and lock nut. The M14 combination tool was used to install and remove the M14E2 muzzle stabilizer.

5) Fore hand grip assembly - The M14 (USAIB) fore grip was made from wood. It folded down against the stock away from the operator. Its position on the stock bottom side could not be moved. The M14E2 fore grip was a lot less bulky and made from aluminum and insulated with a rubber coating. Six holes were drilled in the bottom side of the M14E2 stock to allow the fore hand grip to be moved up to 5 " forward or aft in 1 " increments. The four holes not used to secure the fore grip assembly were plugged with rubber grommets to keep out debris. A latching mechanism locked the M14E2 fore grip in the open position and a detent kept it folded against the stock towards the operator when closed. The latching mechanism was sized so that the rifleman could operate it with mittens. Since it was less bulky, the M14E2 was much more comfortable to carry at sling arms.

6) Sling - The M14 (USAIB) was equipped with the standard cotton web small arms sling used on the M1 and M14 rifles. The M14E2 sling was borrowed from the M1918A2 Browning Automatic Rifle. An extra sling hook was added to connect the M14E2

(M1918A2) sling to the fore hand grip sling swivel. The fore and rear hand grips, in tandem with the M14E2 sling, increased the downward force acting on the M2 bipod legs from 7 pounds with the M14 (Modified) to 31 pounds for the M14E2. The bipod sling swivel also facilitated ease of carry for the M14E2 at sling arms.

7) Butt sling swivel - The M14 (USAIB) had a fixed butt sling swivel. The M14E2 butt sling swivel could pivot 90 degrees to the left side. This enhanced operator comfort when carrying the M14E2 at sling arms.

Final testing on the M14E2 rifle was completed at Fort Jackson, SC in early 1964. Much tighter shot group sizes were obtained with the M14E2 over the M14 (Modified), i.e., 4 " versus 12 " at 25 meters. Like its predecessor, the M1918A2 Browning Automatic Rifle, the M14A1 produces the best effect when fired in two or three round bursts. This was confirmed during testing in 1965 at Fort Benning, GA. With a modest amount of practice, the author has obtained 7 " three shot groups at 100 yards with a NFA Registered Springfield Armory, Inc. M1A in automatic fire. The time to reload is critical for the automatic rifleman.

Physical data for the M14A1 Rifle includes the following:

Length of pull = 13.16 "

Overall length with the shoulder rest up - 46.88 "

Overall length with the shoulder rest down - 44.087 " minimum to 44.272 " maximum

Command height with M2 bipod legs extended - 9.72 " minimum to 13.12 " maximum

Minimum height required to assemble magazine into rifle - 8.43 "

Length of operating rod travel - 4.72 "

Case ejection pattern - half-past one to three o'clock if twelve o'clock is the muzzle

Between July and December 1964, 8,350 M14 rifles were converted to M14E2 rifles and delivered to the military. Originally, TRW and Winchester were tasked with the M14E2 conversions but the supplier was late in delivering the rubber coated metal fore grips. When the fore grips were finally delivered, Springfield Armory did the conversions in order to speed delivery of the M14E2 to military units. By January 1964, the M14E2 had been designated as the M14A1. The classification M14E2 means the second experimental design for the Model 14 rifle. M14A1 stands for the first alternate configuration for the Model M14 rifle. Revisions to the M14A1 design were drawn up in April 1966. Those changes included improvements to the M2 bipod, the muzzle stabilizer, and the stock hand grip.

There were two versions of the USGI pistol grip stock assembly. The earlier stock assembly, 7791671, was developed in October 1963 by Springfield Armory. The latter stock assembly, 11686528, was drawn up in April 1966. The latter stock has a slightly different hand grip assembly and stock subassembly than the earlier version. The late version hand grip assembly was designed to withstand a minimum load of 200 pounds

pushing directly to the rear. Among collectors, the terms M14E2 and M14A1 are interchangeable.

The M14A1 as a Sniper Rifle - Less than 100 M14 rifles were fitted with walnut M14E2 stocks for use as sniper rifles. These rifles could also fire M198 duplex ball ammunition in automatic if need be. This work was performed at Anniston Army Depot and Rock Island Arsenal. An example of these M14A1 sniper rifles is discussed in the article entitled "Snipers in Vietnam Also Need Firepower" by Army Lieutenant Louis A. Garavaglia in the January 1968 *American Rifleman*.

Prior to 1968, a sniper detachment was created within the Long Range Reconnaissance Patrol (LRRP) Company of the U. S. Army 4th Infantry Division in Viet Nam. The LRRP Company sniper detachment tested the following rifles for use as a sniper weapon: Winchester Model 70, Remington Model 700, M14, M16A1, and three versions of the AK47. The M14 was chosen because it was reliable, capable of long distance shots and could deliver volume of fire if needed. These M14A1 sniping rifles were used in the Central Highlands of the Republic of Viet Nam and configured as follows: 1) all Harrington & Richardson models 2) equipped with M14E2 stocks 3) equipped with M84 2.2 X scopes 4) lighter M3 bipods mounted on the gas cylinders just forward of the spindle valves and 5) the selector switches were installed. The M14A1 proved sufficiently accurate for sniping use. It was found that experienced shooters could easily hit Army E type silhouette targets at 700 meters from the prone position. This was equivalent to shooting a man that was kneeling at 700 meters. Snipers equipped with these scoped M14A1 rifles took nine magazines of ammunition with them. The nine magazines were loaded to eighteen rounds each. Two magazines contained M118 match grade cartridges and the other seven magazines held M198 duplex ball rounds. Should the three man sniper team get into a firefight, snipers would remove the match ammunition, insert a magazine of duplex rounds and switch to automatic for suppressive fire.

At the end of 1970 or early 1971, a custom built M14A1 rifle was issued to Chuck Karwan, an officer of the U. S. Army 1st Cavalry Division, while in the Republic of Viet Nam. This rifle was bedded and fitted with a Griffin & Howe, Inc. design scope mount, M84 scope and M14 butt plate. The hand grip assembly was removed.

M14 Grenadier

The M14 Grenadier's rifle was equipped with the M15 grenade launcher sight and the M76 grenade launcher. The M15 sight was designed to be used by the grenadier firing from the shoulder or from placing the rifle butt stock on the ground. The grenadier prepared the M14 rifle by turning the spindle valve, loading a grenade cartridge into the magazine and placing a grenade on the M76 grenade launcher. The grenadier could propel a one and one-half pound grenade out to a distance of 250 meters depending on the angle at which he held the rifle and which launcher position the grenade was placed on. The M76 launching positions consisted of nine annular grooves marked 2A, 3A, 4A,

1, 2, 3, 4, 5 and 6 from rear to front. By pushing back the rifle grenade rearward on the grenade launcher, the grenadier could choose the position for launching the grenade. The tenth annular groove on the M76 grenade launcher was located forward of the retainer spring at the front end. The forward end annular groove was designed as a safety feature. It would keep the rifle grenade from falling off the launcher if the retainer spring just to the rear of it were to break. Rifle grenade types included M23 smoke, M27 signaling, M30 high explosive anti-tank (HEAT), M19A1 white phosphorus and M11A4, M29 and M31 inert training. The M30 HEAT rifle grenade was designed to have the capability to breach 10 " of steel or 20 " of concrete.

The XM79 40 mm grenade launcher was adopted by the U. S. Army on October 19, 1960. It was classified as the M79 on December 15, 1960. Pilot line production for the M79 was underway in the fall of 1960 at Springfield Armory. The U. S. Army 82nd Airborne Division used the M14 and M76 for launching smoke grenades during combat operations in 1964 in the Republic of Viet Nam. Both Springfield Armory and TRW made M79 grenade launchers for the U. S. Army between 1961 and 1967. The M79 had largely replaced the M14 rifle for the purpose of launching grenades by 1965. However, M14 rifles equipped as such did see combat service as late as June 1966 with the U. S. Marine Corps. C Company 1st Battalion 5th Marine Regiment 1st Marine Division launched grenades against the Viet Cong with the M14 rifle during Operation Kansas in Que Son Valley, Quang Tin, Republic of Viet Nam on June 16, 1966.

Besides launching grenades, the spindle valve on the M14 rifle is turned to the closed position (slot in the horizontal position) when shooting a line (rope) from ship-to-ship or when the shooter does not desire the cartridge case to be ejected. The spindle valve may also be closed during routine barrel cleaning to prevent the introduction of bore cleaner into the gas cylinder. If so, remember to open the spindle valve when finished cleaning. Between the spring of 1958 and the fall of 1959, the spindle valve was redesigned at Springfield Armory to have the slot cut across the entire diameter of the spindle valve head.

M14 M

A very few rack grade USGI M14 rifles were permanently rendered semi-automatic. This was accomplished by welding the selector shaft lock, selector lock pin, selector shaft, sear release and the receiver. The welding of the select fire parts was done using the Gas Tungsten Arc Welding method. This prevented removal of the selector lock and installation of the selector switch. In this configuration, the rifles were classified as M14 M. The M14 M rifle was identified by engraving the letter M to the right of M14 on the receiver heel. This modification was officially announced in the Director of Civilian Marksmanship's 1963 Rifle National Matches bulletin. The Army also announced it in Army Regulation 920-25 dated 8 February 1965.

The U. S. Army intended to issue M14 M rifles to National Rifle Association associated shooting clubs and to sell them to the public through the Director of Civilian Marksmanship (DCM) program but this failed to occur. An order was placed in 1962 for Springfield Armory to deliver 1,000 M14 M rifles to meet this requirement. Springfield Armory had converted 1,009 M14 rifles to M14 M models by June 30, 1963. After the M14 M rifles had been delivered to the U. S. Army in 1963, they were sent back to Springfield Armory for additional welding of the select fire components to satisfy the Alcohol and Tax Unit of the Internal Revenue Service. The extra work was completed in June 1964. The Gun Control Act was signed by President Lyndon B. Johnson on October 22, 1968 and it went into effect on December 16, 1968. The Gun Control Act of 1968 changed the definition of a machine gun. This law, among other things, prevented distribution of the M14 M rifle to the public.

M14 NM

A development program to turn the M14 into a competition match rifle was begun at Springfield Armory in 1959. In July 1960, the Chief of the Engineering Division at Springfield Armory took the decision to remove 200 M14 rifles from production to manufacture the first M14 NM rifles, 100 in FY 1961 and 100 in FY 1962. The effort to develop a match grade M14 rifle originated with Lieutenant Colonel Joseph Smith, U. S. Army. Colonel Smith was the Director of Civilian Marksmanship from 1958 until 1971. Colonel Smith was the driving force in convincing the U. S. Army to spend the funds to develop and produce the M14 NM. He promoted the use of the M14 rifle in competition shooting to the National Rifle Association. As part of the Springfield Armory National Match Engineering Program, the first accurized M14 rifles were tested in early 1961.

The competition match M14 rifle was designated M14 NM. Springfield Armory and TRW made M14 NM rifles from scratch. Additionally, Springfield Armory and Rock Island Arsenal converted some M14 rifles to M14 NM models. M14 NM rifles received the same welding operation as the M14 M rifles. The last complete set of drawings for the M14 NM was revised in January 1986. Like the M14, the part and heat (material) lot numbers were stamped below the stock line on M14 NM rifles, e.g., 7790189 R N on TRW M14 NM serial number 1473XXX. U. S. Army and National Guard match armorers had to pass the M14 NM armorer school at Rock Island Arsenal before they were allowed to work on match grade M14 rifles. By the 1980s, the National Guard MTU established an annual M14 NM armorer school at Camp Robinson (North Little Rock, AR). At least one M14 NM, a TRW model, was issued in 2004 to a U. S. Army soldier on active duty in Iraq as a rack grade rifle.

M14 NM Distinctive Features - The receiver heels were stamped M14 NM. The NM stamping appeared just to the right of M14 or on the flat surface behind the rear sight. The major differences between the M14 NM and the M14 were: 1) NM barrel was held to half the tolerances of the rack grade barrel and was not chromium plated 2) NM rifle receiver was glass bedded to the stock 3) specific parts were hand fitted and assembled

4) NM rear sight was adjustable in ½ MOA increments through finer threads in the sight base and windage knob, and through half-turn rotation of a hooded eccentric rear sight aperture and 5) select fire parts were welded to prevent operation. The M14 NM rear sight was the same as what was used on National Match modified M1 Garand rifles. Both walnut and birch stocks have been used to build M14 NM rifles. M14 NM rifles were required to group no more than 3.5 " on average at 100 yards after three ten shot groups using M118 match ammunition. The maximum group size allowed for any single round of ten shots was 5.0 ". M14 rifles assembled by U. S. Marine Corps armorers had the forward end lug of the connector assembly removed as part of its match conditioning procedure.

M14 NM Production – The best accounting to date figures the sum of 18,466 for M14 NM rifle production from 1962 to 1967. Springfield Armory was tasked to deliver 3,000 new M14 National Match rifles by August 01, 1962 and it delivered 3,641 new National Match rifles the following year. TRW manufactured 4,874 new M14 NM rifles in 1964. Springfield Armory rebuilt 2,094 rifles in 1965 and 2,395 rifles in 1966. Rock Island Arsenal rebuilt a batch of 2,462 rifles to M14 NM configuration in 1967. These production M14 NM rifles were assembled with minimal stock bedding, NM sights, and a NM standard contour barrel. They were not built with the USAMTU handcrafted accurizing modifications developed and established in the summer of 1967.

M14 NM and M21 Gas Piston - The gas piston for the M14 NM and M21 had a groove cut on the top of cylindrical portion, according to drawing number D9352724. The groove was made part of the M14 NM and M21 specifications as a result of the efforts of Picatinny Arsenal. Civilian draftsmen and engineers from Picatinny Arsenal interviewed National Guard Marksmanship Unit shooters and armorers to develop standardized build specifications for the M14 NM and M21. From this development effort, the M14 NM and M21 rifles were given the gas piston groove and medium weight match grade barrels. Note that the NM gas piston may not always allow the bolt to move fully rearward if M80 ball ammunition is used in the rifle.

The gas piston groove equalizes the gas pressure inside the cylinder resulting in gentler stroking of the operating rod. The groove also aids in breaking vacuum so that the competition shooter can determine if the gas piston is free to move inside the cylinder by tilting the rifle up and down with the bolt held open. Members of the National Guard Marksmanship Unit, as well as some competition shooters, thought the piston groove also reduced the force impacting the operating rod. The perceived result was a smoother and more consistent cycling of the operating rod. Match armorers also polished the gas piston in M14 NM and M21 rifles with crocus cloth to reduce the friction between the gas cylinder and the gas piston. Some competition shooters had the groove cut on the bottom of the gas piston. Two very credible sources interviewed for this work favored the piston groove on the bottom for the match grade M14 type rifle. By no later than 1984, the U. S. Marine Corps Shooting Team had access to match conditioning documents that specified two grooves to be machined in the gas piston for match use.

M14 NM Operating Rod Spring Guide – The standard USGI operating rod spring guide performs its function of guiding the operating rod spring but not without noticeable binding and twisting due to its thin cross-section. This is acceptable for a rack grade M14 rifle. However, the U. S. Army MTU realized the operating rod spring guide could be improved upon as an aid to M14 NM accuracy. By no later than mid-1967, the AMTU had created the National Match operating rod spring guide. It was made of two pieces, a section of un-heat treated drill rod welded to a cutoff magazine catch portion of a USGI operating rod spring guide. The drill rod section was tapered at the forward end like the issue operating rod spring guide. The benefits were a straight operating rod spring and smoother operation of the gas system. Unfortunately, the National Match operating rod spring guide was not hardened by heat treatment after the welding procedure. Consequently, the magazine catch portion of the NM operating rod spring guide wore out much quicker than the issue spring guide.

In the 1980s and 1990s, the National Guard Marksmanship Training Unit attached the magazine catch portion to the slotted drill rod by silver soldering. This method of attachment kept the magazine catch from softening. Often, a hole was drilled through the rod and a pin inserted to secure the magazine catch as well.

Clearance between the Operating Rod Spring and Spring Guide - There is a valid concern about clearance between the M14 operating rod spring and the operating rod spring guide for two reasons: 1) combat and 2) compatibility between Chinese and US parts.

The USGI operating rod spring inside diameter can vary from a minimum of 0.340 " to a maximum of 0.354 ". Several USGI operating rod springs measured by the author measured 0.349 " to 0.350 " for the inside diameter. The inside diameter of a Chinese M14 operating rod spring measured 0.339 ". The USGI standard operating rod spring guide has dimensional requirements of 0.322 " - 0.007 " for its height where located inside the spring and 0.125 " - 0.005 " for its width. The USGI National Match operating rod spring guide will be 0.344 " - 0.005 " in diameter. Consequently, a USGI National Match operating rod spring guide may not fit inside a Chinese operating rod spring.

For combat purposes, a USGI National Match operating rod spring guide may not provide sufficient clearance with the spring where dirt and debris may collect. Some commercial manufacture National Match operating rod spring guides provide ample clearance for field use because the contour has been milled with flats or flutes. If a rifle is assembled with a military dimension National Match operating rod spring guide, an American manufacture operating rod spring should be used with it.

M14 NM Issue – Shooters were introduced to the M14 NM rifle at the 1963 National Rifle Matches. M14 NM rifles were a regular issue item at the 1964 and 1965 Matches. The M14 type rifle was popular in competition shooting until the early 1990s. The M14 was used by the U. S. Marine Corps at Camp Perry as late as 1996. However, U. S. DCM

shooting clubs, such as the Alabama State Service Rifle Team and the Connecticut State Rifle and Pistol Association, still inventoried M14 NM rifles until early 2007. On January 08, 2007, the Civilian Marksmanship Program (CMP) recalled all USGI M14 rifles in the possession of state associations. The primary reason for the recall was that the small number of M14 type rifles in use for service rifle competition. The CMP recall letter cited only 4 % of the rifles used in the President's and National Trophy Individual Matches at the 2006 National Matches were M14 type rifles. Additionally, since 1996 there had been substantial financial and staffing costs to account for missing M14 rifles loaned out to various state associations. The Civilian Marksmanship Program felt the lack of use was not meeting the purpose for which the rifles were loaned out from the U. S. Army. Hence, the recall was issued and the rifles were returned by May 15, 2007 to the CMP for safekeeping at CMP North (Camp Perry) and CMP South (Anniston, AL).

Civilian Ownership of the M14 NM - The 1980 court case, *U. S. v. One U. S. (TRW) 7.62mm M-14 National Match Rifle, Serial No. 1453711*, is worthy of mention. This federal court case was not appealed, and is not "controlling legal authority" for other situations, even within the Southern District of Ohio. Though this case applies only to this particular M14 NM rifle, it does establish that one court has determined that the M14 NM rifle as manufactured by TRW and Springfield Armory is not capable of and is not designed for automatic fire. The rifle in question was originally manufactured as a M14 National Match model, in contrast to rack grade M14 rifles converted into M14 NM configuration.

Robert Sauerman purchased the TRW M14 NM rifle serial number 1453711 in 1973 or 1974. It was not registered as a National Firearms Act machine gun. In order to set the question of the rifle's legal status to rest, Mr. Sauerman informed the Bureau of Alcohol, Tobacco and Firearms (BATF) that he was in possession of the TRW M14 NM. This TRW M14 NM was confiscated from the owner, Robert Sauerman, by the BATF on September 27, 1977 at his gun shop near Dayton, Ohio. The trial court made findings of fact that included a ruling that this TRW M14 NM was not a machine gun under the National Firearms Act, and ordered to be returned to Mr. Sauerman. The TRW M14 NM serial number 1453711 was sold by Mr. Sauerman around 1986 or 1987 to a private individual. In 2006, this TRW M14 NM was sold again to a collector. After 1987, Robert Sauerman met an untimely death when a drunk driver crossed lanes and hit him head on at a stoplight. The 1987 to 2006 owner of TRW M14 NM serial number 1453711 also possessed the court case documents.

M15

From 1955 to 1959, the M15 (T44E5) rifle was developed as a heavier version of the M14 (T44E4). Although a select fire weapon, the M15 was designed for sustained automatic fire using the same 7.62 mm NATO cartridge as the M14 rifle. Thus, no provision was made for launching rifle grenades. There was no spindle valve incorporated into the gas cylinder. The M15 (T44E5) weighed 15.0 pounds with sling, bipod and a full magazine of

twenty rounds. The cyclic rate of fire was 725 rounds per minute. The overall length of the M15 was 45.3 " and its sight radius was 25.87 ". Its four groove 1:12 twist non-plated heavy contour barrel was 22 " long and weighed 3.5 pounds. For lubrication after cleaning, Springfield Armory specified application of a light coat oil on all metal parts except the barrel chamber and bore and surfaces contacting ammunition.

Mathewson Tool Company produced three samples of the T44E5. An unknown number of T44E4 rifles in the serial number range 1001 to 1500 were built into T44E5 models by Springfield Armory. These Springfield Armory developmental rifles were stamped T44E5 on the receiver. However, one M15 rifle had no receiver markings whatsoever.

The M15 (T44E5) had the following parts that differed from the M14: flash suppressor, barrel, gas cylinder, gas cylinder lock, front band, heavier wood stock with a different liner, heavier and triangular front sling swivel base, bipod, and a M1 Garand butt plate with a BAR hinge carefully inletted and secured with welds. Like the T44E4, the M15 hand guard was made of wood. The M15 flash suppressor had a machined surface just forward of the front sight for attaching the bipod. The bipod had eight height positions and the legs were similar to the M2 bipod. Some experimental M15 parts included a chamfered front end flash suppressor akin to the T44E4, a stock with notches and latching clips for securing the bipod feet, and a grenade launcher fitted to the muzzle coupled with an experimental bipod.

In 1956, the decision was taken to chromium plate (later known as standard contour or profile) M14 barrels. The T44E5 was tested by the U. S. Army and the U. S. Marine Corps in 1958. During U. S. Marine Corps testing of the T44E5, a hinged butt plate and bipod were fitted and tested on a T44E4 rifle. Combined with the chromium plated barrel and slotted hand guard, the T44E4 performed satisfactorily. As a result, the U. S. Marine Corps requested a hinged butt plate and bipod for the M14. These features were adopted for the M14 the following year. Consequently, the M15 was declared obsolete in December 1959 without any USGI rifles ever stamped M15.

One commercial M15 rifle was made. Prior to May 1986, a physician in Ohio custom ordered a select fire M1A receiver from Springfield Armory, Inc. The doctor had Springfield Armory, Inc. stamp the receiver M15 instead of M1A. To this receiver he added M14 and T44E5 parts he had accumulated to create the only known M15 rifle ever built.

U. S. Army Snipers and the XM21 and M21

Before 1985, U. S. Army sniper schools were operated at the division or base command level. From 1956 until 1985, the USAMTU either sent out Mobile Training Teams to combat theaters to train instructors or trained them at Fort Benning, GA to staff up the sniper schools as needed. As the involvement of the Army wound down in a given conflict, the sniper schools were dissolved until the next time they were needed. After

1985, the USAMTU no longer taught sniper school instructors. Now known as the Army Marksmanship Unit (AMU), it is involved with competition shooting and small arms development. The U. S. Army sniper school at Fort Benning, GA was established about 1985 and is a separate command from the AMU. The U. S. Army five week sniper course average student failure rate was 32 % from 2000 through 2004.

The instructors trained at Fort Benning by the USAMTU were sent to the Republic of Viet Nam to establish division sniper schools beginning in June 1968. For example, the 9th Infantry Division sniper school was established at Dong Tam, Dinh Tuong, the 23rd Infantry Division sniper school was based at Chu Lai, Quang Tin and the 25th Infantry Division sniper school was located at Cu Chi, Tay Ninh. In February 1969, the 9th Infantry Division sniper school taught thirty soldiers from the 101st Airborne Division to help establish a sniper school for that division.

On a side note, one of the AMTU staff members is particularly noteworthy in M14 rifle history. Sergeant First Class Gerald "Hook" Boutin, U. S. Army (Retired) fought in World War II at the Battle of the Bulge. He was assigned to the USAMTU beginning in 1954. SFC Boutin built XM21 rifles and was a 23rd Infantry Division sniper school instructor during the American involvement in the Republic of Viet Nam. SFC Boutin was also a service rifle competition shooter. He built accurized semi-automatic M14 type rifles for civilian shooters for decades after the American military pull out from the Republic of Viet Nam. During a six week period he took on the Springfield Armory, Inc. M1A workload for Glenn Nelson while Mr. Nelson was recovering from an illness. Even in his eighties, he was bedding stocks and otherwise tuning up M14 type rifles for civilian shooters. This included putting his accurizing touch to M1A SOCOM rifles as late as August 2007.

SFC Boutin was recognized for his service to the U. S. Army and the American people by his induction into the AMU Hall of Fame on October 23, 2004. His custom built M14 type rifles leave no tell tale signature of his gifted touch other than black color bedding material if the particular stock was bedded by him.

Essentially, the XM21 and M21 rifles were scoped M14 NM rifles. The XM21 weighed 11 pounds by itself and 14 pounds 5 1/3 ounces with equipment. The M14 rifle was used for sniping duty as early as 1965. The U. S. Army 11th Air Assault Division had M14 rifles equipped with M84 scopes on aluminum mounts made by the USAMTU.

In March 1967, the Army Weapons Command shipped the first 125 M84 scoped M14 NM rifles to the Republic of Viet Nam for use by Army snipers. The 101st Airborne Division had 226 M84 scoped M14 NM rifles in February 1969 while deployed in the Republic of Viet Nam. The USAMTU supported the Army sniper program in the Republic of Viet Nam beginning in June 1968 and ending in December 1970. From January 1971 until 1972 when the last major combat elements of the U. S. Army left Viet Nam, Rock Island Arsenal provided support for the XM21 rifle in that theater.

M14 NM rifles equipped with M84 scopes were in use in Viet Nam even after the XM21 with the ART scope was fielded. For example, U. S. Army Private First Class Frank William Humes carried a M14 NM rifle fitted with a M84 scope during combat missions in 1969 as a LRRP member in K Company 75th Ranger Battalion 4th Infantry Division operating in the northern highlands of the Republic of Viet Nam. On July 08, 1969, PFC Humes and two other Army Rangers were inserted behind enemy lines by rope ladder from a UH-1 helicopter. Upon landing, the three Rangers came under intense enemy fire from North Vietnamese soldiers. Regretfully, PFC Humes was mortally wounded during the fight. Reinforcements were called in to turn the tide of the battle and his body was not left behind.

U. S. Army armorers in the Republic of Viet Nam manufactured two M14 scope mounts. Both versions used steel angle iron with a machined rail secured to the top by three flat head screws. Each scope mount had a hole drilled through the vertical portion to bolt into the M14 receiver. Neither version had a vertical key to fit the receiver vertical groove. One version had a horizontal weld bead on the vertical inside surface. The weld bead was filed down to neatly fit the receiver horizontal groove. The other version had two tapped holes 1 3/4 " apart in the vertical portion of the mount. Two 3/16 " screws were threaded into the holes then filed down to rest in the receiver horizontal groove. The two screws were secured with lock pins.

At the request of Army Major General Julian Ewell, commander of the 9th Infantry Division, sixty-five automatic ranging variable power scoped M14 MTU-NM rifles were delivered to the division's sniper school in the Republic of Viet Nam on October 03, 1968. These M14 MTU-NM rifles were assembled by the AMTU at Fort Benning with early version Adjustable Ranging Telescopes. Known as the ART scope, these were Redfield Gunsight Co. variable power scopes modified by the Limited Warfare Laboratory. Franklin Owen at the Laboratory designed the new scope, supervised its initial fabrication, and named it the ART scope. Lieutenant Colonel Vincent Oddi managed the development of the ART scope project. The Army Weapons Command provided an additional seventy-four M14 NM rifles equipped with the M84 2.2 X scope to the same sniper school.

The automatic ranging variable power scoped M14 MTU-NM was designated the XM21 by the U. S. Army Weapons Command at Rock Island Arsenal on September 18, 1969. This designation remained until 1972 when it became the M21. The XM21 was type classified as Standard B in December 1971. The primary reason for this classification was due to the rifle requiring armorer support. Issues related to the Sionics M14SS-1 sound suppressor, the M2 bipod and performance of the XM21 system under severe weather conditions were factors in the decision taken by the Department of the Army to classify it as Standard B.

The XM21 and M21 were both equipped with an automatic ranging variable power telescope and National Match iron sights. By no later than May 1967, M14 NM rifles were

being rebuilt by Rock Island Arsenal for sniping duty. XM21 rifles were either stamped or etched XM21 on the flat surface just behind the rear sight. The selector shaft was not welded on the XM21. Conversion to XM21 configuration included accurizing and installation of a standard contour National Match barrel and marking the scope mount with the last four digits of the receiver serial number by use of a Hermes engraving machine. These gunsmithing procedures were codified in late 1968 by Colonel Frank Conway when he wrote the original edition of the USAMTU Accurized National Match M14 Rifle "M14 (MTU-NM)." This document became the build manual for the XM21. Colonel Conway was the Ordnance Officer for the USAMTU at Fort Benning from 1966 to 1970. He passed away on April 25, 2011. The USAMTU performed final acceptance tests on the XM21 rifles. The XM21 rifles that had passed testing were sent to Anniston Army Depot for packing and shipment to Army units in the Republic of Viet Nam. A few of the XM21 rifle stocks were camouflaged after arrival in Viet Nam. At least a few of the XM21 rifles shipped to the Republic of Viet Nam were assembled with USGI synthetic stocks.

On February 14, 1969, the U. S. Army authorized funding for accurized and scoped M14 rifles through Project ENSURE 240 for its snipers in the Republic of Viet Nam. The first sixty-five XM21 rifles were built by the Limited Warfare Laboratory. These rifles arrived at the 9th Infantry Division on October 03, 1969. The U. S. Army Weapons Command at Rock Island Arsenal was tasked with building these rifles per AMTU specifications. Frankford Arsenal fabricated the scope mounts and purchased modified scopes from Redfield Gunsight Company for the project. The first 100 such rifles from Rock Island Arsenal were delivered to the USAMTU at Fort Benning in October 1969 for evaluation and adjustment. Rock Island Arsenal built 1,435 XM21 rifles from October 1969 to March 1970. By April 1970, more than 1,300 XM21 rifles were in use in Viet Nam.

At a minimum, scoped M14 NM and XM21 rifles were used by snipers from the 1st Cavalry Division, 1st Infantry Division, 9th Infantry Division, 23rd Infantry Division, 25th Infantry Division, 101st Airborne Division, and the Military Assistance Command Vietnam/ Studies and Operations Group (MACV/SOG) in either Viet Nam or Cambodia. The scoped M14 NM and XM21 rifles were typically supplied with 172 grain M118 match grade ammunition. However, 23rd Infantry Division snipers were sometimes given five full magazines of handloaded ammunition with 168 grain Sierra hollow point match bullets and Lake City brass by a certain enterprising instructor. The ammunition was handloaded by the sniper instructor on a bench at his "hooch." His tent was located outside the compound away from scrutinizing eyes. At the time, this type of ammunition was not authorized. Nonetheless, such ammunition worked very well for its intended purpose.

Per request from the U. S. Navy, the Army MTU built and shipped forty accurized and scoped M14 rifles to the Republic of Viet Nam in 1969 for use by sailors on river patrol boats. However, these forty M14 rifles were furnished with conventional fixed magnification scopes and not the ART scopes.

After 1970, USGI National Match standard contour barrels were no longer available for several years. Consequently, the U. S. Army Weapons Command purchased match grade barrels for the XM21 and M21 from commercial barrel manufacturers such as Douglas, Shilen and Hart. XM21 and early M21 rifles had a bedded and epoxy impregnated wood stock. The epoxy impregnating process was described in the Accurized National Match M-14 Rifle "M-14 (MTU-NM)" manual. The XM21 rifles did not have receiver lugs. Some M21 rifles in the late 1980s were built with a rear lug under and extending behind the receiver heel. Later M21 rifles were issued with a fiberglass stock and a medium weight match grade barrel. XM21 and M21 rifles had the M14 stamping lightly ground out and the marking XM21 or M21, as applicable, engraved on the receiver heel.

Although the M24 was officially adopted in 1988, the M21 remained in service with the U. S. Army until at least March 1991. In June 1990, the 101st Airborne Division was in the process of issuing M24 sniper weapon systems at the company level to replace the M21 rifles. The M24 systems were to be issued throughout the division before any of its M21 rifles were turned in. With the pending deployment to Saudi Arabia, the decision was taken by a number of company commanders, A Company 1st Battalion 327th Infantry Regiment and others, to deploy with the M21 rifles. According to one such company commander, (later Lieutenant Colonel) John Russell, the M21 rifles "held up to the desert environment great and maintenance was not a problem." In 1990, each rifle company in the 101st Airborne Division typically had three M21 rifles assigned to each platoon for a total of nine. On March 08, 1991, the first American troops returned home from Operation Desert Storm. In late 1992 or early 1993, the 2nd Battalion 325th Infantry Regiment 2nd Brigade 82nd Airborne Division had its nine M21 rifles removed from inventory, disassembled, and the receivers torch cut by U. S. Army armorers by orders from higher authority.

In the Republic of Viet Nam, 9th Infantry Division sniper school students were each issued a starlight scope with their XM21 rifles. The AN/PVS-1 and AN/PVS-2 models used mounting brackets that situated the scopes over the receiver but to the left of the bore centerline. Some of these brackets were marked SC-D-607-130. The AN/PVS-1 and AN/PVS-2 scopes were first generation technology night vision devices. The Night Vision Laboratory, a part of the U. S. Army Electronics Command (ECOM) by November 1965, began development of the AN/PVS-1 starlight scope in 1961. In 1965, ECOM was based at Fort Monmouth (NJ) and was then a subordinate command of the U. S. Army Materiel Command. The AN/PVS-1 went into production under contract in September 1964 with Electro-Optical Systems, Inc. The AN/PVS-1 scope had been fully developed and a U. S. Army Training Circular written for it by November 1966. It weighed 5 pounds 14.75 ounces. The AN/PVS-2 starlight scope arrived in Viet Nam by early 1967 and replaced the AN/PVS-1 for night shooting by 1969 among U. S. Army snipers. The AN/PVS-2 was more rugged than its predecessor but weighed one pound more and was about an inch longer. The smaller AN/PVS-3, manufactured by Varo, Inc. and Machlett Laboratories,

Inc. (Springdale, CT), was used as early as May 1968 in the Republic of Viet Nam by American snipers as a hand-held night vision monocular for spotting enemy activity. The AN/PVS-3 weighed 3 pounds. These three night scope models were 4X magnification.

The variable power automatic ranging telescope used on the XM21 rifles was conceived by James M. Leatherwood in 1964 and developed by the Army Limited Warfare Laboratory beginning in late 1965. James Leatherwood's design improvement consisted of using a cam connected to the scope's variable power ring to adjust the elevation as the user increased or decreased magnification until vertical stadia bracketed a known distance. This created an automatic bullet drop compensator. Leatherwood's adjustable trajectory rifle scope ideas were patented in 1967, 1969 and 1970. The Viet Nam era Leatherwood scopes were cammed for the M80 and M118 cartridges. The Leatherwood design scope provided an easy means of obtaining center-of-mass first round hits under combat conditions. Early scope mounts used a single mounting screw developed by the USAMTU and the Limited Warfare Laboratory at the Aberdeen Proving Ground. This mount was made from 7075 T6 alloy aluminum. It was finished with a black color chromic acid anodized coating.

The Limited Warfare Laboratory at Fort Benning, GA modified Redfield Gunsight Company Accu-Range scopes for the first and second versions of the Adjustable Ranging Telescope (ART). The first version ART scopes were sent to the Republic of Viet Nam in 1967 for evaluation under combat conditions. The third version of the original ART scope was wholly manufactured by Redfield Gunsight Co. in support of Project ENSURE 240. That model became known as the ART TEL.

While on active duty in the U. S. Army, James Leatherwood made arrangements with Realist, Inc. to incorporate his automatic ranging telescope design into its fixed power Auto/Range scopes in 1968 and its variable power Camputer scopes in 1969. That same year, Realist, Inc. developed its version of the ART I scope for military use. Realist, Inc. submitted the variable power automatic ranging scope to the U. S. Army for testing. The U. S. Army tested the Realist ART I scope in 1970 but it was not adopted. The major differences between the Redfield ART TEL and Realist ART I models were the reticle design and the means of adjusting the vertical angle of the scope tube. The third version Redfield ART TEL scope had an anodized matte black finish. The Realist ART I scope was given a matte dark gray coating.

James Leatherwood left the U. S. Army as a Captain in 1969 after four years having served at the U. S. Army Infantry School (Fort Benning, GA) and in the Republic of Viet Nam. He worked at Realist, Inc. until early 1970. Mr. Leatherwood was then employed by Sionics, Inc. for a period of time before he and his brother, Charles, established Leatherwood Bros. (Stephenville, TX). In the first half of 1974, Realist, Inc. had decided to get out of the rifle scope business. The remaining inventory of Realist ART I scopes, ballistic cams and scope mounts were purchased by Leatherwood Bros.

The company modified the ART I design to increase service life and reliability. The Leatherwood Bros. ART II scope was developed by 1978. The ART II scope had separate power magnification and ballistic cam adjustment rings. Both Realist ART I and ART II scope tubes were made from alloy aluminum. The U. S. Army approved of this upgraded design and ordered its first purchase of ART II scopes in June 1980. Leatherwood Bros. delivered the first batch of ART II scopes to the U. S. Army in December 1981.

Various ballistic cams were available for the ART II scope according to the ammunition in use. Mounts for the ART II scope had a second mounting screw. Leatherwood Bros. produced a rear mounting block for the ART II scope mount that replaced the cartridge clip guide. For reasons unknown, U. S. Army M21 rifles did not use this rear mounting block. Instead, the issue cartridge clip guide was drilled and tapped to accept the second mounting screw. Note that the Springfield Armory, Inc. Third Generation scope mount substitute cartridge clip guide will not accept the U. S. Army ART II scope mount rear screw.

The ART TEL scopes were mostly replaced in 1981 and later by Leatherwood Bros. ART II scopes. Rock Island Arsenal has rebuilt ART scopes as needed. Apparently, a few ART TEL and ART II scopes were still in the inventory of the U. S. Army in 2004. U. S. Army Special Forces at Fort Bragg, NC in November 2004 shipped ART TEL and ART II scopes to U. S. soldiers in Iraq.

M14 Product Improved Rifle

Beginning in 1970, the U. S. Army Materiel Command funded a project at the General Thomas J Rodman Laboratory (Rock Island Arsenal) to further improve the M14 rifle. A civilian employee, Robert E. Snodgrass, headed the project. As an aside, Mr. Snodgrass developed a side two point scope mount for the M14.

Three prototype rifles for the project were produced. Each rifle weighed approximately 10 ½ pounds with sling and empty magazine. These 43 " long rifles had 24 " heavyweight stainless steel barrels, two bedding lugs, improved gas systems, laminated walnut stocks, no hand guard, hooded target grade front sight, and no select fire components including removal of the selector lug. The bedding lugs on the first prototype model were located at the front and rear ends of the receiver. The bedding lugs for the second and third prototype rifles were placed at the front of the receiver lug and the operating rod guide. The barrel on the first prototype rifle was broach cut. Remaining barrels for the M14 Product Improved Rifle project were to be made by the hammer forging method. These rifles grouped less than two minutes of angle at 100 yards with M118 ammunition. This was about a 100 % improvement over the acceptance standard of the M14 NM rifle specifications in 1975. By 1975 the funding for this project was stopped.

XM25 and M25

The M25 rifle is an improved version of the M21. In 1986, the 10th Special Forces Group at Fort Devens, MA had its own machine shop and ammunition reloading shop to support the unit's sniper weapon systems. While the ART II scope and side two point scope mount design were great improvements for the M21 over the original XM21 configuration, these optical systems were still prone to loss of zero when knocked around in the field. The condition of the bedding compound in the XM21 and M21 rifles deteriorated with removal of the receiver and barrel for cleaning and maintenance. The bedding compound in use at the time was also susceptible to chemical attack from various oils. Loss of the bedding material further worsened accuracy by causing the receiver to shift around in the stock.

To alleviate these problems, 10th Special Forces Group armorer Sergeant First Class (later Master Sergeant) Thomas E. Kapp, sought to improve the M21 rifle. So, he and Master Sergeant Bill Amelung, worked with Mitchell E. Mateiko, owner of Brookfield Precision Tool, to develop the XM25 rifle between 1986 and 1988. Master Sergeant Amelung was the Non-Commissioned Officer-In-Charge of the 10th Special Forces Special Operations Target Interdiction Course. Mitch Mateiko had served in the Army National Guard and worked as a tool and die maker for the M14 project at Harrington & Richardson, Inc. Brookfield Precision Tool was located at 126-A Quaboag Street Brookfield, MA 01506. After 1996, Mr. Mateiko went on to become a law enforcement officer in Massachusetts.

Meanwhile, higher authority within the U. S. Army sought Congressional funding to change its sniper rifle from the M21 to the M24 bolt action rifle. This effort was successful with the M24 officially replacing the M21 as the sniper rifle for the U. S. Army in 1988. U. S. Army General Guest, in Congressional testimony seeking funding for the M24 rifle, was of the opinion that the M21 rifle was at the end of its usefulness as a sniper weapon system. Consequently, the development of the XM25 rifle continued quietly. The rifle produced by the 10th Special Forces Group and Brookfield Precision Tool was classified as the XM25 since the M21 was no longer considered viable by higher authority. The 10th Special Forces Group intended for the XM25 rifle to be carried by the sniper team observer in urban operations with an effective range of 600 meters. The XM25 was found to be as accurate as the M24 in the late 1980s when both rifles used M118 Special Ball ammunition. In 1991, the U. S. Army designated the XM25 as the M25. The XM25 / M25 saw combat service in Panama in 1989, the 1990-1991 Gulf War, and in Afghanistan in 2002. The M25 was not adopted throughout the U. S. Army Special Forces but it did serve admirably as the sniper team spotter's rifle in the 5th and 10th Special Forces Groups.

The M14 SSR rifles were built by Naval Surface Warfare Center (Crane, IN). The U. S. Navy SEALs used the M14 SSR until at least 2000. In May 2000, the U. S. Navy

awarded a sole source contract to Knight's Armament Company for 300 SR-25 rifles built to its specifications. The Navy version of the SR-25 was adopted as the Mk 11 Mod 0. In late 2005, the U. S. Army had plans to replace its M24 bolt action sniper rifle with the XM110. The XM110 sniper weapon system was based on the Knight's SR-25 rifle as well. By mid-2007 the XM110 had been officially classified as the M110. The M110 began replacing U. S. Army M24 sniper rifles in early 2007.

Initially, the XM25 rifle did not mount a bipod and it was fitted with a 10th Special Forces Group made scope mount. But as adopted, the XM25 design specification required the rifle to have a synthetic material stock, a medium weight match grade barrel, a Harris bipod and the following Brookfield Precision Tool parts: steel stock liner, operating rod spring guide, scope mount, and titanium nitride coated gas piston. Various Harris bipod models were employed by Special Forces operators but over time the notched-leg swiveling bench rest height model (HBRM-S) was the typical bipod found on U. S. Army issue M25 rifles. A bipod was not always used in the field with the M25 rifle. Often, the M25 rifle was steadied with a ruck sack or a sock containing a plastic bag filled with cooked popcorn for making the shot.

The Brookfield Precision Tool operating rod spring guide was machined with four flat sides on the shaft to reduce friction with the operating rod spring and as an allowance for debris. After all, the XM25 was expected to be used in combat operations. Otherwise, the operating rod spring guide was made by the traditional means of welding a machined vice stamped magazine catch to the slotted end of the shaft. The Brookfield Precision Tool operating rod spring guide was hardened by heat treatment after welding. Consequently, these spring guides did not suffer from premature wear at the magazine catch like the AMTU models. It has the tapered forward end similar to the AMTU operating rod spring guide. A small number, one or two production batches, were not marked with the Brookfield Precision Tool name. The side three point scope mount, modified operating rod spring guide, and gas piston titanium nitride coating employed in the XM25 were innovative developments. Brookfield Precision Tool parts were not assigned National Stock Numbers.

Two side three point scope mount designs were tested by the U. S. Army for the XM25 rifle. The Atlantic Research Marketing Systems, Inc. (West Bridgewater, MA) scope mount was tested by the 82nd Airborne Division and by the 10th Special Forces Group during development of the XM25. The 10th Special Forces Group also tested a scope mount made by Brookfield Precision Tool. The U. S. Army settled on the Brookfield Precision Tool model by 1988 for the XM25 rifle specification.

Optics on the M25 varies according to unit preferences. The U. S. Army XM25 rifles were first outfitted with Leupold & Stevens, Inc. M1 Ultra and Bausch & Lomb Tactical scopes followed by Leupold & Stevens, Inc. M3 Ultra models. Army Special Forces M25 rifles today typically sport the Leupold & Stevens, Inc. M3A 10X scope and Mark 4 scope rings. U. S. Navy SEALs have employed both Bausch & Lomb Tactical and Leupold & Stevens,

Inc. 10X scopes on its M14 SSR rifles. Brookfield Precision Tool also produced an adapter for its scope mount to accommodate the AN/PVS-4 night scope. The AN/PVS-4 second generation technology night scope was field tested in 1974 and later manufactured for the U. S. Army in 1980 and 1981. U. S. Army 10th Special Forces Group successfully used the XM25 fitted with AN/PVS-4 scope and Brookfield Precision Tool scope mount and adapter during Operation Desert Storm. Generation III image intensifier tubes were available for the AN/PVS-4 by 1999.

The Brookfield Precision Tool gas piston was coated with titanium nitride on the larger cylindrical diameter but not on the smaller diameter portion. The company made more than 6,000 titanium nitride coated gas pistons in two versions. Both used part number 7267047. The Revision 1 gas piston had the standard diameter gas inlet. The Revision 2 had a 0.0625 " diameter gas inlet. Only a relatively few 7267047 Revision 2 gas pistons were made. The Revision 2 gas pistons were designed for use in sound suppressed M14 type rifles with 22 " barrels firing M852 or M118 cartridges. The U. S. Navy purchased 7267047 Revision 2 gas pistons for use with its suppressed M14 SSR rifles. The U. S. Army and U. S. Marine Corps did not purchase the Revision 2 gas pistons. For sound suppressed M25 rifles, the U. S. Army welded and drilled the gas piston gas inlet to a smaller diameter and also drilled an approximate 0.030 " diameter hole in the center of the gas cylinder plug in order to keep the chamber pressure and the force acting on the operating rod to acceptable values.

The XM25 rifle had a machined and welded AISI 1018 carbon steel liner placed inside the stock to allow removal of the stock without loss of scope zero. It was given a manganese phosphate finish. The steel stock liner was designed by Master Sergeant Tom Kapp. The design was successful because it allowed the sniper to remove the barrel and receiver from the stock, clean the weapon and reassemble the rifle without a loss of scope zero. Two U. S. Navy M14 SSR rifles were built by Naval Surface Warfare Center (Crane, IN) with the XM25 steel stock liner as an experiment. However, the stock liner was time consuming to produce so it was not kept as part of the M25 rifle specification. The M25 rifle, as used by the U. S. Army, typically sported either a McMillan M1A or M2A bedded stock without the steel liner but had a Freeland adjustable butt plate and match grade heavyweight Krieger, Hart or Barnett barrel. The M25 rifle did not have a rear receiver lug. The spindle valve was operable and the selector lock was not welded. The M25 gas system was not shimmed but unitized by welding the gas cylinder to the front band at six and twelve o'clock. The gas cylinder was modified by drilling a 1/16 " diameter hole at six o'clock through the trepang groove. The trepang groove was a 3/32 " wide radial groove machined into the bore of the gas cylinder at its rear end.

M14 SMUD

U. S. Air Force Explosive Ordnance Disposal (EOD) units were equipped with the M14 Standoff Munitions Disruptor SMUD rifle. The M14 SMUD rifles in the inventory of the U. S. Air Force EOD unit in the Republic of Korea in 1990 had wood stocks and commercial

manufacture Redfield variable 3-9X magnification rifle scopes. The M14 SMUD was assigned a separate National Stock Number from other M14 variants. It was eventually displaced by the M82A1 .50 BMG semi-automatic rifle in U. S. Air Force EOD units by 1996 or 1997. Reportedly, the M14 SMUD was also in use by U. S. Navy EOD units in 1990s. However, in June 2007, the U. S. Air Force 48th Rescue Squadron based out of Davis-Monthan AFB (Tucson, AZ) had ten M14 SMUD rifles in its inventory. These rifles had bedded oversized wood National Match stocks, chromium plated standard contour barrels, standard USGI sights, selector locks installed and traditional daylight scopes mounted on side three point mounts.

M14 DMR

The U. S. Marine Corps adopted a Designated Marksman Rifle and established a Designated Marksman School (Mare Island, CA) by no later than 1992. Initially, the Pacific Fleet Marine Corps Security Force Battalion was equipped with IMI Galil rifles and Nimrod scopes to serve as the Designated Marksman Rifle. The Galil rifles did not provide satisfactory service for the Fleet Antiterror Security Team (FAST) Company according to a Marine in the Weapons Platoon during this period. By 1993 or earlier, the U. S. Marine Corps chose the M14 rifle to become its Designated Marksman Rifle (DMR). The M14 DMR was classified as a precision grade, semi-automatic 7.62 mm NATO caliber rifle and weighed 13 pounds with its issue equipment. The M14 DMR enabled the shooter to deliver accurate semi-automatic fire against multiple targets at greater distances and with greater lethality than with the M16A2. In 2003, Marines selected to become a Designated Marksman attended a four week course given at installations such as Marine Corps Base (MCB) Quantico (VA) and Camp Lejeune (NC).

In August 1998, the U. S. Marine Corps Systems Command negotiated three sole source commercial item contracts for scope mounts and rings, barrels and stocks. McMillan Fiberglass Stocks (Phoenix, AZ) supplied 253 M2A stocks for the M14 DMR. To each M14 DMR stock, a Harris bipod was mounted under the forearm. GG&G (Tucson, AZ) provided 253 M1A1 scope mounts and 253 pairs of Sniper Grade Medium 30 mm scope rings. GG&G had shown its scope mount to the U. S. Marine Corps in 1997. More recently, Badger Ordnance supplied 30 mm scope rings for the M14 DMR. In 2003, the Precision Weapons Shop at MCB Quantico had designed and was capable of producing a scope mount for the M14 DMR.

Accuracy International is a firearms manufacturer known for its Arctic Warfare series bolt action sniper rifles. A British rifle match shooter, Malcolm Cooper, founded Accuracy International, Ltd. in 1978. Mr. Cooper went on to earn gold medals at the 1984 and 1988 Summer Olympics. In 1986, he was the 300 Meter Standard Rifle world champion. The company opened a stateside plant, Accuracy International North America, Inc., in 1997. Mr. Cooper passed away on June 09, 2001 from cancer. Accuracy International, Ltd. was sold to a new British owner in March 2005.

Cooper Precision Manufacturing (Oak Ridge, TN) was owned by Accuracy International, Ltd. (United Kingdom) and its American subsidiary, Accuracy International North America, Inc. Cooper Precision Manufacturing sold 278 barrels for the M14 DMR in 1998 to the U. S. government. Reportedly, the Cooper Precision Manufacturing barrels were found to not meet the external dimensional specifications so they were not used. Cooper Precision Manufacturing struggled financially and was finally closed down by the parent company. The remaining material stock was sold to two individuals who produced quality match grade stainless steel barrels. Mike Rock, in late 1996 and 1997, and Krieger Barrels, Inc. have supplied match grade barrels to the U. S. Marine Corps for M14 DMR rifles.

M14 DMR rifles were built at the Precision Weapons Shop, Weapons Training Battalion, Training and Education Command. The Training and Education Command is a subordinate command under the Combat Development Command at MCB Quantico. U. S. Marines trained as armorers at the Precision Weapons Shop are assigned to build and maintain accurized sniper and marksman rifles including the M14 DMR. This is all done with a modern array of Computer Numerical Control (CNC) machine tools. The Weapons Training Battalion is tasked with training scout-sniper, designated marksman, officer candidate and small arms instructor students.

The M14 DMR has sported Unertl and Leupold & Stevens, Inc. variable 3.5-10X and fixed 10X daylight scopes and the AN/PVS-4, AN/PVS-10 and AN/PVS-17 night vision scopes. The initial ammunition issued for these rifles was the M118 round but that was later replaced with the 175 grain M118LR cartridge. The M118LR round makes the M14 DMR effective to a greater distance. Some M14 DMR rifles have been equipped with OPS, Inc. combination sound suppressor and muzzle brake attachments. The M14 DMR was typically built with a Krieger Barrels, Inc. 22 " 1:12 twist rate match grade medium weight barrel, McMillan M2A stock with adjustable cheek rest and butt stock spacers, bipod, side three point scope mount, reamed flash suppressor and armorer fitted parts. The M14 DMR iron sights were a standard M14 rear sight assembly and a M14 NM front sight.

Every M14 DMR was required to be proof fired with one pressure test round and thirty M118 rounds of ammunition. The accuracy test for every M14 DMR consisted of a check list of items including shot grouping no more than 3 " by 3 " at 300 meters. The successful proof firing was indicated on the exterior of the barrel right hand rear end. The barrel was stamped with 1/16 " size letters in the following manner: PWS – P on the top line and the month and year below that. PWS denoted Precision Weapons Section and P meant the barrel was proof fired.

The 4th Marine Expeditionary Brigade (Anti-Terrorism) was formed at Camp Lejeune on October 29, 2001 in response to the terrorist attacks against the United States of America on September 11, 2001. The 4th MEB (AT) consisted of five subordinate commands: Marine Corps Security Force Battalion, Marine Security Guard Battalion, Antiterrorism Battalion, Chem-Bio Incident Response Force and the Foreign Military Training Unit. The

4th MEB (AT) was deactivated on February 24, 2006. The Marine Corps Security Force and Antiterrorism Battalions and the Chem-Bio Incident Response Force were reassigned to the II Marine Expeditionary Force. The Marine Security Guard Battalion was transferred to the Marine Corps Combat Development Command. The Foreign Military Training Unit became part of the newly established U. S. Marine Corps Forces Special Operations Command. During the existence of the 4th MEB (AT), the M14 DMR was issued to the Marine Corps Security Force Battalion, Marine Security Guard Battalion and the Antiterrorism Battalion. The M14 DMR rifles built in the 1990s were transferred to the 4th MEB (AT) at the request of its first Commanding General, Brigadier General (later Major General) Douglas V. O'Dell, Jr.

The M14 DMR was first used in hostile action from July through November 1993 with the FAST Company 5th Platoon in Mogadishu, Somalia in support of United States and United Nations military forces. The 26th Marine Expeditionary Unit put the M14 DMR to good use from November 2001 to February 2002 while engaged in Operations Enduring Freedom and Swift Freedom to seize Camp Rhino and the Kandahar Airport in Afghanistan. In Afghanistan, the U. S. Marines had OPS, Inc. sound suppressor and muzzle brake attachments available to them for the M14 DMR rifles. The Marines used AN/PVS-10 day/night scopes on the M14 DMR rifles and shot with M118LR ammunition. The Marine Corps U. S. SOCOM Detachment deployed to Iraq from April to October 2004 with the M14 DMR in its Table of Equipment. Less than two weeks before the November 07, 2004 attack on Fallujah, U. S. Marines of the Regimental Combat Team 7 were test firing the M14 DMR on a small arms range at Al Asad, Iraq.

Beginning in December 2001 until at least November 2003, a detachment from the 4th MEB (AT) provided additional security for the U. S. Embassy in Kabul, Afghanistan. The Marines occupied the roof top of the embassy round the clock in two man teams with M14 DMR rifles fitted with Leupold & Stevens, Inc. variable 3.5-10X day scopes and supporting equipment as part of the additional security provided to embassy personnel. The M14 DMR was also used by USMC Explosive Ordnance Disposal and Military Police units. As of mid-2007, the U. S. Marine Corps had 381 M14 DMR rifles in its inventory. In early 2008, the M39 Enhanced Marksman Rifle was replacing the M14 DMR.

M39 EMR

The U. S. Marine Corps field tested the M39 Enhanced Marksman Rifle (EMR) in 2007. Operator and intermediate maintenance level technical manuals were written by March 2008. The Precision Weapons Shop of the Weapons Training Battalion (MCB Quantico) built M39 EMR rifles from M14 DMR rifles. The M39 EMR began to replace the M14 DMR by early 2008. It was issued with five magazines. The Marine Corps inventoried 621 M39 EMR rifles as of mid-2009. The most significant difference between the two rifle models was the stock. The M39 EMR was built on a late second generation Sage International, Ltd. M14 stock that lacked a barrel tensioning screw but included a unique

recoil pad spacer. The M14 DMR barrel was retained for the M39 EMR. The M39 EMR weighed 13 pounds without equipment and 16.6 pounds fully loaded. Its maximum effective range was 770 meters and maximum rate of fire was 60 rounds per minute. The issue optical scope was a Premier Reticles M8541 scope secured with Badger Ordnance rings atop a Smith Enterprise, Inc. scope mount. The selector shaft was welded to the selector lug rendering it incapable of automatic fire. In August 2010, Marine Corps Systems Command approved fielding of the M110 to replace the M39 EMR in 2012.

U. S. Marine Corps Scout-Snipers and the M14 Rifle

Officially, the U. S. Marine Corps has never adopted the M14 rifle or any variant as its primary sniper rifle. Marine Corps scout-sniper schools were conducted in-theatre during the war in the Republic of Viet Nam. For example, in March 1966, the 4th Marine Regiment established a three week scout-sniper school at Phu Bai, Thua Thien. Marine scout-snipers in the Republic of Viet Nam were issued the pre-1964 Winchester Model 70 .30-06 caliber bolt action rifle or the M1D semi-automatic rifle. Marine snipers carried the Winchester Model 70 until December 1967. The Remington Model 700 7.62 x 51 mm bolt action rifle was first issued in April 1966. By December 1967, the Marine scout-snipers had turned in their Winchester Model 70 rifles for the Remington rifles. Since the 1970s, the Marine Corps has refined the Remington Model 700 into the M40A1 and M40A3 models. The scout-sniper nine week basic course failure rate was approximately 50 % in 2003 even though all who attend are qualified Rifle Expert.

Like the M14 DMR, the M40 series rifles were built by the Precision Weapons Shop at MCB Quantico. The present day USMC Scout-Sniper School was established in 1977. Gunnery Sergeant Carlos N. Hathcock, II was the first Non-Commissioned Officer-In-Charge. While serving as a U. S. Marine Corps sniper in the Republic of Viet Nam, Gunnery Sergeant Hathcock used a pre-1964 Winchester Model 70 bolt action rifle. Corporal John Roland Burke, (then Sergeant) Hathcock's observer during his first combat tour, carried and used an unscoped M14 rifle for each mission. Corporal Burke put the M14 rifle to good use on a number of sniper missions. Corporal Burke, assigned as Sniper Team Leader with Headquarters & Service Company 1st Battalion 26th Marine Regiment 3rd Marine Division (Reinforced), was later killed-in-action on June 06, 1967 during heavy fighting against the North Vietnamese on Hill 950 at Khe Sanh, Quang Tri, Republic of Viet Nam. He was posthumously awarded the Navy Cross for gallantry in combat that day.

The M14 rifle was no strange bedfellow to Marine Corps scout-snipers in the Republic of Viet Nam. 4th Marine Regiment scout-sniper teams of two to five carried and used select fire capable M14 rifles along with the issue bolt action sniper rifles during operations from November 1966 until at least January 1968 in Quang Tri and Thua Thien provinces. Sergeant Howard J. Greene, a 9th Marine scout-sniper, used a scoped M14 rifle in March 1967 during Operation Prairie II. Likewise, 5th Marine Regiment scout-sniper team

observers used the M14 rifle with devastating effect in late January and early February 1967. The sniper team observers were supporting Marine rifle companies in actions against the Viet Cong R20 Main Force Battalion in Song Thu Bon Valley, Quang Tri during Operation Tuscaloosa. The M14 rifles provided the necessary firepower to break contact with the enemy at close range. This is a useful feature of the M14 for sniper and reconnaissance teams.

The American military presence in the Philippines ceased shortly after the June 1991 eruption of Mount Pinatubo. During the two years prior to this event, the Marine Corps Barracks at Subic Bay Naval Base was authorized one billet for a scout-sniper and one M40A1 rifle. There were a number of scout-sniper school graduates on the roster of the Marine Barracks during this period. As part of their training routine, the Marine Barracks at Subic Bay conducted jungle patrols in the Philippines. In order to make use of the scout-sniper trained Marines during such operations, these particular Marines were equipped with M14 NM rifles sporting ART II scopes. These rifles worked well enough in the Philippine jungle.

M14 Enhanced Battle Rifle

By October 01, 2002, the M14 Enhanced Battle Rifle was officially classified by the U. S. Navy as RIFLE, 7.62MM, MK 14 MOD 0, Enhanced Battle Rifle (EBR). In 2003, Smith Enterprise, Inc. first built its prototype M14 Enhanced Battle Rifle for consideration by the U. S. Navy. It was favorably received. By no later than August 2003, NSWC Crane had concluded its design specification for the M14 EBR. The M14 EBR weighed 11 pounds 10 ounces with a 22 " barrel but no optics or vertical fore grip when evaluated by *Armed Forces Journal* at its February 2004 Shoot-out. The M14 EBR tested by *Armed Forces Journal* was equipped with the late first generation version of the Sage International M14 EBR stock. In 2005, Smith Enterprise, Inc. developed a barrel for evaluation by NSWC Crane for the Mk 14 Mod 1. This AISI 4140 alloy steel chromium plated standard contour 1:10 twist 18 " long barrel was chambered for the M118LR cartridge and headspaced for USGI receivers. Due to budgetary constraints, the SEI barrel was not adopted.

In acceptance testing, the Mk 14 Mod 0 shot five round groups of 12.5 " to 15.7 " at 600 yards with M118LR ammunition. It fared nearly as well with M80 ammunition. Muzzle velocity was 2,675 and 2,511 feet per second with M80 and M118LR ammunition, respectively. The Mk 14 Mod 0 was designed primarily for semi-automatic fire on point targets out to 600 yards. The rifle could be used to engage area targets out to 1000 yards.

The Mk 14 rifles were on a USGI M14 receiver with enhancements including, but not limited to, a fully adjustable stock, a 18 " standard contour molybdenum-chromium alloy barrel, enlarged rear sight aperture, and Smith Enterprise, Inc. combination gas cylinder lock front sight (part number 2013), direct connect flash hider (part number 2000V) and extended bolt lock (part number 2003). The extended bolt lock allowed the bolt to be

released the same way as on M16 type rifles. M14 EBR scope rings allowed the use of iron sights with the scope installed.

The overall length for the Mk 14 Mod 0 was 34.9 " with the stock fully collapsed and 40.9 " with the stock fully extended. The Mk 14 Mod 1 was 37.0 " long with its stock fully collapsed as compared to 30.5 " for the M4A1 Carbine with 14.5 " barrel. The iron sights for both models consisted of an XS Sight Systems 0.125 " diameter rear sight aperture and a Heckler & Koch style hooded fixed post front sight (part number 11-2166S-580-1). The cartridge clip guide was substituted with a M1913 Picatinny rail pad (Sage part number M14SCSB). The selector switch was operable on the Mk 14 Mod 0 but the selector lock was installed on Mk 14 Mod 1 rifles.

The Mk 14 Mod 0 rifles were assembled with late first generation and early second generation Sage International, Ltd. M14 EBR stocks. The vertical fore grip was secured to the six o'clock rail of the Sage International, Ltd. chassis stock. The operator's hand was protected by a single thermoplastic hand guard, or fore grip, also attached to the six o'clock rail with two screws. The stock chassis side rails were covered with Falcon Industries, Inc. ladder style plastic covers (part number 4373CB). The U. S. Navy issued the additional accessories for each Mk 14 Mod 0 rifle: vertical fore grip, two Badger Ordnance 1.25 " EBR 30 mm scope rings, bipod, Eagle Industries 1.5 " wide sling, cleaning kit, two magazines and a soft carrying case. No optics or sound suppressors were issued with the Mk 14 Mod 0 rifles due to funding limitation. The firing mechanisms were not match conditioned.

The Mk 14 Mod 1 was built with the late second generation Sage International, Ltd. M14 EBR stock, TangoDown BG-16 pistol grip, Magpul Compact/Type Restricted (CTR) butt stock and custom cheek rest, and Vltor Weapon Systems RE-2 buffer tube. The accessories for the rifle included a Surefire, LLC FA762K sound suppressor, TangoDown ACB-4 bipod, Eagle Industries 1.25 " wide sling, TangoDown BGV-MK46 vertical fore grip, and TangoDown BGP4 rail covers. The fore grip was made of two pieces. The six o'clock rail was slightly taller than the Mod 0 part, 0.525 ", to allow mounting of a M203 grenade launcher. The Mk 14 Mod 1 had three storage areas, butt stock cheek rest, pistol grip and vertical fore grip. With the issue vertical fore grip but no bipod and no magazine, the Mk 14 Mod 0 weighed 11.4 pounds and the Mk M14 Mod 1 weighed 10.6 pounds. The Harris bipod weighed 0.74 pounds. The TangoDown bipod weighed 1.04 pounds and the sound suppressor weighed 1 pound 3 ounces.

The Mk 14 Mod 0 and Mod 1 rifles were compatible with optics used on the U. S. Army M4A1 Carbine. For optics, the Mk 14 Mod 1 was fitted with a LaRue Tactical LT 608 scope mount, Nightforce 0.885 " URX 30 mm scope rings, and Nightforce NXS 2.5-10X scope. The scope mount prototype for the Mk 14 Mod 1 was designed by NSWG Crane but production was out sourced to LaRue Tactical (Leander, TX). With its issue optics, sound suppressor and match tuned firing mechanism, the Mk 14 Mod 1 could fill the Designated Marksman Rifle role. In acceptance testing for the U. S. Navy, the Mk 14

Mod 1 rifle typically grouped 1.7 " per five rounds of M118LR ammunition at 100 yards.

The U. S. Navy SEALs were able to field the Mk 14 Mod 0 by no later than the first half of 2005. In the second half of 2006, NSWC Crane was building Mk 14 Mod 1 rifles. In May 2007, NSWC Crane was interested in evaluating match grade barrels, additional gas system tuning and round shaft operating rod spring guides to improve accuracy for the Mk 14 Mod 1 rifle. These enhancements were partially adopted in the Mk 14 Mod 2 rifle.

Development of the M14 EBR - Mike Rock started Mike Rock Rifle Barrels, Inc. in 1978. He made National Match and DMR barrels for the U. S. Marine Corps in the 1990s. After some financial struggles and losing his business, Malcolm Cooper hired Mike Rock to make barrels. After Mr. Cooper passed away in June 2001, engineers Jim Ribordy and Mike Rock teamed up as RD Systems (South Beloit, IL). In 2000, Rock Creek Barrels (Albany, WI) was formed. Rock Creek Barrels, Inc. is owned and operated by Mike Rock and Kim Theiler. Mike Rock produces single point cut rifle barrels. Kim Theiler manufactures pull button rifle barrels. To date, Mike Rock has personally fired over 1,000,000 rounds through firearms. He holds a Master's degree in Mechanical Engineering and an honorary Doctorate in Metallurgical Engineering.

About 2001, Mike Rock was asked by U. S. Army Lieutenant Colonel Gus Taylor at Naval Surface Warfare Center Crane, IN to participate in the SOPMOD Conference at Fort Benning, GA. SOPMOD is a military acronym for Special Operations Peculiar Modification. This term is used to denote that a weapon system has been modified for use by the U. S. Special Operations Command. Mike Rock was the sole barrel maker invited to this conference. Colonel Taylor asked Mike Rock to design a shortened M14 rifle. A contract was signed with NSWC Crane and the project began. As part of the project, Mike Rock was given ten M14 rifles to be used to develop the SOPMOD M14. Mr. Rock thought about the M14 design and how to improve upon it. He came up with the idea to reorient the gas system so that it was in line with the bolt roller. He made a wood mock up at first. It showed to be very promising so further development work was done. Malcolm Cooper and Mike Rock sketched out a "V" block two half stock for an Accuracy International bolt action rifle. This is where the concept of the two half synthetic stock originated. Mike Rock then measured and machined a prototype two half stock that had a wooden fore end with an aluminum channel. After this, Colonel Taylor informed Mike Rock that a collapsing stock was desired for the SOPMOD M14.

Mike Rock then created an aluminum stock body with steel telescoping rails. It allowed the barrel and gas system to float freely. The redesigned SOPMOD M14 gas system pushed directly in line with the bolt roller and reduced barrel whip. This gas system has been patented by Mike Rock under RD Systems. The original USGI M14 barrel was replaced with a 1:11.27 twist five radial groove heavy pull button barrel. Barrel twist rate is defined as how far the bullet must travel down the barrel before it has spun one revolution, e.g., 1:10 means a bullet will turn one revolution for every 10 " of barrel length. A faster twist rate is generally used to stabilize heavier and longer bullets in flight.

It was found through testing that acceptable accuracy could be maintained with as short a barrel as 11 " with this design but the noise level was excessive. All of this work was done by Mike Rock and Jim Ribordy working together at RD Systems. Jim Ribordy hand delivered the prototype SOPMOD M14 to Colonel Taylor at NSWC Crane, IN. Mike Rock's SOPMOD M14 was tested at Fort Campbell, KY by a U. S. Army 5th Special Forces Group soldier. It was also test fired by Colonel Taylor. The results were impressive. Initially, OPS, Inc. designed sound suppressors were used in concert with the SOPMOD M14. These SOPMOD M14 sound suppressors were manufactured by RD Systems. For whatever reasons, this design was not adopted for military use by NSWC Crane but it was available in the commercial market until October 2006.

In the summer of 2002, NSWC Crane supplied a stock design to Sage International, Ltd. Sage International, Ltd. produced alloy aluminum stocks for evaluation. The 2002 NSWC stock design included ambidextrous sling attachment points and full length six and twelve o'clock Picatinny accessory rails. A M203 grenade launcher was installed on a M14 EBR and tested. The loaded M203 added just too much weight to the front end of the system to make it practical. Consequently, the grenade launcher did not become a part of the design specification. However, the M14 EBR with M203 was a significant improvement over the 1960s SPIW models.

NSWC Crane tested the 2002 production M14 EBR stocks with 16 " and 18 " barrels. The 18 " barrel with a 1:11 twist was chosen for the evolving M14 EBR configuration. Later, the thermoplastic hand guard, combination gas cylinder lock hooded post front sight and direct connect style flash suppressor were added to the system specification. The direct connect flash hider was chosen in anticipation of easily attaching possible future sound suppressors for the Mk 14 Mod 0 rifles. Springfield Armory, Inc. was awarded a contract to supply the machined and finished Mk 14 Mod 0 barrels to NSWC Crane. Wilson Arms Company (Branford, CT) supplied the barrel blanks to Springfield Armory, Inc. These standard contour 1:11 twist 18 " barrels were not chromium plated. The barrel gas port was drilled using a # 45 bit and the gas cylinder shoulder boss was moved forward about 0.62 " because of the lack of a gas system front band on the Mk 14 Mod 0. The same barrel was used to build Mk 14 Mod 1 rifles.

In February 2005, the U. S. Navy's proposed funding for the M14 EBR (Mk 14 Mod 0 and Mk 14 Mod 1) purchases was as follows: FY 2008 - \$1,772,000 for 886 rifles, FY 2009 - \$1,782,000 for 886 rifles, FY 2010 - \$1,772,000 for 886 rifles and FY 2011 - \$1,772,000 for 886 rifles. The following year, the acquisition was scaled back dramatically. In February 2006, the U. S. Navy budgeted \$536,000 for 233 rifles in FY 2006 and \$553,000 for 233 rifles in FY 2007 for the Mk 14 Mod 1. Actual NSWC Crane production figures were 1000 Mk 14 Mod 0 and 500 Mk 14 Mod 1 rifles.

M14 T Rifle - On February 26, 2003, the U. S. Coast Guard was transferred from the Department of Transportation to the newly created Department of Homeland Security as part of the Homeland Security Act of 2002. In response to the change in its mission

statement, the U. S. Coast Guard began, among other initiatives, a small arms procurement program to replace its hand guns, add additional machine guns, and replace or add to its stable of rifle systems. Two Coast Guardsmen were sent in 2004 to the 4th Marine Expeditionary Brigade Designated Marksman school at Camp Lejeune, NC as one small part of a branch wide training effort to support the Coast Guard's new mission.

The M14 EBR was evaluated in 2004 to become the U. S. Coast Guard M14 Tactical rifle. The U. S. Coast Guard requirement for the M14 EBR differs from the Navy version in that the direct connect flash hider is replaced with a Smith Enterprise, Inc. muzzle brake. The U. S. Coast Guard is more concerned with minimizing muzzle rise from use on a rolling deck than eliminating muzzle flash. The muzzle brake manufactured for the M14 Tactical rifle is marked U.S.C.G. SMITH ENT. The iron sights were an XS Sight Systems 0.125 " diameter aperture and hooded post front sight. By late 2005, the U. S. Coast Guard had procured 500 M14 Tactical rifles built by Naval Surface Warfare Center (Crane, IN). The U. S. Coast Guard type classified this rifle as the M14 T. It was issued with seven magazines. The M14 T was intended to arm Coast Guard helicopter crews to fulfill its counterterrorism role. The M14 T was expected to see service with the U. S. Coast Guard until 2015.

M14 EBR-RI - In 2008, the U. S. Army Tank Automotive Command (TACOM) began a project to modernize the M14 in support of U. S. Army units in Iraq. This work was performed by the Weapons Product Support Integration Directorate of the TACOM Life Cycle Management Command at Rock Island, IL. The M14 EBR-RI Program Manager was Doug Carlstrom from inception through at least June 2010. The first 400 M14 Enhanced Battle Rifle - Rock Island (M14 EBR-RI) rifles had been completed by June 2008. Another 2,200 units had been completed by March 2009. On May 05, 2010, TACOM completed its five thousandth M14 EBR-RI rifle. An additional 800 units were completed by September 01, 2011 to fulfill all requests submitted by combat unit commanders to date.

The conversion of a M14 to a M14 EBR-RI included replacing the M14 stock with a Sage International late second generation M14 EBR stock, reaming the flash suppressor, replacing the cartridge clip guide with a detachable cantilevered sight base, shimming the gas cylinder, and adding a vertical grip, a Harris bipod and a Leupold & Stevens, Inc. variable 3.5-10X day scope with medium height rings. The M14 EBR-RI rifle was shipped to the combat unit with six magazines, a vertical fore grip, a sling, an Otis Products, Inc. cleaning kit, a combination tool and operator manual. By mid-2009, some minor changes were made on new rifles: 1) a crush washer replaced the stainless steel shims 2) a redesigned operating rod guide to make use of the hand guard screws and 3) an improved detachable cantilevered sight base. All Sage M14 EBR stocks supplied to TACOM were marked with the patent number. The accuracy acceptance criteria for the rifle was a maximum of 1.5 MOA with the result averaging 0.89 MOA for the first 5,000 built. The five TACOM rifle builders observed that TRW and Winchester barreled actions typically delivered the best accuracy. Only one rifle in the first 5,000 units was rejected

for not meeting the accuracy requirement. In 2009, the M14 EBR-RI was fielded by U. S. Army units in Afghanistan, e.g., 1st Battalion 508th Parachute Infantry Regiment.

The M14 EBR-RI was not a program of record so a technical manual was not written for it. These rifles were issued to U. S. Army units upon request from commanding officers during pre-deployment preparations. Typically, the M14 EBR-RI rifles were shipped to the unit within six months of its deployment overseas. Each rifle was issued with six magazines. Because the rifles were on loan from TACOM, they were shipped back to Rock Island Arsenal at the end of the deployment cycle and brought back to Condition A readiness. The Department of the Army took the decision to not have M14 EBR-RI rifles maintained in-theater by small arms repairmen.

M14 EBR-RI NM - In July 2010, Doug Carlstrom took the M14 EBR-RI configuration a step further. A Winchester M14 was built into a M14 EBR-RI designed for competition shooting. It differed from the customary build in three ways: 1) Smith Enterprise, Inc. medium weight M118LR chambered, 1:10 rate of twist, four groove, nitrocarburized molybdenum-chromium alloy steel barrel 2) Smith Enterprise, Inc. gas system and 3) Sage International, Ltd. M14 EBR stock fitted with a Magpul Industries Corporation PRS2 butt stock. The barrel and gas system were assembled by Smith Enterprise, Inc. in October 2009. The manufacturer designated the stock as the M14ALCS/PMRI model. It was marked M14 EBR-RINM on the left side directly above the trigger. The barrel was stamped SMITH ENT TACOM RI M-118 LR. Mike Petersen test fired the rifle in at the Rock Island Arsenal indoor firing range. The rifle grouped 0.5 " at 100 yards with M118LR ammunition. Retired U. S. Army Brigadier General Eddy Newman shot this rifle at Camp Perry on August 14, 2010. He scored 184 points out of a possible 200 shooting at 1000 yards with M118LR ammunition.

Mk 14 Mod 2 - In April 2011, David Armstrong at the Naval Surface Warfare Center (Crane, IN) built two prototype Mk 14 Mod 2 rifles. He upgraded two M14 SSR rifles by installing Sage International, Ltd. M14ALCS/PMRI-H stocks. The AN/PVS-27 night scope and Nightforce NXS 3.5-15X day scope were chosen as the optical devices since the M14 SSR lacks iron sights. Accessories included X-treme Shooting Products, LLC (Milford, OH) steel trigger shoes and B&T Industries, LLC Atlas BT10-LW17 bipods. An additional prototype Mk 14 Mod 2 rifle was built in September 2011. Along with the aforementioned items, the final configuration included two magazines and the following Smith Enterprise, Inc. parts: extended bolt lock, direct connect flash hider, gas cylinder, shims, gas piston, gas cylinder lock wrench and a cleaning rod guide sized for the flash hider. Smith Enterprise, Inc. completed delivery of these parts by December 2011. The final configuration substituted the Atlas BT10 bipod for the BT10-LW17 model. Mk 14 Mod 2 rifles were built from existing M14 SSR rifles. Thus, the 1:10 twist rate heavyweight barrel, match grade operating rod spring guide, and NSWC Crane scope mount were retained. Like the M14 SSR, each Mk 14 Mod 2 rifle was tested to ensure it could meet the five shot 1.5 MOA accuracy requirement. The Mk 14 Mod 2 was 44 " long and weighed 17 pounds with optics, bipod and magazine. Some of the M14 SSR barrels

had been purchased from Springfield Armory, Inc. in years past. The Mk 14 Mod 2 was intended for Navy Expeditionary Combat Command units in providing ship boarding overwatch, perimeter defense, explosive ordnance disposal. and command post security.

M14SE, Mk 14 SEI and M80 SDM

M14SE - The M14 rifle as a sniper weapon system has been successful but it has had its minor shortcomings. The M14 rifle is a sound and proven weapon but glass bedding, steel inserts, and gas system unitizing requires armorer support. The flash suppressor nut and setscrew arrangement affect barrel performance. Installing a sound suppressor to the USGI front sight housing is not the most rugged means of attachment. The USGI bolt lock can be difficult to manipulate with thick gloves. Ron Smith of Smith Enterprise, Inc. has examined the barrel-to-receiver interface, the optics, the barrel itself, the gas system, the flash suppressor and sound suppression of the M14. He has developed simple and reliable solutions to these nagging deficiencies while taking advantage of current technology. The result is the M14SE semi-automatic rifle system. This development work had been completed before 2004. Until mid-2006, the weapon was known as the M14SE Semi-Automatic Sniper System. At that point, the rifle system was billed as the M14SE Squad Designated Marksman (SDM) rifle without any component changes. Per U. S. Army doctrine, a 7.62x51 mm sniper rifle is capable of engaging targets out to 900 meters and a squad designated marksman rifle is intended for use against the enemy at distances to 600 meters.

In May 2004, the U. S. Army 2nd Infantry Division 2nd Brigade Combat Team was preparing to deploy from South Korea to Iraq. The U. S. Army had noted that many soldiers were making individual purchases of Smith Enterprise, Inc. scope mounts and scope rings for their issued M14 rifles. Major Kim Zimmerman from the 2nd Infantry Division approached Leupold & Stevens, Inc. to acquire some scopes, mounts and rings for twenty of the division's 110 M14 NM rifles in anticipation of pending deployment to Iraq. Leupold & Stevens, Inc. assisted Major Zimmerman in acquiring the requested parts but also made him aware of Smith Enterprise, Inc. and its capabilities.

Over the course of the following month, Major Zimmerman was in constant communication with Smith Enterprise, Inc. They discussed at length the needs of the 2nd Brigade Combat Team of the 2nd Infantry Division and what could be done with its M14 NM rifles to meet those needs. In general terms, the 2nd Brigade Combat Team was in need of accurate, rapid fire, heavy fire power sniper rifles for engaging enemy targets at medium and long range distances. Major Zimmerman briefed the 2nd Infantry Division Commanding General, Major General George A. Higgins, on what Smith Enterprise, Inc. was able to do. Major General Higgins immediately saw the merit in converting the M14 NM rifles and gave quick approval. Major Zimmerman wrote the sole source contract and Major General Higgins awarded it to Smith Enterprise, Inc. in July 2004 without either officer having seen a M14SE rifle. Major General Higgins was able to award the contract

because the M14SE is a proprietary shooting system and the M14 NM rifles are owned by, not on loan to, the 2nd Infantry Division. This was the first time that an entire U. S. Army unit had adopted a sound suppressed sniper weapon system.

At about the same time in May 2004, the U. S. Army was getting ready to release the requirements for the XM110 sniping system. The XM110 was a gas operated semi-automatic 7.62 x 51 mm caliber sniper rifle. Smith Enterprise, Inc. briefed the U. S. Army Director of Combat Development (Fort Benning, GA) on the M14SE. The Director of Combat Development was convinced that the XM110 requirements could be met by the M14SE and save the taxpayer money by converting an existing weapon. Rock Island Arsenal was also briefed and convinced of the merits of the M14SE. The Director of Combat Development and Rock Island Arsenal were both well aware of the 2nd Infantry Division's pursuit of the M14SE during all of this. In 2005, additional U. S. Army units had ordered conversion of M14 rifles to the M14SE configuration.

Smith Enterprise, Inc. received 90 M14 NM and XM21 rifles from the 2nd Infantry Division in late September 2004 by U. S. Air Force transport direct to Luke AFB from South Korea. The rifles were in poor condition. The operating rods were coated in rust and dirt filled the rear sight pocket under the rear sight assemblies. The rifles had broken elevation pinions, cracked wood stocks, and worn out operating rod springs. Flash suppressor nut setscrews and gas cylinder plugs were chewed up. One wood stock broken in half was held together by a tent stake and tape. Some rifles had M1 Garand trigger and sear assemblies which were replaced with M14 parts. Cracked receiver bridges were repaired by gas tungsten arc welding. Twenty M14 rifles were held back in Iraq for combat until the first fifty converted rifles were delivered. Ninety-nine M14SE rifles were flown by the U. S. Air Force from Luke AFB to Baghdad, Iraq. The last eleven rifles were transported by the Air Force in August 2005 to units in South Korea.

To convert the M14 into the M14SE the heart of the weapon (receiver, bolt and operating rod) was kept but everything else was replaced. The M14SE configuration included the following modifications: 1) synthetic USGI stock without lugs or bedding 2) 22 " medium weight molybdenum-chromium alloy 1:10 twist four groove barrel chambered for M118LR ammunition 3) the receiver, new barrel and bolt were cryogenically treated separately 4) the gas cylinder, gas cylinder plug, and front band were nitrocarburized 5) unitized gas system 6) thin dense chromium plated gas piston 7) SEI MIL-STD-1913 scope mount and SEI 30 mm heavy duty tactical tall ring set 8) Leupold & Stevens, Inc. rifle scope 9) waterproof strap-on nylon cheek rest with polyvinyl chloride inserts 10) SEI M14DC direct connect flash hider 11) SEI dovetail or hooded style nitrocarburized combination gas cylinder lock front sight 12) SEI extended bolt lock 13) tuned 4.5 pound pull firing mechanism 14) SEI wire electro-discharge machined from bar stock rear sight assemblies and 15) manganese phosphate coating to military specification.

As delivered, optics for the 2nd Infantry Division M14SE rifles were either Leupold & Stevens, Inc. variable 3.5-10X40 mm illuminated reticle or 1.5-5X20 mm illuminated

M14 RIFLE HISTORY AND DEVELOPMENT

reticle scopes per the contract. Later, the 2nd Infantry Division replaced the 1.5-5X20 mm scopes with the 3.5-10X40 mm scopes so that all M14SE rifles were fitted with the higher magnification scopes which better suited its needs.

The selector shaft on each M14SE rifle was inoperable rendering them semi-automatic fire only. The tactical tall heavy duty rings were used to keep the combination gas cylinder lock front sight from obscuring the shooter's view through the scope. The combination gas cylinder lock front sights installed on the 2nd Infantry Division M14SE rifles were marked 2 I. D. on the top line and O. I. F. on the bottom line. Each M14SE was carefully assembled and lubricated with MD Labs XF7 weapons lubricant. Accessories supplied with each rifle included a M1907 leather sling, M14 Direct Connect sound suppressor and a nylon suppressor and tool pouch. The sound suppressor serial numbers for this project ranged from M14-DC-0102 to M14-DC-0222. Other accessories available for M14SE and Mk 14 SEI rifle conversions included an adjustable firing mechanism, angle cosine indicator and mount, magazine pouch, model GLFS-T combination gas cylinder lock dovetail style front sight with tritium insert, and an AN/PVS-22 scope mount.

The barrel for the M14SE was based on the June 1981 U. S. Army Armament Research Development and Engineering Center (Dover, NJ) drawing F9345206. This is the blueprint for the medium weight contour M14 National Match barrel. However, Smith Enterprise, Inc. improved upon the design by giving it a 1:10 twist instead of 1:12 and chambering it for the M118LR cartridge. M80, M852 and M118LR ammunition all shoot well from this barrel. The first batch of M14SE barrels were stamped WA 9345206 9/04. In May 2005, the 18" long M14SE medium weight barrel was made available.

On September 28, 2005, Smith Enterprise, Inc. successfully concluded its M14SE system contract with the U. S. Army 2nd Infantry Division. Most of the rifle serial numbers built into M14SE rifles for the 2nd Infantry Division are listed as follows:

Harrington & Richardson - 825699, 827540, 837104, 837757, 837803, 837860, 839464, 856413, 858817, 868912, 873853, 873945 (heel marked XM21), 876234, 953634, 964390, 1534832, 1581103, 1583548

Springfield Armory - 3589, 335291 (heel marked XM21), 347246, 348984, 349654, 353253, 354444, 354510, 355234, 356298, 356589, 356784, 356895, 357134, 357241, 357413, 357730, 358455, 359560, 359850, 362252, 362924, 524984, 525312, 526573, 528960, 529279, 534730, 534832, 537434, 537462, 538272, 542954, 544351, 550521, 550698, 550866, 555371, 559038, 560780, 1593532, 1594461, 1596100, 1596406

TRW - 607549, 612857, 663816, 1324989, 1440568, 1442083, 1453205, 1453297, 1453321, 1453461, 1453929, 1453979, 1454083, 1454095, 1454371, 1454649, 1467176, 1467233, 1478892, 1478979, 1479013, 1479182, 1479394, 1479525, 1482161, 1495814, 1495894, 1496080, 1496159, 1496203, 1496247, 1499482,

1499569, 1499610, 1500020, 1500072, 1500075

Winchester - 175935, 179514, 191069

M14SE Phase II – Several enhancements to the M14SE and Mk 14 SEI systems were implemented in the spring of 2005. USGI contract trigger and hammer pins made in the 1960s were heat treated to a hardness in the low 40s HRC. With extended use, these pins will wear into an oblong shape causing noticeably inconsistent hammer and trigger operation. Consequently, all M14SE and Mk 14 SEI rifles were fitted with Smith Enterprise, Inc. proprietary S-7 alloy steel trigger and hammer pins hardened to about 58 HRC. The result was a lifetime of use and consistent firing mechanism performance. The M14SE barrel gas ports were slightly enlarged as further assurance that all types of 7.62x51 mm ammunition will work with the direct connect sound suppressor under all weather conditions. The USGI M14 connector lock was replaced with a Smith Enterprise, Inc. proprietary design unit made from S-7 alloy steel. The USGI operating rod and hammer springs were replaced with SEI designed and manufactured chromium silicon alloy steel springs. The operating rod guides were sized perfectly to the M14SE and Mk 14 SEI barrels. The Smith Enterprise, Inc. 7 " long scope mount, steel bipod and optical upgrades were offered as well. The SEI bipod design was changed by the fall of 2007 to include a locking cant.

In June 2006, Smith Enterprise, Inc. started another M14SE rifle contract. Twenty-six worn out USGI M14 rifles were rejuvenated and sent back within thirty days as M14SE SDM models to the U. S. Army 502nd Infantry Regiment 101st Airborne Division in Iraq. Each rifle was rebuilt with the following items: 1) Krieger M14 DMR medium weight stainless steel match grade barrel 2) USGI fiberglass stock with SEI MIL-STD-1913 bipod rail mount 3) Leupold & Stevens, Inc. Mark 4 3.5-10X40 mm M2 TMR scope 4) SEI medium height scope rings 5) SEI 5.38 " long scope mount 6) Harris bipod 7) M1907 sling 8) SEI 22 " combination gas cylinder lock front sight 9) SEI M14 DC flash hider 10) SEI extended bolt lock 11) SEI S-7 tool steel connector lock 12) 4.5 pound trigger job 13) strap on camouflage cheek rest and 14) M14DC sound suppressor. Each rifle was returned with a sound suppressor pouch and gas cylinder lock wrench. The Krieger M14 DMR barrels were used because the M14SE medium weight molybdenum-chromium alloy steel barrels were temporarily unavailable during the short turnaround time requirement of this build project. For this build project, the gas cylinders were shimmed. The M14 rifle serial numbers that were rebuilt for this project were: 170319, 171313, 175999, 355875, 528859, 549187, 552306, 564323, 610752, 611025, 680376, 848756, 852406, 855400, 861460, 864536, 907265, 1008635, 1011788, 1013478, 1042090, 1159987, 1231116, 1453988, 1476541, and 1499648.

Smith Enterprise, Inc. built some M14SE rifles in 2006 for the 25th Infantry Division while serving in Iraq. Smith Enterprise, Inc. rebuilt twenty-three M14 rifles for the 4th Battalion 9th Infantry Regiment 4th Brigade Combat Team 2nd Infantry Division in support of its deployment to Iraq in 2007. The firm completed additional M14SE type rifle builds for the

10th Special Forces Group in March 2007 (three rifles), Vermont Army National Guard in 2009 (three rifles), and Nevada Army National Guard in 2010 (six rifles).

In September 2006, the SEI AN/PVS-22 scope mount was made available for law enforcement, foreign military and U. S. government sales. The AN/PVS-22 scope is a third generation night vision sight designed for ease of use in the field. It was designed and developed by Optical Systems Technology, Inc. in 1996. The SEI AN/PVS-22 scope mount is unique in that it is of a cantilever design. It attaches at one point at the front of a MIL-STD-1913 Picatinny rail side three point scope mount. The SEI AN/PVS-22 scope mount is manufactured by the wire EDM method from AISI 4140 molybdenum-chromium alloy steel. It is nitrocarburized to 60 HRC. The advantage of this design is keeping the scope mount for a night vision optic from touching the barrel.

In March 2007, three USGI XM21 rifles had been rebuilt into M14SE configuration and shipped to the U. S. Army. By July 2007, the U. S. Army designated the M14SE as the M21A5/C-IED. C-IED is an acronym for counter-improvised explosive device. As of February 2008, a M80HT (proprietary nitrocarburizing process) treated M14SE test barrel had 15,000 rounds of M118LR through it while still producing acceptable results. The proprietary M80HT process allows a match grade barrel to have the longevity of a chromium plated barrel while maintaining acceptable accuracy.

On March 28, 2008, the M21A5/C-IED rifle was tested at Fort Benning, GA. The test rifle for the M21A5/C-IED rifle was built by Smith Enterprise, Inc. using a LRB Arms M14SA receiver. Otherwise, the test rifle was built to the same specifications as would have been done for a U. S. military owned model. The test M21A5/C-IED rifle printed a five shot 3/4 " group at 100 yards using M118LR ammunition. With the same lot of ammunition, the M21A5/C-IED test rifle grouped less than 10 " at 1000 yards.

Mk 14 SEI - In 2004, Smith Enterprise, Inc. converted a number of M14 rifles for U. S. Air Force pararescue teams into a variation of the M14SE system unofficially known as the Mk 14 SEI. These rifles were assembled with the Sage International, Ltd. M14 EBR stock in lieu of the USGI M14 synthetic stock. The top rail of the Sage International, Ltd. M14 EBR stock had to be modified for installation of the Smith Enterprise, Inc. scope mount as part of the build specification. The U. S. Air Force rifles were fitted with 18 " medium weight M14SE barrels chambered for the M118LR cartridge. The selector switch was left operable. The chromium plated 18 " barrel (SEI part number 2027) was an option for the Mk 14 SEI system. The U. S. Air Force pararescue teams reported successful engagement of targets out to 900 yards with Mk 14 SEI systems fitted with Leupold & Stevens, Inc. 3.5-10x40 mm illuminated reticle scopes. In the summer of 2005, the U. S. Air Force contracted with Smith Enterprise, Inc. to convert 100 M14 rifles into Mk 14 SEI systems. As of 2010, about 125 Mk 14 SEI rifles had been built for the U. S. Air Force. Like the M14SE, the Mk 14 SEI was designed to fill the U. S. Army requirement for the XM110 semi-automatic sniper system.

Smith Enterprise, Inc. (SEI) converted two U. S. Army 10th Special Forces Group Chinese select fire M14 rifles converted during the fall of 2004 to Mk 14 SEI rifles. The Chinese M14 chu wood stocks with selector cutouts were replaced with Sage International, Ltd. M14 EBR stocks. These two Chinese select fire M14 rifles are not registered under the National Firearms Act since that law does not apply to military property. The only marking, M14, was stamped on the heel of each Chinese select fire receiver. The selector switch was left operable on these two Chinese M14 rifles when returned to the U. S. Army 10th Special Forces Group.

M80 Squad Designated Marksman (SDM) Rifle - Smith Enterprise, Inc. developed the M80 SDM in 2006 for the U. S. Army. This was a M14SE rifle outfitted with a special profile 18 " non-plated M80HT treated barrel, a shorter length-of-pull USGI synthetic stock and a Leupold & Stevens, Inc. moderate variable power scope.

Semi-automatic Only USGI M14 Rifles

At least four semi-automatic only M14 receivers were manufactured at the Springfield Armory. At least three of them were made between January 01, 1962 and March 20, 1962. Two of the receivers were assembled into complete rifles. These semi-automatic only rifles differed from the standard M14 in the following manner: 1) no selector lug or operating rod rail cuts for the connector 2) M1 Garand design operating rod dismount notch 3) no stock selector cutout 4) M1 Garand butt plate on the stock 5) no spindle valve in the gas cylinder 6) no connector-tripping notch in the operating rod 6) M1 Garand sear installed in the firing mechanism 7) ten round magazine in lieu of a twenty round magazine 8) M1 Garand rifle National Match rear sight assembly 9) non-plated match grade barrel. These semi-automatic M14 receivers were numbered X300, X500, X501 and X502. X500 remained at Springfield Armory as a bare receiver for the time being. Receivers X501 and X502 were assembled into complete rifles.

These two rifles were examined by the Chief of Army Field Forces, the Director of Civilian Marksmanship and the Department of Treasury. The Department of Treasury concluded that these rifles were suitable for sales to civilians. Major General Nelson M. Lynde, Jr., Assistant Chief of Ordnance for Field Services, decided that these modifications deviated too far from the original design. These semi-automatic M14 rifles could not be converted back to the issue rifle in the event of a national emergency. Thus, the project was abandoned after General Lynde's visit to Springfield Armory on March 28, 1962. Disposition of the three X500 series receivers is unknown though M14 rifle serial number X502 was observed at Camp Perry in the 1960s. General Lynde went on to become Commanding General of the Ordnance Weapons Command (later Army Weapons Command) from May 1962 to March 1964.

Hahn Machine Company and Pearl Manufacturing

From at least 1990 until 1995 or later, Hahn Machine Company (3101 Sussex St. Charles, MO 63301) legally manufactured semi-automatic only M14 rifles by cutting and welding pieces from scrapped USGI M14 receivers. This was done according to a letter of approval signed by then BATF Chief, Firearms Technology Branch, Edward M. Owen, Jr. dated June 8, 1994. The letter was addressed to Mr. Lloyd Hahn of the Hahn Machine Company in St. Charles, MO. It was the BATF response to Mr. Hahn's May 11, 1994 submission of a modified USGI TRW M14 receiver for a BATF ruling on the assembly of a semi-automatic only USGI M14 receiver. The approval letter granted permission to manufacture semi-automatic only M14 receivers from "properly destroyed" USGI M14 receivers. The destruction procedure first required a specific torch cut procedure on the receiver followed by removal of the selector lug and weld fill in of the operating rod rail cuts. After these steps were completed, the pieces of receiver scrap could be welded into one piece. The letter also required Hahn Machine Company to permanently engrave the company name, city and state on the receiver. A second letter from the BATF dated March 22, 1995 and signed by Technical Section ATF Specialist Naomi L. Rubarts was the cover document for an approved Application for Registration for Tax-Free Transactions as a manufacturer.

The following is presented strictly for providing the reader with a historical perspective regarding civilian ownership of M14 type rifles in the United States. The June 8, 1994 BATF letter to Lloyd Hahn was consistent with a previous letter mailed to Martin Pearl of Grants, New Mexico dated August 21, 1980. In the letter to Mr. Pearl, Edward M. Owen, Jr. stated that the "manufacturing of firearms from properly destroyed (demilitarized) firearm receivers is an acceptable practice" as long as "the first stage of your manufacturing process be the removal of the selector pivot housing" and this "modification will remove the new receivers from the provision of the National Firearms Act." As an aside, Martin Pearl (SOT/FFL Pearl Manufacturing) went on to register and convert thirty-two Maadi AKM and two Valmet M78 rifles to select fire capability. He did these conversions for the 1984 film classic, *Red Dawn*.

Warning: Since the mid-to-late 1990s, the Bureau of Alcohol, Tobacco, Firearms (and Explosives) has not interpreted 26 U. S. Code section 5845 (b) to allow welding of USGI M14 receiver halves back together even if all select fire features are removed. The BATFE considers such activity as manufacturing of a machine gun. The reader is strongly encouraged to NOT attempt any restoration of demilitarized USGI M14 receivers. Machine gun manufacture by a private individual in the United States is a felony and the offender is subject to severe criminal penalties.

The receivers were heat treated after all welding operations had been completed. The quality of the welding on Hahn Machine receivers is reputed to be very good. Bruce Dow of Dow Arms Room (Dade City, FL) has examined four Hahn Machine welded semi-automatic M14 rifles. He found that none of the four Hahn Machine welded M14

receivers met the USGI drawing 7796081 receiver straightness requirement, within 0.010 ". However, three of the four Hahn Machine welded M14 receivers were straighter than two commercial M14 type receivers. All six of these receivers functioned perfectly as part of complete rifles. One of the four Hahn Machine receivers had its bridge located too far aft. The number of Hahn Machine welded semi-automatic M14 receivers is unknown but is thought to be in the hundreds.

In the 1990s thousands of demilitarized USGI M14 receiver halves were auctioned off by the government. These receiver halves have been sold by surplus to collectors as momentos. As is, the BATFE considers the demilitarized receiver halves as scrap metal. Such, apparently, was not always the case. In November 1972, Thomas A. Buss telephoned the BATF and spoke with two field agents, Mr. Barnes at the Cincinnati, OH office and Mr. Mayer at the Philadelphia, PA office. Mr. Barnes told Mr. Buss that,

any piece of a machine gun receiver - no matter how small or worthless - must be registered as an unserviceable firearm. If not already registered, there is no provision for registering except during an amnesty period. The present owner's only recourse is abandonment to the government without penalty.

Mr. Buss was informed by Mr. Mayer,

If enough metal is missing so that the pieces cannot be rejoined, send a photograph or a good sketch to DIRECTOR, BATF, 1111 Constitution Ave. Washington, D.C. 20226. The director personally will decide whether the pieces will be registered or the pieces will be confiscated. Pending the director's ruling, the pieces should be held by a Class III dealer.

U. S. Civilian Ownership of Select Fire USGI and Chinese M14 Rifles

There are several hundred National Firearms Act (NFA) registered USGI select fire M14 rifles (including legally welded USGI receivers) in the United States according to an ATF Agent who conducted an audit of the NFA Registry. The Agent conducted the audit with the specific purpose of determining the number of USGI M14 rifles in the Registry. Most of the NFA Registered select fire M14 receivers have been welded back together. Welded USGI M14 receivers were registered under the National Firearms Act by approved ATF Form.

There were likely a few uncut USGI M14 rifles among the tens of thousands of machine guns registered when the National Firearms Act was revised in 1968. One such amnesty example is Harrington & Richardson M14 serial number 449955. The NFA amnesty period ran from November 02, 1968 to December 01, 1968. At least two Springfield Armory T44E4 rifles made it into the NFA Registry under the amnesty and forty years later remain in the hands of private citizens.

M14 RIFLE HISTORY AND DEVELOPMENT

In late 1985 or early 1986, Harrington & Richardson registered a group of twenty-five to thirty, possibly more, Harrington & Richardson M14 rifles, e.g., serial number 435824, and a handful of the Harrington & Richardson .22 LR caliber M14 Simulator rifles with the BATF. These M14 rifles had never left the factory and were registered in time to become legal for civilian possession before the 1986 McClure-Volkmer Firearms Owner Protection Act ended any further legal registration of automatic capable firearms for civilian purchase. They were sold at auction when the company went out of business.

One of the soon-to-be auctioned M14 rifles, serial number 87156, was transferred by Harrington & Richardson Arms Co. to Qualified Manufacturing (Broken Arrow, OK) on November 02, 1985 by approved ATF Form 2. Qualified Manufacturing was a Class 2 FFL/SOT firearms manufacturing business reportedly owned by Richard Parker. Qualified Manufacturing submitted an ATF Form 2 to return M14 serial number 87156 to Harrington & Richardson on November 14, 1985. The BATF approved the Form 2 on December 05, 1985. Based on this sequence of events, the Harrington & Richardson Arms Co. auction likely occurred soon after December 05, 1985. Robert J. Perry purchased these H&R M14 and M14 Simulator rifles in April 1990 from the anonymous winning bidder of the Harrington & Richardson auction. Subsequent to the passing of Mr. Perry, the Harrington & Richardson rifles were sold to other individuals.

Most of the Harrington & Richardson M14 rifles were test models, experimental Guerilla Gun M14 models or machined receivers that had never been heat treated. Some had no scope mount boss and threaded bolt hole on the left hand side while others were barreled actions or only partially assembled. A few were standard issue M14 rifles with production serial numbers such as 55632, and 87156 and 1545579. Most of the rifles had hand stamped experimental or test model numbers, e.g., X-40. A number of these M14 rifles were assembled with T44E6 parts and some had the rear sight pocket knob holes milled off while others lacked the U S RIFLE M14 marking on the heel. The Harrington & Richardson M14 rifles that required it were heat treated at FPM Heat Treating (Chicago, IL). This collection of Harrington & Richardson M14 rifles was then phosphate coated and assembled into new M14 rifles with standard USGI M14 parts. Parts were cannibalized from the four .22 LR caliber select fire rifles to create three complete .22 LR caliber M14 Simulator models. The phosphate coating and rebuilding of the Harrington & Richardson rifles was done under the supervision of Robert J. Perry and an associate who wishes to remain anonymous.

U. S. Department of Energy - The U. S. Department of Energy (DOE) purchased twenty-five Springfield Armory, Inc. M21 models in the late 1990s for its Special Response Force. The commercial M21 rifles performed well. The DOE subsequently purchased USGI M14 rifles from Anniston Army Depot. At one point, the DOE inventory of M14 rifles was about 300. The M14 rifles were stored in three different locations. Scoped DOE M14 rifles were fitted with Smith Enterprise, Inc. Weaver style rail XM-21 scope mounts.

As of 2007, most of the M14 rifles at DOE have been transferred to other government agencies and the few remaining are not issue equipment. All remaining M14 rifles held by DOE were to be eventually transferred to other government agencies. DOE disposal procedures only allow transfer to another government agency or destruction. Those are the only allowable means of reducing weapons inventory for DOE. It remains a mystery as to how but a small number of the USGI M14 rifles formerly held by the DOE were released for sale in the late 1990s to the public. This small lot of USGI M14 rifles was obtained and subsequently sold into the commercial market by Class 3 SOT/FFL businessman F. Charles Logan (Warrendale, PA).

The number of former DOE M14 rifles released for sale has been reported as fifteen by a very credible source. Many of these DOE M14 rifles have the symbol # and a number etched on the left side of the receiver above the stock line. These are DOE weapons chit numbers. The numbers were engraved on the receivers at the direction of the DOE Senior Firearms Advisor at the time, Dave Shannon. A second very credible source has observed one DOE M14 rifle etched with # 29. Nine of these DOE M14 rifles are etched with the following: # 8, # 10, # 12, # 15, # 19, # 21 (H & R serial number 1564367), # 22 (H & R serial number 1566863), # 34 (Winchester serial number 1117145) and # 38.

NFA Registered Welded Select Fire Models - The following FFL/SOT businesses legally welded pieces of scrap to create USGI M14 receivers and registered them in time to remain transferable: Bill Fleming (Collinsville, OK), H&R Gun Co. (Holland, OH), John Norrell Arms, Inc. (Little Rock, AR), Neal Smith (Smith Firearms in Mentor, OH), Specialty Arms Co. (Springfield, OH) and the late Bruce Swalwell (Metro Tech, Ltd. of McHenry, IL).

One M14 receiver legally welded together by Bruce Swalwell was engraved M Tech McHenry ILL. Mr. Swalwell also worked for Neal Smith before 1986. Reportedly, Bill Fleming registered about fifty welded USGI select fire M14 receivers. H&R Gun Co. M14 type rifle serial number 0556 is a select fire USGI M14 receiver rifle. It was originally registered with the BATF by an approved NFA Form before the May 1986 ban. On March 31, 2003 this rifle sported a USGI birch stock, USGI M2 bipod, 18 " barrel and lugless flash suppressor. It was quickly sold by Elite Firearms (Boaz, KY).

Post-'86 dealer samples - A small number of Chinese Norinco select fire M14 rifles were imported about 1991 into the United States by Century Arms International as post-'86 dealer samples for sale to law enforcement agencies. Serial numbers for some of these NFA registered post-'86 ban dealer sample Norinco select fire M14 rifles are 62012781, 62021815, 62044810, 63015693, 63022377, 63025216, 63028755, 63035184, 63623566, 64000527, 64010551, 64604697, and 65034874. At least one Poly Technologies M14 was converted to a select fire post-'86 ban dealer sample by Pearl Manufacturing (Grants, NM).

In the late 1980s, Global Sales (then Minden, NV) imported USGI M14 rifles from Israel into the United States legally for sale to law enforcement agencies. Dennys Guns (North Kansas City, MO) imported Harrington & Richardson Arms Co. M14 serial number 9970X as a post-'86 dealer sample.

Ignore the Petition to Sell the M14!

Ignore any petition regarding public sales of M14 rifles. Orest Michaels, Chief Operating Officer for the U. S. Civilian Marksmanship Program (CMP), stated in a June 17, 2003 e-mail message to a member of the Internet discussion board www.battlerifles.com: that 1) the U. S. Army has no surplus M14 rifles to sell 2) no M14 rifles are being destroyed and none have been destroyed for almost ten years 3) CMP may not want to or may not be allowed to get involved if such a program existed anyway because the M14 is considered a machine gun. A petition to this effect occasionally surfaces in various e-mail messages and Internet discussion groups, but is filled with outdated information.

The 1996 Fiscal Year National Defense Authorization Act changed the legal status of the Civilian Marksmanship Program and the Office of Director of Civilian Marksmanship. On October 01, 1996, these entities were given non-profit corporate status by statute, and ceased to be a part of the U. S. government. Until then, the CMP was a part of the U. S. Department of the Army.

Select Fire M14 Rifle Rate of Fire Modification

John C. Garand designed a rate reducer for the T20E2 rifle between 1948 and 1950. He modified the T20E2 rate reducer in 1953 for the T44E1 rifle. The T44E1 rate reducer slowed the automatic rate of fire from 735 rpm to 550 rpm. This device was contained inside the trigger housing. It acted to slow the speed of the hammer. An electronic rate of fire controller made by the Pinderton Company was used on the T20E2 and T44 rifles in 1951. David C. Fletcher, believed to be an employee of Springfield Armory, developed a rate reducer for the M1 Garand rifle in 1953. The Fletcher device allowed the rate of fire to be increased or decreased to a degree by adjusting the tension of its coil spring. A rate reducer for the M15 rifle was also tested but eliminated. Tests showed comparable accuracy at both rates of fire in automatic.

During the Viet Nam War, American soldiers experimented with different means of changing the rate of fire of a M14 rifle in automatic. Soldiers in Viet Nam developed modifications which could make the M14 fire at either rate of 550 or 1100 rounds per minute. By milling a 0.060 " wide and deep channel along the top of the cylindrical portion of the gas piston the rate of fire was slowed to 550 rounds per minute. The rate of fire in a select fire M14 can be reduced 40 to 50 rounds per minute by drilling a hole in the center of the gas cylinder. The drill bit size used for this is 0.0400 ". With use, the hole will enlarge due to gas erosion.

Springfield Armory, Inc. M1A serial number 030061 was tested in January 2008 for rate of fire using a P. A. C. T. Mark IV chronograph. The M1A was fitted with a 22 " TRW chromium plated barrel, Smith Enterprise, Inc. flash hider, gas cylinder and chromium plated gas piston, a Sadlak Industries, LLC National Match operating rod spring guide and a CS Speedlock chromium silicon alloy steel operating rod spring. It averaged 798 rounds per minute using 1979 vintage Portuguese surplus ammunition. Using the modified gas cylinder plug mentioned above, the rate of fire averaged 754 rounds per minute with the same lot of ammunition.

Military versus Civilian Use

Human behavior and the laws of nature are constant but technology allows greater opportunity for both good and evil. Every weapon has its physical and historical limitations. What was state-of-the-art becomes obsolete as newer means of delivering incapacitating energy are invented and refined. The historical relevance or military life span for a given weapon or weapon type may be a few short years or several centuries. The M14 may be the top pick in the "Comeback Kid" category in the Age of Smokeless Gunpowder. Despite a general lack of military support for this weapon system, military and civilian demand keeps it very much in use simply because it works well.

First Sergeant Orian E. Melter, U. S. Marine Corps, served from 1959 to 1980 including two tours in the Republic of Viet Nam. On his first tour in 1966, he carried a M14 rifle as the radioman in a rifle platoon of 2nd Battalion 4th Marines while conducting combat operations in Quang Tri. While assigned to the Marine Corps Recruit Depot (San Diego, CA) in 1971 as a Drill Instructor, he stated, "The military is a reflection of the society from which it comes."

The American nation underwent a cultural revolution in the 1960s. The U. S. military was similarly transformed in many ways during this period, including how it developed and procured small arms. The principal change agent within the Department of Defense was Robert Strange McNamara. Mr. McNamara was Secretary of Defense from January 1961 to February 1968. As a result of decisions he took, the traditional system of government arsenals, armories and depots was emasculated in favor of a private sector system of competition and contracts for development and manufacture of military small arms. It is beyond the scope of this work to cover that history but both systems have their own set of advantages and disadvantages.

One of many changes within the U. S. Department of Defense in the mid-1960s was the almost total abandonment of the M14 rifle. Secretary McNamara and combat experience in the Republic of Viet Nam favored the high velocity small caliber 5.56 mm NATO cartridge and the M16 rifle. This was in contrast to the 7.62 mm NATO cartridge and the M14 rifle backed by the U. S. Army Ordnance Corps and Infantry Board. However, the impetus was an honest evaluation of small infantry unit tactics from World War II and Korea. It was found that the infantry rifle fire was effective to less than 200 yards on

average early in the Korean War. At the same time, the M1918 and M1919 type automatic weapons were effective out to 400 yards. Consequently, small infantry unit tactics doctrine changed and the need for automatic fire organic to the infantry rifle squad was established. As a result, each infantry squad was assigned a second M1918 Browning Automatic Rifle late in the Korean War.

By 1958, development of high velocity small caliber rifles and cartridges began the institutional struggle within the U. S. Army to change from a .30 caliber cartridge to a .22 caliber round. The turning point in the debate came with publication of the Hitch Report in 1962. Essentially, the argument turned on three points: 1) rifle and ammunition weight savings with a small caliber cartridge 2) a greater number of hits per pound of ammunition with the high velocity small caliber cartridge and 3) most combat engagements occur at less than 300 yards negating the need for a full size rifle cartridge. In a sentence, it was the .223 Remington bullet that changed everything for the M14 rifle. With the change in ammunition came a new delivery system, the M16 rifle and later variants.

The U. S. Army Combat Developments Command Experimentation Command conducted a field experiment to test and compare the reliability and fire effectiveness of U. S. and Soviet military small arms. It was the most thorough and unbiased testing for small arms fire effectiveness ever conducted by the U. S. military. The experiment took place at Fort Ord, CA. It began on February 23, 1965 and ended May 10, 1966 with promulgation of the final report. The experiment utilized 975 soldiers in nine different simulated combat situations firing fifteen mixtures of U. S. and Soviet made rifles and machine guns for comparison. Test equipment was set up to record hits and near misses. Small arms fire effectiveness was measured by three time dependent criteria: 1) number of targets hit 2) number of near misses and 3) how long a firefight could be sustained with the ammunition carried by the soldiers. Ammunition expenditure for the entire experiment was almost 2.4 million rounds.

The final report concluded that 5.56 mm NATO weapons were superior to 7.62 mm NATO weapons. The number of target hits were about the same for both calibers but the lighter system weights of the 5.56 mm NATO weapons gave better results for suppressive fire and sustainability. The M16E1 had the lowest system (weapon and ammunition) weight of all weapons tested. The lowest system weight allowed the most rounds of ammunition to be carried by an individual soldier. Consequently, a squad of soldiers equipped with the M16E1 had the highest fire effectiveness. The Soviet made weapons were more reliable than all of the U. S. weapons. The M14E2 was the most reliable U. S. made firearm with the M14 and Stoner rifles tied for second place.

Fortunately, the M14 was rescued from near death in the late 1960s and early 1970s. It was the competition match shooter community that created the demand for a commercial M14 rifle. By 1971, civilians could purchase a semi-automatic version of what had been a government monopoly. Sales of M14 spare parts from the U. S. government and its contractors supplied the civilian market with an affordable supply of parts with which to

build new commercial manufacture M14 type rifles. Military and civilian competition shooters upholding the American tradition of marksmanship continued to keep the M14 very much alive through the 1970s, 1980s and into the early 1990s. Due to a second wave of gun control laws in the late 1980s and early 1990s, civilian interest in and demand for the M14 blossomed henceforth. Product development by private industry in the present day continues to fuel both commercial and military interest in the M14 platform.

More than fifty years after the M14 Rifle was adopted by the U. S. Department of Army as its standard infantry weapon, the U. S. government retains less than 10 % of the original inventory, none of the spare parts, no ability to manufacture new parts, and very little of the necessary maintenance support. Some of the remaining M14 rifles have been unwrapped and pressed into service in the Global War on Terrorism in the role of designated marksman rifle for U. S. Army and Army National Guard units. At the same time, the United States civilian population possesses approximately three times the number of M14 type rifles as the U. S. government as well as possessing all of the available spare parts, all of the capacity to produce new parts, most of the maintenance support, and acts as custodian of the associated knowledge base.

Critics of the M14 rifle argue that its long range reach is unnecessary. Well-documented research and testing stemming from World War II onward has concluded that 300 yards is the maximum range for most combat situations involving individual rifle fire. Additionally, the weight and length of the M14 make it cumbersome for military users according to the naysayers. However, newer designs for stocks, barrels and muzzle attachments make the M14 competitive in weight and length with modern high velocity small caliber rifles and carbines. While long range fire is not the typical norm for individual riflemen in modern combat, the greater energy delivered from the 7.62 mm NATO projectile is a reassuring capability at the squad level. The M14 has certainly been put to good use in Afghanistan and Iraq.

The following example serves to illustrate the matter at hand. 1LT (then SSG) Stephen Morgan was in the Louisiana Army National Guard in 2004 when his unit was ordered to federal service. He was issued a M14 rifle prior to his company's deployment to Iraq. Due to a lack of institutional support, SSG Morgan reached out to a private business, Smith Enterprise, Inc., for parts and technical support. He was able to obtain a scope, mount, rings, and other parts from the company to upgrade his issue rifle, Winchester M14 rifle serial number 1233251.

The Louisiana Army National Guard unit including SSG Morgan finally shipped out to Iraq. Serving as a sniper, he was given an enemy combatant to track. On February 24, 2005, after three days of looking for the individual, SSG Morgan engaged the enemy while he was emplacing an improvised explosive device (IED). The successful shot was taken at a distance of 1,016 meters using his scoped M14 and M118 Special Ball ammunition. SSG Morgan received the Bronze Star with Valor for his action. He credits

this M14 rifle for saving his life in several gunfights.

Later during this tour in Iraq, SSG Morgan and other soldiers traveling by vehicle were hit by an IED. He was wounded and received a Purple Heart for injuries sustained in combat. Unfortunately, Winchester M14 rifle serial number 1233251 was destroyed in the IED blast. SSG Morgan went on to be commissioned an officer and served another tour in Iraq.

Neither technology or economics will trump the laws of nature. Neither full power cartridge or high velocity small caliber cartridge can meet all needs for the infantryman. The infantry unit equipped with an appropriate mix of rifles chambered for both schools of thought will fare better than one outfitted with just one size cartridge. For the military end user, the M14 is one of several tools available to the small unit leader. For the civilian, it may be the only viable choice in time of danger. Military operators and civilian firearms owners appreciate the M14 rifle for its reliability, accuracy, and punch. The platform has proven to be fairly adaptable to a number of military and civilian roles. When all is said and done, the M14 serves its purpose faithfully.

The civilian M14 rifle enthusiast has several factors in his favor: 1) a well made receiver will out last more than a dozen barrels 2) parts other than the receiver are not highly regulated 3) within the United States, the technical data is available and 4) many machine shops and heat treaters still welcome business opportunities. For civilians, the M14 rifle is an excellent choice for defense of home and community. The future of the M14 rifle looks clear and bright. Parts 2 and 3 of this work attempt to describe that panorama.

Notes

1. Culver Shooting Page www.jouster.com/lanestips Gus Fisher's FAQ discussion of USGI M14 receivers and parts. Gus Fisher, a former USMC shooting team armorer for two years, was told by a very trustworthy source that TRW receivers were good for 450,000 rounds whereas the other USGI receivers lasted about 400,000 rounds.

Part 2

The Commercial M14

U. S. Commercial Production of the M14 Type Rifle

Commercial production of the M14 type rifle began by 1971 and continues to the present day. U. S. commercial manufacturers have produced well over 350,000 M14 type receivers.

A batch of investment cast AISI 8620 alloy steel semi-automatic receivers were made between 1972 and 1975. Some of these receivers were not completely machined or heat treated. These receivers were marked as follows on the receiver heel M W G ASSAULT-1 BARBERTON OH. The serial number is located on the left side of the receiver at the rear or on the right side on the vertical surface of the operating rod rail. The letters M W G were cast into the receiver on the flat surface just behind the rear sight. The highest observed serial number for the M W G receivers is 000389. If a M14 type receiver has not been heat treated, it should not be used to build a rifle.

Rocky Mountain Arms, Inc. (Longmont, CO) produced the M Shorteen from 1991 to 1994. This rifle was custom built on a Chinese M14 receiver with a 17 " match crowned barrel, custom muzzle brake and front sight, and modified gas system. The receiver left side was marked: top line - ROCKY MOUNTAIN ARMS INC bottom line - LONGMONT COLORADO USA.

Characteristics of Commercial Receivers

Cast receivers - A. R. Sales Co., some Arms Corporation of America, Inc., Armscorp USA, JRM / Armscorp, Federal Ordnance, Inc., Hesse, Ltd., H&R Gun Co., Maunz Match Rifle, Maunz Mfg., most Smith Enterprise, Inc., Smith Ltd. and Springfield Armory, Inc. receivers were made by the investment casting method. Investment casting has existed in China for centuries. However, it did not gain industrial significance until after World War II with the demand for aircraft and aerospace parts. Investment casting allows complex shapes and thin sections to be formed with very close dimensional tolerances. It is common practice for the rifle manufacturer to design and own the casting die for the receiver. Any repairs or modifications to the receiver die are normally the responsibility of the owner.

Billet machined and forged receivers - Entreprise Arms and some Armscorp of America and Smith Enterprise receivers were machined from raw billet. Chinese and LRB Arms receivers were drop forged. The raw Chinese receiver forging weighed 6.6 pounds. The rifle manufacturer, typically, owns the receiver forging dies and is responsible for any maintenance on the dies.

Receiver Barrel Ring - Chinese, LRB Arms, Fulton Armory and some Springfield Armory, Inc. receivers have a distinct machined flat surface with a longitudinal edge on the top of the barrel ring. At some point after the first 3000 Springfield Armory, Inc. M1A receivers, the presence of this flat surface on the top of the barrel ring is found sporadically until a serial number just above 030000. The flat surface on the barrel ring is present on serial numbers 0062XX, 00623X, 00724X and 01899X but is not on 015XXX, 020XXX, 0210XX and 0301XX.

Caliber Marking - Springfield Armory, Inc. used upper case letters MM as part of the 7.62-MM caliber receiver marking until at least serial number 000326. At some point between serial numbers 000377 and 000411, Springfield Armory, Inc. changed the abbreviation for millimeter to lower case mm on its receivers. Springfield Armory, Inc. used to include the stamping 7.62-mm or 7.62mm as part of the receiver marking. The 7.62-mm marking is the more common of the two. Additionally, where the caliber is indicated as 7.62mm (no hyphen) the model number is stamped as M-1A (with hyphen) instead of the usual M1A model number. Receiver serial numbers 0616XX, 062110 and 66857 are stamped with 7.62mm (no hyphen) and M-1A (with hyphen).

The 7.62 millimeter caliber markings began with serial number 000001 and remained as part of the heel stamping until at least serial number 0630XX. By serial number 063112 the caliber marking no longer appears on M1A receivers. Thus, about March 1991 the 7.62-mm and 7.62mm markings were dropped because Springfield Armory, Inc. was producing the M1A in different calibers, e.g., 7mm-08.

Millimeter is stamped with an upper case MM on Armscorp of America, Armscorp USA, JRM / Armscorp, Enterprise Arms, Fulton Armory, LRB Arms, Smith Ltd., Smith Enterprise, and some imported Poly Technologies receivers. On most Chinese M14 type rifles imported into the United States the caliber is typically denoted .308 but will be indicated on the barrel if not on the receiver. A Poly Technologies M14/S rifle, serial number 0653, has been observed with the receiver heel caliber stamping 7.62 NATO.

Receiver Scope Mount Horizontal Groove and Bolt Hole - Some commercial receivers have horizontal grooves too shallow and narrow to accommodate military specification side three point scope mounts, e.g., Brookfield Precision Tool and Sadlak Industries. The USGI drawing specification for the horizontal groove is 0.149 " wide at the top of the groove with a sixty degree angle from the bottom of the groove. Commercial receiver horizontal grooves can measure as narrow as 0.120 " at the top of the groove. Early production Smith Enterprise, Inc. receiver scope mount bolt holes were made with a pitch of twenty-four threads per inch. This is the only known exception for M14 type receivers which otherwise accept a Number 12 - 32 NEF thread screw.

Commercial Receiver Geometry

The commercial semi-automatic M14 type receivers have no selector lug, no operating rod rail center dismount notch, and no groove on the front underside of the operating rod rail. The dismount notch for the operating rod is located at the rear end of the operating rod rail on all U. S. commercial and post-1978 Chinese receivers. Some commercial receivers have a very slight ledge between the operating rod channel vertical surface and the operating rod dismount notch, e.g., Springfield Armory, Inc. and Armscorp USA. This ledge helps to secure the operating rod to the receiver but it increases the patience and care necessary for field stripping.

Bolt Lock Window - A very few commercial receivers were machined with the bottom of the bolt lock window too high. This may cause the bolt lock to bind against the bolt left rear lug making the bolt stick. Some commercial receivers had bolt lock windows with too much radius in the corners which restricted bolt lock engagement. Very rarely, commercial receivers will have burrs in the bolt lock window corners that require minor filing to clean them up. Some receivers from one particular manufacturer have a rounded bolt lock window lower front corner. This can result in unexpected bolt lock release. It can often be corrected by carefully squaring the bolt lock window front corner. Some commercial manufacturers have made the bolt lock windows slightly large in an attempt to eliminate bolt lock problems. The bolt lock window is a difficult area to machine and all commercial manufacturers have experienced problems in this area. Often, simple adjustments by a M14 gunsmith are all that is required to correct any bolt lock issues.

Operating Rod Rail - Springfield Armory, Inc. and Smith Enterprise, Inc. select fire receivers have both the rear and center operating rod dismount notches as well as the cut on the underside of the forward end of the operating rod rail. If a receiver is USGI or 1965 Chinese manufacture, it will not have the operating rod rear dismount notch.

Many of the U. S. commercial receivers (Springfield Armory, Inc., Armscorp USA, Fulton Armory, etc.) have operating rod rails wider than the USGI specification. Operating rod rail width has been measured on Armscorp receivers as follows: 1) serial number 10451 manufactured in April 1993 – 0.232 " 2) serial number 15906 manufactured in January 2000 – 0.258 " 3) serial numbers 17011 and 17013 both manufactured in July 2003 – 0.316 ". The Armscorp USA receiver operating rod rail was also machined differently from USGI specification to prevent the bolt roller from slamming back. Armscorp USA receiver operating rod rail channels were deliberately undersized to accept operating rods with worn tabs, because new USGI operating rods ones are scarce.

The Fulton Armory receiver operating rod rail measures about 0.140 " wider than the USGI receiver operating rod rail specification (0.130 " – 0.01 "). Canadian import Norinco receiver operating rod rails are approximately 2 mm wider than the USGI drawing specification. The select fire Springfield Armory, Inc. receiver operating rod rail is 1/8 " wide while its semi-automatic receivers are made with one 3/16 " or 13/64 " wide. Melvin

A. Smith increased the M1A operating rod rail width by 0.066 " to achieve the same strength as the USGI M14 receiver. Additionally, the wider operating rod rail provides more bedding surface and complicates conversion to select fire.

Semi-automatic M14 type receivers will not have the selector lug and operating rod rail machining cuts. Springfield Armory, Inc. M25, LRB Arms M25 and some Norinco M305 receivers do not have the scope mount boss on the left side. Arms Corporation of America, Inc., Armscorp USA, LRB Arms, Smith Enterprise, Springfield Armory, Inc. and Entreprise Arms also made rear lugged and double lugged receivers for competition shooting. The receiver lug or lugs are welded on to the receiver. Fulton Armory offered rear lugged receivers until 2007. Springfield Armory, Inc. has offered a rear lugged receiver since 1989 and LRB Arms has done so since 2003. Smith Enterprise has added lugs to receivers upon customer request since at least 1991. Receiver lugs are welded on with two known exceptions. About 1985 or 1986, Smith Manufacturing Co. (Holland, OH) produced rear lugged receivers from castings for Arms Corporation of America, Inc. Karl Maunz designed and marketed a bolted receiver front lug from 1985 to 1987.

The first Springfield Armory, Inc. M1A receivers had a notched groove for the sight cover, e.g., serial number 000049. This machining feature was absent by serial number 002884. Some late manufacture Federal Ordnance and other commercial receivers have a screw threaded into a small hole in the center of the rear sight pocket. This aftermarket modification was done to accept a Lyman Products target sight mounting block.

Manufacturing Difficulty and Forgiveness – Even though the M14 receiver is essentially an updated 1936 design, it is not easily machined into final form. The USGI M14 receiver has an overall nominal length of 7.92 " and an overall nominal width of 2.04 ". It weighs approximately 1 pound 4 ounces. A rear lugged receiver weighs an additional 3 ounces. Aside from the M1 Rifle receiver, it is likely the most intricately machined firearms receiver to ever be made.

Springfield Armory, Inc. M1A receivers under serial number 003700 have shown some deficiencies. These deficiencies illustrate both the difficulty of making the receiver and the general ease of repairing same.

1) The receiver bridge primary (bolt closing) firing pin retracting surface can be mislocated. The firing pin itself should be examined on a regular basis. The camming surface of the tang may show damage. If the firing pin is damaged, it should be replaced. Also, the first or second version firing pin should be used in these receivers. Without the chromium plating of the third version, most of the damage will be on the firing pin instead of the receiver bridge. The harder chromium plated surface of the third version firing pin will cut a groove into the receiver bridge deeper and sooner. Note that light polish wear is normal on the retracting surface but a groove cut by the firing pin is not.

2) The receiver rear sight elevation knob indexing detents wear prematurely due to slightly too soft surface hardness. The simple fix is to install an elevation repair disk between the elevation knob and the receiver rear sight pocket left side ear.

3) The bottom of the bolt roller makes contact with the receiver when the bolt is in battery. This is a simple fix for a reputable M14 gunsmith. The fix will save replacing the bolt or bolt roller. It also provides complete bolt-to-receiver lock up.

4) The receiver locking lug engagement surface is slightly misaligned. A reputable M14 gunsmith can lap the bolt to solve this issue. This is a must for competition shooting and it evenly distributes the stress on the receiver.

5) The rear sight pocket is slightly too short. This results in a slight over hang of the base at the rear by about 0.020 ". This springs the rear sight cover more than it should. The front edge of the cover can be lightly filed down. That allows less force needed to install the rear sight cover and thereby secure the rear sight aperture.

6) The holes for the bolt lock pin are too small. The bolt lock roll pins could be forced in which may cause one of the bolt lock window receptors to break. The simple solution is to use a slightly smaller diameter pin.

Modeling the receiver with Computer Aid Design software is extremely challenging for the advanced design engineer. A single five axis CNC machining center was not capable of performing all of the cuts necessary to bring the receiver to final form. Some cuts still require manual manipulation of a cutting tool to complete the form to blueprint specification. The drawings require numerous helical cuts. The left bolt lug camming surface just aft of the barrel ring is the most difficult helical cut to make on the M14 receiver. However, it is a very forgiving design in that many of the machining cuts are purely cosmetic. For example, the top edge contour from the rear sight pocket to the barrel ring, the relief cut above the bolt lock, the barrel ring top center and left hand corner, and the heel corner symmetry on commercial receivers are often not identical to USGI receivers but accuracy and function are not affected in the least. In May 2011, Smith Enterprise, Inc. became the first manufacturer to produce M14 type receivers with CNC machine tools making 100 % of the machining operations.

Comparison of USGI and Springfield Armory, Inc. Select Fire Receivers - There are seven differences between the commercial Springfield Armory, Inc. select fire receiver and a USGI receiver: 1) the commercial receiver has a rear dismount notch 2) receiver heel stamping reflects either USGI contractor or the commercial Springfield Armory, Inc. manufacture 3) the USGI receiver has the part number, 7790189, stamped underneath the operating rod rail forward of the center dismount notch 4) the USGI receiver has a hole drilled in the right receiver leg 5) the commercial receiver selector lug is neatly welded on 6) Springfield Armory, Inc. receivers have a small hemisphere machined on the outboard side of the receiver rear sight pocket right ear and 7) the operating rod rail

forward end underside groove is 0.030 " narrower on the commercial receiver. Otherwise, they look the same. An examination of both select fire receivers under the heel, rear sight base and cartridge clip guide show similar underside machining cuts.

U. S. Commercial Manufacture Select Fire M14 Type Rifles

Civilians may own select fire M14 type rifles in the United States of America as long as federal, state and local laws are complied with. However, the May 19, 1986 McClure-Volkmer Firearms Owners Protection Act banned new production of select fire M14 type rifles allowed for civilian possession under the registration provisions of the 1934 National Firearms Act. Converted and new commercial manufacture receivers were registered under the National Firearms Act by approved ATF Form before May 19, 1986.

Since 1971, U. S. commercial manufacturers have produced more than 310,000 M14 type receivers but less than one percent of them are select fire capable. Springfield Armory, Inc. (Geneseo, IL) produced 125 select fire M1A rifles between the late 1970s and May 1986 at its factory. Some serial numbers observed for original factory built Springfield Armory, Inc. National Firearms Act registered select fire M1A rifles are 006812, 026897, 030061, 033905, 038206, 038215, 038225, 038239, 038503, 038607, 038627, 038679, 038719, 038767 and 038770. Smith Enterprise, Inc. made 176 NFA transferable select fire M-14 rifles and at least one post-ban dealer sample.

A number of Springfield Armory, Inc. M1A rifles made by the Texas company have been identified as NFA registered select fire conversion models such as serial numbers 000908, 001691 and 002860. As early as May 1974, Class 2 FFL/SOT Fred L. Rexer, Jr. (Houston, TX) was converting M1A rifles to select fire capability. He offered his conversions in a standard M14 wood stock for \$365.00 or dressed in a M14E2 stock for \$415.00. The Rexer conversions are denoted by the letters FAKTS on the left side of the receiver. M1A serial number 001691 is one of the FAKTS conversions. At least one Texas M1A was converted by Federal Firearms Licensee Stan Andrewski. In early 1975, Class 2 FFL/SOT Rich Davis (Salem, VA) sold select fire conversions of the Springfield Armory, Inc. M1A for \$550.00. Central Kentucky Arms (Cynthania, KY) converted M1A serial number 003205 to select fire.

A few M1A rifles built in Illinois were converted to select fire after they left the factory and registered under the National Firearms Act. Rock Island Armory (Colona, IL), the late J. D. Farmer of Hard Times Armory (Smyrna, GA), R.P.B. Industries (Avondale Estates, GA), and Federal Firearms Licensees Earl Banta (TX), Charles Erb, and Martin Pearl (NM) were businesses who legally performed such work. Neal Smith (OH) converted M1A serial number 0329XX and Hard Times Armory converted M1A serial numbers 014748 and 026897 to select fire. Neal Smith conversions were marked on the receiver under the stock line: top line - NEAL B. SMITH, JR. bottom line - MENTOR, OHIO. Pearl Manufacturing (Grants, NM) legally converted at least one Springfield Armory, Inc. M1A to select fire. Rock Island Armory converted thirty-five M1A rifles, e.g., serial number

018895, to select fire capability before May 1986. Ozark Mountain Arsenal (Atlanta, IN) converted Smith Enterprise, Inc. M-14 serial number 0013X to select fire.

Camp Perry Military Reservation

Camp Perry Military Reservation is a 640 acre Ohio National Guard marksmanship training center. It is the largest small arms firing range in the world. Camp Perry is located on the shore of Lake Erie about eighty miles west of Cleveland, OH. Since 1907, military and civilian shooters have participated in the National Rifle Association and National Board for the Promotion of Rifle Practice / Civilian Marksmanship Program (CMP) national matches conducted each summer. Collectively, these are known as the "National Matches." The M14 M and M14 NM were first shot at Camp Perry at the 1963 National Rifle Matches. The M14 NM was first used in competition at Camp Perry during the National Matches held August 16 to August 30, 1964. The M16 and its civilian semi-automatic only versions were approved for matches in 1971 by the National Board for the Promotion of Rifle Practice. By the early 1990s, the M16 style rifle had essentially replaced the M14 for match competition at Camp Perry. 1994 was the last year for the U. S. Army shooting team to field the M14 at the National Matches. However, the U. S. Marine Corps held on the longest using the M14 NM as late as 1996 at the National Matches. The Marines experimented with various length gas pistons along with other techniques in a systematic quest to maximize the accuracy of the M14 rifle.

John C. Garand retired in April 1953 from Springfield Armory. He did some consulting work for Mathewson Tool Company in 1954 on the T44E4 rifle, developmental version of the M14. He visited the National Matches at Camp Perry every summer with 1961 being his last trip there. As part of his last visit to Camp Perry, Mr. Garand visited the TRW test facilities at the adjacent Erie Ordnance Depot while developmental work was being done on the M14 NM. TRW occupied four brick buildings at the Erie Ordnance Depot. The U. S. Coast Guard had office spaces in one of these buildings in February 2005. In the early 1960s, Erie Ordnance Depot warehoused hundreds of thousands of M1 Garand and M14 rifles.

As an aside, at the Camp Perry National Matches, TRW assembled and exhibited a display board 4 feet by 8 feet in size displaying all of the M14 rifle parts with many of them in various stages of manufacture. The raw forgings of the eleven TRW manufactured M14 parts were displayed on the board. This included a semi-finished receiver. The rear sight knob components were shown individually and in assembled condition. The display board also had two TRW M14 barrels of which one barrel had been cut in two places along the length to show the chamber and bore rifling. This TRW display board was sold at a Ohio gun show in March 1972.

From 1960 until at least 1968, men such as Elmer Ballance, Karl Maunz, and Richard Smith participated in the shooting competition at Camp Perry. Melvin A. Smith was at Camp Perry each year during this period selling welded M1 Garand receivers and parts to

civilian competition shooters. From the early 1960s until 1974, civilian competitors used the M1 Garand rifle and military shooters were equipped with the M14 rifle. Before 1960 until some time in the mid-1970s as many as 3,500 civilians competing at Camp Perry each summer were housed in hundreds of four man wood huts. The wood huts had originally been built to house Prisoners-of-War during World War II. In the 1960s, they were labeled with automobile license plates to assist the residents in locating their assigned huts. Most of these wood huts were torn down a long time ago but a few dozen were still intact in February 2005. These wood huts were approximately 16 feet square. In the 1960s, each hut had four single military bunk beds and a wall-mounted rifle rack for the occupants to store their rifles.

From about 1970 until 1986, civilian competitors traded M14 rifle parts amongst themselves from these wood huts and from their automobiles. This practice was known as "tailgating." Karl Maunz started an informal association of competition shooters in 1984 in Atlanta, GA known as the American Shooters Union. The American Shooters Union had set up a place to buy, sell, and trade M14 parts in 1985 amongst the Commercial Row at Camp Perry. Camp Perry officials put a halt to tailgating as of 1986. In response, Karl Maunz and other members of the American Shooters Union opened a firearm parts and accessories store known as Uncle Sam's. The store was located at 4484 W. Lakeshore Port Clinton, OH, directly across the highway from the entrance to Camp Perry. In the summer of 1986, Uncle Sam's sold used M14 parts and other firearms related items. From their 1986 catalog, some of the M14 parts prices are as follows: complete bolt \$35.00, stripped bolt \$25.00, barrel \$75.00, flash suppressor \$15.00, gas cylinder \$15.00, operating rod \$30.00, fiberglass stock \$10.00, complete rear sight assembly \$15.00, complete USGI M14 parts kit \$239.95, Accuracy Lug \$39.95, and Maunz Mfg. receivers for \$239.95.

In observance of the 100th Anniversary of the National Matches at Camp Perry, Springfield Armory, Inc. sponsored the NRA / Springfield Armory M1A Match. The match consisted of fifty shots at 300 yards. It was held August 05, 2007 at Camp Perry with more than 500 shooters participating. The firm donated \$25,000.00 in cash, merchandise awards, and medallions to those shooters taking part. The weather for the match was less than ideal. Heavy rain turned the firing line into mud in short order. At the end, seventeen year old Ryan Castonguay (New Hartford, CT) was the match champion with a score of 463-8X.

Civilian and Military Marksmanship Awards

Civilians in the competition shooting community provided the impetus for a commercial version of the M14 rifle. Thus, it may benefit the reader at this point to an explanation of how competitive High Power rifle shooters are classified and why there was a market for such a rifle. The National Rifle Association (NRA) awards marksmanship classifications according to scores achieved in NRA approved or registered shooting matches. The NRA classification is based upon the percentage of possible points achieved in NRA

recognized matches.

The NRA awards an initial classification to a competitive shooter after 120 recorded shots (three recognized matches). Each shot is worth a maximum of 10 points. Thus, a fifty round match is worth up to 500 points. The shooter is reclassified by the NRA every 240 shots thereafter. The classification award for the shooter is based on his average score. To qualify for a particular classification, the shooter must have fired a given average score as listed below within that class.

The highest NRA classification is High Master. High Master is awarded to a competitor who averages a score of 97 % or better for 300 shots in NRA approved or registered matches. The other NRA classifications are Master at 94 %, Expert at 89 %, Sharp Shooter at 84 % and Marksman for less than 84 %. Shooters of the same classification compete amongst each other.

High Power Rifle Matches are typically divided into Service Rifle and Match Rifle categories. Service Rifles must keep the same external appearance of the military service rifles, e.g., M1 Garand, M14 and M16. This rule allows commercial versions of the military service rifles to be used in NRA High Power matches. The competition Service Rifle must also use the same caliber of ammunition as the associated military service rifles. Match rifles do not have the same restrictions as Service Rifles so they are usually customized to the individual shooter.

The Distinguished Rifleman or Distinguished Marksman badge is awarded to Service Rifle competitors. It is presented by the Civilian Marksmanship Program or the recipient's branch of the U. S. Armed Forces. The qualifying meets are known as Excellence-in-Competition (EIC) matches.

EIC matches are held at intraservice and interservice military matches, the annual National Matches at Camp Perry and at civilian State Championship or Regional Match competitions around the country. Competitors are limited to no more than four EIC matches each year but one of the four must be the National Trophy Individual Match at the National Matches held at Camp Perry. These EIC matches are commonly referred to as "Leg" matches. EIC matches are shot with Service Rifles only. The EIC matches use the full distance fifty shot National Match course. No sighting shots are allowed. The top ten percent of non-distinguished shooters earn six, eight or ten points credit toward the distinguished shooter badge.

If a shooter accumulates thirty points over the course of his lifetime, including at least one eight or ten point award, the distinguished shooter badge is awarded. The Navy, Marine Corps and Coast Guard award the Distinguished Marksman for Service Rifle competition. The Army, Air Force and the Civilian Marksmanship Program award the Distinguished Rifleman badge. The distinguished rifle badge was authorized by the U. S. Secretary of War in 1887.

The President's Hundred award was established in 1958 by the National Rifle Association. The President's Hundred shoulder tab is awarded to the top ten percent of civilian and military competitors, subject to the top 100 scorers, in the President's Match held at the National Matches. The President's Hundred cloth shoulder tab is approved for wear on enlisted military uniforms.

The U. S. Army and U. S. Marine Corps award weapons qualification badges as follows:

U. S. Army - A device signifying Expert, Sharpshooter or Marksman suspends a bar by two metal loops. The bar denotes the type of weapon the wearer qualified on, e.g., Rifle, Pistol, Machinegun, Carbine, Mortar, Artillery, etc.

U. S. Marine Corps - Badges are authorized for the most recent weapon qualification of Rifle Expert, Sharpshooter and Marksman and Pistol Expert, Sharpshooter and Marksman. The U. S. Marine Corps M14 Rifle qualification test consisted of the following: 1) ten rounds fired at 200 yards in slow fire in the standing position 2) ten rounds fired in sustained fire at 200 yards from the sitting position 3) ten rounds fired in slow fire at 300 yards with half shot from the sitting position and the other rounds fired in the kneeling position 4) ten rounds fired at 300 yards in sustained fire from the prone and 5) ten rounds at 500 yards in slow fire from the prone position. A total of fifty rounds were shot for a maximum possible 250 points. The minimum points necessary to earn U. S. Marine Corps rifle marksmanship badges were as follows: Rifle Marksman – 190, Rifle Sharpshooter – 210 and Rifle Expert – 225.

The U. S. Navy has issued the Rifle Marksmanship Ribbon and the Pistol Marksmanship Ribbons since 1920. The U. S. Navy Rifle Marksmanship Medal was first authorized in 1969. The U. S. Navy and U. S. Coast Guard award marksmanship medals and ribbons as follows:

U. S. Navy - 1) Navy Rifle (or Pistol) Marksmanship Medal and Ribbon for Expert (letter E device on medal and ribbon 2) Navy Rifle (or Pistol) Sharpshooter Ribbon (letter S device on ribbon) and 3) Navy Rifle (or Pistol) Marksman (plain ribbon).

U. S. Coast Guard - 1) Coast Guard Rifle (or Pistol) Marksmanship Medal and Ribbon for Expert (letter E device on medal and ribbon 2) Coast Guard Rifle (or Pistol) Sharpshooter Ribbon (letter S device on ribbon) and 3) Coast Guard Rifle (or Pistol) Marksman Ribbon (plain ribbon).

The U. S. Air Force awards the Small Arms Expert Marksmanship Ribbon for a qualifying score in either rifle or pistol qualification. A bronze star on the ribbon denotes qualification in both rifle and pistol.

Springfield Armory, Inc.

Springfield Armory, Inc. is the oldest and largest commercial manufacturer of M14 type rifles. Springfield Armory, Inc. has been located in Geneseo, Illinois since November 1974 when Robert (Bob) R. Reese became the owner. While at Camp Perry in August 1973, Bob Reese took a photograph of Karl Maunz with a U. S. Marine utility cover (hat) on his head and a M1A rifle in his hands posing in the offhand position. Mr. Maunz borrowed the utility cover for the photograph from a friend present at the time. This photograph was drawn as an illustration and became the company's logo by no later than January 1976. At the suggestion of Colonel Joe Smith, head of the DCM, in August 1973 at Camp Perry, Karl Maunz encouraged Mr. Reese to shoot the M1A rifle in a DCM match and he did so.

Texas Production

The Springfield Armory, Inc. story begins with U. S. Air Force veteran Mr. Elmer Ballance of Devine, Texas. His last name is correctly spelled with two lower case letters "L." He started his business, L. H. Gun Co., in 1960 while stationed at Lackland Air Force Base in San Antonio, Texas. The base had a housing subdivision named Lackland Heights. To save time writing, he named his company, L. H. Gun Co. "L. H." is an abbreviation for Lackland Heights. While serving in the Air Force, Mr. Ballance shot the M14 rifle in competition on the All Air Force High Power Team. Staff Sergeant Ballance earned U. S. Air Force Distinguished Rifleman Badge (# 42) before completing his military service in 1964. After that, he built match grade M1 Garand rifles for competition shooters. At some point, L. H. Gun Company also produced and sold .30 Caliber M1 Carbine ammunition in boxes of fifty cartridges.

The U. S. Army Springfield Armory had closed down in April 1968. During the NRA National Matches at Camp Perry in the summer of 1968, the closure of Springfield Armory was a topic of discussion among the attendees including Elmer Ballance, Karl Maunz and Melvin Smith. These three men and an unnamed fourth person, held two or three meetings during August 1968 in one of the wood huts used to house civilian competitors. During one of these meetings, there was a Buckeye beer case full of Melvin Smith welded M1 Garand receivers wrapped in newspaper in the middle of the hut. It was in this meeting that Karl Maunz voiced his suggestion to name the business venture that would produce commercial M14 type rifles, "Springfield." This was agreed to by the four men present.

Subsequent to this, Mr. Ballance began the process to acquire the name "Springfield Armory" for production of his commercial version of the M14 rifle. In late 1969, Mr. Ballance commenced work on making the dream of civilian M14 type rifles become reality. Though banks refused to fund his dream, this did not deter him. Mr. Ballance raised the funds himself. He and Melvin Smith of Valley Ordnance Co. worked together to get the equipment set up for production of the civilian receiver and complete rifles at

their respective facilities in Texas and Pennsylvania. Some of the machinery and parts which Mr. Ballance purchased for the project came from the Harrington & Richardson plant in Worcester, MA. The original M1A receiver die supplied to Valley Ordnance was fabricated by tool and die maker Bill Lowry (Holland, OH).

M1 to Semi-auto M14 Receiver Conversions - During this time, Mr. Ballance also modified less than fifty Springfield Armory and Winchester M1 Garand receivers to accept the M14 barrel and gas system, to function with M14 magazines, and to fit in M14 stocks. This was completed prior to September 1971. These are the first commercial production M14 type rifles ever made. In 1971, these M1/M14 receivers and complete rifles sold for \$100.00 and \$250.00, respectively. One of these modified M1 Garand receiver semi-automatic M14 rifles was sold by Collector Firearms in Houston, Texas in 2004 for \$2500.00. The workmanship on these modified M1 Garand receivers is excellent.

In 1971, Jerry's Guns & Ammo (Hibbing, MN) built semi-automatic only M14 type rifles with USGI M14 parts and highly modified M1 Garand receivers. One of the receivers was a Winchester M1, serial number 161125. The Jerry's Guns & Ammo receiver kept a lot of the M1 profile under the stock line but the legs were shortened, the middle portion of the receiver removed, and a bolt lock was added. Under the stock line, the right hand of the receiver was electropenciled: top line - JERRY'S GUNS & AMMO bottom line - HIBBING, MN 55746. The M1 Garand receivers were modified by Valley Ordnance Co.

Western Ordnance (Mesa, AZ) performed at least one M1 Garand receiver conversion to semi-automatic M14 in the early 1970s. The late Ed Bland (Richmond, VA) converted some M1 Garand rifles in 1995 to accept M14 magazines. This conversion included adding a BM59 bolt lock to the receiver. The M1 wood stock and hand guard was replaced with a USGI M14 fiberglass stock and hand guard. The converted M1 Garands were offered in three versions, tanker (18 " barrel), carbine (19 " barrel) or standard (22 " barrel). The carbine model had a commercial manufacture muzzle brake with an integral front sight base. The tanker and standard versions used a M1 Garand firing mechanism converted to BM59 design. Early carbine models utilized a M14 firing mechanism with a M1 Garand trigger guard. Later, the rear receiver leg was modified for carbines to accept a M14 trigger guard. Unfortunately, Mr. Bland passed away in 2000. In 2002, Old Corps Weaponry (Bald Knob, AR) made some M1 Garand receivers capable of accepting M14 magazines. Reportedly, there were several dozen made.

"What's in a name? that which we call a rose By any other name would smell as sweet" - William Shakespeare, *Romeo and Juliet*, 1594. The Bureau of Alcohol, Tobacco and Firearms held the position in 1971 that the M14 rifle was a machine gun as defined by the 1968 Gun Control Act. The Valley Ordnance Co. design receiver was only designed for and capable of semi-automatic fire. Thus, the BATF was of the opinion at the time that it had to be named something other than M14. The text on page 5 of the January 1975 edition of the BATF publication P5300.1 is reproduced here:

M-14 Machine Gun

[photograph of M14 rifle inserted here]

CLASSIFICATION: Machine Gun

DISTINCTIVE CHARACTERISTICS: This is the M-14 Rifle. It generally can be distinguished from the M-1 by shoulder plate, magazine and flash hider. The forestock is also different from that found on the M-1. The Selector Switch on the M-14 Machine Gun is located on the right rear side of the receiver, just above the trigger. All M-14's which are so marked are Machine Guns whether or not equipped with a Selector Switch.

SPECIAL NOTE: The Model M-1A rifle manufactured by the Springfield Armory, San Antonio, Texas is identical in appearance to the M-14, but is NOT a machine gun. The M-1A is a Title I weapon.

RATE OF TRANSFER TAX: \$200.00

The model number M1A appears to have lost any relevance to functionality with Class 2 FFL/SOT licensees legally converting M1A rifles to select fire capability as early as May 1974. About 1985, the BATF changed its stance on the model names M14 and M-14. Ron Smith of Smith Enterprise, Inc. called BATF Director Stephen Higgins to request approval to mark the company's soon-to-be-manufactured receivers with the model name M-14. Director Higgins asked Ron Smith how BATF Agents would be able to distinguish a Smith Enterprise, Inc. M-14 from a select fire capable M14. Mr. Smith proposed that Smith Enterprise, Inc. select fire capable models would have a serial number starting with the letters FA indicating full auto fire. Director Higgins agreed to this proposal and issued a letter to Smith Enterprise, Inc. allowing manufacture of semi-automatic receivers with the model name M-14. From 1985 onward, the following firearms manufacturers produced semi-automatic M14 type rifles stamped M14 on the receiver heel: Arms Corporation of America, Inc., Federal Ordnance, Inc., Fulton Armory and H&R Gun Co. Likewise, Smith Enterprise, Inc. and Smith Ltd. (Smith Manufacturing Co.) produced semi-automatic rifles marked M-14. In 2007, the BATFE publication *Identification of Firearms Within the Purview of the National Firearms Act* posted on its web site still had the same description of the M14 as the 1975 edition of P5300.1 reproduced above.

Mr. Ballance began marketing the M1A rifle in September 1971. The M1A rifle was first advertised in *Shotgun News* in the November 01, 1971 issue. In October 1971, his Federal Firearms License was in the name of his business, L. H. Gun Company at 3426 Weir Avenue San Antonio, TX 78226. About this time, BATF Agents informed Mr. Ballance that he could not market the M1A rifle because the receiver markings did not bear the name and address of the manufacturer or the distributor. Mr. Ballance promptly applied for a new Federal Firearms License in the name of Springfield Armory, Inc. He agreed to indicate the address on the barrel. Thus, L. H. Gun Company became

Springfield Armory, Inc. The name of the closed government arsenal, Springfield Armory, was well known by the public and especially by competition shooters. It turned out to be a successful marketing strategy.

The Commercial M14 Becomes Reality - Production of newly manufactured investment cast M1A receivers began by the end of 1971. For example, M1A receiver serial number 000065 was received by the retail buyer on December 24, 1971. These M1A rifles were assembled from USGI and National Match M14 parts except for the receiver and select fire parts. The Texas business warranted M1A rifles for one year. The first recorded gun show (and public) appearance of the commercial M14 type rifle occurred on January 15 and 16, 1972 at the Ohio Gun Collectors Association show in Canton, OH. Though the temperature dipped to minus 15 degrees Fahrenheit that weekend in Canton, Melvin Smith promoted, but did not sell, the M1A rifle at this and all other gun shows. At this show, Mr. Smith displayed M1A rifles 000003 (in match grade configuration) and 000011 and M1A receiver 000012. In the same row of tables, an OGCA member displayed M1A serial number 000070 dressed in a M14A1 stock, M2 bipod, M14E2 muzzle stabilizer and M14E2 sling. In January 1972, Mr. Ballance sold a stripped M1A receiver for \$110.00 and a barreled M1A receiver for \$125.00. Mr. Smith continued to display and promote the M1A rifle at Ohio gun shows until at least July 13, 1975.

In January 1972 Valley Ordnance Co. (Wilkes-Barre, PA) was prepared to manufacture all major M1A components. Melvin Smith and Elmer Ballance agreed that Valley Ordnance would be responsible for the manufacture of the components parts and for maintaining an adequate supply of spare parts. Valley Ordnance would handle all quality control on receivers and any barrels that it might make. L. H. Gun Company would supervise all quality control during assembly and final testing and would have the sole right to sell M1A rifles. A large stack of customer orders had been building up. The San Antonio plant was not able to meet the demand. So, the L. H. Gun Company was forced to move to a new facility in Devine, TX. Beginning on February 03, 1972, Springfield Armory, Inc. moved its operations and inventory about thirty-five miles to Route 1 Devine, TX 78016. Mr. Ballance was receiving mail and had telephone phone service at Route 1 Box 210 Devine, Texas 78016 by no later than March 04, 1972. No M1A rifles or receivers were shipped until after an amended Federal Firearms License with the new address was issued on March 23, 1972. Before May 13, 1972, Mr. Ballance was marketing his business as Springfield Armory.

In 1972, M1A rifle serial number 000345 failed in the receiver. The owner was shooting the rifle when the new operating rod parted at the weld joining the tube and the handle sections. The receiver cracked at the bolt lock opening and the last ¼ " to ½ " of the receiver heel struck the owner very lightly in the face. The impact of the receiver heel was so light that the shooter aimed the sights and squeezed the trigger again without realizing what had happened. The firing pin gouged itself into the stock. The shooter was using ammunition marked IBI. Although the receiver was ruined, this incident demonstrated the strength of the M1A rifle. Mr. Ballance replaced the receiver and rebuilt

the rifle for the owner at a cost of \$12.50 for a new bolt and new operating rod. It was the opinion of Mr. Ballance that the rifle had a loose operating rod guide when it failed. The loose operating rod guide placed a shearing force on the operating rod which resulted in the separation of the operating rod. Mr. Ballance did not perform the original build on this rifle before it failed.

In December 1972, Mr. Jim Lewis of Ohio reported a receiver crack in his M1A rifle serial number 000414. During a session at the range and while changing magazines, he noticed a crack in the receiver heel that ran parallel to the serial number. The crack was visible on the right side of the receiver but the steel held together on the left side. Mr. Lewis also reported "that one of the hammer hooks had broken off." Mr. Ballance replaced the receiver for Mr. Lewis without cost. Mr. Lewis was not injured.

In January 1973, about M1A serial number 001329, the end of the receiver bolt right lug slot, located under the rear sight base cover, was extended 0.080 " rearward to prevent possible damage to the bolt roller. About five months later, by serial number 001977, the bolt right lug slot was fully extended to the windage knob ear. It has remained so to the present day. In March 1973, Melvin Smith stated that he would adjust his machine tools to remove less steel from the M1A receiver for all future production in order to strengthen the rear end of the receiver. M1A receiver serial number 000049 has a maximum thickness of ¼ " at the heel rear wall centerline. M1A receiver 002884 has 5/16 " thickness at the same location. Receiver serial numbers 030061 and higher all have a full 3/8 " thickness at the receiver heel rear wall centerline. Additionally, there is noticeably more uncut steel in the bolt raceways aft of the cartridge clip guide in the receiver serial numbers 002884 and up.

Guns Illustrated conducted a test of a bedded but rack grade M1A with a Winchester chromium plated M14 barrel in January 1973. The rifle consistently shot 1.5 to 2 MOA out to 500 yards using 1968 Lake City 173 grain Match and Sierra 168 grain Match hand load ammunition.

In the first quarter of 1973, Mr. Ballance supplied the first recorded commercial 18 " barreled M1A receiver made to Thomas Buss of Springdale, PA. To this, Mr. Buss installed a modified M14 stock with BM59 folding butt stock parts and M14A1 fore grip and a modified gas cylinder lock and front sight assembly to create on March 08, 1973 the M1A Assault Rifle. His M1A Assault Rifle had neither flash suppressor nor muzzle brake. It grouped 4 " at 100 yards in comparison to 2 " groups with the M1A and the Mark IV rifles. The machinist who made these modified gas cylinder lock and front sight assemblies was Ray Kryza of Michigan doing business at the time as H&R Surplus Sales.

Wayne E. Young was a U. S. Army armorer of eighteen years experience in 1973 when he was stationed at the Fort Benning AMTU. His Army service included service with the 9th Infantry Division sniper school in 1968 in the Republic of Viet Nam. He had a Federal Firearms License and his own work shop off base. He built match grade M1 Garand,

M1A and Mark IV rifles for civilian competitors. His gunsmithing work was highly regarded by the shooting community. Glenn Nelson, another AMTU armorer, built match grade M1A rifles in the same shop alongside Wayne Young for Elmer Ballance. Another military armorer, John Holden, built at least ten match M1A rifles for Mr. Ballance. The stocks on those rifles were stamped J J H along with the last four digits of the serial number.

On May 06, 1973, a M1A receiver was tested inadvertently when the head separated from a reloaded cartridge during firing. The commercial brass case had been used previously and was loaded with 46.8 grains of H335 gunpowder. All of the bolt parts were blown out of the bolt body including the roller except the ejector spring. The stock was split severely, the magazine blown apart, the hammer broken, the sear torn from the trigger. The receiver was scored by the roller-less bolt and by the firing pin. Close visual examination revealed no other damage to the receiver. The shooter only received a superficial cut to the face. Nonetheless, Mr. Ballance offered to replace the damaged parts and the receiver if magnetic particle inspection or proof firing showed any damage at no cost.

In the fall of 1973, a second improperly hand loaded cartridge caused a M1A receiver to crack but not come apart. Both bolt lugs sheared off when an excessively loaded cartridge was fired. There was no serious injury to the shooter.

The M1A became eligible for use in NRA High Power shooting matches on January 01, 1974. The NRA had modified Rule 3.1.1 in the High Power Rifle Rule Book to allow commercial made M14 type rifles to be used in competition shooting matches. At about the same time, the *American Rifleman* tested and reviewed M1A serial number 001562 in the March 1974 issue. The response to the article was overwhelming. By the third week of March 1974, Mr. Ballance was receiving 200 letters a day. In the July 1974 issue of *American Rifleman*, it was announced that commercial versions of the M14 rifle were acceptable for National Board for the Promotion of Rifle Practice sanctioned Excellence-in-Competition matches.

In early May 1974 Springfield Armory, Inc. moved its operations and inventory to 12106 Radium Drive in San Antonio to cut costs. Production ceased temporarily while equipment and inventory was moved from the Devine facility to the San Antonio facility and set up. An application was submitted to the BATF on May 13, 1974 to change the address on the Federal Firearms License. At this point, *approximately* 2000 receivers and rifles had been shipped. However, rifles and receivers were not sold by serial number sequence. Thus, M1A serial numbers above 002000 were shipped from three locations: 1) Route 1 Box 210 Devine, TX 78016 2) 12106 Radium Drive San Antonio, TX 78216 or 3) Geneseo, IL. The best information available indicates the large majority of the M1A serial numbers shipped from the Radium address were stripped or barreled receivers, not complete rifles. The new FFL was not issued by the BATF until late September 1974. Springfield Armory, Inc. at 12106 Radium Drive San Antonio, TX

78216 shipped M1A stripped and barreled receivers to customers until the end of October 1974.

Mr. Ballance never made or converted any M1A or M14 type rifles to select fire. All of the Texas M1A receiver serial numbers start with a zero. It is not feasible to determine the original model of a Texas M1A by serial number. The serial numbers were logged in as "manufactured complete" regardless of model type, standard, National Match or E2. The serial number was logged a receiver if shipped unassembled. All Texas M1A receivers were test fired by Mr. Ballance, whether sold stripped or with a barrel. Some of the Texas M1A receivers were assembled into complete rifles by U. S. Army armorers at Fort Benning, GA. 100 to 150 of the M1A rifles assembled in Texas were fitted with T44E4 wood stocks with the selector cutout filled in, e.g., M1A serial number 001830. The first T44E4 wood stock was installed on a M1A rifle under serial number 000100. Mr. Ballance charged an additional \$100.00 for a M1A rifle fitted with a T44E4 stock and wood hand guard. He purchased these stocks and hand guards from government surplus sales.

M1A Receiver Shipments from 1971 to 1975

The following information pertains to Valley Ordnance production of M1A receivers as related by Melvin Smith to Thomas Buss while the two met at Ohio Gun Collector Association shows from 1971 to 1975.

December 24, 1971 - M1A receiver serial number 000065 was received by the original buyer.

January 15, 1972 - Serial numbers over 000400 were being shipped to Texas.

September 23, 1972 - M1A serial number 001056 was the latest finished receiver.

November 11, 1972 - The latest M1A serial number was over 001200.

July 14, 1973 - The latest finished M1A receiver was serial number 001838.

September 22, 1973 - The latest finished M1A receiver was approximately 002150. M1A rifle serial numbers being shipped from Texas were above 001500.

January 19, 1974 - The latest finished M1A receiver was 002504. M1A serial number 001727 was received by the original buyer this month.

July 13, 1974 - M1A receiver 003396 was recently finished.

September 21, 1974 - Valley Ordnance recently resumed production of M1A receivers after a six week shutdown period. Production ended the previous month at serial number

003700.

January 18, 1975 - The original buyer took delivery this month of M1A receiver serial number 003322 from Springfield Armory, Inc. in Geneseo, IL.

March 01, 1975 - The latest finished receiver was 004164.

July 12, 1975 - Valley Ordnance Co. had manufactured more than 5000 M1A receivers to date.

The Texas M1A

By no later than the beginning of 1973, Mr. Ballance had a four page color sales brochure made up for the M1A rifle. This same brochure was used in reply to mail order inquiries until the fall of 1974. One of these brochures, mailed from the L. H. Gun Co. on January 06, 1973, had M1A models and prices listed as follows:

Standard model with fiberglass stock \$200.00

Standard model with new walnut stock \$225.00 or used walnut stock \$215.00

Standard model with new beech stock \$215.00 or used beech stock \$200.00

M1AE2 with birch stock \$250.00

M1AE2 with bipod \$275.00

Match grade model with walnut stock \$250.00

New issue bayonet \$5.00

Standard M1A rifles were shipped with one twenty round magazine each and match grade models were shipped with two in the factory box. All M1A complete rifles assembled in Texas had the address where it was assembled indicated on the barrel. These barrel markings were typically located on the underside between the gas cylinder and the flash suppressor but some were stamped between the front band and the chamber. There were three barrel address markings for the Texas company.

The marking L H GUN CO S A TEX 78226 was found on the first 100 rifles assembled by Mr. Ballance. Additionally, a few of these hand stamped barrels were shipped to armorers at Fort Benning. This stamping was done by hand in two lines using serif font characters. L H GUN CO is on the first line and S A TEX 78226 is on the second line.

With the move to Devine, TX the M1A barrel marking was changed to one of three variations: 1) RT I BOX 210 DEVINE TEX 2) RT I BX 210 DEVINE TX or 3) DEVINE TEX. The full Devine address marking was initially done in two lines with RT I BOX 210 or RT I BX 210 on the first line then DEVINE TEX or DEVINE TX on the second line. The two line Devine address marking has been observed as late as M1A serial number 001389. At some point, the Devine address marking was applied in one line to avoid indexing the barrel. The short address marking DEVINE TEX has been observed on M1A rifle serial

numbers as low as 000589 and as high as 000860. This shortened address, DEVINE TEX, has been authenticated by Mr. Ballance in two signed letters to subsequent owners of M1A serial number 000708.

The first Devine address barrel markings appeared in the spring of 1972 on assembled M1A rifles beginning at about serial number 00013X. At least some barreled M1A receivers were not stamped on the barrel, e.g., 000172 and 000214 had no address markings. The original owner received both barreled M1A receivers, 000172 and 000214, on April 21, 1972 from L. H. Gun Company in San Antonio, TX. The Devine address marking was used as high as M1A serial number 002877 which was likely shipped in April or May 1974.

The third Texas address barrel marking was 12106 RADIUM SA TEX 78216. This third barrel marking first appeared on the M1A barrels some time between May and September 1974. This address was a one line marking. The Radium San Antonio address marking appeared as early as M1A serial number 002134. Most, if not all, of the rifles built with the third (12106 RADIUM SA TEX 78216) address barrel marking were assembled by Fort Benning armorer Fred Cousy.

Springfield Armory, Inc. in Texas marked the barrels at the time of barrel installation. The barrels were marked by Mr. Ballance and by his employees. In the summer and fall of 1974, Mr. Chuck Krause was employed by Springfield Armory, Inc. On at least two M1A rifles assembled by him, he stamped his home address RT I BOX338C DEVINE TEX. One of these M1A rifles was serial number 002898. Mr. Krause was a neighbor of Mr. Ballance but the FFL address for Springfield Armory, Inc. was not the home of Mr. Krause.

The barrel of M1A serial number 000564 was electropenciled during assembly as follows: top line - DRW 430, middle line - Devine, bottom line - Texas. The bottom of the bolt and the inboard side of the operating rod were electropenciled 564. The electropenciling appears to have been done by the same person. The May 15, 1973 issue of *Shotgun News* listed a sales advertisement for Springfield Armory, Inc. The ad gave the address for Springfield Armory, Inc. as P.O. Drawer No. 430 Mailing Address RT. 1 Box 210 Business Address Devine, Texas 78016 and included a 512 area code phone number. In September 2006, the owner of M1A serial number 000564 confirmed by telephone interview with Mr. Ballance that it was shipped to Fort Benning by him as a stripped receiver in trade for services rendered. There were approximately 120 such bare and barreled receivers built into complete rifles by Wayne Young and Glenn Nelson for Elmer Ballance.

A very few Texas marked barrels were sent to Geneseo, Illinois. The barrels on the first M1A rifles leaving the Illinois factory were electro-penciled Geneseo Ill. However, M1A rifles in 1975 were sold with a coupon to be used towards the purchase of a spare barrel. Thus, a very few of the spare barrels sold by the Illinois company had Texas markings. It is likely that a very small number of individuals eventually had these Texas marked spare

barrels installed on M1A rifles sold by Springfield Armory, Inc. in Illinois.

Transition from Texas to Illinois

An advertisement announcing the sale of Springfield Armory, Inc. in Texas appeared in the September 01, 1974 issue of *Shotgun News*. *Shotgun News* and *Gun Week* ran advertisements in October 1974 placed by C & M Gun Works (then 2603 41st Street Moline, IL 61265). The advertisements strongly implied that C & M Gun Works had purchased Springfield Armory, Inc. in Texas. C & M Gun Works, a distributor of firearms related items, stamped its company name, city and state on the L. H. Gun Co. M1A rifle brochures. C & M Gun Works, named after the owners Cindy and Michael, created an eight page sales flyer announcing its purchase of much of the inventory of the Texas firm.

Springfield Armory, Inc. changed ownership effective November 01, 1974. Bob Reese, owner of Reese Surplus, Inc., was the new owner. The new company address for Springfield Armory, Inc. was now 218 North State Street Geneseo, Illinois 61254. The transfer of the company assets included all of the unused receivers and barrels and many of the USGI parts. Production problems troubled the Reese family for some time. These problems were sorted out over a few months and M1A production resumed by the spring of 1975.

When the Texas company receivers had been used up, Valley Ordnance continued to supply finished M1A receivers to the Illinois company. It did so until July 1996 when Melvin Smith passed away. The bare receivers, barrels and other parts left over from the Texas firm were used to help start production of the M1A rifle in Illinois.

The M1A serial number transition from Texas to Illinois occurs from about 002700 to approximately 003300. The following individual cases serve to illustrate the transition M1A serial numbers.

Serial number 002709 - M1A serial number 002709 was shipped as a bare receiver to the original buyer in November 1974. This is the lowest known M1A serial number sold from Springfield Armory, Inc. located in Geneseo, IL.

Serial number 002734 - M1A serial number 002734 was shipped from Geneseo, Illinois on April 28, 1975. Geneseo Ill is electro-penciled on the barrel of M1A serial number 002734.

Serial number 002831 - M1A serial number 002831 was sold new to the original owner by a FFL on February 19, 1975. The price was \$309.75 including sales tax. The barrel has the marking RT I BX 210 DEVINE TEX. It is likely that this rifle was assembled in Geneseo, IL with a Texas marked barrel.

Serial numbers 002867 and 002874 – M1A serial number 002874 has the following one line address marking on the barrel: RT I BX 210 DEVINE TEX. According to the original owner and his purchase receipt, M1A rifles with serial numbers 002867 and 002874 were shipped from Devine, TX in May 1974 to his local FFL. Both rifles were then promptly sold to him.

Serial number 002877 – This M1A rifle has an October 1962 production Harrington & Richardson chromium plated barrel. The barrel marking is identical to M1A serial number 002831 except there is an O between B and X. Springfield Armory, Inc. in Geneseo, IL has no record of this serial number.

Serial number 003139 – M1A serial number 003139 has the 12106 RADIUM SA TEX 78216 marking on the barrel.

Serial number 003159 - Stripped M1A receiver serial number 003159 was received by the original owner on November 01, 1974 from Springfield Armory, Inc. at 12106 Radium Drive San Antonio, TX 78216.

Illinois Production

Bob Reese was an Illinois soybean farmer with an enduring passion for firearms. At some point after World War II, he bought military surplus items including firearms parts. He went into business as Reese Surplus Sales, Inc. in December 1963. There was a strong public demand for the M1 Garand rifle. Bob Reese served the non-competitor market demand by welding cut M1 Garand receivers back together to help meet this demand. Mr. Reese purchased Springfield Armory, Inc. in the fall of 1974. It was made a division of Reese Surplus, Inc. and later incorporated on January 24, 1977 as a separate entity. Originally located at 218 North State Street, the business moved to 111 East Exchange Street by January 1976 and then to its present address at 420 West Main Street by September 1981. Bob Reese, his wife and their sons, Tom, David and Dennis, have built the business into an American success story. Beginning in the barns of the family farm, the business grew to forty employees by 1986. That year, Raymond W. "Buddy" Pilgrim was President of the company. A short time later, Bob Reese sold the business to his sons, Tom and Dennis Reese. Tom and Dennis Reese serve as Co-Chairmen with Dennis as the Chief Executive Officer for the firm. By 1994, domestic distribution of the M1A rifle was firmly established through a handful of large distributors who filled dealer orders. By June 2007, Springfield Armory, Inc. employed 135 persons.

In addition to the M1A, Springfield Armory, Inc. of Illinois has made the M1911 pistol, M1 Garand, SAR 48 and BM59 rifles, and the M60 machine gun. The M1 Garand and BM59 receivers were made by Springfield Armory, Inc. and assembled with surplus parts. The Springfield Armory, Inc. M1 Garand was introduced in 1979 and its BM59 debuted in 1981. BM59 rifles and parts are still available through its sister company, Reese Surplus, Inc. The Italian firearms manufacturer, Fabbrica d' Armi Pietro Beretta, developed the

BM59 rifle from 1957 to 1958. Like the M14, the BM59 is a descendant of the M1 Garand rifle.

The M1A receiver design was further changed between serial numbers 002884 and 010048 to include a small hemisphere on the outboard side of the rear sight pocket right ear for use of a ball bearing to engage a detent on a newly designed match windage knob. This windage knob allowed ½ minute of angle sight adjustments by allowing eight “clicks” per revolution of the knob. Original USGI NM sights used a more delicate fine thread on the windage knob and rear sight base to effect ½ minute windage adjustments with four “clicks” per revolution.

Springfield Armory, Inc. made further changes to the receiver geometry around serial number 040000. The chamber was moved very slightly forward to improve accuracy and increase bolt lock up time. Some Springfield Armory, Inc. M1A receivers have a ridge on the bottom right hand side that may slightly interfere with the fit of some stocks. It appears to have been a part of the finished casting. This ridge has been identified on M1A rifle serial numbers as low as 000049 until somewhere between 0343XX and 0422XX. The bottom side ridge was removed from the design as part of the changes made for economic reasons. It meant two less machining cuts but it also had the benefit of a better fit with various makes of stocks. Prior to the May 1986 ban on new manufacture machine guns, Springfield Armory, Inc. had a Full Auto Department that manufactured and assembled select fire M1A rifles.

Springfield Armory, Inc. M1A rifles with serial numbers under 084000 were reportedly made prior to the September 13, 1994 effective date of the U. S. Violent Crime Control and Law Enforcement Act. Springfield Armory, Inc. sold stripped receivers manufactured prior to September 13, 1994 as well. If the stripped receiver was not assembled into a complete rifle by September 13, 1994 it was considered a post-'94 ban firearm by the BATF. During the ten years of the 1994 Assault Weapons Ban, specific features could not be added to M14 type rifles assembled for civilian sale after September 13, 1994 within the United States. These federal restrictions were automatically repealed by the sunset provision (automatic expiration of the law absent further Congressional action) of the same law on September 13, 2004. State and local laws are still in effect though. Certainly, the 1994 Assault Weapons Ban had no adverse effect on the popularity of the M1A. M1A serial number 166761 was built on August 26, 2004, just before the repeal of the ban. Springfield Armory, Inc. had USGI M14 parts kits available to them for assembly of M1A rifles at least through the 100XXX serial number range.

M1A receivers were cast by Alphacasting, Inc. (St-Laurent, Quebec, Canada) for Springfield Armory, Inc. for about one year in the 2003 - 2004 period. Alphacasting, Inc. made the M1A receiver by the lost wax investment casting method. In business since 1991, it is a precision casting firm that makes parts from aluminum, bronze, and many grades of carbon and stainless steels. As of 2009, M1A receivers are supplied by a vendor. The rough machining is done by an Illinois machine shop. Finish machining and

headspacing is performed in-house.

At Springfield Armory, Inc., all basic rifle assemblers have a minimum of two years experience assembling rifles before they are allowed to assemble rifles on their own. A rifle is test fired with five rounds for function and has to function through all five rounds or it doesn't get shipped. If it fails for any reason, it gets torn down and rebuilt. Then the rifle is tested for five rounds again.

On rare occasion, the M1A receiver heel has been stamped erroneously. The letter I is missing from SPRINGFIELD on receiver serial number 062857. The serial number, 064922, is stamped to the right of center on the receiver heel. About 300 receivers in the 165XXX serial number range were stamped AROMRY instead of ARMORY. Specific examples of AROMRY marked M1A receiver serial numbers are 165345, 165389, 165412 and 165418. Obviously, these unintentional markings are only cosmetic in nature and have no bearing on the fit or function of the rifle. Beginning around serial number 270000, M1A receiver heel markings were engraved. Some receiver heel markings were stamped as high as the 296000 number range.

M1A Packaging – After assembly and testing, the M1A rifles are packed for shipment. A brightly colored plastic empty chamber indicator is inserted into the chamber and the bolt closed on it. The factory headspace and safety warning tags are attached to the trigger guard. Then the M1A rifle is inserted into a plastic sleeve and placed inside a cardboard shipping box. The shipping box also contains an owner's manual, safety literature, warranty information, and accessories and parts sales brochures. Springfield Armory, Inc. M1A rifles had a limited warranty for one year after the initial purchase for the period January 01, 1976 until December 31, 1992. Effective January 01, 1993, Springfield Armory, Inc. M1A rifles are sold with a limited lifetime warranty that applies to the original retail buyer. In recent years, a gun lock has been included. The shipping boxes were green and white in color until sometime between serial number 07157X (winter 1993) and 075XXX (fall 1993) when they were changed to blue and white.

Illinois M1A Models

In the August 01, 1975 issue of *Shotgun News*, two M1A models were available, Standard and Match. At about this time, the Super Match M1A was introduced in the August and October 1975 issues of *American Rifleman*. These first Super Match M1A rifles had Shilen eight groove 1:12 twist molybdenum-chromium alloy steel barrels. These barrels weighed 1 pound 4 ounces more than a USGI NM barrel. The Match M1A became known as the National Match M1A between 1976 and 1978. In 1976, the suggested retail price for a Standard M1A rifle was \$342.50. For a Match M1A, the price was \$457.50 and the Super Match M1A was \$511.75. This selection of M1A models, Standard, National Match and Super Match, continued until 1981. From 1978 to 1988, these three models were available from the factory in M1AE2 configuration (assembled with a USGI M14E2 stock). A fourth type, the M1A-A1, was added in 1981. Beginning

with the importation of surplus USGI M14 parts in 1984 and product development in subsequent years, over 100 different M1A configurations have been offered (see Appendix I). The manufacturer's suggested retail price for the Standard M1A with a commercial walnut stock (catalog number MA9102) from 1984 through 1987 was \$842.00. The Match Shop at Springfield Armory, Inc. has built the National Match, Super Match, and M21 model rifles since 2004.

M1A Bush and M1A Scout Squad - The 18" barrel M1A model series debuted in 1981 as the M1A-A1 Assault. Through the years, the M1A with an 18 " barrel has been marketed at different times as the M1A-A1, M1A-A1 Bush Assault, M1A-A1 Bush, M1A-A1 Scout Squad, M1A Bush and M1A Scout Squad models. The Scout Squad model was first sold in 1996 as the M1A-A1 Scout Squad. The Scout Squad models were assembled with muzzle brakes, barrel rail scope mounts and modified hand guards. Assault, Bush Assault and Bush models were assembled with flash suppressors. Regardless of the model name or number, these shorter M1A rifles were defined by the 18 " 1:11 twist six groove non-plated molybdenum-chromium alloy steel barrel. Various wood or fiberglass stocks have been offered for the series. The barrel scope mount was sized for standard contour barrels. The M1A Scout Squad barrel rail scope mount (catalog number MA5056) could be purchased separately.

Between 1999 and 2003, Boyds' Gunstock Industries became the supplier of walnut M1A stocks to Springfield Armory, Inc. Beginning in July 2005 Springfield Armory, Inc. switched from a textured black surface on synthetic M1A stocks to its second generation version, a smooth and more durable black finish fiberglass stock.

Small Production Run M1A Models – Springfield Armory, Inc. has produced a number of small production lot M1A rifles through the years.

1) Gold Series - In 1986, this competition model M1A was offered in a choice of stocks, oversized National Match walnut or aramid material, and in a choice of match barrels, heavyweight Douglas molybdenum-chromium alloy steel or Hart stainless steel. Springfield Armory, Inc. guaranteed each rifle in this series would shoot no worse than ten shots inside 3 " at 200 yards from a bench using premium ammunition.

2) M14 Vietnam Commemorative - Springfield Armory, Inc. offered the M14 Vietnam Commemorative rifle in 1987. There were two models, US Army Commemorative M14 and US Marine Corps Commemorative M14. No more than 1,500 of each model were produced. The receiver serial numbers had AR and MC prefixes, respectively, followed by four digits. Likewise, the outboard side of the operating rod handle was marked US Army Commemorative M14 or US Marine Corps Commemorative M14 as appropriate. Metal parts were given a blued finish or 24 karat gold plating. Gold plated parts included the safety, trigger, rear sight knobs, cartridge clip guide, front and rear sling swivels, front band, spindle valve, gas cylinder plug, flash suppressor and front sight. A service branch medallion was inletted to the right side of the butt stock. The Army medallion was green

and gold. The Marine Corps medallion was red and gold. The outer circumference of the stock medallion bore the inscription VIETNAM REMEMBERED GALLANTRY DUTY DEVOTION for both models. Standard with each rifle was a leather M1907 type leather sling, a blued finish twenty round magazine, an Army M14 technical manual and a certificate of authenticity. Optional items included a walnut display case, M6 bayonet with a blued finish blade, M8A1 scabbard, cleaning kit, and a brass name plate placed on the right side fore end of the select grade walnut stock. There was no selector cutout on the stocks. The walnut display case was lined with green velvet for AR series rifles and red velvet for MC series rifles.

3) Even Hundred Edition - This was a lot of 100 rifles with serial numbers without the usual leading zero but ending in 00. These M1A rifles were produced in early 1989. The receiver heel vertical surface directly above the stock selector cutout was marked 1 of 100.

4) Sport Master - The receiver heel of the Sport Master is stamped as follows from top to bottom: first line – U S RIFLE second line – SPORT MASTER third line – SPRINGFIELD ARMORY fourth line – SM0XXX. These rifles had either a solid walnut or gray wood laminate stock with an integral cheek rest as part of the butt stock and a bipod stud in place of the front sling swivel. This model was available in 1991.

5) Even Thousand Collector Edition – In 1991, Springfield Armory, Inc. produced a small batch of collector grade M1A rifles and an unknown number of M1911A1 pistols. According to a very reliable source, there were probably no more than sixty M1A rifles produced of this type. These rifles had a matte blued finish and gold plated triggers. The handle portion of the operating rod was marked COLLECTORS EDITION. The highly polished wood stock was inlaid with a large medallion applied to the right side of the butt stock. The medallions were marked Collectors Edition and Even Thousand Serial Number. The receiver serial numbers were even thousand numbered, e.g., 15000.

6) IDF M1A - In the late 1990s Springfield Armory, Inc. bought the parts from some Israeli Defense Force M14 rifles. The parts from these rifles, including the Harris bipods, Israeli Military Industries stocks and scope mounts and Nimrod 6X range finding scopes, were assembled on to commercial Springfield Armory receivers with heavy weight match grade barrels. They were sold as a limited run model in 1999. The IDF M1A receiver heels are marked with the Star of David just below the serial number. Each IDF M1A was issued a Certificate of Authenticity as part of the literature packed inside the factory shipping box.

7) Vietnam War Commemorative M14 – About 1998, Springfield Armory, Inc. produced a run of 500 Vietnam War Commemorative semi-automatic M14 type rifles. These M1A rifles were available for sale through the American Historical Foundation. This model was fitted with a Reinhart Fajen designed walnut stock containing a circular badge on the right hand side of the butt stock. The stock badge consisted of a red Oriental dragon walking through white color bamboo shoots all against a yellow background. The badge was

inscribed with the words REPUBLIC OF VIETNAM SERVICE. It had the following 24 karat gold plated parts: lugless flash suppressor, front sight, safety, front and rear sling swivels, rear sight assembly, trigger and magazine latch. The receiver and operating rod were etched and gold-gilt filled with symbols and inscriptions. The operating rod was marked VIETNAM WAR COMMEMORATIVE M14 and had an American flag to the rear of the inscription. The receiver heel serial numbers were stamped VME001 through VME500 along with its factory M1A serial number, VME356 is M1A serial number 109387. VME is an acronym for Vietnam-Museum Edition. Each unit of this model was issued with a ten round magazine, a USGI field manual, a black M1907 style leather sling and a Certificate of Authenticity.

8) M25 - The M25 rifle recognized the service of the late Gunnery Sergeant, USMC (Retired) Carlos N. Hathcock, II. Gunnery Sergeant Hathcock was a sniper who served his country admirably in the Viet Nam War. He is credited with ninety-three confirmed kills and a total of over 300 unconfirmed kills. The Viet Cong nicknamed him "Long Trang," which means "white feather" in the Vietnamese language, because he wore a small white feather in his cover (Marine term for hat) while in the field. Gunnery Sergeant Hathcock passed away in February 1999. The M25 was built with a 22 " Krieger molybdenum-chromium alloy steel heavyweight 1:10 twist barrel, McMillan M3A stock, Springfield Armory, Inc. rear lugged M25 receiver, Match Shop tuned firing mechanism and custom muzzle brake and stabilizer. A special logo and a likeness of Carlos Hathcock's signature was engraved on the left side of the receiver. The first batch of thirty M25 rifles was shipped in December 2001. This high-end model was discontinued at the end of 2009.

9) Camp Perry Limited Edition - Springfield Armory, Inc. produced 500 match grade M1A rifles to commemorate the 100 year anniversary of Camp Perry. The Camp Perry Limited Edition rifle was given a walnut stock with a commemorative design carved into the right hand side of the butt stock. Additional lettering was engraved on the on the receiver and the operating rod. The right side of the receiver heel was marked with the individual rifle number of the series, e.g., 24 of 500. The operating rod had a gold National Rifle Association logo and gold italicized font that read Camp Perry 1907-2007. Each rifle came with a special carry case and a certificate of authenticity.

Springfield Armory, Inc. M1A rifles have been exported to Argentina, Australia, Belgium, Canada, Finland, France, Germany, Italy, Japan, Mexico, the Netherlands, New Zealand, Sweden, Switzerland and United Kingdom for sale to private individuals. Additionally, a small quantity of M1A Scout Squad rifles have been issued to Australian Special Forces units. Private citizens in Japan may not own hand guns or automatic weapons but can own shot guns and rifles. To own a rifle, the citizen must possess ten years of experience with a shot gun or a letter of recommendation from a government recognized shooting club. In Sweden, USGI and commercial M14 (and other firearm) receivers, barrels and bolts may be owned by private individuals after obtaining government permits. From Germany, M1A rifles have been exported to Luxembourg for sale to private individuals. Nioa Trading (Banyo, Queensland) first imported M1A rifles into Australia in 1985 or

1986. The company has remained the sole importer of M1A rifles for Australia. M1A rifles have also been offered for sale to U. S. military members and their dependents through the Army and Air Force Exchange Service and the Navy Exchange at locations such as Fort Richardson (Anchorage, AK) and Camp Allen (Norfolk, VA).

Collector Edition M1A - M1A rifles have been offered in a number of models with USGI stocks. The Springfield Armory, Inc. May 01, 1998 factory price list had catalog number MA9851 for the M1A with a USGI wood stock and stainless steel barrel at a suggested retail price of \$1351.00. The Collector Edition M1A, catalog number MA9103, was a standard model offered in 2002 and 2003. It had a USGI chromium plated barrel and USGI birch stock. The original Collector Edition M1A (catalog number MA9101) was offered from 1984 through 1986 but also returned briefly in 2006. This model was assembled with a commercial standard contour barrel and a USGI wood stock.

Standard M1A - The standard model M1A has a 22 " 1:12 twist four groove molybdenum-chromium alloy barrel with a standard size rear sight and either a standard or a National Match front sight. Standard M1A rifles have been assembled with a variety of stocks: commercial birch and walnut, USGI birch and walnut, brown or black laminated wood, and black, woodland camouflage or mossy oak camouflage synthetic stocks. In 1976, the standard model M1A was only available in the USGI fiberglass stock due to a shortage of walnut stocks.

When available, Springfield Armory installed USGI chromium plated barrels on the standard M1A models. If a M1A rifle was assembled at Springfield Armory, Inc. with a Harrington & Richardson M14 barrel, the barrel was inspected prior to installation for proper chamber diameter. During times of scarcity, such as 1978 to 1986 and beginning January 2004 (by serial number 161920), Springfield Armory, Inc. installed commercial manufacture non-plated standard contour barrels instead. Wilson Arms supplied the commercial standard contour barrel blanks until at least 2005. Dasan Machineries Co., Ltd. (Jeollabuk-do, Korea) has manufactured M1A SOCOM barrels. In the past, Hillside Manufacturing did the barrel machining on Wilson Arms barrel blanks. Today, Springfield Armory, Inc. buys the barrel blanks from suppliers then performs the finish machining of the barrels itself. After January 2004, a few Standard M1A rifles were assembled with USGI chromium plated barrels.

Loaded Standard M1A - The Loaded Standard M1A model debuted on September 01, 1996. This model, MA9201, included a medium weight National Match barrel, National Match tuned firing mechanism, and National Match flash suppressor. This promotional version of the Loaded Standard model was shipped from the factory with three twenty round magazines. Unfortunately, the retail buyer wasn't made aware of the extra two magazines at the time of purchase in some instances. Consequently, some retail buyers only found one magazine in the shipping box after leaving the retail shop. M1A model MA9201 was available until December 31, 1997. In November 2006, Model MA9827 was introduced. This was the MA9826 loaded standard model fitted with the alloy aluminum

Vltor Weapon Systems CAS-14 cluster rail.

The following rifles were offered with either molybdenum-chromium alloy steel or stainless steel barrels:

A) The loaded standard M1A had a 1:11 twist medium weight match barrel, National Match modified flash suppressor, 0.0520 " non-hooded rear sight aperture and National Match front sight, tuned firing mechanism and either USGI wood, commercial walnut, or black synthetic stock.

B) The National Match M1A rifle came glass bedded in an oversized match grade walnut stock with all of the features of the loaded model plus a National Match gas cylinder, match-fitted operating rod, match-modified operating rod spring guide and National Match hooded rear sight aperture. From 1991 onward, a glass bedded walnut stock has been standard dress for the National Match M1A. In years past, the National Match M1A had been built with fiberglass, fancy burley walnut or laminated walnut/maple stocks. The National Match M1A was available with a medium weight stainless steel barrel beginning in 1999. Medium weight barrels on M1A rifles installed at the factory were typically marked NM .308 Geneseo, Ill.

C) The Super Match M1A model has been built with a standard receiver, a rear lugged receiver or a double lugged receiver. Super Match M1A models were assembled using a standard receiver as late as 1990. From 1991 onward, Super Match M1A receivers were manufactured with a rear lug as the norm. A front lug was added per customer request. The Super Match M1A was fitted with a 1:10 twist heavyweight Douglas barrel unless the customer selected another brand of barrel. Regardless of the barrel make, the operating rod will slide through an oversized operating rod guide made to fit the barrel's larger diameter at that area. The buyer also had the choice of an oversized walnut, fancy burley walnut, laminated walnut/maple, McMillan camouflage or black fiberglass stock.

D) The Springfield Armory, Inc. M21 was the rear lugged Super Match M1A dressed in a walnut stock with an adjustable cheek rest. This model was introduced in 1990.

E) The M25 rifle offered by Springfield Armory, Inc. had a rear lugged receiver, McMillan fiberglass stock with adjustable cheek piece, low profile custom muzzle brake, Krieger 1:10 twist heavyweight barrel and no iron sights. The M25 had to be scoped to sight a target. There was no cartridge clip guide or receiver scope mount bolt hole on this model. The scope attached to a rail mounted over the bolt. Production of this model ran from 2001 through 2009.

New in 2004, the M1A SOCOM 16 model weighed 8.9 pounds and had a 16.25 " 1:11 twist six groove non-plated molybdenum-chromium alloy barrel and black color hand guard and synthetic stock. The overall length was reduced about 7 " from the standard model to 37.25 ". The synthetic stock had a steel hinged butt plate. The hand guard was

cut out to accommodate the installed M1A Scout Squad scope mount. The visible portion of the operating rod was stamped SOCOM 16 on 2004 production M1A SOCOM 16 models. The front sight was an XS Sight Systems 24/7 0.125 " wide stripe post. The rear sight aperture diameter was enlarged to 0.125 ". This change in the sights was done to facilitate faster target acquisition at Close Quarters Battle ranges. On 2007 models, the M1A SOCOM 16 operating rod rail is marked SOCOM 16.

The M1A SOCOM barrel gas port was enlarged to the same dimension as the M1A Scout Squad barrel. Both model barrels have gas ports larger than the USGI 22 " chromium plated barrel dimension. The M1A SOCOM barrel muzzle was fitted with a proprietary design combination muzzle brake and gas cylinder lock assembly. The barrel used on the SOCOM models has a proprietary muzzle thread, 43/64 " diameter with a pitch of 40 right hand threads per inch. The SOCOM 16 gas system and muzzle attachment was designed by Dale Rader and first tested in 2003. The pre-production design gas cylinder plug was flush with the gas cylinder end. It was removed and installed with a hex head wrench. Between February and April 2004, the gas cylinder plug design was changed. Thus, 2004 and early 2005 production M1A SOCOM models were fitted with a proprietary gas cylinder plug machined with two cylindrical profile sections sans knurling in lieu of the traditional USGI design part. Beginning in early 2005, M1A SOCOM 16 models were assembled with the traditional design commercial manufacture M14 gas cylinder plug. Like other M1A models, the SOCOM 16 gas cylinder plug could be removed and installed using a M14 combination tool or 3/8 " wrench. After the gas cylinder plug was removed, the M1A SOCOM series combination muzzle brake and gas cylinder lock assembly could be unthreaded from the barrel.

The National Shooting Sports Foundation (Newtown, CT) owns and sponsors the annual Shooting, Hunting, and Outdoor Trade (SHOT) Show. Beginning in 1979, the SHOT Show quickly became the largest gathering of firearms, hunting and outdoor product businesses in the world. The SHOT Show has grown steadily in attendance and floor space through its history.

In 2005, Springfield Armory, Inc. upgraded the M1A SOCOM 16 design with the introduction of three new models, the SOCOM II, the SOCOM II LE, and the SOCOM 16 Urban. These new M1A rifles were debuted at the 2005 SHOT Show. The M1A SOCOM II LE was based on the 2004 M1A SOCOM 16 but with significant differences. It was equipped with a Vitor Weapon Systems (Tucson, AZ) supplied collapsing butt stock, a pistol grip and an aluminum rail mount system that surrounded the black color synthetic stock. The M1A SOCOM II LE was marketed to government agencies and military forces so it is not listed in the firm's retail catalog or on its web site. The M1A SOCOM II was the same as the M1A SOCOM II LE but sported a traditional black color synthetic stock with steel hinged butt plate. The M1A SOCOM II operating rod was marked SOCOM II. The M1A SOCOM II weighed 10.5 pounds without a magazine. In 2007, the M1A SOCOM II with an extended cluster rail was introduced. The rear end of the top cover of the standard cluster rail stopped just forward of the barrel ring. The extended cluster rail

terminated at the cartridge clip guide dovetail. The M1A SOCOM II and M1A SOCOM II LE models lost the front sling swivel because of the rail system mount. Additionally, these models retained the M1A SOCOM 16 rear and front sights and the traditional design commercial manufacture gas cylinder plug.

The M1A SOCOM 16 models came in a choice of black color or black and gray urban camouflage pattern synthetic stock. A matching urban camouflage hand guard was made available in August 2011. A traditional wood M14 stock will fit a M1A SOCOM 16 but it will require modification to clear the operating rod guide clamp on a M1A SOCOM II. The M1A SOCOM series models have been outfitted with the steel hinged butt plate or a rubber butt pad on the stock.

Gray-Syracuse, Inc., Valley Ordnance Co. and Hillside Manufacturing

H. P. Gray founded Gray-Syracuse, Inc. in 1943 as a business to produce investment castings. Its first plant was located in Syracuse, NY. The company purchased a sand casting facility in Manlius, NY in 1953 and converted it to making parts by investment casting. In the 1960s, the company expanded its customer base to include the atomic energy, space and aerospace industries. In 1975, the company moved its operations to a new, larger facility in Chittenango, NY. Gray-Syracuse was purchased by ESCO Corporation in 1987.

Gray-Syracuse made the raw M1A receiver castings starting around 1973 or 1974 until the end of 1996. The casting supplier that preceded Gray-Syracuse has not been discovered. The raw castings and certification papers for each production lot were shipped from Gray-Syracuse to Valley Ordnance until closing in July 1996. Valley Ordnance had been located at 280-282 North Main Street Wilkes-Barre, PA 18702. Valley Ordnance would then send the receivers on to Springfield Armory, Inc. At some point between M1A receiver serial numbers 0320XX and 033964, the pour lot code was made a part of the raw casting. This number is found on the underside of the receiver just behind the left leg. Valley Ordnance machined receivers had letter A prefix numbers for the pour lot. Casting pour lot numbers observed with the letter A prefix have been as high as A193 on receiver serial number 098991 and A203 on receiver 100042. The casting supplier had changed by M1A serial numbers 101255 and 101256. Those receivers were marked J10698-001 on the underside. Similarly, subsequent receivers were marked as follows: 102570 with J10698-014, 103648 with J11082/020, 106XXX with J11085/19, 1107XX was marked 12778-02, and 173898 was marked 16143-08 on the underside of the receiver. The pour lot number is an identifying mark for the casting supplier. Later, the marking Springfield Inc Geneseo IL was added to the bottom of the receiver under the operating rod rail as observed on M1A serial number 191974.

Valley Ordnance Co. had re-welded over 50,000 destroyed M1 Garand receivers when the owner, Melvin Smith, determined that there was a viable market for a civilian version of the M14 rifle. He visited Springfield Armory before it closed in April 1968. He

befriended some of the workers who identified what machine tools would be useful for manufacture of commercial M14 rifles. As a result, Mr. Smith bid upon and won an elevation serration machine and a lathe at the Springfield Armory equipment auction.

Melvin Smith also contacted Winchester to inquire about the machine it had used to make the receiver barrel threads but he was informed that most of its M14 machine tools were going to be sold. Melvin Smith purchased nearly fifty tons of M1 and M14 project machine tools, tooling, fixtures and inspection equipment at government auction so that he could produce civilian M14 receivers and parts. Most of this equipment had been used by Winchester in its M14 rifle production. Valley Ordnance made operation of the fixtures on the machine tools as simple as possible. This minimized the risk of machining errors. Some of the machinery and operations are described as follows:

1. Operating rod channel machine - This was a single spindle mill. Valley Ordnance employees made cutting tools for this machine.
2. Brown & Sharpe spline mill - This 1936 machine was highly sophisticated for its time. It was used in M1 Garand production at Winchester. This was a single spindle mill used to cut the bolt raceway inside the receiver.
3. Circular cut end mill - This machine was used to make the circular cut at the inside rear end of the receiver. A separate machine tool was used to cut the firing pin recess on the inside rear end of the receiver.
4. Elevation serration machine - A receiver was placed under a cutter (similar to a gear cutter) then rotated under the cutter to make the elevation knob serrations. This machine was bid upon and won at the Springfield Armory auction. It was one of eight elevation serration machines at Springfield Armory.
5. Beretta headspacing machine - Winchester did not include a receiver headspacing machine in the government auction of M14 project machine tools. Mr. Smith purchased a receiver headspacing machine from Beretta in Italy. The Beretta headspacing machine had been used in BM59 production. Valley Ordnance modified it for the M1A receiver. However, during Springfield Armory, Inc. production of its BM59 receivers, this machine was used to headspace the commercial BM59 receivers as a special assignment to Valley Ordnance. The operation of the headspacing machine is described as follows. The operator's left hand worked the cutting tool and the right hand ratcheted movement of the receiver by manipulating a fixture. Some timing was involved but the operator could easily hold within 0.001 " on the tolerance. The cutting tools were sharpened by the employees using a Bridgeport mill and a surface grinder. The headspace machine cutting tools were bought ten at a time from Cline Tool and Service Company (Newton, IA).

6. Rear sight pocket milling machine - This was a Bridgeport mill. It was used to machine the flat surface between the rear sight knobs and behind the cartridge clip guide.
7. Receiver scope mount groove milling machine - Another Bridgeport mill was used for this operation. Separate single pass cuts were made for the horizontal and vertical grooves.
8. Receiver heel stamping machine - The receiver heel markings were made with a metal marking press using straight dies and a rolling fixture. This marking press was manually operated as purchased from the Winchester M14 project. At some point before early 1981, Valley Ordnance had modified it to operate pneumatically. Before then, Melvin Smith operated the metal marking press himself. The dies were obtained from Numberall Stamp & Tool Company, Inc. (Sangerville, ME). The receiver was held by the fixture and rolled on a radius while the pneumatically operated ram holding the die stamped the heel. The first die stamped U S RIFLE and 7.62-mm M1A for receivers just under serial number 0630XX or US RIFLE M1A for receivers over serial number 0630XX. The die was then changed so that the machine could stamp the brand name. Then the third die was installed in the machine to stamp the individual serial number. If the number stamping die trip dog switch counter did not trip, a duplicate number was created. Or on occasion, a Valley Ordnance worker would fail to reset the number stamping die properly. In either case, the letter A was hand stamped under the serial number. By doing so, the receiver was given a unique serial number and then did not have to be scrapped. This explains the letter A under receiver serial numbers 031000, 031495, 032476 and others.

Once this equipment was set up in his shop, Melvin Smith designed improvements into the civilian version of the M14 receiver. These changes included increasing the thickness of the receiver bridge, changing the operating rod rail to better support the operating rod and prevent automatic fire, removal of small amounts of material for better clearance, and relocating the operating rod dismount notch. After some persuading by his friend, Edward M. "Ned" Hogan, Mr. Smith kept the receiver left side geometry the same as the USGI M14 even though it would add to the manufacturing cost.

Melvin Smith gave some thought to the name for the new commercial semi-automatic only M14 rifle. In the second half of 1969, Mr. Smith referred to the semi-automatic only commercial legal M14 type rifle as the M14C. At the time, M14 was considered by the BATF, then known as the ATFD, to be a machine gun. The model designation, M14, was flatly rejected by the BATF by no later than July 1970. Mr. Smith then considered naming the new commercial rifle, M15. The select fire rifle model name, M16, was not acceptable either for the same reason as M14.

In a letter from Edward M. "Ned" Hogan dated July 09, 1970, Melvin Smith was given the name for the new commercial M14 rifle. Mr. Hogan suggested M1A with an italicized letter A. Mr. Hogan reasoned that the civilian legal M14 type receiver should be known as

the M1A because it was "legally derived from the present legally modified M1 receivers now marketed by you and Mr. Ballance rather than being derived from the illegal M14 or M15." Mr. Ballance agreed with the suggested name, M1A, but without the italicized letter A. The production receiver heel markings had been decided upon by March 1971. Had Mr. Ballance not agreed to the model name M1A, Mr. Hogan had suggested model names M10 or M11. Mr. Hogan suggested M10 or M11 as alternate choices since the U. S. Army had never used those model numbers.

By no later than 1971 the Valley Ordnance M1A receiver design was approved as a Title I firearm under the 1968 Gun Control Act by the Department of the Treasury. Melvin Smith signed an exclusive contract with Elmer Ballance for Valley Ordnance to supply M1A finished receivers to Springfield Armory, Inc. These receivers were investment cast of certified AISI 8620 alloy steel. Up to as many as a dozen experimental M1A receivers were made before serial number 000001 was stamped. Serial numbers 000001 through 000010 were in the first casting lot and serial numbers 000011 through 000021 were in the second casting lot. At about serial number 000150, the length of the M1A receiver heel was changed slightly.

In 1972, Winchester did supply Valley Ordnance with Winchester marked hammer forged barrel blanks. Valley Ordnance intended to finish machine and install these barrels on match grade M1A rifles but it was not meant to be. Before Mr. Smith could complete the tool set-up, Mr. Ballance found a lot of over 1,000 USGI Springfield Armory chromium plated barrels and so the USGI barrels were used instead. Additionally, another supplier had sold Mr. Ballance 180 USGI M14 NM barrels in late 1972 and early 1973.

When Springfield Armory, Inc. had USGI M14 chromium plated barrels, its workers would often gage the chambers and group them into lots dimensionally. Based on the findings, it had Valley Ordnance cut the M1A receiver headspace to better fit the USGI M14 chromium plated barrels in its inventory. As an example, Springfield Armory, Inc. would request Valley Ordnance make 100 M1A receivers headspaced to - 0.003 " from blueprint zero. Thus, match grade and some standard model receivers have a number on the bottom surface. The numbers will range from 1 to 5. The numeral 1 means the receiver is headspace to 0.001 " longer than blueprint zero. If the receiver is marked with the number - 4 this means the receiver is headspaced to 0.004 " shorter than blueprint zero. This manufacturing practice resulted in improved accuracy because of the tighter headspace.

In January 1972, Valley Ordnance Co. performed sixty-three machining steps for each M1A receiver. Earlier receivers machined by Valley Ordnance Co. were given a lot of hand grinding and polishing by Melvin Smith. Specifically, these areas were: 1) the exterior heel corners on the sides 2) the flat surface aft of the operating rod channel 3) the top surface of the left receiver wall from the cartridge clip guide to the barrel ring 4) the vertical surface on the right side behind the cartridge clip guide all the way back including the windage knob ear 5) the left side of the barrel ring forward of the horizontal scope

mount groove 6) the magazine well aft of the feed lips and 7) the top surface of the barrel ring after all machining operations that located off the barrel ring had been done. This cosmetic detailing is evident as late as M1A serial number 062857 but was no longer being done by serial number 064922. Note that the hand polishing served to enhance the aesthetic appearance but did not add to the functional ability of the M1A receiver. As Melvin Smith moved to semi-retirement the receiver surfaces noted above were finished by machine. For example, the magazine well on M1A receivers was cut and broached by machine tool after Mr. Smith purchased Hillside Manufacturing.

The Missing Connector Lock Hole - The USGI drawing F7790189 indicates that there shall be a hole for the connector lock pin on both sides of the receiver. This allows a stuck connector lock to be pushed out if need be. The connector lock hole on the left side of the receiver was drilled in at least the first eleven M1A receivers but it is not present in M1A receiver serial number 000049. The left side connector lock hole reappeared between serial numbers 002010 and 002028. The connector lock hole was temporarily omitted to reduce the manufacturing cost by \$1.00.

The receiver heels were stamped and numbered by Valley Ordnance Co. with the exception of custom serial numbers. Custom serial numbers were available through Springfield Armory, Inc. in the 1980s. Valley Ordnance shipped custom serial number receivers to Geneseo, IL without a receiver heel serial number. However, to comply with BATF regulations, Valley Ordnance identified each of these receivers before shipping by stamping the letters VO followed by a unique sequentially issued number that was recorded like all other serial numbers at Valley Ordnance. The VO series numbers were first placed on the side of the receiver legs on earlier receivers, then on the bottom side of the receiver on the flat behind the legs on later production custom serial number receivers.

Before Melvin Smith's involvement with the M1A, Hillside Manufacturing (Dallas, PA) was a subcontractor to Valley Ordnance for portions of its manufacture of the Eagle Arms 9 mm and .45 ACP Carbines. The two companies manufactured and assembled the carbines from scratch. Mr. Smith's design for the bolt assembly used in the Eagle Arms carbines was patented in 1968. In the 1970s, Valley Ordnance was a distributor of Fox Wasp .45 ACP carbines made by Tri-C Corporation (Meriden, CT).

When Melvin Smith contracted with Elmer Ballance for the M1A, Hillside Manufacturing became a subcontractor to Valley Ordnance for that project. Melvin Smith bought Hillside Manufacturing (Dallas, PA) upon retirement of the original owner, William Croughn, in about 1990. Dallas, PA is about ten miles from Wilkes-Barre, PA. Prior to the change in ownership, Hillside Manufacturing was a subcontractor to Valley Ordnance for M1A receivers and parts but also made parts for companies like Piper Aircraft and Mack Truck. Hillside Manufacturing did the rough machining work on the M1A castings from before 1976 until 1996. After the change in ownership, Hillside Manufacturing was almost 100 % dedicated to M1A receiver production due to high market demand. The Valley Ordnance

scope of business remained this way until Melvin Smith passed away.

During the entire time Valley Ordnance was in operation, there were no CNC machine tools in its facility. All of the machine tools were single operation units and were set up and operated manually. Valley Ordnance always did the finish machining on the receivers. Valley Ordnance also did some development work on the Springfield Armory, Inc. M1 Garand receivers before 1987 but no production was done.

Since Hillside Manufacturing did not have a Federal Firearms License (FFL), it was limited in the amount of machining that it could perform on the raw castings. Otherwise, the BATF would have considered Hillside Manufacturing to be a manufacturer of rifle receivers, which are regulated the same as completed firearms. Hillside Manufacturing did machine the receiver heel surface, windage knob detents and ball detent hemispheres, and bored and threaded the barrel ring. The receiver heel surface had to be precisely machined and tolerances held closely in order to produce consistent heel stampings at Valley Ordnance. In the early 1990s, Hillside Manufacturing bought and installed three Moog Hydrapoint Model 83-3000 CNC machining centers for M1A receiver work. Before then, it used Moog Hydrapoint NC tape operated machining centers.

Hillside Manufacturing and Valley Ordnance worked together on an experimental project in 1991 to machine two M1A receivers from AISI 8620 alloy steel billet. This was done solely as a study to see if machining from billet was economically competitive with investment casting. The rough machining was done at Hillside Manufacturing and the finish machining was performed at Valley Ordnance. Disposition of these two receivers is unknown.

M1A Receiver Production Flow – A combined total of seventy different machining operations were performed by Hillside Manufacturing and Valley Ordnance for each M1A receiver. Both companies used quality control procedures after each machining operation. For operations that were cosmetic in nature, one out of every ten receivers was checked dimensionally. For critical operations, e.g., receiver threads, every single receiver was checked for dimensional tolerance. The manufacturing cycle time for the M1A receiver at Hillside Manufacturing in 1976 was 1 hour 50 minutes. By 1996, the cycle time at Hillside Manufacturing had been reduced to 45 minutes by use of CNC machining methods. The following describes the production flow for receivers during the period of 1981 to 1996:

1. Casting – Gray-Syracuse pours the castings using certified AISI 8620 alloy steel. The raw castings and material certification paperwork are shipped to Hillside Manufacturing.
2. Rough machining – Hillside Manufacturing performs rough machining of the M1A receiver. The semi-finished receivers and certification paperwork are shipped to Valley Ordnance.

3. Finish machining and inspection – Samples of semi-finished receivers are pulled and sent to Springfield Armory, Inc. for the heat treating vendor. Valley Ordnance performs the finish machining work and dimensional inspection of the remaining receivers. The finished receivers and copies of the certification paperwork are shipped to Springfield Armory, Inc. in Geneseo, IL.
4. Inspection and additional machining – Springfield Armory, Inc. inspects the finished receivers supplied by Valley Ordnance. Receivers that do not meet its standard are sent back to Valley Ordnance for destruction and recycling at Gray-Syracuse, Inc. Receivers that pass inspection are shipped to a heat treating vendor in the Chicago, IL area. If the receiver is to get a custom serial number, the heel is stamped prior to heat treatment. If the receiver is to be made select fire or lugged, this work is completed prior to heat treatment.
5. Heat treatment – The vendor performs the heat treatment procedure using the previously submitted semi-finished receiver samples from Valley Ordnance. The finish-machined receivers are then heat treated and shipped back to Geneseo, IL.
6. Coating, assembly, test fire and customer shipping – The M1A receivers are returned to Springfield Armory, Inc. from the heat treating vendor. The receivers are phosphate coated. The receivers, stocks and other parts are assembled into complete rifles and test fired on site. Similar to what existed at TRW, the test firing facility was a water backstop. If the rifle malfunctions during test firing, it is rebuilt and retested. The rifles are boxed with a magazine, factory headspace tag, M14 manual, and sales literature. M1A rifles are then shipped to firearms distributors for delivery to individual FFL holders.

Every M1A receiver was given a final inspection at Valley Ordnance as part of the quality control program. The finished M1A receiver was placed on a magnetic base and compared using a Starrett dial indicator to a Winchester M14 receiver or custom made gage blocks surface ground and hardened to the USGI receiver blueprint dimensions. The Winchester receiver used for quality control purposes was cut off just behind the rear sight pocket. A less-than-80 % finished TRW receiver was used to check dimensional quality of the receiver heel rear end machining cuts. Every M1A receiver had a bolt inserted into it by hand to check for proper function before leaving Valley Ordnance. Springfield Armory, Inc. also performed inspection of finished M1A receivers. Any receiver deemed to have any machining errors, even minor cosmetic flaws, was sent back to Valley Ordnance for destruction. These less-than-perfect receivers, as many as 100 at a time, were destroyed by sledge hammer at Valley Ordnance then shipped back to Gray-Syracuse, Inc. for recycling back into raw castings. At Valley Ordnance, there were no “factory seconds” M1A receivers. M1A receivers are of good quality. Springfield Armory, Inc. has never used Chinese M14 parts in the assembly of its M1A rifles.

The Starrett dial indicator and custom gage blocks were transferred to Springfield Armory, Inc. in 1996 along with the machine tools from Hillside Manufacturing and Valley Ordnance. Comparison of select fire M1A serial number 030061 to close up photographs of several USGI Winchester M14 receivers reveals similar machining cuts on all surfaces.

The busiest year for Valley Ordnance was 1994. This was the year the federal Assault Weapons Ban was passed and enacted. Valley Ordnance employees worked seventy to seventy-five hours to meet orders for M1A receivers. M1A receiver serial number 076539 was shipped to Springfield Armory, Inc. on January 07, 1994. Receiver serial number 088207 was shipped from Valley Ordnance to Geneseo, IL on December 30, 1994. Average weekly production was approximately 100 M1A receivers through Hillside Manufacturing and Valley Ordnance between 1976 and 1996. However, there were weeks where Hillside Manufacturing and Valley Ordnance produced 300 M1A receivers a week in 1994 but quality control was always held to the same high standard. The second busiest year for the firm was 1990. During lean times Melvin Smith found creative ways to keep cash flowing in and his employees busy. For example, in 1985 and 1986 Valley Ordnance designed, manufactured and marketed a fish scaler. Mr. Smith's design was patented in 1988. The fish scaler was cast at Gray-Syracuse, Inc. and machined by Valley Ordnance Co. This 7.3 ounce kitchen utensil was made of a single piece of 1704 stainless steel and was backed with a twenty year warranty against wear or breakage when used only for scaling fish.

Later on, Mr. Smith fell very ill and was hospitalized. He sold Valley Ordnance to Springfield Armory, Inc. He treated all of his employees very well. In response, he was loved by his employees. Mr. Smith was a U. S. Army veteran and had served in post-World War II Italy. At his funeral, his employees coordinated with the local VFW Post to give him a twenty-one rifle volley using M1A rifles owned by Mr. Smith and the employees. He was survived by his wife and daughter.

The last complete finished M1A receiver made at Valley Ordnance Co., serial number 097726 (zero nine seven seven two six), was shipped to Springfield Armory, Inc. on May 16, 1996. Operations were shut down and the production equipment was shipped to Springfield Armory, Inc. in Geneseo, IL on July 22, 1996. Employees from Valley Ordnance and Hillside Manufacturing went to Geneseo, IL to assist in setting up the newly acquired machine tools. This was a very thorough transition taking between four to six weeks which included instruction by the Hillside Manufacturing and Valley Ordnance personnel on all machining operations. Springfield Armory, Inc. graciously offered positions to the employees from Valley Ordnance and Hillside Manufacturing with competitive wages as part of the transition. As of 2003, the M1A receivers were still machined at Springfield Armory, Inc. in Geneseo, IL in the same manner as was performed at Hillside Manufacturing and Valley Ordnance.

In late 1974 and early 1975, Springfield Armory, Inc. had difficulty obtaining a dependable supply of USGI M14 and M14 NM barrels. Thus, Bob Reese contracted with Numrich

Arms (West Hurley, NY) to manufacture 300 match grade six groove 1:10 twist AISI 4140 alloy steel barrels. Springfield Armory, Inc. advertised these barrels in the February 01, 1975 issue of *Shotgun News*.

In 1976, Springfield Armory, Inc. was purchasing M14 parts from Sherwood Distributors, Inc., Numrich Arms, and Sarco, Inc. Sherwood Distributors, Inc. (1994 address 18714 Parthenia Street Northridge, CA 91324) was owned by Michael D. Kokin. It was a firearms parts and accessories business from April 1969 until 1994. Mr. Kokin sold his company and the new owner, Bernard Hartog, established Northridge International, Inc. (San Fernando, CA) in July 1994. In the mid-1970s, Numrich Arms was owned and operated by George R. Numrich, Jr. Mr. Numrich passed away in 1991. Operations at Numrich Arms were then managed by Ira Trast. Mr. Trast had been with Numrich since at least the mid-1970s. When Mr. Trast retired about 2000, Mr. Numrich's son took the reins. Today, Numrich Arms Corporation and Sarco, Inc. remain very busy supplying firearms parts and accessories for the commercial market.

Hillside Manufacturing produced finished barrels from Wilson Arms supplied blanks from about 1978 until some time before 1990. Only Wilson Arms barrel blanks were used at Hillside Manufacturing. The 1.100 " diameter barrel blanks had the rifling done but otherwise all other machining was performed by Hillside Manufacturing. This included cutting the external contour, cutting off the breech, cutting the feed ramps, chambering, drilling the gas port, grinding the operating rod guide, gas cylinder and flash suppressor lobes, cutting the gas cylinder and flash suppressor splines, threading the chamber end to mate with the receiver, and threading the muzzle end for the flash suppressor nut. The same machine was used to cut the barrel threads and the receiver barrel ring threads. It was a Planomill thread milling machine. This was the same type of machine tool that was used for U. S. government production of the M1 Garand and M14 receivers and barrels. Springfield Armory, Inc. bought the barrel making operation including all of the associated machine tools. Before 1990, Springfield Armory, Inc. also made non-plated barrels for the M1A.

The 22 " long barrels were made in three grades, standard contour, standard contour National Match, and heavyweight National Match. None of the barrels manufactured at Hillside Manufacturing were chromium plated. A notable exception was a single run of a couple hundred M1A-A1 Bush 18 " non-plated barrels made around 1980 or 1981. The rack grade standard contour barrels were supplied to Springfield Armory, Inc. during times when USGI chromium plated M14 barrels were not available. The dimensional tolerances were incredibly tight on the barrels. For example, the diameter of the gas cylinder lobes was held to within 0.0005 ".

The barrel crowning was done by hand. The barrels were lined up by the hundreds on a bench. Melvin Smith then used his steady hand and eagle eye with a portable electric tool and ball stone to machine the crown on each barrel muzzle moving from one end of the bench to the other. The barrels were stamped GENESEO IL or GENESEO ILL at

Springfield Armory, Inc. The practice of marking the barrels with city and state started between 1976 and 1978. Some of the machine tools used in the barrel operation by Hillside Manufacturing and transferred to Springfield Armory, Inc. in 1996 are described as follows:

1. German made hydraulically operated tracer lathe – This lathe cut the external contour in one pass.
2. Cincinnati rise and fall horizontal mill – This mill cut the gas cylinder splines.
3. Ward turret lathe – This mill was used to machine the chamber to desired specification.
4. Landis cylindrical grinder – This grinder was used to obtain the final dimension of the operating rod and gas cylinder lobes after turning on the lathe.

By no later than 1978, Hillside Manufacturing machined reproduction operating rods, trigger housings, flash suppressors, bolts, operating rod spring guides and barrels. No gas cylinders were made by Hillside Manufacturing or Valley Ordnance. It has not been confirmed but most likely the trigger housing and flash suppressor castings for M1A parts were also produced by Gray-Syracuse, Inc. since Mr. Smith was loyal to his suppliers. Valley Ordnance did the finish machining on cast semi-finished cartridge clip guides supplied to the firm. The reproduction bolts, operating rods and trigger housings were stamped at Valley Ordnance. The operating rod spring guides were made from plate steel using a punch press with progressive dies. The operating rods were supplied to Hillside Manufacturing already welded together. Hillside Manufacturing machined the operating rods to final dimension. In the late 1980s, Hillside Manufacturing made fewer M1A parts as Springfield Armory, Inc. found other sources or did the work itself.

Springfield Armory, Inc. and Glenn Nelson

Glenn Eugene Nelson joined the U. S. Army in 1954 and became a member of its shooting team in 1961. He earned Distinguished Rifleman status in 1962. He remained on the Army shooting team until late 1965 when he accepted an offer to become a match armorer. He completed the U. S. Army match armorer school at Rock Island Arsenal then began building M14 rifles for competition as part of the USAMTU at Fort Benning. He was trained at the USAMTU by Sergeant "Hook" Boutin. Mr. Nelson went on to serve in Viet Nam and the Non-Commissioned Officer-In-Charge of the AMU Custom Gun Shop. Master Sergeant Nelson retired from the U. S. Army in 1975. As soon as Reese Surplus, Inc. purchased Springfield Armory, Inc. in 1974, Bob Reese hired Glenn Nelson to establish a shop that could build competition grade M1A rifles.

Mr. Nelson began building Ultra Match M1 Garand and National Match and Super Match M1A rifles from his home. However, by 1987 the business had grown such that Nelson's Custom Gun Shop occupied 5,000 square feet of building space. Over the years he put

together a first rate staff of former AMTU match armorers and former Army team shooters. Mr. Nelson and his staff kept up with and implemented the latest accurizing techniques used by the AMTU as time went on. Mr. Nelson built competition rifles for Springfield Armory, Inc. until 2004. Mr. Nelson's FFL Book had logged over 41,200 entries for rifles received for his gifted touch. When Mr. Nelson retired from business, his machine tools and shop equipment were sold to Chief Warrant Officer 3 Ken Corcoran, U. S. Army (Retired) of North Pole, AK. Chief Warrant Officer Corcoran was an AMU armorer himself.

The custom Super Match M1A rifles were fitted with either Douglas or Hart heavyweight barrels. These heavyweight barrels were available in 1:10, 1:11, or 1:12 twist rates. Mr. Nelson required the air-gauged and stress-relieved barrel blanks supplied to him have a bore diameter between 0.2999 " and 0.3004 " and a groove diameter between 0.3079 " and 0.3084 ". The heavyweight barrel blanks were supplied with rifling obviously, but the rest of the machining was done by Mr. Nelson or his employees. National Match medium weight barrels were supplied by Springfield Armory, Inc. to Mr. Nelson already for installation by other suppliers. The operating rod guides were soldered on to the barrels. For individual customers, Mr. Nelson machined hand picked medium weight and heavyweight Douglas Premium barrel blanks and installed them in rifle builds unless the customer specified otherwise.

To give the reader an idea of what is possible with the M14 rifle and a talented armorer, the following will illustrate the point. In April 1986, Glenn Nelson built a Super Match M1A rifle from stripped receiver serial number 033187. The build included all TRW parts and a National Match rear sight. After final assembly, this rifle was tested on a machine rest. It grouped fourteen shots under the size of a nickel at 200 yards with 168 grain Sierra bullets. The test target was presented to the buyer, a member of the Second Army Shooting Team.

Mr. Nelson and his staff used the same Springfield Armory, Inc. M1A receivers used on standard models to create state-of-the-art competition rifles. They performed the match conditioning work and 90 % of the assembly on the receivers sent to the Nelson shop in Columbus, GA by Springfield Armory, Inc. Subject to availability, Mr. Nelson purchased TRW bolts for building the National Match and Super Match M1A rifles in his shop. Headspace on these rifles was kept between 1.631 " and 1.632 ". The M1A rifles dressed in wood stocks were coated several times with raw linseed oil. The almost-complete rifles were shipped back to Springfield Armory, Inc. for final assembly, test firing, packaging and shipping. Final assembly in Geneseo, IL included installation of the front and rear sights, operating rods, hand guards and slings. Mr. Nelson passed away on February 17, 2007 after battling several types of cancer.

Rock Island Armory, Inc.

Rock Island Armory, Inc. was established in March 1977. David Reese was President of the company. One of its first products was newly manufactured M1 Carbine receivers. By 1985, it was located at 111 Exchange Street Geneseo, IL 61254. In 1997, the company was located at 25144 Ridge Road Colona, IL 61241. Rock Island Armory was a sister company of Springfield Armory, Inc. It mostly performed work for foreign military customers. However, Rock Island Armory did perform thirty-five select fire conversions on semi-automatic Springfield Armory, Inc. M1A rifles. These conversions were stamped with the letters R I A on top of the receiver on the flat surface behind the rear sight base. The firm advertised the M1A conversion in the July 01, 1979 issue of *Shotgun News*. Stripped select fire M1A receivers were listed in the 1983 catalog for \$375.00. Rock Island Armory had no connection with the U. S. government Rock Island Arsenal also located in Illinois. Rock Island Armory, Inc. was in business until August 1997.

Karl Maunz

Karl Maunz began shooting competitively at the age of nine. He started shooting at the Camp Perry matches at fifteen years old. He loved the sport so much that he joined the U. S. Army at the age of seventeen and was an armorer (Military Occupational Specialty was 762.10) at eighteen. He was in active service from 1957 until 1964 in the Army Reserve. He was a member of the U. S. Army shooting team from 1960 through 1964. Lacy DeGrange, a member of the U. S. Army shooting team from 1958 to 1960, helped Karl Maunz build his first M1 Garand rifle. During the early 1960s, members of the U. S. Army Reserve were only allowed to possess a M14 rifle while at Camp Perry. Unquestionably, this put them at a competitive disadvantage with Regular Army competition shooters. So, Karl Maunz ground two M1 Garand receiver halves and Melvin Smith welded them back together with a shorter overall length to replicate most of an M14 receiver's dimensions. Mr. Maunz and Mr. Smith met while at Camp Perry in 1961. While he was on the Army shooting team, Mr. Maunz would practice with this M1 Garand rifle converted to accept an M14 magazine. This is the first known 7.62 x 51 mm caliber magazine fed M1 Garand rifle. At the same time, others had ground out and machined whole M1 Garand receivers to accept M14 magazines. Disclaimer: This must not be done unless one has the proper knowledge, training, equipment and licensing to do so. Metal working operations alter the mechanical properties of steel and can compromise the strength of the finished product.

Mr. Maunz went on to shoot Distinguished Rifleman using the M1 Garand rifle shooting left-handed. He received much encouragement from Colonel Joe Smith, Director of the DCM in pursuing this achievement. In 1965, Karl Maunz scored higher than all shooters using bolt action rifles at the National Matches. He received his Lifetime Master designation from the NRA Competitions Division in 1966. The DCM belatedly awarded Karl Maunz his Distinguished Rifleman award in 1971. In 1972, he was disqualified as a civilian competitor at Camp Perry because he attempted to shoot with a Springfield

Armory, Inc. M1A rifle. The National Rifle Association later changed the High Power Rifle match rules to allow civilian competitors to use the M14 type rifle. Mr. Maunz shot competitively in the years 1960 through 1973, 1978 through 1981 and from 1984 through 1989.

Karl Maunz converted M1 Garand rifles in the 1960s to accept M14 magazines and installed 7.62 x 51 mm / .308 Winchester barrels on them. This conversion was known as the Maunz Model 57 Rifle. Around 1967 and 1968, Rimer Casting Company (Waterville, OH) produced Maunz Model 67 castings for Karl Maunz. The receiver castings were subsequently machined. The Model 67 receiver was a lengthened M1 Garand receiver with a BM59 style bolt lock but it accepted a M14 magazine. The Model 67 receivers were assembled into complete rifles. There were 400 to 500 Model 67 rifles built. The calibers were .308 Winchester or .308 case with .264 bullet. The Model 67 rifle was still available from Mr. Maunz until 1987. Mr. Maunz got his idea for naming his rifle designs, Models 57, 67, 77 and 87, from the legendary German rifle manufacturer, Mauser.

In the late 1960s and early 1970s he owned and operated Competitive Shooters Supply Company in Defiance, OH and another gun shop in Napoleon, OH. In the early 1970s, Karl Maunz built M14 type rifles using Springfield Armory, Inc. M1A receivers. He later owned American Kit Car Company and a General Motors automobile dealership. He sold a 1970 Cadillac automobile to Melvin Smith in 1971. Later, in 1977, Karl Maunz sold him a 1973 model Cadillac. At one time, Mr. Maunz owned a restaurant in northern Florida. In 2005, he owned and operated a beverage company and a vineyard.

Maunz M14 Rifle Synthetic Stocks - In 1967, Karl Maunz designed a prototype commercial M14 fiberglass stock and sent it to Reinhart Fajen, Inc. Reinhart Fajen, Inc. made a wood M14 stock from this prototype. Mr. Maunz enhanced his original design in a drawing done at Cincinnati, OH dated April 10, 1977. He specified lightweight synthetic resin foam material to fill the butt stock in these satin black color heavy contour fiberglass stocks beginning in 1977 to enhance hearing protection for the shooter. The Maunz M14 synthetic stock could be reinforced with ballistic resistant material in 1986 for an additional \$25.00. The Maunz M14 rifle stocks were available from 1977 until about 1989. The first of the Maunz M14 synthetic stocks was installed in 1977 on Springfield Armory, Inc. M1A serial number 000011.

Mr. Maunz sent a wood copy of his 1977 design fiberglass M14 stock to Reinhart Fajen, Inc. about 1978 or 1979. He also traded one of his April 1977 design fiberglass M14 stocks to Gale McMillan around 1985. That same year, Karl Maunz drew up the design for a red, white and blue M1A rifle stock to be sold through the American Shooters Union. Reinhart Fajen, Inc. manufactured this red, white and blue wood laminate stock in 1985 for Karl Maunz. This stock was reportedly featured in the 1985 Edition of the *Shooter's Bible*.

Maunz Receiver Master Die – Karl Maunz drew up the semi-automatic M14 receiver master die using a copy of USGI M14 receiver drawing F7790189 in the winter of 1969. A machinist at Rimer Casting Company (then at its address in Waterville, OH prior to Rimer Road Waterville, OH) reviewed it for Mr. Maunz. Mr. Maunz then gave the modified M14 receiver drawing to Bill Lowry, an employee of Rimer Casting. Fabrication of the receiver master die was delayed due to a lack of funds until late 1970. The receiver master die took six months to fabricate. Finally, the receiver master die was completed some time before August 1971. The stamped serial number of the master die is 71-1761-183. The master die was designed to produce a casting with an open barrel ring. It was found that this caused porosity at the front end of the casting. Consequently, the die was modified on April 05, 1972 by adding an insert that allowed the pour to fill the barrel ring in the casting. Between 1971 and 1987, this receiver master die was used to birth all of the M14 type receiver castings for A. R. Sales Co., Maunz Mfg., Maunz Match Rifle, H&R Gun Co., and Smith Ltd. and some castings for Arms Corporation of America, Inc. For example, in a purchase order dated June 22, 1987 and signed by Jack Friese, Arms Corporation of America, Inc. requested delivery of 1,000 semi-automatic M14 type receivers from Karl Maunz.

Maunz Manufacturing, Inc. – Karl Maunz established Maunz Manufacturing, Inc. in 1977 while he lived in Cincinnati, OH. Maunz Manufacturing first used Springfield Armory, Inc. (Valley Ordnance Co. manufactured) M1A receivers to build complete M14 type rifles. Very quickly though, under the license and supervision of Karl Maunz, his associates cast, machined and stamped Maunz Mfg. receivers. The Maunz Mfg. receivers were cast at Rimer Casting Company. Rimer Casting Company was located on Rimer Road in Waterville, OH from 1970 until June 1997. The owner, Richard Rimer, sold the business and retired in June 1997.

Most of the Maunz named M14 type rifles were stamped Maunz Mfg. The Maunz Mfg. rifles were built between 1976 and 1978 and from 1983 to 1984. From 1983 to 1987, Karl Maunz had M14 parts shipped to and rifles assembled and tested at 3230 Strayer Road Maumee, OH 43537. Maunz Mfg. M14 type rifles were all built with USGI M1 and M14 and National Match grade parts. A very few Maunz Mfg. rifles were experimental models. These rifles have a serial number preceded by EX-. One of the EX- series rifles has been observed without the scope mount hole. Some Maunz Mfg. and Maunz Match Rifle receivers were stamped TOLEDO, OHIO on the scope mount (left) side. Karl Maunz only sold Maunz Mfg. rifles to corporations. Maunz Manufacturing ceased operations in 1987.

Maunz Match Rifle - The Maunz Match Rifle receivers were cast at Funkfein Casting (Columbus, OH). The Maunz Match Rifle receivers were machined by Smith Manufacturing Co. per an agreement with Karl Maunz. Maunz Match Rifle models were all built with USGI and National Match grade parts. The match grade barrels were obtained from Karl Walther, Boots J. Obermeyer, and John Krieger and barrel blanks from Bob Hart. Obermeyer barrels were only used on a few Maunz Match Rifle models though. The original stocks on these rifles have a Maunz Match Rifles badge embedded

in the stock. This 1 ½ " x 2 " badge includes an eagle, crossed Union and Confederate flags and the words In God We Trust against a white color background. All Maunz Match Rifle models were sold originally as complete rifles by Smith Manufacturing Co. and not by Karl Maunz. One Maunz Match Rifle was marked B.P.DOW 0001 in two lines on the receiver heel.

Mr. Maunz only built Maunz Match Rifle models for match shooters who had earned an NRA Master or higher classification. Mr. Maunz built his last Maunz Match Rifle Model 77 for a Master shooter in 1987. One such competitor was the late retired USMC Chief Warrant Officer 4 David I. "D.I." Boyd, II. CWO4 Boyd was the finest American competition shooter ever. He won several team and individual gold medals in various World Championships, Championships of the Americas matches and Pan American Games from 1963 to 1977. He earned at least four National Championship titles from 1972 to 1981 and was the USMC Rifle Champion in 1975. CWO4 Boyd was featured on the October 1981 issue front cover of *American Rifleman*, the year he won the National High Power Rifle Championship. He was a Triple Distinguished Shooter by earning the United States Distinguished International Shooter Badge, the USMC Distinguished Rifleman Badge, and the USMC Distinguished Pistol Shot Badge. CWO4 Boyd's Maunz Match Rifle serial number was USMC 1. CWO4 Boyd retired from the U. S. Marine Corps in 1998 and passed away in May 2000.

All Maunz Mfg. and Maunz Match Rifle receivers were examined by X-ray and then by magnetic particle inspection before phosphate coating. These receivers were machined by Bill Lowry. The receivers were stamped with a number in the rear sight pocket as part of the quality control program. Maunz Match Rifle serial numbers 0002 and 0041 are stamped on the receiver heel from top to bottom: first line – MAUNZ second line – MATCH RIFLE third line - MODEL 77 fourth line – 00XX.

The Maunz Match Rifle Model 77 was designed in 1977 by Karl Maunz but not produced until 1985. It was available from 1985 to 1987 in 7.62 x 51 mm / .308 Winchester with either 22 " long medium weight or heavyweight match barrels. The synthetic stock was a satin black color finish. The Model 77 rifle was supplied with a removable globe style front sight that could be swapped out with the National Match 0.062 " front sight on the USGI flash suppressor. The rear sight was the National Match hooded aperture model. Fifty of the Maunz Match Rifles were produced in 1985 with ASU series serial numbers. Thirty of these rifles had the 1977 Maunz design satin black color fiberglass stocks. The remaining twenty rifles were fitted with the 1985 Maunz design red, white and blue wood laminate stocks.

The Maunz Match Rifle Model 87 was designed in 1987 by Mr. Maunz. It housed all of the gas system, including the gas cylinder, inside an oversized synthetic satin black color stock and had a 26 " medium weight barrel and a globe type front sight. The stock was available in either left-handed or right-handed models. The rear sight was the National Match hooded aperture model. The Maunz Match Rifle Model 87 was available from

1987 to 1989 in several calibers.

Mr. Maunz did not favor welding a lug onto the M14 type receiver. Instead, he designed and marketed a bolt-on front receiver lug for the M14 type rifle. The Accuracy Lug attached to the receiver using a pin inserted through the connector lock holes and secured by a screw through the bottom of the stock. The Accuracy Lug was manufactured at Rimer Casting Company for Karl Maunz. It was part of the Model 77 build configuration. In 1986, it was available at Uncle Sam's and through Arms Corporation of America, Inc. Mr. Maunz designed a rear receiver lug in a December 18, 1984 drawing he made. A steel prototype was made and Rimer Casting Company was going to produce it but the project never moved forward.

H & R Gun Co. and Smith Ltd.

Mr. Maunz sold his M14 rifle business to Smith Manufacturing Co. (then P. O. Box 1070 Toledo, OH 43697) about 1984. The semi-automatic M14 receiver master die was loaned to them as part of the sale. Smith Manufacturing Co. produced complete rifles built on investment cast H&R Gun Co. stamped receivers. The H&R Gun Co. Semi-Auto 7.62MM-M14 receivers were marked TOLEDO, OHIO though Smith Manufacturing Co. was physically located in Holland, OH about fourteen miles to the west. H&R Gun Co. Semi-Auto 7.62MM-M14 rifles were assembled with Harrington & Richardson M14 parts kits imported in 1985 by Jack Friese. All H&R Gun Co. models were originally sold as complete rifles by Smith Manufacturing Co. Smith Manufacturing Co. was operated by Carl Hinkelman, Ron Smith (TN), and Doug Smith (Bowling Green, OH), neither related to Ron Smith of Smith Enterprise, Inc. in Arizona. As an aside, Carl Hinkelman lived in Toledo, OH within blocks of the Schuster family at the time. Karl Maunz was a consultant to Smith Manufacturing Co. on the H&R Gun Co. project.

Smith Manufacturing Co. machined the first Armscorp of America receivers around 1985 or 1986. Armscorp serial number 1120 is marked SMITH MFG. INC. TOLEDO, OHIO on the left side of the receiver directly under the elevation knob and to the rear of the bolt lock. A number of the early Armscorp receivers had rear lugs made as part of the casting. The very first Armscorp of America M14 receiver was hand delivered to Mike Gruber by Karl Maunz. Smith Manufacturing Co. marked a few Armscorp of America receiver heels by electro-discharge machining (EDM) instead of using stamping dies as an experiment.

Smith Manufacturing Co. also produced Smith Ltd. investment cast semi-automatic M14 type receivers. Smith Ltd. receivers were made about 1987. Like Maunz Mfg., a very few Smith Ltd. rifles were experimental models. An example is Smith Ltd. M-14 serial number EX-5 which has a front lug and no rear lug. These rifles have a serial number preceded by EX-.

Smith Ltd. receivers were assembled as complete rifles and sold about 1987 and 1988 at Camp Perry shooting matches by Smith Manufacturing Co. Ron Smith, one of the

principals of Smith Manufacturing Co., assembled the Smith Ltd. rifles at the family gun shop, Georgia Gun Trader, Inc. (then 605 West Nashville Street Ringgold, GA 30736). Ron Smith was a competitive shooter at Camp Perry in the 1980s. He learned how to build M14 type rifles through a couple of retired military armorers who lived in northern Georgia as well as from armorers and competitors he met at Camp Perry. The parts fit, if using USGI and/or National Match parts, is excellent, based on examination of Smith Ltd. rifles serial numbered 0210, 0225, 0236 and 0237. A commercial manufacture bolt and commercial manufacture operating rod were found to be too thick to slide smoothly inside Smith Ltd. receiver serial number 0237.

The following report was given by M14 gunsmith Tim Strait on March 14, 2006 on Smith Ltd. receiver serial number 0003 [minor spelling and punctuation errors corrected]:

Smith Ltd M14 # 0003

Receiver specifications as follows:

1. Excellent cast receiver with virtually no machine marks visible. Excellent parkerized [phosphate coated] metal finish on the entire rifle. Surface hardening was checked at the rear sight base with results of 59 HRC according to a local metallurgist.
2. All parts on this rifle are TRW (barrel, operating rod, firing mechanism and bolt). All parts seem to fit well without any fitting at all. Barrel gauges at 0 for throat erosion and 0 for muzzle wear.
3. Receiver threads (barrel) are correct per M14 military specification (barrel timing or indexing).
4. The machine work done on the inside of the receiver is excellent and smooth. No burrs were found on this receiver.
5. The locking lug helix of this Smith Ltd receiver matches the helix of the USGI M14 bolt very well at approximately 99.9 %.
6. Firing pin retraction was well within standard for USGI military specification.
7. Headspace on this rifle was set at a modest 1.6325 ". This is good enough for commercial .308 Winchester or 7.62 NATO ammunition. The bolt lugs have about 99 % contact with the receiver locking lug engagement area.
8. The receiver heel is just a bit thicker than other commercial receivers being made today.

9. The front pin hole for the bolt stop roll pin is cut exactly the same as USGI M14 rifles.
10. The operating rod dismount notch is 1 ½ times the width of current commercial receivers.
11. The receiver safety bridge was milled correctly and there's no bolt shuck or interference with bolt rotation. The action functions smoothly and without a hitch.

Note

During the 1980s, there were four businesses or individuals with the name of Smith involved with commercial M14 rifles as manufacturers. Neal Smith of Smith Firearms (Mentor, OH) performed NFA registered select fire conversions of already-manufactured Springfield Armory, Inc. M1A rifles. Richard Smith and Ron Smith of Smith Enterprise, Inc. (then Mesa, AZ) produced semi-automatic and select fire M14 rifles stamped SMITH ENT. Melvin Smith of Valley Ordnance (Wilkes-Barre, PA) machined raw castings into M1A receivers for Springfield Armory, Inc. in Geneseo, IL. Smith Manufacturing Co. (Holland, OH) produced Maunz Match Rifle, H&R Gun Co. and Smith Ltd. semi-automatic M14 rifles and the first Armscorp of America M14 type receivers. Ron Smith of Tennessee was one of three stakeholders in Smith Manufacturing Co. He is of no relation to Ron Smith of Smith Enterprise, Inc. None of these entities ever did any work for the others. Although Arms Corporation of America, Inc. sold Smith Enterprise, Inc. M-14 receivers and Smith Manufacturing Co. made some Armscorp of America M14 receivers, there was never any connection or relationship between Smith Manufacturing Co. (Holland, OH) and Smith Enterprise, Inc. (then Mesa, AZ). Additionally, Frank Smith was the All National Guard MTU armorer in the 1980s and early 1990s. The similarity in names is purely coincidental.

A. R. Sales Co., National Ordnance, Inc. and Federal Ordnance, Inc.

In the 1960s, 1970s and 1980s, the Los Angeles area was the firearms manufacturing capitol of the western United States. Three southern California firms from that period were connected to the commercial M14 rifle, A. R. Sales Co., National Ordnance, Inc. and Federal Ordnance, Inc.

A. R. Sales Co. was established at 9624 Alpaca Street South El Monte, CA in 1968 by Ilia I. Karnes. Jack Karnes, his wife Ilia, and their two children ran the company. Mr. Karnes was a tool and die maker by trade. When the family business started, its first large contract was to make M16 scope mounts. The two letters, A.R., were taken from the first two alphanumeric characters of the commercial name for the M16 rifle. Next, A. R. Sales produced high-end lightweight alloy M1911 style pistol frames and accessories.

Ilia Karnes sent a couple prototype Mark IV receivers to the BATF for approval. These prototype receivers were not approved as they included the operating rod rail dismount

notch and forward underside groove. After several months, the BATF approved the third prototype receiver from A. R. Sales. The third prototype receiver lacked select fire machining cuts. A. R. Sales Co. started on its semi-automatic M14 type rifle project by October 1971. An advertisement for its Mark IV rifle appeared in the October 15, 1971 issue of *Shotgun News*. The response from the civilian market was overwhelming. This included 2000 or more mail-in orders with the \$15.00 deposit for a stripped Mark IV receiver.

A. R. Sales received its initial batch of Mark IV receiver castings by no later than March 07, 1972. This first set of receivers were used by Jack Karnes to set up fixtures and tooling for the machine tools. There were two Mark IV receiver production lots for the company. The first occurred in the winter of 1973. The first Mark IV rifles and stripped receivers were delivered to customers in January 1973. Mark IV serial number 0143 had been delivered to the buyer on March 02, 1973. The first production lot of Mark IV receivers was cast at Rimer Casting Company (Waterville, OH) using Karl Maunz's receiver master die according to two sources and at Prico (Los Angeles, CA) according to a third source, all highly reputable. The first production lot of Mark IV receivers was machined by A. R. Sales. The first lot of receiver serial numbers ended at a number less than 0226 with 200 receivers produced.

The second receiver production lot was made in 1976. The receiver serial numbers for the second lot were started at a number below 0226 and ended at number 0250. The second production batch of Mark IV receivers was cast at Gray-Syracuse, Inc. and machined by Valley Ordnance Co. About twenty-five receivers were produced in the second batch.

Twenty-five serial numbers were skipped between the first lot and the second lot. The missing serial numbers were allotted for tool room samples and for intended-but-never-realized forged receivers. Both production lots of Mark IV receivers were heat treated by a local company in southern California.

A. R. Sales Co. at first bought M14 parts brand new directly from USGI contractors. Mark IV rifles were assembled with new and used USGI M14 parts and wood stocks. As an example, serial number 0037 was assembled with a USGI birch stock, March 1967 Canadian Arsenal's NM barrel, TRW bolt, TRW trigger housing, Saco-Lowell operating rod, and NM sights. Any used M14 parts that were broken or worn were compared to the USGI drawings and rejected in the build procedure. The stock selector cutout was filled in for each assembled Mark IV rifle. According to the October 1971 A. R. Sales Co. specification sheet for the Mark IV rifle, "While most of our rifles will be built with N.M. barrels, we do not glass bed the actions, nor do we produce match grade weapons. We feel that this is best left to those who specialize in accurizing and building match grade weapons, and we do not wish to infringe in their domain."

Ford Motor Company was formed on June 16, 1903 by Henry Ford and eleven other business associates. In 1925, Ford Motor Company bought Lincoln Motor Company, a manufacturer of luxury automobiles. For the 1972 model year, Lincoln introduced the Mark IV two-door luxury sport coupe. The Mark IV was longer, wider and slightly lighter than its very popular predecessor; the Lee Iacocca designed Lincoln Mark III. The 1972 Mark IV was Ford's answer to General Motors Corporation's Cadillac Eldorado and was a major success for Ford Motor Company. Lincoln Mark IV automobile production ended with the 1976 model year. Mr. Maunz was impressed with the plush style of the 1972 Lincoln Mark IV. Thus, he suggested to A. R. Sales that its semi-automatic M14 receiver be named Mark IV. A. R. Sales Mark IV receivers are of good quality.

Iliia Karnes sold the manufacturing side of A. R. Sales to Ranger Machine & Tool Corporation in November 1979. Ranger Machine & Tool continued to produce the pistol frames and accessories but did not produce any M14 receivers or rifles. Ranger Machine & Tool Corporation was purchased by Federal Ordnance, Inc. in May 1981. It occupied 9624 Alpaca Street from 1981 until 1984 when it merged with Federal Ordnance at 1443 Potrero Avenue. A. R. Sales moved in 1981 from 9624 Alpaca Street to 1900 Tyler Street in South El Monte. The retail business of A. R. Sales was shut down in 1984 by Iliia Karnes.

Golden State Arms (Pasadena, CA) was established in 1952 by Alvin Gettler. From 1960 onward, the firm was owned by Seymour Ziebert. It was a major importer of surplus firearms and ammunition. Golden State Arms went out of business in late 1966 along with two other related businesses, Pasadena Gun Shop and Pasadena Firearms, Inc. Jack Karnes, Burton "Bob" Brenner and Robert E. Penney were all former associates of Golden State Arms.

Bob Penney and John Arnold co-founded National Ordnance, Inc. and Alpine Sales in May 1960. National Ordnance manufactured M1 Carbine receivers and assembled carbines using surplus USGI parts. In 1962, this work was done at 235 S. Irwindale Avenue Azusa, CA. Alpine Sales was the sales half of the joint venture. In December 1962, the two gentlemen went their separate ways. Mr. Penney was left with Alpine Sales for the purpose of selling commercial M1 Carbines. He wanted to manufacture a commercial M14 receiver but in the early to mid-1960s there were no USGI M14 parts available in the surplus market. Mr. Arnold took over National Ordnance to concentrate on manufacturing M1903 and M1 Garand rifles. During their respective histories, Golden State Arms, National Ordnance and Federal Ordnance built semi-automatic BM59 rifles by welding together cut up BM59 receivers.

National Ordnance moved from Azusa, CA into the newly constructed building at 9643 Alpaca Street South El Monte, CA in 1965. From 1965 to 1970, National Ordnance produced 22,500 newly manufactured M1903A3 receivers and assembled them into complete rifles using USGI surplus parts. National Ordnance also manufactured 2000 M1 Garand welded and investment cast receivers. In the early 1960s, the firm

manufactured an unknown number of M1 Carbine investment cast receivers for Alpine Sales. The newly manufactured M1 Carbine and M1 Garand receivers were cast by Rimer Casting Company. In the early 1970s, when A. R. Sales was developing its Mark IV receiver, John Arnold was pursuing the same goal of manufacturing and marketing his own semi-automatic M14 type receiver.

By 1973, John Arnold, a U. S. Navy World War II veteran, owned or partially owned at least three companies: National Ordnance, Inc., a firearm manufacturing company, Sporting Arms, Inc., a distributor of sporterized military rifles, and Cadmus Industries. The three companies were located on the same block of Alpaca Street. Mr. Wyant J. Lamont, Jr., managed the day-to-day operations of National Ordnance in the early 1970s.

Employees from both A. R. Sales and National Ordnance visited the facilities of one another to discuss set up of machine tools. A. R. Sales did assist National Ordnance in its BM59 project but there was no collaboration between the two firms specific to M14 type receivers. A very small number of National Ordnance stamped semi-automatic M14 type rifles were produced. Stephen Fuller reported two completed receivers for the company but a reliable source closer to the events of the time estimates a half-dozen National Ordnance receivers were finished. Electro Crisol Metal, S.A. (Santander, Cantabria, Spain) made the raw receiver castings for National Ordnance.

Mr. Arnold passed away from cancer on December 23, 1973. Walter Rayno, head foreman, and Jessica LaMont, wife of Wyant LaMont, were left to run the company. Shortly thereafter, National Ordnance was purchased by Bob Brenner. Mr. Rayno passed away suddenly on June 05, 1975 while enjoying the horse races at Santa Anita. Operations were moved to 9649 Alpaca Street in 1976 and appear to have ceased in South El Monte the following year. As part of the liquidation of the company's assets, assembled M14 type rifles and parts kits were sold off. The tooling and molds for the M1 Carbine receivers were sold to Rock Island Armory.

As soon as Golden State Arms had closed down and its assets auctioned off, Bob Brenner went into business for himself on November 16, 1966 as Federal Ordnance, Inc. Initially, he worked out of his home in Pasadena, CA. The company imported ammunition and U. S. and foreign made rifles and hand guns. By the late 1960s, Mr. Brenner's business was doing well and he became very good friends with John Arnold. Federal Ordnance moved in with National Ordnance at 9643 Alpaca Street. Federal Ordnance collaborated with National Ordnance to produce M1903 and M1 Carbines with commercial receivers and surplus USGI parts for sale to the public. In 1969, Federal Ordnance had outgrown its leased space and moved to the adjacent building, 9649 Alpaca Street South El Monte, CA.

In 1981, the business was moved due to further business growth from 9649 Alpaca Street to 1443 Potrero Avenue South El Monte, CA 91733. By no later than 1982, Jack Karnes went to work for Bob Brenner at Federal Ordnance as the chief machinist. He was

employed by Federal Ordnance until 1984. Mr. Karnes then did consulting work for the company until 1985 or 1986. Robert Thomasser joined Federal Ordnance, Inc. in 1982 as a machinist. Later, he was promoted to Vice President. As Vice President, Mr. Thomasser managed the machine shop employees producing the Ranger M1911 style pistol and the Federal Ordnance M14 rifle. Other Federal Ordnance employees included Linda Thomasser and Bob Brenner's wife, Barbara, and son-in-law, Robert Siegal.

In early 1982, Federal Ordnance was finishing up its production of newly made M1 Garand and M1 Carbine receivers. Federal Ordnance, Inc. also manufactured the Model 713 Deluxe Mauser rifle (1986 - 1992) and the All American Sporter Bolt Action rifle (1991 - 1992). Federal Ordnance reached its peak of manufacturing activity around 1985 with about 120 employees. In the late 1980s at least, Federal Ordnance, Inc. supplied a list of firearms manufacturers and importers addresses with its factory literature and a note encouraging customers to contact the manufacturer or importer to get an owner's manual. Federal Ordnance sold lightweight alloy M1911 style pistol frames marketed under its name and a trade name as well as selling a Springfield Armory, Inc. high-end M1911 style pistol.

Federal Ordnance began production of its M14 type rifles by 1984 and ended in late 1991. Federal Ordnance was not able to compete with the price of imported Chinese M14 rifles so production was halted. After the first fifty, M14 receivers were machined on one CNC machining center with several fixture set ups. All receivers were machined from castings of AISI 8620 alloy steel. Except for the first fifty receivers, the castings were supplied by Electro Crisol Metal, S.A. The M14 receivers were manufactured at a leased building one block up on Potrero Avenue. Heat treating was subcontracted to a vendor in El Monte, CA. Federal Ordnance M14 type receivers were heat treated and carburized according to USGI drawing F7790189. A company in Santa Ana, CA finished the receivers with a phosphate coating. Assembly of the Federal Ordnance M14 rifles was performed at a leased warehouse just west of 1443 Potrero Avenue. Each M14 was proof fired before assembly and function tested with three rounds as a complete rifle before packaging. Finished M14 rifles were stored on the first floor at 1443 Potrero Avenue. The total number of complete M14 rifles assembled by Federal Ordnance was more than 13,000. Based on information available, total M14 receiver production did not exceed 16,000.

The Manufacturer's Suggested Retail Price for a Federal Ordnance M14A in 1988 was \$629.00 and its M14SA listed for \$700.00 in 1991. The rifles were sold with a one year parts and labor warranty. Each Federal Ordnance M14 type rifle sold was accompanied by a factory inspection tag, warranty registration card, a copy of U. S. Army FM 23-8 and a fourteen page booklet on firearms safety and care. The safety booklet was written by Federal Ordnance, Inc. in 1984. The factory inspection tag included the following information about each rifle: date, stock number, a description, caliber, and signature fields for checking of headspace, test firing and inspection. USGI M14 accessories such as magazines, magazine pouches, slings and cleaning kits were available from Federal

Ordnance.

Federal Ordnance built two types of M14 rifles, one with USGI parts and one with Chinese parts. Model numbers M14 and M14A were designed to accept USGI bolts and barrels. Otherwise, the receiver was manufactured to mate with Chinese bolts and barrels. USGI parts were used extensively in Federal Ordnance rifles through at least serial number 8877. The USGI parts were taken off USGI M14 rifles imported from Israel. By serial number 9279, if not earlier, Chinese and Taiwanese reproduction parts were used to assemble its rifles. For example, Federal Ordnance M14SA serial number 502XX was assembled at the factory on September 13, 1991 with Chinese manufacture bolt, operating rod, firing mechanism and barrel. Chinese and Taiwanese M14 parts were purchased from U. S. importers. Receivers with serial numbers above 60XXX have engraved heel markings. The model number changed from M14A to M14SA between serial numbers 9139 and 9279. Four digit serial number Federal Ordnance receivers observed were marked on the side with the letter F inside a circle. This marking was sometimes lightly stamped. The circle F marking has not been observed on serial numbers above 10000. Federal Ordnance sold complete rifles as well as stripped receivers. Federal Ordnance sold a few M14 rifles to walk-in retail customers and through *Shotgun News* advertisements but most were sold to firearms distributors.

Some fiberglass stocks on Federal Ordnance M14 rifles appear to have been commercial manufacture of unknown origin. The original owner of Federal Ordnance M14SA serial number 22XX reported that the synthetic stock never had a selector cutout or USGI markings inside the magazine well. Further, the Federal Ordnance stock had a slightly rough finish. The butt plate was glossy black color instead of phosphate coated. Federal Ordnance M14 rifles were also sold with refinished wood, new walnut and USGI synthetic stocks. Federal Ordnance M14 related stock numbers were as follows:

GU-0560 Federal Ordnance M14 receiver
 GU-0706 M14 with Viet Nam camouflage fiberglass stock
 GU-0707 M14 with woodland camouflage fiberglass stock
 GU-0708 M14 with desert camouflage fiberglass stock
 GU-0709 M14 with USGI walnut stock with selector cutout filled in
 GU-0710 M14 parts kit with minor, Federal Ordnance receiver and fiberglass stock
 GU-0711 M14 parts kit in refinished condition, Federal Ordnance receiver and fiberglass stock
 GU-0712 M14 parts kit in refinished condition, Federal Ordnance receiver and desert camouflage fiberglass stock
 GU-0713 M14 parts kit in refinished condition, Federal Ordnance receiver and Viet Nam camouflage fiberglass stock
 GU-0714 M14 parts kit in refinished condition, Federal Ordnance receiver and woodland camouflage fiberglass stock
 GU-0715 M14 with fiberglass stock
 GU-0920 M14 with USGI fiberglass stock and rubber butt pad

M14 RIFLE HISTORY AND DEVELOPMENT

SE-0221 M14 parts kit with minor wear and USGI walnut stock
SE-0222 M14 parts kit in refinished condition and USGI walnut stock
SE-0223 M14 parts kit in refinished condition and USGI fiberglass stock
SE-0224 M14 parts kit with minor wear and USGI fiberglass stock
SE-0225 M14 parts kit in refinished condition and woodland camouflage fiberglass stock
SE-0226 M14 parts kit in refinished condition and desert camouflage fiberglass stock
SE-0227 M14 parts kit in refinished condition and Viet Nam camouflage fiberglass stock

Century Arms International assembled a relatively small number of rifles using Federal Ordnance receivers and Chinese parts. This work was done at their facility in Montreal, Quebec, Canada in 1990 just before the imported parts ban of November 29, 1990. The rifles were brought into the United States with the military style features (twenty round magazine, bayonet lug, flash suppressor, and hinged butt plate) which was legal at the time and sold to the commercial market. These particular Federal Ordnance M14SA or M14S receivers have serial numbers with the letter C prefix followed by a hyphen then four digits, e.g., C-0116. The Federal Ordnance marking may be located on the outboard side of the right receiver leg. If so, it will be stamped: top line - Fed Ord Inc. bottom line - So El Monte. CA USA. The receiver heel for the serial number C-1301 was marked as follows: top line - U.S. RIFLE second line - 7.62MM M14S third line - CENTURY ARMS INC fourth line - ST. ALBANS. VT. fifth line - C-1301. The model number changed from M14SA to M14S between serial numbers C-0377 and C-0694. Century Arms International ceased operations in Montreal around 1993.

Federal Ordnance, Inc. produced 500 Vietnam Commemorative M14 rifles for the American Historical Foundation. They were made to similar finish specifications as the Springfield Armory, Inc. VME series rifles but with three noticeable differences. The Federal Ordnance VCE series M14 had a black color textured surface wood stock. The Federal Ordnance VME series rifles had the same traditional finish walnut stock as the Springfield Armory, Inc. VME series commemorative. On the Federal Ordnance rifles, the prefix changed at a point between serial number VCE 118 and VME 156. All 500 rifles had a black textured hand guard. Lastly, the receiver heels were stamped appropriately to the manufacturer. Federal Ordnance subcontracted the blueing, polishing, engraving and gold plating for the VCE and VME series rifle parts. The VCE series stock was supplied through another vendor to the American Historical Foundation.

A separate venture, Briklee Trading Company was established on April 20, 1992 by Bob Brenner. It was headed by Richard Siegal. Briklee Trading bought the assets of Federal Ordnance in late 1992. Federal Ordnance, Inc. ceased to exist as a California corporation on July 09, 1993. Briklee Trading imported firearms until the 1998 import ban. Mr. Brenner then started Pacific Ordnance (Pico Rivera, CA), an import business specializing in reproduction military holsters and related accessories. Pacific Ordnance was incorporated in November 1998 with Robert and Linda Thomasser on board to help run the company. Mr. Brenner retired in early 2002. As a result, the Thomassers formed Pacific Canvas & Leather Company (Phelan, CA) in February 2002. Bob Brenner passed

away on August 09, 2009 after suffering from a long term illness.

As an aside, Jack Karnes manufactured some 81 mm mortar round fin assemblies in 2002 for the Paramount Studios movie *We Were Soldiers*. These rugged fin assemblies were made to withstand the pressure generated by the mortar ignition charges which were designed to create 18 " flames out of the mortar tube. His son was one of the armorers assigned to the movie production unit. Regretfully, Mr. Karnes passed away on May 27, 2008.

Armscorp

Arms Corporation of America, Inc. was formed on January 27, 1984 by Jack H. Friese. It built accurized M14 type rifles for competition shooters. In 1985, the company was located at 9162 Brookville Road Silver Spring, MD 20910. Mike Gruber and Clint McKee, who would later go on to establish Fulton Armory, also worked at Arms Corporation of America, Inc. at this time. The company moved to 4424 John Avenue Baltimore, MD 21227 at some point between September 1987 and June 1989. Later, the other owner of Arms Corporation of America, Inc. sold out his interest to Jack Friese. The company ceased to exist legally on October 03, 1991. Mr. Friese reorganized the firm on February 07, 1992 as Armscorp USA, Inc. In late 2007, Mr. Friese sold the business to Mark Hartman, owner of James River Manufacturing (then 1512 Jabez Run Millersville, MD 21108) and former U. S. Marine and Master Class competitor with the M14. James River Manufacturing produced Armscorp logo M14 receivers from January until March 2008.

Smith Enterprise, Inc. sold some billet machined receivers to Arms Corporation of America, Inc. in 1986 but none were stamped with its brand name, Armscorp of America. They were Smith Enterprise stamped receivers and advertised as such. A complete service grade rifle with a Smith Enterprise receiver, all USGI parts and a used USGI stock was advertised by Arms Corporation of America, Inc. initially in *Shotgun News* for \$539.95. The Arms Corporation of America, Inc. advertisement listed the bare Smith Enterprise M-14 receiver for sale at \$199.95 and complete USGI parts kits without the receiver for \$239.95. A TRW M14 parts kit was an additional \$10.00. The customer demand for the bare receivers and assembled rifles was so great in 1986 that it took the firm until early 1988 to fill the backlog of orders even with a price increase. The June 1986 *Soldier of Fortune* review of the Armscorp of America M14 listed the retail price for the Armscorp of America M14 at \$674.95 with a used USGI stock. In the summer of 1986, the Armscorp M14 was available with a used USGI wood or fiberglass stock or a new commercial manufacture walnut stock. Each complete rifle was test fired and shipped with a sling and twenty round magazine.

Arms Corporation of America, Inc. was machining investment cast receivers at some point by the summer of 1987 using castings supplied to them by Smith Manufacturing Co. (Holland, OH) through Karl Maunz. As of September 18, 1987, Arms Corporation of America, Inc. had completed the machining of the first five lots of receiver castings using

its own personnel and CNC machine tools. Arms Corporation of America, Inc. receiver heat treatment was performed according to the USGI procedure and certified by the vendor. Smith Enterprise, Inc. sold some casting equipment and tooling to Arms Corporation of America, Inc. about 1988. From that point, Arms Corporation of America, Inc. made its own receiver castings for several years. In the waning years, Lamothermic Corporation (Brewster, NY) supplied the receiver castings to Armscorp USA and James River Manufacturing.

Arms Corporation of America, Inc. and Armscorp USA marketed several versions of semi-automatic M14 rifle through the years:

M14 - Service grade rifle assembled in 1991 and 1992 only with Chinese parts

M14 R - Service grade rifle assembled with USGI parts and USGI synthetic stock. This model was available from 1986 to 2006.

M14 RNS - Service grade rifle assembled with USGI parts and National Match walnut stock.

M14 RNSB - Service grade rifle assembled with USGI parts and USGI birch stock.

M14 Beginning National Match - Match grade rifle assembled with hand fitted USGI parts and USGI National Match barrel from 1993 to 1996.

M14 NMR - Match grade rifle built to the USAMTU specifications with National Match sights and a choice of standard, medium weight or heavyweight barrels. This model was available from 1987 to 2006.

M21 - Match grade rifle with a rear lugged receiver and choice of McMillan fiberglass stock or a wood laminate stock. Rear lugged match grade rifles were available from Armscorp from 1986 to 2006.

Armscorp of America receiver serial number A00326X has been identified as billet machined. However, most Armscorp brand receivers were machined from investment castings, e.g., serial number A0039XX. Armscorp USA, Inc. (later JRM / Armscorp) manufactured standard, rear lug and double lugged receivers. It was the first commercial manufacturer to sell factory new lugged receivers. From the start in February 2003 until May 2007, Armscorp USA made the castings and machined them into finished receivers for Fulton Armory according to its specifications. The firm poured castings and machined them into finished receivers for West Texas Armory. The West Texas Armory receiver serial numbers begin with the letters WTA. The first thirteen WTA prefix serial number M14 NM receivers were manufactured in July 2006. Dan O'Neal of West Texas Armory (Lubbock, TX) went into business as a Federal Firearms Licensee in April 2006.

Armscorp specified receiver surface hardness at 56 to 58 HRC with a case depth of 0.012 " to 0.018 " per the USGI drawing. While it was in business, Armscorp provided M14 gunsmithing services such as rifle assembly, barrel installation, stock bedding, National Match trigger and flash suppressor modification, and clean and lube. Note that the large majority of Armscorp brand M14 type receivers have been sold by the manufacturer as stripped units. However, Armscorp did supply match grade rifles upon request. From

1984 to 1986, Bruce Dow built an average of four match grade rifles per month with Armscorp receivers for Armscorp to fill customer orders. In the 1980s, Arms Corporation of America, Inc. manufactured and marketed a National Match operating rod spring guide. It was made of stainless steel and had a collar at the magazine catch for the end of the operating rod spring to rest against. For awhile some time after 1987, Arms Corporation of America, Inc. also machined M14 barrels in-house from blanks. In mid-2006, Armscorp USA was investigating the possibility of manufacturing four forged M14 parts including the bolt. At least one prototype M14 bolt was made. Unfortunately, this did not come to fruition.

Receiver Markings - Some of the Armscorp receivers were stamped M21 or XM25 instead of M14 NM or M14 to allow for sale in New Jersey, USA. The State of New Jersey, curiously, has banned new sales of some firearms by name rather than by operating characteristics or features. The markings 7790189 or 7790189 F have been observed on Armscorp receivers under the stock line on the right hand side.

Dupage Trading Company (Chandler, AZ) sold in 2003 a very small number of semi-automatic T44 rifles. These rifles were assembled with Armscorp USA receivers marked T44, T44E4 stocks, and surplus USGI M14 parts. A production run of Armscorp USA receivers was produced for the M-14 Firing Line online discussion board in 2007. The serial numbers assigned to this series were TFL001 through TFL250. The TFL series receivers are stamped with the M-14 Firing Line logo on the receiver heel. The serial number is stamped below the logo. Above the logo, the receiver is stamped: top line - U.S. RIFLE second line - 7.62 MM M14 NM. When James River Manufacturing became the owner of Armscorp in January 2008 there were about eighty serial numbers still left in this series to be assigned to receivers.

Armscorp USA receivers with The Firing Line serial numbers (TFL prefix followed by three digits) were made in 2007. James River Manufacturing managed the project of producing the last Armscorp marked receivers from January 01, 2008 until March 11, 2008. This included the last few TFL series receivers. The following is a partial list of TFL series receiver serial numbers that were delivered to the buyers: 001 through 081, 084, 085, 088, 089, 095, 097, 099 through 101, 105, 111, 113, 120 through 123, 130, 137, 158, 164, 171, 172, 176, 177, 193, 194, 222, 225, 226, 230, and 236.

Stampings on Armscorp receiver operating rod rails varied over its production history. There appears to have been seven operating rod rail markings:

- 1) By no later than serial number A1000 to at least serial number A003XXX, the Armscorp receivers were stamped SILVER SPRING MD on the vertical surface of the operating rod rail.
- 2) The operating rod rail stamping changed to ARMSCORP OF AMERICA SILVER SPRING MD by serial number A0035XX.

3) The third operating rod rail stamping was ARMSCORP OF AMERICA BALTIMORE MARYLAND. This information was stamped on a receiver with a serial number as low as A003940.

4) By serial number A006037, the stamping had changed to ARMSCORP OF AMERICA BALTIMORE, MD. The city and state lettering was about half the height of the company name lettering.

5) Next came the operating rod rail marking ARMSCORP USA BALTIMORE MARYLAND by no later than receiver serial number 10451.

6) The sixth operating rod rail marking was ARMSCORP USA. BALTIMORE MD. It appeared by no later than receiver serial number 1119X.

7) The next marking was ARMSCORP BALTIMORE MD as shown on receiver serial number 17371. This operating rod rail marking was also used on WTA prefix serial number receivers. By serial number 17494 the operating rod rail and under-the-stock markings were applied by electropencil.

8) Beginning at receiver serial number 17605, the operating rod rail marking was changed to JRM / ARMSCORP BALTIMORE MD. This reflected the change in ownership of the Armscorp name.

Armscorp did issue custom receiver serial numbers. For example, Bruce Dow had six custom serial number Armscorp of America receivers made: BR DOW 001, MS DOW 001, SB DOW 001, JB DOW 001, NL DOW 001, and RB DOW 001. At least one Armscorp custom receiver serial number was preceded by the letter A. Armscorp of America M14 type receivers were given the letter A prefix about the same time (no later than February 1988) the CNC machine tool programming was changed for cutting the receiver bolt lug recesses. The serial number prefix S indicates the receiver was made of stainless steel instead of AISI 8620 alloy steel. At least twenty stainless steel receivers were produced by Arms Corporation of America, Inc. about 1988.

Fulton Armory

Fulton Armory was established by Clint McKee in 1987 in Fulton, MD. The business was moved to its present location in Savage, MD several years later. Before starting Fulton Armory, Clint McKee worked with Jack Friese at what was then Arms Corporation of America, Inc.

Charles W. Maloney, former head armorer of the First U. S. Army Marksmanship Training Unit (Fort Meade, MD), was the chief gunsmith at Fulton Armory from about 1989 to 1997 when he retired. While working for the U. S. Army as a civilian armorer, Mr. Maloney provided instruction on M14 accurizing to 10th Special Forces Group sergeants Tom

Kapp and Bill Amelung. As previously discussed, Kapp and Amelung would go on to develop the XM25. Among several firearms gunsmithing courses successfully completed, Mr. Maloney was a double honor graduate of the U. S. Army National Match Pistol and Rifle Maintenance Course (Rock Island Arsenal, IL).

Beginning in 2003, Fulton Armory began selling rifles and barreled actions with its own receivers. Fulton Armory receiver serial numbers begin with the letters FA. Receivers FA 00101 through 00110 were manufactured in the winter of 2003. Fulton Armory XM25 serial number FA 00500 is a rear lugged model. Fulton Armory M14 type rifle FA 00550 was assembled in August 2005. Fulton Armory receivers were investment cast from AISI 8620 alloy steel and machined by Armscorp USA until May 2007. Armscorp made many changes to its tooling for production of Fulton Armory receivers. Armscorp also made significant improvements in receiver dimensional geometries as specifically requested by Fulton Armory. This included a wider than USGI specification operating rod rail. The Fulton Armory receiver was custom designed and uniquely manufactured. A sample Fulton Armory receiver heel was marked as follows from top to bottom: U. S. RIFLE 7.62 MM M14 FULTON ARMORY FA00106. The model number may be M14, M14 NM, M21 or XM25. The operating rod rail vertical surface was stamped SAVAGE, MD. Customers had a choice of standard or rear lugged receivers. Receiver production resumed in August 2009 with SSI Manufacturing Technologies Corporation (Bristol, CT) performing the machining work on castings supplied by Lamothermic Corporation. 2009 and later receiver heels were stamped with this format, U. S. RIFLE 7.62-MM M14 FULTON ARMORY F00000. The operating rod rail was again stamped SAVAGE, MD.

In 2006, Fulton Armory introduced its M14 Super Scout Rifle. This model was built using a Fulton Armory receiver, USGI M14 parts, a Super Scout rail hand guard, new manufacture military contour walnut stock, rubber recoil pad, and choice of non-plated or chromium plated 18.5 " or 22 " Fulton Armory barrel. The Super Scout rail hand guard was marked on the operating rod side: Super Scout Made in U.S.A. Fulton-Armory.com. The factory package included one ten round magazine, a rifle sling and owner's manual.

Options for the Fulton Armory M14 Super Scout Rifle included: 1) front sling swivel rail section 2) hand guard side rail 3) National Match trigger 4) National Match operating rod spring guide 5) Smith Enterprise, Inc. 7 " long steel M14 scope mount 6) Fulton Armory non-operable replica selector switch 7) muzzle brake for California compliant models. Each side rail was secured to the rail hand guard by two hex head screws.

Fulton Armory offers a host of M14 type rifle gunsmithing services. Its services include technical inspection, clean and lube, barrel installation and headspacing, phosphate coating of parts, firing mechanism tuning, complete rifle assembly, and match conditioning. Fulton Armory has installed USGI bolts and barrels on hundreds of Chinese M14 receivers. Thus, they offer conversion to USGI parts on Chinese M14 rifles as well.

Western Ordnance International Corporation/Smith Enterprise, Inc.

Western Ordnance International Corporation, which became Smith Enterprise, has designed and manufactured excellent quality firearm parts and built outstanding quality firearms for American and foreign governments and the civilian market. Its rifles and parts are too numerous to list in this work. For the sake of brevity, only its experience with the M14 type rifle will be discussed at length.

Ron Smith and Sonja Sommers own and operate Smith Enterprise, Inc. Smith Enterprise, Inc. is classified by the U. S. government as a veteran owned and operated contractor. Its CAGE Code is 3A5E1. Ron Smith served in the U. S. Marines and carried a Harrington & Richardson M14 rifle in the Republic of Viet Nam in 1968. He shot competitively for the Arizona Army National Guard and California Army National Guard and is a 1986 graduate of the Israeli Defense Force Sniper School. Ron Smith is a fourth generation career professional in the ordnance industry. He has been licensed as a Class 2 SOT/FFL since 1984. He apprenticed under his dad, Richard Smith, and was actively involved in all projects undertaken. This included, but was not limited to, research, development and production of its M14 receivers and the M14K, research and development of Poly Technologies M14 rifles, making parts for the M16 type rifle, and select fire conversions on Browning Hi-Power 9 mm pistols before the May 1986 ban. When Richard Smith retired in 1992, he passed the torch to his son, Ron. From no later than 1994 until at least 1997, the company was known as Smith Arms International. The firm relocated from 325 South Westwood # 1 Mesa, AZ 85210 to the present facility in Tempe, AZ between March 1994 and July 1996.

In 1995, Richard Smith went back to work at Western Ordnance working for his son, Ron Smith. Richard Smith's wife, Helen, was involved in aspects of M14 receiver and parts production at Smith Enterprise, Inc. through the years. Mrs. Smith did quality assurance checks on receivers, custom painted bedded stocks, and machined many M14 parts such as flash hiders, combination gas cylinder lock front sights, and operating rods. She was active in the family enterprise until about four months before her passing on May 13, 2011 in Carson City, NV.

In 1987, Creedmoor Armory (Oceanside, CA) was the first distributor of billet machined Smith Enterprise, Inc. M-14 receivers. Jim Hill purchased twenty Smith Enterprise, Inc. billet machined receivers. These receivers had serial numbers in the single and double digits. Creedmoor Armory was established in 1979 to make shooting jackets and firearms accessories available to the competitive shooter. The owner, James E. Hill, was a retired U. S. Marine, National Champion, 1960 Olympic Silver Medalist and Triple Distinguished Shooter. About 1990, Mr. Hill sold Creedmoor Armory to two gentlemen who renamed the business Creedmoor Sports, Inc. Mr. Hill moved to Illinois. He was the National Matches Highpower Match Director at Camp Perry from 1992 to 2007. In the 1980s, Smith Enterprise manufactured twenty to thirty M-14 NM rifles for Creedmoor Armory. The firm did all of the barrel machining as well on these rifles using Obermeyer,

Douglas and Krieger rifled barrel blanks. The receivers and barrels were cryogenically treated after machining and heat treatment. These rifles were assembled with bedded McMillan stocks finished with a spackled brown custom paint by Helen Smith at Smith Enterprise, Inc. Before shipment to Creedmoor Armory, each rifle was test fired at the Rio Salado Sportsman's Club (Mesa, AZ). Mo DeFina (Mo's Competitor Supply) also purchased twenty of the billet machined receivers with serial numbers below 00100.

Creedmoor Sports, Inc. moved in April 2013 from 1405 S. Coast Highway Oceanside, CA 92054 to 167 Creedmoor Way Anniston, AL 36205. Oceanside, CA was also home for many years to M14 competition shooter and gunsmith Art Luppino. Mr. Luppino served in the U. S. Marine Corps during the Korean War. He built many M14 rifles for competition shooting in his gunsmithing career including the U. S. Navy Rifle Team at Moffett Field (Mountain View, CA). In the early 1970s, he designed and made M14 rifle chamber and gas piston cleaning tools, a gas cylinder lock wrench and a muzzle crown guide. These tools were distributed through Creedmoor Sports. The alloy aluminum gas cylinder lock wrench was marked Creedmoor Sports Inc on each side. Mr. Luppino bought several of the billet machined Smith Enterprise, Inc. receivers with serial numbers under 00100. He built and sold them as match rifles to individuals.

In January and May 1983, Mr. Luppino rebuilt ten double lugged match conditioned Springfield Armory, Inc. M1A rifles for the U. S. Navy SEALs. The M1A rifles had been shipped from and were later returned to SEAL Team Six at Naval Amphibious Base, Little Creek (postal address is in Norfolk, VA). The invoice for this work was paid many months later by check drawn on the U. S. Treasury. This lot of M1A rifles had originally been lugged and match conditioned by another gunsmith. The Navy SEALs were not satisfied with the work done and the accuracy performance. Some of these rifles would not even function. Thus, Mr. Luppino was sent the rifles for rebuild. The serial numbers of the M1A rifles sent to Mr. Luppino were: 018736, 022066, 022074, 022079, 022114, 022131,

022852, 022853, 023219, and 023677. SEAL Team Six was created in October 1980 and was mission-capable by April 1981. It is responsible for counterterrorist operations conducted by the U. S. Navy. In 1987, SEAL Team Six was renamed to Naval Special Warfare Development Group.

Art Luppino was the armorer of instruction in both Lenny Magill Productions *Center X* video tapes on M14 rifle accuracy. The first video, made in 1992, covered cleaning and lubrication of the M14 type rifle. The second video was a tutorial on glass bedding of the M14. By the mid-1990s, Mr. Luppino had moved to Tucson, AZ where he continued to build accurized M14 type rifles. By 2006, he had moved to Texas and retired.

Without question, Smith Enterprise has much more knowledge of and experience with testing and working on Chinese M14 type rifles than anyone outside the People's Republic of China. Smith Enterprise is a Leupold & Stevens, Inc. optics factory authorized distributor to government and law enforcement agencies as well as a Sage

International M14 EBR stock authorized distributor. Among countless customer requests fulfilled, Ron Smith surveyed the Jordan government M14 rifle inventory at the request of King Abdullah II in 1999. In late 2004, the government of Jordan had requested further assistance from Ron Smith on its M14 rifle program.

Smith Enterprise, Inc. Receiver Design, Manufacture and Testing

All Smith Enterprise receivers have been manufactured from certified AISI 8620 alloy steel. About 1985, Smith Enterprise began producing M14 receivers after several months of planning and evaluation. This included creating its blueprints and engineering sketches. Receiver locking lug recesses were machined using a pair of dedicated Bridgeport milling machines. Smith Enterprise M14 receivers incorporated a number of innovative features that improve upon the USGI design. The receiver locking lugs were adjusted forward to reduce the headspace about 0.003 " to 0.005 ". The receiver bridge was adjusted a little aft (to the rear) to retract the firing pin faster in order to better prevent slam fire. The receiver barrel ring thread starting quadrant was changed to reduce barrel torque to about 50 ft-lbf which is sufficient. Typically, Smith Enterprise M14 rifles were headspaced at 1.633 ". Pre-'94 ban receiver production did not exceed fifty per month.

At least forty receivers under serial number 00100 were machined from billet but Smith Enterprise, Inc. made its first receivers by the precision investment casting method. The raw castings left a large amount of metal that had to be machined away to obtain the final form. All Smith Enterprise investment cast receivers have been made with virgin bar stock AISI 8620 alloy steel certified by the supplier and verified by Smith Enterprise. The cast receivers were stress relieved before machining. The Smith Enterprise "forged" billet machined receivers were made from fine grade Hart AISI 8620 alloy steel certified by the supplier and verified by Smith Enterprise. Manufacturing of receivers starting with billet allowed even more control over the receiver form. Billet was plasma cut into the starting shape.

All heat treatment of all Smith Enterprise receivers has been certified by the vendor and verified by Smith Enterprise. After heat treatment, the receivers were cryogenically treated. All of its receivers were examined by magnetic particle inspection and some were X-rayed. All receiver barrel ring threads were inspected using a USGI thread timing gauge. Post-heat treat receiver surface and core hardness was examined by spectrum analysis using test mounts (receiver specimens) every 100 rounds fired for a time then every 200 rounds for awhile and then randomly after that. The specimens for the test mounts were cut at various points on the receivers. These test mounts show the case depth of Smith Enterprise receivers is 0.012 " to 0.015 " and the core hardness to range from 35 to 40 HRC in accordance with the USGI M14 receiver drawing F7790189. Smith Enterprise also required spectrum analysis of the receiver when its heat treat vendor changed personnel. Such testing and resultant analysis led to a standard operating procedure for heat treatment. All of this inspection and non-destructive examination was part of the Smith Enterprise, Inc. quality control program.

Note that the reader MUST NOT perform the testing described herein. Personal injury or death may result. Ron Smith personally test fired the very first receiver without it having been heat treated. He shot it for twenty rounds to prove the integrity of the material. The headspace had set back 0.010 " by the twentieth round. Smith Enterprise had Thunderbird Cartridge Company (Laveen, AZ) make up two hand load lots of proof test ammunition for them. One batch of proof test rounds was loaded to 65,000 psi and the other was loaded to 76,000 psi. Thunderbird Cartridge used nickel plated Federal cases and M118 bullets. The bottoms of the 76,000 psi cases were colored purple for identification. Next, a second receiver with no heat treatment was shot twice with 65,000 psi proof test rounds. The headspace had set back 0.010 ". After this, ten receivers were selected out of the first lot of 100 finished receivers. Each of these ten receivers was fired with one round of 65,000 psi proof test ammunition.

Then one finished receiver was selected for destructive testing. Scott Medesha was a witness to this destructive testing. First, ten rounds of 65,000 psi proof test ammunition were fired. Next, 76,000 psi proof test rounds were fired. After four rounds of 76,000 psi proof test ammunition, there were some signs of problems but the receiver had not failed. The cases were seizing in the chamber. Therefore, Scott Medesha went home and loaded up one round of ammunition. Ron Smith states this cartridge was loaded with a large charge of Hercules (now Alliant Techsystems) Unique pistol powder and a 175 grain bullet. Taking suitable precautions, the destruction cartridge was loaded into the rifle chamber and fired. Scott Medesha achieved the desired result. The receiver failed with a dull, muffled boom. The cartridge case vaporized, the barrel blew out about two feet in front of the stock, and the bottom forward one inch of the bolt blew apart, the magazine blew out of the action and all magazine spot welds gave out. The back of the receiver gently rolled off to one side. The receiver on both sides behind the locking lugs cracked. However, the locking lugs on the receiver and the bolt held! The M14 enthusiast should not turn his nose up at a well-made investment cast receiver.

There is a pronounced difference in the shape of the receiver heel between the Smith Enterprise (and Armscorp of America) billet machined and Smith Enterprise investment cast receivers. The billet machined receivers have almost square heel corners whereas the investment cast receiver heel corners are rounded. Smith Enterprise machined more than 300 semi-automatic M14 receivers from plasma cut plate steel. These receivers were marked FORGED USA because the company believed it was a simple, but not exaggerated, way to state the receiver quality. Smith Enterprise semi-automatic M14 receivers were finished with a phosphate coating until somewhere around serial number 002000. From that point forward, pre-'94 ban receivers had nitrocarburizing treatment which left a black color finish. Investment cast receivers above serial number 002000 had additional finish machining that made them nearly indistinguishable from the billet machined receivers. Post-'94 ban receivers left the factory with a phosphate coating. In the opinion of M14 gunsmith Ted Brown, this particular lot of pre-'94 ban receivers were the best investment cast M14 receivers ever made and the billet machined receivers were the best ever. The post-'94 ban receivers were investment cast and produced in small

lots of ten to fifteen at a time.

New receiver manufacturing was initiated in late 2009. Prototype receiver serial numbers XM001, XM002, and XM003 were displayed at the 2010 SHOT Show in Las Vegas, NV. The first ten production receivers were completed in September 2010. Run Guns (Carpentersville, IL) was the authorized distributor for the receivers. The receiver heel was marked as follows: first line - U.S. RIFLE second line 7.62MM M-14 third line - SMITH ENT. fourth line - TEMPE, AZ. fifth line - four digit serial number. At least one rifle with a new production receiver was legally exported in 2012 to Canada for retail sale.

Smith Enterprise also made a single batch of billet machined select fire receivers before the May 19, 1986 civilian machine gun ban. These select fire receivers were registered under the National Firearms Act and then sold in late 1985 to a Class 3 Special Occupational Tax Federal Firearms Licensee in Oregon. All select fire Smith Enterprise models were machined from billet but lack the FORGED USA marking.

Smith Enterprise, Inc. Receiver Identification

Examination of several rifles reveals distinctive markings on Smith Enterprise receivers. Smith Enterprise did stamp some receivers with customer requested serial numbers. Examples of these are serial numbers of the owner's initials and birth date or USGI M14 serial numbers issued to the customer during military service. Some Smith Enterprise receiver heels used serif style lettering such as serial numbers 002197 and 002198 but others do not, e.g., 002292. The number 1 was added to the beginning of some receiver serial numbers to correct the few instances of duplicate numbers. Note that 7790189 is the USGI drawing number for the M14 receiver. Smith Enterprise, Inc. receivers have features as described below:

Pre-'86 ban billet machined select fire - 1) center and rear operating rod dismount notches 2) no hole drilled in the right side receiver leg 3) the selector lug is a homogeneous portion of the receiver rather than welded on 4) M-14 on the heel 5) serial number starts with the letters FA followed by five digits 6) MESA, AZ on the vertical surface at the forward end of the operating rod rail 7) 7790189 on the right hand side near the connector lock below the stock line or 90189 and an eagle, arrow, and stars cartouche below the stock line on the right hand side near the connector lock.

Pre-'94 ban billet machined semi-automatic - 1) M-14 or M-14 NM on the heel 2) MESA, AZ on the vertical surface of the operating rod rail at the forward end 3) FORGED USA on the vertical surface of the operating rod rail at the rear end 4) 7790189 below the stock line on the right hand side near the connector lock 5) ordnance eagle and three stars symbol below the stock line on the right hand side near the connector lock.

Pre-'94 ban precision investment cast semi-automatic - 1) M-14 NM on the heel 2) MESA, AZ on the vertical surface of the operating rod rail at the forward end 3) 7790189 below

the stock line on the right hand side near the connector lock.

Post-'94 ban precision investment cast semi-automatic - 1) M-14 NM on the heel 2) serial number is a four digit number beginning with the numeral 5 3) TEMPE, AZ on the vertical surface of the operating rod rail at the forward end.

Smith Enterprise, Inc. M14 Services

Smith Enterprise, Inc. offers a host of services for the M14 type rifle. It has performed gunsmithing work for many years and continues to do so for the U. S. Army, U. S. Marine Corps and federal government agencies. Smith Enterprise M14 services include match tuning, assembly, receiver heat treatment, receiver, barrel or complete rifle cryogenic treatment, Chinese rifle bolt conversion to USGI bolt, bush barrel conversion and gas piston heat treatment and hard chromium plating. The Chinese rifle bolt conversion entails reworking the receiver to accept a USGI bolt and headspacing the barrel. Smith Enterprise has offered this service since 1994. The bush barrel conversion included finish reaming, installing and headspacing a 17 5/8 " air gauged medium weight Douglas match grade barrel to the receiver. The 17 5/8 " match grade barrel was available from Smith Enterprise, Inc. as late as 2003.

Smith Enterprise will also install its AISI 8620 alloy steel rear or rear and front lugs to the receiver upon customer request. Its rear lugs are designed with beveled edges and an innovative three degree release angle on all four sides. This design reduces wear on the precision bedding material during routine maintenance. In 1986, some of the U. S. Marine Corps shooting team match conditioned M14 rifles were suffering from weld failure on one side of the receiver rear lug. It was determined that improper selection of welding rod material was the cause. Consequently, the U. S. Marine Corps shooting team adopted the practices of Smith Enterprise, Inc. for installation of M14 receiver lugs. Smith Enterprise, Inc. installs receiver lugs on LRB Arms M14SA and M25 receivers for LRB of Long Island, Inc. That work is identified by the stamping S.E.I. on the bottom of the rear lug.

The company also offers a repair for worn or soft receiver elevation serrations. The repair job involves two steps. First, a special cutter is used to slightly counterbore the serrations on the receiver. Then, a serrated hardened steel disk is silver soldered in place of the original serrated area making the elevation knob move once again in crisp six degree movements (sixty serrations in a circular pattern). Beginning in July 2005, Smith Enterprise, Inc. conducted maintenance training classes for U. S. active duty military personnel on the Mk 14 Mod 0 and Mk 14 SEI systems. The first class consisted of twelve U. S. Air Force pararescue airmen.

M14K

Smith Enterprise, Inc. and LaFrance Specialties (San Diego, CA) have collaborated on various projects through the years. One such venture was the M14K, a very interesting and innovative development of the M14 type rifle. The origin was a desire on the part of Richard Smith and Tim LaFrance in the 1980s to make the M14 more compact and controllable without generating excessive muzzle blast and recoil. Tim LaFrance, Richard Smith and his son, Ron Smith, did the research and development for the M14K. After some experimentation, they found that the M60 machine gun gas system provided great promise in reducing the cyclic rate and in delaying bolt opening. Muzzle blast and felt recoil was softened as well. So, Ron Smith further improved and perfected the M60 type gas system for the M14K. M14K rifles, semi-automatic and select fire, were built by Smith Enterprise, Inc. and LaFrance Specialties. This included the woodworking necessary for the stocks. Stanley C. Crist fired the prototype M14K carbine and wrote an article on it that appeared in the April 1990 issue of *S.W.A.T.* The M14K was marketed through means such as a Smith Enterprise, Inc. sales brochure printed and an advertisement that appeared in an October 1988 issue of *Shotgun News*. Additionally, the M14K was marketed by Tim LaFrance at the 1988 *Soldier of Fortune* Show. The last production run was in 1990.

The conversion to a M14K consists of installing the improved M60 type gas system, adding a unique combination muzzle brake and flash hider, shortening the operating rod and wood stock fore end and installing National Match front and rear sights. The fore end of the wood stock was shortened to accommodate the new gas system. A side folding pistol grip wood stock was optional for the M14K. The M14K barrel length was 13 ½ ". M14K models purchased by civilians had either 1:10 twist four groove medium weight match barrels or 1:12 twist chromium plated barrels. The semi-automatic only M14K rifles were assembled with a permanently attached muzzle attachment to bring the barrel length to 16.25 " (overall rifle length of 34.5 "). This modification then exempted the semi-auto only M14K from registration as a Short Barrel Rifle under the National Firearms Act. The match grade barrels proved to be markedly more accurate than the chromium plated barrels in the M14K. The M14K cyclic rate was about 600 rounds per minute and the muzzle velocity 2560 feet per second using M80 ball ammunition. The M14K weighed 9.5 pounds without a magazine or sling.

During the Reagan Presidency, Smith Enterprise converted some M14 rifles to M14K carbines for the Colombian government. The M14K was very effective in the hands of the Colombian Army. In fact, it was so effective that the drug cartel FARC threatened bodily harm on the Smith family. Because the Reagan Administration was not able to guarantee around the clock protection, Smith Enterprise decided to cease the conversion work for the Colombian government.

Smith Enterprise, Inc. introduced an improved M14K at the January 2007 SHOT Show in Orlando, FL. The gas system had been redesigned for ease of manufacturing. Boyds'

will supply the wood stocks using tooling and patterns owned by Smith Enterprise, Inc. Sage International, Ltd. was the supplier for M14 EBR style stocks specifically for the M14K. The improved M14K carbines will have Wilson Arms 16 " four groove barrels with 1:10 twist for semi-automatic models and 1:12 twist for NFA registered select fire models. Semi-automatic only M14K rifles will require registration as short-barrel rifles under the National Firearms Act. Smith Enterprise, Inc. will make all the gas system components. The M14K rear sight assembly will include a non-hooded National Match aperture. A turnaround time of two weeks will be the goal for completing each conversion.

AWC Systems Technology

AWC Systems Technology owner Lynn McWilliams and Gale McMillan, founder of McMillan Fiberglass Stocks, created the G2 series bullpup M14. From 1991 to late 1994, AWC Systems Technology (Phoenix, AZ) converted some M14 type rifles into a bullpup rifle design. Three models of the Gale McMillan inspired design were made, G2, G2A and G2FA. The G2 was the first version. It had a standard contour barrel and a scope mount. The G2A featured a Krieger heavyweight barrel, modified gas cylinder and a scope mount redesigned by Lynn McWilliams. The G2FA was the select fire model.

The overall length for the G2 model was 33.25 ". G2 series rifles were outfitted with a special McMillan design muzzle brake. The trigger was moved forward of the magazine well. The operating rod was modified so that the operating rod handle was located at the mid-point of the barrel. The G2 series design changed the trigger to be actuated by a cable that ran through a channel inside the stock to a bellcrank acting against the original trigger.

All three G2 models placed the scope directly over the barrel. This was accomplished one of two ways. The early design scope mount consisted of two columns on which scope rings were mounted. The late version scope mount was a rail bridge which placed tension on the barrel. The rail bridge was fitted around the gas cylinder and gas cylinder lock at the front end and a column clamped to the barrel mid-point for the rear. The G2A was capable of 0.5 MOA accuracy using match grade ammunition. The Gale McMillan designed G2 series stock had three sling attachment points, one on each side of the butt stock and one of the left side of the forearm. McMillan Fiberglass Stocks sold four stocks to AWC Systems Technology but the source for the remaining stocks is unknown.

AWC Systems Technology sold retrofit kits for \$695.00 and converted existing M14 type rifles for \$895.00. The 1994 manufacturer suggested retail price for a new complete G2A was \$2,850.00. Reportedly, less than 100 G2 and G2A models and less than a dozen G2FA models were produced. At least one unit has been sound suppressed. Apart from AWC Systems Technology, Gale McMillan built one prototype bullpup G2FA for the Federal Bureau of Investigation. The sound suppressed and G2FA models must comply with the National Firearms Act of 1934.

In the early 1990s, AWC Systems Technology also created the M26 and M27 conversions for commercial semi-automatic M14 type rifles. Both models were built the same except the M26 was assembled with a McMillan traditional profile M1A stock and the M27 was fitted with the McMillan pistol grip M2A stock. The conversion included cutting a Krieger heavyweight barrel to 19.25 ", placing a hooded front sight between the bands of the gas cylinder, removing the gas cylinder lock, and adding a barrel tensioning sleeve. The barrel tensioning sleeve indexed against the gas cylinder to control barrel vibration. The M26 and M27 could accommodate the AWC Spectrum 2000 sound suppressor. These conversions were discontinued about the same time as the G2 series bullpup models.

Hesse, Ltd. and Sarco, Inc.

Hesse, Ltd. was located at 9487 Inver Grove Trail Inver Grove Heights, MN from 1998 to 2002. It made two batches of M14 receivers, the first in 2000 and the second in 2002. Steen Armament Research Co., Inc. doing business as Sarco, Inc. (Stirling, NJ) was established in the 1960s by Charlie Steen. It is one of the largest small arms parts dealers in the world. Sarco, Inc. has dealt in M14 parts since at least 1971. Sarco, Inc. M21 receivers were made in 2002. Sarco, Inc. receiver quality has been reported by owners as good fit and finish.

Entreprise Arms, Inc.

Entreprise Arms, Inc. (1996 address 16021 East Arrow Highway Unit B Irwindale, CA 91706) was established in 1993. The firm was located at 15861 Business Center Drive Irwindale, CA in 2000. From 2003 onward, it resides at 5321 Irwindale Avenue Irwindale, CA 91706. The firm made one production run of 2000 receivers from 1996 to 1997. The last of the Entreprise Arms M14A2 receivers were sold in 2008. The receivers were CNC machined from twelve-pound billets of AISI 8620 alloy steel and given a black oxide finish. The manufacturing process involved sixteen separate set up operations using three CNC machine tools. Entreprise Arms receivers were heat treated to a surface hardness of 52 to 56 HRC and a core hardness of 34 to 38 HRC. The model numbers were K01 for non-lugged, K0RL for rear lugged, and K0FRL for double lugged receivers.

The M14A2 receivers were sold with an unconditional lifetime guarantee. Some of the receivers have the stamping ABNI. ABNI is an abbreviation for ABN Industrial Co., Inc. (Buena Park, CA). ABN Industrial was a subcontractor to Entreprise Arms, Inc. ABN Industrial is a general machine shop, casting foundry, and sheet metal and fabrication assembler. Lower serial number Entreprise Arms M14A2 receivers have the serial number stamped on the left side near the rear sight. Higher serial number M14A2 receivers have a wider than USGI specification operating rod rail and the serial number was stamped on the receiver heel. By 2001, the firm had moved to its present address, 5321 Irwindale Avenue Irwindale, CA 91706. Entreprise Arms, Inc. provided M14 gunsmithing services in the late 1990s and early 2000s including rifle assembly, barrel installation, phosphate coating of parts, NM trigger modification, and clean and lube.

Entreprise Arms, Inc. made an extended bolt lock for the M14 type rifle in the past but currently does not.

Troy Industries, Inc.

The M14 type rifle was further refined for civilians in 2002. Mike Rock and Jim Ribordy developed the Rock SOPMOD M14 for the U. S. Navy but the public is aware of it through the efforts of Stephen P. Troy, owner of Troy Industries, Inc. Troy Industries, Inc. was formed as a Massachusetts corporation on January 15, 2003 at 17 Main Street Lee, MA 02138. By 2008, the firm had relocated to 128 Myron Street West Springfield, MA 01089. RD Systems (South Beloit, IL) built the Rock SOPMOD M14 conversion. Troy Industries marketed and sold the Rock SOPMOD M14 conversion until October 2005. LRB of Long Island, Inc. marketed the Rock SOPMOD M14 conversion from October 2005 until May 2006. RD Systems assumed the marketing duties from that point forward. What follows is a history of the Troy Industries involvement with the Rock SOPMOD M14 project.

Steve Troy was introduced to Mike Rock and the Rock SOPMOD M14 by a mutual business acquaintance. Steve Troy saw potential in the commercial market for the Rock SOPMOD M14. Consequently, Troy Industries promoted the Rock SOPMOD M14 through printed literature at the annual SHOT Show beginning in 2003, the company web site and Internet discussion boards.

As previously discussed, the Rock SOPMOD M14 carbine had been designed and developed under contract for the U. S Naval Surface Warfare Center (Crane, IN) for the M14 EBR project. At that time, neither Mike Rock nor Steve Troy knew of the involvement Sage International had with the M14 EBR project. Personnel from NSWC at Crane, IN informed them that the Rock SOPMOD M14 was still too heavy. Both Mr. Rock and Mr. Troy thought a contract was pending so they took steps to reduce the weight of the carbine. Ironically, the M14 EBR design adopted by the U. S. Navy weighs more than the commercial Rock SOPMOD M14 carbine.

The performance of the first commercial production conversions was puzzling since they were not performing as well as the models built for the U. S. Navy. Steve Troy made several trips to RD Systems to help troubleshoot the loss of accuracy. No further conversions were shipped and all those that had been shipped were returned to RD Systems at no expense to the customer. The loss of accuracy was mostly due to changes in materials used in the conversion to reduce weight to comply with the requirements of the unrealized U. S. Navy contract. Additionally, the varying dimensions of commercial M14 type receivers were responsible for complicating the installation of the receiver front lug that is bolted to the metal stock.

The original design of the Rock SOPMOD M14 featured an aluminum stock and steel telescoping rails. Steve Troy added his input to create the commercial version of the Rock SOPMOD M14. As a result, the Rock SOPMOD M14 was made with a lighter and

stronger titanium butt stock assembly. The stock body was machined from alloy aluminum billet. Steve Troy made further design enhancements such as the operating rod protector, sling swivels, the three-way front lug, CQB combination flash suppressor / muzzle brake and textured coatings. The Rock SOPMOD M14 receiver was double lugged.

The pull button 16.5 " long 1:11.27 five radial groove rifle stainless steel barrels were supplied by Rock Creek Barrels, Inc. The new stock and accessory rail system included four military standard M1913 Picatinny accessory rails. The USGI flash suppressor and front sight were replaced with the combination flash suppressor and muzzle compensator compatible with the optional Troy Industries sound suppressor. A M203 grenade launcher will attach to the Rock SOPMOD M14 stock at the six o'clock rail. The grenade launcher could be removed by disengaging a quick release device.

The Rock SOPMOD M14 weighed less than 10 pounds and the overall length was 27 " with the stock collapsed. Using the Rock SOPMOD M14 and bipod, a twenty round magazine could be emptied into a 5 " group on paper at 100 yards in automatic. The Rock SOPMOD M14 could consistently group 3 " at 500 yards in semi-automatic. In either mode, felt recoil was negligible as compared to the standard M14 rifle.

In 2003, Troy Industries introduced the Rock SOPMOD M14 Calimando. This conversion was performed by RD Systems on California resident M14 type receivers to comply with that state's laws governing semiautomatic firearms. The conversion included a 16.5 " barrel and traditional style butt stock without a pistol grip. Overall length for the Rock SOPMOD M14 Calimando was 35 ".

Both Rock SOPMOD M14 Carbine and Calimando models used the cartridge clip guide as an attachment point for the accessory rails. The Rock SOPMOD M14 models had the visible portion of the operating rod marked with all the Troy Industries model information for those units sold by Troy Industries. Several optional items were available through Troy Industries for the Rock SOPMOD M14 models including single point CQB sling, soft or hard case, sound suppressor, and bipod. Standard surface finish for the stocks and pistol grips was textured black.

At the 2004 SHOT Show there were several Rock SOPMOD M14 carbines were displayed at the Troy Industries booth. One of these models was dressed in a medium brown color Rock SOPMOD M14 stock. The receiver, rear sight assembly, all rails, the firing mechanism parts, and the operating rod were all nickel-boron plated. The benefit of nickel-boron plating is wear resistance superior to that of chromium. The nickel-boron plated parts had a color darker than gold but lighter than bronze. That model was a special order item only available in 2003.

In 2004, several Springfield Armory, Inc. M1A SOCOM models were converted to ROCK SOPMOD M14 carbines. The original factory combination gas cylinder lock front sight

muzzle brake was substituted with a re-threaded Noveski brand muzzle brake sans gas cylinder lock. Troy Industries sold a total of about thirty Rock SOPMOD M14 carbines. In October 2005, LRB of Long Island, Inc., began marketing the Rock SOPMOD M14. Another three Rock SOPMOD M14 units were sold. By September 2006, RD Systems had dropped the project.

In 2010, Troy Industries was asked to develop a suppressed short barrel M14 carbine for a specific military requirement. The result, its CAR-14 prototype, was debuted at the 2011 SHOT Show. The CAR-14 had a 12.5 " long barrel and proprietary gas system, all housed inside a newly designed metal chassis stock. The chassis stock was mated to a Troy Industries Battle Axe collapsing butt stock including an integral GPS unit on the right hand side. The stock was machined with a flared magazine well with interior vertical relief cuts but lacked a selector cutout. The top rail cover of the stock partially covered the handle section of the operating rod. The stock fore end was narrowed, rounded and drilled with lightening holes in contrast to the quad rail fore end of the Troy Industries Modular Chassis Stock. The fore end centerline was drilled with threaded holes for attaching quick detach sling studs. The CAR-14 sound suppressor was installed or removed by way of a quick disconnect mechanism. At the same time the suppressor was attached or detached to the muzzle, the gas system was automatically adjusted accordingly. The entire system was finished in flat dark earth color.

LRB of Long Island, Inc.

In July 2002, LRB of Long Island, Inc. was established. The firm began selling semi-automatic M14 type rifle receivers the following year. LRB is an acronym for the names of the owner and his wife, Lou and Rosemarie Biancospino. The manufacturing of LRB Arms M14SA receivers is briefly described below.

Bourdon Forge Company has manufactured high quality forgings since 1969. It uses Computer Aided Design, Computer Aided Manufacturing and Computer Aided Design for Impact Forging software to develop highly specialized forgings. To make the LRB Arms receivers, Bourdon Forge Company, Inc. (Middletown, CT) cuts extruded AISI 8620 alloy steel bar stock into ingots, heats them and then drop forges them into shape. LRB of Long Island, Inc. designed its receiver forging die from a Winchester USGI M14 forging. The forging die design was slightly altered from the original to accommodate CNC machining operations. Bourdon Forge Company manufactured the LRB Arms M14 receiver forging die but LRB of Long Island retains ownership. Periodically, the die is replaced due to normal use.

The raw forgings are then machined at J. V. Precision Machine Company (Seymour, CT) according to USGI drawing F7790189. Dimensional tolerances are held to within 0.001 ". Most of the receiver dimension gages have been redesigned for compatibility with the CNC machining processes. Traditionally, the magazine well of commercial M14 receivers has been formed by broach cutting. J. V. Precision Machine Company,

manufacturing semi-automatic M14 receivers for LRB Arms, in 2006 became the first ever to form the magazine well using the wire EDM method. In April 2007, J. V. Precision was using a wire EDM machine, a horizontal CNC machining center and two other machine tools in five tool set-ups to machine each LRB Arms M14 type receiver. Due to the complexity of the receiver design, some machining cuts still require manual machine tool operations such as drilling the bolt lock pin holes, final milling of the rear sight pocket and heel underside, cutting the receiver bridge primary firing pin retracting surface and cutting the receiver rear end firing pin recess.

The receivers are inspected at J. V. Precision for proper dimensional geometry and then examined again by LRB Arms itself back in Floral Park, NY. If inspection results are not satisfactory, the receivers are sent back to J. V. Precision for adjustment. If the receiver geometry is satisfactory, it is sent to a vendor for heat treatment. The first heat treating vendor was Beehive Heat Treating Service, Inc. (South Norwalk, CT) but the work was later moved to American Heat Treat, Inc. (Monroe, CT). LRB Arms receivers are heat treated to a core hardness of 28 to 42 HRC and a surface hardness of 52 to 55 HRC with a case depth of 0.012 " to 0.018 ". Each receiver is tested for hardness in the rear sight pocket since this surface is not visible once assembled as a complete rifle. LRB of Long Island, Inc. maintains a log book to record the hardness test results for every receiver. The final step is a phosphate coating that duplicates the color and finish of the original M14 receivers. Initially, the phosphate coating was performed by a metal coating company in St. Albans, VT. Presently, the receiver finishing is performed at Acton Metal Processing Corporation (Waltham, MA). In 2012, H. P. White Laboratory, Inc. (Street, MD) tested LRB Arms M14SA serial number 034XXX. Special cartridges were intentionally overloaded and fired to see if the receiver would fail. Seven proof rounds were fired which developed increasingly higher chamber pressure, 49,200 PSI to 119,020 PSI. The receiver never failed but the bolt face and extractor failed on the last round. The reader must never attempt such testing because personal injury may occur.

The LRB of Long Island, Inc. M14 type rifle receiver design was approved by the Bureau of Alcohol, Tobacco, Firearms and Explosives in January 2003. The law enforcement portion of the Bureau of Alcohol, Tobacco and Firearms was transferred from the Department of Treasury to the Department of Justice and renamed the Bureau of Alcohol, Tobacco, Firearms and Explosives (BATFE) on January 01, 2003 as part of the Homeland Security Act of 2002.

To understand the M14SA receiver numbering sequence the following background is given. In 2000, Mike Kelly Specialties (Grafton, WV), also known as MKS or M-K Specialties, removed the selector lug, filled in the operating rod rail cuts and welded back together at least 250 demilitarized USGI M14 receivers. The Bureau of Alcohol, Tobacco and Firearms apparently took issue with this market opportunity. In 2001 and 2002, the retail buyers of the MKS welded M14 rifles were tracked down by the BATF. All of the buyers had passed a criminal background check and bought the rifles through a Federal Firearms Dealer. Most of the owners "abandoned" the welded receivers but were able to

keep the parts.

In 2006, the Sixth and Ninth Circuits of the United States Court of Appeals affirmed respective District Court rulings in 2002 granting U. S. government motions for seizure of welded MKS M14 receivers. Expert witnesses in both cases testified that the MKS manufactured M14 rifles could be made to fire automatically using metalworking tools in no more than two hours in one case and in no more than six hours in the other case. The phrase "readily restored" used in the National Firearms Act definition of machine gun (26 US Code section 5845 (b)) was not specifically defined in the federal statute. So, the courts turned to dictionaries for understanding of the words "readily" and "restored." Both circuit courts ruled that altering a MKS M14 receiver using metalworking tools within a period of two hours to six hours met the dictionary definitions of "readily" and "restored." Thus, the MKS receivers were judged to be machine guns per the NFA definition and the government had probable cause to seize the MKS M14 receivers since they were not found in the National Firearms Registration and Transfer Record.

In 2002, MKS was marketing the sale of newly manufactured semi-automatic receivers and complete rifles built on these receivers. Rifle models available were Rack Grade, Premier Match and Tanker. The Manufacturer's Suggested Retail price for the M-14-A1 Rack Grade rifle was \$1595.00. The newly manufactured receivers were forged in Taiwan and machined at J. V. Precision Machine. LRB of Long Island was the distributor for the MKS newly manufactured M-14-A1 receivers. At least 100 of these newly manufactured receivers had made it into the hands of the buying public through Federal Firearms Dealers. As part of the purchasing process, all of the buyers successfully passed a criminal background check. These receivers were stamped on the heel as follows from top to bottom: first line – U.S. RIFLE second line – 7.62 MM M-14-A1 third line – MK SPECIALTIES fourth line – 00XXX.

As built, these receivers were only capable of semi-automatic fire and sold as such. However, the BATFE took the position that these receivers were unregistered machine guns. The presence of certain features discussed below was deemed by the BATFE to make these receivers readily convertible to automatic fire capable. These receivers were later confiscated in 2003 by the BATFE from the owners after being allowed to remove all other attached parts.

One day in 2002, a number of raw MKS receiver forgings were in a machine shop in lots of various stages of the machining process. The BATF made a visit and seized a number of the receivers. The semi-finished MKS receivers that were seized had features such as a solid (versus drilled per drawing F7790189) lug on the rear right bottom side, an operating rod center notch and a groove on the forward bottom side of the operating rod rail. After the BATF left the building, the machine shop was left with some of the MKS forgings in various stages of machining. The receivers the BATF left behind had none of the select fire features mentioned above. Some had a little machining completed and some were almost finished. In early 2003, the LRB contractor, J. V. Precision Machine,

was able to finish the machining operations on the former MKS forgings. LRB of Long Island, Inc. sold the receivers with the markings LRB ARMS M14SA. Based on how many receivers were in each stage of the machining process, they were divided into groups for numbering, i.e., ten in the first group, four in the second group, forty-nine in the third group, and eight in the fourth group.

The first ten LRB receivers sold had the least amount of machining needed for completion. These are marked as X00101 through X00110. The next four M14SA receivers needed a little more machining to complete than the first ten and are marked as 00101 to 00104. These needed a little more machining to complete than the first ten. The third group of M14SA receivers, forty-nine of them, starts at serial number 01001. These required more machining than the first two sets. The fourth group of M14SA receivers which began as MKS units starts at serial number 01101 and ends at 01108. These required even more machining than the first three sets.

Subsequent M14SA receiver serial numbers start at 01201. These receivers are forgings made after the machine shop had used up all the forgings previously made for MKS. Receivers starting with serial number 01201 are forged at Bourdon Forge Company. Between receivers numbered 01227 and 01237 inclusive, the serial number marking was changed from dot peening to a roll die stamping. The first operating rod channel marking for the LRB M14SA receiver was JV PRECISION SEYMOUR CT USA. The operating rod channel marking changed to JVP SEYMOUR CT USA somewhere between serial number 01211 and 01237. LRB Arms M14SA receivers between 01500 and 01620 were machined a little too high for the firing mechanism. This is easily accommodated by either: 1) filing a small amount of metal off the top surface of the magazine latch plate or 2) removing a small amount of stock material where the trigger housing pads rest or 3) by installing a used firing mechanism.

At the 2004 SHOT Show, LRB displayed two prototype M14SA receivers each with two integral M1913 Picatinny rail pads. The receiver rail pads are located on top of the barrel ring and at the cartridge clip guide dovetail mount. Known as the LRB Arms M25, the first prototypes of these M1913 integrated rail receivers were forged in October 2004. Subsequent development led to an improved design by the fall of 2006. By November 2006, the two integrated rail pads had been replaced with two dove tail attachment points to be used in conjunction with a removable M1913 rail. The receiver is drilled and tapped for two socket head screws to secure the removable M1913 rail in place. The removable M1913 rail was machined from AISI 4140 alloy steel. It allows the use of iron sights when the optical sight is removed. This change made the M25 receiver more versatile in accommodating optical sights with various eye relief distances. In late 2009 and early 2010, there was a collaborative effort between LRB of Long Island, Inc. and Sadlak Industries, LLC to create an extended M1913 rail for the LRB Arms M25 receiver. The prototype extender rail was displayed at the 2010 SHOT Show. A year later, Sadlak Industries, LLC was producing the M25 extended M1913 rail. Note that the LRB Arms M25 receiver does not have the left side scope mount geometry since it is not needed.

M25 serial numbers 10001 through 10012 were pre-production prototype receivers.

In December 2004, LRB Arms began selling complete M14SA rifles in limited quantities. The M14SA rifles are assembled with all USGI parts except for Criterion or Wilson Arms match grade standard contour barrels. In April 2005, the LRB Arms M14SA Tanker became available for purchase. This is a LRB Arms M14SA with an 18.5 " barrel and optional Smith Enterprise, Inc. muzzle brake. Chromium plating of either length barrel is an option to the buyer. Complete LRB Arms M14SA rifles built by the firm are warranted for one year. In the summer of 2008, LRB Arms sold a run of ninety-nine non-lugged M14SA receivers, serial numbers TFL01 through TFL99, for members of The M14 Firing Line Internet discussion forum.

The LRB Arms 10th Anniversary Rifle was issued in 2012. This model was built with an LRB Arms M14SA receiver, Criterion Barrels stainless steel medium weight 1:11 twist rate barrel, LRB Arms bolt, USGI flash suppressor, National Match front sight, match grade operating rod spring guide, and Boyds' M1A Style I walnut stock. The left side of the receiver was laser engraved with a crossed cannons logo and the identifying number in the series, "10th ANNIVERSARY No. XXX of 200." A 10th Anniversary coin was recessed into the right hand side of the butt stock.

The New York Secure Ammunition and Firearms Enforcement (SAFE) Act became law on January 15, 2013. This law required New York residents, among other things, to register certain firearms classified as Assault Weapons. The definition of Assault Weapon included rifles which could accept a detachable magazine and featured a flash hider, muzzle brake, or threaded barrel designed to accommodate a flash hider or muzzle brake. By July 2013, LRB Arms produced two prototype semi-automatic only M14 type rifles without a barrel threaded at the muzzle. The LRB Arms Sporter model was built with a Criterion Barrels unlined 19 " medium weight 1:12 twist rate barrel, combination gas cylinder lock front sight, and Boyds' M1A walnut stock. The accessories included a five round Check-Mate Industries magazine, sling and manual.

7.62mm Firearms

7.62mm Firearms is a Class 3 SOT/FFL business located in Medina, OH. It is owned by a former U. S. Marine, Chris Thomas. The firm manufactures semi-automatic M14 receivers and M14 parts. The receiver was designed from USGI drawings and demilitarized TRW receivers using CAD software to create three dimensional programming for its CNC machine tools. Demilitarized TRW receivers were sandblasted and examined for tooling marks. This allowed the machining operations to be run in a sequence that closely duplicates the appearance of TRW receivers on the 7.62mm Firearms M14 NM receiver. All receivers were made from AISI 8620 alloy steel. All raw materials were obtained from a local steel mill. All machining, heat treatment, and finishing operations were performed within a fifty-one mile radius of Medina, OH.

The first receivers were machined from investment castings at the end of 2009. A total of 380 forged receivers were made from the spring of 2010 to late 2011. One hundred of these were supplied to James River Armory. The receiver heel was marked as follows: top line - U.S. RIFLE second line - 7.62MM M14 NM third line - 7.62 inside a diamond fourth line - five digit serial number. The operating rod rail was marked 7.62MM MEDINA, OH or FORGED, USA MEDINA OHIO. The part number, 7790189, was stamped under the operating rod rail. Introduced in 2013, the fourth generation receiver operating rod rails were marked FORGED U.S.A. WADSWORTH, OH. Custom serial numbers were available upon request.

James River Armory

James River Manufacturing, Inc. (Halethorpe, MD) ended its production of Armscorp logo receivers in March 2008. The owner, Mark Hartman, resumed sales of M14 related items by advertising complete semi-automatic M14 rifles in the fall of 2009. The rifles with cast receivers shipped to FFL dealers beginning in January 2010. Rifles with forged receivers were delivered to customers starting in April 2010. The investment cast and forged James River Armory receivers were made by 7.62mm Firearms but marked on the heel as follows: top line - U.S. RIFLE second line - 7.62MM M14 NM third line - JAMES RIVER fourth line - ARMORY fifth line - serial number. The operating rod rail was marked FORGED USA BALTIMORE MD. The first couple hundred rifles were assembled with USGI parts and walnut stocks with the exception of the receiver and barrel. These rifles were built with Criterion Barrels, Inc. 22 " long chromium plated standard contour barrels. The forged model M14F ROCK-OLA series receivers were brought to market in October 2013. The operating rod rail was marked FORGED ROCK-OLA FIREARMS BALTIMORE MD. The receiver below the stock line on the right hand side was marked BULA FORGE & MACHINE 7790189. All James River Manufacturing, Inc. M14 type receivers were made from AISI 8620 alloy steel.

Origin of Chinese M14 Rifles

Four credible sources, three former military and one civilian arms importer, attest to the veracity of the claim that the People's Republic of China obtained M14 technical data in 1959. It is alleged that technical data on the M14 was gathered surreptitiously from the Winchester factory at New Haven, CT. These sources also state that unmarked U. S. manufactured M14 rifles provided to Congo were captured and turned over to the People's Republic of China. On November 20, 1960, three members of the National Security Council authorized the Central Intelligence Agency, in support of Project Wizard, to provide arms, ammunition, sabotage materials, and training to Congo Army leader Mobutu Sese Seko. These two particular allegations, theft of M14 technical data and capture of Congolese held M14 rifles, remain unsubstantiated rumor. Another rumor states that M14 rifles produced in the 1960s by the People's Republic of China were reverse engineered from enemy captured M14 rifles in Viet Nam. Such an endeavor would not have been without precedent. The Nationalist Chinese government made

several thousand Model 1921 Thompson submachine guns in 1927 at its Tai Yuan Soldier factory in Shansi Province. The Communist government produced M1 Carbines from 1949 to 1952. In preparing for this work, the author interviewed a very reliable source with extensive firsthand knowledge of Chinese and Taiwanese production and export of small arms. The gentleman wishes not to be identified. He is referred to as Other Source # 12.

It was policy of the Chinese government until 1978 to export Marxist revolution to the world's masses, much like the former Soviet Union tried to do during its reign in eastern Europe into western Asia. This policy changed dramatically in 1978 when Deng Xiaoping assumed leadership in China. After 1978, the Chinese government pursued economic development and trade for the country, whereas before they promoted and supported communist dissident movements around the globe. This trend has continued through the decades. In the 1980s, there were forty ammunition plants. By 2010, there were only four factories in the People's Republic of China producing small arms ammunition.

With the takeover of China by Communists in 1949, the government arsenals were renamed. This numbering convention has remained to the present day. Each arsenal was assigned specific weapons. At some point before 1966, State Arsenal 356 was assigned production of the Chinese M14 rifle. It remains so today. For example, in October 2008, State Arsenal 356 had in its inventory 19,000 Chinese M14 rifles ready for transfer to Norinco for export except that these rifles had no stocks or operating rods. Thus, between October 2008 and May 2009, new operating rods and polymer stocks were manufactured to complete the Norinco order.

By no later than 1965, the Chinese government had manufactured 100,000 M14 rifles and the necessary magazines and ammunition for export to arm rebels in other countries. The Chinese select fire M14 rifles were made to look just like captured American M14 rifles. The Chinese government went so far as to produce 7.62 x 51 mm NATO ammunition identical to British issue ammunition, though with corrosive primers. This 7.62 x 51 mm NATO faux British-headstamped Chinese made ammunition was exported to the United States and sold on the commercial market in the 1980s. The rifles and ammunition were manufactured with U. S. and British markings so as to avoid any connection to the People's Republic of China, and possibly to serve a role in disinformation (propaganda) campaigns for the planned uprising. These M14 rifles were manufactured at State Arsenal 356 at Kunming, Yunnan Province, People's Republic of China. Yunnan Province is in southwest China and borders the nations of Laos and the Socialist Republic of Viet Nam. State Arsenal 356 was built inside a hill. The floor plan of the arsenal was horseshoe shaped.

The Communist Chinese government made two attempts to ship its select fire M14 rifles to the Philippines. The first attempt was largely unsuccessful and the second was a total failure. On December 26, 1968, Jose Maria Sison, founded and chaired the Central Committee of the Communist Party of the Philippines. Three years later, Sison chose

Ricardo S. Malay, then a columnist for the *Manila Chronicle*, to arrange the delivery of weapons from China to the New People's Army in anticipation of an armed uprising against then-President Ferdinand Marcos. Sison was later charged with subversion and imprisoned in 1977 by the Philippine government. He was released from prison on March 05, 1986 by President Corazon Aquino. He has been in exile in the Netherlands since October 1988 serving as the Chief Political Consultant for the National Democratic Front, a coalition of left-leaning political parties, trade unions and agricultural unions in the Philippines.

The New People's Army (NPA) is the military arm of the Communist Party of the Philippines. It was established by the Communist Party of the Philippines on March 29, 1969 with sixty fighters and thirty-five rifles and handguns. Its stated goal is to overthrow the government of the Philippines through long term guerilla warfare. The peak strength of the NPA was 25,000 in the 1980s. Present estimated strength is 10,000 and growing. The NPA is organized into twenty-seven battalions of full time fighters. They operate in Luzon, Visayas and Mindanao to this day.

Ricardo Malay and his family made their way to China in July 1971. Malay and his family were later joined in China by Sison's closest colleague, Ibara Tubianosa, and four other individuals. Certain arrangements were made to package 1,200 of the M14 rifles with magazines, a quantity of ammunition, and other military items. The cargo was soon thereafter loaded onto the ship *MV Karagatan*. The ship and its cargo sailed from the Chinese naval base at Swatow headed for Digoyo Bay, Isabela, Philippines.

Victor Corpus was an instructor and a Tactical Officer at the Philippine Military Academy (Fort Del Pilar, Baguio City, Luzon). The Philippine Military Academy is the Philippine counterpart to the United States Military Academy at West Point, NY. While on duty as the Officer of the Day, Victor Corpus allowed the New People's Army to raid the academy armory. He fled to the jungle the same day.

The New People's Army fighters, led by Victor Corpus, were waiting for the delivery of Chinese M14 rifles. However, the Philippine armed forces intercepted the shipment aboard the *MV Karagatan*. Consequently, a firefight ensued between the New People's Army fighters and the Philippine troops. Corpus and Kumander Dante, Chief of the NPA, were captured by the Philippine government troops. The NPA was only able to salvage only 200 of the 1,200 M14 rifles and little of the other military equipment Mao Zedong had approved as aid to the Philippine revolution. The 1,000 Chinese M14 rifles captured by the Philippine military are rumored to have been sent to the Philippine Military Academy and issued to the cadets for drill purposes as symbolic payback for the treachery of Victor Corpus. Victor Corpus went to prison and served his sentence. In an ironic twist of history, the Philippine government made Victor Corpus an Army Colonel after Ferdinand Marcos fled the country on February 25, 1986. Corpus went on to serve the Philippine government in various capacities including head of the National Intelligence Coordinating Agency, the Philippine equivalent of the Central Intelligence Agency.

In 1973, Sison tasked Malay to attempt another delivery of M14 rifles from China to the Philippines. He proposed that the Chinese prepare a shipment of M14 rifles in watertight packages to be dropped off the Pangasinan coast for recovery by scuba divers. Months later in December 1973, Malay and Tubianosa flew to Sanya, Hainan. Hainan is the southernmost island of China. Sanya is the capital of Hainan as well as the location of a Chinese naval base. When Malay and Tubianosa arrived at Sanya, they were briefed by a Chinese military officer regarding the packaging of the M14 rifles. The rifles were vacuum packed inside reinforced plastic bags with three rifles to a sack. Each sack also contained ammunition. The Chinese military officer had a team that had previously tested the packaging to make sure it would hold in the ocean environment. Malay and Tubianosa flew to Beijing the next day. The ship *MV Andrea*, with four crew members, was assigned to transport the M14 rifles and eight New People's Army fighters to the Philippine Pangasinan coast. Enroute to Sanya, the ship struck a reef somewhere in the Pratas Islands of the South China Sea. The twelve men aboard (four crew members and the eight New People's Army fighters) the stranded vessel were picked up and taken to Hong Kong by a passing Hong Kong salvage ship, the *Oriental Falcon*. In exchange for passage to Hong Kong, the *Oriental Falcon* was allowed to keep the *MV Andrea* for scrap. After a stay in a Hong Kong jail, the Filipino New People's Army fighters were released due to intervention of the Chinese Red Cross and the ship's Chinese crew was quickly moved to the Chinese mainland.

In the early 1980s, Other Source # 12 traveled to China. He was shown the remainder of the approximately 100,000 Chinese manufacture select fire M14 rifles. The Chinese M14 rifles were packed in crates in one warehouse while the British-marked, Chinese produced 7.62 x 51 mm NATO ammunition was stored in a separate warehouse. Some time after this, the select fire M14 rifles were disassembled and only the receivers were destroyed. Since there were no furnaces or ovens in the local vicinity for melting steel, the receivers were mixed with concrete to make concrete blocks for building projects. A limited number of the Chinese select fire rifles, minus the selector lugs, were sold on the commercial market in Canada and New Zealand in the 1980s. Parts from the select fire M14 rifles were later exported to the United States as M14 parts kits for use by Federal Ordnance, Inc., Arms Corporation of America, Inc. and Century Arms International in 1991 and 1992 to build rifles with American made receivers. Surplus parts suppliers such as Northridge International, Inc., Numrich Gun Parts Corporation and Sarco, Inc. stocked Chinese M14 parts for retail sales until they sold out. The ammunition was exported as well to the United States for commercial sale.

Norinco and Poly Technologies Corporation

M14 type rifles exported to the United States from China have been stamped as two brands, Poly Technologies Corporation and Norinco (1992 address 7A Yue Tan Nan Jie P. O. Box 2137 Beijing, People's Republic of China 100045). Norinco is formally known as China North Industries Corporation. Norinco is owned by the government Ministry of Ordnance Industry. It is an enormous business conglomerate that deals in military

defense products, engineering contracting, optical products, oil production, chemical products, small arms, ammunition, automobiles, hotels and other real estate, travel and logistics services, and rare mineral products.

However, Other Source # 12 explained what Norinco is in another way. Norinco was set up as a committee decades ago to supply war materials to prosecute the war in Viet Nam against the United States. Viet Nam was heavily dependent upon China during the war. After the change in government policy in 1978, there was no military need for Norinco. In 1980, Norinco was established as an export corporation since Chinese arms factories cannot sell directly to anyone but the Chinese government. Thus, Norinco has exported small arms and ammunition for sale in the commercial market of various countries since the 1980s. Norinco entered the U. S. market in May 1986. Richard Chen was the U. S. representative for Norinco. In 1998, Norinco spun off its civilian small arms and ammunition marketing and sales operation, with government approval, into the wholly owned subsidiary registered as Norinco Armsports Co., Ltd. Norinco Armsports Co., Ltd. is also known as Norinco Sports. Due to U. S. government trade sanctions, a two year import ban was placed on all Norinco goods in May 2003. The registered trademark for Norinco was cancelled by the U. S. Patent and Trademark Office in December 2003.

Poly Technologies Corporation (Beijing, People's Republic of China) was established in June 1984 by the People's Liberation Army. Poly Technologies was made a subsidiary of China International Trust and Investment Corporation (CITIC) on paper. In reality, Poly Technologies was under the influence of the People's Liberation Army. The trading company was given its name by Xu Zhaolong, then General Manager of CITIC. Poly Technologies exported military ordnance from small arms to missiles for sale until at least 1997. PTK International, Inc. (then 2814 New Spring Road Suite 340 Atlanta, GA 30339) was the main subsidiary of at least seven U. S. companies owned by Poly Technologies. PTK International was headed by Baoping "Robert" Ma. The company was in the business of importing and distributing various Chinese made semi-automatic rifles for commercial sales from May 07, 1987 until August 06, 1996. Since February 1993, Poly Technologies has been one of four major subsidiaries of China Poly Group Corporation.

Production and Export of Chinese M14 Rifles

All Chinese semi-automatic M14 rifle receivers and new (post-1978) production parts for them have been manufactured at State Arsenal 356 as the select fire models were in 1965. During the 1980s, Mr. Wu was the Chief Engineer of State Arsenal 356. He passed away in the mid-2000s. All Chinese M14 receivers were drop forged. Select fire and semi-automatic only M14 type rifles were produced for Norinco. Poly Technologies models were semi-automatic only. Semi-automatic only M14 receivers were made from 1987 to 1994. State Arsenal 356 test fired every M14 and proof fired one in ten M14 rifles.

Chinese semi-automatic M14 rifles have been directly exported to Canada, France, Germany, Ireland, Italy, Luxembourg, New Zealand, Norway and the United States for sale to private owners. At least one Norinco M14 Sporter imported by Century Arms International had made its way to the Netherlands by 2005. Chinese M14 rifles exported to Canada around 1987 were rendered semi-automatic only in order to comply with Canadian law. Chinese semi-automatic M14 type rifles were imported into Germany in early 1987. Germany requires firearms that are imported or sold to an individual must be proof fired with a cartridge loaded to 30 % higher than normal chamber pressure. After successful firing, the barrel is stamped with a proof marking. This testing was done for the Chinese rifles imported into Germany.

New Zealand - Firearms in New Zealand are regulated under the Arms Act 1983 and the Arms Regulations 1992. Gun owners there have been licensed since 1992. A private individual in New Zealand must obtain a firearms license issued by the police before a rifle, shotgun or pistol may be legally owned and used. To obtain the firearms license, the applicant must pass a test on firearms ownership, use and storage, and successfully pass a criminal background check. An arms officer from the New Zealand Police inspects the means of storing firearms at the applicant's home. Ammunition must be kept in separate locked storage. As is typical with government licensing everywhere, the New Zealand firearms license may be revoked for various reasons (conviction for domestic violence, drunk driving, or a crime punishable by prison sentence) and it has an expiration date, ten years in this instance. When not in use, all firearms must be kept in locked storage. Briefly, there are five categories of New Zealand firearms license endorsements: "A" - long guns except military style semi-automatic rifles, "B" - pistol, "C" - collector (allows ownership of certain firearms prohibited from use, e.g., machine guns, pistols with barrels less than 4 " long), "D" - firearms dealer, and "E" - military style semi-automatic long guns.

The semi-automatic M14 type rifle meets the definition of a military style semi-automatic (MSSA) in New Zealand. In that country, a MSSA is a semi-automatic or self-loading firearm other than a pistol which featured one or more following features: 1) folding or telescoping butt stock 2) a magazine capable of holding more than fifteen .22 caliber rimfire cartridges or more than seven cartridges of any other caliber 3) bayonet lug 4) military pattern pistol grip or 5) flash suppressor.

Prior to 1992, the Chinese and USGI M14 type rifles were imported with their military features minus automatic fire capability. Thus, the Chinese M14 rifles exported to New Zealand in the 1980s were only modified by cutting off the selector lugs from the 1965 vintage receivers. New Zealand still allows private possession of a semi-automatic only M14 rifle regardless of its pedigree, Chinese, USGI or commercial US manufacture. USGI and Chinese M14 rifles can be shot in matches in New Zealand but the selector lug is either removed or the selector shaft and selector lock are welded together to render it semi-automatic only.

In 2007, Outdoor Arms imported Norinco M14 Sporter rifles into New Zealand. The rifles were packaged with two five round magazines, a sling and a cleaning kit inside a cardboard box marked Norinco M-14S. The 2007 import models were built with 1990s production receivers intended for sale to the United States. As an example, Norinco M14 Sporter serial number 008827 imported that year into New Zealand was marked as follows on the left side of the receiver above the stock line: top line - M-14 .308 NORINCO bottom line - MADE IN CHINA CJA SFLD. MI 008827. The heel of receiver was stamped with the importer's name, Outdoor Arms. These rifles were imported with faux flash suppressor and no bayonet lug. This configuration allowed them to be imported as Category A firearms instead of being classified as a MSSA and thus requiring a firearms license with a Category E endorsement. Norinco M14 rifles imported into New Zealand in 2009 do not have the Outdoor Arms marking. Some rifles imported in 2010 had 18.5 " barrels.

One Chinese semi-automatic M14 type rifle model was the M305. Rifles marked M305 have been exported to Canada, France, Germany, Ireland, New Zealand and Norway. These were marked on the left side of the receiver as follows: top line - Model 305 middle line - 7.62x51 bottom line - Made in China. The Norinco logo was placed next to the stamped text. A small number of Norinco select fire M14 rifles have been available for sale in the United States as post-'86 ban dealer samples.

Chinese M14 Rifle Export to the United States

There have been five, importers of Chinese M14 type rifles into the United States: 1) Keng's Firearms Specialty, Inc. (then Stone Mountain, GA) 2) Cheshire & Perez Distributors Co., Inc. (135 E. Walnut Avenue Monrovia, CA) 3) Century Arms International (then St. Albans, VT) 4) IDE USA (Southfield, MI) and 5) CJA (Southfield, MI). The Chinese M14 type rifles were imported into the United States from January 1988 until May 1994. As shown on an ATF Form 6 related to one of these export shipments, the importer cost of a Poly Technologies M14S in 1989 was \$225.00. All complete Chinese M14 rifles imported into the United States were assembled with 1965 Chinese production metal parts. Each Chinese M14 rifle and its accessories were shipped in a cardboard box with a single piece styrofoam insert. The estimated number of Chinese M14 rifles imported into the United States was 25,000 to 30,000.

The BATF approved the ATF Form 6 that allowed Cheshire & Perez Co., Inc. to import in 1988 one lot of 500 Norinco M305 rifles. These Norinco M305 rifles were marked on the left side of the receiver: top line - CHESHIRE & PEREZ bottom line - MONROVIA CA. This specific lot of rifles had a milled selector lug, center dismount operating rod notch, and a forward underside groove. The Cheshire & Perez imported Norinco M305 rifles are the only known case of legal importation of Chinese M14 rifles with select fire features as semi-automatic firearms.

Keng's Firearms Specialty, Incorporated imported no more than 2720 to 2920 Poly Technologies M14 type rifles into the United States. The firm did not import any Norinco marked M14 type rifles or receivers. IDE USA imported all Poly Technologies M14 rifles into the United States with serial numbers above a number between 2720 and 2920. It appears that Century Arms International imported at least 1245 Poly Technologies M14 type rifles into the United States. Norinco marked M14 type rifles were imported into the United States by Century Arms International and CJA. The receivers of Poly Technologies M14 type rifles imported into the United States were manufactured between 1988 and 1993. Norinco M14 type receivers were manufactured from 1989 until at least 1994.

Keng's Firearms Specialty, Incorporated

Keng's Firearms Specialty, Inc. (now in Atlanta, GA) was established in 1985. The company has imported firearms and firearm accessories for commercial sale in the United States. Specifically, Keng's Firearms Specialty imported Poly Technologies M14 type rifles in 1988 and 1989. Keng's Firearms was the only company that imported Chinese M14 type rifles (Poly Technologies M14/S models) into the United States before the March 14, 1989 ban on importing military-lookalike semi-automatic rifles. This event is commonly referred to as the "1989 import ban." The Chinese M14 (Poly Technologies M14/S) rifles first appeared in the United States as part of the Keng's Firearms Specialty exhibit at the January 1988 SHOT Show. The first print advertisement for the Poly Technologies M14/S appeared in the July 1988 issue of *Guns & Ammo*. Poly Technologies M14/S serial number 0043X with a hinged butt plate and bayonet lug was imported by Keng's Firearms before March 14, 1989.

Tim LaFrance noted that he had a concern with the Chinese bolts after examining the Poly Technologies rifles at the 1988 SHOT Show. He suggested to Keng's Firearms Specialty that these rifles be evaluated because of his concern with the bolts. Consequently, Poly Technologies representatives from the People's Republic of China contacted Smith Enterprise, Inc. shortly thereafter to discuss the manufacturing of M14 rifles. Representatives from Poly Technologies met for five days with Smith Enterprise personnel, with David Keng of Keng's Firearms Specialty acting as translator. The Poly Technologies representatives were supplied with a set of USGI drawings for the M14 and five stripped semi-automatic Smith Enterprise, Inc. M-14 receivers.

After this first meeting, Poly Technologies sent raw forgings and assembled M14 rifles (Poly Technologies serial numbers 000001 through 000005) to Smith Enterprise, Inc. for evaluation and testing. Ron Smith personally test fired these first five Poly Technologies M14 type rifles. Smith Enterprise thoroughly examined and tested the Poly Technologies receivers and rifles. Chinese receivers tested after these first batch of five were found through spectrum analysis to be made of the Chinese equivalent of AISI 8620 alloy steel, the proper material for M14 receivers. The first Poly Technologies M14 rifles imported into the United States had a varying number of digits, three to six, in the serial number of

each rifle. Very quickly though, no later than serial number 00061, there would only be five digits making up the serial number on each Poly Technologies M14 rifle imported into the United States. Receiver heels were marked using Kuhlmann GmbH pantographs.

Karl Maunz was living in Atlanta, GA when Keng's Firearms Specialty imported Poly Technologies M14/S rifles. Keng's Firearms Specialty supplied him with two Poly Technologies M14/S rifles for testing and evaluation. He found the receiver to be made of equivalent AISI 8620 alloy steel. The receiver material testing conducted by Smith Enterprise and Karl Maunz was done independently of each other. The Chinese bolts, however, were not made of the USGI drawing specified alloy steel.

The Smith Enterprise testing included hardness testing of the Poly Technologies receiver core by cutting it apart. One Poly Technologies receiver was tested to destruction by loading ammunition to create excessively high chamber pressure. The reader MUST NOT exceed powder charges as listed in reputable reloading manuals if hand loaded ammunition is used. Personal injury or death may occur if done so. The very first Poly Technologies receivers were very hard, harder than a file, which left them without the toughness provided by the relatively soft core of receivers made according to USGI specifications. The Chinese arsenal quickly corrected this by strictly adhering to the receiver heat treatment procedure.

After Smith Enterprise completed the evaluation, a second meeting of the parties involved was held. Even after this second meeting, Poly Technologies did not correct all the concerns of Smith Enterprise and Keng's Firearms Specialty had regarding the Chinese bolt. Specifically, 1) the bolt locking lugs were too narrow and 2) the carburizing and hardness remained unsatisfactory because State Arsenal 356 did not change the material to equivalent AISI 8620 steel but continued to use steel equivalent to AISI 4135. This was in spite of the fact that Keng's Firearms Specialty offered to supply USGI M14 bolts until Poly Technologies could manufacture its own bolts according to USGI specifications. Poly Technologies refused this offer from Keng's Firearms Specialty. The Chinese never changed the bolt material for M14 type rifles exported to the United States.

Century Arms International

Century Arms International has imported and exported firearms and accessories for more than forty years. Century Arms International was located at 5 Federal Street St. Albans, VT 05478 in the mid-to-late 1980s. By 1990, the company's address was listed as 48 Lower Newton Street St. Albans, VT 05478. The firm moved its headquarters to Boca Raton, FL in 1997 and then again to Delray Beach, FL in 2004. Phyllis Sucher co-founded Century Arms International Inc. in St. Albans, VT in 1961. In August 1984, the company was sold to new owners but she remained on board as one of the company directors until at least April 2004. Regrettably, she passed away on May 14, 2007.

Century Arms International imported Chinese M14 rifles from 1990 until at least late 1993. It imported both completed Poly Technologies rifles and Norinco M14 type rifles and

receivers before May 26, 1994. Chinese M14 rifles imported by Century Arms International after March 14, 1989 and before November 30, 1990 were assembled with military style features, i.e., hinged butt plate and flash suppressor with bayonet lug, after arrival in the United States. Norinco rifles imported by Century Arms International had the least aesthetic appeal of all the Chinese M14 type rifles imported into the United States. Typically, the chu wood stocks are serviceable but not pleasing to the eye. The Poly Technologies rifles had better looking chu wood stocks and finish.

Poly Technologies M14S and some Norinco M14 Sporter rifles imported by Century Arms International have serial numbers with a letter C prefix followed by a hyphen and four digits or it is denoted as the letter C immediately followed by five digits. Location of the serial number on the receiver varies too. Some of the serial numbers were stamped with roll dies while others were applied by electropencil. Century Arms imported the Poly Technologies rifles before the Norinco marked models.

From November 29, 1990 until importation ceased in May 1994, Century Arms International renamed the Norinco rifle, M14 Sporter or M14 S/A Sporter in some instances. Century Arms International established a facility in Montreal, Quebec by no later than 1988. The firm modified the imported Chinese M14 type rifles at this facility to comply with the March 14, 1989 import "assault rifle" and November 29, 1990 "assault rifle" parts ban in the United States. Century Arms International removed the military style features previously allowed from each rifle by cutting the flash suppressor just forward of the front sight, replacing the hinged butt plate with a rubber recoil pad and not supplying a magazine. A few Norinco M14 Sporter rifles without serial numbers were imported by Century Arms International about 1991 or 1992. When the BATF began to investigate this oversight, it was ordered by the U. S. Department of State to not pursue the matter.

IDE USA and CJA

In April 1983, the People's Armed Police Force was formed out of the People's Liberation Army in China. The People's Armed Police Force is tasked with protecting government buildings and providing security to public corporations and for large public gatherings. Some time later, China Jing An (No. 25, Xitangzi Lane North Wang Fu Jing Street Beijing 10006 People's Republic of China) was formed as an arms export firm for the financial interests of the People's Armed Police Force. China Jing An (CJA) operated its business in Southfield, Michigan from 1989 until at least 1997. The engraving CJA SFLD MICH appears on Norinco M14 type receivers. CJA imported Norinco M14 rifles from at least late 1992 until May 1994. At least one CJA imported Norinco receiver was marked with the model designation M-14. Other than their physical proximity to one another, nothing else is known of any relationship between IDE USA and CJA.

Chinese M14 rifles imported by IDE USA were exported by Poly Technologies. IDE USA stamped Poly Technologies M14/S serial number 090XX was purchased new from a FFL

in the United States by the original owner during the fall of 1993. The original retail purchase of IDE USA imported Poly Technologies M14/S serial number 14821 occurred in November 1993. Yet another original owner reported his purchases of IDE USA imported Poly Technologies M-14S serial numbers, 13955 on December 05, 1993 for \$599.00 and 23260 on February 26, 1994 for \$429.95.

The marking IDE USA SLFD MICH has been observed on Poly Technologies receiver serial numbers 0292X through 25181. IDE USA imported the best looking Chinese M14 rifles into the United States. Representatives from IDE USA traveled to State Arsenal 356 in Yunnan Province, People's Republic of China to discuss the assembly process of the M14 type rifles it wished to import. These rifles were assembled with new production parts with a very good finish and some were given walnut stocks. The walnut wood for these stocks was harvested in Yunnan Province.

Chinese M14 Rifle Export to Canada

Alan Lever of Lever Arms Service Ltd. (Vancouver, BC) imported Norinco M14 type rifles into Canada from 1988 until 2011. Century Arms International imported both Norinco and Poly Technologies M14 type rifles into Canada during the early 1990s. Some Norinco receivers imported around 2002 to 2003 by Marstar Canada and by Lever Arms Service in 1988, e.g., serial number AL000680, had a blued finish instead of a phosphate coating. These receivers lacked the scope mount vertical groove lug and boss. Instead, they were machined flat but retained the drilled and tapped bolt hole and the horizontal groove. At least some of these blued receivers were marked Model 305 7.62X51 on the left side, e.g., serial number AL000680. At some point, Norinco serial number AL000844 found its way to Finland and a Poly Technologies M305 was exported to Ireland in 2010, both from Canada. Dark International Trading Company (Ontario) imported Norinco M14 rifles from 1997 until September 2007. Until 2009, Chinese M14 rifles were exported with chu wood stocks. After 2008, the rifles were assembled with new polymer stocks and marketed as the M305B model.

From September 2003 until November 2008, Marstar Canada, Inc. (Vankleek Hill, Ontario) imported Norinco M14 rifles into Canada with the receivers exhibiting the CJA marking seen on American imports. These complete rifles were assembled with new Chinese manufacture parts but the receivers were residual inventory from production in the mid-1990s. At least some of these rifles were marked with the year of assembly, e.g., 2007, on the right hand side of the receiver. By 2007, the machinery used to manufacture Chinese semi-automatic only M14 receivers had been laid up for many years. Marstar Canada backed the rifles with a one year parts and labor warranty. The firm received export shipments from China in November 2006, November 2007, November 2008, June 2011 and September 2013. Aside from the blued finish M305 models lacking the receiver scope mount geometry, the Norinco rifles imported by Marstar had the slotted flash suppressor and scope mount recoil lug.

The fit and finish of Norinco rifles entering Canada after 2000 were judged to be better than that found on Chinese M14 rifles exported to the United States. Introduced to Canada in October 2013, the SOCOM 18 had a 18.5 " barrel, gas lock front sight and a reversible muzzle brake. The muzzle brake could be threaded from either end on to the 0.595 " x 32 muzzle threads. It weighed 9 pounds. Reportedly, USGI bolts fit properly in the post-'00 assembled Norinco M14 rifles. The bolt hardness was markedly higher than bolts exported to the United States before 1994.

Chinese Receivers

On the whole, Poly Technologies rifles have a better reputation for receiver surface machining and finish as compared to the Norinco stamped rifles. There was no substantial difference between Norinco and Poly Technologies receivers although Smith Enterprise found the surface hardness to vary from 41 to 60 HRC without regard to brand. Smith Enterprise, Inc. did extensive inspection, and non-destructive testing, and destructive examination of Chinese receivers. These inspections and tests verified that Chinese M14 receivers were made of AISI 8620 equivalent alloy steel. Chinese receivers were drop forged into forms of larger bulk and less definition than the USGI receivers were. Then, like the American manufacturers, machine tools cut away at the metal from the raw forging to create the final desired shape before carburizing and heat treatment.

Chinese receivers are not made of high carbon alloy steel such as AISI 52100 or other such high chromium alloy steel. Equivalent AISI 5100 series steel is high carbon (1.0 to 1.1 %) alloy steel that is much too hard for a rifle receiver. Because it is a high carbon steel that is thorough hardened it lacks toughness and ductility needed for the M14 type rifle. AISI 52100 alloy steel is the most commonly used steel for bearings. The machinability rating of AISI 52100 alloy steel is 40 % when in the spheroidized annealed and cold drawn condition as compared to 100 % for AISI 1112 steel. It is difficult to machine and must be quenched below room temperature to form martensite.

Post-1978 production Chinese receivers have a threaded hole for a setscrew in the barrel ring. 1965 production Chinese M14 receivers were not manufactured with the barrel ring setscrew. The post-1978 production Chinese rifles are built with a setscrew threaded far enough through the barrel ring to contact the barrel. The barrel setscrew is unnecessary for securing the barrel in the receiver. However, the Chinese manufactured their receivers this way because it is their psychological mindset.

Markings of Exported Chinese M14 Rifles

At this point in the story, it may be helpful to the reader to summarize the model and serial numbers of Chinese M14 type rifles imported into the United States and Canada.

Model Numbers – Norinco M14 type rifle model numbers observed were M-14, M14 Sporter, M14 S/A Sporter, M305 and SOCOM 18. M14 Sporter was the most common

Norinco model designation. The Poly Technologies model numbers were M-14S, M14S, M14/S and M305. The model number was indicated on the receiver left side, the receiver heel or the factory barrel just behind the front sight.

Serial Numbers - The majority of serial numbers of Chinese M14 rifles were stamped above the stock line on the scope mount side, below and slightly behind the rear sight elevation knob. It was not unusual for the receiver serial number to be lightly stamped or engraved. The serial number was stamped on the receiver heel of early U. S. imports.

Norinco M14/M305 rifles were imported into Canada from as early as 1997 until 2013 by these businesses: 1) Badger Arms Supply 2) Bell Lifestyle Products and Distributors 3) Canada Ammo 4) Dark International Trading Company 5) Dominion Arms 6) Lever Arms Service Ltd. and 7) Marstar Canada. The serial numbers for Norinco M14 rifles with CJA markings were not imported into Canada sequentially. For example:

001199 - Imported by Marstar Canada in September 2003
002096 - Imported by Bell Lifestyle Products and Distributors in January 2005
002194 - Imported by Lever Arms Service Ltd. in December 2001
004739 - Imported by Bell Lifestyle Products and Distributors in May 2005
007926 - Imported by Marstar Canada in May 2006
008511 - Imported by Dark International Trading Company in September 2007
008568 - Imported by Bell Lifestyle Products and Distributors in March 2007
012687 - Imported by Marstar Canada in May 2006

The receiver left side on 2004 and 2005 imported rifles was stamped as follows: first line - M14 .308 second line - CJA SFLD MICH third line - NORINCO MADE IN CHINA and the six digit serial number. A May 2006 import was marked on the receiver left side as follows: first line - M14 .308 NORINCO 00XXXX second line - MADE IN CHINA SFLD, MI. In July 2009, a batch of Poly Technologies M305 rifles were brought into Canada by Bell Lifestyle Products and Distributors (Mississauga, ON). The 2009 imports were not marked on the barrel or the receiver heel but on the left side of the receiver as follows: top line - M305 .308 middle line BELL LIFESTYLE.CA 2009 then four digit serial number bottom line - BY POLY INC MADE IN CHINA. The Poly Technologies M305 rifles imported by Bell Lifestyle had a barrel ring setscrew but without being staked. These rifles were assembled with new commercial manufacture black or camouflage pattern molded polyethylene stocks with metal liners reminiscent of USGI wood stocks but no selector cutout and some had faux flash suppressors. Four months later, the same importer brought in Norinco M305 rifles assembled and marked in the same manner with the only differences being NORINCO instead of POLY INC on the receiver and the flash suppressors were lugged. Likewise, Badger Arms Supply (Melfort, SK) received Norinco M305B rifles in December 2010 and February 2011 with 2009 prefix serial numbers. A Norinco SOCOM 18 imported in 2013 by Dominion Arms into Canada was marked on the left side of the receiver as follows: top line - SOCOM 18 SEMI-AUTO 7.62X51NATO second line - DOMINION ARMS third line - 20130814-13-356 CN 13 CA.

A few Norinco rifles in the United States and Canada had no manufacturer stamping but were marked with the importer's name. Until 2011, most Chinese semi-automatic only M14 receivers were marked with numbers below the stock line on the left side. Sometimes the numbers matched the serial number indicated on the receiver above the stock line and sometimes not. As an example, Norinco receiver serial number 9914 had 9914 stamped on the left side below the elevation knob and 9914 is electro-penciled on the left receiver leg. There were no other markings on the receiver. Two Norinco M14 rifles imported into Canada in May 2006 had the following numbers on the receiver under the stock line on the left side, 4 2 28 14 22 and 4 3 42 22 24. The numbers under the stock line on Chinese M14 type receivers indicate a date code. For example, Poly Technologies M-14S serial number 15079 has the following numbers under the stock line on the left side: 3 4 4 38 7. The first number indicates 1993 as the year of manufacture. By late 2011, Chinese M14 type rifles imported into Canada were no longer stamped with numbers below the receiver stock line. These receivers were also marked differently in order to comply with international agreements. Example, a Norinco M305 rifle with a 18.5 " barrel imported by Canada Ammo in late 2011 was marked on the left side of the receiver as follows: 20111223-11-356-CN 11 CA. Select fire capable 1960s production Chinese M14 receivers were not stamped below the stock line but the bolts and trigger housings were marked with the last five digits of the receiver serial number.

In 1994, Smith Enterprise, then known as Smith Arms International, offered two match conditioning packages for Chinese M14 rifles, Match Grade Basic and Match Grade U.S. The Match Grade Basic service package included receiver heat treatment and glass bedding, rifle phosphate coating, recrowning the barrel muzzle, a unitized and polished gas system and a firing mechanism tune up. The customer also had a choice with either service package: 1) installation of a Smith muzzle brake or 2) National Match modification of the customer supplied USGI flash suppressor. The Match Grade U.S. service included everything in the Match Grade Basic package plus installation of a Smith supplied American made barrel and USGI bolt, stock refinishing and marking the receiver heel as follows from top to bottom: first line - U. S. RIFLE second line – 7.62-MM M-14 third line – SMITH ENT.

United States Firearms Laws

The following discussion of firearms laws is not legal advice. It is presented as background information since firearms laws do affect the sale, transfer and possession of the M14 type rifle. United States law separates firearms into two categories, Title 1 and Title 2. Title 2 firearms are those regulated by the National Firearms Act of 1934 (NFA). These include machine guns, short barrel rifles, short barrel shotguns, sound suppressors, destructive devices and a special class of firearm known as Any Other Weapon (AOW). An example of an AOW is a pen gun. Destructive devices include items such as grenade launchers, mortars and High Explosive rounds. Under United States law, a select fire M14 type rifle is a machine gun.

Title 1 firearms are all other post-1899 design firearms with some exceptions (paintball guns, flare launchers, flame throwers, BB guns, airsoft guns, etc.). Title 1 firearms are regulated by the Gun Control Act of 1968 (GCA). A M14 type rifle designed as semi-automatic only is a Title 1 firearm. State and local laws place additional restrictions on the sale, transfer, possession and use of firearms in the United States.

Before 1934, there was no regulation of private ownership of any firearms in the United States of America, let alone machine guns. Congress passed the National Firearms Act of 1934 and President Franklin Delano Roosevelt signed it into law on June 26, 1934. The National Firearms Act became effective July 24, 1934. The NFA was initially implemented through a federal tax regulatory document titled Regulations 88. This document was revised and published again in 1941 and 1952. At some point before 1969, Regulations 88 was incorporated into the Code of Federal Regulations. Federal firearms regulations are included in Title 27 of the Code of Federal Regulations.

The M14 rifle was officially classified as a machine gun in 1958 by the U. S. Department of the Treasury. The Internal Revenue Service Revenue Ruling 58-417 is reproduced here in its entirety:

The Internal Revenue Service has had occasion to consider the classification status of the new U.S. Army M-14 "rifle" chambered for the 7.62mm NATO cartridge, in the light of the provisions of the National Firearms Act (Chapter 53 of the Internal Revenue Code of 1954). Held, (1) that since the M-14 "rifle" operates either fully automatically or semi-automatically on a selective basis, it is in basic design and function a "machine gun" as defined in Section 5848(2) of the Internal Revenue Code of 1954 and, accordingly subject to the provisions of the National Firearms Act, and (2) that the substitution of a selector shaft lock, in lieu of a selector lever assembly, on the M-14 "rifle" is of temporary nature and, therefore, does not materially alter the classification thereof for purposes of the National Firearms Act.

In the United States, a Federal Firearms License (FFL) is granted to an individual by the Department of Justice Bureau of Alcohol, Tobacco, Firearms and Explosives (BATFE). There are several types of Federal Firearms Licenses. The type of FFL held by the dealer legally dictates what kinds of firearms he can buy or sell. A myriad of state and local laws also affect FFL holders. The type of FFL, among other requirements, also determines if the dealer can pay a Special Occupational Tax to the BATFE to import, manufacture or deal in National Firearms Act firearms (Classes 1 and 4, 2 and 5, and 3 respectively).

Firearms Identification - Firearms manufactured in or imported into the United States are required to meet the following as set forth in Title 27 of the Code of Federal Regulations. The April 2006 edition text is reproduced here:

TITLE 27--ALCOHOL, TOBACCO PRODUCTS, AND FIREARMS

CHAPTER II--BUREAU OF ALCOHOL, TOBACCO, FIREARMS, AND EXPLOSIVES,
DEPARTMENT OF JUSTICE

PART 478 COMMERCE IN FIREARMS AND AMMUNITION

Table of Contents Subpart F - Conduct of Business Sec. 478.92 How must licensed manufacturers and licensed importers identify firearms, armor piercing ammunition, and large capacity ammunition feeding devices?

(a)(1) Firearms. You, as a licensed manufacturer or licensed importer of firearms, must legibly identify each firearm manufactured or imported as follows: (i) By engraving, casting, stamping (impressing), or otherwise conspicuously placing or causing to be engraved, cast, stamped (impressed) or placed on the frame or receiver thereof an individual serial number. The serial number must be placed in a manner not susceptible of being readily obliterated, altered, or removed, and must not duplicate any serial number placed by you on any other firearm. For firearms manufactured or imported on and after January 30, 2002, the engraving, casting, or stamping (impressing) of the serial number must be to a minimum depth of .003 inch and in a print size no smaller than 1/16 inch; and (ii) By engraving, casting, stamping (impressing), or otherwise conspicuously placing or causing to be engraved, cast, stamped (impressed) or placed on the frame, receiver, or barrel thereof certain additional information. This information must be placed in a manner not susceptible of being readily obliterated, altered, or removed. For firearms manufactured or imported on and after January 30, 2002, the engraving, casting, or stamping (impressing) of this information must be to a minimum depth of .003 inch. The additional information includes: (A) The model, if such designation has been made; (B) The caliber or gauge; (C) Your name (or recognized abbreviation) and also, when applicable, the name of the foreign manufacturer; (D) In the case of a domestically made firearm, the city and State (or recognized abbreviation thereof) where you as the manufacturer maintain your place of business; and (E) In the case of an imported firearm, the name of the country in which it was manufactured and the city and State (or recognized abbreviation thereof) where you as the importer maintain your place of business. For additional requirements relating to imported firearms, see Customs regulations at 19 CFR part 134.

(2) Firearm frames or receivers. A firearm frame or receiver that is not a component part of a complete weapon at the time it is sold, shipped, or otherwise disposed of by you must be identified as required by this section.

U. S. Law and the Chinese M14 Rifle

The U. S. Department of Treasury import ban of March 14, 1989 affected the Chinese M14 rifles then being brought into the United States. After the import ban, Chinese M14

type rifles entered the US market with a rubber recoil pad instead of the M14 style hinged butt plate, the bayonet lug ground off, the flash suppressor castle nut welded on and the flash suppressor either removed or installed without the open slots which made the item suppress muzzle flash. From November 30, 1990 onward, the Chinese rifles were usually imported without an accompanying magazine. A known exception is the case of Century Arms International. After June 1992, Century Arms supplied a Chinese twenty round magazine blocked to five rounds capacity with each Chinese rifle for an unknown period. Each modified Chinese magazine had a metal block welded to the bottom of the follower to limit its capacity to five rounds. Presumably, the magazine modification was performed to comply with the July 1992 passage of the Canadian magazine capacity ban. Century Arms International imported Chinese M14 rifles into Canada before they arrived in the United States. Until November 30, 1990 one could install imported parts that would restore the Chinese M14 type rifle to a configuration prohibited from import after March 14, 1989.

On November 30, 1990 the assembly of imported rifles using imported parts to circumvent the import ban became illegal by federal regulation, which has the force of law. The BATF on that date published regulations to enforce Title 18 U. S. Code section 922 (r). These regulations prohibit the assembly of a semi-automatic rifle (or shotgun) using more than ten specified imported parts if that firearm was banned from importation after March 14, 1989. So, after November 29, 1990 the importer or owner of a Chinese M14 type rifle could have replaced a sufficient number of Chinese parts with USGI parts to "domesticate" the rifle (create the legal equivalent of a non-import rifle by making it comprise no more than ten specified import parts), thereby allowing the installation of a slotted flash suppressor with bayonet lug, and pistol grip stock or folding stock. This was legal under federal law until September 13, 1994.

On September 13, 1994 the Violent Crime Control and Law Enforcement Act went into effect. Effective September 13, 1994, all semi-automatic M14 type rifles were allowed only one specified feature if assembled on or after that date. Typically, manufacturers chose the lugless slotted flash suppressor for the one feature. If a sufficient number of specified Chinese parts were replaced with USGI parts on a Chinese M14 type rifle after September 13, 1994 so that no more than ten specified imported parts were in the rifle, a lugless slotted flash suppressor was permissible under federal law. Effective September 13, 2004, the 1994 Violent Crime Control and Law Enforcement Act regarding features on semi-automatic centerfire rifles was automatically repealed by the sunset provision. Thus, the federal laws regarding features and imported parts on Chinese and American semi-automatic M14 type rifles revert back to what existed on September 12, 1994. Some cities and states restrict features of magazine fed semi-automatic centerfire rifles, e.g., Buffalo, California, Chicago, Connecticut, Massachusetts, New York, New York City, Rochester and Toledo. Consult federal, state and local laws before changing any features on any firearm.

After the March 14, 1989 import ban and before May 26, 1994, Armscorp USA, Federal Ordnance and Century Arms International assembled M14 type rifles using American made receivers and Chinese parts sets. Poly Technologies M14 type rifles in the United States are generally regarded as having been imported and assembled prior to September 13, 1994. Reportedly, some Norinco M14 type rifles were sold prior to September 13, 1994 and some were warehoused by Century Arms International and then assembled and sold after September 13, 1994.

Domestication of The Chinese M14 Type Rifle – The owner of a Chinese M14 type rifle imported into the United States after November 29, 1990 may install a slotted flash suppressor with a bayonet lug in the United States if no more ten specified imported parts are in the assembled rifle and if allowed by state and local laws. If the import date or assembly date in the United States for a particular Chinese M14 cannot be solidly documented before November 30, 1990, the rifle owner should not assume it to be so in order to remain within the law. From Title 27 Code of Federal Regulations revised April 01, 2007:

Sec. 478.39 Assembly of semiautomatic rifles or shotguns.

(a) No person shall assemble a semiautomatic rifle or any shotgun using more than 10 of the imported parts listed in paragraph (c) of this section if the assembled firearm is prohibited from importation under section 925(d)(3) as not being particularly suitable for or readily adaptable to sporting purposes.

(b) The provisions of this section shall not apply to:

- (1) The assembly of such rifle or shotgun for sale or distribution by a licensed manufacturer to the United States or any department or agency thereof or to any State or any department, agency, or political subdivision thereof; or
- (2) The assembly of such rifle or shotgun for the purposes of testing or experimentation authorized by the Director under the provisions of Sec. 478.151; or
- (3) The repair of any rifle or shotgun which had been imported into or assembled in the United States prior to November 30, 1990, or the replacement of any part of such firearm.

(c) For purposes of this section, the term imported parts are:

- (1) Frames, receivers, receiver castings, forgings or stampings
- (2) Barrels
- (3) Barrel extensions
- (4) Mounting blocks (trunions)
- (5) Muzzle attachments
- (6) Bolts
- (7) Bolt carriers
- (8) Operating rods
- (9) Gas pistons
- (10) Trigger housings

- (11) Triggers
- (12) Hammers
- (13) Sears
- (14) Disconnectors
- (15) Buttstocks
- (16) Pistol grips
- (17) Forearms, handguards
- (18) Magazine bodies
- (19) Followers
- (20) Floorplates

Semi-automatic Chinese M14 type rifles as imported into the United States, did not have these four parts: barrel extension, mounting block (trunion), bolt carrier, and pistol grip. *One possible method* of installing an American made flash suppressor with a bayonet lug, where allowed by state and local law, while complying with 27 CFR 478.39, is as follows.

Leave these ten specified parts on the Chinese manufacture M14 type rifle: receiver, barrel, operating rod, trigger housing, sear, trigger, hammer, bolt, disconnector and gas piston. The U. S. Rifle M14 nomenclature does not include the term "disconnector." No part of the rifle is named "disconnector" in any of the U. S. military manuals or in any of the product (part) drawings of the M14 or M14 NM rifle technical data packages. The function of a disconnector is to release the hammer when the trigger is pulled. The disconnector is a separate part in the AK47 and the M16. In the M14, the disconnect function is performed by the top lugged portion of the trigger. After the trigger is pulled and released, the trigger lug engages the hammer hooks to prevent further firing until the trigger is subsequently pulled. The M14 trigger counts as two parts for the purpose of the above list of foreign named parts.

After checking the rifle is empty of ammunition in the chamber and in the magazine, replace these six parts in this order: 1) remove the Chinese magazine (three named parts) and never use it again in the rifle 2) remove the Chinese hand guard and stock (two named parts) 3) install a USGI hand guard and American made stock 4) remove the Chinese solid faux or bobbed flash suppressor and flash suppressor nut (one named part). This leaves ten named foreign made parts in the Chinese M14: receiver, barrel, bolt, trigger housing, hammer, trigger, sear, disconnector, operating rod, gas piston. *If allowed by state and local laws*, now install a USGI flash suppressor with bayonet lug and an American made flash suppressor nut. Note that an American made flash suppressor nut will work on a Chinese barrel but not vice versa. By installing an American made flash suppressor and nut on the barrel last the rifle will not even momentarily exist in a configuration that is prohibited from importation. Installing an American made flash suppressor nut on a Chinese barrel should avoid any cute accusation of it being a foreign made "muzzle attachment."

American made parts can be installed in a Chinese M14 type rifle but the U. S. owner must not install a slotted flash suppressor or a folding stock or a stock with a pistol grip with more than ten specified imported parts from the list above on the rifle. Note that parts made by Wayne Machine, Inc. (Taipei, Taiwan) for the Springfield Armory, Inc. M1A are also imported into the United States. Disclaimer: As always, local, state and federal laws and regulations are subject to change. Note that the U. S. Code of Federal Regulations is revised annually. The rifle owner or gunsmith is responsible for complying with all current local, state and federal laws and regulations.

President William Jefferson Clinton imposed a ban on firearms and ammunition from the People's Republic of China on May 26, 1994. His decision was one part of several actions taken to renew Most Favored Nation (MFN) trading status with China. The Presidential decision to renew MFN trading status followed a year long Department of State review of China's treatment of political dissidents, prisoners, emigrants, and religious worshipers. President Clinton imposed the import ban on firearms and ammunition from the People's Republic of China based on authority granted in the Arms Export Control Act of 1976 (22 U. S. Code section 2778). Consequently, the BATF would not approve any further ATF Forms 6 to import Chinese M14 rifles. Firearms already in transit at the time of the ban were exempt though under federal law and allowed to clear U. S. Customs at the port of entry.

On April 06, 1998, U. S. Secretary of Treasury Robert E. Rubin issued an official press release declaring a ban on any further importation of semiautomatic rifles that could accept a magazine capable of holding more than ten cartridges and designed for a military assault rifle. Further, in letters dated July 13 and August 12, 2005, the BATFE stated that ATF Forms 6 would no longer be approved after December 31, 2005 for importing "any frames, receivers, or barrels for firearms that would be prohibited from importation if assembled." Under these current interpretations of the "sporting purposes" language of the 1968 Gun Control Act, Chinese M14 rifles, receivers and barrels are not eligible for importation into the United States.

1994 Assault Weapons Ban

On September 13, 1994 President William J. Clinton signed bill H. R. 3355 known as the Violent Crime Control and Law Enforcement Act of 1994 (hereafter referred to as the 1994 AW Ban), into law. This law created new legal categories of semi-automatic rifles and semi-automatic pistols called "semi-automatic assault weapons" (AW or AWs). Title XI of the 1994 AW Ban prohibited any future manufacture, transfer to or possession by civilians of certain semi-automatic rifles and pistols made after that date, and also outlawed any future transfer to or possession by civilians of newly-manufactured ammunition feeding devices (commonly called magazines) with a capacity exceeding ten cartridges. This law was written with a ten year sunset provision, wherein the law by its own terms would expire on September 13, 2004 if Congress took no action to renew or extend the 1994 AW Ban.

Before this federal law expired, a number of states enacted their own permanent bans on certain semi-automatic firearms (by name and/or physical features). Some states also prohibited civilian possession of ammunition feeding devices capable of containing a specified number of cartridges, either in connection with their own versions of an AW ban or without affecting civilian ownership of semi-automatic firearms. Most states' laws of this sort did not apply to firearms and/or magazines already in possession, while other states required citizens owning the affected items to either surrender them to law enforcement officials, register them with the state government, sell them out of state (or to a licensed firearms dealer who could then sell the newly-declared contraband only to law enforcement or military users), or store them out of state. Such states included California, Connecticut, Hawaii, Maryland, Massachusetts, New Jersey and New York. As it related to the M14 type rifle, the 1994 AW Ban limited the number of specified features it could possess. The applicable sections of this expired federal law are set forth below:

TITLE XI--FIREARMS SUBTITLE A--ASSAULT WEAPONS

SEC. 110102. RESTRICTION ON MANUFACTURE, TRANSFER, AND POSSESSION OF CERTAIN SEMIAUTOMATIC ASSAULT WEAPONS.

(a) RESTRICTION- Section 922 of title 18, United States Code, is amended by adding at the end the following new subsection: `(v)(1) It shall be unlawful for a person to manufacture, transfer, or possess a semiautomatic assault weapon.

(b) DEFINITION OF SEMIAUTOMATIC ASSAULT WEAPON- Section 921(a) of title 18, United States Code, is amended by adding at the end the following new paragraph: `(30) The term `semiautomatic assault weapon' means-- `(B) a semiautomatic rifle that has an ability to accept a detachable magazine and has at least 2 of-- `(i) a folding or telescoping stock; `(ii) a pistol grip that protrudes conspicuously beneath the action of the weapon; `(iii) a bayonet mount; `(iv) a flash suppressor or threaded barrel designed to accommodate a flash suppressor; and `(v) a grenade launcher;

Consequently, manufacturers and gunsmiths in the United States almost always assembled M14 type rifles with a fixed stock and lugless flash suppressor or muzzle brake while the 1994 AW Ban was in effect. After the federal AW ban expired, Springfield Armory, Inc. M1A rifles were still shipped from the factory with either a lugless flash suppressor or muzzle brake and a ten round magazine because of the various state AW bans in effect.

Canada Firearms Laws

Until about 1978, a USGI M14 rifle was treated the same as any other rifle under the law in Canada. Canada then implemented restrictions on the ownership of firearms capable

of automatic fire. Since 1992, firearms in Canada have been assigned to one of three legal categories: 1) Non-Restricted 2) Restricted and 3) Prohibited. A semi-automatic only M14 type rifle, e.g., Springfield Armory, Inc. M1A, is classified as a Non-Restricted firearm. Semi-automatic only M16 type rifles are listed as Restricted firearms. A rifle with a barrel less than 18.5 " long is also categorized as a Restricted firearm. Fully automatic and "converted automatic" rifles are both classified as Prohibited firearms. The category of Prohibited Weapon, later changed to Prohibited Firearm, was created in 1978 by passage of a bill in the Canadian Parliament. A select fire capable M14 is considered as fully automatic. A M14 that was select fire capable but rendered semi-automatic only is called a "converted automatic." Canadians may still possess USGI M14 rifles but are prohibited from shooting them and the selector shaft and sear release is welded together or the selector lug is cut off.

Effective October 01, 1998, the Firearms Act requires a Canadian firearm owner to possess a valid license, known as a Possession and Acquisition License (PAL). After obtaining the PAL, the firearm owner is required to register each firearm. A Registration Certificate for each firearm is issued to the licensee. However, registration of long guns was abolished effective April 06, 2012. To obtain a PAL, the applicant must successfully pass at least one firearms safety course, submit an application and pay a fee. The licensee must pass an additional firearms safety course and pay a higher fee to obtain a PAL that allows possession of Restricted firearms. The PAL is issued for a period of five years.

Moving a Restricted or Prohibited firearm from the owner's residence requires obtaining an approved Authorization To Transport (ATT) document from the appropriate Province Chief Firearms Officer. Regardless, an ATT cannot be approved for taking a Prohibited long gun to a shooting range. Firearms in Canada are also subject to storage, display, and handling regulations. There are also individual Province regulations and licensing for hunting activities. Interestingly, a non-resident can legally obtain a PAL and all necessary Registration Certificates and ATT documents. Effective July 01, 1993, all semi-automatic centerfire rifle magazines must be modified to accept no more than five cartridges.

Disclaimer: The reader is encouraged to research state and local laws regarding magazine feeding devices and semi-automatic firearms to avoid violating any law. Nothing in this work is to be interpreted as offering legal advice, and the author encourages anyone with legal questions to consult with an attorney, or an attorney with a government authority responsible for enforcing the relevant law(s) and who is assigned responsibilities relating to enforcement of those laws.

Part 3

All Things Small and Wonderful

M14 Barrel Material

Typically, commercial manufacture M14 type rifle barrels are made of AISI 4140 alloy or AISI 416 stainless steel. The known exception is the Chinese M14 barrel which was manufactured from equivalent AISI 1050 carbon steel. While much has been written discussing the merits of molybdenum-chromium versus stainless steel for barrels the best evidence seems to indicate that both are equal in match accuracy for at least the first 5000 rounds. Throat erosion and accuracy degradation occurs slowly and steadily in AISI 4140 barrels. AISI 416 stainless steel barrels tend to retain consistent accuracy then suddenly develop significantly larger shot groups. The advantage of the stainless steel barrel is better general surface corrosion resistance.

General Information on AISI 4140 Alloy Steel

The following information on AISI 4140 alloy steel is presented as background information. It is a medium carbon molybdenum-chromium alloy steel. Its description is as follows:

Typical Uses – This is a very common alloy steel. It is used to manufacture gears, axles, connecting rods, hand tools, etc.

Features - Toughness, good ductility and good torsional and fatigue strength

Machinability – Average surface cutting speed is 110 feet per minute. The machinability rating is 66 % of AISI 1112 in the annealed condition.

Forming – Good in the annealed condition

Normalizing – Typically heated at 1675 degrees Fahrenheit for sufficient time to ensure thorough heating then allowed to air cool

Hardening – This alloy can be hardened by 1) normalizing by heating to 1550 Fahrenheit then oil quenching then tempering or 2) annealing then cold working.

Annealing – Heat to 1600 degrees F then slowly cool in the furnace.

Forging – Forging is performed from 2200 degrees to 1750 degrees F.

Tempering – The steel is heated at temperatures ranges from 400 to 1200 degrees F depending on the hardness wanted. The lower the tempering temperature the higher the hardness and tensile strength. For example, AISI 4140 steel that is oil quenched then tempered to 1300 degrees Fahrenheit has an ultimate tensile strength of 118,000 psi. The same steel that is oil quenched and tempered to 700 degrees Fahrenheit has an ultimate tensile strength of 231,000 psi.

General Information on AISI 416 Stainless Steel

Stainless steels are alloy steels with at least 10.5 % chromium content and nickel content ranges from 0 to 22 %. Stainless steel alloys are divided into five types, austenitic, duplex, ferritic, martensitic and precipitation hardening. Each type of stainless steel has its own set of characteristics. This in turn determines the suitability for a given application. For example, martensitic stainless steels are chosen for applications where high mechanical strength is needed and corrosion resistance is not critical. AISI 416 alloy is a martensitic stainless steel. Its description is as follows:

Typical Uses – Valve parts, pump shafts, bolts and nuts, gears, electric motor shafts, gears

Features – Very good corrosion resistance, good strength, excellent machinability, poor weldability and magnetic in all conditions

Machinability – The machinability rating is 85 % of AISI 1112 steel. This alloy was the first free machining stainless steel developed. It has the highest machinability rating of any common stainless steel.

Hardening – This alloy can be hardened by heating between 1700 and 1850 degrees Fahrenheit, quenching in oil and tempering. This process first produces 100 % austenite structure followed by formation of martensite.

Annealing – For a full anneal, heat AISI 416 stainless steel to between 1500 and 1650 degrees Fahrenheit for thirty minutes per inch of thickness. Cool the steel at a maximum rate of 86 degrees Fahrenheit per hour to 1112 degrees Fahrenheit then air cool.

Tempering – First heat the steel to obtain the hardness and strength wanted. A lower tempering temperature results in higher hardness and tensile strength, while higher tempering temperatures produce lower hardness and tensile strength. When AISI 416 stainless steel is heated, oil quenched and then tempered to 1202 degrees Fahrenheit, it will have an ultimate tensile strength of 109,000 psi and a hardness of 20 HRC. The same steel that is heated, oil quenched and tempered to 399 degrees Fahrenheit has an ultimate tensile strength of 194,000 psi and a hardness of 41 HRC. Industry practice is to avoid tempering this alloy between 750 and 1076 degrees Fahrenheit because poor toughness and corrosion resistance results.

The Barrel Making Process

Barrel making is a centuries old process. Some steps in the process may not be performed in the order described herein, depending upon the method of rifling employed. To make a rifle barrel, a hole is drilled through the center of a piece of round bar stock using a gun drill. The hole is then reamed if it will be cut or button rifled or it is honed if it will be hammer forged. Reaming and honing improve the bore finish and make the interior diameter more consistent. The barrel blank is then rifled. Rifling forms the lands and grooves of the barrel at the desired twist rate. M14 barrels are typically formed with four grooves but some have five, six or eight grooves.

Rifling is performed using one of three methods: 1) cut 2) button and 3) hammer forging. Cut rifling uses a cutter to form the barrel grooves. Krieger, Obermeyer and Satern make their barrels by the single point cut method, with the tool cutting in only one groove at a time. Harrington & Richardson Arms Co., Springfield Armory, Saco-Lowell and Winchester M14 barrels were produced by the broach cut method. Badger Barrels, Inc. used this method to make the M62-R1 barrels. Button rifling involves pushing or pulling a button with lands through the blank to form the grooves of the barrel. Barrel makers such as Criterion, Douglas, Hart, Shilen and Wilson Arms use the button rifling method. In hammer forging, the barrel blank starts off shorter than the finished length. The blank has a mandrel passed down the bore then it is pounded on the exterior by opposing hammers. The barrel blank is squeezed off the mandrel and cut to the desired length. TRW made chromium plated USGI M14 barrels by the hammer forging method.

After rifling, the barrel blank will usually be stress relieved. Stress relieving can be done by heat treatment or cryogenics. When drilling removes material from the bore, stresses build up inside the barrel's remaining material. If this stress is not relieved, the barrel blank can bend during the next step in the process. Such a barrel will also not shoot well. After stress relief, the barrel blank exterior contour is formed by turning it on a profile lathe. The last major metalworking step is lapping. This is done to polish the bore, remove machining marks, and achieve the desired dimensional consistency. Bore and groove diameter tolerances will vary: a) USGI part number 7791362 - 0.001 " b) USGI part number 9345206 - 0.0001 " c) Douglas Barrels, Inc. and USGI part number 9349847 - 0.0003 ". The final machining operation is usually cutting the chamber. The barrel is stamped as desired by the maker then blued or phosphate coated if made of molybdenum-chromium alloy steel. Finished rifle barrel hardness is typically 25 to 35 HRC. For example, Smith Enterprise, Inc. M14SE 22 " and Mk 14 SEI 18 " chromium plated barrels are hardened to 35 HRC. This leaves the barrel strong enough to handle the chamber pressure with a comfortable safety factor yet tough enough to resist substantial impact.

Springfield Armory chromium plated M14 barrels were drilled, turned and plated from forged blanks. Winchester used the following procedure to make USGI M14 barrels. Re-sulphurized AISI 4150 molybdenum-chromium alloy steel was hot extruded and sheared

into barrel blanks. The barrel blanks were furnace heated and oil quenched with a twenty minute cycle time for the heat treatment. Next, the barrel blank was machined by drilling and broaching the bore then turning the exterior contour by four passes on lathes. The barrel was then prepared for chromium plating by electro-polishing the bore. The chromium plating was then applied. The chromium plating was applied 0.0015 " thick at the breech end of the rifling, with the plating thickness intentionally tapered very slightly to a thickness of 0.001 " at the muzzle. The barrel bore was finished to a bright luster. The USGI chromium plated barrel bore has a minimum hardness of 850 on the Vickers scale (better than 65 HRC). The final manufacturing step was phosphate coating.

USGI M14 barrels were fired with a proof round and then examined by magnetic particle inspection for any signs of cracks, seams or other defects. If the barrel passed proof firing and non-destructive examination, it was stamped on the chamber with the symbols M and P inside a circle. USGI chromium plated M14 barrels were designed for a service life of 15,000 rounds. The USGI M14 chromium plated barrels has a time dependent maximum rate of fire. The USGI M14 with a chromium plated barrel may be fired at the following rate without damage to the rifle or injury to the operator:

Semi-automatic: 1 minute - 40 rounds per minute (rpm), 2 minutes - 40 rpm, 5 minutes - 30 rpm, 10 minutes - 20 rpm, 15 minutes - 20 rpm, 20 minutes - 20 rpm, 30 minutes or longer - 15 rpm.

Automatic: 1 minute - 60 rpm, 2 minutes - 50 rpm, 5 minutes - 40 rpm, 10 minutes - 30, 15 minutes - 30 rpm, 20 minutes - 25 rpm, 30 minutes or longer - 20 rpm.

M14 Barrel Length

M14 barrels vary in length and contour profile but they share some common features. Both ends of the M14 rifle are threaded. The breech end threads secure the barrel to the receiver. The muzzle end threads are for securing the muzzle attachment to the barrel. Raised outside diameter surfaces locate the operating rod guide, front band, gas cylinder and flash suppressor. The M14 barrel has female splines for locating the flash suppressor and gas cylinder. The barrel gas port channels propellant gas into the gas cylinder. The barrel chamber is cut with two longitudinal grooves for securing the hand guard band. A locating shoulder serves as a rearward stop for the front band.

Troy Industries had barrels less than 16 " in length installed on Rock SOPMOD M14 units upon special request. A rifle with a barrel less than 16 " long is considered a short barrel rifle in the United States (all NFA rules apply).

USGI M14 Rack Grade Barrels

Military service barrels are made of molybdenum-chromium alloy steel. Two particular alloys were used to manufacture them, chromium-molybdenum-vanadium or

resulphurized AISI 4150. Harrington & Richardson Arms Co. and Olin-Mathieson Chemical Corporation manufactured chromium-molybdenum-vanadium M14 barrels initially. Due to the difficulty in machining this alloy, the U. S. government allowed a change in their contracts to use resulphurized AISI 4150 alloy steel for making barrels. As of August 1961, all USGI M14 barrels were being manufactured from resulphurized AISI 4150 steel. Springfield Armory never made M14 barrels from chromium-molybdenum-vanadium alloy steel. Presumably, the same could be said for TRW.

M14 rack grade barrels are chromium plated, standard (lightweight) contour and have a 1:12 twist rate. There were several manufacturers of USGI M14 chromium plated barrels. The following is a list of the manufacturers along with the barrel identifying markings and *observed* dates of production:

Harrington & Richardson (H-R) - December 1959 to February 1964
Olin-Mathieson Chemical Corporation (Winchester) - November 1960 to May 1964
Saco-Lowell / Maremont (SAK, 26978) - November 1968 to Jun 1985
Springfield Armory (S A) - May 1959 to October 1967
Thompson-Ramo-Wooldridge (TRW) - November 1962 to April 1966

Saco-Lowell - Saco-Lowell became a part of Maremont Corporation by no later than 1971. Arvin Industries, Inc. acquired Maremont Corporation in 1986. Colt's Manufacturing Company, Inc. (West Hartford, CT) owned the Saco, ME plant from late 1998 to July 2000. General Dynamics Armament Systems, a wholly owned subsidiary of General Dynamics (Falls Church, VA) bought Saco Defense in July 2000. In May 2002, General Dynamics Armament Systems purchased Advanced Technical Products, Inc. (Roswell, GA). Consequently, the division became General Dynamics Armament and Technical Products, Inc. This facility has manufactured firearms under contract for Magnum Research, Weatherby and other commercial firearms companies. The plant also produced M60 machine guns and Mk 19 40 mm automatic grenade launchers for the U. S. military. Saco-Lowell enjoys a highly favorable reputation amongst the chromium plated M14 barrel makers.

In the spring of 2005, Smith Enterprise, Inc. extensively tested its chromium plated standard contour 1:10 twist M118LR chambered 18 " barrel. Production quantities of this barrel were delivered to Smith Enterprise, Inc. beginning in March 2006. This barrel was designed for the Mk 14 Mod 1 rifle. The barrel was intended to replace barrels on rack grade M14 rifles while being able to shoot 110 to 175 grain projectiles. These barrels have a one degree crush angle and are designed to headspace between 1.6325 " and 1.6355 " on USGI M14 receivers. The exterior of the chamber is machined to provide additional gripping surface during barrel installation. Military Specification MIL-R-45012E allows removal of chromium plating to properly headspace a barrel to the receiver. Due to variations in receiver geometry among commercial manufacturers, these barrels may not headspace properly on commercial manufacture M14 type receivers.

Chromium plating of barrel chambers and bores increases barrel life, improves sustained fire capability, enhances corrosion resistance and makes cleaning easier. The chromium plated chamber aids extraction and allows the rifle to function when fouled with firing residue and dust. The disadvantages of a chromium plated bore are a slight loss of accuracy and increased manufacturing cost as compared to a non-plated bore. The loss of accuracy is not an amount the average shooter would notice. In the plating process, the anode must be centered perfectly in the barrel to avoid uneven deposition of chromium on the bore.

A typical USGI M14 barrel marking is as follows: H R 7790190 1 63 AK. H R is the manufacturer, Harrington & Richardson, Inc. 7790190 is the USGI part number for the M14 chromium plated barrel. 1 63 is the month and year of manufacture, January 1963. AK was the material lot for the steel used to make this particular barrel. Typically, the barrel manufacturer, drawing number, date and material lot are visible by simply retracting and locking the operating rod. The exception to this rule is that some Canadian Arsenals (National Match), Springfield Armory, and Winchester barrels require the hand guard to be removed to see the factory markings.

USGI M14 barrels that have passed all inspections will have the DOD acceptance stamp, magnetic particle inspection M stamp and the proof firing circle P stamp all on the chamber exterior. Canadian Arsenals manufactured M14 barrels are the exception to this rule because they lack the DOD acceptance stamp. If there is a punch mark just inside or just outside the circle of the proof firing stamp it means the barrel was removed from a M14 rifle by the military, nothing more, nothing less.

USGI M14 National Match Barrels

USGI match grade M14 barrels were made to stricter dimensional standards than the rack grade barrels. In 1963, the M14 National Match barrel bore diameter was specified as $0.300" + 0.0010"$ and groove diameter was required to be $0.3075" + 0.0010"$. Any taper in the bore had to decrease from the chamber to the muzzle. These dimensions were checked with an air gauge that had an accuracy of $0.0001"$. The M14 National Match barrel was also examined for straightness using an optical straightness gauge. The optical barrel straightness gauge was developed at Springfield Armory and was accurate to within 42 seconds of arc. The maximum deviation for straightness was 2 minutes 23 seconds of angle along the entire length of the barrel. The M14 National Match muzzle barrel was required to be free of all burrs and nicks. USGI M14 National Match grade barrels of all contour sizes were short chambered. Installation of a USGI M14 National Match barrel required finish reaming of the chamber.

According to the August 1975 *American Rifleman*, there were some chromium plated standard contour National Match barrels made at Springfield Armory in 1962 during the production run of the first 3000 M14 NM rifles. The part number for these barrels was 7791173. This was an alternative standard match barrel. It was held to the same

dimensional tolerances for the bore and groove as the non-plated National Match barrel (USGI part 7791362). The chromium plating added to the manufacturing cost but did not enhance rifle performance. Consequently, chromium plating of National Match M14 barrels was discontinued. With this one exception, match grade M14 barrels were not chromium plated.

The U. S. Army Marksmanship Training Unit tested heavyweight design match grade barrels in the mid-1970s at Fort Benning. The heavyweight barrel was found to significantly improve target group size and required much less external contour machining. The longer operating rod guide adopted in 1982 for use on heavyweight M14 barrels was originally designed by SFC Gerald "Hook" Boutin. All other factors being equal, heavyweight barrels produce tighter target shooting groups because of better resistance to vibration and elongation from prolonged firing and the forces created from sling tension over thinner contour barrels.

The National Board for the Promotion of Rifle Practice (NBPRP) approved the heavyweight design for the M14 NM rifle used in its regional and National Trophy competitions by July 1975. The NBPRP required that M14 type rifles used in competition with the heavyweight barrels had to keep the M14 sights, stocks, hand guards, gas systems and flash suppressors. In 1979, Ohio National Guard armorer, (then Staff Sergeant) John M. Miller, tested M1A serial number 010047 for accuracy in a test tunnel. The average extreme spread for ten shot groups of match ammunition fired from a machine rest at 200 yards was 5.25 " with a 1:12 twist standard contour USGI National Match barrel and 3.35 " with a Douglas heavyweight 1:10 twist match grade barrel.

Gene Barnett (using Douglas Premium blanks), Canadian Arsenals, Hart Rifle Barrels, Krieger Barrels, Mike Rock Rifle Barrels, Nomura Machine, Saco-Lowell / Maremont, SGW, Springfield Armory, and TRW made National Match M14 barrels. The following is a list of the manufacturers for standard contour National Match barrels along with the identifying mark and *observed* dates of production:

Canadian Arsenals, Ltd. (C A) - March 1967 to June 1967
Saco-Lowell / Maremont (SAK, 26978) - July 1965 to June 1985
Springfield Armory (S A) - December 1962 to ~ 1965
Thompson-Ramo-Wooldridge (TRW) - March 1964 to April 1966

Standard contour National Match barrels are capable of respectable accuracy with good ammunition. Mr. Art Luppino was able to group 0.465 " at 100 yards with handloaded ammunition (168 grain Sierra match bullets, Federal Cartridge Company cases and F210 primers, and 41.7 grains of IMR 4895 powder) on March 19, 2007 with a Canadian Arsenals M14 National Match barrel on a Springfield Armory, Inc. M1A using iron sights.

Gene Barnett was an Army National Guard armorer before going into business. He supplied the U. S. Air Force, U. S. Marine Corps and U. S. Army National Guard with M14

National Match barrels from the early 1980s onward. Barnett barrels were typically stamped with the initials of the gunsmith for whom they were made, e.g., IM stood for Isaac McCaskill (Cassatt Gun Works). Mr. Barnett retired in 2008. The Marine Corps used medium and heavyweight barrels while the National Guard and Air Force used only heavyweight barrels from Gene Barnett. The U. S. Marine Corps marked its shooting team M14 rifle barrels with the letters RTE. RTE meant Rifle Team Equipment.

In June 1981, the drawing for the medium weight contour National Match barrel, F9345206, was completed at the U. S. Army Armament Research and Development Command (Dover, NJ). The material, inspection, testing, marking, and coating requirements were essentially repeated from the lightweight National Match barrel drawing. However, the machining tolerances for the barrel bore and groove diameters were held to a more stringent limit. The medium weight NM barrel bore diameter was not allowed to vary by more than 0.0001 " over the entire length. The same restriction applied to the barrel groove diameter. The more restrictive diameter limits for the bore and the groove results in a more accurate barrel, all other factors being equal.

Schuetzen Gun Works (SGW) was established in 1956 by Bob Schuetz as a barrel manufacturer. The company moved from Colorado Springs, CO in 1975 to its new home of Olympia, WA. In 1982, the firm was renamed Olympic Arms. Dates of production observed for SGW lightweight match barrels extend from July 1982 through August 1983. The contract ended in September 1983. More than 1,200 of these barrels were produced. Its government contract required SGW to use steel from a particular vendor. The material lot numbers observed on SGW barrels were 45346 (1982 production) and 20084 (1983 production). SGW manufactured the barrels and delivered them to Rock Island Arsenal for assembly on M14 NM and M21 rifles. At that point, Rock Island Arsenal found the properties of this lot of steel to be inconsistent. This was the fault of the steel supplier and not SGW. For reasons not understood, the SGW barrels were distributed through the military supply system and some were installed on M14 NM and M21 rifles. Some of the SGW barrels failed during normal use. Consequently, the SGW barrels, installed and those in stock, were recalled and collected by Anniston Army Depot. From there, the barrels were sent back to SGW around 1984.

SGW then tested all the barrels for proper hardness. Those that passed testing were remarked OLY and sold. These OLY marked broach cut match grade barrels give excellent accuracy and service. WARNING: One of the SGW barrels that did not pass testing was tested for hardness at three positions on the exterior. The result varied from 10 to 14 HRC. This is too soft for a rifle barrel and unsafe to use. The M14 NM standard contour barrel is to be hardened to 35 HRC per the drawing. If a SGW M14 barrel is encountered it should be tested for hardness and evaluated by a reputable M14 gunsmith. The author observed an SGW M14 barrel for sale at a gun show in Phoenix, AZ in December 2003. Beware!

Nomura Machine made M14 medium weight National Match barrels in 1992 and heavyweight National Match barrels in 1992 and 1993. Saco-Lowell / Maremont made lightweight (standard), medium weight and heavyweight contour National Match M14 barrels. Maremont produced medium weight and heavyweight National Match barrels in 1983. Mike Rock Rifle Barrels, Inc. M14 barrels were made in 1994 and 1995 for the U. S. Marine Corps. The gas system was moved forward 0.035 " on these heavyweight barrels to increase the dwell time so that 190 grain bullets could be used in competition. These barrels should not be confused with the Rock Creek barrels used on the M14 DMR. Canadian Arsenals, Springfield Armory and TRW manufactured USGI M14 National Match barrels in the standard contour.

The USGI National Match barrels for the most part used a 1:12 twist. One exception was several Lackland AFB U. S. Air Force-built M14 NM rifles which were rebuilt by Ted Brown in the past for the Oregon Air National Guard. These Barnett barrels had a twist rate of 1:10 and were stamped USAF on the right side of the chamber.

A USGI contract M14 National Match barrel that has passed all quality assurance inspections will be stamped or engraved NM near the muzzle. Typically, match grade M14 type rifle barrels begin to lose competition level accuracy after 5000 to 9000 rounds depending on use and cleaning regimen. Non-plated barrels can provide rack grade accuracy as long as 12,000 rounds. The approximate weight for a medium weight M14 barrel is 2 pounds 6 ounces and 3 pounds 9 ounces for a heavyweight M14 barrel.

Chinese M14 Barrels

Chinese barrels are lightweight (standard) contour chromium plated barrels. The quality of Chinese barrels is generally very good and the chromium plating is well done. The Chinese have extensive experience in chromium plating parts because of manufacturing AK type and SKS rifles. A Chinese 22 " M14 barrel was tested in 2011 by a U. S. laboratory. Surface and core hardness ranged from 31 to 35 HRC. The chromium plating measured 0.001 " thick and had an average hardness of 851 V100. Chinese barrels are chambered for 7.62 x 51 mm NATO ammunition. Shooters have obtained 1 " groups at 100 yards with Chinese 22 " barrels. Numrich Gun Parts Corporation imported a small quantity of 17.625 " long chromium plated Norinco M14 barrels around 2002.

U. S. Commercial M14 Barrels

Commercial M14 barrels in production range from 16 " to 22 " long. Installation of barrels less than 16 " long on M14 type rifles in the United States are custom made and require registration as a Short Barreled Rifle under the National Firearms Act of 1934. Where allowed by state and local law, a bayonet lug installed on barrels 18.5 " or longer will allow normal removal of the gas cylinder plug for cleaning of the gas system.

Barrel makers, such as Douglas and Krieger, offer M14 type barrels in different twist rates and choice of molybdenum-chromium or stainless steel. The standard twist rates are 1:10, 1:11 or 1:12. Commercial match barrels will be medium weight or heavyweight. 1:10 twist barrels are better for stabilizing heavier bullets, e.g., 168 grain Sierra hollow point boat tail Match. The commercial manufacturers listed below all produce high quality M14 barrels. Springfield Armory, Inc. first assembled 1:11 twist barrels on its M1A rifles in 1978.

The first commercial barrel installed on a M14 rifle was performed by U. S. Army Sergeant Telkey at the U. S. Army MTU in the early 1960s. At the time, the U. S. Army was not sure if the National Rifle Association would approve of such a modification. Commercial and match barrel makers include Citadel, Criterion Barrels, Douglas, Hart, Krieger, Obermeyer, Shilen and Wilson Arms. Douglas Barrels, Inc. (Charleston, WV) has been manufacturing rifle barrels for over fifty years. RD Systems installed a proprietary 1:11.27 twist barrel for its Rock SOPMOD M14.

Wilson Arms Company (Branford, CT) began business in 1954. The firm has been engaged in large scale rifle barrel production since the early 1960s. Wilson Arms uses CNC machining centers to produce molybdenum-chromium alloy steel and stainless steel barrels made to customer specifications. Chromium plating of the chamber and bore is available. Wilson Arms was the supplier of standard contour and medium weight barrels to Springfield Armory, Inc. until May 2005.

Shilen Rifles, Inc. (Ennis, TX) began business in 1955. The company produces various rifle and pistol barrel blanks. For the M14 type rifle, Shilen offers 416 stainless steel .308 caliber barrel blanks in 1:10 and 1:12 twists.

Krieger Barrels and Obermeyer produce excellent quality custom barrels. Krieger Barrels, Inc. (Richfield, WI) was established in 1982 by John Krieger. The firm has manufactured M14 barrels for U. S. military branches since 1982. In 1999, Krieger formed another company, Criterion Barrels, to make rifle barrels for manufacturers such as Weatherby, Inc.

Criterion Barrels, Inc. has produced M14 barrels from 2003 onward. A typical marking was a chromium plated barrel made in November 2009: CBI 7790190-C 11/09 3L. Criterion Barrels, Inc. and Jon Wolfe, owner of M-14 Parts and Armorer Services (Columbus, NC), collaborated in September 2009 to design a new medium weight M14 barrel. The barrel used a single pin slip operating rod guide. This design change allowed the barrel diameter to taper slightly from the operating rod guide all the way to the gas cylinder. At the gas cylinder, the barrel diameter was 0.9 ". The operating rod guide profile made it flush with the top plane of the barrel. This design feature prevented contact with the hand guard. The operating rod guide was made from AISI 4140 alloy steel. The first Wolfe Modified medium weight barrels were manufactured from AISI 4140 alloy steel. They were marked 1193790 WM MW 1-11 01/10 3N. A production lot of

these barrels were manufactured from stainless steel in late 2010. The Wolfe Modified medium weight barrel weighed about 0.5 pounds more than the USGI medium weight barrel but could still be used in service rifle competition. M-14 Parts brought its Wolfe Modified Standard Weight barrel to market in October 2013. The nitrocarburized AISI 4140 alloy steel, 1:10 rate of twist, four groove barrel was available in 18.5 " and 22 " lengths. It weighed 0.40 pounds more than a USGI M14 barrel and was marked WMSW.

Olympic Arms produced some heavyweight match grade 1:12 twist stainless steel M14 barrels in 1985. They are marked with a proof P stamp, the brand identifier OLY, the letters SS and NM, and the month and year of manufacture. These should not be confused with the USGI contract standard weight barrels previously discussed.

In November 2003 Fulton Armory began selling chromium plated and non-plated commercial manufacture standard contour M14 barrels. Criterion Barrels, Inc. supplies these barrels to Fulton Armory. They are marked C.B.F.A or FA NM 7790190. Lightweight (standard contour) and medium weight M14 barrels sold by Fulton Armory are made to its specifications and come with a limited lifetime warranty on materials and workmanship. LRB Arms was selling Wilson Arms chromium plated and non-plated standard contour M14 barrels as of May 2004. These barrels were stamped, e.g., LRB 7790190 5/04 WA. Later that same year, LRB Arms began to offer Criterion 18.5 " chromium plated and non-plated standard contour barrels. Criterion chromium plated barrels assembled on LRB Arms receivers were marked in a manner similar to the USGI drawing requirement, e.g., LRB 7790190 9/05 JG CBI. The 9/05 is representative of the month and year the barrel was made. Between 2004 and 2006 Springfield Armory, Inc. had used three standard contour barrels of the same length on its SOCOM M1A models but each with a slightly different chamber external profile.

Smith Enterprise, Inc. was to be supplied with barrels from Wilson Arms for future production M14K rifles and to fulfill a 2004 request from the Philippine government for 1,400 M14 barrels. The barrels were to be made to Ron Smith's specification. This specification required the barrel to be 22 " long, four groove standard (lightweight) contour with a 1:10 twist rate and 7.62 mm Navy chamber. The 7.62 mm Navy chamber is sized for heavier bullets. Some of the barrels were to be chromium plated and some not. The firm brought its 16 " long, 1:10 twist rate four groove standard profile AISI 4140 alloy steel barrel to market in November 2010. The first lot of 16 " barrels was marked 1-10 11/10 3T.

Accuracy Systems, Inc. can install a 1.100" diameter 26" stainless steel plain end barrel on a M14 type rifle. This installation includes a modified gas cylinder and gas cylinder lock. M14 barrels installed by gunsmiths may have lettered markings such as FJ (Fred Johnson), TLC (Tom Luhmann), NM SAMA (Noah's Motors in Saugus, MA), and M.A.C. (Mark Chanlynn). Lothar Walther (Konigsbronn, Germany) manufactured match grade M14 profile barrels for the civilian market in Europe.

USGI M14 Stock Designs

The stock serves five basic functions for the M14 rifle: 1) reduces felt recoil to the operator 2) protects and holds the operating components 3) provides a comfortable gripping surface for the operator 4) allows attachment of a carry sling for hands free transport and 5) in some designs acts as a storage compartment for a cleaning kit.

The following list is a compilation of USGI M14 stock variations and the month and year of the original drawings. Different part numbers were assigned to the stocks, stock subassemblies and stock assemblies. Typically, a stock subassembly consisted of the bare stock, the ferrule, and the front sling swivel assembly and for wood stocks, the liner and two liner screws. The stock liner prevented the wood stock from cracking when the rifle was used to launch grenades. It also protected the magazine well from damage when magazines were inserted. The butt plate assembly and fasteners and rear sling swivel were added to the subassembly to form the stock assembly. The 1984 design M14 NM rifle stock lacked a stock liner and liner screws. The purpose of the ferrule was to protect the relatively thin front end of the stock.

1) September or October 1954 - T44E4: 7267084 - wood stock assembly (7267083 - bare stock)

2) September 1959 - M14: 7790702 - wood stock assembly (7790810 - stock subassembly)

3) December 1961 - M14 NM: 7791175 - wood stock assembly (7791280 - stock subassembly, 7791174 - bare stock)

4A) June 1964 - M14 NM: 11010281 - wood stock assembly with routing and bedding (11010282 - stock subassembly, 7791174 - bare stock)

4B) June 1964 - M14: 11010264 - wood stock assembly (11010262 - stock subassembly, 11010263 - bare stock)

5) December 1965 - M14: 11686428 - reinforced fiberglass stock assembly (5910348 - stock subassembly with upper butt screw, nut and retainer, 11686427 - stock subassembly, 11686426 - bare stock)

6) May 1984 - M14 NM: 9392337 - wood stock assembly with routing and bedding (9381706 - stock subassembly, 9362638 - bare stock)

USGI M14 Wood Stocks

Background Information – The information on black walnut, yellow birch and cherry wood is presented below for the benefit of the reader.

Black Walnut (Juglans nigra)

Description – The heartwood color is light gray brown to chocolate brown to purple-black brown. The sapwood is colored creamy white to yellow brown. Black walnut has a straight grain typically but the grain can be wavy or curly. Its texture is coarse. Walnut can be steamed to make the sapwood darker and the heartwood lighter which allows more of the tree to be used. Steaming is done for aesthetic purposes and does not otherwise change the properties of walnut.

Common Uses – Gunstocks, furniture, cabinets, musical instruments, and other uses. It is an excellent wood for carving and lathe turning.

Durability – Black walnut is very durable. The sapwood is susceptible to attack by the powder post beetle. The heartwood is resistant to preservative treatment and biodegradation.

Yellow Birch (Betula alleghaniensis)

Description – The heartwood color is light brown to reddish brown. The sapwood is colored light red brown or light yellow. Yellow birch has straight, close grain and a fine, even texture.

Common Uses – Furniture, high grade flooring and plywood, upholstery frames among others

Durability – Yellow birch is perishable and susceptible to attack by the furniture beetle. The heartwood is moderately resistant to preservative treatment. The sapwood is permeable.

Cherry (Prunus serotina)

Description – The heartwood color varies from red to reddish-brown to deep red. There may be brown flecks in the heartwood. The sapwood is colored creamy white to creamy pink to reddish brown. Cherry has a fine, straight grain and a smooth texture.

Common Uses – Furniture, cabinets, flooring, boat interiors, and others. It is an excellent wood for carving and lathe turning.

Durability – Cherry is moderately durable. The heartwood is moderately resistant to preservative treatment. The sapwood is susceptible to attack by the furniture beetle.

Wood blanks supplied for military small arms were inspected and sampled to meet minimum requirements for general condition, grain slope, moisture content, end coating, and contractually specified dimensions. Wood blanks were inspected to be free of splits, honeycombing, brashness, checks, shakes and excessive warping and shrinkage.

Defects such as sapwood, mineral streaks, burly grain and a limited amount of sound pin knots and pinworm holes were allowed. The grain slope for M1 and M14 rifle stock wood blanks could not vary more than 1 " from the horizontal for any 12 " in length in the critical area. The critical area for M1 and M14 rifle wood stock blanks was defined as the forward 26.5 " + or - 1" of the blank. Average moisture content for kiln-dried blanks was limited to 6 to 8 percent. Air-dried wood blanks could not have more than 25 percent average moisture content. Green wood blanks had no limits for moisture content. Both ends of every wood blank supplied were required to be coated to control split ends. If the number of unsatisfactory blanks examined exceeded the allowable number for a given lot size, the entire lot was rejected. Regardless, any unsatisfactory condition specimen was not accepted. Kiln-dried wood blanks were sampled for case hardening. No more than two of the fifty-four specimens of each kiln charge were allowed to fail the case hardening test. If so, the entire kiln charge lot was rejected.

USGI Wood Stock Production - Springfield Armory, Harrington & Richardson, and Winchester made wood stocks for their USGI M14 rifles. Frank Overton was the owner of S. E. Overton Co. (South Haven, MI). This company was the largest employer in South Haven, MI when it went out of business in 1990. From World War II until 1990, S. E. Overton Co. produced M1 Carbine, M1 Garand and M14 stocks and M1 Garand hand guards. It was the exclusive supplier to TRW for walnut and birch M14 stocks. Early S. E. Overton Co. M14 stocks were made from black walnut but most were made from birch harvested from a single forest in Maine near the Canadian border. The black walnut wood came from the U. S. government stockpile. The wood was shipped at government expense to S. E. Overton and formed on government owned stock making machinery operated by S. E. Overton Co. employees. The automatically operated multi-station machines performed all woodworking operations except the finish sanding. Overton birch M14 stocks tend to be stained a very dark brown. The production rate for these machines was 400 stocks per hour. The M14 stock making machinery was converted around 1971 or 1972 to produce M1 Garand stocks for a new government contract. S. E. Overton Co. was still producing M1 Garand stocks and inventoried contract over run M14 stocks when it closed down in 1990. S. E. Overton Co. had also manufactured match grade M14 stocks for Karl Maunz. A wood furniture manufacturer, H. Sacks & Sons, Inc. (Brookline, MA), made replacement M14 stocks for Springfield Armory.

The basic process of making a wood gun stock can be divided into four steps. A rectangular piece of wood is first shaped to create the rough exterior outline of the stock. Next, the interior geometry of the stock is formed with inletting tools. Finish work creates the final dimensions of the stock. Lastly, the stock is sanded to remove splinters and rough texture. The first M14 stocks were made of black walnut. During the first half of 1961, yellow birch was the standard wood with black walnut as the alternate. All four manufacturers each used black walnut and yellow birch stocks to assemble M14rifles.

Some wood USGI M14 stocks have a raised shelf at the base of the firing mechanism inletting. Ferrules, the piece of metal at the very front end of the stock, on wood USGI

stocks are either dimpled (round punch mark on the sides) or crimped (half-moon indentation on both sides). Both means of staking the ferrule were employed by Springfield Armory, H. Sacks & Sons, Inc. and Winchester. Harrington & Richardson and S. E. Overton Co. used the punch method. Standard size wood stocks were made from 1959 to 1963 and later depending on the drawing number. In contrast with the high degree of automation in all other production processes for the M14 rifle, the USGI wood stock makers all hand sanded every stock one at a time with a rotary sander. This was done to smooth the stock and ensure that all surfaces were true and all corners sharp. Due to naturally occurring differences in density of wood, the yellow birch and black walnut M14 stocks weighed between 31 and 38 ounces. USGI M14 wood stocks were made with steel liners fitted around the magazine well. This feature was incorporated into the T44 and T44E1 rifle designs in 1953 to prevent the stock from splitting when launching grenades. Military Standard MIL-STD-1270A(WC) is the repair procedure for M14 and M14E2 wood stocks.

USGI Wood Stock Markings – USGI manufacturers' markings were often stamped in the butt end of the M14 wood stocks as follows: H for Harrington & Richardson, O for S. E. Overton Co., S A for Springfield Armory, S under a half-diamond for H. Sacks & Sons, Inc. and W-W for Winchester. Some Harrington & Richardson and Springfield Armory M14 wood stocks were stamped with a number, e.g., 1, 3, or 5, on the butt end along with the manufacturer stamping. Mathewson Tool Company and Springfield Armory made T44E4 stocks but not all were stamped with the manufacturer marking. Some T44E4 stocks were marked S A under the butt plate and had the DOD cartouche. Other T44E4 stocks were marked O under the butt plate and were proof fired. The 1966 Springfield Armory inspection procedure required the M14 NM stock to be identified with the last four digits of the receiver serial number.

M14 and M14 NM wood stocks were marked with a ½ " high DOD cartouche, also referred to as a Defense acceptance stamp, on the left side near the receiver and a proof mark on the underside of the grip if they passed final ordnance inspection and proof firing, respectively. A DOD cartouche inside a circle on the left side of the butt stock near the rear sling swivel has been observed on a small number of USGI wood stocks. A smaller DOD cartouche is often stamped in the firing mechanism inletting area of Winchester M14 stocks. The proof firing stamping in original assembly was a 5/16 " high letter P inside a ½ " diameter circle that was stamped on the forward side of the stock grip. Either of two types of letter P proof marks were used, one with a serif font P and the other with an Arial-style P. S. E. Overton Co. used the Arial style proof marking. If a rifle was rebuilt and proof fired at an arsenal or depot in the 1960s, the stock was stamped with a letter P inside a square. The circled letter P marking appeared on U. S. military rifles from 1873 until the end of M14 production in the 1960s.

Before final assembly, each wood stock was dipped in tung oil. The walnut stocks were dipped twice but the birch stocks only once. It was found during the first half of 1962 that two coats of oil left excessive oil and residue on the birch stocks due to that wood's

different grain characteristics and slower absorption of oil as compared to walnut. Consequently, the procedure was changed to one coat of oil for birch stocks. Commercial producers of the USGI M14 rifle sprayed a stain on the birch stocks prior to the dipping in oil. This produced a color very close to that of black walnut. After several days of draining and drying, sample stocks were tested for resistance to smoke and water before the rest of the lot was approved for oil treatment and final assembly. TRW was assembling its M14 rifles with birch stocks in the fall of 1962. The last M14 rifles assembled with wood stocks left the commercial manufacturers in July 1963. Birch is stronger and harder than walnut. Walnut is about 10 % lighter than birch.

A few cherry stocks were made as well. Some beech M14 stocks with the selector cutout were available in the civilian market in 1973. Reportedly, the beech stocks were manufactured by Reinhart Fajen, Inc. but this has not been confirmed. Springfield Armory was not the source of the beech M14 stocks. The Armory only used walnut and birch for making M14 stocks. Wood M14 stocks will not become too hot to handle if left in direct sunlight but the preservative, tung oil or linseed oil, will be drawn out. The walnut M14 stock will burn after 1 minute 20 seconds of exposure to an open flame.

The 1984 design National Match stock (part number 9352638) can be made with the following materials: 1) black walnut 2) English walnut 3) yellow birch 4) sweet birch 5) laminated layers of black walnut 6) laminated layers of English walnut 7) laminated layers of yellow birch 8) laminated layers of sweet birch 9) sycamore 10) pecan 11) black locust 12) maple 13) red birch or 14) heat-moulded plastic. The plastic moulded stock must weigh a minimum of 2.5 pounds and have color Forest Green number 34079 per FED-STD-595.

Replacement Stocks - Most replacement USGI wood stocks will not have the proof P and DOD cartouche markings. Replacement M14 stocks from Springfield Armory, however, were stamped with the DOD cartouche. Some of the Springfield Armory National Match M14 walnut stocks were bedded to a gage rifle. Springfield Armory National Match M14 walnut stocks were given the DOD cartouche and proof P markings. Springfield Armory shipped both bedded and non-bedded National Match M14 walnut stocks.

Winchester and H. Sacks & Sons, Inc. National Match "big red" birch M14 stocks have the part number 11010263 stamped into the wood under the butt plate. A number of the Winchester stocks were stamped with the DOD cartouche and proof P markings but with the cartouche placed on the left side of the butt stock. Other H. Sacks & Sons, Inc. wood stocks were stamped with the part number 7791174 on the butt end. These were replacement National Match stocks. Replacement USGI M14 wood and synthetic stocks were packaged without the hardware with the exception of the ferrule and sometimes the liner and screws for the wooden models. A square shaped piece of plastic was installed in the hinge area and two pieces of thin wood, one on either side inside the packaging, were used to protect the stock during transport and storage. The butt hinge protectors are gold or white in color and have the part number 7791050 centered on the top surface.

Around 1982, oversized stocks were allowed for competition at Camp Perry. Quickly, oversized walnut, birch and laminated wood M14 stocks became popular among military and civilian shooters. Solid wood USGI stocks are sought after for the appearance and historical authenticity. However, solid wood tends to swell or contract with changes in ambient temperature and humidity.

Laminate stocks were in use as early as World War II when Nazi Germany fielded Steyr K98 rifles with wood laminate wood stocks. Wood laminate stocks are made by gluing layers of wood together to create a rough form that could be worked into a finished rifle stock. This composition of wood and glue is very strong and resistant to impact. Yale University performed destructive testing in 1954 on wood laminate gun stock blanks. Laminated wood stocks are slightly heavier than solid wood stocks but they are more resistant to temperature and humidity fluctuations. They can be bedded just like solid wood stocks.

Reinhart Fajen began making wood gun stocks in the 1950s at his facility in Warsaw, MO (1963 address Box 338 Warsaw, MO). His craftsmanship earned a well-deserved reputation among hunters. After 1992, Reinhart Fajen, Inc. grew rapidly with the purchase of another stock maker, E. C. Bishop & Son, Inc. (119 Main Street Warsaw, MO 65355). Reinhart Fajen produced factory issue stocks for rifle manufacturers such as Sturm, Ruger & Co. and Savage Arms Company. Reinhart Fajen Acquisition, Inc. made M14 stocks from 1988 to 1990 for two U. S. Army contracts. Some of the stocks were ink stamped 9352638 and 77742 under the butt plate. Fajen made three styles of M14 stocks in two materials, walnut and laminated wood. Style I was the USGI standard contour and Style III was the oversized National Match stock (USGI part number 9352638). The Fajen oversized National Match stocks did not have stock liners but were routed for the rear lug and made to be bedded. Fajen M14 stocks supplied to the U. S. government for the First Gulf War were shipped to Rock Island Arsenal for cutting the selector cutout, preserving and packing before stocking in the DOD supply system.

Unfortunately, Mr. Fajen passed away in 1998 and the company struggled thereafter. Reinhart Fajen, Inc. was then acquired by the Potterfield Group. The Potterfield family made a valiant but unsuccessful attempt to turn a profit from the plant which had moved earlier to Route 1 Box 214A Lincoln, MO 65338. Manufacturing operations were suspended in Lincoln, MO by the fall of 1998. Production of stocks for other rifles was then contracted out to several companies around the United States using proprietary CNC software programs. The equipment and inventory was sold off. Boyds' bought the stock inletting equipment from Reinhart Fajen, Inc. Springfield Armory, Inc. bought half of the remaining inventory of M14 stocks and Midway USA purchased the remainder. All of the stocks, including the M14 models, quickly sold out once it was known that the Lincoln, MO plant had ceased operating. Springfield Armory, Inc. installed stocks made by Reinhart Fajen, Inc. on M1A rifles until at least January 1999.

As of 2004, Battenfeld Technologies, Inc. continued to manufacture this line of stocks for rifles other than the M14 type. Midway USA was originally started as a local gun shop in Ely, MO in 1976 by Larry and Brenda Potterfield. The business grew rapidly so that by 1983 it was strictly a mail order company. By 2007, Midway USA employed 250 people and occupied a 100,000 square foot facility in Columbia, MO. Battenfeld Technologies, Inc., a product development company for the shooting sport, is headed up by their son, Russ.

USGI M14 Synthetic Stocks

The purpose for development of a synthetic material stock for the M14 rifle was two-fold: 1) to avoid a single supply source or single type of material for the stock and 2) to avoid the varying quantity and quality of walnut wood. As a result of testing performed in 1961, the U. S. Army Infantry Board expected that synthetic material stocks would last twice as long as those made from walnut and that pricing for the synthetic stock would compete with walnut stocks.

Experimental and production versions of the synthetic stock were fiberglass reinforced polyester plastic shell halves glued together with polyurethane foam filling in between. Experimentation with synthetic material stocks began in the late 1950s for the M14 project as at least two T44E4 rifles were fitted with black color man-made material gunstocks. James S. Lunn and others patented a reinforced fiberglass M1 Garand rifle stock in 1959. Lunn Laminates (NY) made a number of M1 reinforced fiberglass stocks. Synthetic material stocks for the M1 and M14 rifles were evaluated by the U. S. Army Infantry Board during the first half of 1960. Due to similarity with the Lunn design M1 stocks, the firm may have been involved in the 1960 development for the M14 reinforced fiberglass stock but this has not been confirmed.

General Tire & Rubber Company joined Springfield Armory in 1960 in conducting research to develop a synthetic stock for the M14 rifle. Development of this lighter, stronger stock made of fiberglass reinforced polyester plastic for the M14 proceeded in stages from 1960 until late 1965. The drawing for the final version M14 fiberglass stock is dated December 1965. Beginning in 1962, fiberglass stocks were installed on M14 rifles at the factory but it was not by Springfield Armory. The following year, Springfield Armory produced a single batch of 10,000 M14 rifles in October 1963 with synthetic material stocks.

The early synthetic material stocks had no checkering and the hole for the upper butt plate screw had a wood insert to which the wood stock upper butt plate screw was anchored. These early issue synthetic stocks were milk chocolate brown in color. At least some of these early stocks were marked on the inside of the magazine well as follows: right side top line - DM-1775-GB-2, right side bottom line - DT, left side top line - DT and left side bottom line - DM-1775-GB-1. Later-manufacture fiberglass stocks were assembled with an upper butt plate screw with a finer thread. The later upper butt plate

screw is anchored to a steel nut held inside a metal bracket inside the stock. 1961 pre-production synthetic stocks were found satisfactory for mounting the M15 grenade launcher sight. If a M15 grenade launcher sight was mounted on a 1961 synthetic M14 stock, the screws had to be mounted about 1/8 " lower than what was done on the wood stock. This was to avoid protrusion of the top screw into the magazine well creating interference with fitting the receiver. This fitment issue was solved by the time the 1965 design was drawn up.

Stock ferrules on synthetic USGI stocks are either crimped or dimpled but the dimpled ferrules are not common. Military Specification MIL-S-45921A and drawing F11686427 require the ferrule to be cemented and crimped to the stock to prevent movement. Thus, it appears that dimpled ferrules are earlier production stocks. While not common, some USGI synthetic stocks were marked at the factory with the Defense Acceptance Stamp using a steel die.

The USGI M14 synthetic stock was designed and tested for ruggedness. Forty sample stocks were selected by the U. S. government representative during initial production and monthly thereafter. Any failure of any test of any sample stock meant the day's production or the represented batch was rejected.

Ten tests were conducted on each sample lot of production fiberglass reinforced plastic stocks: 1) physical examination 2) functioning firing 3) targeting and accuracy 4) adhesive and foam 5) twist 6) shock resistance 7) shock resistance endurance 8) low temperature shock resistance 9) low temperature abuse and 10) heat resistance. Some tests were conducted on all forty sample stocks, e.g., visual, functioning firing and targeting and accuracy. Most of the tests though were conducted on a portion of the sample lot. For example, twist testing was performed on five stocks and shock resistance was tested on ten stocks in each sample lot. The sample stock testing is briefly reviewed here:

Physical Examination – The sample stock was examined for proper assembly and measured for compliance to specified dimensions at several points. Both sides of the synthetic stock were tested twice each at the butt, the receiver and the forearm areas for hardness for a total of twelve readings per stock. The readings were required to average a minimum of 50 Barcol. The Barcol scale is used to measure the hardness of reinforced and non-reinforced rigid plastics.

Functioning Firing – The stock was assembled with other components to make a complete M14 rifle. The rifle was placed into a fixture to simulate offhand firing. The rifle was test fired using two full twenty round magazines in both semi-automatic and automatic using M59 or M80 ball ammunition.

Targeting and Accuracy – Again, the sample stock was made part of a complete M14 rifle and placed into a test fixture. The rear sight aperture was set at eight clicks from bottom and zero windage. The rifle sights were aligned at the six o'clock position on a target and

fired for ten rounds. The results of the sample lot of forty synthetic stocks were compared to the targeting and accuracy results of forty wood stocks known to be satisfactory. The targeting and accuracy results of the synthetic stock sample lot had to equal or exceed those of the forty wood stocks to pass.

Adhesive and Foam – The stock was sectioned by cutting at a minimum of eleven specified areas along the length of the stock. The foam was examined for any presence of voids. The specific requirement was that the foam fill had to be free of voids more than 10 % of the total volume with none more than ¼ " in diameter and no more than one void per two cross-sectioned areas.

Twist – The sample stock was mounted into a test fixture and torqued to 40 ft-lbf once each in the clockwise and counterclockwise directions. The stock was visually examined for any defects.

Shock Resistance – The stock was assembled with other components to make a complete M14 rifle. The M76 grenade launcher was attached to the flash suppressor and the spindle valve turned to the horizontal (gas cutoff) position. The rifle was placed into a fixture. With the toe of the butt stock at 45 degrees, five practice anti-tank grenades were launched using M64 grenade cartridges. The sample stock was then removed from the rifle and examined for any defects or signs of damage.

Shock Resistance Endurance – Three of forty stocks in each sample lot were selected for this test. It is performed in the same manner as the shock resistance test but 100 rifle grenades are fired instead of five using each sample stock.

Low Temperature Shock Resistance Test – This test was performed just like the shock resistance test except the rifle was kept at – 65 degrees Fahrenheit + or – 5 degrees for three hours before and then during the test.

Low Temperature Abuse Test – The sample stock assembled into a complete M14 rifle was stored at – 65 degrees Fahrenheit + or – 5 degrees for three hours then dropped from a height of 3 feet on to a hardwood bench. The test was repeated so that the stock would impact at different points (left side, right side, and butt stock toe and heel) on the bench. After this, the rifle was allowed to swing 90 degrees by its own weight from a horizontal position, while held at the muzzle, so that the stock would hit the flat side of the hardwood bench. This was repeated so top, bottom and both sides of the stock impacted the side of the bench.

Heat Resistance – The sample stock was assembled into a M14 rifle with the bolt, firing mechanism and operating rod spring removed. The test rifle was placed in a stand to hold it in the horizontal position. A 115 Volt AC, 1000 Watt heating rod with an effective heating length of 24 " was placed inside the barrel. The heating rod was connected to a variable voltage control. A thermocouple was attached to the top of the barrel about

10.5 " from the end of the muzzle. The thermocouple was wired to a pyrometer to indicate the barrel temperature during the test. By increasing the voltage applied to the heating rod in stages, the rifle barrel temperature was brought up to 1200 degrees Fahrenheit. At that point, electric current flow through the heating rod was stopped and the barrel cooled to ambient temperature. The stock was then examined for any damage.

USGI M14 synthetic stocks have the letters DT as well as other alphanumeric characters in the magazine well area. A small gap between the middle portion of the receiver and the stock is normal for USGI wood and synthetic M14 stocks, but is more noticeable on many fiberglass stocks. The USGI synthetic M14 stock itself weighs 34 to 39 ounces. A USGI M14 synthetic stock with all the correct metal hardware weighs 44 to 49 ounces. The USGI M14 synthetic stock will become too hot to hold if left outdoors for as little an hour in the direct sun. If the synthetic stock is brought into the shade for two minutes or more, it will cool sufficiently to be comfortable to handle. The USGI M14 synthetic stock will burn after 2 minutes 10 seconds of exposure to an open flame. Both wood and synthetic M14 stocks are strong enough to break the operator's fall to a prone shooting position from a run. Each type of stock will withstand fifty vertical butt strokes against a test dummy but will suffer damage in less than fifty horizontal butt strokes against the same butt stroke dummy. The damage is likely to occur in the firing hand grip area of the stock. USGI M14 synthetic stocks have always been allowed for competition at Camp Perry.

USGI synthetic M14 stocks were made as late as 1969. The U. S. Army awarded a contract to General Tire & Rubber Company in October 1966 for 500,000 synthetic M14 stocks to be used as replacement parts. At about \$4,883,000.00, it was the single largest dollar amount ever awarded for production of a M14 rifle part or accessory. According to an employee working at the lab during the period, a product improvement program had been written up for the M14 synthetic stock at the General Thomas J Rodman Laboratory at Rock Island Arsenal in the early 1970s. In 1972, the Army reorganized the arsenal system. As part of the reorganization, the Rodman Laboratory staff was reduced from 125 employees to a skeleton crew of twenty-one. The M14 stock improvement program never went any further.

USGI M14E2 Stocks

The M14E2/M14A1 rifle was fitted with a walnut or birch straight-line stock. At least one laminate wood M14E2 stock was made and it was issued for service. At least 10,350 M14E2 stocks were made in the 1960s. At least 8,350 M14E2 stocks were produced in 1963 and 1964 and another 2000 or better about 1967 or 1968. The first M14E2 stocks were made in late 1963. Most of the M14E2 stocks were made of birch at Canadian Arsenals Limited in Long Branch, Ontario, Canada in 1964 to support the M14E2 conversion project at Springfield Armory.

Canadian Arsenals Limited produced Browning pistols, Sten submachine guns and other military equipment during and after World War II. In 1986, the Canadian government privatized its Crown corporation, Canadian Arsenals Limited, by sale to the SNC Group for \$Cdn 92,000,000. By 2001, SNC Group was known as General Dynamics Ordnance and Tactical Systems-Canada, Inc. Long Branch is a suburb of Toronto.

The few walnut M14E2 stocks were made at Springfield Armory, Rock Island Arsenal and Anniston Army Depot. Springfield Armory walnut M14E2 stocks have the DOD cartouche but Canadian Arsenals birch M14E2 stocks do not. Winchester made at least one cherry M14E2 stock. H. Sacks & Sons, Inc. made 2,000 or more birch M14A1 stocks in 1969. These stocks were manufactured without the fore grip and butt plate assemblies. This batch of stocks was released to the public around 1978 or 1979. They were sold with commercial reproduction fore grip and butt plate assemblies. The reproduction M14E2 butt plate bracket assemblies were made by casting.

In 1971, surplus parts dealer Pete Michaels (Batavia, IL) bought more than 3,000 M14A1 stocks without hardware and more than 200 M14A1 stocks with hardware. Springfield Armory, Inc. sold M14E2 birch and walnut stocks before 1994. Jack Dailey, owner of Fred's (Ramseur, NC), was the winning bidder in 2000 on a U. S. government auction of 2,701 M14E2 stocks.

The USGI M14E2 stock has a selector cutout, rubber and steel recoil pad, smooth surface flip up butt plate, a pistol grip and rubber coated aluminum fore grip. The fore grip locks into place when in use. It retracts and swings upward towards the operator by pulling on a latch on the rear side of the grip. The position of the fore grip is adjustable. A medium weight or heavyweight M14 barrel will fit in an M14E2 stock with no problems. In 1966, a barrel channel backing plate was added to better secure the fore grip.

Commercial Synthetic Match Grade Stocks

McMillan Fiberglass Stocks, Inc. – As a boy, Gale Alvin McMillan became an excellent marksman by hunting rabbits to help provide food for the family. He became a bench rest competition shooter in 1958 and enlisted in the U. S. Air Force the same year. During ten years of military service, Gale McMillan shot competitively and worked on rifles for other competitors. After the service, he settled in Phoenix, AZ and was employed in the plastic mold making industry. He applied his knowledge and experience to start making fiberglass rifle stocks in 1973. He started his own company in 1975 producing fiberglass rifle stocks and building rifles. Around 1986 or 1987, McMillan Fiberglass Stocks began using CNC machine tools in its manufacturing operation. Through the years, Gale was assisted by his wife, Gloria, and other family members in the day-to-day operations of the business. In 1987, their sons Kelly and Rock, bought and took over the stock making business. Sadly, Gale McMillan succumbed to cancer on May 29, 2000. McMillan Fiberglass Stocks, Inc. has brought many creative designs to the gunstock market.

McMillan Fiberglass Stocks made its stocks from multiple layers of epoxy resin laminated woven fiberglass cloth. The fore end was filled with epoxy and glass beads. The butt stock portion was filled with urethane foam from the rear of the grip to 2 " forward of the butt end. The purpose of the urethane foam filling was to absorb recoil vibration and help deaden the sound of firing to the shooter. McMillan Fiberglass Stocks developed its M1A stock in the 1980s to meet the request from the U. S. Marine Corps for a more durable M14 stock. Around 1987, the McMillan M1A stock design was changed to lengthen the grip and eliminate the stock liner screw depressions. McMillan offered three models of fixed butt stock synthetic stocks for the M14 type rifle, M1A, M2A and M3A. The obvious difference between the three models was the grip style but required bedding to the rifle's receiver and firing mechanism before use. The stocks could be fitted with or without a steel liner and were available in several colors from the factory. The M2A and M3A models had adjustable cheek pieces. For 2010, McMillan introduced a second version of the M3A stock, the ADJ M3A. The ADJ M3A stock housed an integral adjustable cheek piece which allowed for horizontal and vertical adjustment. The ADJ M3A cheek piece could be set using two thumbscrew lock posts or an optional thumbwheel mechanism. The McMillan M1A stock was a traditional design sized for heavy barrel M14 type rifles and is the most common choice of stock for U. S. Army M25 rifles. McMillan M2A stocks have been fitted on M25 rifles for the Army 10th Special Forces Group and M14 DMR rifles for the U. S. Marine Corps. The U. S. Navy SEALs built its M14 SSR rifles with McMillan M3A stocks. The M2A and M3A stocks are not allowed to compete as Service Rifles per the rules for Director of Civilian Marksmanship and NRA High Power Competition matches, but may be used in NRA High Power Rifle competitions as a Match Rifle (a class usually populated by shooters using bolt action rifles).

Bell and Carlson - Bell and Carlson is a designer and manufacturer of synthetic material rifle stocks. It offered a M14 rifle stock in 2005 and 2006 in its special purpose line of stocks (catalog number C190). The stock was built with structural urethane, aramid, graphite and fiberglass in a choice of seventeen finishes. The stock accommodated a heavyweight contour barrel and the magazine well was flared to facilitate quick magazine changes.

Warbirds Custom Guns - In November 2007, Warbirds Customs Guns made available a mixed material match style stock for the M14. These stocks were made of fiberglass with an internal aluminum skeleton from the receiver area to the fore end. Options included a metal stock liner and inletting for a receiver rear lug. Stocks without the liner required bedding behind the receiver lets in order to provide a recoil bearing surface. The stocks were sold with a lifetime warranty as long as any adjustments or modifications were done by Warbirds Custom Guns. The Warbirds Custom Guns M14 stock had a semi-target pistol grip, weighed just under 3 pounds and was available in a choice of colors.

Commercial Folding and Telescoping Stocks

Folding and telescoping design stocks have been commercially available for the M14 type rifle since at least 1978. States such as California, Connecticut, Massachusetts and

New York prohibit or regulate installation of folding or telescoping stocks on semi-automatic centerfire rifles capable of accepting a detachable magazine, e.g., M14 type rifles. There may be other states and municipalities with restrictions on the installation of folding or telescoping stocks. Consult state and local laws before installing these stocks.

When purchasing a folding or telescoping stock for the M14 type rifle, the end user should determine what features and capabilities are important for its intended use. The following criteria should be evaluated for each model when selecting a high end commercial M14 stock: 1) ability to use iron sights 2) available rail space over the receiver 3) adjustment of the butt stock length-of-pull 4) ease of field stripping 5) ability to accommodate different barrel contours 6) flexibility in mounting night vision and daylight optics and other accessories (flashlight, vertical fore grip, etc.) 7) accuracy enhancement 8) receiver-to-stock fit including the ability to accommodate select fire components 9) balance of the rifle when fully configured and 10) operator comfort.

1978 Commercial M14 Folding Stock – About 1978, Wayne Young (then 4723 Marino Street Columbus, GA) manufactured and sold a BM59 Alpine style folding stock for the M14 type rifle. He sold ninety-eight of these high quality M14 folding stocks. The folding butt stock mechanism was fabricated by arc welding steel tubes and steel plates together. The upper horizontal tube of the butt stock was 0.9 " in diameter. The folding butt stock was phosphate coated then covered with several layers of black color vinyl. The thick vinyl covering of the wide upper bar made a firm and comfortable cheek weld possible. The butt stock was folded to the right side by pushing a friction latch, on the left side of the stock, outward from the stock and moving the butt stock to the right. The folding butt stock mechanism was mated to a modified M14E2 stock subassembly behind the receiver heel. The folding stock weighed 3.2 pounds. Length of pull for the folding stock was 14 ". With the butt stock folded, the overall length for a 22 " barreled rifle was 36 ". Thomas A. Buss, a surplus small arms parts dealer hailing from Springdale, PA, bought eighty of these folding stocks. The remaining stocks were sold to various individuals.

Springfield Armory, Inc. offered commercial M1A-A1 folding stocks in the 1980s and early 1990s. The company made three versions of the M1A-A1 folding stock. The first version was either a modified M14 or a modified M14E2 stock. These stocks were cut just behind the receiver well, where a Beretta BM59 Alpine metal butt stock was added. These BM59 butt stocks had butt plates with a rubber pad on the upper half of the butt plate and two braces for supporting the butt plate. The first version M1A-A1 stock often used a modified M14 stock and had a Beretta BM59 plastic pistol grip added to it, rather than starting out as a M14E2 stock. The plastic pistol grip had a storage space accessed by a metal cover on the bottom. The first version of the M1A-A1 stock may or may not have the selector cutout because it originated as a USGI stock. M1A serial number 0663XX, built in the fall of 1991, was assembled with a Beretta BM59 Alpine folding stock mated to a commercial walnut stock and Beretta BM 59 plastic pistol grip with the metal cover.

The second version of the Springfield Armory, Inc. folding stock has the same BM59 butt stock folding mechanism as the first version but does not have the lower butt plate supporting brace. It has a hardwood pistol grip and full length rubber butt pad. The butt pad itself will fold up against the single metal brace. On the second version, the supporting brace, butt pad assembly, and hardwood pistol grip were commercially manufactured parts. The second version M1A-A1 folding stock was made with either a modified BM59 stock or a USGI M14 stock. If a modified BM59 stock was used there will be no selector cutout and the front end sling swivel was left on the left side. If a M14 stock was used to build this version of the folding stock, the selector cutout and front end bottom side sling swivel were left as is. This version was available from Reese Surplus, Inc. (Colona, IL) as a modified Beretta BM59 folding stock fitted to the M1A or M14. The company sold this version in the past with a M14 wood stock as the base for the assembly. Reese Surplus, Inc. closed its business in December 2010.

Springfield Armory, Inc.'s third version of a M1A folding stock was a Choate Machine & Tool, Inc. plastic butt stock folding arm with steel hinge, mated to a truncated USGI M14 stock. The folding arm mechanism was attached by two large screws to either a M14E2 stock without the selector cutout filled in or a synthetic M14 stock with an added synthetic pistol grip and the selector cutout filled in. The third version synthetic material folding stocks were black color with a textured surface and a full length rubber butt pad. This type of folding stock was assembled to M1A serial number 081239 in mid-1994 at the factory. The inside of the butt plate on the Choate Machine & Tool folding arm was marked as follows: first line – CHOATE TOOL CO. second line – BOX 218 third line – BALD KNOB, ARK. fourth line – 72010. Springfield Armory, Inc. sold the third version folding stocks as late as 1999 with the instruction that they were to be installed on rifles assembled prior to September 13, 1994, in compliance with the 1994 Assault Weapons Ban still in effect at that time.

Choate Machine & Tool, Inc. (Bald Knob, AR) began operation in 1972. Choate Machine & Tool produces gun stocks and other firearms accessories. The company brought back its side folding stock in the spring of 2012. The Choate spring loaded folding stock mechanism and pistol grip were mated to the factory Springfield Armory, Inc. injection molded M1A stock. The cast metal butt stock arm was coated with polyethylene and fitted with a recoil pad for shooter comfort.

In 2005, Springfield Armory, Inc. introduced the M1A SOCOM II LE model. This rifle was fitted with a Vltor Weapon Systems M14 Modstock. The Vltor M14 Modstock (model number M1S-1) was a collapsing butt stock and pistol grip mated by a machined aluminum adapter to a USGI reinforced fiberglass M14 stock. The Vltor M14 Modstock could be raised or lowered 1 " in height for better alignment between the shooter's eye and any mounted optical sight. The height of the M14 Modstock could be adjusted by loosening, moving up or down, and then tightening a 3/8 " hex head bolt at its front end. The five-position collapsing butt stock allowed the length of pull to be adjusted from 10.5 " to 14 ". The butt stock had ambidextrous connections for installing a sling swivel. Both

the butt stock and pistol grip had storage compartments. The Vltor M14 Modstock was available in black, flat dark earth (tan) or olive drab green. It could not be fitted to select fire M14 type rifles as the selector cutout was filled in. The right hand side of the aluminum adapter is laser engraved with a code and serial number. As an option, the Vltor collapsing butt stock assembly could be replaced with its fixed length A1 Modstock. The Vltor pistol grip could also be swapped out for other makes of M16 style grips.

In June 2007, Vltor Weapon Systems introduced the Enhanced Modstock butt stock in black (M1S-1E), flat dark earth / tan (M1S-1ET) and green (M1S-1EG). The Enhanced Modstock was an improved design over the legacy Modstock. It had a 1 " longer available length of pull, longer storage compartments, new reinforcement around the latch pin, and an aluminum plate under the rubber butt pad to better distribute the load if the rifle was used for butt strikes. Like the original Modstock, the Enhanced Modstock could be adjusted up to 1 " vertically and had five length-of-pull positions. For 2011, Vltor added Enhanced Modstocks for select fire rifles (models M1S-2E, M1S-2ET and M1S-2EG). In its 2010 catalog, Vltor announced an adapter kit for Sage International, Ltd. M14 EBR stocks. The adapter kit replaced the original butt stock components with a Vltor Weapon Systems Enhanced Modstock assembly and pistol grip. The adapter kit was offered in black (RE-EBR), tan (RE-EBRT) and green (RE-EBRG).

SparrowHawk Stocks - In the fall of 2003, SparrowHawk Stocks introduced the M-14CM4 stock to the market. The M-14CM4 stock is the mating of a M16 type four-position telescoping stock and pistol grip to a synthetic M14 stock for use on M14 type rifles where allowed by law. State and local law may allow installation of this stock if the butt stock is fixed and a muzzle brake is permanently installed. Consult state and local laws before installing this stock. A lower front hand guard and M1913 Picatinny style accessory rails are optional. Colors available were black, white, olive drab and earth brown.

Rock SOPMOD M14 Stock - The Rock SOPMOD M14 had a telescoping stock. The alloy aluminum stock body was attached to a titanium six-position collapsible rail butt stock and adjustable cheek rest. Length of pull from the rear of the butt stock to the pistol grip was approximately 11 " when fully extended. This was designed to accommodate operators wearing body armor. The telescoping stock extended and retracted with the push of a button at the end of the stock behind the receiver heel. The stock had ambidextrous sling swivel studs. The stock color was usually black.

Troy Industries Telescoping M14 Stock Project - LAW483 Enterprises designed the Drop-In Modular Battle Stock for Troy Industries. Troy Industries had a prototype Drop-In M14 Battle Stock on display at the 2004 SHOT Show. The prototype stock was made of fiberglass and incorporated a magazine well with an opened up lengthwise dimension, making magazine insertion much easier. The enlarged magazine well also resulted in a hump-like area just in front of the magazine well, providing a grip point on the stock. The Drop-In M14 Battle Stock prototype had a telescoping M16 type stock that also folded to the left side, an M16 type grip with a textured surface and ambidextrous sling swivel

studs. The prototype model had M1913 Picatinny style rails at the three, six and nine o'clock positions on the fore end. The company then expressed plans to add a twelve o'clock rail to the production model.

By the fall of 2004, the M14 Drop-In Modular Battle Stock had been further refined and reclassified as the M14 Modular Stock System (MSS). The M14 MSS was a drop in stock with no replacement of parts needed other than the stock and hand guard. It was designed to fit all standard configuration M14 type rifles and be modified to accept other M14 type models. The stock body was machined from bar stock T6 alloy aluminum and hard coat anodized to military specifications in a choice of black, green, or tan colors. The design called for a six-position collapsible and side folding M16 carbine style butt stock. The butt stock assembly was to have modular storage compartments and a sling swivel on the top edge at the rear end. Further, the M14 MSS included a full M1913 Picatinny rail system with a full length bottom rail, 6 " side rails and a detachable top rail. The side and bottom rails were to be supplied with rail covers. The detachable top rail ran from the front band to just in front of the rear sight aperture. All rails featured numbered cross slots and sported military specification ¼ " x 20 threaded holes. The Troy Industries M14 modular stock weighed less than 3.5 pounds.

Several design changes were made in the M14 MSS project in 2005. Consequently, it made sense to rename the M14 stock project. Troy Industries introduced its Compact Battle Rifle Stock (CBRS) at the Tactical Response Expo on August 30 and 31, 2005 in Chantilly, VA. As introduced in August 2005, the CBRS consisted of a 2.5 pound stock assembly and a 1.9 pound M1913 Picatinny rail assembly. Both assemblies were made of alloy aluminum and available in either black or dark earth (brown) PTFE finish with matching pistol grip and rail covers.

By May 2006, the CBRS was renamed the Drop In Stock System (DISS). The M14 DISS was designed to duplicate the ergonomics of the M16A4 carbine. Consequently, no cheek rest was needed for this stock with optical scopes and sights. The M14 DISS stock assembly was shaped to accommodate standard, medium weight and heavyweight barrels and the M14 select fire components. The stock assembly included a Vltor Weapon Systems six-position collapsing M16 style butt stock with storage compartments. A removable plate could be attached to the side of the stock whether or not a selector cutout was present. The stock assembly had adjustable and locking mechanical bedding at the trigger guard, operating rod guide and the gas cylinder. These features allowed the stock to be tensioned for improved accuracy because the barrel harmonics remained consistent with each shot fired.

The M14 DISS was removed and installed just like a USGI M14 stock. The operating rod guide did not need replacement. The Vltor collapsing butt stock could be replaced with Ace Ltd. USA (Winchester, KY) stocks and adapter blocks to create a left-hand or right-hand folding stock. The top rail required removal of the rear sight assembly, but not the cartridge clip guide, to allow installation of the rail assembly. The twelve o'clock rail

attached to the rear sight pocket and the barrel with a V-shaped block assembly. A different V-shaped block assembly was used for medium weight and heavyweight barrels. The top rail ran from the front band back to the rear sight. The rail assembly had three, six and nine o'clock M1913 Picatinny rails as well. The six o'clock rail was 12 " long.

By October 2006, Steve Troy took the decision to return to the term SOPMOD because Troy Industries brought the SOPMOD M14 to the market and that product is identified with the firm in the M14 rifle community. The Troy modular M14 stock was then coined as the Troy SOPMOD M14 Modular Chassis System or Troy MCS for short. In October 2006, the pre-production model was marked on the left side at the magazine well as follows: top line - TROY SOPMOD M14 middle line - MODULAR CHASSIS SYSTEM bottom line - CAGE CODE 311EZ. A semi-automatic only M14 rifle fitted with an October 2006 pre-production Troy SOPMOD M14 Modular Chassis System, Magpul M93B collapsing butt stock, EOTech dot sight, Troy Industries backup iron sights and a full magazine weighed in at 12 pounds.

The exploded parts diagram for the production version of the Troy M14 MCS was dated March 29, 2007. A Troy MCS stock manufactured in July 2007 was marked as follows on the upper rail left side: top line - TROY M-14 MODULAR CHASSIS SYSTEM middle line - CAGE CODE 3EZ11 P/N MCS-14 PATENT PEND. bottom line - WWW.TROYIND.COM. The lower rail right side was marked: top line - TROY M-14 MODULAR CHASSIS SYSTEM middle line - CAGE CODE 3EZ11 P/N MCS-001 PATENT PEND. bottom line - WWW.TROYIND.COM.

Troy Industries began shipping the stock to retail customers in May 2007. Initially, due to the variety of commercial products available for the M16 family, the Troy M14 MCS was not supplied with a butt stock or pistol grip and only came in black. The following year, the M14 MCS was available in black or flat dark earth as a bare chassis stock or as a complete stock assembly with a M16A2 pistol grip and a choice of either M16A2 or M16 carbine butt stock. It was a true drop-in modular stock for the non-receiver lugged M14 type rifle with any barrel contour up to and including USGI heavyweight match grade. The Troy M14 MCS had three, six, nine and twelve o'clock M1913 Picatinny rails. The twelve o'clock rail had an impressive fifty-four rail slots.

The upper half of the assembly was secured to the rifle by use of a barrel band guide at the front end and a M16 type push pin at the rear end. The barrel band guide was made from two machined aluminum halves surrounding the barrel and gas cylinder just behind the front band. The two halves of the barrel band guide were secured by four hex head screws. The rear sight assembly was removed to clear the rear sight pocket for the twelve o'clock rail. Two hex head screws were threaded through the rear sight knob holes to secure the twelve o'clock rail at the rear. The M16 receiver style push pin was inserted through a hole on the right side just behind the receiver heel to secure the lower half to the upper half of the assembly. A cover plate was placed in front of the front band and secured by three hex head screws to the lower and upper halves of the MCS. Later

versions of the Troy M14 MCS had a set of hex head tensioning screws under the rear end of the firing mechanism. These tensioning screws ensured the firing mechanism remained level and tight. The Troy M14 MCS was made to be compatible with all M16 type butt stocks except thumbhole models. Field stripping the Troy MCS stock was accomplished by removing the firing mechanism and pushing the M16 receiver style push pin outboard to release the lower half. The upper half remained attached to the barreled action for maintenance. Use of a unitized gas system with the M14 MCS was not recommended. The weldment between the front band and the gas cylinder and the upturned front band hand guard tabs would more often than not interfere with the fit of the barrel band guide.

Troy Industries replaced the M14 MCS in July 2009 with a redesigned version based on customer requests to make it easier to disassemble in the field. The legacy system became known as the MCS Mod 0 and the new design was dubbed the MCS Mod 1. The major change made was a new design barrel bank guide. The Mod 1 barrel band assembly only had two fasteners, five less than the Mod 0 unit, to secure its three parts. The new design barrel band assembly made it easier to field strip the rifle. The MCS Mod 1 replaced the rear sight pocket hex head screws with flat head screws. The upper rail side bolt was given a flat tip screwdriver slot. The six o'clock barrel tensioning screw was omitted on the MCS Mod 1 lower chassis but the firing mechanism tensioning hex head screws were retained. Installation of the Troy MCS Mod 0 did not require removal of the muzzle attachment and gas system and the M14 front band was reused. The MCS Mod 1 required removal of the muzzle attachment and gas system to install. The front band was left off so a unitized gas system was not compatible with the MCS Mod 1 stock assembly. At least one Troy M14 MCS stock was exported to Germany.

Some stock weights are provided for comparison purposes:

USGI M14 birch stock with hardware but no hand guard assembly - 2 pounds 11 ounces
USGI M14 synthetic stock with hardware but no hand guard assembly - 2 pounds 14 ounces
USGI M14E2 birch stock with hardware but no hand guard assembly - 3 pounds 6 ounces
Troy M14 MCS Mod 0 with no pistol grip, fore grip or butt stock - 3 pounds 12 ounces

Depending on the make and model of butt stock, vertical fore grip and pistol grip used, the fully outfitted Troy M14 MCS assembly weighs 1 to 2 pounds more than a USGI M14 synthetic stock with hardware.

Sage International, Ltd. – Sage International, Ltd. began operations in 1973. Mr. John Klein is the owner and President of the company. Its modern manufacturing facility boasts extensive machining and welding capabilities. Sage International, Ltd. makes rifle and shotgun accessories, vehicle gun racks and inspection mirrors.

The idea for the M14 Enhanced Battle Rifle began in 2000 with some U. S. Navy SEALs from the Atlantic Fleet looking for a compact M14 rifle for arctic operations. The project request was assigned to Naval Surface Warfare Center (Crane, IN). David P. Armstrong worked on this new M14 rifle project. He first modeled the M14 EBR stock by starting with the telescoping mechanism sold by Sage International, Ltd. to NSWC Crane for use on the Remington 870 shotgun and adding it to a USGI M14 fiberglass stock.

Other modified USGI M14 stocks were submitted to the U. S. Navy SEALs for evaluation. These experimental M14 stocks included: 1) a Butler Creek side folding model 2) a telescoping M16 carbine stock assembly mated to a modified USGI M14 synthetic stock and 3) a cut off M14E2 stock with a M2 bipod leg and rubber butt pad added to the rear. The Navy SEALs preferred the Sage International telescoping shotgun stock modification from among those submitted for evaluation. The Navy SEALs requested a cheek rest be developed for the compact M14 design as the original modified Sage model did not have one. Due to feedback provided by the U. S. Navy SEALs, several USGI M14 synthetic stocks were modified with Sage International Remington 870 telescoping butt stocks, assembled to M14 rifles with 22 " barrels and issued for use. Additionally, two experimental prototype M14 rifles were fitted with the Sage telescoping modified USGI synthetic stocks but given 18 " heavyweight barrels, custom made accessory rails and a prototype quick detaching sound suppressor. A standard model Knight's Armament Company RAS-14 rail system was added to a M14 rifle fitted with one of the Sage telescoping modified USGI synthetic stocks in a brief experiment. The M14 EBR concept blossomed from that point onward to include accessory rails.

NSWC Crane designed a stock chassis in the summer of 2002. The task of manufacturing prototype M14 EBR stocks for evaluation was then assigned to Sage International, Ltd. The firm initially considered making the stock body out of plastic by injection molding but settled on an alloy aluminum design. A highly modified form of the original Sage telescoping shotgun butt stock was added to the stock chassis to create the first design M14 EBR stock. The 2002 design modified telescoping butt stock included a cheek rest. The stock chassis included weight lightening machine cuts and full length six and twelve o'clock Picatinny accessory rails. The USGI cartridge clip guide was replaced with a Picatinny rail strip for mounting of a scope ring.

Sage International, Ltd. debuted the M14 EBR stock for the public at the 2003 SHOT Show in Orlando, FL. Subsequently, Mr. Armstrong patented the M14 Enhanced Battle Rifle (EBR) stock. Mr. Armstrong was the In-Service Engineering Agent for the Mk 14 project at the Weapons Branch, Weapons Division, Ordnance Engineering Department at NSWC (Crane, IN).

NSWC Crane let a bid for the M14 EBR stock on May 11, 2004. The five year contract was awarded to Sage International, Ltd. The Sage International M14 EBR stock was a steel wire telescoping pistol grip stock with adjustable polycarbonate cheek piece and adjustable butt pad. The stock body was CNC machined from 6061 T6 aluminum-

magnesium alloy billet. This alloy is commonly used to fabricate items such as aircraft and electrical fittings and bicycle frames. The M14 EBR stock had ambidextrous sling swivels and four military standard M1913 Picatinny rails around the barrel and one behind the receiver heel. It was designed to fit a M14 type rifle with a standard contour and medium weight barrels. The Fulton Armory medium weight barrel had been contoured to fit in between the two hand guard screw bosses in the EBR stock. The M14 EBR stock was not made to fit heavyweight barrels until April 2011.

The standard size operating rod guide was replaced with an operating rod guide supplied by Sage International, Ltd. The operating rod guide was attached to the stock with three screws. Once that was done, it was a matter of reassembling the rifle with the stock bolted to the new operating rod guide and replacing the traditional front band with a washer to align the gas cylinder to the barrel. The M14 EBR stock operating rod guide was machined from AISI 4130 alloy steel. The M14 EBR stock top rail could be taken off by removing six screws. The M14 EBR stock was built with a barrel tensioning screw located at the front end of the top (twelve o'clock) rail. Earlier models of the stock utilized a lock nut and later models had a setscrew to keep the tensioning screw from backing out. The barrel tensioning screw was adjusted to eliminate vertical stringing during rapid fire. The tensioning screw was not utilized during U. S. Navy acceptance testing of the Mk 14 Mod 0 rifle. Sage International, Ltd. also made a M1913 Picatinny rail clip guide for anchoring a scope or dot sight. The clip guide base could be used in conjunction with its stock to mount optics. The stock grip was marked SAGE INT'L LTD on the left side.

Sage International, Ltd. (Oscoda, MI) has produced M14 EBR and M14 Chop Mod stocks for the U. S. military and for domestic and foreign commercial markets. The Sage International EBR stock has seen service on M14 rifles in use by U. S. Army soldiers in Afghanistan. As of November 2006, at least one Sage International M14 EBR stock was fitted to a T57 rifle in the Taiwan Army. That particular T57 had the selector lock installed and was fitted with a traditional design rifle scope.

In late November 2004, Sage International produced an unknown quantity of upgraded M14 EBR stocks for the U. S. Navy SEALs for evaluation. The specification for this developmental stock was supplied by Naval Surface Warfare Center at Crane, IN. This upgraded second generation version of the M14 EBR stock was named "Chop Mod." It was intended to lighten the weight of the U. S. Navy Mk 14 Mod 0 rifle. NSWC prototype Chop Mod stocks were created by cutting a section of the fore stock out and then welding the front end back on to the remaining body. The Chop Mod stock is a lighter weight non-reflective anodized gray color version of the M14 EBR stock. Twenty-five extra holes are drilled in the frame, rails and butt stock/pistol grip mount to reduce the weight. Additionally, the top rail is 11.25 " long or 1.75 " shorter than the original M14 EBR stock. The side rails are 1.60 " shorter than the original black color M14 EBR version. The shortening of the accessory rails further reduces the stock weight. Consequently, the Chop Mod stock weighs four ounces less than the original M14 EBR model. The six-position steel wire butt stock runs through a sturdier butt stock/pistol grip mount that is

fitted with a new internal metal support tab. The side of the Chop Mod stock is marked on the right hand side below the operating rod rail from top to bottom: first line – EBR CHASSIS STOCK second line – SAGE INTERNATIONAL, LTD third line – Oscoda, Mi 48750 Patent Pending. The stock inscription was done with dot matrix style lettering for all stocks produced in November 2004.

During the November 2004 batch production run of M14 Chop Mod stocks Sage International, Ltd. also made twenty-five of these lightened anodized gray color M14 stocks but with a 13 " full length top rail like the original black color M14 EBR stock model. This single lot of twenty-five stocks was released by Sage International through authorized distributors to the civilian market. Beginning in the winter of 2005, all Sage International M14 stocks available to the civilian market have the same features as this single lot of twenty-five gray color M14 stocks except smooth lettering is used for the manufacturer's inscription. The Chop Mod version is used on the U. S. Navy Mk 14 Mod 0 rifles from the end of 2004 onward. Before production of the original M14 EBR stock ceased in January or February 2005, a number of black EBR stocks were produced with the shorter Chop Mod side rails and smooth lettering inscription described above. The Sage M14 Chop Mod stock has also been produced with an anodized coyote brown finish and by May 2013, desert digital camouflage.

Sage International, Ltd. introduced its Mk 14 Mod 0 CQB stock at the 2005 SHOT Show in Las Vegas, NV. This model was a M14 Chop Mod stock fitted with a collapsible M16 carbine style butt stock. These stocks became available to the commercial market in April 2005. They were available in black or gray and reduced the weight by 1.1 pounds over the M14 Chop Mod stock. A vertical fore grip that attached to the bottom rail was a factory option. A California legal version of the Sage International M14 stock was available to the public by March 2005. This version had a fixed synthetic black overmolded Hogue shot gun butt stock with sling plate, butt pad, and top, bottom and side rail mounts but no pistol grip. LAW483 Enterprises offered two standard grip butt stocks for the Sage International, Ltd. M14 EBR stock, 11.5 " and 13.25 " length of pull. LAW483 modified Hogue shot gun butt stocks to achieve the desired length of pull. The Hogue overmolded shot gun butt stocks featured a good quality recoil pad and textured grip.

In December 2006, Sage International produced the first batch of its third generation M14 stock, the Sage CQB SEAL model. This stock had dark earth (medium brown) color plastic parts: vertical fore grip, pistol grip, hand guard, and triangular frame collapsible butt stock with removable cheek rest. The magazine well has been redesigned to further reduce the overall weight. The side rails have been lengthened and the top rail changed to allow installation of a M14SE barrel. All of these components with the stock chassis total 4 pounds 9.2 ounces in weight. The chassis body has a dark earth anodized coating. The Sage CQB SEAL stock will accept a medium contour barrel without modification. This model was 1.25 " shorter than the first generation M14 EBR stock when both were fully extended and 2 " longer than the first generation M14 EBR stock when both were fully collapsed. Eleven of the Sage CQB SEAL stocks were released to

the civilian market in early 2007. In June 2008, the color of the stock chassis was changed to a lighter shade of gray.

The Sage M14 EBR stock for the U. S. Marine Corps was released for limited sale in the civilian market in October 2007. This model had a light chocolate brown color. The stock twelve o'clock rail was factory modified at the rear end to accept a side three point scope mount. The Sage operating rod guide was changed so that it would fit a Smith Enterprise, Inc. M14SE medium weight barrel. This Sage stock model was marked as follows on the right hand side: top line - EBR CHASSIS STOCK middle line - SAGE INTERNATIONAL, LTD bottom line - Oscoda, MI 48750 Patent 6839998. The U. S. Marine Corps designated the M14 configured in this stock as the M39 Enhanced Marksman Rifle (EMR) in October 2007. Collapsing rail or buffer tube butt stocks can be installed on both variations of the CQB stock and the M39 EMR stock. The factory pistol grip on M14ALCS (collapsing rail only) stocks may be replaced with an Ergo Sage EBR SOPMOD grip. Sage stock models M14ALCS/CV and M14ALCS/PMRI will readily accept M16 compatible pistol grips. Note that airsoft M14 EBR stocks will not have a batch number stamped into the chassis just forward of the magazine well.

The Sage International, Ltd. collapsible M14 stock has evolved through a developmental progression. The chassis style defines the version. The Sage International, Ltd. M14 alloy aluminum chassis stock is an approved alteration for the USGI M14. Sage International, Ltd. had sold close to 3,000 M14 EBR stocks to individual U. S. Army units by early 2010. USGI M14 rifles assembled with Sage International, Ltd. M14 EBR stocks by combat unit armorers are similar in appearance to the M14 EBR-RI but are not built and tested to those specifications. To summarize the evolution of the Sage International, Ltd. collapsible stocks associated with modern military versions of the M14 rifle, the following sequence of product development is offered:

Early First Generation - 1) full length forestock terminating at the gas cylinder 2) ribbed and very straight chassis bottom from the rear end to the magazine well 3) lack of radial holes in the magazine well 4) lack of rail grooves.

Late First Generation (early Mk 14 Mod 0) - 1) full length forestock 2) slightly curved chassis bottom from the rear end to the magazine well 3) rail grooves 4) lack of radial holes in the magazine well 5) welded rail brackets.

Early Second Generation (late Mk 14 Mod 0) - 1) full length forestock 2) slightly curved chassis bottom from the rear end to the magazine well 3) rail grooves 4) six radial holes in the magazine well 5) lack of welds on the rail brackets.

Late Second Generation (M14 EBR-RI, Mk 14 Mod 1 and M39 EMR) - 1) chopped length forestock 2) moderately machined chassis bottom from the rear end to the magazine well 3) rail grooves 4) six radial holes in the magazine well 5) lack of welds on the rail brackets or fitted with a M4 style butt stock extension tube.

Early Third Generation - 1) chopped length forestock 2) heavily machined chassis bottom from the rear end to the magazine well 3) moderately machined pistol grip area 4) rail grooves 5) six radial holes in the magazine well.

Middle Third Generation - 1) chopped length forestock 2) heavily machined chassis bottom from the rear end to the magazine well 3) heavily machined pistol grip area 4) rail grooves 5) six radial holes in the magazine well.

Late Third Generation - This design was introduced in July 2010. It was the same as the middle third generation model but the weight reduced through additional small machining cuts. The copper colored stocks were sandblasted for a more uniform finish. An anodized olive drab green finish became available in 2013. The factory shipped top cover accommodated a medium weight barrel. The top covers for the standard barrel use six screws. One of the screw holes was omitted for the medium weight barrel top covers due to the wider barrel profile.

Marstar Canada - Beginning in January 2007, Marstar Canada was offering a Canadian manufactured alloy aluminum chassis stock for the M14 rifle (catalog number M14-105). The M14-105 was machined with three, six, nine and twelve o'clock Picatinny rails. The stripped chassis had a black anodized finished and weighed 4.5 pounds but did not have a selector cutout.

LAW483 Enterprises - As previously mentioned, the Drop-in Modular Battle Stock was introduced at the 2004 SHOT Show. It was on display at the Troy Industries booth as the the Troy Industries Modular Battle Stock. It was intended to be a prototype for Troy and be molded rather than a hand modified USGI fiberglass stock. However, Troy Industries took an order for one so the order was filled and more were made. Troy Industries eventually used alloy aluminum for its stock. LAW483 Enterprises continued to offer the stock as orders came in. LAW483 Enterprises was able to make the Drop-in Modular Battle Stock in-house. The stock used a machined aluminum M870 shotgun pistol grip adapter purchased online, Ace Ltd. USA receiver blocks, and an Ace Ltd. USA folding mechanism. One was made with a synthetic pistol grip adapter. The last one made used an aluminum adapter like the originals, but it was overlaid with fiberglass for a molded-in look and greater durability. The final fore end shape became the basis for what was called the # 7 Tactical Forend with Enhanced Magwell. Later, the enhanced magazine well was removed and that design was named the # 6 Tactical Forend.

By the fall of 2004, LAW483 Enterprises offered two folding stocks. The Drop-In Modular Battle Stock was a folding and collapsing stock model. It had Picatinny rails at three, six and nine o'clock, a proprietary enhanced magazine well for easier insertion, and proprietary fore end texturing with a choice of either bottom or side sling swivels. The stock rails were used from the Rock SOPMOD M14 project. The highly modified USGI M14 synthetic stock utilized a M16 carbine type collapsible butt stock and M16A1 style pistol grip. The BSR Folding Stock was a USGI fiberglass stock modified to be a

fiberglass version of the Beretta type wood stock made by Springfield Armory, Inc. It had the side mount sling swivels found on the original Beretta stocks and accepted the original BM59 folding hardware and plastic pistol grip. One only was made at a customer's request. Non-availability of the hardware limited its appeal. BSR stood for Beretta Springfield Reese because this stock would fit the folding mechanisms offered by those three manufacturers. Additional options for either folding stock included filling of the selector cutout, various grades of surface texturing, single point sling attachment, and camouflage pattern painting. These folding stocks were no longer available as of 2006.

McMillan Fiberglass Stocks, Inc. – McMillan Fiberglass Stocks completed its first production run of folding MFS-14 stocks in October 2004. The McMillan Fiberglass Stocks tactical MFS-14 stock used a six-position M16 carbine style padded butt stock that was attached to a folding mechanism mounted to a modified M2A stock. The butt stock folded to the receiver left side which allowed for firing while folded. When extended, it locked positively and only required a tug to release. The sling swivel was located on the right side of the stock just above the pistol grip. The McMillan tactical MFS-14 stock had three different fore end rail configurations. One rail configuration covered the barrel from the barrel ring to the front band and the front 4 " or so at the fore end at the three, six and nine o'clock positions. Another rail arrangement extended the six o'clock rail forward to accommodate a bipod and the third configuration extended the twelve o'clock rail to the rear. By 2009, the MFS-14 stock was arranged with 4 " rails at three and nine o'clock and an 11 " rail at six o'clock and fitted with a five-position Ace Ltd. USA SOCOM butt stock. The MFS-14 stock required bedding for installation.

Accuracy International, Ltd. - At the 2008 SHOT Show in Las Vegas, NV, Accuracy International displayed its prototype aluminum chassis folding stock for the M14. It had an adjustable stock comb and thumbhole grip. The paint finish was mostly tan with a little brown. Unfortunately, this stock had not yet gone into production as of mid-2010.

CM Manufacturing - CM Manufacturing produces the Modular Stock Platform (MSP) for the M14 type rifle. The MSP is an aramid reinforced and modified USGI synthetic stock with a rail mount and folding stock adapter. Aramid reinforcement further stiffens the USGI stock. To build the MSP, CM Manufacturing cuts a USGI synthetic M14 stock in two just behind receiver heel. A pistol grip and folding stock adapter is attached to the rear end of the stock body. The customer supplies a M16 pistol grip, folding stock mechanism, and a butt stock.

The M16 pistol grip bolts to the MSP pistol grip and folding stock adapter. An Ace Ltd. USA folding stock mechanism (model FSM or FSM-PB) bolts on to the adapter as well. From there, an Ace Ltd. USA skeleton stock (model AKFX) or a M16 carbine telescoping butt stock is attached to the folding stock mechanism. The M16 carbine telescoping butt stock will require the Ace Ltd. USA CAR15 stock block (model number PN) to be fitted between the folding stock mechanism and the butt stock. The Ace Ltd. USA folding stock mechanisms and the CAR15 stock block each may be adjusted up to ½ " higher than the

lowest settings. This allows the operator to achieve a better cheek weld when the rifle is scoped.

There are two versions of the MSP, Model 5 and Model 8. Both models have six o'clock M1913 Picatinny rails bolted to anchors inside the barrel channel. The Model 8 rail is 8 " long. The Model 5 stock has a 5 " rail behind a bipod stud. The M1913 Picatinny rails and the pistol grip and folding stock adapter are machined from 6061 alloy aluminum and finished with hard coat anodizing. The MSP selector cutout is filled with a plug secured by glue. It may be removed if desired. CM Manufacturing also offers aramid reinforced USGI slotted or solid fiberglass hand guards. The MSP and the aramid reinforced hand guards are given a textured non-slip black color finish.

In early 2007, Ingram Custom Rifleworks (South Cariboo, BC) began meeting a market demand for custom M14 type rifle stocks in Canada. The firm modified Chinese and USGI synthetic stocks per customer request until mid-2010. At that point, the firm introduced its own M14 stocks made with precision molds and fixtures. The M14S-CQB, M14SE2, and M14SA2 Hunter models were manufactured using carbon fiber, fiberglass, and epoxy adhesive. M1913 rails of various lengths were an optional feature for the M14S-CQB stock. The drop-in M14S-CQB stock was intended to be mated with a M4 carbine compatible butt stock and M16 style pistol grip. Stocks with ICR prefix serial numbers were sold with a lifetime warranty. Production had ceased by May 2013 because the company owner retired.

After two years of development, The Upgrade Path Inc. for M14.ca (Victoria, BC) shipped its first batch of fifty Blackfeather^(R) RS aluminum chassis stocks in July 2011. The stock assembly had ten major components: chassis stock, butt stock adapter, two end plate adapters, one 6 " and two 4 " removable Picatinny rails, wear plate, operating rod spring guide and operating rod guide. The operating rod guide allowed for barrel tensioning and greasing of the operating rod bearing surface. The chassis stock and adapters were made of black color anodized 6061 T6 alloy aluminum. Additional color choices were made available in February 2013, flat dark earth, olive drab green, and white. The operating rod guide, wear plate, and operating rod spring guide were machined from AISI 4140 alloy steel and given a black oxide coating. The Blackfeather^(R) RS stock accommodated any M16 rifle or M4 carbine butt stock and standard and medium weight M14 barrels. It would not fit lugged or select fire capable receivers. The operating rod guide was sized for standard contour barrels. The stock assembly weighed 35.2 ounces without a grip or butt stock. It was marked as follows on the left rear side: top line - M14.ca BLACKFEATHER "RS" bottom line - Made in Canada. In December 2012, the 6061 alloy aluminum Scout Hand Guard (SHG) was unveiled. It was a 12.625 " top cover which attached to the Blackfeather^(R) RS operating rod guide and barrel chamber with fasteners and clamps. The SHG had a twelve o'clock and optional two and ten o'clock Picatinny rails. It was marked as follows on the left rear side: top line - M14.ca SHG bottom line - Made in Canada.

In October 2012, Xander Customs (Vancouver Island, BC) announced its aluminum chassis M14 stock. It was compatible with M16 style butt stocks and pistol grips. Installation of a M16 style butt stock precluded use of the iron sights. The stock had three, six and nine o'clock rails at the fore end. The proprietary operating rod guide secured the barrel to the chassis with three screws and threaded steel inserts. Setscrews at the front end could be adjusted for pretensioning. The Xander Customs stock was not compatible with barrel rail mounts or standard length connector locks. The stock weighed 2.04 pounds with no butt stock or pistol grip. Standard colors offered were green, black and coyote brown.

After six prototype designs were tested, Delta 14 Chassis, Inc. (Ferndale, MI) released its 6061 alloy aluminum chassis stock for sale in May 2013. The black anodized Delta 14 Chassis stock was compatible with semi-automatic only M14 type rifles and standard contour barrels. It was designed to mate with aftermarket Mossberg 500 shotgun collapsing butt stock kits. M1913 Picatinny rails at three, six and nine o'clock could be installed or removed as desired. Without a butt stock or pistol grip, the stock chassis weighed 2.02 pounds.

Other Stocks

Generally, commercial market wood stocks will not have a selector cutout. There has been at least one exception though. In 2005, Fulton Armory offered an unfinished new manufacture walnut USGI pattern M14 stock with or without the selector cutout. It was made by Boyds' Gunstock Industries and marked BOYDS in the stock barrel channel. Some walnut M1A stocks made in the 1980s were ink stamped with a four digit number in the barrel channel. These stocks may have been made by E. C. Bishop & Son, Inc.

Before 1994, Springfield Armory, Inc. offered extra fancy AAA grade walnut stocks as an option for the M1A. Springfield Armory, Inc. M1A synthetic stocks are often fitted with a rubber butt pad. The company logo may or may not be part of the rubber surface texturing. The rubber butt pad softens the recoil and the overall length is increased by an inch. Some Springfield Armory, Inc. black color crinkle texture and woodland camouflage synthetic stocks did not have the selector cutout filled in. This was typical of M1A stocks in the late 1980s and early 1990s. Beginning in 2003, Springfield Armory, Inc. standard and Scout Squad M1A rifles were produced with mossy oak hunting camouflage pattern synthetic stocks. Until the summer of 2008, Springfield Armory, Inc. M1A rifles were outfitted in textured and painted USGI synthetic, commercial walnut or USGI birch stocks. Beginning mid-2008, Springfield Armory, Inc. assembled some M1A rifles with its new injection molded black color polymer stock. By April 2009, the polymer stocks were produced in both black and medium green with matching hand guard. As of June 2010, two camouflage patterns were added and matching Scout Squad hand guard was offered for all color choices. The new M1A polymer stocks have no selector cutout but do have storage compartments for the USGI cleaning kit. The polymer stock does not require use of the USGI butt plate screw square nut and nut retainer.

Boyd's Gunstock Industries, Minelli S.p.A. (Italy), Reinhart Fajen, Inc., Shaw and Wenig Custom Gunstocks have manufactured wood stocks for the M14 type rifle at one time or another. Reinhart Fajen, Inc. supplied a lot of 100 match grade M1A stocks without the selector cutout to Springfield Armory, Inc. in Texas in late 1971. The Reinhart Fajen, Inc. Style II was a medium contour stock available in walnut or laminated wood. Fred Wenig was the plant manager at Reinhart Fajen, Inc. for many years. He now operates his own gun stock making business in Lincoln, MO. Wenig Custom Gunstocks produces a Monte Carlo style comb M1A rifle stock with a more vertical grip and double palm swells. It is available in walnut or laminated birch. The Wenig traditional style M1A stocks are made in maple or walnut. Wenig also produces the adjustable cheek rest walnut stock for the Springfield Armory, Inc. M21 rifle.

Boyd's Gunstock Industries offered two styles of M1A stock in walnut or laminated wood. The Boyd's Style I was not inletted for bedding but retained the stock liner. The Style II did not have a stock liner but was cut with a semi-inlet and required bedding. Neither style had a selector cutout. Both stock models were discontinued in October 2007. By January 2010, both Boyd's Style I and Style II stock were available again. Style I was available in walnut, nutmeg laminate or pepper laminate. The Style II stock was offered in walnut, unfinished or finished. Boyd's M1A walnut stocks were manufactured slightly wider at the rear end than the USGI M14 butt plate.

Springfield Armory, Inc. offered Shaw stocks from 1982 through 1990. In 1982, there were two M1A Combat models. One model had a laminated walnut standard stock and a metal flappered butt plate. The other M1A Combat model was fitted with a laminated walnut pistol grip stock and a rubber butt pad. Both stocks had the John Shaw design forearm. The following year, Shaw stocks were available as an individual part but the selection of Shaw stocks was expanded. The standard Shaw stock was offered in walnut, walnut/walnut laminate, or walnut/maple laminate. The E2 style stock with a rubber butt pad could be ordered in walnut/walnut laminate or walnut/maple laminate. M1A rifles with walnut standard and E2 style Shaw stocks were listed in factory price lists from 1984 through 1989. In 1990, the Shaw walnut standard stock was an optional configuration for the standard, National Match and Super Match M1A rifles. The John Shaw design stocks were easily identified by the rectangular shaped extra forearm thickness in the area of the front sling swivel. The front sling swivel was secured to the stock by two hex head screws.

The Chinese stocks on M14 rifles imported into the United States by Keng's Firearms Specialty and Century Arms International were made of chu wood. Chu wood only grows in Manchuria, China near the Russian border. Chinese M14 type rifles imported by IDE USA/CJA into the United States have walnut stocks. The walnut for these stocks was harvested in Yunnan Province, People's Republic of China. Chu is softer and lighter than black walnut. Why was chu wood selected for the Chinese M14? Because chu has very good resistance to the effects of mildew, a desirable property in the humid climate of Viet Nam.

For long term storage, a rifle fitted with a wood stock should have the trigger guard unclamped from the stock. This will allow the wood stock to expand and contract as the weather changes, avoiding compression of the wood and loosening of the receiver-to-stock fit.

The USGI M14 fiberglass stock lends itself to camouflage pattern finishes by anyone with an imagination, a steady hand and paint. Whamo Camo (MO) painted about 500 M14 fiberglass stocks with camouflage patterns between 1998 and 2006. Of the two dozen or so patterns offered, the Vietnam Tiger Stripe was the most requested. Likewise, Karsten's Custom Camo (UT) camouflage patterns are likewise superb examples of what can be done to dress up the M14. Karsten's Custom Camo has been in business since 2001.

The flip up butt plate on the M14 and M14E2 stocks was adopted from the M15 rifle that was declared obsolete in 1959. An M14 stock can be fitted with an M1 Garand butt plate to shorten the overall length by about $\frac{1}{4}$ ". However, the part of the stock heel which houses the butt plate's hinge should be filled in with suitable material. An alternate solution provided by SparrowHawk M14 Stocks is to remove the hinge and roll pin from the M14 butt plate. The stock is preserved and the storage compartment is still readily accessible. A USGI M14 stock installed to a Chinese M14 rifle will require fitting, as there are small dimensional differences. A design for an adjustable butt stock extender was patented by Peter Lautrec (then of Baldwin, WI) in 1994. Mr. Lautrec's design took advantage of the butt stock storage compartment to house two dowels. A butt plate was attached at the rear of the dowels. Without the spacers, the length of pull was extended by $1 \frac{5}{8}$ ". Various length spacers up to 1" could be added for even greater length of pull.

Israeli Military Industries modified the USGI M14 stocks it supplied for the Israeli Defense Forces. An integral cheek rest and rubber butt pad for sniper duty was added to each stock. The Israelis used two different versions of its M14 stock. The early version had a shorter length cheek rest, while the later version used a longer cheek rest. A rubber pad was attached to the rear end of the longer cheek rest on stocks so equipped. The IDF M14 stocks also had left hand side sling swivels just aft of the stock ferrule and just forward of the rubber butt pad and a metal-reinforced bipod stud just aft of the bottom front sling swivel. Some of these stocks have been exported back to the United States for commercial sale. Springfield Armory, Inc. purchased some of these stocks and painted them black. These stocks were used in the assembly of the IDF M1A rifles. By 2000, scoped M14 rifles in the Estonian Army were fitted with medium green color thumbhole plywood stocks and classified at the M14 TP model.

Sage International, Ltd. - Sage International offered its M14 EBR stock with a fixed Remington 870 shot gun butt stock or in conjunction with Fulton Armory, a wood M14 butt stock. This stock is legal under local state law for sale to California residents. The company had developed the M14ALCS/MP-EBR model by January 2010. Essentially, this was the M14ALCS/PMRI model but with a Magpul Industries Corporation PST butt

stock. The M14ALCS/MP-EBR was never taken to market. By May 2010, Sage International, Ltd. had come up with the M14ALCS/PMRI design. The charcoal color M14 EBR-RI NM stocks and M14 EBR-RINM-SEI marked stocks debuted in July and September 2010, respectively. These stocks were given the model name M14ALCS/PMRI. This stock model was assembled with a black color Magpul Industries Corporation PRS2 butt stock. The PRS2 butt stock is wheel adjustable for length of pull and cheek rest height. In February 2011, Sage International, Ltd. made available a heavyweight barrel top rail cover and operating rod guide for its M14 stocks.

J. Allen Enterprises, Inc. - J. Allen Enterprises produces and markets the JAE-100 stock for M14 type rifles. Development of the stock began in 2003. The JAE-100 is legal for civilian owners in California. J. Allen Enterprises corresponded with the California Department of Justice for several months to ensure the design of the JAE-100 stock did not meet the California definition of an assault weapon pistol grip stock. This correspondence resulted in a letter from the California Department of Justice dated October 22, 2003 which specifically confirmed the definition of an assault weapon pistol grip stock. The JAE-100 stock design did not meet the definition of an assault weapon pistol grip stock.

The first generation JAE-100 stock was made of a proprietary polymer material molded over a full length aluminum skeleton. It had a textured exterior surface. The JAE-100 stock was offered in seven colors: dark earth, coyote brown, olive drab, titanium grey, lowlite green, grit tan or SWAT black. A cheek rest with adjustment spacers, a palm rest, an off hand rest and butt spacers were supplied with the stock for individual fitting. The cheek rest, palm rest, off hand rest, butt spacers, and butt adapter were made of polymer and the butt pad and grip were made of rubber. The first generation stock was configured for semi-automatic only M14 type rifles but would accept receivers with a rear lug.

The JAE-100 design changed the way the M14 type receiver was held to the stock. Two adjustable titanium locking plates and two screws locked the receiver to the full length aluminum skeleton. The locking plates rested outboard of the trigger guard hooks inside the stock. The screws attached to the locking plates from the bottom of the stock. The firing mechanism was installed in the normal manner. The first generation JAE-100 stock weighed 3 pounds 4 ounces stripped (out of the mold before hardware added) and 5 pounds 4 ounces with all accessories installed. The first generation JAE-100 stock would accommodate standard, medium weight or heavyweight contour M14 barrels without any fitting. Sling swivel studs were located on the left hand side of the stock. The bipod stud was located aft of the M1913 Picatinny style rail section on the fore end bottom side. Options included textured matching color traditional style hand guard, a single point sling plate, and personalized markings. The first generation JAE-100 stock length of pull could be adjusted from 12.4 " to 15.4 ". Its dimensions were as follows: overall length - 34.6 ", overall width - 2.1 " and overall height - 6.5 ".

In November 2007, J. Allen Enterprises brought the second generation JAE-100 stock to market. The same seven color choices were available to the buyer. Without optional accessories, the weight of the second generation JAE-100 stock was about 4 pounds. For the second generation stock, the optional accessories included: hand guard (standard, heavy barrel, or cutout for barrel scope mount), adjustable cheek rest with spacers, thumbwheel adjustable cheek rest, 6 " or 9 " long six o'clock Picatinny rail section, aluminum off hand rest with integral Picatinny rail section, 4 " or 9 " Picatinny side rail assembly, side mounted flush cups, bipod adapter with a sling swivel stud, butt pad and spacers, butt stock single point sling plate, adjustable palm rest with spacers, barrel tensioner, titanium lug slides, and personalized markings.

The second generation JAE-100 stock differed from its predecessor with these features: 1) trimmer, narrowed butt stock 2) lower cheek comb for facilitating use of iron sights 3) shorter length-of-pull for the basic stock 4) butt adapter was changed to anodized aluminum construction 5) augmentable or removable rubber grip 6) selector cutout model available for select fire rifles 7) 7075 alloy aluminum lug slides standard 8) flush plugs in eight positions standard with flush cups optional for either side of the stock 9) new fore end structure built into the aluminum skeleton to accept new optional barrel tensioner for in-use adjustment of force bearing on the barrel and front band 10) more visible aluminum on the bottom side of the stock 11) optional thumbwheel operated cheek rest enabling the operator to lower the cheek rest without tools 12) the inside of the fore end was all aluminum with welds machined down and no need for a thermal deflector and 13) optional quick detach mechanism for the cheek rest.

J. Allen Enterprises, Inc. began production of its third generation JAE-100 stock in May 2011. The JAE-100 G3 stock further refined the design over the G2 model with the following improvements:

- 1) the thumbwheel had a separate brake wheel that made the cheek rest rock solid
- 2) the butt pad extended downward for better shoulder positioning
- 3) the aluminum skeleton was redesigned for less weight and better balance
- 4) the bezel around the cheek rest brake wheel was formed with a lower profile
- 5) cheek rest available with a quick detach option for using iron sights
- 6) the stock fore end was tapered for offhand shooting
- 7) the grip was slightly lowered for better ergonomics

LAW483 Enterprises – From 2003 through 2006, LAW483 Enterprises created fixed butt M14 stocks by modifying USGI synthetic stocks. The USGI M14 stocks were typically

stiffened in the fore end and any factory depressions filled in. The USGI synthetic stocks could also be modified to create a right, left, or ambidextrous vertical grip. Options included filling of the selector cutout, various grades of surface texturing, single point sling attachment, and side sling swivels. The most requested model was a short length of pull stock with a recoil pad. One short length of pull stock was made with a M14 butt plate. Two stocks were made using a M16 style grip adapter from a Rock SOPMOD M14 and a fixed stock. During this time, much of the production was customer requested along with speculative projects taken on for product research and development.

LAW483 Enterprises made custom design laminate wood or wood fixed butt M14 stocks by manual woodworking methods during 2006 and 2007. The wood laminate stocks were available in four types: 1) pistol grip 2) vertical grip 3) thumbhole and 4) standard grip. The pistol grip models were the M-14 E2, and the M-21 E2. Vertical grip M14 stock choices included the LAW-TAC Vertical Grip Ruck Rest, the LAW-TAC Off-Hand, and the Vertical Grip Match.

The first Vertical Grip Match stock was made from a modified USGI fiberglass stock. The fore end was overlaid with fiberglass material and the grip was highly modified to be a right hand only grip without a raised comb per customer request. This stock was painted primer gray then sent to Whamo Camo for its Seminole Camo paint. At this point, LAW483 Enterprises realized it had made a mistake. All of that work would have to be repeated to make another copy of the same stock. Before going any further, the firm contacted a company that ran a stock duplicator that would make one or two copies and would accept work for semi-automatic rifle stocks. As this company was not familiar with duplicating M14 type stocks, the first 3 " to 4 " of the barrel channel were filled in. Consequently, LAW483 Enterprises had to use hand tools to finish inletting the fore end, install the stock ferrule, drill for the stock liner screws, install the stock liner, inlet for the military butt plates, and sand and finish the stock. The M14 models had selector cutouts but the M21 models did not.

The LAW483 Thumbhole Sporter was a design created by customer request. It started as a USGI fiberglass stock and was hand formed and glassed over by hand. This was the first stock in which the pattern was not made as a functional stock but was made to be a pattern. The more traditional standard grip choices included Standard Grip Recoil Pad, USGI M-14 Buttplate, M-1 Garand Buttplate, Body Armor Designated Marksman, and the LAW-TAC Patrol Stock. These were still modified USGI fiberglass stocks.

Wood stocks were crafted from extra fancy woods such as maple, myrtle or walnut. The M14 butt plate was often replaced with a M1 Garand butt plate or a rubber recoil pad according to customer request. LAW483 proprietary enhanced magazine well, camouflage pattern painting, acrylic coating, and reducing or increasing the length of pull were customer options for modified USGI or new manufacture custom stocks.

The firm spent 2008 through 2010 refining its designs and automating the manufacturing process. By April 2008, the LAW483 stock model number system was established. The model number indicated the type of rifle, pistol grip style and fore end contour. For example, M14P3 was a M14 rifle stock with a pistol grip and fore end suitable for a heavyweight barrel. Stock grip styles included classic (C), enhanced standard grip (H), pistol grip (P), replica USGI (R), standard grip (S), thumbhole grip (T), and vertical grip (V). Fifteen fore end contours were available for any grip style such as lightweight for standard profile barrels (1), medium for medium weight barrels (2), sporter for medium and heavyweight barrels (5) and tactical for all barrel profiles on non-lugged receivers (6).

The LAW483 M14H6 stock debuted at the 2009 SHOT Show in the LRB Arms booth. It was a drop-in fiberglass stock with a fore end suited for adding rail mounts. The enhanced standard grip of the M14H6 stock was more vertical than a USGI M14 stock. However, the web of the hand was kept below the highest point of the exposed trigger. The last 4 " of the butt stock were made parallel at the heel and toe for two purposes; to make short length of pull stocks possible without reducing the stock footprint and to allow installation of M1 and M14 butt plates on short length of pull stocks.

LAW483 Enterprises added a Terrco Northstar 20-2R Duplicarver and a milling machine to its capital inventory in February 2009. The duplicator machine was running for production by February 2010. By mid-2011, wood and wood laminate M1 Garand and M14 stocks using the LAW483 model numbering system were available. Customer options included QD sling studs, matching hand guards, and customer specified length of pull. From 2009 onward, stock standard features included military sling swivels, USGI style steel stock liner, National Match ferrule, and Pachmayr SC100 rubber butt pad. The first wood and wood laminate butt stocks were fitted to Sage International, Ltd. M14 EBR stocks in June 2013. Semi-finished stocks were sold starting the following month. The 60 % completed stocks were shaped and roughly inletted with a milled barrel channel and sanded to 120 grit. Stock metal hardware was offered as a finishing kit. In August 2013, LAW483 standardized the comb height for all of its stocks except scope only stocks.

Short Rifle Stock Systems, Inc. - Richard G. Cabral served in the U. S. Marine Corps from 1966 to 1974 and in the Army National Guard in the 1990s. He is owner and Chief Executive Officer of Short Rifle Stock Systems, Inc. During his employment as a contractor in 2006 in Iraq, Mr. Cabral was inspired with the idea for a bull pup M14 stock while observing a U. S. Army soldier getting in and out of a vehicle with a M21 rifle. In September 2007, Short Rifle Systems, Inc. introduced its bull pup stock conversion for the M14. The Short Rifle Stock System, or SRSS, was available in two versions, the SRSS-14T-A for Close Quarters Battle and the SRSS-21SA for precision marksmanship. Depending on the length of barrel on the rifle and the version installed, the overall length could be reduced from 17 " to 20 ". Accordingly, the owner would be obligated to comply with the NFA rules regarding short barrel rifles. The stock body itself which supported the barreled action and firing mechanism could be fabricated from a number of materials to include machined alloy aluminum billet, fiberglass, polyethylene terephthalate resin,

wood or carbon fiber. The cheek rest for the SRSS-14T-A model was made from alloy aluminum. Separate right hand side panels were made for M14 type rifles with and without select fire parts. The issue hand guard was replaced with an Amega Ranges, Inc. accessory rail for mounting optics. The stock panels and accessory rail were made of CNC machined alloy aluminum. The internal bedding system was formed from polychloroprene synthetic rubber. Installation of either SRSS model required removal of the rear sight assembly. By September 2008, second generation conversion kits were available in synthetic material, SRSS-1421SM, or machined billet alloy aluminum, SRSS-1421BA. The alloy aluminum conversion kit weighed 1.5 pounds more than the synthetic material kit.

In late 2009 and early 2010, third generation SRSS prototypes were tested by U. S. Navy SEALs at the Basic Underwater Demolition / SEAL School (Coronado, CA) and used in combat in Afghanistan by the U. S. Army 5th Special Forces Group. Production models of the third generation SRSS became available in March 2010. Additional machining cuts further lightened the alloy aluminum stock system weight. The third generation SRSS only added 1 pound 4 ounces over a M14 rifle fitted with a USGI stock and hand guard. The SRSS design had evolved by this point so that hand fitting of component parts to commercial M14 rifles was totally eliminated with one exception. The third generation stock required some additional inletting in the trigger guard area to accommodate a Chinese M14 trigger housing. The third generation SRSS was designed to keep the rifle overall length to 26.5 " with a Springfield Armory, Inc. M1A SOCOM barrel and muzzle attachment installed. This circumvented the issue of the end user unintentionally assembling a rifle shorter than 26 " long and running afoul of the National Firearms Act. Note that some states have length restrictions on long guns that may be more restrictive than the National Firearms Act.

The stock system was comprised of three major components, cheek rest, lower stock and top rail. SRSS component parts were now interchangeable between commercial and military rifles. The only tools need to install the SRSS, also known as the BullDog 762, were a hex head wrench and a screw driver. The gas system and muzzle attachment were not removed in the installation procedure, only the original stock and the hand guard were swapped and the rear sight assembly was taken off. The third generation SRSS kit was completely manufactured in the United States. It would accommodate any barrel contour. The cheek rest accommodated USGI or extended bolt locks.

All machining tolerances on the BullDog 762 were held to within 0.003 ". The lower stock and top rail were CNC machined on a Haas Automation, Inc. HS-7 CNC horizontal machining center from a single thirteen pound billet of 6061 T6 alloy aluminum. The top Picatinny rail was screwed into two AISI 4140 alloy steel mounting blocks mounted over the barrel, at the chamber and between the legs of the gas cylinder. During development, alloy titanium and alloy aluminum mounting blocks were experimented with but it was found that steel was the best material suited for these parts. The rear mounting block had a "dog leg" that fit over the receiver scope mount bolt hole and was secured by a steel

bolt. The front mounting block was a two piece split clamp secured by screws. The twelve o'clock rail provided a maximum 15 " sight radius with detachable flip-up iron sights as compared to 14.8 " for the U. S. Army M4 carbine.

Quality synthetic rubber was used to form the butt pad and the integral bedding system on the lower stock. The rubber bedding system was in the form of a horse shoe along the top rear receiver area of the lower stock. The bedding system fully seated the receiver while accommodating differences in geometry among commercial brands. The balance of the BullDog 762 was immediately in front of the magazine well. The stock conversions were available from inception in a choice of three finishes, black, tan or green.

Short Rifle Stock Systems, Inc. considered about twenty different ideas for the SRSS safety before settling on a very robust but simple solution, an ambidextrous cross pin that blocked the trigger bar. The cross pin safety was located directly above the stock pistol grip and could be easily manipulated by the firing hand thumb or index finger. A heat treated stainless steel trigger bar ran protected inside a channel along the underside of the lower stock from the M16A2 pistol grip to the firing mechanism. The trigger bar was formed by machine so that it remained interchangeable from stock to stock. The trigger bar worked equally well with rack grade or match tuned firing mechanisms. Use of a solid bar of steel instead of a cable allowed the trigger squeeze to feel the same as experienced with a conventional M14.

The thick rubber butt pad and the straight line stock design reduced felt recoil by 25 % as compared to a rack grade USGI M14 rifle. The BullDog 762 M14 could be field stripped fairly quickly. The cheek rest was removed by unthreading four screws. Otherwise, it field stripped in the same manner as a rack grade M14.

With the introduction of the third generation stock system, a number of options were made available for the basic kit: ambidextrous operating rod handle, aramid sleeve for the cheek rest, cheek rest coin slot fasteners (vice hex head), fully enclosed firing mechanism, brass deflector for left-handed shooters, 6 " versus 4 " three and nine o'clock Picatinny rails, and a threaded detent for barrel tensioning. The three and nine o'clock Picatinny rails were supplied by Vltor Weapon Systems. The threaded detent located at the very front end of the lower stock body placed 0.5 pounds force upward against the barrel for the purpose of reducing barrel vibration.

The fourth generation BullDog 762 stock debuted in November 2011. The three and nine o'clock rails were shortened to 3.5 ". The safety was redesigned with an ambidextrous M16 style safety switch. With the selector switch in safe, a lever engaged the M14 safety thus preventing the factory trigger from being pulled. The cheek rest was given a textured coating to reduce heat transfer between the shooter's face and the stock. The trigger guard was enlarged to better accommodate the use of gloves by the operator. The BullDog 762 stock trigger curvature was changed to give it a more rearward than upward feel thereby creating a more natural trigger pull for this pistol grip stock. A 10-32

threaded hole on each side of the stock, just forward of the magazine well, permitted installation of a sling swivel attachment. The stock assembly weighed 82.8 ounces.

Juggernaut Tactical, Inc. - Juggernaut Tactical, Inc. was established as a California corporation in February 2011. The firm began shipping its M14 Rogue Chassis System in August 2011. This bullpup stock was CNC machined from 6061 T6 alloy aluminium and AISI 4140 alloy steel. It had three, six, nine and twelve o'clock M1913 Picatinny rails. The Rogue stock was available in a black or tan Type III hard coat anodized finish. The stock was made to fit M14 type rifles with standard or medium and heavyweight barrels, depending on mounting brackets used, with or without a selector switch per customer order. It shortened the length of a USGI M14 stock by 11.5 ". The weight of a Chinese M14 rifle with a standard profile 18 " barrel fitted to the Rogue stock was 11 pounds 12.2 ounces. The Rogue stock system itself weighed 6 pounds 0.1 ounces. The Rogue system included a push button safety and alloy aluminum trigger pad.

By early 2012, a left side operating rod handle and a 2 " butt end spacer were optional accessories. The 2 " butt end spacer had an integral Picatinny rail on the bottom and was marked ROGUE. In March of the same year, the company released its second generation Rogue stock. The trigger shoe was redesigned and the rear panel was reshaped to accommodate an XS Products X-14 drum magazine. The newer design stock assembly weighed 5 pounds 1 ounce. Ten limited edition chromium plated units, marked FPS RUSSIA on the right side of the rear panel, were produced in the first batch.

McCann Industries - McCann Industries is a family owned business established by Richard and Debbie McCann in 1968. Initially, the couple started out operating a gun and sporting goods store but the business has evolved and grown into a firearms accurizing and repair shop with complete machine shop capabilities. Unfortunately, Richard McCann passed away on August 13, 2010.

Introduced at the 2008 SHOT Show, the McCann Industries carbon fiber M14 stock was compatible with any M16 type butt stock and pistol grip. It came with a matching carbon fiber hand guard that was secured to the stock with eleven hex head screws. Other than that, it assembled to the rifle like a USGI M14 stock. The McCann carbon fiber hand guard did not clip to the barrel. The front end of the hand guard and stock were formed to mate with the front band. A two piece alloy aluminum fitting was bolted and epoxied to the interior rear end of the stock. This fitting served as the means of attaching the butt stock assembly and pistol grip provided by the end user. The McCann carbon fiber M14 stock would accommodate standard, medium or heavyweight contour barrels. The stock was fitted with 7 " long M1913 Picatinny anodized alloy aluminum rail sections at three, six, nine and twelve o'clock. It was available in black only but could be easily painted like the USGI synthetic stock. The McCann carbon fiber M14 stock was in production by April 2010. Production models of the stock did not require bedding.

ProMag Industries - ProMag Industries (South Gate, CA) introduced its Archangel M1A stock at the 2011 SHOT Show. The carbon-fiber reinforced polymer stock featured a cheek rest and butt pad, both click adjustable. At the lowest setting of the cheek rest, the shooter could use the rifle iron sights to aim with. The stock had a storage compartment inside the integral pistol grip but it lacked a selector cutout and would not accept a lugged receiver. There were six quick detach sling attachment points molded into the stock, two on the bottom rear and front ends and two on either side. The stock fore end was molded with an integral six o'clock Picatinny rail and a rail cover was supplied. A twelve o'clock Picatinny rail cover replaced the traditional style hand guard. The Archangel M1A stock (catalog number AAM1A) required no gunsmithing to install or remove. It was only available in black until desert tan and olive drab green colors were added in March 2013.

During late 2007, Jim Horton (Half MOA, Inc.) modified USGI synthetic stocks by adding an 11 " six o'clock Picatinny rail and giving the assembly a tan color finish. It was known as the Rigid Rail Modification (RRM). Jeffrey Shapiro (NY) custom manufactures carbon-graphite-aramid M14 stocks. In early 2008, Viron Tactical (Omaha, NE) made available its Generation 4 Viron stock for the M14 type rifle. The Generation 4 Viron stock is a wood core completely wrapped in carbon fiber. It has a clamp on each end of the receiver area to allow for secure fitting of different manufacture commercial receivers. The Generation 4 Viron stock accepts M16 compatible butt stocks and pistol grips. This stock has a six o'clock M1913 Picatinny rail, either 6 " or 11.5 " long according to the buyer's preference. The President of Viron Tactical is Kenneth Hall.

Ingram Custom Rifleworks - At the same time the M14S-CQB model debuted, Ingram Custom Rifleworks came out with its M14SA2 Tactical Hunter stock. The M14SA2 had a vertical grip and straight-line comb. The fore end was available in standard or wide profile. The following year, the M14SE2 stock was offered. The M14SE2 stock was a full length stock with a straight-line comb and a M16 style pistol grip.

Hand Guards

USGI Hand Guards - The very first hand guards for the USGI M14 were made of black walnut. These were changed to a slotted fiberglass model in 1961 to allow for adequate ventilation during sustained fire. At least two versions of the slotted hand guard were issued, one with circular vents and the other being the common pattern with oval race track shaped vents. Later, the underside of the slotted fiberglass hand guards were painted silver to help dissipate barrel heat. Apparently, some of the slotted hand guards stayed with the rifles for some time. From a photograph of PFC John F. Dugan, USMC taken in September or October 1966 near An Hoa, Quang Nam, Republic of Viet Nam, one can see a slotted hand guard on his M14 rifle.

The slotted fiberglass hand guards were found to be relatively fragile (especially by U. S. Marines practicing close order drill), and caused mirage over the barrel on rapid fire. So, some changes were made to the hand guard die to create a solid fiberglass hand guard.

The average thickness of the M14 hand guard was increased from 0.070 " to 0.090 ". Both slotted and solid USGI hand guards were ribbed to increase rigidity. Early solid hand guards retained the centerline longitudinal ribs of the slotted model. The solid fiberglass hand guard design was finalized in October 1961. The solid hand guard became the standard in 1962. USGI solid hand fiberglass guards were made in at least four color variations, coffee, brown, dark brown and black although the drawing only specifies one shade of lusterless brown, FED-STD-595 number 30045. Late production solid fiberglass hand guards have two ribs on the underside of the hand guard band (clip) groove. Wood and slotted fiberglass hand guards on USGI M14 and M14 NM rifles were replaced with solid fiberglass hand guards during overhaul.

Fiberglass was developed in the late 1940s. It is a composite material made up of glass fibers dispersed throughout a polymer resin matrix. Fiberglass has about the same longitudinal tensile strength as wood but it is not as stiff. The benefits of fiberglass hand guards over wood hand guards are less maintenance and better resistance to the effects of weather. Wood and fiberglass both have poor thermal conductivity which means they are excellent insulators. This is a useful engineering property for the M14 hand guard and stock for obvious reasons.

USGI M14 solid fiberglass hand guards have been observed with the following markings on the bottom side: 1) the letters DT followed by a number ranging from 2 to 67 or 2) the letters WC followed by a number or 3) just a number such as 2, 3, 4, 5, 6 or 8 as found on those made by Structurlite Plastics Corporation. The slotted hand guards have been observed with markings such as DT 9, DT 10, DT 12, DT 15, DT 23, DT 25, DT 31, and DT 32 on the underside. Earlier slotted and solid fiberglass hand guards were not painted silver on the bottom. Later production slotted and solid hand guards were painted silver on the bottom for heat dissipation. Solid fiberglass USGI hand guards weigh about 3 ounces and are about 0.010 " thicker than Chinese hand guards.

Commercial Production Hand Guards - Between 1978 and 1994, Springfield Armory, Inc. sold heavy walnut match, fancy burley walnut, extra fancy AAA grade walnut and laminated walnut/maple hand guards for the M1A. It has installed commercial reproduction plastic hand guards on M1A rifles from the mid-1990s onward due to the scarcity of new USGI hand guards. Early plastic hand guards were shiny but later copies had a dull finish. Chinese M14 hand guards appear to be manufactured by injection molding. They are marbled brown on top and silver on the bottom. The bottom side was marked DT25. Reinhart Fajen, Inc. and Minelli S.p.A. offered matching wooden hand guards with their M14 stocks. Boyd's did sell matching hand guards (walnut, nutmeg laminate and pepper laminate) for its wood stocks until production ended in October 2007 and then again beginning January 2010. Wenig Custom Gunstocks, Inc. offered walnut and laminated birch hand guards for its M1A Scope Stock. Commercial wood hand guards were noticeably thicker than the USGI wood hand guards. Fulton Armory sold a more rugged solid glass-reinforced polymer brown color hand guard, as compared to even the USGI solid fiberglass hand guard. The Fulton Armory hand guard was available

with an optional black color textured epoxy coating. Fulton Armory glass-reinforced polymer and Springfield Armory, Inc. plastic hand guards were not silver color on the bottom side.

Carbon Fiber Hand Guards - In 2004 and 2005, there was a limited amount of research and development performed by private individuals to manufacture carbon fiber M14 hand guards. Carbon fiber-polymer, or carbon fiber for short, is one of many types of fiber-reinforced composite materials. A reinforced-fiber composite material is made up of strong but brittle fibers residing inside a tougher and more ductile solid matrix material, e.g., bricks made of mud and straw.

The carbon fibers can be loose and randomly arranged inside the matrix or they can be woven into two or three dimensions. Fibers can be formed from metal, glass, plastics, carbon, or other materials. The matrix material can be made from a metal (aluminum, magnesium, tin, etc.) or a polymer (polyester, epoxy, vinyl ester, etc.) or a ceramic (aluminum oxide, zirconium oxide, glass, etc.). Polymer base matrices are suitable for operating temperatures below 600 degrees Fahrenheit, e.g., M14 hand guard.

The size, shape and number of parts to be made will influence the choice of manufacturing method. Loose carbon fibers can be mixed with a liquid resin (matrix material). The mixture could then be loaded into an injection molding machine. The mixture is pushed through a die to form the part. Or the composite material mixture could be sprayed against a form and allowed to harden.

Loose, random carbon fibers may be held inside a sheet of matrix material. Such a structure is referred to as a mat. The part can be formed by laying and pressing reinforced-fiber resin mat against a die, or pattern of the part. This method is suitable for manufacturing M14 hand guards. Pressing the mat against the die to form the part can be accomplished in a number of ways: 1) pushing a hand roller against the mat while the mat is lying in the die 2) using gas pressure or vacuum to press the mat against the die or 3) using a matching die to push the mat against the die underneath it. The form is taken from the die, cured, and the flashing, or trim removed to create the final product. Fiber-reinforced composite material can be finish machined by conventional means (saw, router, mill, drill, shear, sander, etc.) but precautions must be taken to avoid skin contact or inhalation with splinters and dust.

Carbon fiber mat is more expensive than fiberglass mat. Carbon fiber-epoxy composite material is several times stronger and stiffer than fiberglass, pound for pound. Not surprisingly, the greater strength of carbon fiber is more expensive. In 2005, carbon fiber mat was about four times the cost of fiberglass mat. Carbon fiber will deteriorate over time from ultraviolet ray exposure (sun light). Thus, a clear polyester coating containing an ultraviolet ray inhibitor should be sprayed on the surface of the die before the carbon fiber mat is laid down.

Epoxy resin is stronger than polyester resin or vinyl ester resin but also more expensive. M14 hand guards made from three layers of carbon fiber-epoxy resin composite material are strong enough to support the weight of a man standing in the middle with the ends supported without breaking or cracking. However, carbon fiber-epoxy resin is a brittle material. When the sides of a carbon fiber-epoxy resin hand guard were flattened together in a vise the material broke where held by the jaws of the vise.

In 2005, a private individual in the United States made carbon fiber-epoxy resin M14 hand guards for himself and a friend. When finished, the hand guards were about 0.030" thick using the vacuum bag method described above. One of the hand guards had an aesthetically pleasing turquoise color. He was able to produce this color by adding a small amount of blue pigment to the clear polyester ultraviolet ray inhibitor coating.

USGI Sights

The M14 type rifle has the best iron sights of any battle rifle. The sights are easy to operate. Once a 250 meter zero is set, the sights do not need adjust under most battlefield conditions. The M14 sights are almost identical to those found on the M1 Garand rifle but it has the longest sight radius of any magazine fed semi-automatic battle rifle in the world. The M14 rifle has a sight radius of 26.75 " with the rear sight aperture set at 100 meters. The very long sight radius helps maximize the battlefield accuracy of the M14 rifle. The long sight radius also makes it easier for farsighted shooters to use iron sights. There are three sizes of front sight blades and three sizes of rear sights.

Rear Sight Assembly - The standard issue rear sight aperture has a diameter of 0.069 " + 0.005 ". The USGI M14 also had two National Match rear sight aperture sizes, 0.0520 " and 0.0595 ". Either National Match rear sight aperture can be fitted with an adjustable hood (National Match rear sight apertures without the hood were made only for the M1 Garand rifle). Use of the hood on the rear sight allows for one-half minute of angle adjustments in elevation. The elevation knob always moves point of impact one minute of angle per click, while rotating the sight hood will add or subtract a half-minute of angle of elevation. A notch in the rear of the hood designates the direction of the extra adjustment—rotating the notch from the six o'clock position to the twelve o'clock position will add elevation, while rotating the notch from the top position to be on the bottom will subtract elevation. The hooded eyepiece was developed by no later than May 1961 at Springfield Armory by Nicholas J. Angelica.

Rear Sight Base - The M14 standard (rack grade) rear sight base was borrowed from the same 1937 vintage part for the M1 Garand rifle. Additionally, three other rear sight bases could fit the M14 rifle. These rear sight bases were marked NM, NM/2 and NM/2A. The NM rear sight base was designed about 1958. It accepted a non-hooded rear sight aperture but would not allow a hooded aperture to fully lower into the base. The 1961 design NM/2 rear sight base was a NM rear sight base machined after manufacture to allow a hooded aperture to fully seat in the base. Subsequent to the NM/2 modification,

the 1963 design NM/2A rear sight base was a newly manufactured part that allowed the rear sight base to be fully lowered into the base.

Elevation and Windage Knobs - USGI and some commercial manufacture M14 elevation knobs have the letter M inscribed between the numbers 10 and 11. This denotes calibration in meters. If the elevation knob does not have a letter M and the highest number is 12, it is calibrated in yards and was made for the M1 Garand rifle. If the letter M is missing and the highest number is 11, it is a commercial made elevation knob and calibrated in meters. As a rule, M1 Garand rifle elevation knobs were not allowed on M14 rifles in the U. S. military. However, for a period of four months or less in 1969, M1 Garand rifle elevation knobs were authorized for replacement of M14 elevation knobs on M14 rifles at Fort Bragg. During this time, there was a shortage of M14 elevation knobs in the Army supply system. The elevation knobs on the M14 rifles at the Basic Training shooting ranges had worn out from use by recruits. In order to keep the M14 rifles in service for training and qualification, Rock Island Arsenal authorized the short term substitution of M1 Garand elevation knobs for the M14 rifles.

The windage knob on an M14 type rifle will either be the standard one minute per click adjustment, or the National Match model of one-half minute of angle per click adjustment. The National Match windage knob must be matched to a National Match rear sight base because they both have finer threads than the standard USGI parts. The finer threads of the National Match rear sight parts allow the smaller angle adjustments.

Front Sight - The front sights are classified by the width of the rear side of the sight blade. The standard or USGI front sight is 0.084 " - 0.010 " wide. The military National Match front sight is 0.065 " - 0.005 " wide. The top surface of both sight blades slope downward at an angle of 5 + 1 degrees, rear to front. The M14 front sight can be used as a range finding device by the shooter. Assuming a 22 " barrel length, a 20 " wide target (frontal view of a deer) will appear to be the same width of the front sight post at the following distances: 0.062 " USGI NM sight - 230 meters (251 yards), 0.072 " commercial NM sight - 198 meters (216 yards), and 0.084 " USGI sight - 169 meters (185 yards). NM sights will be marked NM 062 or NM 072 as appropriate.

Combination Gas Cylinder Lock Front Sight - The traditional M14 front sight and flash suppressor assembly is not the most suitable attachment point for a sound suppressor. The combination gas cylinder lock front sight was developed by Smith Enterprise, Inc. to meet the U. S. Navy requirement to allow for the possibility of installing a sound suppressor on Navy Mk 14 Mod 0 rifles. There are two basic designs of the Smith Enterprise combination gas cylinder lock front sight, a hooded non-adjustable post type sight and a traditional dovetail type sight.

If a M14 type rifle is assembled with a Sage International M14EBR or Chop Mod stock, the fastening of the Sage operating rod guide to the stock causes the bullet point of impact to be lower than it would be if a non-Sage stock was used. Also, a shorter barrel

requires the height of the front sight to be taller to achieve the same point of impact as the standard configuration of 22 " barrel and traditional USGI flash suppressor and front sight. Thus, when SEI installs a combination gas cylinder lock hooded non-adjustable front sight, the barrel length (18 " or 22 ") and the stock (Sage or non-Sage) are factors in setting the height of the post sight.

The hooded non-adjustable post type sight, model GLFS-H, was developed by no later than 2003. It was the first combination gas cylinder lock front sight produced by Smith Enterprise. The advantages of the hooded non-adjustable post type combination gas cylinder lock front sight over the traditional M14 front sight are faster target acquisition, better front sight protection, and no possible shifting of the front sight. Subsequently, the GLFS-D-18 and GLFS-D-22 combination gas cylinder lock dovetail type front sights were developed for users who wanted to be able to fine tune the iron sights while maintaining the option to mount a sound suppressor in conjunction with the SEI M14DC flash hider. The GLFS-D-18 model has a taller sight base to account for the shorter 18 " barrel it is mounted on. Similarly, the GLFS-D-22 part is intended for use with 22 " length barrels.

A very few of the Smith Enterprise M14 EBR combination gas cylinder lock dovetail type front sights have metal removed from under the front half of the dovetail sight base. The machining cut is a pronounced ninety degrees under the sight base. This particular modification was done in 2003 to allow installation of a Smith Enterprise direct connect flash hider on a 17 5/8 " barrel. These parts were marked: top line - PAT. PEND. bottom line - U.S.N. All Smith Enterprise combination gas cylinder lock front sights were made from nitrocarburized AISI 4140 alloy steel. The hardness specification for the combination gas cylinder lock front sights was 55 to 60 HRC. From 2004 onward, Smith Enterprise stamped its parts with serif font lettering.

Beginning in July 2005, the Navy issue combination gas cylinder lock dovetail type front sight was marked U.S.N. on the top line and SMITH ENT on the bottom line. Later that year, Smith Enterprise began marking combination gas cylinder lock front sights with U.S.A.F. and SMITH ENT in a similar fashion. By April 2006, the Navy Mk 14 issue combination gas cylinder lock sight marking was changed to U.S.N. on the top line and MK-14 on the bottom on the front side and S.E.I. on the rear side. The part markings change again by December 2006 to read on the front side: top line - U.S. and bottom line - M-14. The rear side was marked the same, S.E.I.

Installation of a Sage International, Ltd. M14 stock locks the stock and barrel together at a third point through the proprietary operating rod guide (the other two contact points are the stock ferrule to barrel front band and the receiver-to-firing mechanism interface). This fastening of the barrel improves accuracy but causes the non-Sage stock combination gas cylinder lock front sight, model GLFS-D-22, to have a point of impact markedly lower than what it would otherwise. The GLFS-D-18 model is employed on U. S. Navy and U. S. Air Force Mk 14 variant rifles which use the Sage International stocks. In 2006, Smith Enterprise, Inc. installed GLFS-D-22 gas cylinder lock front sights installed on M14

rifles rebuilt for the U. S. Army 101st Airborne (Assault) Division.

Both models GLFS-D-18 and GLFS-D-22 have a modest bevel on the front end under the barrel. This bevel facilitates use of the Smith Enterprise direct connect flash hider on 17 5/8 " barrels equipped with these front sights. The longer distance from front to rear of the dovetail style combination gas cylinder lock front sights does not permit use of the M2 type bipod.

Gruning Precision installs its combination gas cylinder lock front sight on M1A SOCOM conversions. The Gruning Precision SOCOM front sight is an adjustable M16 post housed within the body of the hooded gas cylinder lock front sight. The part is engraved GRUNING PRECISION on the right hand side. The bottom of the gas cylinder lock front sight is contoured to accommodate the USGI design gas cylinder plug. In 2013, Gemini Technologies (Eagle, ID) offered a M1A SOCOM compatible combination gas cylinder lock front sight. It had industry standard 5/8 " x 24 external threads for mounting muzzle attachments. This part allowed use of USGI design gas cylinder plugs.

Commercial Sights

Chinese rear sight aperture diameter tends to be larger than on the USGI standard model. Tooltech Machine, Inc. (Oxford, MI) can install a 1/8 " tritium insert into the M14 type front sight for use in low light conditions. In 2009, Ameriglo, LLC (Atlanta, GA) introduced a tritium dot standard height front sight to the commercial market. Brownells, Inc. sells an Alley Supply globe style front sight and set of inserts for the M14 type rifle. This type of front sight is useful in reducing eyestrain in target match shooting. The Rock SOPMOD M14 and Troy Industries M14 MCS can use flip-up type M16 type sights.

Springfield Armory, Inc. - Springfield Armory, Inc. made a 0.072 " NM front sight for its match rifles in 1987 and 1988. It is marked NM 072 on the side. Springfield Armory M1A Scout and Bush rifles are fitted with slightly different front sights to compensate for the shorter barrel. The Scout / Bush front sight is marked NM 062 on the side. Its front sight blade is 0.062 " wide. The blade height itself appears no different than a standard USGI sight, but its base is 4 millimeters taller. It measures 0.697 " to 0.705 " from the bottom of the front sight base to the top of the rear side of the blade. This in comparison to the USGI design front sight which has a nominal height of 0.567 " from the base to the top of the rear side of the blade. This is significant as each 0.008 " is equivalent to one click of elevation on the rear sight knob for a 22 " barrel. The wrong front sight for either barrel will make a huge difference on the setting of the rear sight aperture for the sight zero.

Smith Enterprise, Inc. – Smith Enterprise M14 National Match front and rear sight parts are machined from AISI 4140 alloy steel bar stock using the wire EDM method. The hooded rear sight aperture was made available in 2009 and the standard rear sight aperture in 2010. The Civilian Marksmanship Program and Brownells distributed Smith Enterprise M14 National Match sights beginning in 2009.

In August 2005 Smith Enterprise, Inc. debuted its M14 dovetail style tritium 0.076 " diameter dot front sight for low light conditions in short range combat. This sight was made from wire EDM manufactured AISI 4140 alloy steel and finished with a phosphate coating. The sealed tritium vial was supplied by Trijicon, Inc. In March 2006, Smith Enterprise, Inc. made available a second tritium front sight, a luminescent vertical bar post model. Like the tritium dot sight, this sight was also made from wire EDM machined AISI 4140 alloy steel and given a phosphate finish. It was marked SMITH ENT. on the right hand side. The luminescent post was supplied by Unertl Optical Company, Inc. In December 2008, the company finished its first batch of USGI design front sights.

Smith Enterprise, Inc. brought its threaded dovetail front sight base to market in 2010. The part was machined from AISI 1144 fatigue proof steel, nitrocarburized, and finished with a manganese phosphate coating. This material has a yield strength of about 180,000 PSI. The threaded dovetail front sight base retained the existing front sight, flash suppressor nut, and front sight base setscrew. For a rifle with a barrel 18 " or longer, this sight base design offered some attractive advantages: 1) retention of the original sight radius 2) quick installation or removal of the muzzle attachment and 3) an industry standard male thread pattern, 5/8 " x 24, allowing use of multiple brands and types of muzzle attachments.

In response to passage of the New York Secure Ammunition and Firearms Enforcement (SAFE) Act, Smith Enterprise, Inc. designed and manufactured a M1A SOCOM combination gas cylinder lock front sight without a muzzle attachment. The front sight deck height of this part was lowered 0.045 " as compared to the factory part so rear sight settings could remain unchanged. The development work had been completed by March 2013. The parts were available for sale the following month.

XS Sight Systems, Inc. - In 2004, XS Sight Systems introduced a M14 type rifle front sight for Close Quarters Battle situations. It is the factory issue front sight for the M1A SOCOM models. The front sight is a post sight. The rear side of the post, facing the operator, is a white color vertical strip with a tritium dot centered within the strip. This sight set is designed for faster acquisition of targets over the traditional sights. Sight sets for 16 ", 18 " and 22 " barrels are available. The XS Sight Systems front sight installed on M1A SOCOM models has a height of 0.725 " from the bottom of the base to the top of the rear side of the post. The rear sight aperture on the commercial M1A SOCOM and government Mk 14 Mod 0 models has been enlarged from the standard military diameter for faster target acquisition. In June 2009, XS Sight Systems brought its hooded post front sight for the 22 " barreled M14 to market. Part numbers are as follows: a) hooded front sight with tritium dot for 22 " barrel - 10-21665-580-4 b) hooded front sight with tritium dot for 18 " barrel - 10-21665-675-4 c) winged style front sight with tritium stripe for 22 " barrel - 11-21665-580-6 and d) winged style front sight with tritium stripe for 18 " barrel - 11-21665-675-6.

In May 2007, Marstar Canada introduced M14 metric thread gas cylinder lock front sights made in-house. The Marstar gas cylinder lock hooded front sight was manufactured from a choice of two materials, AISI 4140 alloy steel with a phosphate coating (catalog number M14-106) or titanium with a dull satin finish (catalog number M14-106T). These parts were sized for Chinese 22 " barrels only. By February 2011, Dlask Arms Corporation (Delta, BC) offered a blued finish steel gas cylinder lock front sight for Chinese barrels shortened to 18.75 ".

In mid-2010, Tech-SIGHTS, LLC (Hartsville, SC) introduced an all steel construction M16 style front sight for the M14. Its design utilized an extended length M14 front sight base to house a M16 front sight. Like the M16, the TSM14 front sight was adjustable up or down and locked into position by a detent. The assembly was secured to the flash suppressor dovetail with a hex head screw. The M16 front sight post is 0.047 " wide.

Muzzle Attachments

Several different muzzle attachments are available for the M14 type rifle. They can be classified into four categories, flash suppressors and hidere, muzzle brakes and stabilizers, grenade launchers and sound suppressors. Sound suppressors are discussed in separate sections. The reader should consult federal, state and local laws before removing or installing any muzzle attachments to an M14 type rifle. Some muzzle attachments may be illegal to attach to the rifle.

Closed Prong Flash Suppressors / Flash Hidere - A flash suppressor or hider is desirable for military purposes. It serves to eliminate the flash signature of a rifle or machine gun thereby conserving the shooter's night vision and concealing his position from the naked eye. The flash suppressor works by cooling the gunpowder gas temperature to a point below the flash point. The wider bottom prong of the USGI and NM M14 flash suppressors aids in reducing recoil and muzzle rise. Finally, the flash suppressor serves as an attachment platform for the front sight, M6 bayonet, and M76 grenade launcher.

Flash suppressor testing of a T20E2 rifle in late 1951 demonstrated that a longer five prong suppressor was more effective at reducing muzzle flash than a shorter three prong suppressor. Consequently, the M14 flash suppressor design consists of five long closed prongs with one wider prong centered at the six o'clock position. This also reduces muzzle climb and dust signature. The USGI flash suppressor was fitted on all USGI M14 rifles except for match M14 rifles.

Match grade M14 rifles were fitted with flash suppressors that have been reamed out to National Match specification (a standard taper reamer is used to enlarge the end of the flash suppressor to 0.406 " wide). The USGI M14 flash suppressor drawing F7791053 required the wrought or cast specified steel to be heat treated before machining. This heat treatment procedure consisted of first heating the specified steel to between 1350 and 1575 degrees Fahrenheit. The steel was then oil quenched and tempered for a

minimum of thirty minutes to achieve the specified hardness.

Brookfield Precision Tool also made a special flash suppressor for the U. S. Navy. It had a front sight machined into it as it was built to support a silencer. The silencer hid or interfered with the standard front sight so the standard flash suppressor was not used. Some Chinese made M14 type rifles imported into the United States after March 1989 have faux flash suppressors or the suppressors completely cut off at the muzzle. Some of the imported Chinese M14 rifles had the flash suppressor tack welded to the flash suppressor while others were not permanently secured at all. The Chinese faux flash suppressors were made without milling out the slots between the prongs. In 2001, Entreprise Arms, Inc. sold a M16A2 bird cage style flash suppressor for M14 type rifles. This has the advantage of shortening the rifle overall length by about one and one-half inches.

Yankee Hill Machine Co., Inc. introduced its Phantom M14 Flash Hider in 2008. It was offered with a detachable dovetail front sight base (Item # YHM-3080-M14-A) or without (Item # YHM-3080-M14). The front sight base was designed for use with a standard USGI or National Match front sight. It was secured to the rear end of the flash hider by a hex head screw. The detachable dovetail front sight base was also sold separately (Item # YHM-3330). In 2010, the company introduced its Phantom M14 QD Mount flash hider with the detachable dovetail front sight base (Item # YHM-3302-M14-SA). The mount allowed installation of its Phantom Stainless 7.62 sound suppressor. The detachable dovetail front sight base was not compatible with M14 barrels 18.5 " or shorter.

Open Prong Flash Suppressors / Flash Hiders – Smith Enterprise, Inc. makes an open prong flash hider which is not subject to problems normally associated with such designs. The straight prong flash hider design is susceptible to loosening under fire unless it is very tightly torqued on to the barrel. The Smith Enterprise flash hider solves this problem. It was invented, designed and refined by Sonja Sommers of Smith Enterprise, Inc. in 1994 and early 1995. It is a patented accessory. This flash hider is machined from AISI 8620 bar stock alloy steel then case hardened to provide a tough core and hard surface for maximum strength. It is given a phosphate coating and comes with a conditional lifetime guarantee. The dimensions are 2 ¼ " long and 0.861 " diameter. It is sound suppressor capable. The flash hider is secured to the barrel by threads but it is not a timed item (no specific parts need to be lined up when installed). When the Smith Enterprise flash hider is fastened, it is simply snugged tight and it does not need a lock washer to stop its rotation at any specific alignment. Four special angle helical flutes evenly force more than half of the gas out to the sides before the bullet clears the flash hider. This keeps the propellant-rich gas in the path of the bullet cool enough to prevent re-ignition and producing visible light, i.e., muzzle flash. Even distribution of the gas flow reduces muzzle climb even in full automatic fire.

Smith Enterprise manufactured Sommers design M14 flash hidere for a short time in 1994. These flash hidere had six degree angled flutes, M16 style blank firing attachment

grooves and a muzzle end snap ring brush protector groove. These features were incorporated into the 1995 patent. Subsequently, the Smith Enterprise M14 flash hider design was changed to a helix design without the blank firing attachment and brush protector grooves. It was discovered through testing that the brush protector groove enhanced flash so it was removed from the design. The helical flash hider tightens itself on the barrel's muzzle threads when the weapon is fired. The design also helps to evenly align exiting barrel gas to improve accuracy with all bullet types. The flash hider will have "left hand" angled slots for barrels with left hand threads and "right hand" angled slots for barrels with right hand threads. The Smith Enterprise flash hider has successfully passed the U. S. Navy 5000 round endurance test. It is in service with many U. S. law enforcement agencies and has been used in combat by the U.S. military.

Smith Enterprise offered several types of M14 flash hidings: 1) direct connect 2) traditional style front sight base with an integral flash hider 3) standard barrel muzzle attachment kit and 4) M1A SOCOM barrel muzzle attachment kit. The direct connect model threaded directly to the barrel muzzle threads. The traditional style front sight base and standard barrel muzzle attachment kit versions attached to the barrel using the flash suppressor nut. The standard barrel muzzle attachment kit was a two part affair, a traditional style front sight base with male threads and a removable flash hider with female threads. The M1A SOCOM barrel muzzle attachment kit was also assembled into two parts, a combination gas cylinder lock front sight with a dovetail base with male threads and a removable flash hider with female threads. The M1A SOCOM barrel kit flash hider was patterned on the SA80 rifle flash hider supplied to the British military by Smith Enterprise, Inc. By June 2010, the Smith Enterprise, Inc. M1A SOCOM combination gas cylinder lock front sight was redesigned with 5/8 " x 24 x 0.635 " male threads. This design change provided the end user a greater choice of commercial muzzle attachments. Except for the direct connect devices, these muzzle attachments used USGI deck height compatible front sights. The Smith Enterprise direct connect and M1A SOCOM kit flash hidings were sound suppressor capable (all NFA Rules apply). Use of the M1A SOCOM kit flash hider in conjunction with a sound suppressor required installation of a modified gas cylinder plug available from Smith Enterprise, Inc. The modified gas cylinder plug allowed the sound suppressor to fully engage the flash hider. Smith Enterprise, Inc. modified gas cylinder plugs made before November 2009 should only be used on 16 " barreled rifles. After October 2009, the modified gas cylinder plugs were bored with a volume about 0.5 cubic centimeters larger than a USGI gas cylinder plug. The increased volume made them suitable for use with any length barrel. In 2012, a 10 threads per inch exterior groove was added to Smith Enterprise, Inc. flash hidings. The exterior groove of the G6A3 style flash hider made it easier to remove a sound suppressor after extended use.

Springfield Armory, Inc. sold its M1A-A1 model with an open five prong flash hider from 1981 to about 1984. The prongs were about 1 " long and had a slight taper narrowing to the front end. Starting in 2006, Arizona Response Systems (ARS) offered a muzzle attachment for the M1A SOCOM models. ARS modified the Springfield Armory, Inc. M1A

SOCOM muzzle attachment by removing the muzzle brake and attaching an open four prong flash hider to the factory combination gas cylinder lock front sight. Entreprise Arms, Inc. listed a M14 open prong flash hider for sale for a time on its web site.

Adjustable Vibration Flash Hider - In years past, AWC Systems Technology has modified the M14 type rifle to increase accuracy by reducing barrel vibration. This modification included removing the front sight and flash suppressor, cutting the gas cylinder just forward of the spindle valve, welding a HK91 front sight just forward of the front band and threading an adjustable bird cage style flash hider on the barrel. This adjustable flash hider works in much the same way as the vibration reducing muzzle attachment on Browning bolt action rifles. The flash hider is turned on the threads to find the optimum spot where accuracy is maximized for a given cartridge load.

Muzzle Brakes - Muzzle brakes are installed on M14 type rifles to reduce muzzle climb, felt recoil or to comply with state law, e.g., California's prohibition of civilian-owned flash suppressors. The disadvantage is that a muzzle brake adds eight or nine decibels to the rifle sound signature. JP Enterprises, Inc. (Hugo, MN), famous for its M16 style muzzle brakes, has in the past manufactured a muzzle brake for the M14 type rifle. This muzzle brake included the sight base for the traditional dovetail front sight. In October 2010, JP Enterprises, Inc. manufactured a batch of its large profile tactical compensators to mate up and index with the Delta P Design M14 muzzle adapter. The muzzle end outside diameter was 1.2 ". The large profile tactical compensator was manufactured from stainless steel and given a black oxide finish. Fabian Brothers Sporting Goods, Inc. (1986 address 3333 Midway Drive Suite 104 San Diego, CA 92110) made and marketed its M14 DTA MIL BRAKE muzzle brake in the mid-1980s. It was a two piece muzzle attachment consisting of a muzzle brake and flash hider. It was threaded on to the rear portion and secured with a lock nut. The flash hider was narrower than the muzzle brake section. The rear portion was secured to the barrel with the traditional flash suppressor "castle" nut. The rear portion had a bayonet lug and dovetail mount for the front sight. It was marked front to rear: front line - Fabian Bros middle line - MUZZLE STABILIZER rear line - CAL. 7.62. Even on automatic fire, it worked very well to keep the muzzle from rising. James E. Clark, Sr. of Clark Custom Guns, Inc. (Princeton, LA) bought the design rights from Fabian Brothers. Clark Custom Guns produced another M14 muzzle brake for a time (catalog number CLK-800-M1A). It was designed by Jim Clark, Jr., Jerry Miculek, and Kay Clark-Miculek. This second muzzle brake had four radial holes at three and six o'clock and two smaller holes at twelve o'clock in an otherwise solid wall cylinder. The muzzle brake was integral with the front sight dovetail and bayonet lug.

With the exception of M1A SOCOM models, Springfield Armory, Inc. installs its muzzle brake on M1A Scout Squad models and all M1A rifles shipped to California. The muzzle brake is machined with an integral front sight base. It is secured to the barrel by the flash suppressor nut, similar to the USGI flash suppressor. In 1996, the first M1A-A1 Scout units were assembled with a combination gas cylinder lock and muzzle brake. A separate front sight base was fitted around the barrel behind the gas cylinder lock. It was secured

by tightening a screw at the bottom of the sight base. The M1A SOCOM models have a proprietary combination gas cylinder lock and muzzle brake. Springfield Armory, Inc. installed a combination muzzle brake and stabilizer on its M25 model. That muzzle attachment has no provision for mounting a front sight. The M25 barrel threads were cut to time with the proprietary muzzle attachment. If the M25 muzzle attachment is installed on a USGI design M14 barrel, propellant gas will blow by the threads out its rear end.

Similar to its flash hidens, Smith Enterprise offers four models of M14 muzzle brakes: 1) U. S. Coast Guard (USCG) 2) Direct Connect California Compensator 3) standard barrel muzzle attachment kit and 4) M1A SOCOM barrel muzzle attachment kit. The Smith Enterprise, Inc. U. S. Coast Guard muzzle brake was first developed in 1996. It was machined from AISI 8620 alloy steel. After 2008, the two halves of the brake were made from fatigue proof AISI 1144 alloy steel and marked S.E.I. on the front end. This muzzle brake has successfully passed the U. S. Navy 5000 round endurance test. The USCG and standard barrel kit muzzle brakes attach to the barrel in the traditional manner, a threaded flash suppressor nut. In October 2007, Smith Enterprise, Inc. made available its Direct Connect California Compensator. This part was made to look like the Smith Enterprise direct connect flash hider including the helical flutes but was in fact a muzzle brake making it legal for use in California. However, a small number were sold initially with straight flutes. The standard barrel and M1A SOCOM barrel muzzle attachment kits were introduced in mid-2008. All Smith Enterprise muzzle brakes use a standard USGI or National Match front sight except for the Direct Connect California Compensator which has no provision for a front sight like its sibling, the direct connect flash hider.

The standard barrel and M1A SOCOM kits both utilize threaded muzzle brakes to attach to the dovetail front sight base and the combination gas cylinder lock front sight, respectively. The removable muzzle brakes are included in each kit. Other muzzle brakes with 5/8 " x 24 threads are compatible with the Smith Enterprise, Inc. muzzle kits. The Primary Weapons Systems FSC30, introduced in mid-2009, and the Battle Comp Enterprises, LLC BABC, which debuted in 2010, are such examples. The Smith Enterprise, Inc. Direct Connect California Compensator and M1A SOCOM kit muzzle brakes are sound suppressor capable (all NFA Rules apply). Use of the M1A SOCOM kit muzzle brake in conjunction with a sound suppressor requires installation of a modified gas cylinder plug available from Smith Enterprise, Inc. The modified gas cylinder plug allows the sound suppressor to fully engage the muzzle brake. In 1985, Smith Enterprise, Inc. manufactured a prototype muzzle brake that slipped over the USGI flash suppressor. The part was machined on an engine lathe by Ron Smith. Only five or six were made. The was secured with a compression nut at the rear end. In the past, Entreprise Arms, Inc. produced a steel muzzle brake with a black oxide finish.

Troy Industries offered a CQB combination flash suppressor/muzzle brake for the Rock SOPMOD M14. It was machined from AISI 4140 alloy steel and given a phosphate finish. The Troy Industries SOPMOD M14 muzzle attachment threads were made to fit the SOPMOD M14 barrel. Thus, the muzzle attachment threads were not made to 5/8 " x 24

dimensions, a common .308 caliber barrel thread pitch for sound suppressors. The front surface of the Troy Industries muzzle compensator consisted of many pyramid shaped points. The purpose of this was to prevent slippage of the muzzle when pressed against an opponent in extreme close quarters combat. By 2010, Troy Industries offered its phosphate coated M14 medieval muzzle brake manufactured from AISI 8620 alloy steel and the 7.62mm NATO caliber Claymore Muzzle Brake with 5/8 " x 24 female threads.

The SOCOM Recoil Reducer is one part of the M1A SOCOM conversion offered by Gruning Precision. The Gruning Precision muzzle brake threads directly on to the M1A SOCOM barrel. Testing has proven that the Gruning Precision muzzle attachment reduces recoil force by 30 %.

In 2007, Joe Dlask (Dlask Arms Corporation) produced a small lot of muzzle brakes suitable for Chinese M14 barrels. The production Dlask Arms muzzle brake had four ports. It was threaded on to the barrel and then secured to the barrel flash suppressor splines by three small hex head setscrews. A pre-production version of this muzzle brake had a fifth port drilled at the front end for test instrumentation. In December 2012, The Upgrade Path Inc. for M14.ca offered its two port Light Muzzle Brake (LMB). The LMB was threaded for Chinese barrels.

Juggernaut Tactical, Inc. introduced its Juggerbrake muzzle brake in 2011. The part was machined from AISI 316 stainless steel into three sides with three spikes on the muzzle end. The Juggerbrake was available in black or satin finish.

Young Manufacturing, Inc. (Phoenix, AZ) produced two M14 muzzle brakes, the YM-14 and the YM-14 radial compensator. Both items were designed to have the same appearance as a USGI M14 flash suppressor but were actually muzzle brakes. The YM-14 had an internal chamber with three ports which directed gas flow upward to reduce muzzle climb. The YM-14 radial compensator had a radial cut on either side to better distribute the gas flow. Either model may be purchased with or without a bayonet lug. The AISI 8620 alloy steel muzzle brakes were carburized and hardened to 89.5 HRN.

USGI M14E2/M14A1 Muzzle Stabilizer - The M14E2/M14A1 was fitted with the M2 bipod clamped to the gas cylinder and a stabilizer assembly fitted over the flash suppressor. Most rifle shooters are right-handed. Consequently, the stabilizer assembly had holes drilled in it which direct the majority of the muzzle gas to exhaust to the left side and slightly upward of the flash suppressor. This helped reduce muzzle climb during automatic fire. The original 1962 design of the USGI muzzle stabilizer did not include a locking mechanism also known as the yoke assembly. In September 1963, a yoke assembly was added to the muzzle stabilizer design. The early style yoke stop did not lock well enough to keep the stabilizer on the rifle during extended firing. So, the yoke stop was redesigned in April 1966 to the final version that is available today as a commercial reproduction. The second and final versions of the USGI M14E2 stabilizer assembly will be marked on the operating rod side of the locking mechanism with the part

number. The second version was marked 7791661. The final version was marked ASSY 11686521. Earlier second version muzzle stabilizers were marked M on the front side of the locking mechanism lug while later second version and third version units were marked MPI in the same spot. Presumably, M and MPI mean the part was examined by magnetic particle inspection.

In the late 1980s, NSWC Crane modified the USGI M14A1 muzzle stabilizer. The muzzle stabilizer itself was redesigned as a hollow cylinder with semi-circumferential radial slots along most of its length but at the front end five wider radial slots were milled across the top and sides leaving the bottom solid. The front half of the NSWC muzzle stabilizer had more solid surface on the bottom than the rear half. The NSWC muzzle stabilizer project was begun by the supervisor of David P. Armstrong. His design greatly reduced felt recoil. Mr. Armstrong refined its design to minimize muzzle rise in automatic fire. Testing of the NSWC muzzle stabilizer in 1989 showed marked improvement in recoil reduction and muzzle control over the USGI design. The NSWC muzzle stabilizers were fabricated using both USGI and commercial reproduction M14E2 yoke assemblies. Mr. Armstrong did all of the production work with the exception of welding the yoke lugs to the stabilizer bodies. About thirty-five units were made and distributed to U. S. Navy SEAL Teams, including SEAL Team 3, for field evaluation. Unfortunately, funding was never obtained for this item.

Commercial reproduction M14E2 muzzle stabilizers made by Ray Kryza of Ray's Surplus (Warren, MI) are of high quality. These M14E2 muzzle stabilizers have been made since at least 1987. They will have a part number on the right side of the locking clamp.

Commercial Stabilizer – Springfield Armory, Inc. very briefly made its own version of a muzzle stabilizer for its folding stock M1A-A1 Bush rifle. Two variations of the Springfield Armory, Inc. muzzle stabilizer were made, one with a bayonet lug and one without. The lugged version was made in late 1982 and 1983. The muzzle stabilizer without the bayonet lug was installed at the factory in 1984, e.g., M1A-A1 serial number 0298XX. The front portion of the Springfield Armory, Inc. muzzle stabilizer had a combination muzzle brake and bird cage style flash hider. It threaded on to the rear portion but was held in place by a single SAE 10-32 thread setscrew on the bottom. Removing the flash hider reduced the length of the rifle by 2.75 ". The rear portion of the muzzle stabilizer consisted of the front sight base and bayonet lug. It was marked on the bottom, front to rear: first line - SPRINGFIELD ARMORY second line - MUZZLE STABILIZER third line - CAL. 7.62. The outside diameter measured 0.6 " for the entire length of the stabilizer. Numrich Gun Parts Corporation and Sarco, Inc. imported cast reproduction M14E2 muzzle stabilizers which may or may not have any markings such as numbers or lettering. If there are no numbers or letters on a M14E2 muzzle stabilizer at all, it is of commercial manufacture.

Grenade Launchers – John C. Garand designed and patented a flash suppressor mounted grenade launcher for the T20/T44 type rifle. A benefit of his design was the

positioning of the grenade all the way to the rear against the launcher no matter what the range. The distance to be fired was selected by turning a conical gas bleed ring at the launcher rear end to the desired setting. The stock suffered less impact force from launching grenades because excess gas was bled off through the conical gas bleed ring.

Earle M. Harvey at Springfield Armory may have designed what may be the most ambitious muzzle attachment ever conceived with the M14 rifle in mind. Mr. Harvey designed a combination muzzle stabilizer, recoil brake, flash hider and grenade launcher attachment. The muzzle attachment replaced the M14 flash suppressor and flash suppressor nut. It threaded on to the barrel muzzle end threads. It was designed to be installed as part of the rifle. The muzzle attachment was made ready for launching grenades by a quick twist of the front portion of the device. The Harvey muzzle attachment did not have any provision for mounting the rifle front sight. Presumably, the front sight would have been mated to the gas cylinder for M14 rifles equipped with these devices. Mr. Harvey filed a patent application for his muzzle attachment design on October 23, 1957 and it was approved on April 28, 1959.

The X-1 was an experimental breech-loading 40 mm grenade launcher made for the M14 rifle in 1961. It attached to the gas cylinder and bayonet lug. The electro-penciled marking Grenade Launcher 40 mm X-1 appears on the bottom side at the rear end. The X-1 grenade launcher used an experimental sight mounted on the left side of the stock like the issue M15 sight but it was larger with the angles of fire indicated along a protractor. A pull wire mounted along the right hand side of the stock terminated in a loop at a point between the trigger guard and the magazine.

The X-1 grenade launcher was developed by a Springfield Armory research engineer. It was tested at Fort Benning with very good success. However, the engineer, known as "Nick", almost lost his job because of it. Nick was asked by an unnamed official to fit a 40 mm grenade launcher to a M14 rifle. The unnamed official had been told by Rock Island Arsenal personnel that a 40 mm grenade launcher could not be added to a M14. Rock Island Arsenal was the parent command for Springfield Armory in 1961. Unfortunately, some professional jealousy existed at Rock Island Arsenal over the engineering expertise at Springfield Armory. Consequently, Nick's useful invention was not well received by personnel at Rock Island Arsenal. Nick may have been the same Nicholas Angelica who filed patents for the chamber brush and the National Match hooded eyepiece but this has not been confirmed.

While employed at Springfield Armory, Mr. Stanley D. Silsby of Granby, MA invented at least four different grenade launchers for the M14 rifle. He applied for a patent in 1961 on each design. The patents were approved in 1968 and 1969. All four designs had the launcher attached to the rifle at the bottom of the gas cylinder and at the bayonet lug. Two of the launcher designs employed pre-loaded disposable launcher tubes. The other two designs utilized permanent launcher barrels. Two grenade launchers were fitted with a storage rack under the launcher itself to hold an additional two 40 mm grenades or pre-

loaded tubes. A patent application was filed simultaneously by Albert J. Lizza for an ejection mechanism used as the ejection mechanism in the Silsby design approved as U. S. Patent 3,404,477.

Of the four Silsby concepts, one was breech-loading (U. S. Patent Number 3,408,761). To launch a grenade using the breech-loading grenade launcher after loading, the operator had to simultaneously push the safety and the trigger buttons together against a spring. The safety and trigger buttons were located at the front end of the launcher on the bottom side. The breech-loading grenade launcher was the most viable of the Silsby designs.

Mr. Silsby was later employed by Colt's Manufacturing Company (then Hartford, CT) in the late 1960s and early 1970s working on the Army's Special Purpose Individual Weapon (SPIW) and the Air Force's Individual Multi-Purpose Weapon (IMP) projects. He was awarded five patents for work related to these two projects plus four patents for the M16 type rifle during his career.

Two 40 mm grenade launcher systems for the M14 rifle were demonstrated at Fort Benning and tested at Springfield Armory during the period of July 01, 1963 to June 30, 1964. The particular designs demonstrated and tested have not yet been identified.

The T140 grenade launcher was developed for the M14 rifle in 1955. The T140 grenade launcher latching handle assembly was redrawn in 1960. The T140 grenade launcher was adopted as the M76 and produced in 1961. The M76 grenade launcher weighed about 7 ounces. It was marked LAUNCHER GRENADE M76 U S on the rear end ring and 7790900 on the right side of the locking clamp. It became obsolete with the introduction of the M79 grenade launcher in the mid-1960s. Starting in 2010, Wayne Machine, Inc. produced a reproduction M76 grenade launcher.

Rock SOPMOD M14 stocks could accommodate the newer M203 40 mm grenade launcher originally designed for installation on M16 series rifles. Civilians may own 40 mm grenade launchers in the United States in accordance with the National Firearms Act of 1934. Consult federal, state and local laws prior to installing a grenade launcher on a M14 type rifle.

Military Sound Suppressors

Military sound suppressors are used to conceal the origin of sniper fire, and/or deceive enemy troops regarding the shooter's location, by minimizing the muzzle blast. During the Viet Nam War, the XM21 rifle was sometimes equipped with the Sionics M14 SS-1 suppressor. Forty Sionics SS-1 suppressors were sent from the U. S. Army AMTU in February 1969 to the U. S. Army 9th Infantry Division Sniper School for testing in combat. An unknown quantity of Sionics SS-1 suppressors were shipped as a single batch to the U. S. Army in Viet Nam after April 1969 in support of the XM21. This suppressor

consisted of a series of counterclockwise and clockwise metal spiral shapes abutting each other around a smooth perforated barrel extension core with rings fore and aft. A gas relief port was located at the rear end of the SS-1 suppressor. The SS-1 suppressor was designed for semi-automatic fire only. The Sionics SS-1 parts were made from 6061 T6 alloy aluminum and AISI 4130 alloy steel. The SS-1 suppressors were given a black color anodized finish. Physical data for the M14 SS-1 sound suppressor was as follows: 12.75 " overall length, 9.0 " additional length to the rifle when installed, 1.665 " outside diameter, 0.375 " bore diameter and 1 pound 15 ounces in weight. Some M21 rifles have been outfitted with Brookfield Precision Tool sound suppressors.

O. P. Seberger, Jr. was an electrician by trade but in retirement he took up sound suppressor design as his new career. He established OPS, Inc. (Shingletown, CA) in 1988. OPS, Inc. sound suppressors have seen service in Panama, Desert Storm, Somalia, Haiti and Afghanistan with the U. S. military. OPS, Inc. did more to advance sound suppressor technology from 1988 onward past 2000 than any other concern. One of its sound suppressors is featured in the 1994 movie *Clear and Present Danger*. OPS, Inc. sound suppressors are self-cleaning, maintenance free and guaranteed for 30,000 rounds or two years, whichever comes first.

After the American involvement in the Republic of Viet Nam, M14 DMR and M25 rifles were at times suppressed using OPS, Inc. 12th Model muzzle brake mounted sound suppressors designed by Phil Seberger. Designed to drain itself of water in six seconds or less, the 12th Model muzzle brake sound suppressor was made of fusion welded AISI 300 series stainless steel. Its sound attenuation was listed as 40 decibels. The military version muzzle brake suppressor included a barrel sleeve and thread protector. To install the OPS, Inc. sound suppressor, the operator needs to remove the thread protector on the suppressor. To configure a M14 rifle to accept the OPS, Inc. sound suppressor, the gas piston hole was welded shut then drilled to a diameter of approximately 0.055 ". The small hole restricted the flow of gas to the desired rate. With the suppressor installed, the bullet cleared the rifle before the operating rod was able to move enough to affect accuracy. Use of the OPS, Inc. 12th Model muzzle brake sound suppressor resulted in an average accuracy increase of 0.25 MOA and an increase of 20 to 50 feet per second bullet velocity. The muzzle brake portion of the assembly (manufacturer part number 01-B) reduced recoil and muzzle climb. If the sound suppressor was not installed, the muzzle brake created a noticeable flash signature at night when the rifle was fired. The OPS, Inc. suppressors saw service on M14 DMR rifles in Afghanistan during the Global War on Terrorism.

M14 Direct Connect Sound Suppressor - Ron and Richard Smith of Smith Enterprise, Inc. and Dave Fisher of Fisher Enterprises (Tempe, AZ) developed and produced a M14 sound suppressor that quickly attached to and detached from the Smith Enterprise, Inc. direct connect flash hider. The two firms collaborated on suppressor production for the purpose of supporting the war effort in Iraq and Afghanistan. Production of the M14 Direct Connect, or M14DC, sound suppressor began in 2004. It was a factory supplied

part of the M14SE/M21A5 rifle system, a first for the M14 platform. This sound suppressor weighed 2.08 pounds and had an overall length of 11.2 ". The length of the rifle was extended by 8.9 " with the suppressor installed. The suppressors sold to eligible civilians and U. S. law enforcement agencies were marked on the tube: first line - FISHER ENT. MESA, AZ 85201 and the second line - MDL M14-DC CAL 7.62 S.N. M14-DC-XXXX. M14DC suppressors sold to the U. S. government and to other countries through the Foreign Military Sales program were marked with SMITH ENT. The coupler was marked FISHER ENT or FISHER/SMITH ENT. The M14DC sound suppressor was specified for various U. S. military M14 rifle projects from 2004 to 2007. As of mid-2011, the two companies parted ways on friendly terms due to winding down of the war effort. Smith Enterprise, Inc. continued to manufacture suppressors as the market demanded.

The Direct Connect suppressor tube, end cap and baffles were made of 300 series stainless steel. The stainless steel portions of the suppressor exterior were coated with a black oxide finish. The quick detaching locking collar was made of titanium. Original locking collars had a single start thread but newer collars were given a three start thread. 17-4 precipitation hardening stainless steel was used to fabricate the locking plates. All baffles were coated with thin dense chromium resulting in a surface hardness of 80 HRC. The first baffle in the sound suppressor was coated with polytetrafluoroethylene over the chromium. By May 2006, the M14DC suppressor body was changed to incorporate a 1 " long fluted, or revolver, contour coupler just forward of the locking collar. In 2009, Dave Fisher created an optional locking collar to allow the M14 DC sound suppressor to be mounted to Springfield Armory, Inc. M1A SOCOM models.

The Direct Connect suppressor did not require any modification of the M14 type gas system. It could be completely rebuilt in the field, a first for military sound suppressors. The M14DC sound suppressor could also be employed on M16 style, Enfield SA80, Fabrique Nationale FAL and FNC, and Heckler & Koch G3 and G36 rifles with the appropriate Smith Enterprise flash hider. In the fall of 2006, Smith Enterprise, Inc. made the initial delivery of M14DC sound suppressors to the U. S. Navy. The U. S. Navy has safety certified the M14DC sound suppressor for automatic fire on its Mk 14 Mod 0 and Mod 1 rifles.

M14DC Lightweight Sound Suppressor - By March 2006, Smith Enterprise, Inc. had developed and manufactured a titanium body version of the original M14DC model sound suppressor. The serial number format was M14-DCA-XXXX. The lightweight M14DC sound suppressor weighed 1.42 pounds. It was designed for semi-automatic fire and could be also rebuilt in the field. The method of attachment to the rifle remained the same as with the original M14DC sound suppressor.

M14 Wind Talker Sound Suppressor - In late 2011, Smith Enterprise, Inc. began producing the Wind Talker sound suppressor. The Wind Talker suppressor tube was marked with the serial number format WTA-XXXX or WTSS-XXXXX, A for alloy aluminum tube and SS for nitrocarburized stainless steel tube. The tube was also marked with the

outside diameter of the SEI direct connect flash hider it was intended to mate with, e.g., .852. The coupler was marked: top - U.S. bottom - SEI. Smith Enterprise, Inc. obtained an approved BATFE variance that allowed its sound suppressor to be built at Richard Smith's machine shop in Carson City, NV.

Like the Direct Connect model, the Wind Talker sound suppressor could be maintained at the depot level and the M14 gas system did not require modification for employment. However, the Wind Talker suppressor had several design differences as compared to the original Direct Connect unit, including a new triaxial baffle design. The proprietary baffle was designed by Arthur Peter Lipsio, Armament Systems International (Bullhead City, AZ), and Ron Smith, Smith Enterprise, Inc. These Wind Talker model features were Smith Enterprise, Inc. innovations: revolver contour coupler, shortened locking collar, lack of a backing plate, nitrocarburized baffles and stainless steel locking collar, and lack of a setscrew on the tube. The revolver contour coupler allowed propellant gas to exit to the front just forward of the locking collar. The stainless steel locking collar better facilitated removal of the suppressor from the flash hider after extended use. The locking collar only required two full turns to fully expose the locking clips. Thus, the Wind Talker sound suppressor could be installed or removed faster than the Direct Connect model.

In June 2013, four M14 Direct Connect sound suppressors originally supplied to the 2nd Infantry Division were sent to Smith Enterprise, Inc. by the 2nd Battalion 505th Infantry Regiment 82nd Airborne Division. After nine years of service, the suppressors were in need of cleaning. Smith Enterprise, Inc. rebuilt the sound suppressors using Wind Talker model baffles, end caps, and couplers but retained the original tubes. The refurbished sound suppressors were painted flat dark earth.

Commercial Sound Suppressors

Installation of a sound suppressor on an M14 type rifle may require modification of the gas system to prevent parts damage. Using a sound suppressor on a M14 type rifle generates some gas blow back into the face of the shooter. However, installation of a side three point scope mount on the suppressed M14 type rifle greatly reduces perceived blow back. Be sure to wear proper eye protection when shooting a suppressed M14 type rifle. Commercial manufacture sound suppressors sized for and used on .308 Winchester caliber rifles *typically* reduce the sound signature by 20 to 30 decibels.

Sound suppressors are regulated in the United States of America by the National Firearms Act of 1934 (the "NFA"). Note that the BATFE considers a sound suppressor to be a flash hider as well. It may be legal to own an NFA registered sound suppressor but still be illegal to use it for any purpose, e.g., State of Washington law. Consult all laws and an attorney knowledgeable in firearms laws prior to purchasing a sound suppressor.

American Suppressors - AWC Systems Technology has been manufacturing sound suppressors since 1983. In the past, the firm manufactured the M30 sound suppressor.

The M30 suppressor used two mounting points to attach to a M14 type rifle. Today, AWC Systems Technology offers a smaller sized but very efficient sound suppressor for the M14 type rifle, the Spec M1 7.62. It is based on its Thundertrap model. The Spectrum 2000 sound suppressor is made from AISI 304 stainless steel, is 1.5 " in diameter, and weighs 28 ounces. It is 10.4 " in length but when installed the overall rifle length is only increased by 6.5 ". The flash suppressor and nut are removed from the rifle barrel. The Spectrum 2000 suppressor is then slid down the barrel and threaded on to the barrel threads for the flash suppressor nut. The rear end of the Spectrum 2000 suppressor stops about an inch from the front end of the gas cylinder plug. The suppressor comes in a choice of two finishes, matte black or matte stainless. The USGI front sight may be replaced with a combination gas cylinder lock front sight to retain the use of iron sights.

A commercial copy similar to the Sionics, Inc. M14SS suppressor was made before 1999 by Don Floyd, Inc. (Woodstock, GA). The Floyd Mod 14 suppressor had a relief valve at the rear end. At least 179 were made. Advanced Armament Corporation (Norcross, GA) initially produced a three prong M14 flash hider in May 2008 to mount its 762SD sound suppressor. The model 18T and 51T flash hidere were later offered with M14 barrel compatible threads for mounting its sound suppressors.

Tim Bixler at South Central Research Corporation (Katy, TX) makes a sound suppressor for the M14 type rifle. It is called the Mk23 and can be taken apart for cleaning. Jet Suppressors (Aransas Pass, TX) offers a .308 Winchester caliber sound suppressor that can be threaded on to the M14 barrel flash suppressor nut threads. The titanium sound suppressor is seal welded. It measures 1.5 " in diameter and 9 " long. It is cleaned by soaking in solvent then air dried.

Troy Industries sold an optional sound suppressor for the Rock SOPMOD M14. It was made of fusion welded and stress relieved AISI 300 series stainless steel. The M14 sound suppressor weighed 22 ounces and had a diameter of 1.5 ". It was 10 " long but only added 5 " to the overall length of the firearm. The sound suppressor screwed on the barrel with left hand threads and self-tightened as the rifle was fired. The Rock SOPMOD M14 conversion allowed installation of the Troy Industries sound suppressor without modifying the gas system. This was because the Troy Industries suppressor was built with a back chamber to accommodate the gas. The Rock SOPMOD M14 would operate normally without harm while this suppressor was in use. The Troy Industries sound suppressor reduced sound level by 30 decibels or better when installed on a Rock SOPMOD M14.

Suppressed Tactical Weapons, Inc. (Rougemont, NC) offers a sound suppressor that screws on or permanently attaches to the USGI design M14 flash suppressor. The titanium STW suppressor weighs 14 ounces. The suppressor dimensions are 8.5 " long and 1.315 " in diameter. The advantage of this suppressor is that the front sight is not removed from the rifle.

Surefire, LLC (Fountain Valley, CA) offered two sound suppressors for the M14 type rifle. The sound suppressors weighed 1 pound 3 ounces and were 1.5 " in diameter. These were available in a black finish for civilian sales. The sound suppressors could be quickly installed by use of a model specific Surefire suppressor adapter. For the M14, Surefire offered a flash hider adapter (part number FH762KM14) or muzzle brake adapter (part number MB762213F) for its FA762K suppressor or a muzzle brake adapter (part number MB762SS01) for its FA762SS suppressor. The flash hider and muzzle brake adapters were made from heat treated stainless steel and given a black finish. The FA762K suppressor was 8.4 " long and extended past the muzzle by 5.6 " when installed with a Surefire adapter. The FA762SS suppressor measured 9.8 " long but only added 5.5 " to the rifle length when installed. Surefire, LLC sold its sound suppressors with a lifetime warranty under normal use and conditions. In 2006, Surefire, LLC supplied a limited number of FA762K sound suppressors and FH762KM14 adapters to the U. S. Navy for the Mk 14 Mod 1 rifle.

In 2006, Gemini Technologies introduced its .308 Winchester caliber HVT sound suppressor. The HVT suppressor was made from stainless steel and given a flat black oxide finish. It had an overall length of 8.25 ", a diameter of 1.5 " and weighed 24 ounces. The HVT suppressor attached to the M14 rifle by either of two Gemini Technologies Quickmount flash hider type adapters, standard or vortex. The standard flash hider type adapter added 0.85 " and 4 ounces to the length and weight of the suppressor. The company also produced a 5/8 " x 24 muzzle thread adapter for the M14 barrel. It was marked as follows: top line - GEMTECH bottom line - M1A -- 5/8-24.

Delta P Design, Inc. (Walterville, OR) manufactured a sound suppressor and M14 muzzle adapter beginning in 2009. The Brevis model sound suppressor was made of welded and hardened stainless steel construction. The exterior was given a black oxide finish. It was 5.5 " long, 2.25 " in diameter and weighed 1 pound 5 ounces. The second generation model was shortened by 0.75 " and lightened by 1 ounce. The suppressor body had wrench flats to allow for ease of installing or removing from the muzzle adapter.

The Delta P Design M14 muzzle adapter substituted for the USGI flash suppressor. The adapter was machined from stainless steel billet and subsequently heat treated. It consisted of a front sight base with a 5/8 " x 24 threaded end to which the sound suppressor was attached. The muzzle adapter was secured to the barrel using the barrel splines, flash suppressor nut and flash suppressor nut setscrew. The muzzle adapter accepted all standard dimension USGI or NM front sights. Delta P Design, Inc. followed up in March 2011 with a M1A SOCOM muzzle adapter. The M1A SOCOM muzzle adapter was also manufactured from hardened stainless steel and given a black oxide finish. It consisted of three parts, a cylindrical adapter threaded to the barrel with 5/8 " x 24 male threads at the front end, a gas cylinder lock front sight which threaded on to the cylindrical adapter, and a setscrew for positive retention between the two major parts. The M1A SOCOM muzzle adapter allowed use of the Springfield Armory, Inc. M1A SOCOM or USGI gas cylinder plug. The gas cylinder lock front sight base height was

sized for the factory Springfield Armory, Inc. M1A SOCOM front sight.

Foreign Suppressors – BR-Tuote (Joensuu, Finland) produces a line of suppressors for pistols, rifles and automatic weapons. Its all steel construction T6M14 suppressor screws onto the M14 barrel once the flash suppressor assembly is removed. These suppressors are self-cleaning.

USGI M14 Technical and Training Documents

Parts and accessories for the M14 rifle were manufactured according to government drawings and item specific military specification documents covering requirements not listed in the drawings. The government agency awarding a particular contract sent the latest Technical Data Package for the item to be made to the contractor. This practice continues to the present day.

The centerline for the M14 rifle is the center of the barrel gas port. The gas port itself is centered between two bore rifling lands. All the dimensions for the M14 are referenced from that datum line.

Part drawings for many M14 parts date to as early as 1954 and were updated until at least June 17, 1994 (drawing B7267096 Revision L). Virtually every M14 part drawing has been revised several times since 1958 when the original technical data package was assembled. A typical example is the operating rod spring guide drawing D7267027, originally dated October 04, 1954. It was redrawn and revised on July 10, 1958 at Springfield Armory. Through the years, this drawing has been revised many times. Drawing D7267027 was last updated by Picatinny Arsenal on April 01, 1979 as Revision M. The bolt may have been revised the most times, Revision Y to drawing F7790185 was issued on December 30, 1992. At least one M14 part drawing made its way into the computer age. Drawing C7267007 for the stock swivel bracket was last revised on August 30, 1993 using Computer-aided Design.

Although Computer-aided Design (CAD) drawings were first used in the 1960s by the automobile and aerospace industries, the M14 project drawings were done by hand with a rare exception as noted above. Before the advent of CAD, firearms designers and ordnance engineers drew parts by hand. The parts were machined, inspected, heat treated, assembled and tested. This process was repeated until the desired results were achieved. There was no magic in firearms design and manufacturing, just a lot of thought and effort. A couple gentlemen serve as fine examples of the talent involved in the production of the M14 rifle.

Mr. Albert A. Cole, Jr. was an ordnance engineer at Springfield Armory. Mr. Cole managed the draftsmen who drew and updated the drawings for the M14 project. He also worked with production employees at the four M14 manufacturers in testing and evaluating design changes to the M14 rifle. Most of the hundreds of refinements were

minor but were made for the purpose of reducing the manufacturing cost. After Springfield Armory closed in 1968, Mr. Cole went to work at Picatinny Arsenal and later at Rock Island Arsenal. After his years of public service, he was employed by Sturm, Ruger & Co. in designing firearms before retiring in 1988.

One of the designers that worked for Mr. Cole was Guilio V. Savioli. Mr. Savioli immediately went to work at Springfield Armory upon graduating from high school. He designed the M1E3 bolt which featured the bolt roller later adopted in the M14. During the rain test of a T44, the barrel channel in the stock became flooded. So, Mr. Savioli solved the problem by designing the 5/16 " diameter hole into the bottom of the stock just forward of the sling swivel. He also designed the pre-'61 cleaning kit combination tool. After Springfield Armory closed in 1968, he worked at the Rodman Laboratory at Rock Island Arsenal and then at Picatinny Arsenal. He retired with thirty years of government service and at least eleven U. S. Patents to his credit. Mr. Savioli passed away in 2009.

All of the documents associated with manufacturing the M14 rifle are listed in a Technical Data Package List (TDPL). The M14 Rifle TDPL organizes the documents into five areas: 1) product (parts) drawings and associated lists (164 pages) 2) packaging drawings and documents (15 pages) 3) inspection drawings and documents (1034 pages) 4) specifications and standards (102 documents) and 5) outstanding approved engineering changes (29 pages). Similarly, the M21 Rifle TDPL consists of the following: 1) product drawings and associated lists (211 pages) 2) packaging drawings and documents (16 pages) 3) inspection drawings and documents (1,116 pages) 4) specifications and standards (95 documents) and 5) outstanding approved engineering changes (30 pages).

Specifications and standards in the TDPL fit into one of two broad categories, government and commercial. The government standards and specifications are identified by a MIL, DOD, FED or two letter prefix, e.g., MIL-W-12332 or QQ-S-698. A standard, in contrast to a specification, is denoted by STD in the second part of the document identifier, e.g., FED-STD-595. From 1989 onward, the M14 and M21 TDPLs include commercial standards and specifications from these professional organizations: American National Standards Institute (ANSI), American Society of Mechanical Engineers (ASME), American Society for Testing and Materials (ASTM), American Welding Society (AWS) and the Society of Automotive Engineers (SAE-AS and SAE-AMS). In 1989, the U. S. military services began to adopt commercial manufacturing standards and specifications as they ceased maintaining equivalent federal and military documents. As of 2006, forty-seven of the 102 M14 Rifle TDPL standards and specifications were commercial documents.

Up until the Iran-Contra affair in 1987, the entire M14 Technical Package was available for civilian purchase from the U. S. government for less than \$1000.00. This information is now made available to businesses with a CAGE Code which have a need for it or firms that are asked to bid on an item that the U. S. government needs. The item contract up for bid will come with the associated drawings and specifications. The term "mil spec" is

not a trademark or other protected descriptive term, but is often used freely by sellers when describing firearms parts of uncertain origin or even clearly from non-military sources, so buyers must beware.

The U. S. Army, U. S. Marine Corps and U. S. Navy have published approximately thirty operations, maintenance, repair and inspection manuals for their M14 rifles. Every M14 type rifle owner should own a copy of 1972 edition TM 9-1005-223-34 as reference material because it is comprehensive and readily available. Rock Island Arsenal drafted an operator's manual for the XM21 rifle, DTM 9-1005-221-10, but it was never adopted for distribution. Rock Island Arsenal did the original printing for the May 1967 edition of TM 9-1005-223-20. For the most part, the M14 series technical manuals were printed or reprinted by either the Government Printing Office or the Army Adjutant General's Office. The numbering system for Army technical manuals can be explained as follows: a) TM 9 means it is a technical manual written for an ordnance item b) 1005 identifies the subject matter as a small arm c) 223 is the unique identifier for the M14 rifle and d) the last two digits identify the echelon level of maintenance the publication is intended to support.

Instructional manuals and other materials were written to train soldiers and sailors whose occupational duties included the maintenance and repair of the M14 rifle. Such examples include the 1968 Armorer/Unit Supply Specialist Course Small Arms Repair student materials created by the U. S. Army Quartermaster School (Fort Lee, VA) and the Gunner's Mate series of rate training manuals developed by Naval Education and Training Command (NAVEDTRA 14109 and 14110 dated 1996 and 14324 published in 2002).

Timeline of U. S. Army M14 Field Manuals

December 07, 1959 - FM 23-8 issued.
May 20, 1960 - FM 23-8 1959 edition Change 1 issued.
August 15, 1962 - FM 23-8 1959 edition Change 2 issued.
May 07, 1965 - FM 23-8 issued, supersedes 1959 edition and all associated changes.
March 22, 1968 - FM 23-8 1965 edition Change 1 issued.
April 15, 1974 - FM 23-8 issued, supersedes 1965 edition and associated change.
August 27, 1975 - FM 23-8 1974 edition Change 1 issued.
March 16, 1987 - FM 23-8 1974 edition Change 2 issued.

Timeline of U. S. Army M14 Technical Manuals

July 31, 1959 - TM 9-1005-223-12P issued.
October 28, 1959 - TM 9-1005-223-12 issued.
November 1959 - TM 9-1005-223-35P issued.
November 05, 1959 - TM 9-1005-223-34 issued.
1960 - TM 9-1005-223-12 1959 edition is reprinted.
September 15, 1960 - TM 9-1005-223-34P issued.

LEE EMERSON

November 22, 1960 - TM 9-1005-223-20P is issued.
May 26, 1961 - TM 9-1005-223-12 issued, supersedes October 1959 edition.
September 07, 1961 - TM 9-1005-223-34 issued, supersedes November 1959 edition.
September 25, 1961 - TM 9-1005-223-35P issued, supersedes November 1959 edition.
November 15, 1961 - TM 9-1005-223-12 1961 edition Change 1 issued.
March 16, 1962 - TM 9-1005-223-12P issued.
January 22, 1963 - TM 9-1005-223-12 issued, supersedes 1961 edition with associated change and TM 9-1005-223-12P 1962 edition.
April 08, 1963 - TM 9-1005-223-34 issued, supersedes 1961 edition.
April 11, 1963 - TM 9-1005-223-12P M14 NM issued.
January 22, 1964 - TM 9-1005-223-12 1963 edition Change 1 issued.
February 08, 1965 - TM 9-1005-23-12 issued, supersedes 1963 edition with all associated changes.
August 16, 1965 - TM 9-1005-223-35 issued.
October 01, 1965 - TM 9-1005-223-12 1965 edition Change 1 issued.
March 23, 1967 - TM 9-1005-223-12 1965 edition Change 2 issued.
March 23, 1967 - TM 9-1005-223-35 1965 edition Change 1 issued.
May 19, 1967 - TM 9-1005-223-20 issued, supersedes TM 9-1005-223-12 1965 edition with all associated changes.
September 14, 1967 - TM 9-1005-223-35 1965 edition Change A issued for the U. S. Marine Corps.
December 29, 1967 - TM 9-1005-223-20 1967 edition Change 1 issued
January 02, 1968 - TM 9-1005-223-35 1965 edition Change B issued for the U. S. Marine Corps.
February 06, 1968 - TM 9-1005-223-20 1967 edition Change 2 issued
February 23, 1968 - TM 9-1005-223-12P M14 NM and M14 M manual issued, supersedes 1963 edition.
June 1968 - TM 9-1005-223-20 1967 edition Change 3 issued
July 01, 1968 - TM 9-1005-223-35 issued, supersedes 1965 edition with all associated changes.
July 02, 1968 to February 02, 1970 - TM 9-1005-223-35 1968 edition Change 1 issued.
1969 - TM 9-1005-223-20 1967 edition is reprinted.
June 1969 - TM 9-1005-223-35 1968 edition is reprinted.
June 20, 1969 - TM 9-1005-223-20 1967 edition Change 4 issued
October 27, 1969 - TC 23-14 issued.
November 1969 - DTM 9-1005-221-10 issued as a draft version.
December 15, 1969 - TM 9-1005-223-20 1967 edition Change 5 issued
1970 - TM 9-1005-223-12P 1968 edition is reprinted.
February 03, 1970 - TM 9-1005-223-35 1968 edition Change 2 issued.
July 14, 1970 - TM 9-1005-223-35 edition Change 3 issued.
1971 - TM 9-1005-223-35 1968 edition with Changes 1, 2 and 3 is reprinted.
January 1971 - TM 9-1005-223-20 1967 edition Change 6 issued
July 1971 - TM 9-1005-223-35 1968 edition is reprinted.
March 21, 1972 - TM 9-1005-223-10 issued, supersedes portions of TM 9-1005-223-20

M14 RIFLE HISTORY AND DEVELOPMENT

1967 edition.

August 02, 1972 - TM 9-1005-223-20 issued, supersedes 1967 edition with all associated changes.

August 02, 1972 - TM 9-1005-223-34 issued, supersedes TM 9-1005-223-35 1968 edition with all associated changes.

October 06, 1972 - TM 9-1005-223-10 1972 edition Change 1 issued.

April 20, 1973 - TM 9-1005-223-12P M14 NM and M14 M manual Change 1 issued.

May 08, 1973 - TM 9-1005-223-10 1972 edition Change 2 issued.

1975 - TM 9-1005-223-10 1972 edition is reprinted.

1976 - TM 9-1005-223-34 1972 edition is reprinted.

1980 - TM 9-1005-223-34 1972 edition is reprinted.

June 14, 1989 - TC 23-14 Sniper Training and Employment issued.

Note: The technical manuals currently in use by the U. S. Army are as follows:

M14 and M14A1 - 1972 editions of TM 9-1005-223-20 and TM 9-1005-223-34

M14 M and M14 NM - 1968 edition of TM 9-1005-223-12P with Change 1

Publication dates obtained for U. S. Navy and U. S. Marine Corps manuals were as follows:

November 27, 1972 - U. S. Marine Corps: TI-02648A-25/10B Match Condition Procedures Rifle, 7.62MM, M14

April 16, 1981 - U. S. Marine Corps: TI-02648A-25/10C Match Condition Procedures Rifle, 7.62MM, M14

July 31, 2000 - U. S. Marine Corps: TM 02648C-24&P/2 Organizational and Intermediate Maintenance Manual Including Repair Parts And Special Tool Lists For Rifle 7.62-MM, M14, DMR W/E 1005-01-458-6235

October 01, 2002 - U. S. Navy: SW370-A2-OPI-010 Operator's Manual for Rifle, 7.62MM MK 14 MOD Enhanced Battle Rifle (EBR)

Beginning in June 1951, the U. S. Army has produced an equipment maintenance periodical in comic book format for its soldiers. Through the years, *PS The Preventive Maintenance Monthly* has been produced at Aberdeen Proving Ground (MD), Fort Knox (KY), Raritan Arsenal (NJ) and Redstone Arsenal (AL). Issues back to 1990 are also available online. Through its history, *PS* magazine has had two characters, Miss Connie Rodd (no later than April 1954 to the present) and Master Sergeant Half-Mast (no later than July 1954 to the present). Both characters instruct soldiers on proper care of all sorts of equipment. Specifically, there were more than sixty articles related to M14 rifle care and maintenance in the issues between December 1958 and July 1971. The August 1989 article included cleaning tips for the M14/M21. Basic preventive maintenance was covered in July 2006 and magazines and a M14 scope mount was mentioned in the June and September 2006 issues.

Normount Armament Co. (Forest Grove, OR) reprinted FM 23-8 in 1968. Nicolaus Associates (Jefferson, GA) has reprinted many hard-to-find U. S. military small arms documents including some of the early U. S. Army M14 manuals. Nicolaus also offers several informative wall posters compiled from government documents: 1) M14 Be Your Own Inspector 2) Rifle, 7.62 MM, M21 Sniper's 3) Rifle, 7.62 MM, M14 National Match: Initial Specifications 4) Rifle, 7.62 MM, M14: Cycle of Operation and 5) Rifle, 7.62-MM, M14 Nomenclature. William J. Ricca Surplus Sales has compiled all of the relevant *P S Magazine* articles from 1951 to 1973 on the M14 onto a compact disc.

USGI Parts

Parts for the 1957 design U. S. government M14 rifles were made from December 1958 onward until at least 2011. The bulk of the parts production was, however, from 1960 to 1968. The U. S. government issued at least 319 contracts and purchase orders for M14 parts between 1961 and 2011. Total expenditures for contracts and purchase orders for M14 parts during this time period were at least \$71,831,748.71.

The government contractors involved were held to strict quality control standards. Requirements for correct dimensional geometry, surface roughness and finish, and heat treatment were specified in the applicable Quality Assurance Provisions and Supplementary Quality Assurance Provisions associated with each part. For example, the USGI M14 extractor had twenty-two inspection points for proper dimensional geometry. Still, there are often slight but significant differences in how USGI parts fit, e.g., bolts and operating rods with respect to the receiver. USGI bolts have been found to differ by as much as 0.004 " in length even when made by the same manufacturer.

AISI 440A stainless steel is magnetic and can be heat treated to obtain very high strength, hardness and wear resistance. AISI 440A stainless steel is a martensitic stainless steel. AISI 8645 is a nickel-chromium-molybdenum alloy steel like AISI 8620 steel but it has a much higher carbon content at 0.45 %. This material can be sufficiently hardened and strengthened for parts like the M14 operating rod without the added step of carburizing.

Some USGI M14 parts are marked with manufacturer codes. Typically, the manufacturers stamped the operating rod, bolt, elevation and windage knobs, trigger housing, and hammer. Sometimes, the manufacturer is identified on the stock, flip-up butt plate, operating rod spring guide, trigger guard, front band, gas cylinder, rear sight base, safety and sear release. Examples of such are:

- 1) Delta-X Corporation rear sight base
- 2) Harrington & Richardson front band, rear sight base, and safety
- 3) Killeen Machine & Tool operating rod spring guide, butt plate flapper and trigger guard
- 4) Olin Mathieson (Winchester) rear sight base
- 5) Harrington & Richardson, Saco-Lowell, and Springfield Armory gas cylinders.

Springfield Armory gas cylinders are very faintly stamped S A. Gas cylinder markings are generally not visible because the surface finish hides them. M14 NM trigger housings were marked with the last four digits of the rifle serial number to which it was made part of during the accurizing process.

It is possible that Killeen Machine & Tool did not place its manufacturer's marking on each M14 part it made. M14 gunsmith Ted Brown reports that while refinishing a batch of M14 butt plate assemblies he found that seven of the butt plate flappers exhibited identical flaws left by the stamping die. Of the seven flappers, three were marked KMT CO. and four were unmarked.

Butt Plate and Butt Plate Flapper - M1 Garand butt plates used on the T44E4 stocks were made of steel. USGI M14 butt plates were made of alloy aluminum to help reduce the weight of the M14 rifle. The numbers 8 and 10 have been observed on the back side of M14 butt plate trap doors. These may be mold numbers. The USGI M14 butt plate flapper (shoulder rest plate) is made of steel and has one hole on the left side of the hinge as the rifle is pointed down range. Several types of USGI M14 butt plate flappers have been observed. The following classification scheme is presented as a means of cataloging the differences:

Group 1 - These butt plate flappers have bumps around the bottom screw hole only.

Type 1A - round bumps with two weld dimples and no trap door lock

Type 1B - square bumps but no weld dimples

Type 1C - square bumps with two weld dimples

Group 2 - These butt plate flappers have bumps around the top and bottom screw holes.

Type 2A - round bumps with no weld dimples, truncated hinge slot corners, and a raised trap door pin well

Type 2B - square bumps but no weld dimples or welds filled in

Type 2C - square bumps with two weld dimples (Killeen Machine & Tool made this type)

Type 2D - square bumps with two smaller weld dimples

The DOD acceptance stamp (eagle, arrows and three stars) is usually found on USGI M14 chromium plated and National Match barrels, M6 bayonets and M2 bipods. The DOD acceptance stamp, or cartouche, is sometimes found on wood stocks, Winchester gas cylinders, Winchester operating rods with the forward end vent hole and Springfield Armory operating rods. Winchester gas cylinders removed from an unopened tube packed in 1967 had faint DOD acceptance stamps at the rear end of each on the right hand side. The DOD cartouche was used on rifle parts as early as 1953 but certainly was discontinued for M14 rifle parts by 1968 when Springfield Armory closed down. The DOD cartouche was stamped to the M2 .50 BMG machine gun barrel in 1977 and applied with ink to 1980s production Colt M16A2 rifle receivers in the 6,14X,XXX to 6,16X,XXX serial

number range.

Bolt Markings - A USGI bolt (and receiver) may or may not have a dimple from a pin punch after successful proof round testing. Replacement bolts were proof round tested using a fixture. Frankford Arsenal and Lake City loaded the proof rounds to 65,000 psi. An inscribed letter M on a USGI bolt means it was examined by magnetic particle inspection. Not all USGI bolts will have the letter M though. USGI M14 bolts have additional stamps besides the part number and bolt manufacturer. The other markings are the material lot and the steel supplier codes. Such an example can be found on a bolt marked 7790186 HRT A20 CDR. These are in order: 1) part number 2) manufacturer code 3) material lot number and 4) steel supplier code. If a manufacturer had only one steel supplier then just the heat treat or material lot code was stamped on the bolt. Other manufacturers consolidated their markings to include both material lot and steel maker. All M14 type rifles properly assembled will have bolts with rollers attached.

The U. S. government Springfield Armory bolt markings can be confused with commercial reproduction Springfield Armory, Inc. bolts. The U. S. government Springfield Armory stamped its bolts in one of two ways, one format for 7790185 marked bolts and another format for 7790186 marked bolts. If the bolt was made by the U. S. government Springfield Armory and it is marked 7790185 it will have the following: 7790185-SA on the first line and the material lot number on the second line, e.g., YO2. U. S. government Springfield Armory bolts made to the 7790186 drawing have this identification scheme: 7790186 on the first line and then SA and the material lot number on the second line, e.g., Z1B. USGI M14 bolts made by Winchester have its CAGE Code, 66118, on the second line whether stamped 7790185 or 7790186 on the first line. Textile Machine Works M14 bolts can have the manufacturer code, HRT, either on the first line or the second line of the bolt markings. USGI M14 bolts were stamped with the 7790186 part number by no later than 1961. The 7790185 marking was used on USGI M14 bolts until at least 1961.

There are bolts with counterfeit markings. Ron Smith of Smith Enterprise, Inc. has seen two M14 bolts stamped TRW that were not made by TRW. Some demilitarized M1 Garand bolts have been rewelded and modified to fit the M14 receiver. Such bolts will have USGI M1 Garand markings, e.g, top line - 028287-125A bottom line - S-A10. Most genuine unaltered commercial Springfield Armory, Inc. M1A bolts do not have a pin punch dimple. The M1A bolts marked 7790185 on the top line and SA RRR on the bottom line are an exception to this rule of thumb. Bolts so marked have a visible casting sprue on the bottom side. All USGI bolts were phosphate coated. Any M14 bolt that is bare steel or has a finish other than phosphate coating was not produced that way by the USGI contractor so buyer beware! The bolt installed in the M14 type rifle should be able to pass the slide test as discussed in Kuhnhausen's manual and have proper lug engagement and proper headspace prior to use.

USGI National Match parts such as the barrel, front sight, and rear sight parts will be marked NM or NM/2A if made after October 1963. The NM marking may be stamped or engraved on USGI National Match barrels. The NM marking is applied by engraving to prevent deforming the inside of the barrel. 1983 vintage Maremont Corporation medium weight National Match barrels, as well as others, will have the engraved NM marking.

Smith Enterprise, Inc. manufactured the extended bolt lock for the Mk 14 Mod 0 and M14SE projects. It was developed for the U. S. Navy SEALs to facilitate ease of chambering the M14 rifle in cold weather. This extended bolt lock was made of AISI 8620 alloy steel, heat treated to a surface hardness of 60 HRC and given a phosphate coating. The first batch of Mk 14 Mod 0 and M14SE extended bolt locks were marked U. S. on the inboard side. U. S. and Tempe, AZ were placed on the inboard side of the extended bolt locks for the second production lot. Some were stamped MK-14 in serif font on the inboard side as well. In August 2010, the extended bolt lock was improved upon. The new extended bolt lock was manufactured by the metal injection molding process. It was given increased purchase area on the rear side for more positive engagement with the bolt. The part geometry was changed to better accommodate varying bolt window geometry found on commercial manufacture receivers. It now required removal of the empty magazine from the rifle (or depressing the follower) to release the bolt as an additional safety consideration.

Firing Pin - Three types of M14 firing pins were made. The original firing pins were made of completely phosphate coated AISI 8640 or 8645 alloy steel. The next version was a phosphate coated steel firing pin with a chromium plated tip. These were only made in 1962 and only by Springfield Armory. The second version firing pins were installed in Springfield Armory M14 bolts marked with the part number 7790186. The last version is a fully chromium plated steel firing pin. These were manufactured by no later than 1969.

The minimum hardness of the fully chromium plated firing pin is 600 on the Vickers scale or more than 55 HRC. Chromium plating of the firing pin resulted in a change to the NO GO (maximum) firing pin hole width at the bolt face to change from 0.083 " to 0.084 ". Only fully chromium plated firing pins are acceptable for overhaul of the USGI M14 rifle. The benefits of chromium plating are improved wear resistance and lubricity even though the plating on the firing pin is only 0.0002 " to 0.0008 " thick.

Flash Suppressor – There are no manufacturer markings on USGI or commercial reproduction government design M14 flash suppressors but a number of feature differences are discussed below:

1) Barrel Splines and Suppressor Slots - Commercial reproduction flash suppressors can have barrel splines with square ends or round ends. No USGI flash suppressors have been observed with round end barrel splines. The suppressor slots, including the ends, in both USGI and commercial reproduction units vary slightly in width. The slot ends can be rounded or almost square. The M14 flash suppressor drawing, F7791053, allows two

different spline end designs.

2) Front Sight Step - Some USGI flash suppressors, e.g., at least some Harrington & Richardson contract units, will have a "step" directly behind the front sight base while other USGI units do not. The presence of the "step", and the lack thereof, has been observed on commercial reproduction and forged and cast USGI flash suppressors.

3) Muzzle End Bevel - Additionally, some USGI and commercial reproduction flash suppressors have a 45 ° beveled muzzle end while others do not. Beveled and non-beveled ends are not indicative of the manufacturer as both type of muzzle end contours have been observed on commercial and USGI cast and forged units. The M14 flash suppressor drawing, F7791053, requires a length of 0.040 " + 0.020 " for the muzzle end bevel. However, USGI M14 flash suppressor muzzle end bevels have been measured as short as 0.037 " and as long as 0.065 ".

4) Cast and Forged Manufacture – Springfield Armory was manufacturing cast flash suppressors as early as 1959 but began producing forged units in September 1960. Flash suppressors made for Harrington & Richardson M14 rifles were cast as observed from New-In-Tube units. Well done finish machining can remove any obvious evidence that the part was made by casting. This is often the case with USGI flash suppressors as they generally have a better finish than commercial reproduction units. The poorer a cast flash suppressor was machined, the more likely the following can be observed: evidence of the casting sprue on the side of the front sight, the longitudinal mold parting line on the suppressor, rough edges on the suppressor slots and a less pronounced circumferential radius in front of the sight base. However, these exterior surface blemishes do not affect the function or reliability of the part. TRW flash suppressors were forged. An experienced machinist equipped with a jeweler's loop can discern if a flash suppressor was made by casting or forging. If the flash suppressor was formed by forging it is a USGI unit since commercial reproduction flash suppressors are made by casting.

The best means of determining whether or not a flash suppressor is USGI contract manufacture is to measure it with vernier calipers and compare the readings to the USGI M14 flash suppressor drawing F7791053. If several dimensions are out of tolerance, then the part is likely not USGI contract manufacture.

Operating Rod - The operating rod in the USGI M14 rifle serves three purposes in the cycle of operation: 1) moves the bolt rearward once acted upon by the gas piston 2) moves the bolt forward under spring force from the operating rod spring and 3) engages the connector assembly to facilitate automatic fire. Some Harrington & Richardson, Springfield Armory, and Winchester operating rods do not have a vent hole drilled in the forward end of the cylindrical portion. Three 1961 manufacture new-in-tube operating rods (two Harrington & Richardson and one Winchester) opened for examination had no vent hole. U. S. Army Aberdeen Proving Ground Report No. DPS-471 discusses the testing of twenty-one randomly selected M14 rifles. This testing was performed from

September 28, 1961 to January 30, 1962. The Winchester and Springfield Armory operating rods on the rifles in this test did not have the vent hole, but the Harrington & Richardson operating rods did. It appears that Harrington & Richardson added this change to the operating rod beginning in 1961. Springfield Armory and Winchester did likewise after 1961. The vent hole on the forward end of the tube section was added to the drawing with Revision G dated September 29, 1960. Harrington & Richardson operating rods were all marked 7267064 HRA at the forward end of the handle of the portion. Some of the Harrington & Richardson operating rods were also stamped with a material lot number centered below the first marking, e.g., 1, 3 or 5. Harrington & Richardson operating rods made of 8645 steel typically measure 35 to 38 HRC. A random sample TRW operating rod tested in April 2008 measured 42 HRC.

There were two USGI contracts awarded in 1984 for M14 operating rods. The operating rods were made by Mercury Tool & Machine for both contracts. However, Mercury Tool & Machine was a subcontractor to Rock Island Arsenal for one of the two contracts. Mercury Tool & Machine operating rods have the marking: top line - 7267064 bottom line - MFR 24411. Mercury Tool & Machine operating rods sometimes have misaligned factory welds straight out of the wrapper. The welded area is usually easy to see on Mercury Tool & Machine operating rods.

The USGI M14 drawing F7267064 shows the welding of the operating rod handle and cylinder halves together and requires a hole at the front end of the operating rod. The diameter of the hole is specified to be 0.077 " + 0.006 ". The welding techniques for assembling the operating rod were developed in Remington Arms Company in 1951. Only TRW made one piece operating rods for the U. S. government. TRW operating rods have a vent hole at the front end. All other manufacturers of USGI operating rods made operating rods by inertia welding the two halves together. The front end of the operating rod that contacts the gas piston is chromium plated for improved impact resistance. Rewelded USGI operating rods are sold on the surplus market. Many rewelded operating rods will not function smoothly due to misalignment of the two halves. Operating rods should be able to pass the slide test discussed in Kuhnhausen's manual before the rifle is completely assembled.

Gas System – The design of the gas system for the M14 rifle was decided upon after testing in 1954 of the T44E2 rifle. The original cutoff and expansion gas system design used in the M14 rifle was patented by Joseph C. White in 1933. It was more expensive to manufacture and the tolerances were tighter than the M1 Garand impingement design gas system. This gas system design was tested by the U. S. Army Ordnance Command as early as 1942 in an experimental M1 Carbine. The gas cutoff and expansion design produced a longer dwell time and lower peak pressure in the T44E2 with service ammunition than the M1 Garand impingement gas system, 2.0 milliseconds versus 1.4 milliseconds and 2000 psi compared to 2300 psi. Thus, it acts more gently on the rifle than the impingement design. The M14 gas piston moves about 1.5 " in operation. Early production Winchester gas pistons were finished with a black oxide coating.

In the 1980s, Art Luppino and another individual built a commercial manufacture semi-automatic M14 rifle with a modified gas system. It was built on an early production Smith Enterprise, Inc. receiver. The barrel and gas cylinder lock were modified to direct the flow of gas to the front of the gas piston through the gas cylinder lock. The barrel length and consequently, the front sight radius, was lengthened by two inches. A new design gas piston was manufactured. The unique gas piston was completely solid except for the front end which was successively drilled to a depth determined by test firing. The gas cylinder was modified and the flash suppressor was reamed out. Initially, the rifle would often short cycle or fail to feed during testing on Range 103 at Camp Pendleton. As the hole in the front end of the gas piston was drilled deeper, failure to cycle properly occurred less often. Mr. Luppino shot very well with this rifle at several 600 yard matches held in California. Unfortunately, this rifle was stolen from Mr. Luppino at Camp Perry.

The front band in the gas system serves two purposes: 1) a spacer between the barrel shoulder and the gas cylinder for proper alignment of the gas cylinder to the gas port 2) retention of the stock and hand guard. All variations of the gas cylinder lock serve the purpose of preventing forward movement of the gas cylinder. The gas cylinder plug limits the forward movement of the gas piston and keeps the gas cylinder lock from rotating.

Two versions of the M14 gas cylinder were manufactured. The early version does not have a lip just aft of the bottom gas port to support the front band. The late version (March 1960 design) gas cylinder was manufactured with a support lip for the front band. The lip is 0.095 " wide and 0.112 " high but serves a very important purpose. These early version gas cylinders were used in the production of T44E4 and some M14 rifles. Bill Ricca estimates that 75,000 to 100,000 of the early version gas cylinders were made by Winchester and Springfield Armory. Early version Winchester gas cylinders were stamped with intertwined P and W letters.

USGI gas cylinders made by the Torrington Company (Torrington, CT) have been observed with these markings: 1) G then T inside a circle followed by L 2) S then T inside a circle followed by L 3) Y then T inside a circle followed by L 4) K then T inside a circle followed by L 5) E then T inside a circle followed by L or 6) T inside a circle. Two gas cylinders marked in the first manner were removed from a Harrington & Richardson marked and sealed cardboard tube dated July 1962. Two gas cylinders marked in the fourth case were removed from a Harrington & Richardson marked and sealed cardboard tube dated 1964. An April 1962 dated tube of two Harrington & Richardson marked gas cylinders to find the marking noted in the fifth case. These subcontractor markings appear to denote a production date code. Early version and early production late version gas cylinders were machined from forgings. Rough forgings of gas cylinders were available for sale at gun shows in the 1970s. Late production late version gas cylinders are thought to be made from castings but this has not been confirmed.

Safety Markings - The following safety markings have been observed on USGI M14 safeties: 88 T I, 89 T I, 90 T I, A (raised letter), T I, HA, HB, H&R D, HRA, K8, MXR, O

(raised letter), ROBER HT-B, ROBER HT-D, HT-B, HT-D, TRW HT-A, TRW HT-B, TRW HT-C, and TRW HT-D. TRW safeties were marked in two lines of lettering with TRW on the top line. M1 Garand safeties, e.g., SA-9 or SA 11, were factory installed on commercial versions of the M14 rifle. They are interchangeable with the M14 type rifle.

Springs and Spring Design – The M14 rifle has fifteen springs though some are not readily obvious: bolt lock spring, butt plate hinge spring, butt plate trap door spring, connector assembly spring, elevation knob screw spring, ejector spring, extractor spring, hammer spring, hand guard band, magazine latch spring, operating rod spring, rear sight cover, safety spring, selector shaft spring, and spindle valve spring. The M14 NM has additional springs in the hooded rear sight aperture, two small coil springs and a beryllium-copper alloy snap ring. There is one coil spring in the hand grip assembly of the M14A1 stock. The M14 magazine, M3 breech shield, M6 bayonet, M12 blank firing attachment, and M76 grenade launcher each have one spring as well. The M2 bipod has four springs, one for each plunger button.

There are many types of coil springs, compression, die, extension, torsion, etc. A coil spring is typically made by coiling round wire or thin rod into a helical shape. With the exceptions of the elevation knob screw spring, hand guard band, rear sight cover and the safety spring, M14 type rifle springs are classified as constant diameter compression coil springs. A compression coil spring will resist a force applied straight into the end of the spring. When a compression coil spring is compressed axially (end-to-end), other forces are induced on the spring as well: lateral (side-to-side), a rotating moment and a tilting moment. The constant diameter design means the width of the spring does not vary.

Compression coil springs are further categorized by how the end of the spring is formed and how the material is wound. The end of a constant diameter compression coil spring can be formed in one three ways, tangential or open, squared or closed, and pigtail. The open end spring is cut anywhere along the helix so that there is no change in the pitch or spacing of the coil. The pigtail end means the spring is curled inward on the last coil to a smaller diameter then cut. The closed end spring is formed so that the spring will stand upright when placed on end. Closed end and open end compression coil springs are often ground to create very flat surfaces at each end. The flat ends provide better stability. A ground closed end increases the seating area and reduces buckling for the compression coil spring. The following M14 rifle springs have closed ground ends: ejector spring, extractor spring, hammer spring, operating rod spring and spindle valve spring. The selector shaft spring and bolt lock spring have open ends and are not ground. Magazine latch springs observed have closed ends but do not appear to be ground.

Grinding the end of the spring may be done to better distribute the applied force, make assembly of the parts easier, or in some cases prevent buckling. The free length of the compression coil spring compared to its mean diameter is known as the slenderness ratio. The free length of a compression coil spring is the distance from one end of the

spring to the other with no force applied. A compression coil spring with ground closed ends having a slenderness ratio of less than four will not buckle. A compression coil spring with unground closed ends may buckle if the slenderness ratio exceeds 2.63. The slenderness ratios for the bolt lock spring and the extractor spring are 4.05 and 4.03, respectively. It is not known if the slenderness ratio was considered in the designs of the bolt lock spring and extractor spring or if those values were coincidental to any concern for spring buckling.

The direction of the coil spring helix (left-hand or right-hand) is specified in several of the drawings. The bolt lock spring helical direction is optional per USGI drawing F7267074. The USGI drawing C7267078 specifies a left-hand twist for the magazine spring. The USGI drawings for the ejector spring, extractor spring, magazine latch spring and operating rod spring require a right-hand helical direction for each spring. Some USGI contract springs were made with the wrong twist. Such examples are a batch of operating rod springs made in 1983 and Harrington & Richardson contract extractor springs produced in November 1964. If the contractor was able to convince the contracting officer that spring function was not affected, though made with the wrong twist, it was accepted by the U. S. government.

The compression and fatigue strength of a coil spring is dependent upon a number of factors: material composition, wire surface finish, wire diameter and length, coil diameter, total number of coils and heat treatment. Spring manufacturers use a wide variety of materials for coil springs: carbon, alloy and stainless steels, phosphor bronze, copper beryllium alloy and brass depending on the application.

The USGI drawings for the M14 rifle compression coil springs specify the wire material, wire diameter, coil outside or inside diameter, free length, and total number of coils. The USGI drawing B7267079 for the operating rod spring is illustrative of the detailed requirements typical of M14 parts production. Some of the drawing B7267079 specifications are described below.

The operating rod spring material was 17-7 precipitation hardening stainless steel wire per military specification Mil-W-46078 and manufactured under military specification Mil-S-13572 Type 1 Grade B. This material was chosen for the operating rod spring in 1952 as part of the T44 rifle modifications. The physical dimension and performance requirements were as follows: wire diameter equal to 0.054 " + or – 0.001 ", coil outside diameter of 0.4575 " + or – 0.0025 ", free length of 15.23 ", a total of 104 coils, and the direction of the helix must be right-hand wound with closed ends.

The operating rod spring formed by coiling cold drawn wire had to be heat treated as follows: age hardened at 900 degrees Fahrenheit for one hour then air cooled. After that, the operating rod spring was heat set by heating at 700 degrees Fahrenheit for twenty minutes with the spring compressed to a length between 5.9 " and 6.0 ". Heat setting a spring improves the stress relaxation during use. Age hardening is used to increase the

strength and hardness of manufactured parts made from certain alloys, e.g., copper-beryllium and 17-7 cold drawn stainless steel. Each material responds differently to the age (precipitation) hardening process based on a combination of time, temperature and the amount of cold drawing from the initial rod size into the final wire diameter.

Depending on the material, the toughness, corrosion resistance, fatigue strength, electrical conductivity or thermal conductivity can be improved upon by stopping the hardening procedure before or after the time needed to achieve maximum strength. By age hardening and heat setting the operating rod spring, service life was significantly increased.

The operating rod spring, like other compression coil springs, was designed with a given spring rate. The spring rate, or stiffness, is defined as the amount of load (force) needed to compress the spring one inch. The lower the spring rate the softer the spring. After the operating rod spring had been heat treated and heat set it was compressed to solid length three times and then load tested at several specific lengths. These tests verified the operating rod spring met the design spring rate. The design spring rate for the M14 operating rod spring was 1.95. When the operating rod spring was compressed to a length of 10.97 " the applied load had to equal 8.13 pounds + or – 0.81 pounds. When the operating rod spring was compressed to 6.42 " the required load was 17.00 pounds + or – 1.69 pounds.

When the operating rod spring was compressed to the minimum operating length it measured about 7.19 " long with an applied load less than 16.00 pounds but sufficient to engage the bolt lock. The USGI drawing B7267079 for the operating rod spring specified a maximum length of 5.78 " for the solid compressed length. The design and manufacturing process ensured the USGI M14 operating rod spring would function properly for thousands of cycles. It also means that the minimum force necessary would always be exerted on the operating rod spring guide, and consequently, the magazine full of life sustaining ammunition. The M14 rifle enthusiast or collector should proceed with caution when hearing the term "mil-spec" in casual conversation with such detailed design, manufacturing and testing requirements for USGI M14 parts.

Coil spring material is subjected to torsional (twisting) stress when it is compressed. For a given set of spring dimensions, the varying amounts of applied force and compression distance determine the range of stress the spring will be subject to. Why does this matter? Because the maximum stress and the range of stress will determine the life of the spring. As the maximum stress increases or as the range of stress increases the life of the spring decreases. In other words, a thinner diameter spring or a spring that is compressed over a greater distance from its free length will wear out faster.

When a wire is twisted, the stress is greatest at the surface. Fatigue cracks commonly begin at defects in the spring surface. A very smooth spring surface will prevent fatigue cracking. Consequently, wire surface defects, e.g., pits and seams, are controlled in the cold drawing manufacturing process. For example, Seneca Wire & Manufacturing

Company (Fostoria, OH) limits the depth of surface defects in its ASTM A877 chromium silicon alloy steel wire to no more than 1.0 % of the wire diameter. ASTM A877 chromium silicon alloy steel wire is suitable for service applications requiring high fatigue strength at moderately high temperatures, e.g., M14 operating rod spring. Additionally, the USGI drawing C7267078 required the magazine spring to be "free from scratches, splits, laps, cracks, seams, nicks, die marks and other injurious defects." Replacement M14 magazine springs with noticeable nicks, often found on the outside of coil bends, are most likely not pre-1990 manufacture.

The question often arises as to whether or not a compression spring will take a permanent set if compressed to the minimum length and held over time, e.g., a fully loaded magazine or the bolt is held open. Coil springs can be designed to compress to solid height or length without taking a permanent set. The solid height of a compression spring is the length of the spring when fully compressed. If a permanent set is not desired, the spring material and diameter is chosen so that the torsional stress when compressed solid does not exceed approximately 40 % of the material minimum tensile strength. The minimum tensile strength, or yield strength, will vary with the diameter of the wire, e.g., 231,000 to 399,000 psi for ASTM A228 music wire. A permanent set occurs when the compression spring is compressed beyond its elastic limit and does not return to the original length. This results in a shorter free length but more significantly, lower spring force.

M14 magazine springs were tested and inspected to ensure they would not take a permanent set. Magazine springs selected for inspection were compressed to a height of 11/16 ", essentially compressed solid height, three times then examined for compliance with USGI drawing C7267078. This included meeting the free length requirement of 13 " – 2 ". A permanent set in a USGI M14 rifle compression spring is not formed when compressed to the minimum length and left indefinitely.

The majority of the compression coil springs in the M14 rifle are subjected to fatigue stress over a very large number of operating cycles. These springs were designed with this service requirement in mind. If a spring weakens enough the M14 rifle will malfunction in one manner or another. A weak magazine spring could cause cartridge feeding problems. If the extractor spring is weak the spent case may stick in the chamber after firing. A soft ejector spring could result in a spent case being caught between the bolt and receiver. In a combat situation, such malfunctions could prove fatal. Nonetheless, over the course of thousands and thousands of cycles, the free lengths of the operating rod spring and the hammer spring will gradually shorten so that they will warrant replacement.

Check-Mate Industries has been in business since 1972 as a tool and die and metal stampings manufacturer. The firm has completed more than 400 government arms related contracts and produced more than 10,000,000 rifle and pistol magazines. For the M14 rifle, Check-Mate Industries manufactures the magazine follower assembly, floor

plate and tube (body) using steel from American mills. The magazine springs are supplied to Check-Mate Industries. The springs typically exhibit slight surface nicks on the outboard side of the angled segments of each coil. These surface irregularities appear to be made in the same manner and at the same location and appear identical in dimension and finish. Sample springs examined in post-1991 Check-Mate Industries magazines manufactured over a period of several years possess these surface nicks. The surface nicks were formed by CNC bending machines during manufacture. The same springs were used in both government contract and commercial sale M14 magazines. Even though the magazine springs passed government inspection every time, Check-Mate Industries performed extensive testing on the springs to alleviate consumer concern. Check-Mate Industries found no negative effect on spring integrity or performance due to the presence of these surface blemishes.

By comparison, springs from genuine 1960s production Borg-Warner magazines are smooth in appearance and possess identical dimensions but the free length is about ½ " shorter than the springs found in Check-Mate Industries magazines. Before 1992, USGI M14 magazines springs had smooth surfaces with no irregularities visible to the naked eye, regardless of the contractor. What is the requirement for the M14 magazine spring appearance? The USGI drawing C7267078 Note 2 specifies, "Springs shall be free from scratches, splits, laps, cracks, seams, nicks, die marks, and other injurious defects."

Jeff St Paul (Tygh Valley, OR) tested 2006 production Check-Mate Industries magazine springs in December 2006 to determine if they met the USGI drawing spring force requirements at each specified length under compression. The magazine springs met the requirements exactly on each one tested. The magazine springs are heat treated after forming which tends to minimize any effect from minor surface irregularities.

At the same time, Mr. St Paul also performed accelerated use testing to determine what effect the minor die marks would have on magazine spring cycle life. He tested 2006 production M14 magazine springs with minor surface nicks sold by Check-Mate Industries. Spring force measurements were taken after 500 and 1000 cycles (simulation of 10,000 and 20,000 rounds respectively). At both points in the testing, there was no reduction whatsoever in spring force measurements taken at various compressed lengths and no change in the free length. In other words, Check-Mate Industries magazine springs show no degradation after simulating 20,000 rounds of fire. The surface nicks do not appear to have any adverse affect on performance. Thus, they are not an injurious defect and the spring meets the USGI drawing requirement. This is borne out by the fact that every lot of Check-Mate Industries M14 magazines supplied to the U. S. government under contract has exceeded the government conducted firing and corrosion resistance tests and visual inspection. There has never been any rejection of Check-Mate Industries M14 magazines by the U. S. government.

Springfield Armory performed an evaluation of M14 magazine springs in the 1960s. The effects of and repeated cycling of magazine spring were studied. The specified load

(spring force) for the USGI M14 magazine spring is 5.5 pounds + 0.75 pounds at a compressed length of 5.5 " (unloaded magazine). However, the Springfield Armory tests found that the M14 magazine spring will perform satisfactorily at a load as low as 4.5 pounds force at 5.5 " length.

In the Springfield Armory study, three USGI M14 magazine springs were placed into a vertical shaper for a gymnastication test. Each spring was cycled at a rate of 116 strokes per minute. The spring force was measured after so many cycles, 5, 55, 655, 1,655, etc. After 6,655 cycles, the spring force at 5.5 " long were 6.1, 6.1 and 5.75 pounds each. The load, or force, of each spring was checked again after 10,000 cycles. The results were 5.1, 5.75 and 3.9 pounds at 5.5 " length. One spring measured 5.25 pounds at 5.5 " length even after 12,000 cycles. The springs were found badly distorted at 10,000, 12,000 and 14,751 cycles, respectively.

In another part of the spring evaluation, ten magazines were stored loaded for five years. After the first week in storage, the magazine spring force was found to range from 5.1 to 5.6 pounds at 5.5 " length. After five years of loaded storage, the same ten magazines were test fired with six loadings (120 rounds per magazine). The magazines were then disassembled and the spring force measured. The results were 4.6 to 4.75 pounds for length of 5.5 ". There was no malfunction of any magazine.

Unloaded magazines were tested as well for the effects of long-term storage. Ten magazines were stored unloaded for five years. After the first week in storage, the force for each spring ranged from 8.3 to 8.8 pounds at 5.5 ". After five years, the same ten magazines were loaded and fired six times each (120 rounds per magazine). The force for each spring was then measured. The results ranged from 5.0 to 5.25 pounds at 5.5 " length. There was no malfunction of any magazine.

The spring design must also consider the temperature to which it will be subjected. The gas piston, and to a lesser degree, the operating rod guide, transfer heat to the operating rod and the operating rod spring. Temperature at the forward end of the operating rod has been measured above 500 degrees Fahrenheit. Chromium silicon alloy steel operating rod springs are rated for service to 475 degrees Fahrenheit.

The spindle valve spring is heated from burnt gunpowder gas flowing from the barrel into the gas cylinder. The spindle valve spring is made from either AISI 302 or 304 stainless steel to resist the high temperature gas. Stainless steel has a higher maximum service temperature than carbon steel. For example, 17-7 precipitation hardening stainless steel wire is rated for a maximum service temperature of 600 degrees Fahrenheit as compared to 250 and 300 degrees Fahrenheit for hard drawn carbon steel and oil tempered carbon steel, respectively.

The USGI M14 hammer spring is made from American Society of Testing and Materials (ASTM) 228 specification music wire. Music wire is manufactured by the cold drawing

method. ASTM 228 music wire is a high carbon steel with hardness ranging from 41 to 60 HRC. It is composed of a minimum of 98.4 % iron and a range of 0.2 to 0.6 % manganese and 0.7 to 1.0 % carbon content. ASTM A228 music wire is rated for a maximum service temperature of 250 degrees Fahrenheit. This rating is acceptable since the hammer spring is not intended to operate at that high a temperature. ASTM A877 chromium silicon alloy steel wire and ASTM 228 steel music wire are popular materials for compression springs requiring excellent fatigue strength, e.g., M14 rifle hammer spring.

The USGI hammer spring has twenty coils and a free length of 2.15 ". The length of the hammer spring coil affects lock time. Lock time is defined as the time from hammer release to firing pin depth strike. Art Tuttle was the troubleshooter at Springfield Armory on the M1 Garand rifle during World War II. He wrote in 1984 that the M1 Garand lock time was just under 6 milliseconds. In 2012, Art Neergaard, ShootingSight, LLC (Cincinnati, OH), obtained a lock time of 9 milliseconds in testing of a M14 type rifle. If the hammer spring has been shortened by cutting, it should not be used but replaced with a new one. Cutting the hammer spring coils increases the chance of an accidental discharge.

Other Parts and Accessories - Both types of M14 trigger guards were stamped from spring steel. The early trigger guard has a pin to act as the hammer stop. The hammer stop pin was brazed to the trigger housing. It was required to withstand an axial load of 500 pounds without failure. The design of the hammer stop in the late trigger guard is a bent tab. The design change occurred in September 1960 but early style trigger guards were still being made by Winchester in January 1962. The trigger guard can be used as an emergency means of cocking the hammer. With the hammer forward and the safety disengaged, the hammer can be cocked by pulling the trigger guard downward and upward similar to a lever action rifle. Springfield Armory triggers often have a numeral, e.g., 4 or 19, on the side. This number represents the forging die used to make the trigger. Springfield Armory manufactured front sights and selector switches by casting. Harrington & Richardson performed the finishing operations on its selector switches. The bar stock blanks made on screw machines were supplied by Wright Manufacturing Co.

Extractors were made by forging. If an extractor is made by casting it is a commercial reproduction. Harrington & Richardson and Winchester rear sight bases were often stamped with a code, e.g., B1, B2, B3, B4, B5 or B10. These were heat lot numbers. A milled rear sight base marked NM/2A on the right hand side and BST2 on the bottom is likely a USGI contract item.

Operating rod spring guides have one hole at the rear end for the connector lock to slide through. The "spine" of the early version operating rod spring guide was machined with a center channel on either side running most of its length. The channel lightened but strengthened the part. The late version USGI operating rod spring guides had four stadium holes in the "spine" as well as the hole for the connector lock. The late version

was less expensive to manufacture. Both versions were hardened to give long service life for the magazine catch. The connector lock secures the operating rod spring guide to the receiver. For comparison purposes, the weight of several versions of the operating rod spring guide are as follows: 1) early USGI – 0.81 ounce 2) late USGI - 0.87 ounce 3) master armorer built NM – 2.10 ounces 3) Brookfield Precision Tool NM – 2.24 ounces 4) Sadlak Industries hollow shaft NM – 1.73 ounces 5) Sadlak Industries solid shaft NM – 2.26 ounces.

Springfield Armory made all parts for the M14 rifle but also used subcontractors for various parts in later years. Workers there made production runs of flash suppressors in December 1964 and gas cylinders between July 01, 1964 and June 30, 1965. Between July 01, 1965 and June 30, 1966 the Armory began production to deliver an order of spare M14 parts including 64,000 bolts, 35,000 operating rods, and 12,000 stock assemblies. This spare parts production was expected to be completed by April 1967. Springfield Armory also received an order for 52,700 M14 barrels in Fiscal Year 1967. The first of these barrels were delivered in June 1967 and production continued into October 1967.

The marking BRW S-1 indicates the part was made at the Bellwood, Illinois plant of Borg-Warner. The BRW S-1 marking may be stamped upright, upside down or diagonally on genuine USGI M14 magazines. The Borg-Warner Brake Division may have produced the BRW B-2 marked magazines but this has not been confirmed. Borg-Warner made magazines from as early as December 1961 until June 1969. BRW, KMT and UHC marked magazines were made for Springfield Armory in the 1960s.

Winchester made all the major M14 parts and most of the small parts with the exception of springs, pins and screws. The M14 parts Winchester made equaled 80 % of the value of the rifle at the time. Westinghouse Electric made M14 magazines for Harrington & Richardson in 1961 and Olin-Mathieson Chemical Corporation (Winchester) in 1962. Likewise, Union Hardware & Metal Company, which became Brunswick Sports Products Company, made magazines for Olin-Mathieson Chemical Corporation. Winchester had three M14 parts contracts totalling about \$881,000.00 from October 1965 until about February 1971. One of the contracts was for gas cylinders in 1967. On a side note, Union Hardware & Metal Company sold its business to Brunswick Corporation in late 1960. Brunswick continued to use the UHC marking for its contract M14 magazines.

TRW made eleven major parts during its M14 rifle production, which equaled 65 % of the rifle's value. The company's management purposefully produced what it thought could be made economically well. TRW did produce replacement gas cylinders until at least August 1967 and bolts as late as March 1970. The cardboard box containing five cardboard tubes of gas cylinders indicated TRW as the USGI contractor but the individual cardboard tubes did not list TRW as the manufacturer.

M14 RIFLE HISTORY AND DEVELOPMENT

M14 bolts stamped 7790186 TRW ZJ and wrapped in packaging dated July and October 1969 and March 1970 reveals that TRW kept and used some of the M14 project machinery for some time after the M14 NM rifle contract was fulfilled. From October 1965 until about February 1971, TRW had M14 parts contracts totaling approximately \$2,144,000.00. One contract was to make bolts with the roller assembled and the other for gas cylinders. At \$1,927,000, the 1968 contract to make bolts was the third largest single award ever for a M14 part or accessory. Some or all of the M14 replacement parts made under contract by TRW, Inc. may have been through its TRW Replacement Parts Division (CAGE Code 66614). The U. S. government budgeted \$4,000 to lay away twenty-one M14 project production machines at TRW (\$2,000 in Fiscal Year 69, \$1,000 in Fiscal Year 70 and \$1,000 in Fiscal Year 73). Twenty of the twenty-one production machines were to be laid up by the end of June 1970. The last M14 production machine at TRW was scheduled for lay up in February 1973. Based on the contracts awarded, these machine tools were likely use for making M14 bolts.

Harrington & Richardson subcontracted parts production to a large extent for its rifle contracts. Parts marked with HR followed by a third letter, e.g., HRT, were manufactured by subcontractors to Harrington & Richardson. Harrington & Richardson went on to produce a substantial selection of M14 replacement parts under twelve U. S. government contracts totalling approximately \$1,600,000.00 between October 1965 and about December 1971. Harrington & Richardson, Inc. produced gas cylinder locks and bolt locks in 1966 and gas pistons, selector switches and connector assemblies in 1967.

Frazier Manufacturing Company produced elevation knob and pinion assemblies in 1962 as replacement parts and Wico Electric Company did likewise in 1969. Bruce Machine & Engineering produced gas pistons in 1966. Spec Tool Co. manufactured operating rod spring guides in 1967. The same year, Structurlite Plastics Corporation made solid fiberglass hand guards and Precision Products, Inc. produced ejector assemblies. The M2 bipod was made by Farmer Tool & Supply Co. as late as 1968. Mechanical Components Corporation made gas cylinders in 1969 and Benrus Watch Company manufactured firing pins the same year. Dennison Machine Tool Co., Inc. made hammers about 1969 to 1970. Hesse Machine & Mfg. Co. manufactured flash suppressors in 1970. The Brookfield Precision Tool parts were made from 1988 to 1996.

Watervliet Arsenal - Watervliet Arsenal (Watervliet, NY) was established in 1813. It is famous as the cannon and artillery factory for the U. S. Army and U. S. Navy. However, Watervliet Arsenal did play a part in the production of the M14 rifle. In February 1961, the Arsenal was awarded \$330,906.00 by Springfield Armory to manufacture M14 parts. This work mostly consisted of pilot line production of bolts and cartridge clip guides for Harrington & Richardson. Mr. S. J. Soltys, of Troy, NY, was the head of the minor components section. The minor components section made the M14 parts for the Arsenal in 1961.

Watervliet Arsenal also modified about 200 M14 bolts in its tool room shortly after Operation Desert Storm. The bolts were machined for a precision lug rear-to-face dimension. A special machine tool fixture was provided to the tool room along with the lot of bolts for the job. Less than fifty of the bolts were found to have sufficient material to meet the dimensional requirements for this unusual order. The source that provided the tool fixture is unknown as well as where it went to or if there were any further plans for its use.

Genuine USGI stampings are 1/16 " tall on the bolt and trigger housing. Note that not all USGI M14 parts were made by forging or extrusion. Some were made by investment casting, e.g., flash suppressors, winter trigger safeties, selector switches, sear releases and M14E2 muzzle stabilizers. Sometimes a casting can be identified by a raised line on the surface of the part where the halves of the mold were fitted together.

A July 1966 report by Springfield Armory reported on Department of the Army Project number 45-4-73102-01-45-M6. The project was an investigation into the serviceability of eleven SPIW parts made by investment casting. The report concluded that investment cast parts were suitable for the SPIW with improved service life for some of the parts. As an example, the service life of the SPIW hammer made by investment casting was twice that of a hammer machined from bar stock even though both parts were heat-treated to the same hardness. IBM brand M1918A2 Browning Automatic Rifle receivers were made by investment casting in the 1940s. The largest firearms manufacturer in the United States, Sturm, Ruger, & Co., Inc. has enjoyed tremendous commercial success with its rifle, shot gun, pistol and revolver receivers, frames, slides, bolts and other parts made from investment castings. The chief advantage of investment casting to produce rifle parts is cost savings from reduced machine tool run time. If sound castings meeting the required element compositions are used and heat treatment procedure is strictly followed, investment cast parts are satisfactory for use in rifles.

FSCM and CAGE – From late in World War II until late 1974, contractors doing business with the U. S. government were identified by a five digit number known as the Federal Supply Code for Manufacturers (FSCM). The FSCM system eventually ran out of five digit numbers. So, as of October 25, 1974 all new contractors are identified by a five alphanumeric character code known as a Contractor and Government Entity (CAGE) code. The CAGE system includes the old FSCM numbers as well. For example, 0LB99 was a part made by McMillan Fiberglass Stocks. Consequently, any part made by a business assigned an alphanumeric CAGE Code could not have been produced before October 25, 1974.

FSN, NSN, SNL and FSC - The four character code starting with "A", "B", "J", etc. found at the end of a part Federal Stock Number (FSN) was part of the Standard Nomenclature System (SNL) in use by the U. S. Army for ordnance items since the late 1920s. The SNL system code identified the system the part was associated with. The first character, a letter, identified the group of systems. The letter A stood for automatic weapons. The

letter B group included small arms and pyrotechnic launchers. The letter J was assigned to systems for tools. The numbers were sequentially assigned to each system within a group. For example, B21 was the M1 Rifle and B53 was the M14 (and T44E4) rifle system. The system codes sometimes had zeroes in the format but the meaning was the same, i.e., B53 was the same as B053. Items that were carried over to new systems, i.e., M1 rear sight aperture, kept the original SNL system code. That is why sometimes the B21 code is used on the packaging of M14 parts. The SNL system codes were to be discontinued with the adoption of the Federal Stock Number system. However, the SNL codes were used until about 1970.

To standardize identification of parts, vehicles, fuels, lubricants, clothing and everything else the U. S. Armed Forces needed, the Federal Stock Number system was adopted on January 01, 1954. U. S. Army ordnance items were adopted into the FSN system. The FSN number was an eleven digit numbering format. The M14 gas cylinder had a FSN of 1005-790-8766. The first four digits of the FSN (and later National Stock Number) was the Federal Supply Code or FSC. The FSC was an item group number. For example, 1005 was assigned to items belonging to small arms up to and including 30 mm diameter bore. The FSC 9150 was assigned to lubricants and so forth.

By the early 1970s, the number of items in the Federal Stock system had grown so large that it was apparent the eleven digit format would not have enough numbers to provide a unique number for each item. Consequently, the National Stock Number (NSN) system was implemented. For existing FSNs, the conversion to NSN was relatively simple by adding two digits immediately after the FSC. Hence, the gas cylinder FSN of 1005-790-8766 became the NSN 1005-00-790-8766. The two digit code is known as the National Codification Bureau. The two digit code identifies the nation that assigned the NSN and maintains the item. The USA is assigned the two digit codes 00 and 01. As more items were added to the supply system the numerals 01 were placed after the FSC to continue the practice of assigning a unique stock number for every supply item. The NSN system is used by NATO member and other allied countries. M14 items such as pins and screws were reclassified into other Federal Supply Codes. As an example, the late version trigger pin had a FSN of 1005-819-4501 but was given a NSN of 5315-00-819-4501.

By 2004, the U. S. military supply system had a shortage of spare M14 parts. On May 04, 2004, a solicitation for M14 parts was posted on the Internet by Rock Island Arsenal. This request for parts included 1,400 hammer spring plungers, 100 operating rods, 150 gas pistons, 750 ejector assemblies and 150 flash suppressors. From 2004 to 2009, Rock Island Arsenal awarded contracts and issued purchase orders for M14 parts:

December 29, 2004 - 400 gas pistons (Advanced CNC Manufacturing, Inc.)

March 28, 2005 – 400 ejectors and ejector springs (Anco Machine Co.)

May 23, 2005 – 700 front sights (Tri-Technologies, Inc.)

June 08, 2005 – 900 flash suppressors (Airtronic Services, Inc.)

June 28, 2005 – 450 operating rods (Tri-Technologies, Inc.)

LEE EMERSON

August 03, 2005 - 400 gas pistons (Advanced CNC Manufacturing, Inc.)
August 12, 2005 - 350 trigger and sear assemblies (Tri-Technologies, Inc.)
September 19, 2005 - 25,000 magazines (Check-Mate Industries, Inc.)
March 02, 2006 - 400 hammers (Smith Enterprise, Inc.)
March 07, 2006 - 155 operating rod guides (Beta Engineering, Inc.)
September 08, 2006 - 400 safeties (Bells Chapel Machine & Tool)
January 04, 2007 - 2,600 ejector assemblies (Focus Hope Companies, Inc.)
January 29, 2007 - 400 safeties (Connectec Company, Inc.)
March 12, 2007 - 300 gas pistons (Scott Products, Inc.)
March 29, 2007 - 300 operating rod guides (Swaim Machine Co., Inc.)
April 17, 2007 - 30 M14 EBR stocks with accessories (Sage International, Ltd.)
October 18, 2007 - 900 front bands (Connectec Company, Inc.)
October 29, 2007 - 500 M14 EBR stocks with accessories (Sage International, Ltd.)
January 28, 2008 - 350 operating rod guides (Swaim Machine Co., Inc.)
June 01, 2009 - 20,000 magazines (Check-Mate Industries, Inc.)

Since late 2001 when hostilities began in Afghanistan, individual servicemen and combat unit supply officers in the U. S. Army have purchased small quantities of accessories, magazines, parts, and optics from the commercial market to better equip and upgrade the M14 rifles in their custody. Some funds were eventually budgeted for maintenance support tools and repair parts. Rock Island Arsenal purchased the following M14 tools and parts in Fiscal Years 2008 and 2009: 426 breech bore field reject gages, 297 gas piston snap gages, 450 firing pin protrusion gages, seventy-six 1.6355 " headspace gages, 245 field test gage bolts, 244 flash suppressor alignment tools, 216 gas cylinder plug gages, sixteen field chamfer tools, 176 1.6455 " headspace gages, two sets of M14 DMR headspace gages, 147 M14E2 muzzle stabilizers, 1,067 front bands, 398 standard rear sight apertures, 582 operating rod guides, 203 magazine latches, seven National Match rear sight apertures, five front sling swivels, twenty-one selector shafts, and twenty-five selector switches.

U. S. government financial records did not always identify the specific M14 part or accessory made for a given contract. Nonetheless, the following companies have not been listed above but were definitely involved in making at least one USGI M14 rifle item under contract. All of the companies listed below were awarded contracts valued at more than \$10,000.00 for a M14 related item between July 01, 1965 and June 30, 1997 by either the U. S. Army or the U. S. Navy.

Allied Materials & Equipment Co. - Kansas City, MO
Argo Spring Mfg. Co., Inc. - Norwalk, CA
Astron Industries, Inc. - Glastonbury, CT
Basic Manufacturing, Inc. - Butler, WI
Bemis & Call Co. - Springfield, MA
Bristol Dynamics - Brooklyn, NY
Cantellos Tool & Gage - Oglesby, IL

M14 RIFLE HISTORY AND DEVELOPMENT

Connecticut Spring Corp. - Farmington, CT
Contract Machining Corp. - Cambridge, MA
Crocket & Kelly, Inc. - Westminster, CO
Cumberland Machinery Inc. - New Kingston, PA
Edson Tool, Inc. - Freeport, NY
Engineering Research, Inc. - Indianapolis, IN
Engineering Research, Inc. - Naples, FL
G Z Products Inc. - Rancho Cordova, CA
Handy Tool & Mfg Co., Inc. - Woodside, NY
Harder Precision Components - Clearwater, FL
Harris Manufacturing Co. - Smyrna, DE
Hawkeye Speciality Co. - Davenport, IA
Herlo Engineering Corp. - Hawthorne, CA
Holiday Manufacturing Co. - Grand Island, NE
Hoppe Tool Works, Inc. - Chicopee Falls, MA
J C Manufacturing, Inc. - Minneapolis, MN
Kan Du Tool & Instrument Corp. - Valley Stream, NY
Kurz Kasch, Inc. - Newcomerstown, OH
Leetronics, Inc. - Brooklyn, NY
Lemco Plastics, Inc. - Milwaukee, WI
Lewis Machine & Tool Co. - Milan, IL
Lincoln Machine Parts Corp. - New York, NY
Lisk G W Co., Inc. - Clifton Springs, NY
Micron Mfg. Co. - Springfield, MA
Mil Std Corp. - Glen Cove, NY
National Metalcrafters, Inc. - Philadelphia, PA
Newcastle Industries, Inc. - Kentwood, MI
Nichols Engineering, Inc. - Shelton, CT
Northampton Machine Co., Inc. - Northampton, MA
Northeastern Machine & Tool Corp. - Stamford, CT
O'Hare Spring Co., Inc. - Des Plaines, IL
Opto Mechanik, Inc. - Melbourne, FL
Outdoor Sports Industries, Inc. - Denver, CO
P M Engineering Service, Inc. - Van Nuys, CA
Penjaska Tool Co. - Owosso, MI
Precision Founders, Inc. - San Leandro, CA
Precision International Corp. - Tullahoma, TN
Remington Arms Co., Inc. - Ilion, NY
Roy-Alan Corp. - New York, NY
Skyline Industries - Fort Worth, TX
Southwest Grinding & Mfg., Inc. - Euliss, TX
Standard Armament, Inc. - Glendale, CA
Textile Belting & Strapping Co. - Fall River, MA

Tompkins Products - Detroit, MI
Ubique, Ltd. - Brooklyn, NY
United States Industries, Inc. - Grand Island, NE
Vari Ohm Electronics, Inc. - Islip, NY
Wall Mfg. Co. - Freeport, NY
Westchester Tool & Die Corp. - Buchanan, NY

Some M14 and M14E2 parts were marked with the respective USGI part number. For some parts, the part number was consistently applied, e.g., barrels and bolts. For other parts, they were usually not marked with the part number. Most gas cylinders were not stamped with the part number. The exceptions were those made in 1963 by Saco-Lowell and in 1969 by Mechanical Components Corp. Those parts were stamped S/N 7790902.

USGI Parts Sales

USGI parts were sold to the American public after termination of M14 rifle production in 1964. Harrington & Richardson, TRW and Winchester all sold off their M14 parts inventory to the commercial market. This was done in an attempt to recoup some of their investment in the M14 program. Additionally, in the 1960s the U. S. Army declared much of its M14 parts inventory surplus and released them to the public for sale. Mr. Elmer Ballance of Devine, Texas purchased the parts inventory from companies who manufactured the M14 and from foreign nations that had received M14 rifles and parts under U. S. military assistance programs. From these parts stocks, his business began production of the M1A rifle in 1971.

In the early 1970s, surplus small arms parts dealers such as Thomas A. Buss (then of Springdale, PA), Gerald Drasen (1993 address Nesard P. O. Box 56 Lake Zurich, IL 60047) and William J. Ricca (PA) bought and sold USGI M14 parts from government auction sales and on the open market. In 1970 and 1971, a fair number of individuals, small gun shops and large parts and accessories houses sold surplus USGI M14 parts and accessories to the civilian market. AR Sales Co. bought M14 parts directly from the contractors about the same time or earlier. Bob Penney, associated with Federal Ordnance, Inc. in the early 1970s, was also buying surplus M14 parts. In 1973, USGI M14 bolts and operating rods could be had at gun shows in San Jose, CA for \$5.00 each and USGI M14 barrels for \$10.00 to \$15.00 each. In the 1970s and 1980s, surplus parts dealers William J. Ricca, Thomas A. Buss, Fred Hochrein (PA), Bill Plantamura (M14 Research Service), Jay Higgins (The Amherst Depot), and Bruce Dow (then of East Oakmont, PA) bought and traded USGI M14 parts at gun shows in Pennsylvania and Ohio.

About 1985, Jack Friese, owner of Arms Corporation of America, Inc., imported approximately 2000 M14 parts kits from Israel. Before these parts kits arrived in the United States, they made their way through the United Kingdom. Gerald Drasen purchased the bulk of these parts kits. Some of these M14 parts kits were sold by Bill

Ricca on a consignment basis. Some of these parts kits were used to assemble H&R Gun Co. semi-automatic M14 rifles. At about the same time, a batch of 1,200 M14E2 stock fore grips and 30,000 M14 gas cylinder plugs were released by Naval Surface Warfare Center (Crane, IN) and purchased and divided among three parts dealers. Arms Corporation of America, Inc. purchased M14 parts and other items from Karl Maunz from December 1985 until August 1987. Several times in the 1980s, Bob Reese also brought large shipments of M14 parts into the United States. Some other companies also imported M14 parts from Israel during the 1990s. M14 bolts, barrels and operating rods imported from Israel will have Hebrew markings. These Hebrew letter markings are typically found on the top side of the bolt, on the top of the barrel chamber and adjacent to the USGI markings on the operating rod. Through the years, NSWC Crane and Rock Island Arsenal have released various USGI M14 parts for public sale. Many of these parts were sold as a result of destroying M14 rifles. Some of the operating rods from demilitarized M14 rifles were broken in the process, sold as scrap, welded back together and sold in the surplus parts market..

The Office of the Director of the Civilian Marksmanship Program (ODCMP) received and sold USGI M14 parts in the 1990s. ODCMP received its last shipment of USGI M14 parts in 1996 as part of its normal routine operations. These parts were sold to members of DCM affiliated shooting clubs in the United States until supplies were exhausted at the end of 2003. The sales ended because the ODCMP sold what M14 parts they had, according to Orest Michaels, Chief Operating Officer. In February 2004, he did not know when or if the ODCMP would be able to sell any M14 parts in the future. USGI M14 parts remain available for sale from various gunsmiths and parts houses, but in very limited quantities and at increasingly higher prices. Beginning in early 2004, USGI contract barrels, bolts, gas cylinders, operating rods, and flash suppressors are not widely available in the commercial market.

Parts Interchangeability with the M1 Garand Rifle

The following parts are interchangeable between the M1 Garand and the M14 type rifle: butt swivel, lower butt plate screw, rear sight aperture, elevation knob and pinion (note that the M14 elevation knob is calibrated in meters, while the M1 Garand elevation knob is calibrated in yards), rear sight base, sight cover, trigger (although the sear requires slight modification of the M14 sear for use in the M1 Garand rifle), hammer, hammer spring, hammer spring plunger, hammer spring housing, safety, hammer pin, trigger pin, extractor, extractor spring, extractor spring plunger, hand guard band (as long as it has not been deformed during removal from the M14 rifle hand guard or the M1 Garand rifle rear hand guard), and butt plates on certain M14 stocks.

A M1 Garand rifle ejector will fit inside a M14 bolt if mated to a M14 ejector spring. However, it is best to use the M14 ejector. The M1 ejector has a single beveled surface on its forward end. The ejector for the M14 was improved by creating two beveled surfaces on the forward end. This minor change resulted in a much more consistent

ejection path for spent cartridge cases.

Hammers marked with part numbers C46008, C5546008 and D5546008 are often found in the firing mechanisms of commercial M14 type rifles. These markings indicate World War II, early 1950s and mid-to-late 1950s production M1 Rifle hammers, respectively. The letter prefix of the part number indicated the actual physical size of the part drawing.

The M1 Garand rifle hammer spring plunger *may* cause a problem with the M1A rifle. The design for the USGI M1 rifle hammer spring plunger, B6008880, was originally drawn on August 02, 1937. In 1978, Springfield Armory, Inc. assembled M1A firing mechanisms with modified M1 Garand rifle hammer spring plungers. The head portion of the M1 Garand rifle hammer spring plunger was originally designed with “wings” or “ears” akin to the M1 receiver rear sight pocket. The hammer spring plungers were modified by grinding down the left side “wings” before assembling into the M1A firing mechanisms. By not grinding the “wings” of the hammer spring plunger, the hammer spring plunger *may* move out of the hammer notch which could cause the hammer to move. The USGI drawing B6008880 was revised, likely in 1958, to remove the “wings” from the head portion of the hammer spring plunger. Nonetheless, both types of hammer spring plungers are acceptable for USGI M14 rifle overhauls per U. S. Army DMWR 9-1005-223. The M1 hammer spring plunger is often used in match grade M14 type rifles.

The following operator level items are interchangeable: web sling, cleaning rod section carry case, cleaning rod sections, cleaning rod patch tip, short oiler bottle, plastic spacer for bore brush and patch tip, 7.62 mm chamber brush for 7.62 mm M1 Garands only, .30 Caliber bore brush (although the drawing during the 1960s shortened the brush slightly to prevent it from hitting the inside of the butt plate), and either Plastilube or Lubriplate grease was authorized for use on both rifles. The bolt assembly and disassembly tool can be used with either rifle bolt.

M1 Garand Parts on M14 Type Rifles

As part of the Marshall Plan after World War II, Italy was given Winchester's M1 machine tools and dies for producing M1 rifles and M1 parts for our European allies which had adopted the M1 Garand. Beretta was given the machinery for making the M1 Garand but two other Italian companies made M1 rifle parts as well. Italian parts quality is as good as USGI M1 Garand parts quality.

Springfield Armory, Inc., Reese Surplus, AIM Surplus and a few other American and Canadian companies have imported many M1 parts kits from Italy. Springfield Armory, Inc. has used some of these Italian parts in its assembly of M1A rifles. Except for very small parts the Italians marked M1 Garand rifle parts with one of three markings: 1) PB for Pietro Beretta 2) BMR for Breda Meccanica Romana Italia and 3) BMB for Breda Meccanica Bresciana. Inexplicably, Pietro Beretta marked BM59 rear sight knobs were observed on two USGI M14 receivers destroyed by the U. S. government in the 1990s.

The destroyed M14 receivers were obtained through U. S. government surplus auction.

USGI Parts Packaging

The USGI contractor who manufactured the part may be identified on the packaging, e.g., Winchester and Harrington & Richardson flash suppressors, Springfield Armory and Harrington & Richardson gas cylinders and Winchester trigger and sear assemblies. More often than not, the contractor is not identified on the packaging. M14 parts made by Springfield Armory or subcontracted out will usually have the marking Springfield Armory on the package label. M14 parts made by contracts let by the U. S. Army Material Command, Weapons Command or the Defense Supply Agency usually do not identify the contractor on the package label.

Genuine USGI parts were always identified with a Federal Stock Number or a National Stock Number on the packaging. The change from Federal Stock Numbers to National Stock Numbers occurred between 1971 and 1975. Bar codes did not appear on USGI parts packaging until the 1980s. The term REPACK was not used on genuine USGI parts packaging. The Defense Supply Agency was named as such from October 01, 1961 until January 01, 1977. From 1977 to the present, it has been known as the Defense Logistics Agency.

Shell Development Company (San Francisco, CA) and Daubert Chemical Company (then Oak Brook, IL) held at least one patent in the 1960s for the volatile corrosion inhibitor used in the wrapping paper for USGI M14 parts, magazines and accessories. Cadillac Products, Inc. (Warren, MI), Champion Packages Company (Columbus, GA), Chase Bag Company, Continental Can Co., Inc. (Flexible Packaging Division), Crawford Paper & Plastic, Inc., EDCO (Brooklyn, NY), H P Smith Paper Co., Lawrence Packaging Supply Corp. (Newark, NJ), Ludlow Corporation Packaging Division (Holyoke, MA), Orchard Paper Company (St. Louis, MO), Plastic Film Corporation, RAP Industries (Columbus, GA), Richmond Corporation, and Seal Bag (Rochester, NY) were among dozens of USGI contractors in the 1960s and 1970s that produced chemical vapor paper for the packaging of USGI M14 parts, magazines and accessories. Additionally, Ludlow Corporation produced a private label wrapping paper marked Marvellum. Ludlow manufactured many types of packaging paper for the U. S. military from as early as 1946 until at least 1981. Daubert Chemical Company and EDCO are still in business. RAP Industries and Seal Bag are no longer in business.

If the packaging was not torn or opened, the part was safe from corrosion for five to twenty-five years. The U. S. government over the years released sizeable quantities of chemical vapor barrier paper used to package USGI M14 parts. This paper has been used to package commercial reproduction M14 rifle items which implies the contents were made as part of a U. S. government contract when such is not the case.

Before the early 1980s, USGI M14 parts wrapped in chemically treated paper got coated with volatile corrosion inhibitor, a white powdery substance, over time. This is perfectly normal and the substance can be wiped off. In the early 1980s, packaging technology had advanced so that the volatile corrosion inhibitor was applied to the paper in a thin film of slow drying solvent. Thus, newer technology volatile corrosion inhibitor treated paper will feel moist when freshly made.

A complete list of Federal Stock Numbers for M14 parts, accessories, tools, maintenance supplies, special equipment and special packaging material can be found in Appendix B of TM 9-1005-223-34. Some parts such as firing pins, combination tools, and magazines were opened, inspected and repacked by Anniston Army Depot, Crane Naval Surface Warfare Center, Letterkenny Army Depot, Red River Army Depot and other supply depots. This occurred as early as February 1968. Used parts such as blank firing attachments and magazines, were cleaned up and rewrapped by the supply depots for reissue as needed.

USGI M14 Magazine Packaging - In the 1960s, USGI M14 magazines were wrapped in one of three ways: 1) cheese cloth on the outside and chemical vapor barrier wrapper surrounding the magazine on the inside 2) oil preservative wrapper or 3) chemically treated cardboard sleeve inside a sealed transparent plastic wrap. Either method protected the magazine from moisture inside the package while it remained sealed. Chemically treated sealable wrapping paper was not available until about 1985. Packaging of USGI M14 parts was inspected by government employees as part of the production contract.

As with other USGI parts, the USGI M14 magazine packages were printed with specific information to identify the contents. Markings from a package from 1968 serves to illustrate what information was indicated (from top to bottom): first line – 1005-628-9048 is the Federal Stock Number second line – MAGAZINE ASSY is the nomenclature third line – 2-EA is the quantity fourth line – DAAG-25-68-C-0402 is the contract number fifth line – A-MAR-1968 is the year and date the magazines were packaged. From at least 2004 onward, Check-Mate Industries packaged its USGI contract M14 magazines in blue color plastic bags for the U. S. military. Check-Mate Industries magazines produced in 2005 and 2006 for the U. S. government contract kept the RESTRICTED USE - LAW ENFORCEMENT / GOVERNMENT USE ONLY marking on the magazine body rear side.

Notes on Commercial Parts

Commercial manufacture and Chinese M14 parts are available in much smaller quantities than what USGI parts were back in the 1960s and early 1970s. While certain commercial parts are available at the time of this writing that may not be the case in the future.

Badger Ordnance - Established in 1982, Badger Ordnance specializes in the manufacture of firearms precision tools, gauges, accessories and scope mounts and

rings. It offers a fluted National Match operating rod spring guide designed to minimize spring binding and drag. The Badger Ordnance operating rod spring guide (part number 223-05) was introduced in its 2004 Product Catalog. The Badger Ordnance spring guide is made from a single piece of AISI 4142 molybdenum-chromium alloy steel.

LRB of Long Island, Inc. - LRB Arms gas cylinders are forged by Bourdon Forge and machined by J V Precision Machine Co. These were introduced to the commercial market in March 2008. At the same time, LRB Arms began marketing faux flash suppressors with bayonet lugs and M14E2 style muzzle brakes. Both of these muzzle attachments consist of demilitarized USGI flash suppressor front sight dovetail sections welded to new muzzle devices. In the case of the faux flash suppressor, the USGI bayonet lug is retained for aesthetic reasons. The faux flash suppressor complies with California law. The M14E2 style muzzle brake is similar to the first version USGI M14E2 muzzle stabilizer in appearance except the bayonet lug has been removed and the right hand side of the muzzle device has three radial holes. The three radial holes keep the muzzle from moving to the right during fire. The demilitarized USGI flash suppressor front sight dovetail sections were supplied by Armscorp USA, Inc. The muzzle attachments were welded together at a machine shop in Bridgeport, CT. By January 2010, J V Precision Machine Co. was machining its first forged bolts, bolt rollers, ejectors and extractor detents for LRB Arms. The bolt was marked: top line - 7790186 bottom line - LRB 11. LRB Arms offered its nitrocarburized gas piston in mid-2012. The nitrocarburizing process was performed by H & M Metal Processing (Akron, OH).

Canadian Manufacture Parts - In 2004 and 2005, Laszlo Klementis, doing business as Rooster33 (Chilliwack, BC), produced a M14 type operating rod spring guide, a M14 bolt lock, and a metric thread combination gas cylinder lock front sight. The bolt lock was marked R33 on the outboard side. The operating rod spring guide was CNC machined from a single piece of AISI 410 stainless steel bar stock. Rooster33 parts were no longer available by early 2006. Magwedge.com brought the Rooster33 design bolt lock back to the Canadian market in 2012 but lacking the R33 marking. By early 2009, Marstar Canada made a stainless steel match grade operating rod spring guide sized for the Chinese operating rod spring (catalog number M14-102). Rauch Tactical first offered its AISI 303 stainless steel CNC machined M14 match grade operating rod spring guide in July 2009. Two months later, Tartan Tactical (Alberta, Canada) came out with its M14 match grade operating rod spring guide. The Tartan Tactical spring guide was made from heat treated and nitride coated AISI 4140 alloy steel. It was no longer available by March 2011. By June 2010, North Eastern Arms offered an operating rod spring guide, a bolt lock and an extra wide magazine latch through Canadian dealers. The fluted spring guide was made from AISI 303 stainless steel. In August 2011, Dask Arms introduced a 4.25 " six o'clock M1913 Picatinny rail which replaced the front sling swivel on USGI style M14 stocks. Magwedge.com sold its match grade operating rod spring guides starting in mid-2012. The spring guides were made of nitrocarburized AISI 4140 alloy steel. There were two versions, round and fluted. In late 2012, The Upgrade Path Inc. for M14.ca offered its fluted operating rod spring guide. It was made from a single piece of AISI 1144

carbon steel and given a black oxide finish. The 3 ounce part was compatible with Chinese and USGI operating rod springs. In mid-2013, Blackrose Tactical (Vancouver, BC) offered a Chinese barrel compatible phosphate coated steel muzzle brake.

Sadlak Industries, LLC – Sadlak Industries, LLC develops, markets, and sells various rifle parts, industrial components and tooling. It is the distribution agent of Sadlak Innovative Design Company. Sadlak Innovative Design Company is a manufacturing job shop and machine design company that was founded in 1989. Mike Sadlak is the President of Sadlak Industries, LLC. He was introduced to the M14 rifle by competition shooter and gunsmith David Ferrante. In 2002, Mike Sadlak asked David Ferrante what parts could be made from a stock of certified titanium on hand. This titanium billet was production contract over run made for Pratt & Whitney. Mr. Ferrante suggested M14 scope mounts and Sadlak Industries agreed. By March 2003, Sadlak Industries was producing high quality steel and titanium scope mounts and an operating rod spring guide for the M14 type rifle.

Sadlak Industries makes National Match operating rod spring guides. Initially, they were made from case hardened AISI 8620 alloy steel but by 2008 the material was AISI 4140 alloy steel. In either case, the spring guide surface hardness is 40 to 45 HRC. All spring guides are kept within 0.002 " straightness. The Sadlak Industries spring guide design is based on the Brookfield Precision Tool part but is an improvement in that it uses a single piece of solid steel stock. In 2003, Sadlak Industries manufactured a single batch of 100 operating rod spring guides with a hollow shaft from two pieces of material.

Sadlak Industries also manufactures National Match gas pistons from AISI 420 stainless steel. This version has a highly polished cylindrical section. The other version is first polished then coated with titanium nitride. Sadlak Industries, LLC consulted a large firm specializing in metal coatings. Mike Sadlak met with the technical experts at this metal coating firm, showed them the M14 gas system parts and explained to them the nature of the application for a coated gas piston. The gas piston moving forward and aft inside the gas cylinder subjects it to heat and abrasiveness. The coating firm analyzed the situation and selected a specific ingredient mixture of titanium nitride for the M14 gas piston. This specific titanium nitride coating is approximately 0.0001 " thick but it results in high anti-galling and anti-seizing properties. The benefit to the M14 type rifle owner is smoother gas system operation and improved gas system service life.

Sadlak Industries can machine the National Match / M21 groove into the gas piston per the USGI part number 9352724 upon customer request. The firm recommends using match grade ammunition for rifles assembled with the National Match groove gas piston. Otherwise, short cycling of the bolt may occur with military surplus or commercial ammunition. Sadlak Industries also offers very slightly oversized gas pistons to fit worn customer supplied gas cylinders. These custom order gas pistons are typically 0.0002 " or two ten-thousandths of an inch wider than the USGI outside diameter specification. The Sadlak Industries 2006 SP3 production lot gas pistons were marked: top line -

SADLAK INDUSTRIES LLC bottom line - COVENTRY CT USA SP3. Sadlak operating rod spring guides and gas pistons are marked SADLAK INDUSTRIES LLC. The U. S. Army 173rd Airborne Brigade equipped twenty-two accurized M14 rifles in the fall of 2004 with Sadlak Industries operating rod spring guides and titanium nitride coated gas pistons.

Sadlak Industries, LLC was testing chromium plated M14 gas cylinders in late 2004 and early 2005 as a means to extend the service life. A very thin layer, 0.0001 " thick, of dense chromium was applied to the interior surface of the gas cylinder. This created a smooth surface less subject to wear. The conclusion of this testing was that it is more affordable to produce custom made oversized gas pistons than to plate the gas cylinder bores.

In July 2007, Sadlak Industries and FFL John Bourguignon of Patriot Armory (NC) collaborated on the design and manufacture of eight heat treated and phosphate coated M14 extended magazine latches. After testing and evaluation by volunteers, the first production lot of 140 Tactical Magazine Release Latches were available in June 2008. The Chinese M14 compatible Tactical Magazine Release Latch went into production in August 2009. The Chinese compatible latch was made to fit the narrower Chinese pin. The firm introduced in November 2008 its post assembly for mounting quick disconnect (QD) bipods to the stock. This item, Model QD-5F, replaced the front sling swivel and bracket.

Sadlak Industries developed and brought to market another style of six o'clock rail mount in August 2010. It was available in four variations, basic, basic with QD post, heavy duty, and heavy duty with QD post. In each case, a 3 " Picatinny rail was mounted under (outboard) the existing USGI stock sling swivel bracket and the sling swivel bracket rivets were removed and replaced with screws. The two basic models used flush head screws and counterbored washers inside the stock channel to secure the sling swivel bracket and the Picatinny rail section to the stock. The heavy duty rail sections were attached to the stock and sling swivel bracket by two hex head cap screws and a threaded backing plate resting inside the stock channel. The rail sections had formed lips on the sides to provide additional rigidity for mounting accessories and a top side channel to allow the stock to drain normally through the factory drain hole. The rails were made from AISI 4140 alloy steel. A limited production run of about 100 tungsten coated alloy titanium heavy duty rail sections were made in August 2012.

Smith Enterprise, Inc. - Smith Enterprise has made or presently does make the following M14 parts: connector locks, flash suppressors, gas cylinders, gas cylinder plugs, gas pistons, gas cylinder locks, hammer pins, trigger pins, spindle valves, muzzle brakes, operating rods, operating rod springs, hammer springs, stock ferrules, extended and standard bolt locks, combination gas cylinder lock front sights and National Match (front and rear) sight parts. Smith Enterprise combination gas cylinder lock front sights, bolt locks, extended bolt locks were made of carburized and hardened AISI 8620 steel. The

standard barrel thread muzzle devices and M1A SOCOM barrel muzzle attachment kit parts were made from either fatigue proof AISI 1144 steel or carburized and hardened AISI 8620 steel. Spindle valves were made from 440 stainless steel and hardened to 58 HRC clear through.

February 2007 saw the first production run of forged gas cylinders by Smith Enterprise, Inc. A total of 200 gas cylinders were made including some with the M80HT treatment. The following month, the firm manufactured 130 gas pistons and another 200 gas cylinders. The gas cylinders were machined from AISI 416 stainless steel forgings. Standard gas cylinder plugs were made of AISI 420 stainless steel. M1A SOCOM kit gas cylinder plugs were machined from 17-4 precipitation hardening stainless steel. The gas cylinder plugs and some gas cylinders were given the proprietary M80HT heat treatment resulting in a surface hardness of 60 HRC to a maximum depth of 0.0002 ". After M80HT heat treatment, the gas cylinders, gas cylinder plugs and gas pistons were cryogenically treated. The AISI 420 stainless steel gas pistons were then plated with thin dense chromium and given a surface finish of 16 microinches. The USGI gas piston major outside diameter dimension was 0.4975 " - 0.0005 ". Finished Smith Enterprise, Inc. gas pistons had a major outside diameter of 0.4975 + 0.0005 ". In 2008, DOD civilian employee Chuck Olson (Fort Benning, GA) found M118LR ammunition average muzzle velocity to be 58 feet per second faster with a Smith Enterprise, Inc. gas system installed on a M14 rifle as compared to a USGI gas system. In January 2012, the Smith Enterprise, Inc. M14 gas piston was further improved by polishing the plated surface to a finish of 9 microinches, holding the internal hole dimensions to within 0.001 " tolerance, and making a full radius cut to form each circumferential groove vice a flat bottom cut. The new design pistons were made from 440 stainless steel. The radius cut grooves allowed easier removal of carbon.

The hammer spring is made from chromium silicon alloy steel of a thinner diameter wire and has 2 ½ more coils as compared to the USGI hammer spring. Smith Enterprise, Inc. also cuts and polishes barrel chambers using Douglas medium weight and heavyweight blanks. Match style and USGI design operating rod spring guides manufactured by Smith Enterprise, Inc. became available in November 2008. These spring guides were M80HT treated. A month later, the firm completed its first production run of 200 operating rods.

Smith Enterprise offers a safe and reliable adjustable M14 firing mechanism to the public. This adjustable firing mechanism is an optional accessory for the M21A5-CIED. A member of the U. S. Army 5th Special Forces Group was testing it in Iraq in 2004 and into 2005. To make this unit, a USGI firing mechanism is modified by adding parts hidden inside the stock. The rifle stock requires only about 1/8 " of inletting to accommodate the adjustable firing mechanism. The trigger pull can be simply and easily adjusted anywhere from 1.75 to 5 pounds. It remains a two stage trigger even at 1.75 pounds pull. The design utilizes two springs and two plungers, one set for the trigger and another set for the sear. This removes any influence of the hammer spring on the trigger pull. An M14 rifle equipped with the Smith Enterprise, Inc. adjustable trigger can be quickly

M14 RIFLE HISTORY AND DEVELOPMENT

restored to a standard firing mechanism in the field.

Smith Enterprise, Inc. part numbers for M14 related items are listed as follows:

- 1000V - M1A SOCOM kit flash hider
- 1018 - MD Labs XF7 weapons lubricant, syringe container
- 1019 - MD Labs XF7 weapons lubricant, tube container
- 1907S - M1907 sling
- 2000V - direct connect flash hider
- 2001 - U. S. Coast Guard muzzle brake
- 2001V - M1A SOCOM muzzle attachment kit
- 2001V-GL - M1A SOCOM combination gas cylinder lock front sight
- 2001V-GL-NY - combination gas cylinder lock front sight for 16 " barrel with no muzzle attachment (formerly part 2001V-GL-C)
- 2002 - dovetail sight base for threaded muzzle attachment
- 2002V - dovetail flash hider
- 2003 - extended bolt lock
- 2004 - National Match front sight
- 2005 - scope mount, Trijicon, Inc. Advanced Combat Optical Gunsight compatible
- 2006 - scope mount, 5.38 "
- 2007 - scope mount, 10 "
- 2008 - scope mount, 7 "
- 2009 - scope mount, PVS-22
- 2010 - bolt lock
- 2011 - combination gas cylinder lock front sight - dovetail for 22 " barrel
- 2012 - combination gas cylinder lock front sight - hooded for 18 " and 22 " barrels
- 2013 - combination gas cylinder lock front sight - dovetail for 18 " barrel
- 2014 - tall strap on cheek rest, black, camouflage, or coyote brown
- 2015 - direct connect Good Iron (formerly California) compensator
- 2017 - combination gas cylinder lock front sight wrench
- 2018 - front sight with tritium post
- 2019 - front sight with tritium dot
- 2021 - strap on cheek rest, black, camouflage, or desert tan
- 2023 - M1907 leather sling
- 2024 - tool kit pouch
- 2025 - M21A5 22 " medium contour molybdenum-chromium alloy steel barrel
- 2027 - M14 18 " standard contour molybdenum-chromium alloy steel barrel
- 2028 - M21A5 22 " standard contour molybdenum-chromium alloy steel barrel
- 2029 - connector lock, S-7 tool steel
- 2030 - gas cylinder shim set, hardened 301 stainless steel
- 2031 - USGI fiberglass stock with cryogenic treatment and M1913 rail
- 2033 - bipod, quick detachable
- 2050 - M21A5 stock tri-rail mount system
- 2052 - cleaning rod guide

- 2055 - standard front sight
- 2060 - pin and spring kit for firing mechanism
- 2061 - National Match rear sight assembly
- 2070 - USGI design gas cylinder
- 2071 - M80HT treated gas cylinder
- 2075 - gas piston, thin dense chromium plated
- 2076 - gas cylinder plug, M80HT treated
- 2077 - operating rod
- 2079 - gas cylinder plug, M1A SOCOM
- 2080 - M14 direct connect sound suppressor (formerly part 0001AK)
- 2080LW - M14 direct connect sound suppressor, lightweight (formerly part 0002AK)
- 2087 - M21A5 C-IED Max-Pak trigger upgrade
- 2088 - M21A5 C-IED mid-range trigger upgrade
- 3005 - suppressor carrier (made with an interior flap and longer sleeve as of 2011)

Springfield Armory, Inc. - Springfield Armory, Inc. began making parts in the late 1970s as the supply of USGI M14 parts became limited. Commercial reproduction trigger housings marked 7267030-G were installed in M1A rifles as early as April 1978 and as late as May 1984. Standard model M1A serial number 007041 left the factory in 1977 with a commercial manufacture barrel and a commercial manufacture operating rod. In the 1980s, some M1A rifles were assembled with commercial cast rear sight bases marked SA 554600 on the bottom. Some Springfield Armory, Inc. non-hooded rear sight apertures were marked N M outboard of the peep hole. A bolt lock with a number cast into it is a reproduction part. The connector assembly forward end top guide rib was milled about 0.030 " to fit select fire M1A receivers.

A National Match model M1A produced in 1978, serial number 00909X, was assembled with a commercial bolt at the factory. This particular bolt has no markings except for the letter N on the rear end. These cast bolts are referred to as the "lettered series" bolts. A standard model M1A with serial number 0093XX left the factory in early 1979 with a commercial non-plated standard contour barrel, commercial operating rod and commercial bolt. M1A serial number 010047 was assembled in 1979 at the factory with a "lettered series" M1A bolt, reproduction ejector and M1 Rifle ejector spring. The "lettered series" cast bolt on M1A serial number 010047 was tested for cracks and hardness by an Ohio National Guard armorer. No cracks were found by magnetic particle inspection. The bolt hardness was 55 HRC. However, the bolt firing pin hole was larger than required by the USGI drawing. By April 1979, Springfield Armory, Inc. had changed to "numbered series" reproduction bolts in M1A rifles.

From 1978 to 1986 Springfield Armory, Inc. was short on USGI M14 barrels so it installed non-plated standard contour barrels. The standard contour barrel blanks were supplied by Wilson Arms. Springfield Armory, Inc. M1A medium weight stainless steel National Match barrels are marked NM 308-SS. The medium weight molybdenum-chromium alloy National Match barrels are marked NM 308. In the 1980s, Super Match M1A barrels

were marked S. M. The match grade marking is located between the gas cylinder and the flash suppressor. Douglas Barrels, Inc. supplied the stainless steel blanks for standard loaded model M1A barrels.

Springfield Armory, Inc. commercial reproduction operating rods are made from two pieces of steel welded together as was done by Springfield Armory, Winchester and Harrington & Richardson. Match rear sight bases marked NM/2A on the right hand side and NM/2A and SA 7791571 on the bottom were manufactured by Wayne Machine, Inc. for Springfield Armory, Inc. The company offered an adjustable firing mechanism for sale. The trigger pull could be adjusted from 1 ½ to 4 ½ pounds by using an adjustment screw not visible from outside the stock. It was designed by Dale Rader. Mr. Rader was head of the Match Shop at Springfield Armory, Inc. from July 2000 to January 2009.

Springfield Armory, Inc. M1A rifles built from the mid-1980s to 1994 *tend* to be built with a majority of USGI parts. For example, M1A serial number 081004 (assembled in 1994) was built at the factory with the following parts: TRW trigger housing, HR-N hammer, TRW bolt, Winchester barrel, and WCE USGI rear sight elevation and windage knobs. There are USGI parts on M1A rifles built from the mid-1990s until the present day but they are the exception rather than the rule, especially from 2002 onward.

Troy Industries, Inc. – In 2005, Troy Industries offered an extended magazine release and a bolt lock for the M14 type rifle. These parts were machined from steel bar stock and finished with manganese phosphate coating. The extended magazine release was similar to the USGI part with smooth rounded edges but was a little longer and wider with a convex surface facing the trigger guard. These parts, catalog numbers M14EMR and M14CBR, are no longer available.

W. C. Wolff Company - Walt Wolff, Sr., a U. S. Army veteran of World War II, established his gunsmithing business in 1951. He found it difficult to find replacement springs for the firearms he was asked to repair. After a time, he bought a small hand-operated machine to make his own coil springs for firearms. Other gunsmiths found out about this source of gun springs. Soon, the W. C. Wolff Company (Newtown Square, PA) was advertising in industry periodicals and filling direct mail orders. By the late 1950s, Brownells, Inc. became the first distributor of Wolff springs. Later, Mr. Wolff invented extra power and reduced power springs. In the late 1970s, he introduced the variable power recoil spring for M1911 type pistols. Today, W. C. Wolff Company produces quality M14 type rifle ejector springs, extractor springs, hammer springs, ten and twenty round magazine springs, and operating rod springs. Wolff springs are all made from the same proprietary material.

Wayne Machine Inc. – Wayne Machine Inc. of Taipei, Taiwan was established in 1979 and moved to its present location in May 1994. It manufactures ordnance components, combat vehicle parts and military and commercial firearms parts. Wayne Machine Inc. exports 90 % of its production to the United States, United Kingdom, and other countries.

It lists the Taiwan Army as one of its customer references. Since the mid-1980s, Wayne Machine Inc. has made and supplied reproduction M14 parts to Century Arms International, Numrich Gun Parts Corporation, Sarco, Inc., and Springfield Armory, Inc.

In 1996 or 1997, Numrich Gun Parts Corporation received a shipment of cast reproduction operating rods from Taiwan. They had Winchester markings. Apparently, Wayne Machine Inc. had been sent a Winchester M14 operating rod as a sample. Most commercial M14 type rifle parts are cast. The April 2004 M14 products list of Wayne Machine Inc. includes the gas cylinder, flash suppressor, M14E2 muzzle stabilizer, front sight, rear sight parts, hand guard assembly, and firing mechanism parts but not the bolt or operating rod. Commercial manufacture M14 bolts have been cast, machined from bar stock and forged. These reproduction parts usually function in a satisfactory manner when fitted and assembled correctly.

Republic of Korea - Shinsung Industrial Co. (Jeollabuk-do, Korea) manufactured trigger housings, safeties, hammers, triggers, trigger guards, extractors, firing pins and at least some of the forged M1A bolts, e.g., lot code F00086. The company began producing M1A operating rods beginning in the winter of 2008. The operating rod was machined from a single piece forging on CNC equipment. Gloria Material Technology Corporation (Hsin-Ying, Taiwan) supplied the raw material, SNCM439 alloy steel. SNCM439 steel is equivalent to AISI 4340 alloy steel. These operating rods were first imported into the United States beginning in March 2008 by Red, White and Blue, LLC (Springfield, VA). Most of the RWB imported operating rods were marked 7267064 and 18242. Two Arizona laboratories, Controlled Thermal Technology, Inc. and Metals Engineering & Testing Laboratories, tested sample Shinsung operating rods in April 2008 for hardness. The results varied from 42 to 44 HRC. A very few of the imported operating rods were marked, upside down, 7267064 TRW. As of January 2010, Shinsung Industries Co. (Daly City, CA) was importing the Shinsung Industrial Co. operating rod. Operating rods imported by Shinsung Industries Co. were only marked 7267064. Dlask Arms Corporation marketed the Shinsung operating rod in Canada beginning in January 2009. Dasan Machineries Co., Ltd. (Jeollabuk-do, Korea) has manufactured the following parts: lugless flash suppressors, gas cylinder, gas cylinder plug, M1A SOCOM combination gas cylinder lock front sight, windage knob, and muzzle brakes for the M1A Scout Squad, M1A SOCOM and M25. In 2004, DPMS, Inc. (St. Cloud, MN) sold a high quality lugged flash suppressor manufactured in the Republic of Korea. Further importation of lugged flash suppressors has been blocked by U. S. Customs & Border Protection.

Other Commercial Parts Suppliers - Gerald Drasen, who did business as Nesard and Sendra (Chicago, IL), went into the firearms parts business no later than 1963 selling M1 Garand rifle and M1911 pistol parts. He produced reproduction M14 items such as the flash suppressor nut wrench, bolt assembly tool, front band, gas cylinder, magazine latch, rear sight cover, safety and trigger housing in the 1980s. His business continued to sell reproduction M14 items until at least 2002. Brookfield Precision Tool made match grade operating rod spring guides and titanium-nitride coated gas pistons from 1988 to 1996.

Ron Gale manufactured his custom design National Match operating rod spring guides in the 1990s. His operating rod spring guide was marked R. GALE RGL-42 on one side of the shaft and NM on the other side. Juggernaut Tactical, Inc. has produced a California compliant magazine lock, also known as a "bullet button, from billet steel."

In 2005, F A Enterprises made a M14 flash suppressor nut from AISI 1018 carbon steel. It was given a blued finish. Superior Shooting Systems, Inc. (Canadian, TX) M14 chromium silicon alloy steel operating rod springs and hammer springs were rated for 500,000 cycles. Arrowhead Industries (Afton, MI) manufactured M14 gas pistons from AISI 420 stainless steel and M14 gas cylinder plugs from AISI 416 stainless steel. Arrowhead Industries M14 gas pistons and gas cylinder plugs were only sold to its distributors, e.g., Sherluk (Delta, OH). The Amherst Depot (Englewood, FL) sold reproduction M14 parts including safeties, hammers and rear sight apertures.

Fulton Armory offered commercial manufacture extractors milled from bar stock. Fulton Armory brought its first generation forged bolt to market in November 2009. The bolts were machined by SSI Manufacturing Technologies Corporation and marked as follows: top line - 7790186 middle line - FA A00 bottom line - BNU. Fulton Armory M14 bolt heat treatment specifications are 44 to 48 HRC surface hardness to a case depth of 0.012 " to 0.018 " and 35 to 40 HRC core hardness. The second generation bolts, introduced in December 2011, met USGI drawing heat treatment requirements and were marked HT04 below BNU.

In May 2009, Thrustline Manufacturing, Inc. (Ogden, UT) made available its M14 operating rod. It was marked: top line - 7267064 bottom line - 4JNK8. In 2010, Krieger Barrels, Inc. produced National Match rear sight aperture assemblies in both sizes, 0.0520 " and 0.0595 ". ProMag Industries brought its extended magazine latch to market in mid-2011. This part was made from a casting (product code PM236). Safeties stamped with WCS inside a circle were made by Windy City Sourcing, Inc. (Wood Dale, IL). In late 2012, Warbirds Custom Guns first offered its DTA muzzle adapter. It was machined from AISI 4140 alloy steel then heat treated and given a phosphate coating. The DTA adapter threaded directly to a M14 barrel. Any 5/8 " x 24 threaded device could be attached to the front end. This American made DTA muzzle adapter had a dovetail sight base sized for USGI or National Match dimension front sights. In 2013, AMS Machine made a 6061 alloy aluminum 3 1/2 " long M1913 Picatinny six o'clock rail with a black anodized finish (part number A-3025). It was secured to the stock with screws and washers using the existing front sling swivel holes. James River Armory first marketed its forged M14 bolt in November 2013. Its bolts were made from AISI 8620 alloy steel and heat treated to the USGI drawing requirements. It was marked on the top side as follows: first line - 7790186 second line - ROCK-OLA third line BULA FORGE fourth line - & MACHINE fifth line - A2.

In mid-2009, 7.62mm Firearms began manufacturing USGI design M14 parts. Its gas cylinders were made from AISI 416 stainless steel. The following parts were milled from

bar stock: safety, spindle valve, cartridge clip guide, operating rod guide and sear. The operating rod spring guide was laser cut. The gas cylinder plugs were machined on a Swiss CNC screw machine. The gas pistons were machined from AISI 416 stainless steel castings or forgings with optional black oxide and titanium nitride coatings. Hammers were machined from AISI 8620 castings and marked 7.62MM USA on the bottom side. Safeties were marked 7.62 inside a diamond. Trigger housings were cast or milled and marked as follows: top line - 7267030 middle line - 762mm third line - USA. Gas cylinder locks, hammers, and trigger housings were available in phosphate or black oxide finish. By March 2010, the company was manufacturing ejectors, ejector springs, extractor springs, extractor plungers and milled extractors. New bolts with rollers were available in September 2010. The bolts were marked on the rear end of the top surface with 7790186 above the company logo. Later, the firm made operating rods from forgings. The firm has made the following parts: standard and National Match rear and front sights, connector lock, complete bolt assembly, front band, flash suppressor nut, complete firing mechanism, cartridge clip guide, operating rod spring guide, flash suppressor, bolt lock, operating rod, and complete gas system. All M14 parts sold by 7.62mm Firearms were machined, heat treated, and finished within a fifty-one mile radius of Medina, OH. The steel was supplied by a local mill. The parts were backed by a lifetime guarantee.

Notes on Chinese Parts

USGI and commercial manufacture parts are theoretically interchangeable but occasionally the fit is too tight or too loose between each other. Generally, USGI and commercially manufactured parts are interchangeable with their Chinese counterparts but there are some exceptions. When the select fire Chinese M14 rifles were assembled in the 1960s, the last five or six digits of the receiver were electropenciled on the associated bolt, operating rod and trigger housing and stamped on the flash suppressor. Chinese bolts made in 2011 were stamped with a four digit number on the bottom side, e.g., 1223.

Chinese barrels have metric dimension barrel shank, gas cylinder lock and suppressor nut threads. However, the Chinese barrel shank thread size is very close to the American made receiver barrel ring thread size. Chinese M14 barrels will usually, but not always, thread into an American made M14 type receiver without any trouble. Nonetheless, barrel installation and headspacing should be performed by a reputable M14 gunsmith. A USGI gas cylinder lock will not fit on a Chinese barrel because of the differing thread sizes. Similarly, the Chinese gas cylinder lock will not fit on a USGI or U. S. commercial manufacture M14 type barrel. Introduced in 2010, gunsmith Barry Jensen, owner of Bits of Pieces (Delta, BC), manufactured a combination gas cylinder lock front sight for Chinese M14 barrels. Rooster33 and Dlask Arms made their own as well. The Chinese flash suppressor nut will go on a USGI barrel without resisting but at a slightly downward angle due to the slight difference in threads. The USGI and Chinese flash suppressor nuts are interchangeable on the Chinese barrel. Chinese flash suppressors are made from castings. Chinese hand guards are not painted silver on the bottom side.

Bolt - For unknown reasons, the Chinese did not use equivalent AISI 8620 alloy steel for their bolts as specified per the USGI drawing but elected to make them out of equivalent AISI 4135 alloy steel. Chinese bolts have austenite and ferrite grain structures with surface hardness varying from 33 to 47 HRC. With thousands of firing cycles, the contact points willpeen. If the bolts are heat treated to improve hardness, the hardness increases all the way through the bolt instead of just at the surface. Hardening a Chinese bolt will add a little more service life to the item. In the long term, however, hardening a Chinese bolt is still not desirable. This is because increasing the core hardness of the bolt decreases the core toughness.

Another significant problem plagues Chinese bolts imported into the United States. Besides not being made of a material suitable for long term use, the locking lugs are too narrow. Thus, American and Chinese bolts are not interchangeable except in very rare instances. The owner of a Chinese M14 rifle with a Chinese bolt should not expect a USGI bolt to drop in to the Chinese receiver. Even if a USGI bolt does fit the Chinese receiver, it may headspace less than the safe minimum, 1.630 ", or it may headspace longer than the SAAMI maximum, 1.634 ". Converting a U. S. imported Chinese M14 type rifle to accept an American made bolt should be performed by an experienced M14 gunsmith. These problems may or may not continue to affect Chinese M14 bolts which were more recently exported. For example, three Norinco M305 rifle bolts shipped to Canada in 2003 were tested for surface hardness. The results ranged from a minimum of 45 HRC to 48.5 HRC, with the average at 47 HRC. More detailed information on the bolt material or the core hardness of these 2003 vintage bolts is presently unavailable. Chinese ejector springs tend to run about 1/16 " longer than USGI ejector springs.

Firing Mechanism - The machining of Chinese firing mechanism parts is comparable to USGI firing mechanisms. The Chinese trigger guard is made with the bent tab stop similar to the late version USGI trigger guard. Chinese hammers and triggers are sometimes a little soft, but this can be corrected with appropriate nitrocarburizing treatment. The pin sizes and locations in the Chinese unit are the same as the USGI original. Occasionally, a Chinese hammer pin or trigger pin may be too soft or machined slightly too narrow. The Chinese magazine latch pin is 4 mm diameter, slightly thinner than the USGI pin.

Gas System - Chinese gas cylinders and gas cylinder plugs are made of molybdenum-chromium alloy steel and gas pistons are chromium plated. Chinese and American gas cylinder plugs are not interchangeable. The Chinese gas cylinder plug has 25.4 threads per inch and the USGI gas cylinder plug has 40 threads per inch. The Chinese gas piston outside diameter and the gas cylinder inside diameter are slightly larger than USGI gas piston and gas cylinder drawing specifications. A USGI gas piston may be too narrow to function properly inside a Chinese gas cylinder. The inside diameter of a Chinese operating rod spring is about 0.010 " smaller than a USGI spring. Some National Match operating rod spring guides will not fit inside Chinese operating rod springs because the interior diameter is too small.

Operating Rod - Three kinds of operating rods have been identified on Chinese semi-automatic M14 type rifles. One kind has no notch at all for the connector assembly. Since this version cannot be used with a connector assembly, it is likely post-1978 production. Another has an almost straight angle cut to the notch, which does not closely match the USGI connector's contours. These operating rods have numbers engraved on them. The notch *may* have been machined away after original manufacture. The third type of Chinese operating rod has a connector notch very similar to the USGI model, but with a slightly more circular shape. The third type was made in 1965 as part of the production of 100,000 complete rifles. In all other important dimensions, the three types of Chinese operating rods are the same. Chinese operating rods are forged and are as hard as USGI Harrington & Richardson operating rods.

Rear Sight Assembly - Chinese and American rear sight knobs and bases are not interchangeable because the Chinese sight parts have about 36 threads per inch versus 32 threads per inch for the standard USGI rear sight parts. However, a complete Chinese manufacture rear sight assembly will fit on an American made receiver and vice versa. The Chinese rear sight base is a casting.

Stock Assembly - Chinese connector locks were standard length in 1965 production M14 rifles but shortened to sit flush with the receiver in post-1978 production rifles. USGI stocks require some filler material to prevent lateral drift of the shortened Chinese connector lock. Chinese butt plates and butt plate flappers are both made of steel. The butt plate is a casting. The flapper-to-butt plate joint is built up by welding then ground flat. Two types of Chinese M14 butt plate flappers have been observed: Type 1) the flapper has two raised indentations on the right side of the hinge and Type 2) the flapper has one hole on the left side of the hinge as the muzzle is pointed down range. Chinese M14 firing pins have a phosphate coating. Chinese flash suppressors are castings. The bolts and operating rods of Chinese M14 rifles imported in May 2006 into Canada have etched numbers on the bolts and trigger housings and W C E is marked on the elevation knobs.

Commercial Parts Identification

Barrels - Springfield Armory, Inc. in Illinois marked its USGI and commercial manufacture barrels SPRINGFIELD INC. GENESEO IL or GENESEO ILL or GENESO, IL 308. This marking is typically found on the barrel chamber. Chromium plated standard contour barrels supplied by Criterion Barrels, Inc. to Fulton Armory are stamped C.B.F.A. 7790190 followed by the month and year of manufacture. A 2004 production Wilson Arms chromium plated standard contour barrel sold by LRB Arms had the following markings: LRB 7790190 5/04 WA. Smith Enterprise, Inc. installed a Douglas 1:10 twist four groove heavyweight barrel on a M1A rifle in January 2003. The barrel was stamped with the following markings from top to bottom: first line - 1 10 308 WIN 1 03 second line - 4 35T SEI. At the bottom of the barrel at the rear end just forward of the operating rod spring guide slot it was marked 1.

Bolt - Springfield Armory, Inc. M1A bolts are typically marked 7790186-SA on the first line and A00030, B00048 or F00059 or similar number on the second line. They may have markings such as D and M3 on the rear end and A9 or B1 on the bottom surface. The letter A prefix for the number under 7790186-SA means the bolt was cast then finish machined. Letter A prefix numbered bolts were used in the assembly of M1A rifles from early 2002 to late 2005. The letter B prefix for the number under 7790186-SA means the bolt was machined from bar stock. The B prefix numbered bolts were used in M1A rifles built between late 2001 and early 2002. The letter F prefix for the number under 7790186-SA means the bolt is forged. Springfield Armory, Inc. began installing F prefix M1A bolts by no later than 2000.

See 1987 Springfield Armory, Inc. Recall Notice for additional M1A bolt markings. No M1A parts, including bolts, are made by metal injection molding. Around receiver serial number 165XXX, Springfield Armory, Inc. commercial manufacture factory installed bolts have letters and numerals with a taller and thinner font than the style found on USGI M14 bolts. A Springfield Armory, Inc. M1A bolt not subject to recall was tested for surface hardness. The result was 52 HRC, the same as a USGI HRT marked M14 bolt.

Gas System - Some Smith Enterprise, Inc. gas cylinders were electropenciled with the marking 3A5E1 S.E.I. LRB Arms gas cylinders were marked 12182 until late 2009. This number stands for L (twelfth letter of the alphabet) R (eighteenth letter of the alphabet) B (second letter of the alphabet). Starting in 2010, 12182 was left off the gas cylinder forging. Spindle valves with a round head are commercial manufacture.

Sadlak Industries, LLC titanium nitride coated gas pistons have a gold color. The National Match version will have a longitudinal groove at the top center of the major diameter. Springfield Armory, Inc. commercial manufacture gas pistons typically exhibit visible turning and milling marks on the tail section. USGI M14 gas pistons have a smooth, polished appearance on all surfaces. The Smith Enterprise, Inc. M21A5 gas piston is completely chromium plated. The minor diameter has a slight frosty appearance. Gas pistons made in the People's Republic of China are chromium plated on the cylindrical portion and machined with a finned texture on the tail section. Brookfield Precision Tool XM25 Revision 1 and Revision 2 gas pistons can be easily identified by the marking BKFLD PREC TL on the flat surface of the minor diameter. The Revision 1 piston gas port had a smaller diameter than the USGI drawing specification. The Revision 2 piston gas port diameter was the same as the USGI requirement. Both Brookfield Precision Tool pistons have titanium nitride coating only on the major diameter.

Operating Rod - Springfield Armory, Inc. M1A operating rods have been manufactured in the United States of America and in the Republic of Korea. The handle portion from the saddle rearward is made from an investment casting. The cylindrical portion of the operating rod is cold rolled. An Illinois machine shop is subcontracted to machine the bolt roller cam slot. The welding of the two pieces together, the deep hole drilling of the cylindrical portion and the finish machining are performed in-house. Every M1A operating

rod is heat treated and phosphate coated.

On Springfield Armory, Inc. operating rods, look for either: 1) 7267064 on the first line and SA centered below it or together in one line 2) 7267064-2 on the first line and SA centered below it. The first example is the earlier of the two markings. Springfield Armory, Inc. operating rods with the early marking, no -2, will not have a notch under the handle like USGI operating rods. By no later than 1993, the notch under the handle was added to its operating rods, e.g., M1A-A1 serial number 0748XX. For clarity, U. S. government Springfield Armory operating rods are marked 7267064 SA all on one line and are machined with the notch under the handle but may or may not have the forward end vent hole.

A rear sight base marked NM/2A with no other markings may be a commercial reproduction. For commercial Springfield Armory, Inc. trigger housings, look for part numbers 7267030-G, 7267030-H, 7267030-I or 7267030-S. Springfield Armory, Inc. hammers may be unmarked or marked on the side: top line - 5546008-2 bottom line - SA.

USGI Magazines

The M14 magazine design was finalized by John C. Garand in the first five months of 1954 while he was a consultant to Mathewson Tool Company on the T44E4 rifle contract. The M14 magazine design was borrowed from Garand's T31 rifle project. The T31 (and M14) magazine design requires very low cartridge stripping forces. Rochester Manufacturing Company, Inc. (Rochester, NY) developed the welding procedure for the M14 magazine parts.

Springfield Armory, government contractors and commercial magazine manufacturers have at one time or another produced five, ten, fifteen, twenty, twenty-five and thirty round magazines for the M14 type rifle. The five, fifteen, twenty-five and thirty round magazines are commercially manufactured but not marked with any manufacturer's initials. The Springfield Armory, Inc. M1A description in the 1987 *Shooter's Bible* lists magazine capacity as five, ten, twenty, and twenty-five rounds.

A seven round magazine was produced by the U. S. Army MTU for use with the XM21 in Viet Nam. The XM21 seven round magazine was small enough to allow the sniper to assume a lower position with the rifle yet long enough to allow the magazine to be removed quickly. The U.S. Department of Defense contracted with several companies to supply five, ten and twenty round M14 magazines. For example, Check-Mate Industries, Inc. made ten round magazines about 1990 for the U. S. Army Marksmanship Unit. The five round M14 magazines were made by Check-Mate Industries but supplied by Springfield Armory, Inc. to the U. S. Department of Defense. The U. S. Marine Corps used both ten and twenty round magazines in the M14 DMR. For comparison purposes, the approximate length of the magazine tube (body) rear side for the various sizes are: five round - 2.25 ", seven round - 2.58 ", ten round - 3.44 " and twenty round - 5.75 ".

Usually, the U. S. government contractor manufacturer initials were marked on the rear side of USGI M14 magazines. Quantico Arms & Tactical Supply, Inc. purchased a batch of 12,000 New-In-Wrap USGI twenty round M14 magazines in 2004. Quantico Arms found that about 20 % of these magazines either had no manufacturer marking or the initials were very faint. At least at some point, the manufacturer's marking on the magazine body became required per USGI drawing F7790181. USGI Borg-Warner magazines have been unmarked straight from packaging dated as early as January 1963.

The following manufacturer initials have been observed on magazine follower stops: BW and B-W (Borg-Warner), CTX (unknown) and OM (Winchester). The manufacturer's marking on the magazine follower is optional per USGI drawing B7267085. If a USGI magazine follower has spot welds on the flat portion of the stop, there will be three evenly spaced weld "dimples" or "buttons." BRW S-I and OM magazines were assembled with BW and OM marked followers, respectively, in 1962.

Be aware that some commercial reproduction M14 magazines have USGI contractor style markings on the rear side and the packaging has been expertly copied. Such "GI" style reproduction magazines may not charge and reliably feed twenty cartridges. The magazine body thickness of these magazines may be thinner than genuine USGI units. A genuine USGI M14 magazine will hold and reliably feed twenty cartridges then activate the bolt lock as required by the USGI drawing D7790183.

The savvy collector can identify genuine USGI and Taiwanese government manufacture M14 magazine bodies. Examine the spot welds on the front side of a known USGI or Taiwanese twenty round magazine. Make notes on the size, number, alignment and location of the spot welds. Note that some KMT marked magazines differ from the typical pattern of USGI magazine body spot welds. The USGI drawing F7790181 requires twelve evenly spaced spot welds up the center of the front side and one spot weld just to the right of the operating rod spring guide hole as the magazine stands up. Use this information when examining M14 magazines for sale.

Drawing D7790197 allows for the latch plate to be attached to the magazine body by two, four, five or six welds. USGI M14 magazine latch plate weld dimple patterns were consistently the same pattern according to manufacturer. The following latch plate dimple patterns have been consistent for genuine USGI magazines:

two dimples with a horizontal line immediately above the bottom pair - CMI

four dimples - W, bar W, HR-R, bar R

five dimples with the fifth centered - Atwood Vacuum Machine, UHC

five dimples with the fifth placed towards the top pair - BRW S-I, BRW B2

five dimples with the fifth placed towards the bottom pair - BRW B2, OM, OM over a dot

six dimples - A, KMT

six dimples with a horizontal line immediately above the bottom pair - CMI

The USGI drawing D7790197 (magazine body assembly) does not specify a manufacturer's marking but drawing F7790181 (magazine tube) does. USGI magazine springs were coated with lubricating oil before packaging. Beginning in January 2007, Check-Mate Industries ten and twenty round magazines made for commercial sales were marked C.M.I. on the rear side of the magazine tube. Before 2007, some ten round magazines were marked and some were not. Check-Mate Industries five round magazines remained unmarked.

USGI magazine contractors included Apex Metal Stamping Co., Atwood Vacuum Machine Co., Borg-Warner, Brunswick Sports Products, Check-Mate Industries, Killeen Machine & Tool, Olin-Mathieson Chemical (Winchester), Rochester Manufacturing, Springfield Armory, TRW, Union Hardware & Metal Company and Westinghouse Electric. Check-Mate Industries made twenty round M14 magazines for 1989, 1996, 2004, 2005 and 2009 U. S. Army contracts. The 2005 contract was for a guaranteed minimum of 25,000 and up to a possible maximum of 360,000 twenty round magazines. Check-Mate Industries marked some of its ten round magazines C.M.I. on the rear side of the body (tube). The USGI magazines are generally regarded as the best made.

Magazine body (tube) wall thickness can vary from 0.028 " to 0.041 " as observed among USGI, Chinese, Taiwanese and U. S. commercial manufacture M14 magazines. The specification per USGI drawing F7790181 for the body (tube) thickness is 0.0310 " + or - 0.0015 ". If a magazine body is too thick, e.g., 0.041 ", it may fail to lock the bolt open after the last round is fired.

Note that assembly of a complete twenty round M14 magazine from spare parts may be a violation of applicable local or state law in the United States, or may violate Canadian law. Possession, manufacturing, importation, sales or transfer of centerfire rifle ammunition magazines capable of holding more than five rounds may be prohibited or restricted in U. S. cities and states. Under present Canadian law, magazines for the M14 type rifle and other centerfire long guns are pinned to limit the capacity to five cartridges. Consult state and local laws before purchasing or accepting any firearm magazine.

M14 magazine replacement parts have been available in the civilian market since about 1989 from Sarco, Inc. Replacement M14 magazine springs should be inspected for signs of any defects and for proper dimensions. Genuine T44E4 and twenty round M14 magazine springs have eight coils. The replacement magazine followers should have three neat and evenly spaced spot welds attaching the stop to the follower. USGI M1 magazine followers are heat treated to file hard. Consequently, do not bend the rear tab on USGI M14 magazine followers any appreciable distance as they will snap off. If the rear tab is bent significantly and it does not snap off, it is likely a commercial reproduction part.

USGI M14 magazines have been modified to fit other rifles such as the Armalite, Inc. AR-10, IMI Galil .308 caliber AR, ARM and SAR models and modified M1 Garand rifles.

During the ten years of the Assault Weapons Ban, M14 magazines modified for use in the AR-10 were required to still function in the M14 type rifle to remain compliant with the law. Since the sunset of the ban, new manufacture AR-10 magazines are being made by Check-Mate Industries for Armalite. After 2004, a modified M14 magazine is known as a Generation I AR-10 magazine and the post-'04 manufacture units are referred to as Generation II magazines. A Generation II AR-10 magazine will not function in a M14 type rifle. For a time, Marc Krebs of Krebs Custom, Inc. (Wauconda, IL) modified Russian made Molot brand .308 caliber RPK style rifles to accept unmodified USGI M14 magazines.

The Australian International Arms 7.62 x 51 mm caliber bolt action M10 series rifles use a magazine identical to the ten round M14 magazine but for three differences. The follower is chromium plated, the latch plate has an angled bottom edge, and it lacks the front side magazine catch slot. The latch plate angled bottom edge is detailed as an alternative design on USGI drawing D7790197. These rifles were briefly imported in 2003 and 2004 into the United States by Tristar Sporting Arms, Ltd. (North Kansas City, MO). Tristar Sporting Arms specializes in shotguns for women shooters. It was established in 1994 by Marty Fajen, former Vice President at Reinhart Fajen, Inc. and daughter-in-law of the late stockmaker. Marstar Canada imported AIA M10 rifles into Canada from 2005 onward.

Foreign Manufacture Magazines

Taiwan and People's Republic of China also produced twenty round magazines that were imported from the late 1980s until 1994. Some Chinese twenty round magazines were blocked to five rounds capacity by welding a metal block under the follower following the 1989 import ban. Such magazines were included in the shipping boxes for Chinese M14 rifles imported by Century Arms International and IDE USA. While Chinese magazines are narrower than the USGI magazines, they have an excellent reputation for reliability. Chinese magazines imported into the United States in the 1980s and 1990s were coated with grease. Chinese magazines imported into Canada after 2000 were preserved with oil and packed in heat-sealed transparent plastic bags. In 2013, Luxembourg Defence Technologies imported a batch of Chinese twenty round magazines into Luxembourg. They were wrapped in plastic coated brown paper. Canadian plastic twenty round magazines have been imported into the United States. These magazines have a good reputation but may require a small amount of plastic to be removed from the locking tab to feed reliably. Korean M14 twenty round magazines hit the U. S. market in May 2009. These are identified by the marking HNR on the floor plate. In the fall of 2011, BTP Arms offered a commercial twenty round magazine with PTFE coated body, follower, and floor plate (catalog number T-0003). Reportedly, this coated magazine was being manufactured in Taiwan.

U. S. Commercial Magazines

Aftermarket magazines often fail to function reliably because of their thinner body sheet metal, weak springs and flashing on their plastic followers. U. S. aftermarket brand twenty and thirty round magazines were produced before September 13, 1994 by companies such as Triple K Manufacturing Company (San Diego, CA) and U.S.A. Magazines, Inc. (1992 mailing address in Downey, CA). U.S.A. Magazines, Inc. made blued twenty and thirty round magazines. As of October 1994, U.S.A. Magazines, Inc. was located at 13050 Florence Avenue Santa Fe Springs, CA but appears to have gone out of business by August 2001.

Herman and Leo Krasne established the San Diego department store, Krasne's Incorporated, in 1946. Triple K Manufacturing Company was founded in 1963 by Jerry Krasne, son of Leo Krasne and grandson of Herman Krasne. Triple K is a division of Krasne, Inc. and remains a family owned business. Triple K stands for Kim, Kurt, and Karen, the three children of Jerry Krasne. Triple K manufactures leather goods for firearms carry and rifle and pistol magazines. The Triple K company produced blued finish five, ten, twenty and thirty round magazines for the M14. The catalog numbers were 572M, 567M, 1018M and 1995M, respectively.

A nylon resin twenty round M14 magazine was developed in 1977, patented in 1979 and manufactured by D. & D. Inc. (Wilson, NC). The magazine body is marked as follows on the right hand side adjacent to the floor plate: top line - THERMOLD second line - D.& D. INC. third line - WILSON, N.C. bottom line - U.S.A. The magazine floor plate is marked on the bottom as follows: PAT NO 4139959. A thirty round model was distributed by Toblas Guns (Albemarle, NC) in 1989. A nylon resin five round magazine charger was also manufactured. The charger is identified is marked as follows: left hand side - PAT. NO. 4,538,371 right hand side - THERMOLD D. & D. INC. WILSON N.C. U.S.A.

Springfield Armory, Inc. sold twenty round M14 magazines blocked to five or ten rounds at least during the period 1976 to 1980. The sporterized five round magazine which sits flush with the stock was first offered in 1980.

After the Assault Weapon Ban sunset in 2004, ProMag Industries manufactured twenty round magazines (product number M1A-A1). The ProMag Industries magazines had blued finish carbon steel bodies, chromium silicon alloy steel springs and polymer floor plates and followers. Likewise, 9.14 Magazine and National Magazines also made M14 magazines after 2004. 9.14 Magazine made phosphate coated five, ten and twenty round models. National made five, ten, twenty, twenty-five and thirty round units in either blued or phosphate finish.

Check-Mate Industries has manufactured ten, fifteen, and twenty round magazines for Springfield Armory, Inc. Until mid-2006, twenty round magazines produced for the commercial market had no manufacturer markings. Beginning that summer, the

company logo was often stamped on the twenty round magazine floor plate exterior. The Armalite, Inc. company logo was stamped on a run of twenty round magazines in the summer of 2006. Starting in January 2007, Check-Mate Industries stamped its retail sale twenty round magazines C.M.I. on the rear side. As of February 2008, the crossed cannons logo of Springfield Armory, Inc. appears on the rear side of twenty round magazines manufactured for Springfield Armory, Inc. The same logo appears on fifteen round magazines as of March 2009. Until 2009, Springfield Armory, Inc. M1A fifteen round magazines used a twenty round body with a wood block under the follower to prevent loading more than fifteen rounds. By March 2009, the magazine body was sized perfectly for fifteen cartridges. Three months later, Check-Mate Industries introduced polished stainless steel twenty round M14 magazines to the commercial market. The stainless steel magazines were assembled with PTFE coated steel followers and marked C.M.I. on the rear side and the floor plate was stamped with the company logo.

In October 2007, Check-Mate Industries made available through a distributor, 44Mag Distributing, its twenty-five round M14 magazine. The extra five rounds of capacity added about 1.25 " in length over the standard twenty round model. This magazine was marked C.M.I. on the rear side and had the Check-Mate logo stamped on the bottom of the floor plate. The spring for the Check-Mate twenty-five round magazine had eight coils and was interchangeable with the twenty round magazine. By May 2009, a nine coil spring was used in the assembly of twenty-five round magazines.

Viking Tool and Machine made a small batch (less than ninety) of seventy-two round M14 magazines before the 1994 Assault Weapons ban on new "large capacity" magazines. This conversion consists of cutting then screwing an MG-15 saddle drum to a Viking magazine tower. These M14 type drum magazines have been used at the legendary Knob Creek Machine Gun Shoot held every April and October in West Point, KY. These magazines commanded a premium price during the ten years the 1994 Assault Weapons ban was in effect.

Allied Armament, Inc. (Scappoose, OR) was incorporated on January 26, 2005. Its owner was James A. Malarkey. The firm developed and successfully tested a prototype single stack fifty round M14 drum magazine between the fall of 2010 and the spring of 2011. The magazine body was made from aluminum and given a ceramic coating which eliminated the need for lubrication. The internal parts were made from steel and aluminum. No plastics were used in its construction. Each unit was sold with a limited lifetime warranty. Fully loaded, the black color X-14 drum magazine weighed 4.9 pounds. It could operate in semi-automatic and automatic fire up to 850 rounds per minute with full metal jacket cartridges. If desired, the rear side retaining cap could be easily removed to access the interior of the drum for cleaning. Although the company was dissolved on March 25, 2011, Mr. Malarkey took the X-14 magazine to market in August of the same year under the XS Products brand. The company was renamed X Products by April 2013. Twenty-five skeletonized X-14 drum magazines were made in February 2012. These units had longitudinal openings on the major diameter and circular openings on the

minor diameter of the drum. For 2012, the X-14 magazine top end exterior chamfered edges were changed to a radiused cut. A different coil spring replaced the dual springs used in the first generation models. The new spring allowed the operating handwheel to be shortened by 0.5 ". The X-14 magazine was also made available in olive drab. By December 2012, 500 X-14 magazines had been produced.

The Beta Company (Tucker, GA) began shipping its 100 round twin drum M14 magazine in September 2011 to distributors. The M14 C-MAG^(R) was made from polymer components. It had transparent drum covers on the rear side. Each unit was sold with a black nylon carry bag, user manual, magazine loader, and tube of graphite lubricant. From 2007 to 2011, 44Mag Distributing and John Masen Company marketed replacement parts such as followers, floor plates and twenty round springs. The replacement parts sold by 44Mag Distributing were supplied by Check-Mate Industries. On April 26, 2013, the first .stl format files for three dimensional printing of a M14 magazine were posted on the Internet. The files included five, seven, ten, and twenty round magazine tubes, floor plate, and two followers, one for the twenty round magazine and another design for the smaller capacity magazines.

Miscellaneous Notes on Scope Mounts

Mathewson Tool Company in 1954 designed a means to mount an optical scope on the T44E4 receiver. This design feature was adopted by the U. S. government as part of the M14 receiver. After its involvement with the T44 and M14 rifle projects, Mathewson Tool Company moved from New Haven to Orange, CT by no later than July 1965. The firm was awarded at least forty-four weapons and ammunition programs contracts from 1965 to 1975 by the U. S. Army and U. S. Air Force. The last contract was awarded to Mathewson Tool Company in March 1975 with estimated completion for June 1975.

Brookfield Precision Tool, GG&G, Leatherwood Brothers, and Smith Enterprise mounts have been purchased by the U. S. military for match conditioned M14 type rifles. GG&G made its M14 scope mount for the M14 DMR. The GG&G M1A1 scope mount came in two versions. The first one had two small rail pads and was marked G.G.&G. TUCSON. AZ. on the top. The second type came with a full length rail with the outboard horizontal surface marked GGG TUC AZ U.S.M.C. Both models allowed use of iron sights and were designed with a horizontal key but not a vertical key to avoid fitment issues. Most of the GG&G scope mounts were sold to the U. S. Marine Corps but a few are held privately.

Picatinny Arsenal conducted a study on the difficulties of mounting a scope on the M14 rifle. The U. S. Naval Surface Warfare Center (Crane, IN) also worked on the issue. Scope mount adapters were made for the AN/PAS-4 and AN/PVS-1, -2, and -3 night scopes (NSN 5855-00-941-3036) by GPC Night Vision (CAGE Code 1YE66) and the AN/PVS-4 night scope by Brookfield Precision Tool. The scope mount adapter was issued as part of the AN/PAS-4 sight.

The variety of commercial M14 scope mounts and rail systems today make the M14 a versatile platform. The type of optics to be employed will dictate the choice of scope mount or rail system for the rifle. For a traditional hunting rifle scope, a side three point scope mount provides a stable method of attachment while adding minimal weight to the system. The Global Defense G1-OSM or Smith Enterprise (part number 2005) side three point mounts are excellent choices for mounting the Trijicon, Inc. Advanced Combat Optical Gunsight. If the mission requires several optics, the Troy Industries MCS or Vltor Weapon Systems CAS-14 Cluster Rail provides the maximum amount of uninterrupted rail space. Other options for M14 systems requiring generous rail space include the LRB Arms M25 receiver or a side three point scope mount in concert with a Sage International M14 EBR stock. A barrel rail mount is useful for extended eye relief scopes.

Side Single Point Scope Mounts

Side single point design scope mounts attach to the receiver left hand side using the only bolt hole, with alignment-theoretically at least-assured through firm contact with the receiver's horizontal and vertical grooves. These mounts do not require removal of the cartridge clip guide, while some other mounts do.

In 1966, the Army Weapons Command at Rock Island Arsenal developed a scope mount for the M84 scope to be used on the M14 NM rifle. This scope mount was a two piece affair. The machined base had an integral rail and vertical and horizontal keys to mate to the receiver grooves. The base was attached to the receiver by either a hex head socket screw, large knurled knob screw or a small know with a screwdriver slot. The bases were made of aluminum or steel. The finish of the base was blued, black oxide or phosphate.

The M84 scope was held by a Griffin & Howe, Inc. hinged mount borrowed from the M1C sniper rifle. The scope and mount assembly was secured to the base rail by throw levers. The base had a clearance undercut at the top of the vertical exterior surface to allow free movement of the Griffin & Howe, Inc. mount levers. The scope was centered over the receiver when in use. To use the iron sights, the hinged Griffin & Howe, Inc. mount was rotated counterclockwise to move the scope outboard of the receiver.

The first commercial M14 rifle scope mount was offered by Pete Michaels from 1971 to 1974. This side single point scope mount was a quality copy of the Rock Island Arsenal model used on the M14 NM rifles in the Republic of Viet Nam. There were two versions of this reproduction item. Both versions were made of phosphate coated steel and had horizontal and vertical keys. One version had a clearance undercut at the top of the vertical exterior surface like the Rock Island Arsenal unit. The other copy lacked the clearance undercut. Some were marked on the inboard side: top line - P MICHAELS bottom line - BATAVIA. ILL. Aimpoint, Inc. marketed its M1A1/M-14 single point scope mount around 1996.

The Israeli Military Industries (IMI) scope mount borrowed from the U. S. Army Weapons Command M14 NM mount for its interface with the receiver with its vertical and horizontal receiver keys. It also included integral scope rings. It was made of steel and finished with phosphate coating. The IMI M14 scope mount was marked 2888-89058 along with Hebrew characters and the serial number of the USGI receiver to which it was mounted. IMI also produced a steel night vision scope mount with the same means of attaching to the receiver as the day scope mount. The night vision mount was marked 2888-8755 above two Hebrew characters.

S&K Manufacturing Co. (then in Pittsfield, PA and now known as S&K Scope Mounts) started producing scope mounts for surplus military rifles in the mid-1960s. It introduced one of the first commercial production M14 scope mount in late 1974 (catalog number 1765). It was of the side single point design and made from two black anodized pieces of machined 2024 alloy aluminum. The top piece was screwed to the side piece. The top portion of the mount had two blued finish split 1 " scope rings secured by setscrews. The rings and screws were made from steel. The S&K scope mount attached to the M14 type receiver by one thumbscrew and alignment ribs.

Bill Bassett opened his machine shop in 1951 and made his first scope mount for the M14 type rifle in 1979. The Bassett Machine SM14-1A scope mounts were sized for two different heights and made from 6000 series alloy aluminum except for the hardened stainless steel keys that mated to the receiver grooves. The original design was modified twice with minor improvements through the years to facilitate ease of use. The approximate weight of the mount was 4 ounces. The SM14-1A scope mount had two angled mounting pads for accepting Weaver style rings and was marked on the outboard side: top line - BASSETT MACHINE bottom line - DRIPPING SPRINGS, TEXAS. The Bassett scope mount bolt was designed to be sufficiently tight at 22 in-lbf of torque. The mount was designed such that if the same torque is consistently applied upon installation, the scope will return to within one-half minute-of-angle of its initial zero at 100 yards.

In 2007, Mr. Bassett produced two new prototype "flat top rail" scope mounts, one for Weaver rings and the other for Picatinny style rings. Both solid rail design scope mounts were made to center the scope over the bore and be machined with a relief angle on the underside to help ensure case ejection from the rifle action. In August 2008, the first batch of Bassett Picatinny rail alloy aluminum scope mounts was produced and offered for sale. This mount had a channel milled through the center of the rail to allow the operator to use iron sights up to thirty-two clicks of elevation even with a scope installed. It allowed the cartridge clip guide to remain installed. Two hardened stainless steel keys and a bolt mated the scope mount to the receiver. It was marked on the outboard side: top line - BASSETT MACHINE bottom line - DRIPPING SPRINGS TEXAS. The following year, a low height version of the Picatinny rail mount was made available. Its low height precluded the use of iron sights. Bassett Machine also produced a low height Picatinny rail mount with slightly larger stainless steel keys for Armscorp receivers.

Master Sergeant Allen M. Ewing, USAR (Ret.) was a gunsmith and competitive shooter for many years on U. S. Army Reserve shooting teams. He designed and manufactured two M1A scope mounts. Both models were machined from tool steel and finished with a phosphate coating. MSG Ewing's scope mounts were easy to identify by the vertical Weaver #58 rail attached by two screws to the side single point scope mount. Low height scope rings were used in conjunction with either mount so that the optical scope was fixed directly over the rifle boreline. The Gen I design used sections of drill rod welded to the mount as horizontal and vertical keys for mating with the receiver grooves. It had three pairs of holes at the top of the mount to adjust the height of the Weaver rail over the receiver. The Ewing Gen II scope mount had integral horizontal and vertical keys and four pairs of mounting holes for adjusting the height of the Weaver rail. Its inboard side was further machined to remove material for weight reduction.

The Springfield Armory, Inc. First Generation aluminum scope mount was first advertised in the February 01, 1975 issue of *Shotgun News*. Its design was based on the U. S. Army Limited Warfare Laboratory scope mount made for the ART TEL scope mounted to Vietnam era XM21 rifles. However, the design was modified to accept commercial Weaver rings in lieu of the integral ring bases on the U. S. Army scope mount. It was discontinued in 1995. The Springfield Armory, Inc. A.R.T. IV thumbscrew scope mount was a two piece unit made by Burris Company (Greeley, CO). The top plate was secured to the side plate by three screws. Split ring scope rings attached to either end of the top plate. The side plate was stamped SA A.R.T. IV. This item was available from 1978 to 1990. The Springfield Armory, Inc. scope mounts accept Weaver style rings. Early Leatherwood Brothers scope mounts were made of aluminum and used a single point of contact to the receiver on XM21 rifles.

Side Two Point Scope Mounts

Side two and three point scope mounts are generally manufactured to accept either of two rail geometries, Weaver style or Picatinny style. The Picatinny rail design is also known as MIL-STD-1913 or NATO STANAG 2324. The terms are interchangeable. The Weaver design is more often used to mount optics on commercial market rifles. The Picatinny rail mounts are generally found on military design firearms. The difference in the dimensions between the two designs is important. The nominal recoil groove width for the Weaver design is 0.180 " but it is 0.206 " for the Picatinny rail.

The side two point design scope mount uses the receiver bolt hole and the cartridge clip guide to secure the mount. The cartridge clip guide must be removed before this type of scope mount can be installed. B-Square, Barska, Marstar Canada, McCann Industries, Springfield Armory, Inc. Third Generation, XTA, AIM Sports and latter military issue Leatherwood Brothers mounts mount on the side of the receiver at two points. The U. S. Army armorers installed Leatherwood Brothers side two point alloy aluminum scope mounts on M21 rifles.

The XTA 5100 alloy aluminum M14/M1A scope mount utilizes a 6.13 " long Weaver style rail. It allowed limited use of the iron sights and was marked M14/M1A SCOPE MOUNT on the outboard vertical surface. It had a matte black anodized finish. The XTA mount is very similar in appearance to the Springfield Armory, Inc. Third Generation scope mount. This scope mount was marketed by John Masen Company, New Century Science & Technology, Inc., and M1Surplus from 2006 to 2011. Likewise, the AIM Sports, Inc. (San Gabriel, CA) model M1401 scope mount was very similar to the Springfield Armory, Inc. Third Generation mount. The M1401 scope mount was made from alloy aluminum and given a black anodized finish. It weighed 10.9 ounces and had a 6 " long Weaver rail. It sold in Canada and the United States. Similarly, the Barska scope mount appeared to be a clone of the Springfield Armory, Inc. Third Generation mount. It was first marketed in 2011. The outboard side of the mount was marked M14 / M1A SCOPE MOUNT.

Beginning in 2006, Marstar Canada offered the M-14 Deluxe Tactical Scope Mount (part number M14-103). This was an alloy aluminum scope mount designed and manufactured in Canada for Marstar. This CNC machined scope mount used a substitute cartridge clip guide made of carbon steel. It had horizontal and vertical receiver keys and a Weaver style rail. The McCann Industries M1A/M-14 mount was made of steel and came with two Weaver style ring bases. An optional full length M1913 Picatinny rail is interchangeable with the Weaver style ring bases on the McCann Industries mount using the four factory supplied screws.

The rifle iron sights can be used up to about an elevation of 200 meters with a Springfield Armory, Inc. scope mount. At higher elevation settings the mount will block the shooter's vision through the rear sight aperture. The Springfield Armory, Inc. Third Generation mount uses a supplied substitute guide that replaces the cartridge clip guide. It was available for sale from 1986 through 2009. The Springfield Armory, Inc. Third Generation scope mount was marked on the side as follows: top line - SPRINGFIELD ARMORY bottom line - Geneseo, Illinois. This scope mount had a rail 6 1/8 " long. It was manufactured with a hybrid rail geometry best suited for Weaver style scope rings.

Side Three Point Scope Mounts

Mounts that have three points of contact with the receiver are very reliable for keeping the scope zeroed under all conditions, including removal and re-mounting on the receiver. This type of scope mount contacts the M14 type receiver at the scope mount lug on the left side, at the cartridge clip guide and on top of the barrel ring. Note that side three point scope mounts are not always compatible with rail system mounts or modular chassis stocks. The rear end of the top rail on a rail system mount or a modular chassis stock may interfere with the front end of the side three point scope mount.

Commercial M14 manufacturers do not and never have guaranteed that their receivers meet the dimensional tolerances of USGI M14 receiver drawing F7790189. As such, slight dimensional differences exist between USGI and commercial manufacture M14

receivers. On the other hand, several, but not all, manufacturers have designed their scope mounts to fit USGI M14 receivers without making any accommodation for commercial manufacture receivers. The bottom line for shooters wishing to use a scope sight on an M14 type rifle is that side three point scope mounts do not always fit hand-to-glove on all M14 type receivers. This scope mount style is very popular among M14 rifle enthusiasts. The overall rail length on this type of scope mount varies from 5 " to 10 ". Several models are described below.

Brookfield Precision Tool - The Brookfield Precision Tool mount was developed by Mitch Mateiko. He made the first scope mount in his work shop at home out of steel and subsequently always used steel for his scope mounts. The Brookfield Precision Tool scope mount was installed on U. S. military XM25, M25 and M14 SSR rifles. It was sold in the commercial market for a number of years. Brookfield Precision Tool scope mounts and other parts now command a premium due to the collector value. The Brookfield Precision Tool mount was made from an investment casting. It allowed the shooter to use the rifle's iron sights with or without the scope installed. It was a M1913 Picatinny style rail with a cam type mounting bolt designed to fit all four makes of USGI M14 receivers. Brookfield Precision Tool scope mounts were marked as following on the outboard side, BKFLD PREC TL U S PROPERTY. One small production batch of Brookfield Precision Tool M14 scope mounts were marked with BKFLD PREC TL PAT PEND on the mounting bolt side. There was also a lightweight version of the Brookfield Precision Tool scope mount. The lightweight scope mount had lightening holes drilled along the entire length of the top rail and two relief cuts made on the underside at the front and at the rear. It was marked with a stamped L on the right hand side just to the right of the manufacturer marking. Brookfield scope mounts were not machined with a case deflection angle on the underside.

Smith Enterprise, Inc. - Smith Enterprise scope mounts are made from nitrocarburized AISI 4140 alloy steel. Their surface hardness is approximately 60 HRC and they have a matte black finish. As of 2003, the Smith Enterprise MIL-STD-1913 Picatinny rail tactical scope mount was stocked in the U. S. military supply system. This mount allows the shooter to use the iron sights with or without the scope installed. It is in use by the U. S. Army 25th Infantry Division and the U. S. Navy. On September 28, 2005, Smith Enterprise was awarded a contract by the U. S. Army 101st Airborne Division to supply deploying units with this scope mount along with its 30 mm heavy duty scope rings and Leupold & Stevens, Inc. 3.5-10X 40 mm scopes to deploying units. This scope mount was marked NSN 5855-01-506-5750 U. S. PROPERTY. It is manufactured using the wire electro-discharge machining (EDM) method. EDM can be described as spark erosion of metals by local heating and melting. This metalworking method holds very tight tolerances and leaves burr free surfaces.

In April 2005, Smith Enterprise made available a 7 " rail length version of its wire EDM manufactured scope mount to the U. S. Air Force and U. S. Marine Corps. This scope mount was assigned the National Stock Number 1005-01-533-8160 on September 28,

2005 by the Defense Supply Center - Columbus. This scope mount is marked: Smith Ent. "Crazy Horse" MIL STD 1913 United States Property NSN 1005-01-533-8160.

In April 2006, Smith Enterprise, Inc. introduced its Trijicon, Inc. Advanced Combat Optical Gunsight compatible scope mount for the M14 rifle. This mount is made by the wire EDM manufacturing method. The material is AISI 4140 alloy steel. Initially, it was marked: inboard side - US PROPERTY SMITH ENT NSN 1005-01-535-4430. Later versions are marked: outboard side - UNITED STATES PROPERTY inboard side - NSN 1005-01-535-4430. The advantage of this scope mount is the detachable MIL-STD-1913 Picatinny rail. The user can quickly swap a traditional rifle daylight scope for a Trijicon, Inc. Advanced Combat Optical Gunsight. There is no loss of zero when the daylight scope is reinstalled. The detachable rear rail section is removed and installed by loosening or tightening the bolts with a t-shape handle hex head wrench. This scope mount does not have a see through channel so iron sights are not available with the mount on the rifle.

The Smith Enterprise, Inc. 10 " scope mount was introduced to the market in July 2007. This scope mount allowed the use of iron sights without a scope mounted and had a MIL-STD-1913 rail pattern. It was compatible with the Trijicon, Inc. Advanced Combat Optical Gunsight. It was marked simply UNITED STATES PROPERTY.

Smith Enterprise's earlier M14 scope mounts were made using conventional machining methods but are nonetheless just as trouble-free and durable. The older model Smith Enterprise rail scope mounts were produced in two versions, Weaver style rail and MIL-STD-1913 rail. This earlier MIL-STD-1913 version was sold to the U. S. Army in the late 1980s and 1990s. These scope mounts were marked SMITH ENTERPRISE. TEMPE. AZ M21.

The older Smith Enterprise Weaver style rail mounts were manufactured in 1994. These mounts were marked SMITH ENT. XM-21. This scope mount was briefly reintroduced in 2006 as part number 2024 with the marking SMITH ENT. M-21. Both Weaver style rail mounts were made using conventional machining methods.

The Smith Enterprise scope mount had a three degree upward slope on the underside of the rail, just above the rifle's bolt. This allowed ejected brass to clear the action while minimizing any contact with the mount because of varying receiver geometries among the manufacturers. The mount utilized an AISI 4140 alloy steel cam type mounting bolt to compensate for the differing position of the bolt hole on various makes of rifles. This bolt was heat treated to 35 HRC and could withstand 140 in-lbf without shearing. However, 65 in-lbf of torque was sufficient for installing any scope mount. Beginning in December 2008, Smith Enterprise, Inc. offered a scope mount cam bolt for commercial receivers with bolt holes made with a non-USGI thread pitch. This heat treated and nitrocarburized cam bolt was made from 17-4 precipitation hardening stainless steel. The surface hardness was made 60 HRC to prevent the bolt threads from stripping when installing the mount. The bolt could withstand a minimum of 200 in-lbf of torque. Installation

instructions were included with every scope mount sold by Smith Enterprise as well as being posted on the company web site. Smith Enterprise machined its M14 scope mounts to fit customer supplied commercial M14 type receivers.

Armscorp USA - The Armscorp USA M14 scope mount was a very faithful copy of the milestone Brookfield Precision Tool mount. It was machined from steel and heat treated to U. S. military specifications. It had an adjustable cam bolt. The iron sights could be used with this mount installed without removing the scope. The Armscorp USA side three point scope mount was marked as follows on the side ARMSCORP U.S. PROPERTY or ARMSCORP BALTO. MD U.S. PROPERTY PARA MODEL.

Atlantic Research Marketing Systems, Inc. – Atlantic Research Marketing Systems (CAGE Code 0FBA6) was established by Richard Swan. His 1983 dovetail style rail design for mounting firearm optical sights was adopted by the U. S. Army Picatinny Arsenal on February 03, 1995 as the MIL-STD-1913 accessory rail. MIL-STD is an abbreviation for Military Standard. This rail mount design is referred to as the M1913 Picatinny rail. Atlantic Research Marketing Systems produces a wide variety of optical sight mounting rails for firearms.

Its # 18 mount is designed for use on the M14 type rifle. The # 18 mount has been made in two versions. The early style was first introduced to the commercial market in 1989. It had two Weaver style rail pads, one at each end, for mounting the scope rings. Until 1998, the early style mounts had an integral cartridge clip guide in the rear pad, useful only when mounted on the receiver without a scope installed.

Introduced in 2003, the new style # 18 mount had a M1913 Picatinny full-length rail running from the cartridge clip guide dovetail to the top of the barrel ring. Both split and full rail versions were marked on the outboard side: above the bolt - company logo, below the bolt - A.R.M.S. M21/M14 W.B. MA. In 1998, the number 98 was added to the end of the markings under the bolt. The NSN was added as a second line under the bolt, NSN 1240-01-316-0055. Additional markings were placed above the bolt: registered trademark indicator, 18, and sometimes, SWAN. The new style # 18 was made of case hardened AISI 8620 alloy steel. Both styles of the # 18 scope mount were made from investment castings. The overall rail length for both versions was 4 9/32 ".

The # 18 scope mount sat low enough on the receiver to allow use of the iron sights if the scope was removed. It sits the lowest over the rifle's bore of any scope mount available. Due to differences in commercial receiver geometry the user may find that a little judicious removal of metal at the underside corner of the mount's front end may be necessary to get a # 18 mount to fit perfectly. The Atlantic Research Marketing Systems # 20 throw lever mount will secure an AN/PVS-4 night vision scope to a M14 type rifle fitted with a Weaver style rail scope mount.

Mil-Spec Logistics, Inc. and Millett - Mil-Spec Logistics, Inc. marketed a side three point scope mount that was based on the Brookfield Precision Tool design. It was made of steel and had two moderate length Picatinny rail pads instead of a full length rail. The outboard vertical surface of the mount was marked MIL SPEC LOGISTICS, INC. By the winter of 2010, Millett made available its Picatinny rail M1A-M14 Mounting System (Item # PC000014). It was made from 6061 T6 alloy aluminum and given a matte black finish.

Sadlak Industries - Since 2002, Sadlak Industries has produced scope mounts for the M14 rifle. This company offers its M1913 Picatinny style rail scope mounts manufactured from three different materials, titanium, steel and aluminum alloys. The rail length is the same for each model, 5 3/8 ". The Sadlak Industries M14 scope mount is based on the Brookfield Precision Tool model.

Sadlak Industries incorporated some new enhancements to its M14 scope mount in late 2004. Two setscrews securely hold the wider adjustable dovetail piece (clip guide key) to the rifle's receiver, to keep it from loosening. The rear end of the scope mount has cutouts to allow wrench access to the dovetail setscrews. The dovetail setscrews securely lock the dovetail piece (clip guide key) into the receiver. The scope mount hole for the adjustable dovetail piece (clip guide) screw has been machined with an oval slot and a larger counterbore to make it more easily compatible with non-USGI receivers. The front post screw size has also been increased for a larger contact area with the receiver barrel ring. The front screw has also been changed from a 1/4 " x 28 fine thread to a 5/16 " x 24 fine thread. The new size front screw reduces the number of hex head wrenches from three to two. The front screw and the dovetail key socket screw now both use the same size hex head wrench. 2006 production scope mount weights were 7.258 ounces (alloy titanium), 11.113 ounces (4142 alloy) and 4.331 ounces (7075 alloy).

Its titanium scope mounts were machined from hot rolled billet and then heat treated to a hardness of 26 to 30 HRC. From 2002 to 2006, the titanium scope mounts were made from two alloys of hot rolled titanium billet: 1) 6 % aluminum 4 % vanadium 89 % titanium 2) 6 % aluminum 5 % vanadium 2 % tin 87 % titanium. After heat treatment, the titanium mounts are finished with a matte black nitride coating for improved corrosion and abrasion resistance. This coating increases the surface hardness to approximately 80 HRC. The Sadlak titanium scope mount is tougher and stronger than steel but about 35 % lighter. A Sadlak Industries titanium M14 scope mount made in 2004 was marked SADLAK INDUST. LLC COVENTRY CT USA M14 T-02.

Before 2005, the manufacturer information was located on the inboard side of the mount. From 2005 and onward, the marking is indicated on the outboard side of the mount. Scope mounts are coded by a single letter prefix and a two digit number, e.g., S03. T stands for titanium and S for steel. The number means the blueprint revision for the scope mount made from the material denoted by the letter, e.g., S or T. There are slight changes between blueprint revisions. As an example, T-02 scope mounts have a two degree relief angle under the horizontal surface. T-03 scope mounts will have a five

degree relief angle under the horizontal surface.

Sadlak's standard design steel scope mounts were made from stress relieved AISI 4142 bar stock with a core hardness of 28 to 32 HRC. The steel mounts were given a military specification manganese phosphate coating. A Sadlak Industries steel scope mount made in 2006 was marked: top line - SADLAK INDUSTRIES LLC M14 RIFLE Steel middle line - COVENTRY CT bottom line - USA. The scope mount markings changed slightly over time.

A 7075 alloy aluminum-magnesium-zinc version of its M14 scope mount was in testing in November 2004. This alloy is commonly used to fabricate aircraft frames. The 7075 alloy M14 scope mount is fully machined and hard coat anodized. It became available in early 2005. In early 2006, Sadlak Industries produced a small batch of anodized gray 7075 alloy scope mounts. Otherwise, the 7075 alloy models have been anodized black.

The original alpha-titanium-carbon-nitride coating used on the titanium model was not always as consistent in color as desired. Sadlak Industries, LLC does not compromise on its quality control. So, those off-color mounts have been rejected even though all other inspections were satisfactory. Unfortunately, the rejection rate due to improper color only was unacceptably high. Consequently, as of late 2004, Sadlak Industries was testing a second and more color consistent matte black nitride coating as well as a tungsten coating for the titanium M14 scope mounts. The tungsten coating is even more durable than the nitride coating and has a slight greenish-gray phosphate coloring reminiscent of older military weapons. The tungsten coating was so successful that the black nitride coating for titanium scope mounts was discontinued in 2005.

Beginning in early 2005, a five degree relief angle is machined into the bottom of its scope mounts to minimize interference from spent cases in rifles with worn ejector springs. Sadlak Industries produced in March 2005 a single batch of six tungsten coated version S03 steel scope mounts. In April 2005, Sadlak Industries started a custom scope mount fitting service to accommodate non-USGI dimension receivers and / or allow for elevation adjustment. At the end of September 2005, Sadlak Industries filled a request from the U. S. Army for ninety-eight steel M14 scope mounts.

The Sadlak Airborne model M14 scope mount was produced per request of the U. S. Army 101st Airborne Division in September 2007. The Army Division requested a lighter steel version of the Sadlak standard M14 scope mount. Sadlak Industries, LLC produced the requested quantity of twenty in time for the unit to deploy. Another six of the Airborne M14 scope mounts were sold to another U. S. Army division shortly thereafter. The Airborne model weighs 9 ounces. Lightning holes were drilled and counterbored along the entire length of the rail. Two relief cuts were made on the underside and the side wall metal was cut away on either side of the bolt hole. It was machined from molybdenum-chromium alloy steel bar stock, heat treated to 45 to 50 HRC, and given a manganese phosphate finish. Like the standard steel model, the iron sights may be used with scope

rings attached and it retained the underside five degree case deflection angle. The additional marking, ABN, was initially added to the bottom of the outboard side of this model scope mount. A 2009 unit was marked: top line - SADLAK INDUSTRIES LLC M14 U.S. RIFLE Steel middle line - USA bottom line - AIRBORNE. Beginning in the winter of 2010, Sadlak Industries, LLC manufactured side three point scope mounts for Leupold & Stevens, Inc. These mounts were marked on the outboard side as follows: top line - LEUPOLD bottom line - USA.

Entreprise Arms, Inc. - Entreprise Arms offered a Weaver style rail scope mount. It was machined from AISI 4140 alloy steel. The Entreprise Arms web site listed the mount in two lengths, standard and extended (catalog numbers TT18 and TT18E). The standard length model had a rail length of 5.3 " and weighed 11 ounces. The Entreprise Arms mounts allowed the shooter to use the rifle iron sights with or without the scope installed. The Entreprise Arms M14/M21 scope mounts had a military specification phosphate coating.

Global Defense Initiatives, Inc. – In 2003, Global Defensive Initiatives, Inc. (San Diego, CA) designed and produced a side three point mount that differed somewhat from the classic Brookfield Precision Tool design. Its G1 Optical Sight Mount (G1-OSM) allows the use of iron sights with the scope removed or installed. However, the M1913 Picatinny rail extended rearward to a point just behind the rear sight aperture. The rear sight assembly stayed in place with the mount installed. The G1-OSM mount accommodated an optical sight requiring very short eye relief between the shooter and the ocular lens. Thus, the versatility of the G1-OSM design allows the use of traditional telescopes and dot sights as well as Trijicon, Inc. Advanced Combat Optical Gunsight without the use of rail adapters. The G1-OSM was finished with a black oxide coating. The side hex locking screw torque specification is 55 in-lbf.

Two years later, Global Defense Initiatives (GDI) introduced its second generation G1-OSM scope mount. Initially, the second generation G1-OSM mount had a molybdenum disulfide finish but that was changed to a nitrocarburizing finish by mid-2005. The nitrocarburizing gave the mount a surface hardness of 70 to 72 HRC. The second generation also allows use of iron sights whether optics are installed or not. The G1-OSM Gen 3 Scout scope mount was developed and production started in 2008. This model has the same finish as its predecessor but it is more than 25 % lighter. It features an increased underside relief angle to further minimize stoppages from ejected cartridge cases. All versions of the G1-OSM scope mount are made from CNC machined 17-4 precipitation hardening stainless steel. GDI scope mounts lack a vertical key and are machined with an elongated bolt hole for better compatibility with commercial M14 receivers. All G1-OSM scope mounts are marked on the outboard side: GDI Inc. Pat. Pend. Made in USA.

Leatherwood Brothers, McCann Industries and Talbot – Leatherwood Brothers began advertising its new side three point rail mount in *Shotgun News* in 2004. All parts are

made from steel. This mount weighs 8 ounces and allows the use of iron sights without the scope rings. There is no vertical key. It is adjustable for elevation and windage. It has a blued finish and will accept M1913 Picatinny style scope rings. Leatherwood Brothers began shipping its mount to customers in June 2004. The McCann Industries MITS mount is a side three point design unit that uses a unique three bolt design. Installation requires gunsmithing. A traditional design M14 bolt lock should be used in conjunction with the MITS scope mount as it may interfere with an extended bolt lock. The Talbot steel scope mount for the M14/M1A uses an optic mounting surface and quick detach combination dual ring and rail assembly that is common to the firm's many models of scope mounts. Various interchangeable dual ring and rail assemblies are available for the Talbot family of scope mounts. Talbot also offers a dual ring and rail assembly for M1913 Picatinny rail scope mounts.

Keng's Firearms Specialty, T T International and US Tactical Systems - These are moderately priced side three point mounts for the M14 type rifle. The Keng's Firearms Specialty unit has a M1913 Picatinny rail. The US Tactical Systems model has a Weaver style rail and is made from AISI 4140 alloy steel. It is heat treated and has a black color nitride surface finish. With the scope removed, the iron sights can be used with these mounts installed on the rifle. The TSA marked scope mount was marketed about 2004 by T T International. It was manufactured from hardened steel with a M1913 Picatinny rail. Like the US Tactical Systems mount, the T T International mount lacks a vertical key.

ProMag Industries - ProMag Industries introduced two M1913 Picatinny rail scope mounts for the M14 in 2006, product codes PM081 and PM081A. Both mounts were made from high carbon steel and finished with a black oxide coating. The PM081 model was similar to the Brookfield Precision Tool scope mount. It was marked PROMAG PM081 U.S.A. on the inboard vertical surface. The PM081A mount was of similar design as the Atlantic Research Marketing Systems, Inc. # 18 full rail mount but with two minor differences. The rear end of the PM081A mount was secured to the cartridge clip dovetail by use of a ¼ " x 20 cup point socket setscrew in lieu of a milled key, spacer and screw. A ¼ " x 20 cup point socket setscrew made contact with the receiver barrel ring vice a circular contact pad for the # 18 scope mount. The scope mount bolt must not be tightened with more than 100 in-lbf of torque. Otherwise, the bolt will shear. In January 2012, the PM081A model became a reproduction of the early style (split rail) A.R.M.S. # 18 mount except that a hex head screw and jamb nut replaced the mounting bolt. The split rail ProMag Industries mount did not have any markings.

Unertl Optical Company - In the summer of 2006, Unertl developed two prototype design M14 scope mounts. Both mounts were improved versions of the basic Brookfield Precision Tool design. The mounts were made from alloy steel and had forward and rear M1913 Picatinny rail pads. The shorter of the two prototypes was about 6 " long. The rail pads had four slots each with the rear rail pad extending approximately ¾ " past the front edge of the rear sight cover. The longer scope mount had an overall length of about 7 " with six front slots and two rear slots. The front rail pad of the longer mount reached 2 "

past the receiver barrel ring. This version better accommodated dot sight optics and scopes greater than 10X magnification. The open space between the two rail pads was designed to avoid stovepiping of spent cases. Both prototype scope mounts were marked on the left side UNERTL ORDNANCE with the company logo to the right of the lettering. The longer Unertl scope mount became available for sale in February 2007.

Springfield Armory, Inc. - In February 2010, Springfield Armory, Inc. introduced its M1A Fourth Generation scope mount in alloy aluminum (model MA4GENAM) or steel (model MA5028). Both models were marked on the outboard vertical surface, SPRINGFIELD ARMORY for the steel version and SPRINGFIELD ARMORY Geneseo Illinois for the alloy aluminum mount. The fore and aft rail pads each had five Picatinny rail slots. The rear end of the steel model was secured by a dovetail key. The alloy aluminum mount utilized a substitute cartridge clip guide and large hex head screw. The steel version lacks a horizontal key but the aluminum version does not and neither has a vertical key.

Side Three Point Scope Mount Fitting on Commercial M14 Receivers

There are five points of contact between the side three point scope mount and the rifle's receiver that may cause improper fit up with military design side three point scope mounts when installed on commercial M14 receivers. The surface contact between the left side of the scope mount and the left side of the receiver is of primary importance. The more contact between these two surfaces the less likely the mount is to shift from firing recoil. The scope mount should be tested first for fit without the cartridge clip guide dovetail key supplied with the mount.

Receiver Bolt Hole - The USGI M14 receiver drawing F7790189 specifies a distance of 1.500 " + or - 0.003 " for the distance between the bolt hole centerline and the front vertical edge of the barrel ring. If the bolt hole is drilled too far to the rear, the rear of the scope mount may contact the receiver cartridge clip guide dovetail. This lifts the back of the mount so the mount horizontal key doesn't fully seat in the receiver horizontal groove. Consequently, the mount is moved left or right, and usually also down, at the front end. The rifle is then likely to shoot high and/or to one side. Furthermore, some bolt holes are undersized because the maker used worn out reamers, or the bolt holes may not be drilled perfectly perpendicular to the receiver wall. A very few commercial receivers lack the scope mount recoil lug or bolt hole. Care must be taken to not exceed the torque specification for the manufacturer supplied scope mount bolt or screw. A torque wrench calibrated in in-lbf is the best tool to use for tightening the scope mount receiver bolt or screw.

Receiver Horizontal Groove - The height, angle and width of the horizontal groove affect the fit of side three point scope mounts to M14 type receivers. Some commercial receivers have horizontal grooves too shallow and narrow to accommodate military specification mounts such as the Armscorp USA, Brookfield Precision Tool and Sadlak Industries models. A 2002 manufacture commercial M14 type receiver examined by

Sadlak Industries, LLC in December 2004 is a representative case study of the mismatch between commercial receivers and military dimension scope mounts. The receiver horizontal groove of this particular 2002 manufacture commercial receiver measured 0.048 " deep, 0.080 " wide at the bottom and 0.134 " wide at the top.

The width at the top of the receiver horizontal groove should be 0.0149 " to 0.153 " by calculation based on the sixty degree angle and groove bottom width dimension as specified in the USGI drawing number F7790189. The bottom of the horizontal groove is required to be 0.070 " to 0.078 " wide according to the USGI drawing F7790189. The horizontal groove should be 0.062 " to 0.072 " deep by calculation. Commercial M14 receiver horizontal grooves have been measured as narrow as 0.120 " at the top of the groove.

Receiver Barrel Ring - The top front left hand corner of the receiver barrel ring may interfere with the new style Atlantic Research Marketing Systems # 18 mount. This is no fault of Atlantic Research Marketing Systems, Inc. as its mount was designed to fit on USGI M14 receivers.

Receiver Cartridge Clip Guide Dovetail - The receiver cartridge clip guide dovetail may be machined such that the scope mount adjustable dovetail key will not slide in from the side of the bolt hole, but may do so from the operating rod side. The height of the cartridge clip guide dovetail may also be tall enough to push up on the rear end of the scope mount. The cartridge clip guide dovetail has been found to be as much as 0.030 " taller than USGI specification.

Barrel Hand Guard - The Atlantic Research Marketing Systems # 18 front rail pad setscrew may contact the hand guard. This can be remedied by replacing the mount's front setscrew with one that fits flush with the pad. Again, this is no fault of Atlantic Research Marketing Systems, Inc. Commercial M14 type receivers are not always machined to the USGI drawing F7790189 dimensions.

Smith Enterprise, Inc. has found as much as 0.010 " variance front to rear for the location of the scope mount bolt hole on USGI M14 receivers. In the 1990s, the U. S. Marine Corps and U. S. Navy had success with the Brookfield Precision Tool scope mounts since it was designed without a vertical key. However, the U. S. Marine Corps found that the location of bolt holes on Harrington & Richardson M14 receivers adversely affected mount alignment to require excessive windage adjustment to zero the scopes. The U. S. Marine Corps had no such problems with the Winchester M14 rifle receivers.

Scope Mounts Secured to the Rear Sight Pocket

In 1985, Smith Enterprise designed and produced pre-production units of two models of longer side three point scope mounts. Both were 9.250 " long. The rear end of both

models mounted to the rifle's rear sight pocket, requiring removal of the rear sight assembly. The front end of the mount rail extended past the receiver barrel ring. One mount was TIG welded to the receiver, while the other was bolted on at the rear sight pocket through the sight knob holes. The heads of the bolts for the rear sight pocket were the same diameter as the sight knobs. The project was not pursued since it was found that the commercial market in 1985 was not ready for this new style of scope mount.

In years past, Atlantic Research Marketing Systems, Inc. marketed its M-14/M-1A Rigid Rail Mount. This mount had a ring at the front end that fit around the barrel just forward of the receiver barrel ring. The rear end of the mount fit inside the rear sight pocket and was secured by a bolt through the sight knob holes. The Atlantic Research Marketing Systems M-14/M-1A Rigid Rail Mount had a M1913 Picatinny rail and was offered in two choices of material construction and three differing lengths. The material was either phosphate coated AISI 4140 alloy steel or an aluminum rail with steel barrel ring. The aluminum and steel model was hard coat anodized for the surface finish treatment. The mount was available in standard, extended front or extended rear lengths. The flash suppressor, gas system and operating rod guide had to be removed to install this scope mount. Installation of this scope mount should be done by a gunsmith familiar with the M14 type rifle.

Gruning Precision (Riverside, CA) has designed and offers its M1A/M14 Scope Base in three variations: Standard Steel Optic Mounting System, Steel NVS Optic Mounting System and NVS Lightweight Full Length Optic Mounting System. NVS is an acronym for night vision sight. The Gruning scope mounts are manufactured with a M1913 Picatinny rail pattern. The rail length for each model is approximately 8.75", 16.25", and 22", respectively. All three scope mounts are secured at the rear terminus by a bolt placed and fastened through the rear sight knob holes and a ring around the barrel chamber just forward of the receiver barrel ring. The NVS Lightweight Full Length Optic Mounting System has an additional attachment point at the gas cylinder lock. The portion of the hand guard aft of the hand guard band is neatly removed to accommodate installation of the scope mount barrel ring.

The Springfield Armory, Inc. M25 and Accuracy Speaks, Inc. M1913 Picatinny rail scope mounts both attach to the rear sight pocket instead of the cartridge clip guide dovetail and the barrel. The forward end of the M25 rail mount attaches to a ring that fits in a milled groove on the barrel chamber. Installing the barrel locks the front end of the M25 rail in place. The Accuracy Speaks mount will fit either the M1 Garand or M14 type rifle. This aluminum mount replaces the rear sight and firmly attaches to the barrel. Installation requires drilling and tapping the barrel and removal and modification of the hand guard.

In late 1997, Derrick Martin and Barrett Tillman conducted some accuracy testing of handloaded 175 grain .308 Winchester caliber ammunition in the Arizona desert. The test rifle was a modified and scoped Springfield Armory, Inc. M1A. This particular M1A was outfitted with a Douglas 1:10 twist bull barrel, a McMillan stock, a Harris bipod, and

custom gas system. The test rifle had no iron sights. The rear sight assembly was displaced by the Accuracy Speaks, Inc. scope mount.

The Upgrade Path Inc. for M14.ca brought the M14/M1A CASM^(R) scope mount to market in December 2010. It was designed by Larry Zakreski with Frank Goluza offering suitable modifications. The 6.125 " long 4 ounce Picatinny rail mount was machined from 7075 alloy aluminum and finished with black anodizing. The M14/M1A CASM^(R) mount was secured to the rear sight knob holes by two ¼ " tapered self-centering flat head screws. Two vertically mounted 5/16 " self-locking half dog setscrews, one at the barrel ring and the other above the rear sight pocket, provided the Picatinny rail with a secure means against vertical movement during recoil. Each of the four mounting screws was further locked in place by a 10-28 setscrew. In July 2011, the firm introduced a similar mount designed for red dot optical sights. The M14/M1A CASM^(R) RD mount had an overall length of 1.5 " allowing it to lie within the rear sight pocket. It weighed 2 ounces, 0.8 ounces less than a USGI standard rear sight assembly. The RD sight Picatinny rail cross-section was machined to provide a sight tunnel groove. A non-adjustable peep hole drilled into the rear side facilitated use as a backup iron sight. The following year, the 2 ounce MRD base and hood mount was introduced to the market. It was used to mount a JP Enterprises, Inc. JPointTM dot sight in the rear sight pocket. Both RD and MRD mounts were made from 6061 T6 alloy aluminum and coated with black anodizing. By early 2012, the M14/M1A CASM^(R) Gen II mount was made with the sight tunnel groove and non-adjustable peep hole sight. The second generation mount was made from either of two materials, 7075 alloy aluminum or equivalent AISI 4140 alloy steel hardened to 30 HRC. A longer 9.125 " version of the alloy aluminum M14/M1A CASM^(R) scope mount, Gen II EX, was made available in the winter of 2013.

Heritage Arms, Inc. (Loma, CO) produced a rear sight pocket scope mount with mechanical adjustments for windage and elevation up to 150 or 300 minutes of angle. The forward end of the mount was secured to the scope mount bolt hole by a hinged arm. It was marked COLD SHOT M1A M14 on the left side.

Rail System Mounts

C. Reed Knight has been supplying firearms related items to the U. S. military since 1986. His company, Knight's Armament Co., employed approximately 300 at its Titusville, FL plant in 2007. The firm produced an M16 Carbine style rail system for the M14 by no later than 2002. The rail system was known as the M14 RAS. It was offered in two models. The rear end of the top rail for both models stopped at the receiver barrel ring. The deluxe model had a rear scope mount base (part number 23097) that replaced the cartridge clip guide. The standard model weighed 13 ounces. It resembled the deluxe model, but without the rear scope mount base. This was a very solid mount and its installation was a simple matter. The rear end of the M14 RAS bolted to the receiver scope mount bolt hole. It was sized only for rifles with standard contour barrels. The

RAS' side ribbed accessory panels interfered with National Match, JAE-100 or other oversized stocks, but not USGI contour stocks. The M14 RAS was marked as follows on the right hand side from top to bottom: first line – KNIGHT'S ARMAMENT CO. second line – TITUSVILLE, FL third line – (321) 607-9900 fourth line – PN #22121. The company logo was just to the left of the text markings. The M14 RAS was discontinued in 2010.

In 2004, C. J. Weapons Accessories (then Moreno Valley, CA later Jefferson City, MO) offered the Striker-14 M-14/M1A Tactical Rail System. This model used three M1913 Picatinny rails, with the rear end of the top rail attaching to the cartridge clip guide. The rifle's iron sights could be used with a scope installed. The Striker-14 unit attached to the rifle at three points. It was CNC machined from a single piece of aluminum and had a black anodized finish.

The Springfield Armory, Inc. M1A SOCOM II models are fitted with the Vltor Weapon Systems CAS-14 rail system mount. Vltor introduced the aluminum CAS-14 rail system mount at the 2004 SHOT Show. Springfield Armory, Inc. refers to the Vltor rail system as the Cluster Rail. The M1A SOCOM II Cluster Rail has four M1913 Picatinny rails. This longer version of the Vltor CAS-14 rail system has the twelve o'clock rail running from the front band to the cartridge clip guide. A shorter version of the CAS-14 mount terminates at the rear end of the barrel. Both versions attach to the M14 type rifle at the receiver scope mount bolt hole, the barrel hand guard band grooves and the operating rod guide. A U-shaped bracket is used to mate the CAS-14 rail system to the operating rod guide. A 3/8 " hex head bolt threads into the scope mount hole to fix it to the left side of the receiver. The longer CAS-14 mount uses two screws to mate the rear end to a substitute cartridge clip guide. The bottom portion of the M1A SOCOM II rail system can be quickly removed and left off the rifle by depressing two buttons at the rear of the stock and swinging the part downward.

The alloy aluminum Vltor Weapon Systems CASV-14 is a "drop-in" top rail cover that works with traditional design M14 stocks. It attaches to the rifle at three points. At the rear, the top rail is screwed to a substitute rail block that replaces the cartridge clip guide. The rail mount clamps to the barrel chamber groove on the left side. This contact point is secured by a bolt that is tightened against the barrel chamber. The CASV-14 fits tightly around the operating rod guide at its front end. It is only compatible with standard contour barrels. Iron sights can be used if no optic is mounted. The 17 " long top rail extends from the front band to the cartridge clip guide. Threaded holes on either side of the mount allow installation of M1913 Picatinny rail sections. The CASV-14 mount is available in black, green or tan. The left side of the rail mount system is marked with the company logo, the model number, and MADE IN USA. It weighs 13.5 ounces. The company released the CASV-14 to the retail market in the summer of 2011.

Note that rail system mounts such as the Vltor CAS-14 and CASV-14, Knight's M14 RAS and C J Weapons Striker-14 are not compatible with conventional side one, two and three point contact scope mounts. This is because rail system mounts utilize the receiver

scope mount bolt hole or the top rail extends behind the receiver barrel ring.

Sage International, Ltd. - By March 2008, Sage International, LLC introduced a detachable cantilevered Picatinny rail sight base designed to bridge the M14 action. The forward end of the sight base mounts to the Sage M14 EBR type stock twelve o'clock rail or a barrel rail mount. The forward end of the base is fastened to the rail over the barrel by two lever actuated cams. A steel cartridge clip insert is placed on top of the USGI cartridge clip guide. The rear end of the cantilevered sight base has a stainless steel adjustment setscrew that threads into a hole on top of the cartridge clip insert. The setscrew is designed to prevent vertical and horizontal movement of the sight base. The cartridge clip insert is secured into the cartridge clip by tightening a locking setscrew on the front side of the insert. As a result of feedback from Rock Island Arsenal, the detachable cantilevered sight base was redesigned by mid-2009. Two tabs were machined into the bottom of the sight base and the lever actuated cams were swapped to place the locking lever at the front to further prevent a loose fit during recoil.

Smith Enterprise, Inc. - The Smith Enterprise MIL-STD-1913 Tri Rail mount consists of three short Picatinny rail sections that are screwed through the USGI synthetic stock to 7075 T6 alloy aluminum backing plates at the three, six, and nine o'clock positions just aft of the stock ferrule. Initially introduced in 2006, the Picatinny rail sections were made from M80HT heat treated AISI 4140 alloy steel. By 2008, Smith Enterprise, Inc. was making the rail sections from hard anodized 7075 T6 alloy aluminum. This change in material reduced weight and cost of the part while retaining plenty of strength and stiffness for its intended use. The three and nine o'clock rails were 3 3/4 " long. The six o'clock rail with sling swivel could be had in either 1 1/4 " or 3 3/4 " lengths. Each part was marked SMITH ENT.

Barrel Rail Mounts

Springfield Armory, Inc. – Springfield Armory, Inc. offers a barrel scope mount for extended eye relief scopes. The M1A Scout Squad and SOCOM 16 models are sold with a hybrid style rail barrel scope mount installed. The Springfield Armory, Inc. barrel scope mount utilizes a rail geometry that will accept either Picatinny or Weaver style rings. End users of this mount report greater satisfaction with employment of Weaver style rings on Springfield Armory, Inc. scope mounts. This mount is made of die cast alloy aluminum and attaches to a standard contour barrel using six 7/32 " hex head screws that secure the upper half to the lower half of the mount. Medium weight and heavyweight M14 barrels and M1 Garand barrels cannot accept this mount. Springfield Armory, Inc. offers the Scout Squad scope mount finished in a choice of black or brown. Springfield Armory, Inc. also sells this item separately.

Rooster33 - Rooster33 produced and sold its own barrel scope mount from March 2004 until the second half of 2005. It was made of steel and sized only for a lightweight (standard) contour M14 barrel. The Rooster33 1 " long scope mount attached to the

barrel by four hex head bolts. It had a manganese phosphate coating and accepted either Weaver style or M1913 Picatinny style rings.

Marstar Canada - By May 2007, Marstar was manufacturing its own barrel rail mounts (part number M14-104). These steel short length split ring rail mounts consisted of two halves that fastened to a standard contour M14 barrel by four hex head screws. The Marstar barrel rail mount will accept either Weaver or Picatinny style scope rings.

Amega Ranges, Inc. – In early 2006, Amega Ranges offered a M1913 Picatinny rail barrel mount for the M14 type rifle. It was made from anodized black color 6005-T6 alloy aluminum and weighed 18.5 ounces. By May 2006, two mounts were available, the M14-M1A Standard Military Model for USGI standard contour barrels and the M1A SOCOM Model for Springfield Armory, Inc. 16 " and 18 " barrels. In May 2011, the firm introduced a new M14-M1A barrel rail mount sized for USGI standard contour and Springfield Armory, Inc. 16 " and 18 " barrels. The weight of the improved mount was reduced to 16.1 ounces. Amega Ranges M14-M1A barrel rail mounts would not fit Chinese, medium contour or heavyweight M14 barrels. The Amega Ranges rail mount ran from the front end of the barrel ring to the front band. It attached to a M14 barrel by hex head screws fastening a long or short length stainless steel clamp to the bottom side of the mount.

D. D. Ross Company - As of 2006, D. D. Ross Company (Medina, OH) produced a M14 barrel rail scope mount designed for the contour of the heavyweight barrel. The scope mount was a M1913 Picatinny style rail. It attached to the rifle at the cartridge clip dove tail and at the barrel about four inches forward of the receiver. The forward end of the rail terminated about 6 " forward of the receiver.

Midwest Industries – Introduced in 2005, Midwest Industries manufactures an anodized 6061 alloy aluminum dual M1913 Picatinny rail mount that attaches to the barrel over the gas cylinder (Item # MCTM14-1A). It is useful for attaching tactical lights or lasers. Any rail mount or bipod that is secured to the barrel may change the zero of the rifle. The rifle should be sighted in and test fired to check for any change in sight zero or accuracy after installation. Midwest Industries brought another innovative mount to market in the winter of 2012. Its M1A/M14 Mini Dot Mount allowed for use of iron sights while a miniature red dot sight was mounted to this barrel rail. The mount was sized to fit around standard contour barrels and within a M1A Scout Squad hand guard. It was made from 6061 alloy aluminum and given a black anodized finish. The two halves of the mount fastened together with four flat head screws and secured to the barrel with six hex head screws.

Troy Industries, Inc. - By 2008, Troy Industries brought the M14 Battlerail to market. This was a 6061 T6 alloy aluminum M1913 Picatinny rail mount with a twelve o'clock rail running from the rear sight to its replacement front band as well as three and nine o'clock rails forward of the operating rod. The M14 Battlerail was designed to prevent binding of the barrel when installed. The M14 Battlerail was secured to the rifle at the rear end through the rear sight knob holes. The twelve o'clock rail provided sufficient clearance for

the cartridge clip guide to remain in place. This rail mount was compatible with all barrel profiles and USGI wood and synthetic stocks but not with the Troy Industries MCS chassis stock. Its integral front band precluded use with a unitized gas cylinder. The M14 Battlerail was offered in anodized black and flat dark earth colors.

Ultimak - The Ultimak Model M8 scope mount was designed to attach to a USGI, commercial or Chinese M14 standard contour barrel only. The M8 mount ran the length of the barrel from the receiver to the front band. It was a M1913 Picatinny style rail made of CNC machined 6061 T6 alloy aluminum. It was given a matte black anodized finish and marked M8 on the right side. The top of the rail sat as high as the top of the receiver barrel ring. No gunsmithing was required to install the unit. The manganese phosphate coated AISI 4142 molybdenum-chromium alloy steel barrel clamps and recoil lug were secured to the barrel by hex head screws. The entire assembly weighed 10 ounces. When replacing a USGI hand guard, it added 7 ounces weight to the rifle. Ultimak offered the M8 scope mount beginning in mid-2006.

Viron Tactical - As an accessory to its line of M14 stock models, Viron Tactical produced three barrel rail mounts, SOCOM, Scout and 22 " models. All three models used the M1913 Picatinny rail design and attached to the rifle at the cartridge clip guide. The difference between the three mounts was the length. The SOCOM model ran forward to just past the front band. The Scout model rail terminated at the front sight on a 18 " long barrel and the 22 " model did likewise for a 22 " long barrel.

McCann Industries - The McCann Industries M1A Scout scope mount debuted in June 2010. It was a three piece anodized alloy aluminum Picatinny rail mount bridging the operating rod guide to provide longer rail space. It was secured by fourteen hex head screws. The rails were marked in yellow lettering www.mccannindustries.com U.S.A. A rectangular hole must be cut into a USGI style hand guard to allow mount installation.

AMS Machine - In 2013, AMS Machine offered two barrel rail mounts. Its 4 " long M1913 Picatinny rail mount, part number A-3024, was a replacement for the Springfield Armory, Inc. M1A barrel rail mount. The firm also made a 12 " long 6061 alloy aluminum M1913 Picatinny barrel rail mount (part number A-3026). The rear end was secured using the cartridge clip guide dovetail. Both mounts were secured to the barrel using six screws.

Nordic Armoury LLC - In 2013, Nordic Armoury LLC, known as NordArm (Tallinn, Estonia), manufactured 500 mm long M1913 Picatinny barrel rail mounts for the M14. The NordArm rail mounts were used on M14 rifles issued to Estonian troops deployed to Afghanistan. The black color twelve o'clock rail mount had an integrated bipod with folding six position adjustable legs. The rear end attached to the rear sight pocket. The integral front band of the rail assembly slipped over the stock front end.

Cleaning Kit

The M14 is easy to clean even under field conditions. Springfield Armory developed and tested the issue cleaning kit for the M14 from 1958 until 1961, when the final version was fielded. The idea for the USGI cleaning kit was clearly borrowed from the M10 cleaning kit developed in the 1950s for the M1 Garand rifle. The pre-1961 M14 cleaning kit consisted of the following items: a three piece combination tool (handle, wrench head, and plastic cap), separate oiler case and grease cup, chamber brush without or with a ratchet mechanism, four M3 cleaning rod sections, a 3 " swab holder, and a M1 Garand cleaning rod case. The M1 Garand cleaning rod case was developed by early 1958. It was marked CASE B021 7162792. Before the three piece combination tool was designed, a short 3/8 " box end wrench was included. The prototypes for the final version M14 combination tool and chamber brush had been manufactured by no later than May 1960 but the oiler and grease containers were still separate items. By December 1960, the USGI M14 cleaning kit as we know it today was ready for production.

The 1961 USGI M14 cleaning kit consists of a single piece combination tool, a chamber brush, four M3 cleaning rod sections, bore brush, a 3.5 " swab holder, combination oil and grease lubricant case, a plastic spacer to separate the bore brush and swab holder, and a heavier canvas case for storing the rod sections, bore brush and swab holder. Four versions of the canvas case were made between 1961 and 1968. The small chamber of the lubricant case held about 2.5 cubic centimeters of rifle grease. The large chamber was designed to store about 7 cubic centimeters of small arms lubricating oil known as LSA (Lubricant, Small Arms). Most lubricant cases were assembled by the contractor with a gasket for the cap on the large chamber but a few had gaskets for both caps. The USGI M14 lubricant case was marked as follows: top line - LUBRICANT CASE bottom line - 7790995.

By March 1961, Worden Specialty & Machine Tool won the first contract to manufacture the M14 combination tool. During the 1960s and into the early 1970s, there were several more government contracts awarded to produce the combination tool. Chinese M14 rifles sold in the United States and Canada came with a cleaning kit. The Chinese cleaning kit is a close copy of the USGI kit except for the single compartment black plastic lubricant case.

The M1 Garand, M14 and M60 ratchet style chamber brush was designed in 1955 and patented in 1958. The M14 chamber brush is marked 7790463 on the bottom of the ratchet mechanism. M14 chamber brushes produced in 1959 and 1960 had white color ratchet mechanisms. The color of the ratchet mechanism was changed in 1961 to black. Chamber brushes issued in the BII kits, the white color ratchet chamber brushes and Harrington & Richardson subcontractor chamber brushes had a different style pressed-on lock holding the ratchet to the body. It had a machined appearance versus the press stamped look from Hertzberg & Son production after 1965. This same ratchet lock with the machined appearance was used on M1 Garand rifle chamber brushes made in 1963

by USGI contractors in Ohio. The M14 chamber brush was produced by no later than June 1960 for Harrington & Richardson. Either Mill-Rose (OH) or Better Brushes (OH) was probably the subcontractor to Harrington & Richardson for this item. The M14 chamber brush is easily confused with the M1 Garand rifle and M60 machine gun chamber brushes because of their similar size. Unless it is an emergency, those brushes should not be used in the M14 type rifle.

The M14E2 stock does not have a butt stock compartment like the M14 stock, so the M14A1 cleaning kit was placed inside an olive drab water repellent nylon pouch and carried on the web belt or inside the field pack by the automatic rifleman. The M14A1 cleaning kit pouch has a single ALICE clip for attachment to the automatic rifleman's web belt. Fifty test M14E2 cleaning kit pouches were tested by the U. S. Army General Equipment Test Activity from April 04 to August 01, 1966 at Fort Lee (VA). The pouch was recommended for use by the U. S. Army Testing and Evaluation Command on September 19, 1966. Improvements were made to the prototype design and incorporated in the production contracts: heavier weight nylon ties instead of cotton, a double-stitched ALICE clip holder and heavier thread in the seams. The improved (production) design M14E2 cleaning kit was satisfactorily tested to meet the minimum life expectancy of 120 days under combat conditions.

The 1968 contract USGI M14E2 nylon pouch is marked on the inside of the flap as follows from top to bottom: first line – CASE, MAINTENANCE EQUIPMENT second line – SMALL ARMS, M-14E2 third line – DSA 100-68-C-1853 fourth line 0465-926-6768. Most of the cleaning kit pouches from the 1968 contract were sent to the U. S. military in the Republic of Viet Nam. The 1970 contract M14A1 nylon pouch is marked on the inside of the flap as follows from top to bottom: first line – CASE, MAINTENANCE EQUIPMENT second line – SMALL ARMS, M-14-A1 third line DSA 100-70-O-1941 fourth line – 8465-926-6768 fifth line – LADY MAC CORSET CO, INC. The letters US appear on the outside of the pouch flap on both versions.

The Chinese M14 rifle butt stock cleaning kit consisted of a chamber brush, combination tool, black color single compartment lubricant case, four cleaning rod sections, a patch tip and an olive drab canvas storage case. The lubricant case had a threaded lid and rubber seal. An applicator tip was attached to the lid for applying grease. After 2004, C. J. Weapons Accessories and John Masen Company sold an imported reproduction military style butt stock cleaning kit. The cleaning rod case was marked CASE, B098-7267754. Otis Products, Inc. supplies a lightweight and compact cleaning kit for modern versions of the M14 used by the U. S. military. The advantage of the Otis Products kit is the ability to clean from the breech to the muzzle end.

In the civilian market, J. Dewey Manufacturing, Co. Inc. (Southbury, CT) makes a single piece nylon coated cleaning rod that helps the owner from scratching the bore. P&M (Oak Forest, IL) patented an injection molded plastic receiver insert which allowed bore cleaning while holding the bolt. Alternately, the bolt can be locked back while cleaning

with an empty magazine inserted into the well or an empty cartridge clip inserted into the receiver stripper guide. To quiet the rattle of the cleaning kit inside the butt stock place three .30 Caliber bore patches through the hex box end of the combination tool then stow it. Wayne Machine Inc. produces reproduction M14 chamber brushes. Sinclair International sells a Dewey Manufacturing M14 chamber brush with a hole drilled through the top ratchet portion. The advantage of this design is that it allows for a two handed pull to remove the brush from the chamber. In 2009, GG&G sold a chamber cleaning tool consisting of a slotted jag attached to a rod with a rubber handle by way of a polyethylene universal joint. The slotted jag was made from 6061 T6 alloy aluminum. The chamber cleaning tool had an overall length of 14.5 ".

USGI Tools

An assortment of maintenance tools was made for the USGI M14 rifle. The carrying case for the armorer's kit was a maple wood box with internal cutouts for each tool. The armorer's kit carrying case design was modified in 1962 by adding a storage compartment for the flash suppressor alignment tool. The cost to the military in 1988 for a M14 armorer's field service tool kit was approximately \$375.00. All USGI M14 flash suppressor nut pliers were made during one production run in 1962. Smith Enterprise, Inc. supplied combination gas cylinder lock front sight wrenches beginning in August 2005 to the U. S. Army, U. S. Navy and U. S. Air Force as a maintenance tool for the Mk 14 variant and M14SE/M21A5 rifles. These wrenches are made of 7075 T6 alloy aluminum-magnesium-zinc. The wrenches are marked as follows: first line – SMITH ENT second line has the Smith Enterprise, Inc. trademark name for the M14SE system and the third line – M14.

The 7.62 mm NATO ruptured cartridge case extractor was an improvement over the .30 Caliber model used for the M1 Garand rifle and the M1919 machine gun. The 7.62 mm NATO model is designed to be pushed out of the barrel chamber using a cleaning rod. The .30 Caliber ruptured cartridge case extractor often had claws broken when used. The 7.62 mm NATO ruptured cartridge case extractor was used for the M1918 series Browning Automatic Rifle, the M1 Garand and M14 rifles, and the M60 machine gun.

The M14 combination tool is very handy. The USGI M14 combination tool is marked: first line - COMBINATION TOOL second line - 7790769. The handle of the combination tool also holds the chamber brush and protects its bristles while stowed in the butt stock. The following tasks can be performed with this tool:

1. Tighten or loosen the gas cylinder plug
2. Tighten or loosen the rear sight knob screws
3. Remove or install the butt plate screws
4. Remove or install the muzzle stabilizer
5. Remove or install the M2 bipod
6. Act as a handle for the cleaning kit rod

7. Disassemble and assemble the bolt
8. Operate the spindle valve
9. Push cartridges from a stripper into the magazine
10. Disengage the connector lock from the operating rod spring guide for disassembly
11. Clean carbon fouling from the gas piston grooves with the screwdriver blade
12. Adjust the height of the Vltor Weapon Systems M14 Modstock
13. Tighten or loosen the Troy MCS top rail slide bolt
14. For emergency purposes, tighten or loosen the hex head bolt of the Atlantic Marketing Research Systems, Inc. # 18, Bassett Machine, Sadlak Industries, LLC, Smith Enterprise, Inc. and Vltor Weapon Systems CAS-14 scope mounts.

Bondhus Corporation (Monticello, MN) produced four multi-tools for military M14 type rifles. The Mk 14 Mod 0 tool was supplied to NSWC Crane in 2006 and the M39 EMR tool was delivered to the U. S. Marine Corps in 2007. The firm was awarded a contract by Rock Island Arsenal in 2010 for the M14 EBR-RI multi-tool. A similar tool was produced for NSWC Crane on the Mk 14 Mod 2 project. Both Mk 14 multi-tools were marked MK 14 EBR on each side of the handle. The Mk 14 Mod 0 multi-tool was sold to the public through Fulton Armory and Smith Enterprise, Inc.

Operator level tools – cleaning kit

Organizational level tools – cotton cleaning patch, fabric envelope, barrel reflector, ruptured cartridge case extractor, flash suppressor alignment tool, flash suppressor nut pliers. A set of nine headspace gauges, sizes 1.630 " to 1.638 ", is authorized as part of the M14 DMR Organizational and Intermediate Maintenance Special Tools and Equipment.

Direct Support level tools – armorer's kit (firing pin protrusion gage, bolt roller retaining ring pliers, gas cylinder piston hole NOT-GO gage, gas piston diameter NOT-GO gage, breechbore field reject gage, FIELD REJECT headspace gage, field test bolt, firing pin hole gage, and wooden case), flash suppressor alignment tool, and 7/64 " hex head L-shaped wrench. The bolt roller retaining ring pliers are marked 762 MM M14 FIELD SERVICE on one handle and 7799723 (A1) US GOVT INSP on the other handle.

Depot Maintenance (General Support) level tools – The Depot kit included: GO, 1.6375 " and NO GO headspace gages, headspace reamer assembly with crank handle, bolt assembly and disassembly tool, barrel and receiver disassembling fixture, firing mechanism assembling fixture, bolt and roller grease fitting adapter, gas port alignment gage, bore straightness gage, targeting jack gage, butt stock holes to butt plate GO gage, and torque testing gage. The bolt assembly and disassembly tool is marked 7791607 M14 M1. When the operating lever is pinned to the hole marked M14, the tool is set for use with the M14 bolt. The U. S. government purchased bore straightness plug gages in 1991 from Greene Metal Products, Inc. (then Harrison Township, MI).

Commercially Available Tools

Commercial .308 headspace gauges can be used in lieu of the military 7.62 x 51 mm gauges, but lack of a clearance cut for the ejector requires that the bolt must be disassembled to use them. Throat erosion and muzzle wear gauges have been made by Ara-Mor and Battle Arms Development. Muzzle wear gauges sold by Shooters Den in 2012 were made by Pacific Tool & Gauge, Inc. Stone Axe Engineering 7.62 x 51 mm throat erosion and muzzle wear gauges were made in 2005 and 2006. Twist drill bits (sizes P and 15) can be used by hand to remove carbon buildup inside the gas cylinder plug and gas piston. Sadlak Industries, LLC and others have attached handles to drill bits as a convenient way to clean the gas piston and gas cylinder plug. Magna-Matic Corporation (Waldo, WI) produced a line of carbon removal tools for AR-10, M16 and M14 series of rifles. These tools were made from hardened steel and plated with zinc for corrosion resistance. The M14 rifle carbon removal tool, the CRT-14, was introduced in 2011. It consisted of two parts, a wrench for holding the gas cylinder plug and the gas piston and a tool with a handle and three dead-stop reamer ends for cleaning the gas cylinder plug and the gas piston gas port and internal cavities.

A 1/16 " hex head wrench is used to remove or install the flash suppressor setscrew. A 7/64 " hex head wrench will fit the front sight screw and Springfield Armory, Inc. Scout Squad forward scope mount screws. USGI early version and some commercial manufacture front sight screws will take a 3/32 " hex head wrench instead. A 3/32 " pin punch is useful in removing the cartridge clip guide pin and the magazine latch pin. To install the selector switch use a 1/16 " pin punch to drive the roll pin out of the selector lock. Wayne Machine Inc. has produced reproduction ruptured cartridge case extractors and flash suppressor nut pliers. The tools necessary to remove and install a barrel are available from Brownells, Inc. Badger Ordnance produces a gas cylinder-to-barrel gas port alignment gage, a stock liner screw wrench, hand guard band pliers and two models of bolt roller greasers. AIM Sports, Inc. made flash suppressor nut pliers and hand guard band pliers of steel construction.

Strobel has produced a bolt disassembly tool that can be used for M1 Carbine, M1 Rifle and M14 Rifle bolts. It was made of aluminum and marked on the side: top line - M1 M14 CARBINE bottom line - STROBEL. In October 2009, a gunsmith (British Columbia) made available a new design bolt disassembly tool for M1 and M14 Rifles. This tool required use of a 1/8 " hex head wrench to secure the top cover over the bolt and a 5/64 " hex head wrench to push on the bolt from the middle of the top cover to fix a bolt in place. A 3/16 " hex head wrench was then needed to push the ejector into the bolt and the extractor out of the bolt for disassembly. This bolt disassembly tool was machined from 6061 T6 alloy aluminum and given a hard anodized coating. It was marked M14 DOCTOR MADE IN CANADA on one side. The same year, Brownells began making a reproduction USGI bolt assembly and disassembly tool. It had a steel handle and an aluminum body.

Fulton Armory offers an anodized alloy aluminum gas cylinder lock wrench. Sherluk markets a carbon steel gas cylinder lock wrench. Sadlak Industries, LLC manufactures CNC machined alloy aluminum and carbon steel gas cylinder lock wrenches, a scope mount hole thread chase tool and a scope mount hole repair tap. The gas cylinder lock wrench from Smith Enterprise, Inc. is made from hard anodized alloy aluminum and marked SMITH ENT. Commercial reproduction gas cylinder locks are slightly wider than USGI and Chinese gas cylinder locks. Thus, some gas cylinder lock wrenches, as manufactured, will not fit commercial reproduction gas cylinder locks.

A true M14 rifle multi-tool was designed and made available in mid-2009 by Battle Arms Development, Inc. (Henderson, NV). The BAD-T1 multi-tool had thirty uses for the M1 and M14 rifles. It was made from precision machined 41L40 chromium-molybdenum alloy steel heat treated to 50 to 52 HRC. From August 2010 onward, the BAD T-1 was produced with a chemical vapor deposition finish. It weighed 0.42 pounds and could be stowed in the USGI M14 stock storage compartment or in its MOLLE compatible nylon carry pouch. The carry pouch weighed 0.18 pounds. Battle Arms Development, Inc. quickly followed up in the fall of 2009 by producing the T-3 and T-4 gas cylinder lock wrenches. Both gas cylinder lock wrenches were made from 7075 T6 alloy aluminum with a hard anodized finish. Both gas cylinder lock wrenches were double-ended with gas piston and gas cylinder plug holders in the center. The T-3 was suitable for the M1 Garand, USGI M14 and M1A gas cylinder locks. The T-4 was used for USGI M14 and M1A gas cylinder locks and Smith Enterprise, Inc. gas cylinder lock front sights.

USGI Accessories

A number of accessories supported the various roles filled by the M14 rifle. These included the M2 bipod, M3 breech shield, M5 winter trigger assembly with or without safety, M6 bayonet, M8A1 and M10 scabbards, M12 blank firing attachment, M15 grenade launcher sight, M76 grenade launcher, M151 and M35 vehicle rifle mounting kits, M2 aiming device, M2 bandoleer kit (magazine filler, cartridge clips, cardboard sleeves and canvas carrier), empty chamber indicator, front and rear sight and operating rod protectors, Mk 87 Mod 1 line (rope) throwing kit, sling (M1907 leather, canvas web, hard nylon weave, and soft nylon weave), and a watertight carrying case for the XM21 ART scope. The winter trigger is marked WINTER TRIGGER M5 on one side and 7790808 on the other. The XM152 winter trigger kit was available for the M14A1.

The Universal Rifle Rack was patented in 1942 to securely stow rifles and submachine guns in jeeps and other military vehicles. It consisted of a spring-loaded long metal bracket contoured to fit any of several U. S. military small arms and a rubber padded cam-locking metal arm. It was in use from World War until the mid-1970s by the U.S. Army and even later by the U. S. Air Force. The design of the Universal Rifle Rack allowed quick retrieval because it was designed for military purposes.

The apparent successor to the Universal Rifle Rack was the M151 vehicle mounting kit. The mounting kit for the M151 vehicle secured the M14 rifle vertically on the front passenger side. The major parts of the kit, butt socket, upper support bracket and spring loaded clamping bar, were coated with plastic to protect the rifle. By 1969, the butt socket was redesigned to fit both M14 and M16 rifles. The mounting kit was also installed on U. S. Army helicopters assigned to combat operations in the Republic of Viet Nam.

The M2 aiming device was made by Weaver Manufacturing, S. I. Howard Glass Co., and a third contractor. Only the Weaver Manufacturing contract aiming devices had a marking, WEAVER B174999.

There were two models of the ART scope and mount carrying case for the XM21/M21. Both versions of the ART scope and mount carrying case were waterproof. The case lids were fitted with a gasket or seal to protect the scope from moisture or immersion. Both versions of the case also had rubber cushions to protect the scope against physical shock. The first carrying case, used during the Viet Nam war, was made of 6061 T6 alloy aluminum and painted olive drab. The first version carrying cases were made by Frankford Arsenal beginning in 1968. It attached to the load bearing equipment belt by use of a single ALICE clip. The second version of the carrying case was made of green color fiberglass and issued with the ART II scopes. The fiberglass carrying case was secured to the user by looping the load bearing belt through the case canvas strap. The AN/PVS-2 carrying case was made of waterproof fiber reinforced neoprene. It had two ALICE belt clips and tie down straps.

Slings - The M1907 leather sling was issued with the M14 M, M14 NM, XM21 and M21 rifles. The M1907 leather slings were marked MRT and some were marked with a date code. MRT stood for Mildew Resistant Treatment meaning the sling had been chemically treated. The USGI M1907 sling was 47.56 " long. The M1907 sling consisted of two leather straps each with a metal hook at one end. The two hooks were made of phosphate coated ASTM A109 steel. M1907 type slings with brass hooks are commercial reproduction units. M14SE system leather slings are marked as follows: first line has the Smith Enterprise, Inc. trademark name for the M14SE system second line – SMITH ENT. third line – M-14 fourth line M-118 LR. A Defense acceptance stamp is centered between the second and third lines.

One USGI contractor for M1907 slings and leather pistol holsters was Cathey Enterprises, Inc. (3423 Milam Drive Brownwood, TX 76081). Cathey Enterprises, Inc. made pistol holsters for the U. S. Army in the 1960s and M1907 slings for the U. S. Army under a 1986 contract. The firm closed its doors about 1998 after thirty years of successful business when its founder, George M. Cathey, retired. His wife, Lila, established Hill Country Leather in January 1999 to carry on the family tradition of producing quality leather firearms accessories. Day-to-day operations for the business are managed by the couple's daughter, Laurie Perkins. Hill Country Leather has completed several government contracts. The firm manufactures nylon web magazine

pouches and web belts and reproduction M1907 slings, M1 Garand cheek rests, and military pattern pistol holsters for the commercial market.

The fabric one piece gun sling was patented in 1944. At the time, there were five requirements for a military rifle sling: 1) parade or close order drill 2) shoulder carry 3) cross-back carry 4) arm loop sling for accurate fire 5) hasty sling for firing. The length of a military gun sling had to be long enough to accommodate the largest soldier carrying the largest pack on his back yet be useful as an arm loop sling for the soldier with the shortest arms. By relying on the hook ends to adjust the sling length, the M1907 sling was not a good fit for the soldier in some situations. The one piece gun sling was an advancement over the M1907 sling in that one end was no longer needed for adjusting the length. The minimum length of the sling was then dictated solely by the length needed for a cross-back carry by the largest soldier carrying the largest pack. The one piece gun sling fabric construction and metalware made it easy and quick to adjust for the user and economical to manufacture.

The M1 Gun Sling was made of canvas web. Some canvas web slings have the same MRT marking as the M1907 sling as well as a month and year date stamp on the metal tip, such as 4 64. The last USGI canvas web slings were made about 1966. It was known as the M1 Gun Sling and weighed 0.3 pounds or about 5 ounces. Subsequent slings, known as Small Arms Sling, have a different National Stock Number and are made of nylon weave material. The hard nylon weave sling was introduced in 1969. The first soft nylon weave sling was produced for the U. S. Navy about 1973.

The hard nylon weave sling had cadmium plated fittings. The soft weave nylon sling had cadmium plated fittings as well until the 1990s. In recent years the soft nylon weave sling has been made with phosphate coated fittings. The M1 Gun and Small Arms Slings have a metal clamp designed to attach to the stock rear sling swivel. The free end is looped through the stock front sling swivel then secured in the sling keeper. The M14E2 sling was made of canvas and longer than the standard small arms sling. It had two clamps instead of one and weighed 0.4 pounds or about 6 ounces. The clamps attached to the M2 bipod sling swivel and the M14E2 hand grip assembly. Chinese M14 rifles sold in the United States and Canada came with a canvas web khaki color sling with gloss black hardware.

Bayonet - The M6 bayonet was used for close combat, guard duty, riot duty, and as a general utility knife. The final production drawing for the M6 is dated January 24, 1955. Thus, the T12 bayonet was developed and adopted as the M6 bayonet even before adoption of the M14 rifle in May 1957. Initially, the decision was made that there would be no bayonet issued for the M14 rifle. So, the M6 bayonet was not produced in significant numbers until 1961. Eventually, 1,633,000 M6 bayonets were delivered to the U. S. Army between July 1961 and February 1969. Aerial Cutlery, Imperial Knife Company, and Columbus Milpar and Manufacturing Company all made M6 bayonets. Imperial Knife made the most M6 bayonets of the three contractors and Aerial Cutlery

made the fewest. Columbus Milpar and Manufacturing Company made M6 bayonets in 1962 and possibly later. Imperial Knife Company was the last known contractor for the M6 bayonet with its final delivery to the U. S. Army in February 1969. Beware that there are commercial reproduction M6 style bayonets marked AERIAL and IMPERIAL. In the early 1980s, several surplus parts dealers financed a production run of M6 bayonets by Imperial Knife Company. The commercial run Imperial M6 bayonets will not have a Defense Acceptance Stamp. A fourth M6 bayonet marking, AN, has been observed but the manufacturer has not been positively identified. Staff Sergeant John Chalker, New York National Guard, carried a M6 bayonet for his M14 rifle while conducting convoy escort duty in February 2005 in Khadimiyah, Iraq. Around 2010, M6 bayonets with counterfeit markings began circulating in the commercial market. They are identified by the marking PAKISTAN on the tang under the handle grips. Eichorn-Solingen (then West Germany) produced M6 bayonets for the government of Haiti but instead sold them to the commercial market. The President of Haiti, Jean-Claude Duvalier, was exiled in February 1986 before delivery of the order was due.

Out of the packaging, the blade bevel angle on Columbus Milpar and Manufacturing Company M6 bayonets typically requires more stoning to hone the edge than the other two M6 bayonet manufacturers. The bayonet blade material is AISI 1080 high carbon steel and the grip is made of molded plastic. Its weight is 12 ounces. The overall length is 11.51 " with a blade length of 6.75 ". The bayonet is designed to be loose when attached to the M14 rifle in an effort to minimize its effect on the bullet point of impact. The internal parts of the M6 bayonet are interchangeable with the M5 bayonet which is used on the M1 Garand rifle. Lubricate the M6 bayonet with CLP for temperatures down to - 10 degrees Fahrenheit. For temperatures below - 10 degrees Fahrenheit, leave the metal surfaces dry.

Is Your Bayonet Combat Ready? - The U. S. Army maintenance inspection for the M6 and M7 bayonets required soldiers to check the following: 1) handle latches had to snap back when depressed and lock the bayonet securely to the rifle 2) no rust or corrosion allowed on the metal 3) no nicks in the blade edges 4) misalignment between the blade and the handle could not exceed 3/16 " 5) the bayonet hand guard was allowed to be slightly loose.

Scabbard - One manufacturer of the M8A1 scabbard was Victory Plastics Company (Hudson, MA). Victory Plastics produced M8A1 scabbards in 1953 (for the M1 Garand rifle) and in 1961. Its 1961 production scabbards have the metal tip protector while those made in 1953 do not. Victory Plastics went out of business in 1964.

The metal tip protector was added to scabbards made after 1955. The phosphate coating on the 1961 scabbards is lighter gray and more granular than on the 1953 scabbards, and the webbing is a darker green with a lighter sewing thread. Viz Manufacturing had a contract in 1967 to produce M8A1 scabbards. Another contractor was Pennsylvania Working Home for the Blind who made M8A1 scabbards between 1966 and 1968.

Scabbards made by Pennsylvania Working Home for the Blind in the 1970s are marked TWB because the business's name was changed to The Working Blind. Eichorn-Solingen manufactured M8A1 scabbards for the government of Denmark with both British and U. S. compatible belt attachments and for the government of Haiti with the U. S. compatible belt attachment. Eichorn-Solingen M8A1 scabbards did not have the metal tip protector. Eichorn-Solingen M6 bayonets and M8A1 scabbards were never U. S. government issue.

The M10 scabbard was issued on a replacement basis for the M8A1 scabbard in the U. S. military by no earlier than 1983. The M10 scabbard can be used with the M5, M6 or M7 bayonets. The M10 scabbard was produced by General Cutlery under U. S. government contract as late as 2002. USGI contract M10 scabbards are black in color. An Imperial Knife M10 scabbard is marked on the back M10 then adjacent to that: top line - 19204 ASSY 8448476 bottom line - MFG 74846. 19204 is the CAGE Code for Rock Island Arsenal. Reproduction M10 scabbards have been made in tan color.

Bandoleer Kits - Each bandoleer kit contained one M2 bandoleer, twelve cartridge clips, six cardboard inserts, one magazine filler and one large safety pin. The M2 bandoleer is made of olive green cotton fabric sewn into six pockets and attached at both ends with a sewn-in carry strap. It will hold twelve cartridge clips, two clips in each of six pockets. Each pocket has a flap for easy access. Each cartridge clip will hold five rounds of ammunition, for a total of sixty rounds. The cartridge clips were placed two to a cardboard insert inside each of the pockets. The purpose of the cardboard insert was to prevent the ammunition from tearing or cutting the cloth bandoleer during movement such as would occur if a soldier was running with a bandoleer slung over his shoulder. The 1974 design four pouch M8 bandoleer for the M16 rifle will hold four M14 twenty round magazines, one in each pocket.

The M14 magazine filler was based on the charger made for the M1 Carbine. There were two versions, the early version was developed in 1958 and the late version was designed in 1961. The late style magazine fillers were marked with the manufacturer's marking on the first line and 7791154 on the second line. The late style also had a reinforcing rib on the rear side. The reinforcing rib allowed the magazine filler to withstand a minimum loading of 45 pounds without breaking or cracking as it pushed downward into the cartridge clip guide. The addition of the reinforcing rib implies the early version magazine filler was not sufficiently robust.

Usually, but not always, U. S. made 7.62 x 51 mm NATO ammunition cartridge clips were stamped with the manufacturer's marking on the rear side. There may be an exception, but as a general rule the U. S. never placed a date code on 7.62 x 51 mm NATO ammunition cartridge clips. Ammunition could be manufactured several years apart from the cartridge clip so there would be no benefit in date coding the cartridge clips. 7.62 x 51 mm NATO ammunition cartridge clips made in the United States have one stop or nib on each side and hold five cartridges. .30 caliber ammunition cartridge clips with two or

three nibs on either side were not manufactured in the United States. Australia and all NATO member countries, including the United States, only made five round cartridge clips for 7.62 x 51 mm NATO ammunition.

Five round cartridge clips made in the People's Republic of China were marked MTY 60. These black phosphate coated cartridge clips have been found in ammunition containers of the Chinese made British (RG 60 L2A2 head stamp) marked ammunition exported in the 1980s. Tapco, Inc. (Kennesaw, GA) has imported Chinese made five round cartridge clips, packaged fifty to a box. They had a blued appearance and no manufacturer markings. Both types of Chinese five round cartridge clips have one nib on each side. Ten round cartridge clips have been made in the People's Republic of China for New Century Science & Technology, Inc. (City of Industry, CA formerly in El Monte, CA). The Chinese ten round cartridge clips have two nibs on each side and a medium gray color. They were packed twenty to a retail display package. Cartridge clips made outside of Australia or NATO member countries were sometimes cheaply made as they may have sharp corners and edges and varying dimensions.

Grenade Launcher Sight - The M15 grenade launcher sight was used on the M1903 Springfield and M1 Garand rifles and carried over to the M14. It was designed by John C. Garand and others in 1945. M15 grenade launcher sights were made before 1957 by Boehm Pressed Steel (Cleveland, OH), Pressure Lube, Inc. (New York, NY), Slaymaker Lock Co. ((Lancaster, PA) and Western Newell Mfg. (Fremont, IL). The M15 sight base was mounted to the M14 stock on the left hand side with two wood screws. The M15 sight could be installed or removed quickly from the sight base by the grenadier. A canvas pouch with M1910 hooks attached to the web belt for carriage of the M15 sight and instruction sheet.

Blank Firing Attachment and Breech Shield - The M12 blank firing attachment (BFA) was issued to the individual soldier for training purposes, along with the M3 breech shield. The M12 BFA is a simple device used to operate the M14 rifle for training purposes without sending bullets down range. It is a metal stem, or orifice tube, that is long enough to enter the barrel a short distance from the muzzle end of the flash suppressor. The orifice tube is hollow so that gunpowder residue and gas from the fired M82 blank cartridge is restricted as it flows out of the barrel. The flow restriction of propellant gas creates enough pressure to fully cycle the bolt. The orifice tube is attached to the rifle by a sheet metal spring that fits over the bayonet lug.

The BFA will function as designed with U. S. made M82 blank cartridges above 0 degrees Fahrenheit. In subzero temperatures, the bolt may not fully cycle resulting in failure to feed or failure to eject stoppages. No other type of ammunition should be used in the rifle with the M12 BFA installed. Care must be taken to prevent use of bulletted cartridges if the BFA is installed. Otherwise, damage to the rifle will occur. The M12 BFA will not cycle the bolt using Canadian and European blank cartridges. Service life of the BFA is dependent upon the rate of fire and the time of cooling allowed. The M12 BFA will last in

excess of 5000 rounds at a firing rate of ten rounds (three or four round bursts) per minute with complete cooling every 1000 rounds. More severe firing rates accelerate gas erosion of the rear end of the orifice tube.

The M12 BFA will not cycle the bolt if installed on a rifle with a National Match dimension flash suppressor. Additionally, the M12 BFA tube will not fit all the way into a T44E4 or early M14 flash suppressor. The early M14 flash suppressor, part number 7267088, did not have an inside diameter large enough at the rear end to allow the M12 BFA tube to be fully inserted. Springfield Armory drew up a new flash suppressor design, part number 7791053, in September 1960. The inside diameter shoulder at the rear of the suppressor was done away with to allow use of the M12 BFA with the flash suppressor. The M3 breech shield was intended to protect the shooter from any blow back particles when firing blank ammunition, and to prevent loading live ammunition through the cartridge clip guide.

There were three versions of the M12 BFA and two versions of the M3 breech shield. The first version BFA was packed with the early style breech shield. These were produced in 1962. The second version blank firing attachments were packed with the early style breech shield in 1964 and the late style breech shield in 1968. The first and second versions were later modified at the General and Direct Support levels by riveting a curved 1/8 " thick piece of steel to the horizontal surface of the spring latch. The steel strap was curved at the front end in order to dissipate gases exiting the muzzle. The M12 BFA modification was implemented with Change 2 to TM 9-1005-223-35 dated February 03, 1970.

The third version of the BFA was made from 1969 to 1973 and packaged with the late style breech shield. Two companies made all the M12 blank firing attachments, East Moline Metal Products Company and Hesse Machine & Mfg. Co. East Moline Metal Products made some M12 blank firing attachments in 1973 at the end of its production that were phosphate coated instead of painted orange and silver.

Line Throwing Kit - The U. S. Navy Mk 87 Mod 0 and Mod 1 kits allow the M14 rifle to reliably launch a nylon cord attached to a butyl rubber projectile up to 90 yards. The projectile will travel 55 yards with the M14 fired horizontal to the surface and 90 yards if shot at an angle of 45 degrees. The launcher is attached to the M14 by a wire loop that is placed around the bayonet lug and secured by the safety retaining pin. Once the projectile with the attached nylon cord has been launched from one ship to another, a line (heavy rope) for underway replenishment chores can be pulled from the first ship to the second. The Mk 87 Mod 1 line throwing kit consists of one launcher, one butt stock recoil pad, six reusable projectiles, eighteen chemical light wands, one wound spool of 550 feet of 125 pound test orange color water repellent nylon cord and an optional canister to hold the spool of nylon cord. The line throwing kit requires the use of M64 grenade cartridges. The butyl rubber projectiles have a stainless steel disk on the rear end to absorb the cartridge propellant gases and wadding. For night time use, an activated chemical light

wand is inserted into the butyl rubber projectile. This helps the ship's crew on the receiving end find the front end of the nylon cord after launching. Operation and maintenance of the Mk 87 Mod 1 kit is detailed in NAVSEA SW350-A1-MMO-010.

While not made for the M14 rifle specifically, in the 1960s the U. S. military issued a canvas web Universal Rifle Case. The universal rifle case could hold a scoped rifle such as the M1903A4, the M1C, the M1D, the XM21 or the M21. There were two versions of the rifle case. One version had leather reinforcement points and was marked: first line - UNIVERSAL-RIFLE-CASE second line - D78926. The other version had double thick canvas reinforcement points and was marked: first line - RIFLE CASE, UNIVERSAL second line - ORD. PART NO. 6578296. Both cases had full length stainless steel zippers.

The canvas M1950 individual weapons case was made for Army paratroopers. This case could hold a M1 Garand or M14 rifle. Some M1950 cases were produced in 1968 under a Defense Supply Agency contract. This was a U. S. Army Quartermaster Corps item.

Commercial Accessories

Commercial accessories in the market have included bipods, brass catchers (canvas and plastic), butt stock recoil pad, dual magazine clamp, elevation sight repair disk, front and rear sight protectors, keyed cable lock, gun cases, magazine loader and unloader, magazine pouches, recoil buffer/reducer, slings, stock comb/cheek rests, trigger shoes, vinyl magazine covers and even a gadget. From 1995 to 2004, Springfield Armory, Inc. sold a combination stock liner disassembly tool and multipurpose screwdriver known as the M1A gadget. In the fall of 2011, BTP Arms offered a reproduction M3 breech shield and second version M12 blank firing attachment.

Reproduction operating rod handle, muzzle and rear sight protectors and the chamber flag have been produced in green and in white. Reproduction (and USGI) operating rod handle, muzzle and rear sight protectors were marked with the appropriate USGI part numbers on them, 7790231, 7790232 and 7791358, respectively. The green color sight protectors were made overseas.

Shooters can purchase dry fire devices in the civilian market for practicing trigger squeeze, shooting position, and competition courses of fire. However, Springfield Armory, Inc. offered a pneumatic shooting simulator in the 1990s. A switch mounted behind the trigger activated injection of compressed air or carbon dioxide into the gas cylinder to cycle the bolt and operating rod. The purpose of this device was to allow realistic recoil movement of the rifle during dry fire practice. A cylinder was threaded into the gas cylinder in lieu of the gas cylinder plug. The forward end of the cylinder was connected to a hose that ran to a source of compressed gas at 50 to 120 PSI.

B.Jones Sights makes a prescription lens insert for the hooded National Match rear sight aperture. Buffer Technologies (Jefferson City, MO) markets a patented recoil buffer for the M14 type rifle. Marstar Canada sells a Canadian made recoil buffer for M14 owners (catalog number M14-101). Rubber recoil pads for USGI design M14 stocks have been available from John Masen Company, Hogue, ProMag Industries and Pachmayr. Tyler Manufacturing & Distributing Co., Inc. (Oklahoma City, OK) offers alloy aluminum and manganese bronze trigger shoes (size 11) for the M1 Garand / M14 trigger. Smith Enterprise, Inc. offered a zippered nylon M14 tool pouch beginning in 2011. Magblock, LLC sells U. S. made blocks to limit twenty round magazines to ten rounds capacity. The bottom end of the spring is inserted through a hole in the block. Thus, no magazine modification is needed.

Fabric Cheek Rests - There are several fabric material rifle stock cheek rests available for the M14 type rifle. The fabric cheek rests are secured by adjustable straps and plastic buckles, hook and pile fasteners or by lacing run through eyelets. Fabric cheek rests come in various colors, black, brown, coyote tan, olive drab green and Army Combat Uniform digital, desert, or woodland camouflage. Suppliers include BlackHawk Products Group, Eagle Industries, Fulton Armory, ITC, Smith Enterprise, Inc., Stitchery of West Virginia and Tactical Night Vision Company. Charles A. Finn (Oceanside, CA) patented an adjustable cheek rest for long guns that has a pouch for storage of small items. This patented design is one of several rifle cheek pads distributed by BlackHawk Products Group. The RSP Mod 0 cheek rest from Tactical Night Vision Company includes a single twenty round magazine pouch and a protected transparent sleeve pocket for range data cards. A cheek rest with the ability to raise the comb height is recommended for M14 type rifles fitted with telescopes and traditional contour stocks. Otherwise, the shooter typically does not achieve proper cheek weld.

Plastic Cheek Rests - In the early 2000s, Karsten's Custom Camo and Rooster33 produced hard plastic black color cheek rests for M14 stocks. Both models had vertical grooves to facilitate adjustment of the comb height. These cheek rests were secured using two bolts and nuts or knobs passing through two radial holes in the butt stock.

S & J Hardware (Ontario, Canada) introduced its cheek rest to the Canadian market in July 2009. The S& J Hardware cheek rest was made from black color thermoplastic acrylic-polyvinylchloride. This type of plastic material provided a smooth, rigid, waterproof, and scratch resistant surface that could be adjusted and painted to the operator's liking. Like the previously mentioned designs, it had two vertical grooves for height adjustment and it was secured to the stock using two bolts. The S&J Hardware model differed though in that the nuts were replaced with CNC machined and hard anodized 7075 T6 alloy aluminum knobs for quicker height adjustment.

In December 2009, Tac Pro, Inc. (Ontario, Canada) brought its unique design cheek rest to the commercial market. The cheek rest was designed with input from a former Israeli Defense Force M14 SWS sniper. The Tac Pro, Inc. thermoplastic acrylic-

polyvinylchloride cheek rest was given an asymmetrical shape at the top to better align the shooter's eye to the ocular lens of the scope. The cheek rest is precision formed using CNC machined molds. At its lowest setting, the Tac Pro, Inc. cheek rest may be used comfortably with the iron sights. It is secured to the butt stock by two stainless steel bolts. The cheek rest is marked TAC PRO INC on the symmetrical side.

Slings - Turner Saddlery, Les Tam, Ron Brown, and John Weller M1907 style slings were highly regarded by M14 enthusiasts. The Turner Saddlery biothane M1907 sling was available in a choice of black, dark brown, olive drab green or tan. Les Tam M1907 style slings could be ordered with brass, phosphate coated steel or stainless steel hooks depending on the model. Turner slings were fitted with phosphate coated steel hooks. Ron Brown Custom leather slings were available in natural, saddle tan, dark brown, or hand color dyed camouflage. Mr. Weller offered his M1907 style slings in a choice of black, natural or ox blood colors with either brass, steel or stainless steel hooks. High quality tactical and patrol carry nylon M14 rifle slings of various configurations were available from Best Made Designs, LLC, Specter Gear or Tactical Intervention Specialists. AIM Sports, Inc. sold a reproduction tan color cotton M1 Garand sling.

maglula, Ltd. (Rosh Ha'ayin, Israel) manufactures a patented magazine loading and unloading device for the M14 and other military small arms. It came to the U. S. market about 2006. The maglula M14 magazine loading device was given a five of five stars rating from Midway USA customers. In 2006, ProMag Industries produced a polymer ammunition loading device suitable for M14, AR-10 and G3 rifle magazines (product code PM080). Later, a redesigned loader was offered for the M14 (PM186).

Magazine Pouches – Commercial reproduction ALICE system M14 magazine pouches have been made in black, green and tan colors. The U. S. Army Modular Lightweight Load-carrying Equipment (MOLLE) system was introduced to the U. S. Armed Forces in 2001. With the new load bearing equipment came the need for new accessory pouches of all sorts including 7.62 mm NATO magazine pouches. The following companies have made MOLLE system compatible 7.62 mm NATO magazine pouches: Atlantic Diving Supply, Inc., Best Made Designs, LLC, BlackHawk Products Group, Eagle Industries, Knight's Armament Co., MSA Paraclete Armor & Equipment Co., S.O. Tech, Tactical Assault Gear, Tactical Tailor and Tuff Products. These pouches could carry magazines for several rifle models: M14, AR-10, Mk 11, M110, FN FAL, SCAR 17 and H&K-91. The pouches were made from canvas or nylon and came in various colors. Many of the pouches were issued National Stock Numbers. Typically, 7.62 mm NATO magazine pouches held one or two magazines but some held more. The X4 and X6 pouches by Best Made Designs, LLC held three and five magazines, respectively. Tuff Products made two 7.62 mm NATO magazine pouches, one for five magazines and the other retained eight magazines. In 2006, Best Made Designs, LLC. offered a M14 butt stock magazine pouch. M14 Mag Bag (Sumrall, MS) introduced, in November 2010, leather load bearing equipment for the M14. The M14 Mag Bag leather goods were made from quality vegetable tanned cowhide. The leather belt, suspenders, bayonet sheath, and

magazine and accessory pouches were available in four colors, natural, oiled, black and sunburst (reddish-brown).

Adjustable Gas Plugs - Rich Schuster (Toledo, OH) designed and makes Schuster Nuts. These are aftermarket M14 type gas cylinder plugs that can be used in competitive shooting. The top of the plug has a vent hole drilled to 0.015 " diameter. The interior diameter of the plug is larger than the standard M14 gas cylinder plug. This allows the gas pressure to drop about 2600 psi (equivalent to the effect of reducing a cartridge's charge weight by ½ grain of powder). The result is less wear and tear on the rifle through lower initial pressure and less vigorous operation of the gas system. By adjusting a nut inside the plug, the net volume of gas in the cylinder is changed. This in turn changes the speed of the operating rod and the harmonics of the barrel vibrations. M14 gunsmith Clint Fowler (Barboursville, VA) and Derrick Martin (Accuracy Speaks in Mesa, AZ) can supply adjustable gas cylinder plugs for the M14 type rifle. These adjustable gas plugs use socket screws to vary the size of the opening in the top. Thus, the competition shooter can set the amount of gas venting to maximize accuracy and minimize wear.

M2 Type Bipods

The M2 bipod design was standardized in December 1959 and improvements were added later. It was modified several times in the 1960s and 1970s as the bipod for the CAR-15 Heavy Assault Rifle M1, CMG-1, CMG-2, XM106, and XM235 experimental weapons. Made of steel, the USGI M2 bipod weighed 28 ounces. M2 type bipods have been produced in the United States, Taiwan and China. Chinese copies of the M2 bipod do not have as excellent a reputation as compared to the USGI and Taiwanese models.

Taiwan models - The Taiwanese M2 bipod is reliable and suitable for civilian use. It was available commercially by the late 1980s. Around 1998, some Taiwanese M2 bipods were sold to the U. S. Navy by Sarco, Inc. (CAGE Code 8R320). Taiwanese M2 bipods are made by Wayne Machine Inc. of Taipei, Taiwan. Early Taiwanese bipods were brazed but failed routinely. The early Wayne Machine, Inc. M2 bipods were marked S A BIPOD M2 or BIPOD RIFLE M2 on the head assembly. Otherwise, Wayne Machine, Inc. M2 bipods were welded together and will hold up to thousands of rounds of automatic fire. Later (welded) Wayne Machine, Inc. bipods were marked BIPOD RIFLE M2 or W M I BIPOD RIFLE M2 on the head assembly. Taiwanese late version M2 bipods sold by Sarco to the U. S. Navy do not have the W M I mark.

A few Taiwanese M2 bipods were installed on M14 rifles and used in combat in Afghanistan in 2005. Seven of these bipods were removed from combat service in July 2005 because each suffered the loss of the retaining pin holding the spring and button in one of the leg folding pushbutton assemblies.

Chinese models - The Chinese M2 bipod was marketed by Norinco beginning in 2003. The Chinese version was marked W M I BIPOD RIFLE M2 on the head assembly similar

to the copy made by Wayne Machine, Inc. If the locking bolt accepts a hex head wrench less than 3/8 " size, it is a Norinco bipod. AIM Sports, Inc. marketed a reproduction steel construction M2 bipod (catalog number BPM14) in Canada and the United States starting in 2011. In 2009, New Century NcStar, Inc. (previously New Century Science & Technology) introduced a hybrid M2 bipod for the M14 rifle. It was very similar to the M2 bipod except that its attachment mechanism was unique. The M14 Quick Release Bipod attached to the rifle by way of the NcStar design quick release system that allowed removal or attachment of the bipod with a single push button. It could attach to any Weaver or Picatinny style rail or to the M14 rifle barrel itself. The NcStar M14 Quick Release Bipod (catalog number ABUQ14) was made from steel and aluminum parts.

ProMag Industries - As of 2007, ProMag Industries was producing its own M2 bipod (product code PM019). It was made from high carbon steel and marked PM BIPOD RIFLE M2.

USGI models - USGI M2 bipod parts were made of carbon or alloy steel depending on what the drawing specified for the part. A USGI M2 bipod will likely be of brazed construction for the most part. The leg shoes or pads were always arc welded to the bottom of the leg extensions. When deployed, the leg shoes act as skids when the rifle is moved laterally. The furnace brazed joints on the leg shafts had to withstand an applied tensile load of 2,000 pounds without separating. Similarly, the head assembly brazed joints were tested with a load of 3,500 pounds. Alternately, the head assembly plates could be arc welded to the leg assemblies. The welds and the jaws were examined for defects by the wet process magnetic particle inspection method.

A phosphate coating was applied to all surfaces of the bipod. USGI M2 bipods left the factory with a yellow DOD acceptance stamp and four blue letter M markings, one on the bottom of each leg pad and one on the outside of each jaw. The blue letter M signified satisfactory results from non-destructive examination. The yellow DOD acceptance stamp was applied to either the front or the rear head assembly plate. The yellow and blue markings tended to wear off with use in the field and are rarely seen on bipods found today. An American made USGI contract M2 bipod will have the following markings on the head assembly: U. S. 7790688 BIPOD RIFLE M2 or U. S. 7790833 BIPOD RIFLE M2.

The USGI contract manufacture M2 bipod was initially produced without a sling swivel. The sling swivel was added to the M2 bipod by no later than 1962 for testing of the M14 (USAIB). This modified M2 bipod was made part of the M14 (USAIB) Technical Data Package in September 1963. It carried over to the M14E2 (later M14A1) Rifle. M2 bipods were later manufactured with a sling swivel. Sling swivels were also added to M2 bipods while in service through a Modification Work Order or a Direct Support level field modification. M2 bipods with swivels will have a longer pin to secure the swivel to the head assembly. Some early USGI M2 bipod locking bolts do not have a screwdriver slot. The M2 bipod was revised in February 1967 to add a small screw and nut to the top of

each leg extension. In March and April 1967, the bipod jaw drawings were revised for improved grip.

Other Bipods

In 1979, Rock Island Armory (Geneseo, IL) produced and sold a reproduction T44 Type II bipod (referred to as a Type I bipod in other references). The item was marketed as BIPOD, M1. This bipod attached to the bayonet lug of any M1 Garand or M14 type rifle. Reportedly, 200 of the BIPOD, M1 units were made. They retailed for \$42.00 each.

Harris bipods are often mounted to the rifle's stock just aft of the front sling swivel. A hole is drilled in the stock to which a Harris adapter is fitted and secured. The stock forearm may or may not be reinforced as desired. The 5/16 " diameter drain hole located 1 " behind the stock ferrule may also be used as an attachment point. Either way, this method of attachment avoids changes in point of impact that may occur with the M2 bipod. Another means of attaching a bipod is to replace the USGI sling swivel and bracket with a M14 six o'clock Picatinny rail adapter such as those offered by GG&G, Sadlak Industries, LLC, Smith Enterprise, Inc. or Vltor Weapon Systems (part number QDM-14). Modern bipods like the Harris HBRM-S, GG&G Heavy Duty XDS, and TangoDown ACB-4 models weigh 16 to 17 ounces.

The 5/16 " diameter drain (not vent) hole behind the stock ferrule is an acceptable location to mount a bipod. According to M14 gunsmith Ted Brown [minor spelling and punctuation errors corrected]:

Actually, the hole is not meant to bleed off gas from the gas cylinder. All of the gas is blown back on to the stock and vents between the stock and hand guard. The hole is primarily designed to drain water from the stock. Of course, it comes out everywhere else too. The hole is a reasonably good place to mount a Harris bipod. One must keep in mind that it is not the strongest part of the stock, but it does work.

The Keng's Firearms Specialty M14 bipod is a Chinese copy of the Parker-Hale precision rifle bipod. Its bipod mounting adapter for the M14 type rifle is catalog number 150-102. This bipod mounting adapter replaces the American threaded gas cylinder plug to allow a Keng's Firearms Specialty bipod to be mounted to the rifle. This mounting adapter will not work on Chinese manufactured M14 gas cylinders because of the different thread pitch. A Keng's Firearms Specialty M14 bipod can also attach to a standard quick detachable sling swivel with its universal mounting adapter (catalog number 150-100). In 2005, the firm introduced a 3 3/8 " long MIL-STD-1913 Picatinny rail that attaches to the bottom of the M14 stock just forward of the front sling swivel (catalog number 150-807). This steel M14 stock MIL-STD-1913 Picatinny rail section requires no stock modifications to be installed. The KFS rail section has a channel machined on the top surface to allow gas from the gas cylinder to vent out of the stock. The KFS rail section includes a 1 5/8 "

wide freely rotating sling swivel. In 2013, KFS produced a slightly shorter 3.25 " six o'clock Picatinny rail section with the same sling swivel (catalog number 150-807B). This latter rail section was intended for synthetic stocks only.

The Mk 14 Mod 0 bipod was developed by Keng's Firearms Specialty and Mike Rock. This bipod had a patent pending quick detach clamp that attached to the bottom Picatinny rail of stocks so equipped such as the J. Allen Enterprises JAE-100, Sage International M14 EBR, Troy Industries MCS, and McMillan MFS-14 models. The Mk 14 Mod 0 bipod legs were adjustable in six increments for a height of 9 " to 12 " when unfolded from the stock. The patented claw-like design of the bipod feet kept them from sinking into wet or sandy soil. The bipod (catalog number RD-923) had pan and tilt movement to allow target tracking and axial rotation to correct for uneven ground.

Troy Industries offered a bipod for the Rock SOPMOD M14. It mounted to the six o'clock rail on the stock and had a quick release mounting lever.

Ammunition

Headspace - USGI, Chinese and Taiwanese M14 type rifles are chambered for the 7.62 x 51 mm NATO cartridge. Chinese M14 rifles from the factory are headspaced long. The majority of Federal Ordnance M14 type rifles were assembled with Chinese barrels and bolts or sold as bare receivers. U. S. commercial manufacturers typically headspace M14 type rifles to Sporting Arms and Ammunition Manufacturers' Institute (SAAMI) specifications for .308 Winchester unless chambered for another caliber. However, some U. S. commercial M14 type rifles built by armorers and gunsmiths for competition were headspaced for 7.62x51 mm NATO ammunition. Therefore, the buyer should check the headspace when purchasing a rifle unless the factory or gunsmith supplies the headspace reading at the time of purchase. If the headspace is from 1.630 " to 1.634 ", then either commercial manufacture .308 Winchester or military manufacture 7.62 x 51 mm NATO ammunition can be used. The subject of hand-loaded ammunition in the M14 type rifle is beyond the scope of this work.

If a USGI M14 rifle bolt closed on a USGI FIELD REJECT gage with a FIELD TEST bolt (part number 7274799) installed, the rifle was removed from service and the receiver and barrel declared unserviceable. If the FIELD TEST bolt would not close on the FIELD REJECT gage but the issue bolt did then the bolt was removed from service and replaced. The USGI M14 headspace gage sizes were as follows: 1.6355 " GO, 1.6375 ", 1.6415 " NO GO and 1.6445 " FIELD REJECT.

Frankford Arsenal was founded on May 27, 1816 and was located in what is now northeast Philadelphia, PA. It was an ammunition research, development and production facility throughout its history. During World War II, as many as 22,000 personnel were employed at the arsenal. Frankford Arsenal developed and produced the T275 cartridge by no later than 1959. Four experimental versions later, the T275E1 was designated as

the XM118 cartridge in 1961. It was first produced by the arsenal as the M118 cartridge in 1964. Frankford Arsenal produced and adopted small arms ammunition as late as 1965, e.g., M198 cartridges. Frankford Arsenal developed some experimental small arms lubricants that tested favorably under arctic conditions from November 1966 to January 1967. The experimental lubricants were tested on M14 rifles and other small arms. In 1968, Frankford Arsenal was part of the U. S. Army Materiel Command with 5,714 workers. Frankford Arsenal closed in 1977. The 112 acre property was eventually sold by the U. S. government and is now an industrial park.

Lake City Army Ammunition Plant (Independence, MO) was established in 1940 to produce small arms ammunition for the U. S. Army. Lake City manufactured M852 Match ammunition was introduced in 1980 for military competition shooters. This cartridge was first classified as XM852 in 1981 and then M852 later in the same year. It provided better performance than the M118 Match cartridge at distances out to 600 yards. Lake City remains in operation today as part of the U. S. Army Industrial Operations Command. The Industrial Operations Command is a subordinate command of the U. S. Army Materiel Command.

U. S. military 7.62 mm NATO ammunition was packaged in linked belts, cartridge clips inside bandoleers or inside cardboard cartons. Linked cartridges were used for belt fed machine guns, obviously. For the M14 Rifle, the ammunition was packed in cardboard cartons or bandoleer kits. M62 tracer, M80 ball, M82 blanks and M198 duplex rounds were packed in bandoleer kits, sixty cartridges to a kit. M62, M80, M82, M118, M172, and M198 cartridges were packed in cardboard cartons of twenty cartridges each. Due to the expense, ammunition packaged in bandoleer kits was issued for combat use only.

7.62 mm NATO ammunition delivers a substantial punch to hard targets. M80 ball ammunition is able to penetrate the barriers listed below:

Pine (0.75 " thick) - 17 boards at 100 meters, 9 boards at 600 meters
Sandbags - 11 " at 200 meters, 5 inches at 600 meters
Steel (14 gauge) - 3 plates at 500 meters
Concrete (building block with one center rib) - both sides at 400 meters

Subsonic ammunition was hand loaded at Fort Benning, GA for XM21 sound suppressed rifles in the Republic of Viet Nam. This subsonic round was designed to be stable for a distance of 100 meters or less. Placing the spindle valve in the "OFF" position reduces the muzzle velocity by only 15 feet per second using M118 Match ammunition but it does noticeably intensify felt recoil. Likewise, removal of the flash suppressor does not significantly alter bullet muzzle velocity. Match grade ammunition has been in use by competition shooters since the 1921 National Matches.

The M198 duplex cartridge was developed by Winchester-Western and standardized on May 07, 1964. The 84 grain front bullet had a light green tip and hollow base and the 85

grain rear bullet had a slanted base. Accuracy for the front projectile was 2 " mean radius at 100 yards. Dispersion for the rear projectile was 5 " to 10 " at 100 yards. Testing by the U. S. Army Infantry Board in 1961 found 7.62x51 mm duplex ammunition 14 to 22 % more effective in hitting personnel type targets in simulated infantry squad combat conditions. In the 1965-66 field experiment at Fort Ord, M198 ammunition produced more near misses and more hits per target over ball ammunition out to 545 meters.

In the spring of 1971, the U. S. Army tested the effectiveness of using M62 tracer in daylight conditions. One hundred soldiers from the 197th Infantry Brigade at Fort Benning, GA participated in the test. The soldiers were given refresher marksmanship training and allowed to obtain battle zero settings for their M14 rifles. The test was conducted with soldiers firing both M62 tracer and M80 ball ammunition at a total of twelve stationary Army E type silhouette targets painted yellow. The targets were placed at three distances, 100 meters, 300 meters and 500 meters. The soldiers were divided into three groups, each firing ball ammunition but using a different technique to engage the targets with tracer rounds. All rounds were fired in semi-automatic mode with only one soldier firing the course at a time. The soldiers were only able to detect the tracer rounds moving toward the target about 23 % of the time. Overall, the probability of making a hit on target in the same amount of time was about the same, 44.4 % for ball and 45.2 % for tracer. None of the techniques employed in firing tracer rounds proved to be significantly better or worse than the others. The M14 rifle is better suited for night firing of M62 tracer ammunition over the M14A1. The M14E2 muzzle stabilizer produces enough flash signature with M62 ammunition to affect the operator's night vision.

A M62 tracer projectile usually ignites 35 to 70 meters forward of the muzzle. It will be fully lit before reaching a distance of 100 meters down range. The tracer projectile will burn out between 800 and 900 meters away from the rifle. Tracer ammunition serves a number of purposes: 1) an individual shooter can adjust fire on a single target 2) target designation 3) target illumination 4) signalling to others 5) supervision of a unit's firing 6) signal to the shooter that it is time to reload 7) incendiary effect 8) aid in range estimation and 9) psychological effect on the enemy.

Surplus military ammunition can be of high quality. Ron Smith (Smith Enterprise, Inc.) was a member of the Arizona and California National Guard Shooting Teams. He reports that his scores were from 490 to 495 in High Power Shooting competitions (fifty shot National Match Course) with match grade ammunition. Using surplus Portuguese military ammunition, his scores ranged from 485 to 490!

Commercial ammunition in .308 Winchester is available in varying bullet weights of full metal jacket, soft point and hollow point. Black Hills, Federal, Remington, and Winchester all produce high quality ammunition. Springfield Armory, Inc. does not recommend the use of soft point ammunition in the M1A rifle. Use of soft point cartridges can cause build up of lead deposits in the chamber. Dirty barrel chambers will cause excessive pressure which may result in serious personal injury. The M14 type rifle can be

loaded using magazines or cartridge clips. Some scope mounts prohibit loading the rifle with cartridge clips.

Semi-automatic fire is more accurate on point targets but automatic fire has a greater incapacitating effect on enemy troops due to greater volume and rate of fire. On the other hand, ammunition supplies deplete much more rapidly with automatic fire. A unit's rate of fire is proportional to its fire superiority and inversely proportional to its sustainability. Carry more ammunition and mobility is reduced and logistics support is increased. The cartridge, the rifle, and the combat load will always be a compromise solution for any infantry unit.

One of the criticisms of the M14 is its full size rifle cartridge. During the 1960s, the proponents of small caliber high velocity cartridges within the U. S. Department of Defense argued that more rounds could be carried by the infantryman and logistically more rounds could be packaged and transported for the same weight over the 7.62 mm NATO cartridge. That is very true. Unfortunately, the troops did not realize much of a reduction in the load bearing equipment burden.

The M14 and M16 series rifles use essentially the same small arms sling and the butt stock cleaning kits have approximately the same weight. The M14 rifle with a full twenty round magazine minus the sling and cleaning kit weighs 10.3 pounds. Add 6.0 pounds for another four fully charged magazines for a total of 16.3 pounds. 100 rounds of 7.62 mm NATO ammunition was the M14 rifle basic issue load of ammunition for combat.

The M16A1 Rifle was further developed and improved due to issues discussed in other references. The result was classified as the M16A2 in 1982 and first adopted by the U. S. Marine Corps in 1983. The M16A2 Rifle weighs 8.8 pounds with a full thirty round cartridge but without the sling and butt stock cleaning kit. From at least 1976 onward, the basic issue of ammunition for the M16A1 and M16A2 has been 210 rounds of 5.56 mm NATO. The other six fully loaded M16 magazines weigh 5.4 pounds. This gives a total weight of 14.2 pounds for the M16A2 rifle and its basic ammunition load. A M14 rifle with five fully charged magazines but no cleaning kit or sling weighs 16.3 pounds. Both weapon systems are in line with the historical expectation, 17 to 18 pounds for an infantry rifle and basic issue of ammunition. However, an infantry unit will have mobility and equipment requirements as the mission dictates. Those requirements will influence how much weight can be allotted to a rifle and ammunition.

For the M14 rifleman, six additional magazines would provide an equivalent number of cartridges as compared to the M16 ammunition load at a cost of another 9.0 pounds. The physical bulk of two M14 magazine pouches is about the same as two M16 magazine pouches. Though 5.56 mm NATO ammunition weigh less, the weight advantage is partially offset by the increased bulk of any additional M16 magazines. From the 1960s onward, additional ammunition was sometimes carried in bandoleers for those carrying either M14 or M16 variant as the needs of the mission dictated.

The combat load of a soldier consists of his weapon, ammunition, clothing, water, food rations, and equipment. It is the equipment necessary to put the infantry soldier into battle and sustain him for immediate combat operations. In other words, it's what will sustain the soldier for up to 72 hours in combat. The basic issue of ammunition for the M14 rifle in the 1960s, 100 rounds, was sufficient for an average day of combat based on data tables developed from combat experience up to that time.

In 1961, the U. S. Army infantry soldier wore 35.9 pounds of clothing and equipment (boots, bayonet and scabbard, load bearing equipment, uniform, first aid kit, gas mask, two grenades, helmet, entrenching tool, pack, water, poncho, flak jacket, toiletries and rations). Adding the M14 rifle, five full magazines, and two magazine pouches increased the total combat load to 50.7 pounds for the U. S. Army infantry rifleman. In 1961, the U. S. Army Infantry School recommended a maximum combat load of 45 pounds.

By 1992, the U. S. soldier was much more burdened. The U. S. Army combat load consisted of a fighting load (helmet, water, gas mask, bayonet and scabbard, load bearing equipment, grenades, first aid kit, and gas mask), minus the M16A2 and ammunition, of 20.7 pounds, and an approach march load (pack, rations, more water, toiletries, towel, entrenching tool, poncho and poncho liner) of 22.1 pounds. The U. S. Army position was that the total combat load should remain less than 60 pounds but the Army failed to account for the weight of clothing, boots and the body armor, about 15 to 17 pounds, which really are a part of the combat load. Thus, a 1990s soldier would carry about 72 pounds of clothing, equipment, weapon, ammunition, rations and water. The soldier's physical strength, ease of movement and responsiveness decrease as the combat load increases.

Going forward from the 1960s to the 1990s, the soldier's combat load increased by more than 20 pounds even with a reduction of 2.1 pounds for the rifle and issue load of ammunition. Worse yet, a 2003 study by the U. S. Army Center for Army Lessons Learned found that the average combat load (fighting load plus approach march load) was 95.7 pounds for 82nd Airborne Division riflemen conducting dismounted operations in Afghanistan. Just the fighting load itself averaged 63 pounds for the rifleman on foot in Afghanistan. As of early 2009, the U. S. Army and U. S. Marine Corps was experiencing an increasing number of non-deployable troops due to acute orthopedic injuries. For the U. S. Army, this number was about 20,000 at the time. These injuries were caused from repeated combat tours in Afghanistan and Iraq which required soldiers and Marines to carry heavy individual equipment loads. Changing to a more flexible "as needed" individual equipment list and/or adopting newer design commercial off-the-shelf (COTS) load bearing equipment would provide much greater benefit to the warfighter at much less time and cost. Since the First Gulf War, the U. S. military has adopted some of the COTS load bearing equipment, e.g., hydration bladders with nylon fabric carriers.

Except for special operations units, combat and combat support troops can generally anticipate resupply as needed. Not that one wants to run out of ammunition in a firefight

but the supply train should ensure adequate resupply for the "trigger pullers." In other words, if the logistics and transportation components of the armed services do their job, the individual grunt doesn't need to carry 500 rounds of rifle ammunition at all times. After all, military operations are a team effort.

Other Calibers

After then-Secretary of Defense Robert McNamara announced the cancellation of M14 rifle production in 1963, TRW attempted a conversion of the M14 to .223 Remington in an effort to save what it could of its investment with the M14 Rifle. This conversion was performed by TRW employee John Dodds. It included adding a longer extractor, changing the bolt face to fit the smaller cartridge, modifying the magazine latch and M16 magazine follower, and installing a M14 contoured .224 caliber barrel and a filler block for the rear of the magazine well. The barrel was machined at TRW from a Douglas supplied barrel blank. This unique TRW rifle was demonstrated to the military but the project went no further.

In 1992, Armscorp USA made at least one receiver stamped 5.56 MM M14 NM. It was made to the same dimensions as the 7.62 x 51 mm receiver and no modifications were made. Gene Barnett made a 5.56 mm 1:12 twist M14 barrel for the receiver. The bolt face and extractor were modified for the smaller 5.56 mm cartridge case. This rifle uses a twenty round M16 magazine that is riveted inside a M14 magazine tube.

In the late 1970s and early 1980s Karl Maunz converted about 100 M1 Garand rifles to a number of experimental calibers such as 6.5 mm, 7 mm, .45 ACP and "wildcat" calibers .451 through .459. Through the 1960s, 1970s and 1980s, Karl Maunz drew up drawings for these wildcat cartridges and sent them to Clymer Manufacturing Company (Rochester Hills, MI) to have chamber reamers made. This included manufacture of a .308 Winchester caliber headspacing chamber reamer in 1963 for the M1 Garand rifle. Karl Maunz obtained the wildcat caliber barrels from Jack Krieger and Bob Hart after Clymer Manufacturing Company had supplied the Maunz designed chamber reamers. Clymer Manufacturing Company was established in 1958 by Max and Tina Cramer. In 2005, Karl Maunz was developing a .45 ACP cartridge for the M1 Garand and M14 type rifles.

Karl Maunz came up with the idea of mating a 6.5 mm 140 grain bullet to a 7.62 x 51 mm cartridge case. He named this cartridge the .630 Maunz. As a matter of personal preference, he used Frankford Arsenal match cartridge cases over Lake City match cartridge cases. Karl Maunz came up with .630 Maunz design after looking at the .276 cartridge that had been originally developed for the M1 Garand rifle. It proved to be an exceptionally flat shooter at 600 yards. He did some development work in 1964 on a muzzle-feeding chamber reamer. This chamber reamer was intended for use in the .308 Winchester barrel M1 Garand rifle. This preliminary work was done while he was still in the Army Reserve. He was able to finish the design and manufacture of the original .630 Maunz muzzle-feeding headspacing chamber reamer in 1965. Later, the use of .308

Winchester cartridge cases mated to smaller bullets was made available in the Maunz Match Rifle Model 87. The Model 87 was available in the following calibers: 7.62 x 51 mm / .308 Winchester, .308 case with .224 bullet, .308 case with .244 bullet, .308 case with .264 bullet or .308 case with .284 bullet.

Springfield Armory, Inc. offered M1A rifles chambered in .243 Winchester from at least 1978 until 1994 and in .358 Winchester from 1978 to 1980. Barrel blanks in .22, 6 mm, .243, .25, .270, 7 mm, .30, .35 and .358 caliber were offered from 1978 through 1980. Springfield Armory, Inc. would install one of its barrels into a M1A rifle during this period for a nominal charge, \$10.00 to \$14.00. From 1990 and later, the M1A was available in 7mm-08. These M1A rifles were sold in the United States and in countries where civilians were prohibited from owning military compatible ammunition, e.g., France. For example, Super Match M1A serial number 088619 was custom built in 1995 by Springfield Armory, Inc. It had a Hart 7mm-08 heavyweight barrel and the receiver was rear lugged. Armscorp M14 NM serial number 12148 was built with a .243 Winchester 18 " barrel long but it is not known if the barrel was installed by Armscorp USA. M1A rifles exported to Spain are chambered for .307 Winchester.

Arizona Expert Arms (Mesa, AZ) and Dow Arms Room (Dade City, FL) can convert M14 type rifles to .300 Winchester Short Magnum upon customer request. The Arizona Expert Arms conversion includes installation of a custom Krieger heavyweight barrel, machining the bolt face and extractor, drilling the proper size barrel gas port, and relieving the stock to accommodate the barrel. Standard USGI M14 twenty round magazines will hold and feed eleven .300 WSM cartridges without modification.

About 2004, Mr. Dow converted two Springfield Armory, Inc. M1A rifles to .300 Winchester Short Magnum caliber M21 type configuration. The conversion work included installation of Smith Enterprise, Inc. scope mounts. The two rifles were delivered to McDill Air Force Base by Charles Moore, a night vision supplier to McDill Air Force Base (AFB) or some resident command therein. The M1A rifles were to be tested at McDill AFB. The rifles were supplied with a quantity of hand loaded ammunition (175 grain SMK projectiles). There were no follow on orders. At least one of the .300 WSM caliber M1A rifles was tested in Iraq by a member of the U. S. military. The individual was pleased with the performance of the system. Mr. Dow's conversion includes modifying the extractor, installing a heavyweight barrel with a reduced gas port diameter, enlarging the barrel chamber, opening the bolt face, installing a proprietary design ejector assembly and removing up to an 1/8 " of material from the scope mount bottom surface.

Mr. Roland Beaver of Old Corps Weaponry, a M14 gunsmith, has built several commercial M14 trainer rifles in .22 LR caliber using Sturm, Ruger & Company, Inc. 10/22 rifle receivers. Mr. Beaver adds a .22 LR caliber chambered barrel, a custom carved walnut stock and hand guard and M14 gas cylinder, flash suppressor and front sight to create a custom made M14 training rifle. He made both prototype and production models of his M14 trainer.

The M14 Rifle is credited with being the inspiration for the Sturm, Ruger & Company, Inc. Mini-14 Rifle. Ruger employee L. James Sullivan began work on the Mini-14 project in 1967. After several modifications were made to the original design, the Mini-14 was made available to the public and law enforcement agencies in 1974. The .223 Remington caliber Mini-14 receiver is machined from an investment casting.

M14 Problems

After government production began, the M14 rifle experienced occasional failures where the bolt did not strip the next round from the magazine and so closed on an empty chamber. Sometimes, the bolt would contact the cartridge halfway through the cycle causing a jam. This occurred because the bolt speed increased with using ball-shaped gunpowder while the M14 rifle had been originally designed to use ammunition loaded with extruded gunpowder. Springfield Armory redesigned the magazine spring to help raise the rear end of the follower and shortened the rear end of the cylindrical portion of the operating rod by 0.1 ". The shortening of the operating rod increased the bolt cycle time to give the magazine spring sufficient time to raise the top cartridge to where it needed to be. These changes were successful in eliminating the cartridge stripping problem.

In the early 1960s, U. S. Marines used the M14 rifles with fixed bayonets for Close Quarters Battle training. When Marines executed the movement known as the vertical slash, the stock would sometimes disengage from the front band causing the barrel to separate from the stock. Also, a similar problem occurred when the Marines used the M14 rifle as a step to hurdle over obstacles. Two Marines would hold the rifle, one at either end while a third Marine stepped on to the rifle in the middle to clear a fence or wall. To keep the stock from separating from the barrel under such combat conditions, the gas cylinder was redesigned to incorporate a lip just aft of the bottom gas port to support the front band.

In close quarters combat, shorter and lighter carbines are faster to get on target than longer and heavier rifles. But with practice, the time difference can be shortened to a fraction of a second longer with the heavier weapon. The NATO Research & Technology Organization found that a soldier equipped with a 8.3 pound C7A2 (M16 style) rifle could turn with his rifle shouldered from face front to ninety degrees to the side in 1.69 seconds. The same soldier with a more heavily accessorized C7A2 rifle weighing 13.5 pounds could make the same maneuver in 1.78 seconds.

The most common failures of the M14 rifles while in service were cracked stocks and rear sight pinions, missing rear sight nuts, and misaligned flash suppressors. Less common failures were broken safeties, broken firing pins, and out of specification gas cylinders. The least common problems were broken hammer hooks or spurs, extractors and bolt locks. Few, if any, problems were reported with the operating rod, firing mechanism (except safety), butt plate, or front sight itself. The early version 3/32 " socket front sight

screw was often stripped and could not be removed. The late version 7/64 " socket front sight screw was issued to alleviate this problem. Repeated automatic fire from the hip with the M14E2 stock will cause it to crack at or near the top of the pistol grip.

The U. S. Army anticipated a certain amount of parts failures. TM 9-1005-223-35 July 1968 Section II Repair Parts List indicated the maximum number of repair parts allowed in inventory per 100 rifles at the following maintenance levels: Direct Support thirty day supply, General Support thirty day supply, one year contingency and Depot Support. Many M14 and accessories parts were only authorized two spares per 100 pieces supported at the Direct Support and General Support levels. Aside from small pins, the front sight screw (76) and the firing pin (48) were the parts with the highest authorized quantity for Depot Support.

During arctic testing of small arms lubricants from November 1966 to January 1967 by the U. S. Army, nine firing pins, two operating rod springs, three sears, three ejectors and one bolt were replaced among ten M14 rifles that were fired for a total of 73,105 rounds. Recorded temperatures during these parts failures ranged from a high of - 10 degrees Fahrenheit to a low of - 55 degrees Fahrenheit.

There were two versions of the M14 extractor. The early version was designed by John C. Garand and patented in 1940. The early extractor was identical to the M1 Garand rifle extractor and had a sharp point on the lower front right-hand corner which could snag the cartridge. This caused the extractor to leave the bolt when firing M82 blank cartridges. This problem was corrected with the late version (drawing changed in March 1963) extractor. The late version extractor was milled with a beveled lower front corner which allowed the M82 cartridge to clear the extractor. The early version extractor is unacceptable for overhaul of USGI M14 rifles.

By 2005, if not before, some USGI XM21 and M21 rifles sometimes had developed very long headspace. Over the years, the bolts had been lapped too many times by various military armorers as the rifles were overhauled or rebarreled. One of these rifles had a bolt that closed on a military Field Reject headspace gage with a short chambered barrel that was to be installed. Other XM21 and M21 rifles were found to just meet headspace requirements with a short chambered barrel. These rifles have no equipment maintenance history logs to keep track of such data. A maintenance log that is faithfully kept up is not a bad idea for any piece of important equipment, the M14 included. Bolts with weldment on the bolt face were removed from M14 rifles issued to JROTC units. These bolts must not be used in a rifle that will be shot. The firing pin hole on the bolt face is welded over to prevent installation of a firing pin. This demilitarization procedure causes the bolt to be annealed making it soft and unsafe for use.

No projectile weighing over 168 grains should be used in an unmodified M14 type rifle with standard barrel chamber. This is because of increased chamber and gas port pressure generated with heavier bullets. Thunderbird Cartridge Company (Laveen, AZ)

tested some M118 ammunition for Smith Enterprise in 1990. The chamber pressure measured from 53,000 to over 59,000 cupric units of pressure (CUP). The adjusted average chamber pressure was 57,000 cupric units of pressure at 78 degrees Fahrenheit. Shooting a steady diet of 180 grain cartridges has bent the operating rod on a Norinco M14 Sporter. U. S. Army M14 rifles in Iraq in 2004 were experiencing overpressure problems with M118LR 175 grain ammunition. An M14 rifle may safely shoot M118LR ammunition if the barrel chamber is reamed to the M118LR chamber dimensions. At the time of this writing, Smith Enterprise, Inc. is the only firm with a M118LR cartridge chamber reamer. The M118LR reamer is made only for Smith Enterprise, Inc. by Dave Manson Precision Reamers (Grand Blanc, MI). Dave Manson started Dave Manson Precision Reamers in 1999 after having worked at Clymer Manufacturing Company for sixteen years as Production Manager.

Ammunition must NEVER be loaded by hand into the chamber with the bolt allowed to close at full speed driven by the operating rod spring. That practice presents the risk of slam fire. Ammunition should instead be fed only from the magazine. The receiver bridge should prevent this from occurring but it is not wise to rely on it. For added protection against a slam fire condition caused by a forgetful operator and a worn receiver bridge, gunsmith Roland Beaver has installed a firing pin spring in the bolt assembly for M14 type rifles he has built. Always point all firearms in a safe direction and always assume a loaded chamber for safety reasons. The M14 operating rod handle can be quickly and easily tapped forward in a combat situation should the bolt fail to lock after chambering a cartridge.

The user should not attempt to engage the safety on an M14 type rifle unless the hammer is cocked. Otherwise, the safety can fail. The M14 safety was designed to prevent it from being engaged with the hammer uncocked. The feature avoids failure to cock the hammer due to interference from the safety. Manipulating the M14 safety creates an audible sound. In a tactical situation, audible sound may not be desirable to the rifle operator. Other components of the firing mechanism are remarkably trouble-free and durable, so long as amateurish "trigger jobs" are avoided.

Based on civilian experience, USGI gas pistons have a useful life between 10,000 and 15,000 rounds. USGI gas cylinders will require replacement after approximately 40,000 rounds. If the gas system is never cleaned and the rifle is fired for thousands and thousands of rounds the operating rod will eventually break based on experience with Australian government wildlife agency shooters. Flash suppressor prongs experience signs of gas erosion near the muzzle after thousands of rounds fired. The prongs will eventually crack at some point after 15,000 rounds.

Some Viet Nam War veterans have stated that the M14 magazine feed lips could and did bend when hitting the deck hard in a combat situation. While this is a true statement, it is not unique to the M14 rifle. This is a concern with other magazine fed military rifles as well.

Some M14 type rifles left the factory with loose flash suppressors and operating rod guides. The flash suppressor nut can be over-tightened causing slight stretching of the barrel. This was an issue with XM21 and M21 rifles. The gas cylinder plug can and has loosened during firing and in combat at that. The prepared M14 type rifle owner always carries a M14 combination tool to check the gas cylinder plug on a routine basis. Once these parts are correctly installed, the M14 rifle is almost always trouble free. Every 1000 rounds, the M14E2 muzzle stabilizer should be removed from the rifle and cleaned of baked on carbon residue. If the bolt does not cycle after the first shot is fired, check the spindle valve to see if it is in the open position (slot in the vertical). The wise M14 type rifle owner carries a spare complete bolt assembly already headspaced and fitted to the rifle.

There are sixty elevation serrations on the M14 type receiver. Consequently, each click of the elevation knob raises or lowers the sight aperture by one minute of elevation angle or 0.008 " vertically. A few M1A receivers between serial numbers 007000 and 020000 tend to wear prematurely on the elevation serrations. These receivers can be heat treated and the surface hardness increased to correct this condition. As an alternate solution, the receiver serrations counterbored and covered with a hardened steel elevation serration repair disc by firms such as Smith Enterprise, Inc. This disc was developed by Fort Benning USAMTU armorers. It has 120 serrations on one side and sixty serrations on the other side. The disc can also be used to obtain half-minute elevation adjustments with a standard rear sight aperture. In 1973, the elevation serration repair disc was manufactured by Liberty Tool & Die Corporation (Rochester, NY). The disc has been available through Fulton Armory and Smith Enterprise, Inc. The design of the standard windage knob detents prevents similar problems on that side of the receivers.

There have been cases where commercial manufacture extractors have flown out of the bolt while the rifle is cycling. These extractors can usually be made serviceable by further machining of the divot where the extractor spring plunger rests on the extractor, or by replacing the extractor spring plunger. An alternate solution is to replace the commercially-made extractor with a USGI extractor. Often, the commercial extractor spring tension is insufficient, the extractor spring detent is too large or the extractor stem is too long. The hole to house the extractor spring was not always drilled sufficiently in commercial manufacture bolts. An unissued USGI M1/M14 extractor spring was required to be 0.480 " long and have twelve right-hand coils. Check the length and count the coils of a replacement extractor spring before installation. If the commercial bolt hole is too shallow to accept a USGI extractor spring, consult a reputable M14 gunsmith.

Extended bolt locks may require some gunsmithing work to install on commercial receivers. This is because the bolt lock window dimensions or location or the receiver left side exterior surface above the bolt lock window may not exactly match the requirements of USGI drawing F7790189. So, the extended bolt lock may require modification to fit on a commercial M14 type receiver.

Chinese M14 type gas cylinders and gas cylinder plugs are prone to rusting because they are not made of stainless steel. Chromium plating on the Chinese gas pistons makes rust less of a problem with that part. The USGI M14 rifle, like other small arms, was susceptible to surface rust from the jungle environment in the Republic of Viet Nam. Modern firearms preservatives can alleviate this condition for the M14 in humid climates. The canvas M1956 ammunition cases (magazine pouches) shrank from being soaked with rain in southeast Asia. This made it difficult to remove M14 magazines from the pouches. Conversely, U. S. troops in the Republic of Viet Nam found that the wood M14 stock could swell from exposure to heavy rain to the point that the rifle could not be reassembled without drying out the stock.

From late 2001 when M14 rifles were fielded with the 82nd Airborne Division until the present day operations in Afghanistan and Iraq, the U. S. Army suffers from a dearth of armorer expertise to maintain the M14 rifle in combat theaters at the Direct Support and General Support maintenance levels. Nonetheless, the M14 rifle has proven itself over and over in combat with even less-than-adequate support.

Regarding the full traditional battle rifle silhouette, the M14 can be fitted with a telescoping butt stock, 18 " barrel and a shorter, updated design flash suppressor for end users operating in such environments. Installation of an 18 " barrel alone would reduce its overall length to approximately 39.3 ". In comparison, the M16A2 rifle is 39 5/8 " long.

1987 Springfield Armory, Inc. Recall Notice

Springfield Armory, Inc. issued a recall of specific bolts and safeties in 1987. Some Springfield Armory, Inc. M1A, M1 Garand and BM59 rifle firing mechanism safeties could be disengaged by pulling on the trigger with a heavier than normal amount of force. These rifles would not fire after the trigger was pulled the first time but would fire after the trigger was released and pulled again with a normal amount of force. After unloading the rifle of all ammunition and pointing the muzzle in a safe direction, the firing mechanism should be tested as follows: 1) cycle the bolt 2) place the safety in the off position 3) place the safety in the on position 4) pull the trigger with more than a normal amount force then release it. Perform this test several times. If there is any forward movement (disengagement) of the safety, the firing mechanism should be removed from the rifle and Springfield Armory, Inc. contacted.

The 1987 recall applies to M1A bolts with these markings: 1) no numerical or alphabetical characteristics on either the top or back of the bolt (completely unmarked) 2) any bolt with any numerical or alphabetical markings at all on the back of the bolt 3) any bolt with the top marked 7790185 and with SA RRR centered below that number or 4) any bolt with the top marked 7790185 and with SA centered below that number. If the reader has such a bolt, contact the Customer Service Department at Springfield Armory, Inc. Politely discuss your situation with the Customer Service Representative. Springfield Armory, Inc. still honors this recall if applicable to the part concerned. The bolts subject to recall were

found to have incorrect locking lug angles. The RRR marking stood for Reese Reese Reese.

Accurizing Tips

A competent gunsmith can enhance the accuracy of an M14 type rifle. Some of the procedures the gunsmith may perform include: checking the operating rod spring guide for parallel, padding the hand guard, gluing or pinning the gas spindle valve open, measuring the operating rod spring for proper length, unitizing the gas cylinder to the front band, shimming the gas cylinder to the barrel to correct gas cylinder lock timing, peening or knurling the barrel to ensure interference fit of the gas cylinder, operating guide, and flash suppressor, tuning the firing mechanism, backing off the flash suppressor setscrew, reaming the flash suppressor, polishing the gas piston, hand fitting various parts, installing National Match front and rear sights, bedding the stock, modifying the stock liner, and lapping the bolt. Springfield Armory developed the concept of bedding military rifle stocks in the early 1880s. Stock bedding of match rifles was done as early as 1903. Some match shooters will file down the height of the front sight blade so as to get the 100 yard zero of the sights to be zero clicks of elevation from bottom. Beware of this modification if a used M14 type rifle is purchased. It will become obvious during the sighting in procedure if its National Match aperture is replaced with a standard peep aperture. The rifle will then shoot high above the point of aim unless the front sight is also replaced.

The single best modification for accurizing the M14 is to unitize the gas system. U. S. Army M14 match armorers used the more labor intensive method of screwing the gas cylinder to the front band to unitize the gas system. Before the spindle valve can be drilled and tapped, it and the front band must be annealed. The spindle valve is heated to 1300 degrees Fahrenheit then allowed to slowly cool for twelve hours. The front band is spot annealed with a torch. Stainless steel screws are then screwed into the front band and spindle valve with epoxy adhesive applied to the threads. Finally, the screws are staked to the front band to keep them from loosening. A special jig is used to keep all the parts aligned while this is accomplished. U. S. Marine Corps M14 match armorers unitized the gas system by silver soldering the gas cylinder to the front band. This method is much less time consuming. Either method achieves the desired result.

As a general rule, U. S. Army MTU armorers modified the following M14 parts: flash suppressor, front band, gas cylinder, gas piston, hammer, operating rod, operating rod spring guide, sear, and stock. Some shooters have a National Match front sling swivel installed on their stock. The USGI riveted front sling swivel is removed and replaced with a quick detach sling swivel that is mounted to the stock with bolts and nuts. This increases the strength of the swivel attachment and allows the shooter to wrap his arm into a tighter sling when shooting.

Stock bedding can be accomplished without traditional bedding materials. Newer stock designs offered by Sage International, Ltd., Troy Industries, Inc. and J. Allen Enterprises, Inc. use tension bedding that never wears out. Smith Enterprise, Inc. modifies USGI synthetic stocks so that there is downward pressure on the front band. In either case, accuracy is enhanced by eliminating movement between the stock and the barrel.

Miscellaneous Tips

Maintenance - Civilian M14 type rifle owners may not have the benefit of a Marine Corps Drill Instructor to coach and mentor them. Hence, it is up to you to take the initiative to perform operator level preventive maintenance on the M14 type rifles and other firearms you own.

What is firearms preventive maintenance? U. S. Army manual DTM 9-1005-221-10 defines preventive maintenance as the "systematic care, inspection, and servicing of equipment to keep it in serviceable condition, prevent break downs and assure maximum operational readiness." Consult the Original Equipment Manufacturer (OEM) owner manuals for specific procedures for firearms other than the M14. This volume lists several military and commercial publications detailing preventive maintenance procedures for the M14 rifle. Along with the appropriate manuals, possessing and knowing how to use the basic cleaning kit items for each firearm is a must for every civilian owner.

These items form a good general inspection check list for the M14 type rifle:

- 1) Clean the chamber and bore and lubricate the rifle.
- 2) Check the gas cylinder plug is snug while the rifle is at ambient temperature. Do not overtighten the gas cylinder plug.
- 3) **With the chamber clear, no magazine inserted into the rifle and the muzzle pointed in a safe direction**, cycle the bolt by pulling the operating rod to the rear then letting it go. There should be no binding of the bolt or operating rod.
- 4) Engage the safety to check its operation.
- 5) Operate the windage and elevation knobs to check operation. Move the knobs back to the established zero of the rifle.
- 6) Check the front sight to make sure it is not loose.
- 7) The sling should be in good repair.

8) Magazines should be clean, dry and not deformed.

The M14 extractor can be removed from the bolt with the rifle still assembled. Pull the operating rod handle rearward and lock the bolt. Place an empty .30-06 cartridge case inside the barrel chamber. Gently ride the bolt forward until it stops. The empty .30-06 cartridge case will keep the ejector and ejector spring depressed. This facilitates removal or installation of the extractor without use of the M14 combination tool.

When removing the firing mechanism (first check that the rifle is clear of ammunition, cycle the bolt, and engage the safety) keep fingers out of the inside of the trigger guard when pulling the trigger guard away from the stock to avoid injury. Instead, use a thin metal object and place the end into the hole on the rear end of the trigger guard and pull out and away from the stock. If a screw driver or the M14 combination tool is not available, the rim of an empty cartridge case can be used to tighten the elevation knob screw. To begin disassembly of the firing mechanism, place the hammer in the "as fired" position before removing the trigger pin.

When cleaning the inside of the receiver, lower a cartridge clip through the cartridge clip guide to a point below the bolt face. This will keep the bolt from going into battery and causing injury. Removing the sling keeper from the sling and then looping the sling through the rear sling swivel will reduce noise from the sling while carrying the rifle.

Write down sight adjustments for various ranges and points of impact for different cartridges on a small piece of paper. Tape this note sheet to the inside surface of the butt plate flapper. Brass marks on the operating rod are created by ejected cartridge cases. This is perfectly normal for the M14 type rifle. The operator may notice one or two "ping" sounds when firing the rifle. This sound is made by the hammer during dry firing. When firing live ammunition, the sounds are caused by the hammer and the flash suppressor.

The M14 type rifle should not be cleaned or lubricated too much but neither should its care be ignored. Service conditions and the level of match conditioning should drive the preventive maintenance regimen for each M14 type rifle. Appropriate, not excessive, preventive maintenance facilitates excellent rifle performance. To remove light surface rust from phosphate coated parts, gently rub the rusty areas with 0000 steel wool and CLP. The phosphate finish will not be harmed. A USGI M14 rifle will have a 250 meter sight zero at 4.6 centimeters above the point of aim at 25 meters using M80 cartridges.

Storage - For long term storage, several weeks or more, the U. S. Army and National Guard Marksmanship Units recommend storing match conditioned (bedded stock) M14 type rifles muzzle down with the trigger guards unlatched and hung from the rear sling swivel. This keeps the weight of the barreled action off the stock bedding. Otherwise, M14 type rifles may be stored with the muzzle up.

Your Relationship with M14 Gunsmiths and Firearms Dealers

The following suggestions will enhance your experience with these professionals if you adhere to them: 1) keep a written detailed journal of problems with your firearm 2) do not whine 3) listen before you speak 4) be willing to learn 5) be patient 6) accept the fact that quality service is never the least expensive 7) submit clear and complete written information describing the problem(s) or work to be done in the same package with your insured and unloaded firearm 8) be polite 9) educate yourself on your firearm and 10) the original equipment manufacturer should be contacted first if possible.

The following is a partial list of gunsmiths with experience working on M14 type rifles. No particular business is being endorsed.

Brown, Ted Shooters Den Jacksonville, OR www.tedbrownrifles.com Ted retired as a Master Sergeant from the U. S. Air Force and Air National Guard. He has been a team member, armorer and coach for National Guard shooting teams and successfully coached Junior Rifle Teams for several years. He earned the U. S. Air Force Distinguished Rifleman Badge (# 214) and Master Class designation in 1988. He has built National Match M14 type rifles since 1978. Ted specializes in M1 Garand and Carbine, M14 type and semiautomatic M16 style rifles.

Corcoran, Ken North Pole, AK 907-488-3258. Ken has been working on M14 type rifles since the late 1970s. He served over twenty years in the U. S. Army. He was an AMU armorer and served over twenty years in the U. S. Army. He has built match winning M14 rifles for competition shooters and battle ready M14 rifles for troops deploying to Iraq in the Second Gulf War.

Dow, Bruce R. Dow Arms Room Dade City, FL www.dowarms.com Bruce was a competitive pistol and high power rifle shooter. In the 1980s, he was a member of the New Hampshire State Rifle Team for five years at Camp Perry. He earned shooting awards with his Super Match M1A rifle. He has been a gunsmith since the 1960s and a source of knowledge for books on firearms and court cases involving firearms.

Evan's Gunsmithing and Shooter's World Orange, CA www.egsw.com/home.htm
Featured in *American Survival Guide* and *Gun World*.

Ferrante, David Heart Mountain Precision Powell, WY Dave is a High Master shooter with the M14 type rifle as well as a highly reputable M14 gunsmith.

Hansen, Troy Flagstaff, AZ www.fullcanopyarmory.com Troy is a U. S. Army veteran. He has years of experience working on the rifles he specializes in, M1 Garand, M14 and M16.

Leisinger III, Carl A. Trenton, NJ <http://radomski.us/njhp/major.htm>

LEE EMERSON

Luhmann, Thomas T.L.C. Gunworks Clovis, CA www.tlccgunworks.com T.L.C. Gunworks was established in 1989. Tom Luhmann specializes in the M1 Garand and M1A.

McKee, Clint Fulton Armory Savage, MD www.fulton-armory.com

Morris, Ronnie Match Service Works Madison, TN

Pierce, Eric National Match Armory Rendon, TX www.nationalmatcharmory.com

Smith, Ron Smith Enterprise, Inc. Tempe, AZ www.smithenterprise.com

Strait, Tim Warbirds Custom Guns Houston, TX <http://www.warbirdscustomguns.com>
Tim has thirty years experience as a military armorer and commercial gunsmith specializing in Mauser, M1 Garand, and M14 type rifles and M1911 pistols. His experience includes performing M1A receiver warranty work during the 1980s for Springfield Armory, Inc. Tim has performed hundreds of USGI bolt conversions on Chinese M14 receivers.

Tabor, Frank Tabor's Shooters Supply San Bruno, CA

Tank, Jon Tank's Rifle Shop Fremont, NE www.tankrifleshop.com Jon specializes in M1 Garand and Carbine, M14 type, and M16 style rifles and Remington shotguns.

Appendix A

The Military M14

Table 1: Elements of Alloy Steels

Element of Alloy Steel	Advantages and Disadvantages
carbon	increases hardness, strength and brittleness
chromium	increases hardenability and corrosion and wear resistance
iron	principal element of steel
manganese	increases hardenability by 1) lowering transformation points and causing those transformations to be sluggish 2) counteracts the brittleness effect from sulfur
molybdenum	prevents grain growth resulting in uniformity of hardness and high strength
nickel	increases toughness, ductility and corrosion resistance
phosphorus	improves strength and machinability but has to be limited to prevent brittleness
silicon	improves hardness and corrosion resistance
sulfur	improves machinability but increases brittleness
vanadium	increases strength while retaining ductility

Table 2: Composition of AISI 8620, AISI 4140 and AISI 416 Steels

Element of Composition	AISI 8620 Alloy Steel	AISI 4140 Alloy Steel	AISI 416 Stainless Steel
carbon	0.18 to 0.23 %	0.38 to 0.43 %	0.15 %
chromium	0.4 to 0.6 %	0.8 to 1.1 %	13 %
iron	major element	major element	major element
manganese	0.7 to 0.9 %	0.75 to 1.0 %	1.25 % maximum
molybdenum	0.15 to 0.25 %	0.15 to 0.25 %	0.6 % maximum
nickel	0.4 to 0.7 %		
phosphorus	0.035 % maximum	0.035 % maximum	0.06 % maximum
silicon	0.15 to 0.35 %	0.15 to 0.35 %	1.0 % maximum
sulfur	0.04 % maximum	0.04 %	0.15 % minimum

Table 3: Properties of AISI 8620, AISI 4140 and AISI 416 Steels

Property	AISI 8620 Alloy Steel	AISI 4140 Alloy Steel	AISI 416 Stainless Steel
density (lb/in ³)	0.283	0.28	0.28
specific gravity	7.8	7.83	7.7
specific heat (BTU/lb/degrees F)	0.1	0.114	0.11
melting point (degrees F)	2600	2580	2714
thermal conductivity (BTU-in/ft ² -h-degrees F)	180.3	159.5	172.6
mean coefficient of thermal expansion (x 10 ⁻⁶ in/in/degree F)	6.6	7	5.5
modulus of elasticity in tension (x 10 ⁶ psi)	31	33	29

Table 4: Suppliers of USGI Rifle Grease

Supplier and Original CAGE Code	Product Name and Type	Year Manufactured
BG & O Co. (Kansas City, MO)	Plastilube - mineral oil with bentonite clay and additives	1963
Fiske Brothers Refining Co. (Newark, NJ and Toledo, OH) CAGE Code = 73219 for NJ and 9N579 for OH	Lubriplate 130-A or RG-62-A - mineral oil with calcium soap and additives	1969, 1985, 1999
International Lubricant Corp. (New Orleans, LA) CAGE Code = 74898	DGSC-SSH (1992) - mineral oil with thickening agent and additives	1963, 1992
International Supply Corp. (Richmond, VA) CAGE Code = 6A908	Lubriplate RG-62-A - mineral oil with calcium soap and additives	1996
Parr, Inc. Warren Refining Division (Cleveland, OH) CAGE Code = 02307	Plastilube - mineral oil with bentonite clay and additives	1971
Southwest Grease & Oil Co., Inc. (Wichita, KS)		1965
Witco Chemical Corp. Southwest Petro-Chem Division (Olathe, KS) CAGE Code = 3V856	SA 824 1027 - mineral oil with barium soap and additives	1990

Table 5: Select Properties of Some Military Greases

Property	MIL-G-46003-A Lubriplate 130-A	MIL-G-46003 Plastilube	MIL-PRF-10924-G Grease, Automotive and Artillery NATO Code G-403
NLGI Number	2.5	2	2
Type	mineral oil with calcium soap and additives	mineral oil with bentonite clay and additives	ingredients are the perogative of the contractor
Service Temperature (degrees Fahrenheit)	20 to 170	- 49 to + 356	up to 320 minimum
Dropping Point (degrees Fahrenheit)	200	none	428
Flash Point (degrees Fahrenheit)	400	non-flammable	470
Boiling Point (degrees Fahrenheit)	> 550	> 428	700

The reader is referred to the applicable military specification for a complete listing of performance requirements for the greases and oils listed in these tables.

Table 6: Select Properties of Some Military Lubricating Oils

Property	MIL-L-46000-C Lubricant, Semi-fluid (Automatic Weapons) NATO Code O-158	MIL-PRF-14107-D Lubricating Oil, Weapons, Low Temperature NATO Code O-157	MIL-PRF-63460-E Cleaner, Lubricant and Preservative NATO Code S-578
Kinematic Viscosity	10.0 centiStokes minimum at 104 degrees F	5.8 centiStokes minimum at 100 degrees F	14.0 centiStokes minimum at 104 degrees F
Type	synthetic lubricant in a lithium based thickener	ingredients are the perogative of the contractor	ingredients are the perogative of the contractor
Service Temperature (degrees F)	- 65 to + 260	- 70 to 0	- 60 to + 160
Pour Point (degrees F)	none specified	- 75 maximum	- 74
Flash Point (degrees F)	none specified	305 minimum	149

The static coefficients of friction for various materials obtained from several sources are listed for the benefit of the reader. Values for kinetic coefficients of friction are usually significantly lower. The lower the value for coefficient of friction the less resistance there is to sliding contact on the material.

Table 7: Coefficient of Static Friction for Select Materials

Material(s)	Coefficient of Static Friction
clean aluminum on aluminum	1.35
clean iron on iron	1
clean steel on steel	0.6 to 0.8
clean titanium nitride on steel	0.4 to 65
clean chromium on chromium	0.41
clean nitrocarburized steel	0.16 to 0.33
ice on ice	0.1
thinly greased steel on steel	0.05 to 0.20
polytetrafluoroethylene on steel	0.04
SAE 30 oil lubricated nitrocarburized steel	0.03 to 0.12
human shoulder, elbow, wrist and finger joints	0.01

Table 8: Harrington & Richardson X Series Rifles

Serial Number	Description
X-26	M14 Simulator .22LR caliber semi-automatic only - H&R auction
X-35	R14 Experimental Rifle with folding stock - NFA Registered transferable
X-40	M14 Guerilla Rifle with folding stock - NFA Registered transferable
X-42	M14 Guerilla Rifle - Springfield Armory National Historic Site
X-45	M14 Guerilla Rifle - Springfield Armory National Historic Site
X-81	R14 Experimental Rifle - NFA Registered transferable
X-82	R14 Experimental Rifle - NFA Registered transferable
X-85	R14 Experimental Rifle - NFA Registered transferable

M14 RIFLE HISTORY AND DEVELOPMENT

Serial Number	Description
XX1	M14 Simulator .22LR caliber select fire - NFA Registered transferable

Table 9: M14 Rifle on Television

Show Title	Network/Producer	Episode and Original Air Date
24	Fox	Day 8: 8:00 AM - 9:00 AM 04/12/10 Day 8: 12:00 PM - 1:00 PM 05/10/10
<i>After Armageddon</i>	History Channel	01/05/10
<i>Alias</i>	ABC	
<i>Almost Human</i>	Fox	"Are You Receiving" 11/25/13
<i>American Dreams</i>	NBC	
<i>American Guardian</i>	Outdoor Channel	"AMU SDM" 05/27/09
<i>American Guns</i>	Discovery Channel	"Wounded Vet Rifle / 60s Icons" 10/31/11
<i>American Masters</i>	PBS	"The Doors: When You're Strange" 05/12/10
<i>American Rifleman Television</i>	Outdoor Channel	"John Garand's Legacy: The M14" 02/08/12
<i>Ancient Discoveries</i>	History Channel	"Ancient Super Navies" 04/27/08
<i>Archer</i>	FX	"El Contador" 01/26/12 "Bloody Ferlin" 02/23/12 "The Wind Cries Mary" 01/24/13
<i>Army Wives</i>	Lifetime	"The Hero Returns" 07/06/08 "Guns & Roses" 05/09/10

LEE EMERSON

Show Title	Network/Producer	Episode and Original Air Date
<i>Arrow</i>	The CW	"Lone Gunmen" 10/24/12 "Home Invasion" 04/24/13
<i>Battle Stations</i>	Military Channel	"Huey Helicopter: Air Armada" 11/04/06
<i>Battlefield Diaries</i>	Military Channel / Normandy Films	"Kiowa Down" 09/26/05
<i>Battlefield Vietnam</i>	PBS / Time Life Video	"Showdown in the Iron Triangle" 1998 "War On The DMZ" 1998
<i>Beverly Hillbillies</i>	CBS	"Military School" 12/15/65
<i>Burn Notice</i>	USA	"Family Business" 07/26/07 "Turn and Burn" 07/17/08 "Do No Harm" 01/22/09
<i>Carrier</i>	PBS	"Squared Away" 04/28/08
<i>Combat Zone</i>	Discovery Channel	"Invasion of Grenada" 02/10/07 "Battle of Hue, Vietnam" 02/17/07 "Ambush in Hawijah" 03/24/07 "Patrol Boat Rescue Vietnam" 04/21/07
<i>Criminal Minds</i>	CBS	"Divining Rod" 05/02/12
<i>CSI Crime Scene Investigation</i>	CBS	"Inside the Box" 05/15/03
<i>CSI Miami</i>	CBS	"Shock" 05/08/06 "Guerillas in The Mist" 12/10/07
<i>DEFCON 2: Cuban Missile Crisis</i>	Military Channel	Television Special 07/07/07
<i>ER</i>	NBC	"21 Guns" 05/18/06
<i>Explorer</i>	National Geographic	"Supercarrier" 12/13/06 "Iraq's Guns for Hire" 01/21/07

M14 RIFLE HISTORY AND DEVELOPMENT

Show Title	Network/Producer	Episode and Original Air Date
<i>Falling Skies</i>	TNT	"Live and Learn" 06/19/11 "Sanctuary" Part 2 07/24/11 "Worlds Apart" 06/17/12 "Molon Labe" 07/22/12 "Badlands" 06/16/13
<i>Family Guy</i>	Fox	"Saving Private Brian" 11/05/06
<i>Fight Science</i>	National Geographic	"Special Ops" 01/27/08
<i>Firefly</i>	Fox	"Heart of Gold" 06/23/2003
<i>For God & Country: A Marine Sniper's Story</i>	MSNBC	Documentary 12/12/06
<i>Future Weapons</i>	Discovery Channel	"Future Combat" 03/12/07 "Firepower" 11/15/07
<i>Gomer Pyle, U.S.M.C.</i>	CBS	Credits scenes from second season onward
<i>Hawaii Five-O</i>	CBS	"Savage Sunday" 10/22/69 "Murder: Eyes Only" 09/12/75 "Ha'uoli La Ho'omoaika'i" 11/22/13
<i>Heroes Under Fire</i>	History Channel / Wild Eyes Productions	"Caught In The Middle" 12/16/05
<i>High Impact: M-16</i>	History Channel	04/03/09
<i>Homeland</i>	Showtime	"Two Hats" 11/25/12 "The Choice" 12/16/12
<i>Human Target</i>	Fox	

LEE EMERSON

Show Title	Network/Producer	Episode and Original Air Date
<i>In the Heat of the Night</i>	NBC	
<i>Inside The Vietnam War</i>	National Geographic	01/27/09
<i>It Takes A Thief</i>	Discovery Channel	"Station Break" 10/17/06
<i>Jericho</i>	CBS	"Coalition of the Willing" 05/02/07 "Termination for Cause" 03/11/08
<i>Jonny Quest</i>	ABC	"Treasure of the Temple" 10/23/64 "The Robot Spy" 11/06/64
<i>Law & Order: Criminal Intent</i>	NBC	"The Pilgrim" 11/17/02
<i>Las Vegas</i>	NBC	May 2005 episode
<i>Leverage</i>	TNT	"The Rundown Job" 09/16/12
<i>Lock N' Load</i>	History Channel	11/14/08 pilot 10/10/09 "Ammo"
<i>Lost</i>	ABC	"Three Minutes" 05/16/06 "Every Man for Himself" 10/25/06 "Dead is Dead: 04/08/09
<i>Machines of War</i>	National Geographic	"Guns: Machines of War" 01/16/07
<i>Mail Call</i>	History Channel	# 31 08/10/03 # 45 02/08/04 # 50 04/04/04 # 65 09/26/04 # 89 11/11/05
<i>Man Moment Machine</i>	History Channel	"JFK & the Crisis Crusader" 01/16/07

M14 RIFLE HISTORY AND DEVELOPMENT

Show Title	Network/Producer	Episode and Original Air Date
<i>Military Showcase</i>	Military Channel	"Coast Guard at War" "Corpsmen and Medics" 01/24/07 "Navy Bomb Squad" "Task Force Devil" 09/29/06 "The U. S. Army Range" 03/30/07 "Vietnam's Helicopter Heroes" 03/15/07
<i>Mission Impossible</i>	CBS	"TOD-5" 10/14/72
<i>Modern Marvels</i>	History Channel	"Axes, Swords and Knives" 05/07/02 "Camouflage" 06/18/02 "M16" 09/14/02 "Tunnels of Vietnam" 11/13/02 "Machine Guns" 04/30/03 "Bullets" 08/13/03 "Super Ships" 04/29/10
<i>Modern Sniper</i>	Military Channel	"Army" 02/18/10 "Coast Guard" 02/28/10
<i>Monk</i>	USA	"Mr. Monk Goes Camping" 11/06/09
<i>MythBusters</i>	Discovery Channel	James Bond Special Part 1 01/16/08 "Dive to Survive" 03/31/10
<i>Navy SEALs: BUDS Class 234</i>	Discovery Channel	2000
<i>NCIS</i>	CBS	"Engaged" Part 1 11/08/11 "Engaged" Part 2 11/15/11
<i>Person of Interest</i>	CBS	"Extremis" 04/25/13 "The Devil's Share" 11/26/13
<i>Return of the Pirates</i>	History Channel	10/21/07
<i>Rocket City Rednecks</i>	National Geographic	"Close Encounters of the Redneck Kind" 10/12/11

LEE EMERSON

Show Title	Network/Producer	Episode and Original Air Date
<i>Sarah Palin's Alaska</i>	The Learning Channel	12/12/10
<i>Secrets of SEAL Team 6</i>	Discovery Channel	07/10/11
<i>Secrets of the Dead</i>	PBS	"Deadliest Battle" 05/20/10
<i>Shooting Gallery</i>	Outdoor Channel	"Knob Creek 1" 09/14/07
<i>Shootout</i>	History Channel	"Return to Fallujah" 07/19/05 "Tet Offensive" 12/08/06
<i>Sniper Deadliest Missions</i>	History Channel	09/24/10
<i>Sniper: Inside the Crosshairs</i>	History Channel	12/20/09
<i>Snipers</i>	History Channel	"Stalk & Kill" 11/11/06
<i>Steven Seagal: Lawman</i>	A & E	"Medicine Man" 12/16/09
<i>Supercarrier</i>	National Geographic	"USS Ronald Reagan" 09/15/04
<i>Tactical Arms</i>	Sportsman Channel	"SOCOM II" 02/19/10
<i>Tales of the Gun</i>	History Channel	"Guns of Valor" 2005
<i>The A-Team</i>	NBC	"Mexican Slayride" 01/23/83
<i>The Last Templar</i>	NBC	Television Movie 01/25/09 and 01/26/09
<i>The Lieutenant</i>	NBC	Aired from 09/14/63 to 04/18/64

M14 RIFLE HISTORY AND DEVELOPMENT

Show Title	Network/Producer	Episode and Original Air Date
<i>The Man From U.N.C.L.E.</i>	NBC	"The Survival School Affair" 11/20/67
<i>The Marines</i>	PBS	02/21/07
<i>The Outer Limits</i>	ABC	"The Brain of Colonel Barham" 01/02/65
<i>The Shield</i>	FX	"Spanish Practices" 06/05/07
<i>The Time Tunnel</i>	ABC	"Revenge Of The Gods" 10/21/66
<i>The Walking Dead</i>	AMC	"Walk With Me" 10/28/12 "Prey" 03/17/13 "Welcome to the Tombs" 03/31/13
<i>The Wrong Mans</i>	BBC	"Wanted Mans" 10/22/13
<i>The X-Files</i>	Fox	"The Field Where I Died" 11/03/96 "Tunguska" 11/24/96
<i>Top Guns</i>	History 2 Channel	"Rifle Rundown" 02/16/12
<i>Top Shot</i>	History Channel	"The Long Shot" 06/06/10 "Sweating Bullets" 02/14/12
<i>Top Sniper</i>	Military Channel	Special 01/14/08 "Aerial Mission" 2009 "Urban Combat Education" 03/23/09
<i>Top Ten</i>	Military Channel	"Armor" 2010 "Combat Rifles" 2006 "Infantry Fighting Vehicles" 2006 "Tanks" 2006
<i>Tour of Duty</i>	CBS	two episodes in the third season
<i>U. S. Navy SEALs - In Harm's Way</i>	Military Channel	Television Special 12/15/07

LEE EMERSON

Show Title	Network/Producer	Episode and Original Air Date
<i>Vietnam in HD</i>	History Channel	"The Beginning" 11/08/11 "Search & Destroy" 11/08/11 "The Tet Offensive" 11/09/11 "An Endless War" 11/09/11 "A Changing War" 11/10/11
<i>War Stories</i>	Fox News Channel	"Flashpoint Vietnam The Road to War" 04/10/05 "Terror in Paradise" 11/03/07
<i>Weaponology</i>	Military Channel	"Rapid Fire" 01/29/07 "US Army Rangers" 12/18/07
<i>Wild Justice</i>	National Geographic	"Marijuana Mountains" 11/28/10 "Deer Meat for Meth" 12/08/10 "Gold Diggers" 01/26/11
<i>Woodstock Now and Then</i>	VH1	Documentary 08/14/09

Table 10: Springfield Armory National Historic Site M14 Rifles

Serial Number	Comment
D.D.E. 1	one of two presentation M14 rifles made for President Eisenhower and used as an endurance test piece
X-42	Harrington & Richardson M14 Guerilla Rifle
X-45	Harrington & Richardson M14 Guerilla Rifle
2000	first production M14 rifle
10117	M14E2 rifle
106436	M14 rifle with the experimental X-1 40 MM grenade launcher
539712	M14E1 Type V rifle
540833	M14 rifle used as an endurance test piece for 6000 rounds
545480	M14 rifle used as an endurance test piece for 30,000 rounds
552554	M14 M rifle
562823	M14 M rifle

Table 11: U. S. Government Exports of M14 Rifles to Foreign Nations

Nation	Quantity	Year(s)	Transfer Method	Rifle Model
Belize	15	1994	EDA	M14
Chad	3,503	1983	MAP	M14A1
Chad	2,000	1987	MAP	M14
Chile	12	1994	EDA	M14
Colombia	10,000	1990-92	FMS	M14
Estonia	40,500	1998	EDA	M14
Ethiopia	23,451	1971-75	MAP	M14
Greece	9	1995	EDA	M21
Israel	35,000	1973		M14
Israel	Not available	1978	FMS	M14
Latvia	10,000	1996	EDA	M14
Latvia	30,500	1999	EDA	M14
Lithuania	40,000	1998	EDA	M14
Philippines	908	1966	MAP	M14
Philippines	3,638	1994	EDA	M14
Senegal	20	1992	MAP	M21
Taiwan	8,000	1969	MAP	M14
Taiwan	30,450	1995	EDA	M14
Turkey	200	1995	EDA	M14

EDA = Excess Defense Articles program FMS = Foreign Military Sales program MAP = Military Assistance Program

Table 12: M14E1 Rifle Types

Model	Description
M14E1Type I	no information available, tool room folding style model
M14E1Type II	under folding style with left side mounted front and rear sling swivels
M14E1Type III	under folding Soviet AKM style with left side mounted front and rear sling swivels

LEE EMERSON

M14E1Type IV	under folding style with folding front and rear pistol grips and hinged butt plate
M14E1Type V	left side folding style with folding front and rear pistol grips and hinged butt plate

Table 13: M14 Type Rifle Headspace Dimensions

Reference	GO (inches)	NO GO (inches)	FIELD REJECT (inches)
SAAMI	1.630	1.634	1.638
Drawing F7267000 Rifle, 7.62 MM, M14 Revision AH dated January 24, 1986	1.6355	1.6405	
Drawing F7790476 Rifle, 7.62 MM, M14 NM Revision D dated April 10, 1969	1.6355	1.6385	
1967 National Match Rifles - U. S. Army Materiel Command	1.6355	1.6385	
AMU M14 MTU-NM Manual	1.631	1.635	
National Guard MTU Accurizing the M14 Service Rifle	1.632	1.636	
SA-SIP-7790476	1.6355	1.6385	
MIL-R-45979 dated 24 Sep 76 Military Specification M14 NM	1.6355	1.6385	
TI-02648A-25/10B November 1972	1.630	1.638	
TM 9-1005-223-34 August 1971 and TM 9-1005-223-35 July 1968			1.6455
DMWR 9-1005-223 July 1970 and October 1971	1.6355	1.6415	
TM 02648C-24&P/2 July 2000	1.632	1.638	

M14 RIFLE HISTORY AND DEVELOPMENT

NSWC Code 4081 Form M14 USCG	1.632	1.6415	
---------------------------------	-------	--------	--

Ammunition Variety and Suppliers - The U. S. government (Frankford Arsenal, Lake City, Twin Cities and Winchester) has produced 7.62 x 51 mm NATO ammunition as follows:

Table 14: 7.62x51 mm NATO Ammunition Cartridges

Cartridge	Description
M59 Ball	150.5 grain mild steel core bullet with lead tip and base all contained inside a gilding metal jacket, produced from 1955 to 1960, also made by Federal and Remington Arms
M60 High Pressure Test	171.5 grain bullet with tin coated case
M61 Armor Piercing	150.5 grain boat tail steel core bullet with black tip
M62 Tracer	142 grain bullet with orange tip, traces out to 800 meters
M62 Tracer Overhead Fire Mission	146 grain bullet with red tip
M63 Dummy	case has six longitudinal flutes, no primer
M64 Grenade	rosette crimped case mouth, original drawing dated July 1955, first produced by Lake City in 1962
M80 Ball	146 grain lead-antimony core bullet, original drawing dated January 1962
M80 Ball Overhead Fire Mission	149 grain bullet
M82 Blank	double tapered neck, front portion replicates loaded cartridge length for reliable feeding
M118 Match	172 grain bullet headstamped MATCH or NM, no NATO circle-cross, primer not crimped to enable marksmanship units to easily reload training ammunition, adopted by 1964
M118 Special Ball	172 grain bullet usually headstamped L C and the last two years of manufacture at ten, two, four and eight o'clock for each character, no NATO circle-cross
M118LR	175 grain hollow point boat tail bullet
M160 Frangible Ball	108.5 grain lead and phenolic resin bullet with green and white tip or green tip with white primer annulus

LEE EMERSON

M172 Dummy	149 grain bullet with black oxide finish case that has no primer or primer vent hole
XM178 Ball Overhead Fire Mission	bullet made of bronze to prevent fragmentation
M192 Blank	rosette crimped case mouth with red wad or purple lacquer
XM192E1	lightweight ball with white tip
M198 Duplex Ball	two copper plated AISI 1112 steel core bullets
XM256E1	low recoil steel core copper jacketed bullet with white tip, developed and tested by Frankford Arsenal in 1975, the bullet is physically the same as the M198 cartridge upper bullet, 80 to 84 grains
M276 Dim (Night Vision) Tracer	140 to 150 grain bullet with violet tip after 09/94, green tip with pink primer annulus before 10/94
M852 Match	168 grain hollow point boat tail bullet headstamped MATCH, case body knurled about ½ " from the head, primer not crimped
M948 Saboted Light Armor Penetrating (SLAP)	tungsten bullet in an amber plastic sabot, produced in 1988 by Winchester-Western
M959 SLAP Tracer	M196 5.56 mm tracer bullet in a plastic sabot
M973 Training Ball	fluted bullet
M974 Training Tracer	fluted bullet with red tip
M993 Armor Piercing	126.6 grain bullet with black stripe at the tip
Mk 316 Special Ball, Long Range	175 grain hollow point boat tail bullet
Mk 319 Ball, Barrier	130 grain bullet

Throughout its history, the M14 rifle has been evaluated by the U. S. military for various purposes. The table below is an attempt to chronicle some of the more significant tests the M14 was a part of.

Table 15: Significant Military Tests Involving the USGI M14 Rifle

Test Date(s) and Location	Lead Agency	Report Title and Date	Comments
1956 - Fort Benning and Marine Test Center Quantico	US Army Aberdeen Proving Ground	<i>46th Report on Project No. TS2-2015</i> 1956	Comparison tests of the T44E4, M1 Garand and T48
July and August 1958 - Aberdeen Proving Ground and Fort Benning	US Army Continental Army Command	<i>Report of Project NR 2787 Evaluation of Small Caliber High Velocity (SCHV) Rifles</i> September 19, 1958	Comparison of the M14, Winchester .224 and ArmaLite .223 caliber rifles
March 1958 - Fort Benning	US Army Infantry Board	<i>Evaluation of Small Caliber High Velocity Rifles, ArmaLite (AR-15)</i> May 1958	M14 rifles are test control specimens for .222 Special ammunition testing
December 01, 1958 to March 22, 1959 - Fort Ord and Hunter Liggett Military Reservation (CA)	US Army Combat Developments Experimentation Center	<i>Rifle Squad Armed with Lightweight High-Velocity Rifle</i> May 30, 1959	Field trials of the M14, Winchester Lightweight Military Rifle and the ArmaLite .223 caliber rifle
December 1960 to January 1961 - Lackland AFB	US Air Force Lackland Air Force Base	not available	Comparison of the M14, M2 Carbine and Colt's Manufacturing Co., Inc. .223 caliber rifle
May 22, 1961 to July 31, 1961 - Fort Benning	US Army Infantry School Fort Benning	<i>Rifle Squad and Platoon Evaluation Program 22 May 61 - 31 July 61</i> November 13, 1961	Evaluation of infantry squad and platoon composition

LEE EMERSON

September 28, 1961 to January 30, 1962 - Aberdeen Proving Ground	US Army Aberdeen Proving Ground Development and Proof Services	<i>Tests for Ad Hoc Committee on Accuracy and Targeting of 7.62-mm Ammunition and M14 Rifles Report No. DPS-471</i> March 1962	Inspection and test of twenty-one sample M14 rifles
October 30 to December 15, 1961 - Hunter Liggett Military Reservation (CA)	US Army Combat Development Experimentation Center	<i>Rifle Platoon Firepower Experiment</i> March 1962	Evaluation of infantry squad and platoon composition
November 01, 1962 to December 05, 1962 - Aberdeen Proving Ground	US Army Aberdeen Proving Ground Development and Proof Services	<i>Comparative Evaluation of AR-15 and M14 Rifles</i> by George Hendricks December 1962	Comparison of the M14 and a .223 caliber M16 type rifle
Forty-eight documents cited including various U. S. Army reports	US Army Combat Developments Center	<i>Rifle Evaluation Study</i> December 20, 1962	Comparison of the M14, M14 (USAIB), AR-15, AK47 and SPIW, portions of this report were classified Secret until 1974
March 1964 to May 15, 1964 - Fort Benning	US Army Aberdeen Proving Ground Human Engineering Laboratories	<i>Technical Memorandum 1-65 Auditory and Acoustical Evaluation of Several Shoulder-Rifles</i> January 1965	Comparison of the effects of the M14 and other rifles on the hearing acuity of soldiers
June 1965 to November 1965 - Fort Benning	US Army Infantry Board	<i>Small Arms Weapons Systems</i> December 1965	Comparison tests of M14, M14E2, M60, XM16E1, CAR-15, HK33, AR18, and Stoner 63

M14 RIFLE HISTORY AND DEVELOPMENT

October 22, 1965 to February 21, 1966 - Fort Ord	US Army Combat Developments Command Experimentation Command	<i>Small Arms Weapon Study Field Experiment</i> May 1966	Comparison of the M14, M14E2, M16E1, Stoner, and AK47
March 1967 - Fort Benning	US Army Aberdeen Ballistic Research Laboratories	<i>Accuracy of Rifle Fire: SPIW, M16A1, M14 Memorandum Report No. 1919</i> March 1968	Comparison of the M14, SPIW, and M16A1 for accuracy in automatic mode
Data obtained from several sources	US Army Aberdeen Research and Development Center	<i>Technical Report No. 1 M16 Rifle System Reliability and Quality Assurance Evaluation</i> July 1968	Analysis of data concerning reliability of the M14 and M16A1 rifles
1968 - Fort Benning	US Army MTU	August 1968	Accuracy tests of the M14 NM and M16 models
April 16 to August 19, 1970 - Aberdeen Proving Ground	US Army Aberdeen Proving Ground Material Testing Directorate	<i>Military Potential Test of Short Range Cartridges, 5.56-mm Ball, 7.62-mm Ball, and 7.62-mm Tracer</i> by Daniel Chmiel October 1970	Comparison of actual cartridge performance versus published data
May 01, 1977 to December 30, 1977 - Aberdeen Proving Ground	US Army Aberdeen Proving Ground	February 1978	Comparison of M21, modified M14, modified AR-10, M40A1, French FR-F1, Winchester M70, Parker-Hale 1200TX.

The following table lists the patents associated with the text of this volume. What is often taken for granted was once new and innovative.

Table 16: United States Patents

Patent No.	Date Filed	Date Approved	Inventor(s)	Description
870937	04 Apr 07	12 Nov 07	Thomas Watts Coslett	iron phosphate coating
1069903	15 Aug 12	12 Aug 13	Frank Richards	manganese phosphate coating
1886218	29 Jun 27	01 Nov 32	John M. Olin Alfons G. Schuricht	chromium plating of rifle barrels
1892141	21 Apr 30	27 Dec 32	John C. Garand	semi-automatic rifle with M1 style bolt
1907163	23 Nov 31	02 May 33	Joseph C. White	semi-automatic rifle with cutoff and expansion gas system
1929418	10 Dec 30	10 Oct 33	John C. Garand	rear sight base (M1, M14)
1996393	23 Nov 31	02 Apr 35	Joseph C. White	firearm breech closure and firing mechanism
2198610	22 Nov 33	30 Apr 40	John C. Garand	firearm extractor (M1, M14)
2287805	13 Nov 41	30 Jun 42	William B. Johnson	rifle rack (M1903, M1, BAR)
2293716	03 Feb 41	25 Aug 42	Van M. Darsey	zinc phosphate coating
2230654	01 Jul 39	04 Feb 41	Roy J. Plunkett	tetrafluoroethylene polymers
2337537	01 Jun 42	28 Dec 43	Bryan C. Arnold	M2 aiming device
2352191	21 Aug 43	27 Jun 44	John C. Garand	firearm hammer mechanism (M1, T20, M14)

M14 RIFLE HISTORY AND DEVELOPMENT

2357363	16 Jun 42	05 Sep 44	Hartley P. Smith	gun sling (M1, M14, M16)
2363520	16 Jul 42	28 Nov 44	Stanley W. Fish	combination cleaning tool
2377338	16 Mar 39	05 Jun 45	John C. Garand	firearm (improvements to the M1 rifle design)
2406011	17 Mar 44	20 Aug 46	John C. Garand	rear sight elevation and pinion assembly and windage knob (M1, M14)
2449962	26 Mar 46	21 Sep 48	Aaron Wachter and Nathan Stillman	volatile corrosion inhibitor chemical
2458510	09 Nov 45	11 Jan 49	John C. Garand Eli G. Cooper John R. Bird Harold C. Miller	grenade launcher sight attachment (M15 sight)
2462091	03 Jun 46	22 Feb 49	John C. Garand	collapsible stock (M14E1 Type I?)
2462836	01 May 47	01 Mar 49	Robert S. Barker Erne L. Ballinger Eli G. Cooper Parley F. Lamberi Edward C. Fletcher	magazine filler
2486400	07 Jun 46	01 Nov 49	John C. Garand	rear sight (M1, M14)
2489283	19 Sep 47	29 Nov 49	John C. Garand	bipod (M1)
2499378	10 Apr 46	07 Mar 50	John C. Garand	operating rod latch mechanism (T20)
2589227	27 Dec 49	18 Mar 52	Martin H. Colley	winter trigger (T44 and M14)

LEE EMERSON

2710476	06 Jun 46	14 Jun 55	John C. Garand	cartridge magazine latching system including the connector lock and operating rod spring guide (for M14)
2715789	26 May 49	23 Aug 55	John C. Garand	cartridge magazine (T31, T44, M14)
2783570	29 Apr 54	05 Mar 57	William R. Kunz	firearm magazine charger (for T44)
2791942	08 Jan 54	14 May 57	David C. Fletcher	rate reducer (for M1/T20)
2807112	24 Mar 54	24 Sep 57	John C. Garand	grenade launcher for gun with a gas cylinder (for T44)
2824322	21 Nov 55	25 Feb 58	Nicholas J. Angelica and Robert S. Henry	chamber brush (M1, M14 and M60)
2834137	15 Jun 56	13 May 58	William R. Kunz	ten round magazine charger (T44E4)
2841908	16 May 55	08 Jul 58	Eugene Bourquin	trigger device (T44E4)
2856720	14 Aug 56	21 Oct 58	William R. Kunz	ten round magazine charger (T44E4)
2864280	04 Apr 56	16 Dec 58	William E. Keller	device for inspecting barrel bore straightness
2869198	17 Aug 55	20 Jan 59	Merton L. Clevett, Jr.	pistol belt clip (M1956, ALICE load bearing equipment)
2883781	23 Oct 57	28 Apr 59	Earle M. Harvey	combination muzzle stabilizer, recoil brake, flash hider and grenade launcher (for M14)

M14 RIFLE HISTORY AND DEVELOPMENT

2894350	11 Apr 56	14 Jul 59	Stefan Kenneth Janson	firearm magazine charger (for BAR and others)
2920413	27 Jan 59	12 Jan 60	Andrew J. Marefka Irving L. Kintish	arctic trigger
2987821	19 May 59	13 Jun 61	Jack F. Kettler	multilite sights (M14)
3010370	05 Apr 61	28 Nov 61	Stanley D. Silsby	controlled burst firing mechanism (M16 type)
3011283	09 Mar 59	05 Dec 61	James S. Lunn Harry T. Douglas Vagn Vernegaard	reinforced plastic rifle stock (M1)
3091878	24 May 62	04 Jun 63	Giulio V. Savioli	auxiliary trigger with safety (M14)
3098311	27 Feb 62	23 Jul 63	Giulio V. Savioli	bolt lock (M14)
3100936	23 May 61	20 Aug 63	Nicholas J. Angelica	hooded eyepiece for sight aperture (M1 NM and M14 NM)
3141254	18 Apr 62	21 Jul 64	Giulio V. Savioli	auxiliary trigger with safety (M14)
3327422	23 Oct 65	27 Jun 67	Gerald Harris	bipod (Harris Bipods)
3340614	19 Oct 64	12 Sep 67	James M. Leatherwood	adjustment means for gun sighting scope (ART scopes)
3345771	07 Jan 66	10 Oct 67	Stanley D. Silsby	high capacity magazine and cooperating fire-arm structure (U. S. Army SPIW)
3363351	30 Mar 67	16 Jan 68	Melvin A. Smith	bolt assembly (Eagle Arms carbines)

LEE EMERSON

3404477	23 May 61	08 Oct. 68	Stanley D. Silsby	semiautomatic grenade launcher (for M14)
3404478	23 May 61	08 Oct 68	Stanley D. Silsby	semiautomatic grenade launcher (for M14)
3404479	15 Nov 61	08 Oct 68	Stanley D. Silsby	semiautomatic grenade launcher (for M14)
3408761	13 Jun 61	05 Nov 68	Stanley D. Silsby	grenade launcher firing mechanism with breech closure (for M14)
3416252	02 Apr 63	17 Dec 68	Stanley D. Silsby	grenade launcher combination firing and ejecting mechanism (M16 type)
3421242	23 May 61	14 Jan 69	Albert J. Lizza	grenade launcher ejector (for M14)
3431652	21 Sep 66	11 Mar 69	James M. Leatherwood	rangefinder and automatic reticle setter (ART scopes)
3492733	23 Apr 68	03 Feb 70	James M. Leatherwood	variable power sighting scope (ART scopes)
3565539	12 Jun 67	23 Feb 71	Joseph La Russa	collimated sight (M14)
3566527	12 Dec 68	02 Mar 71	Stanley D. Silsby	emergency firearm firing mechanism for grenade rounds (U. S. Air Force IMP)
3568350	17 Dec 68	09 Mar 71	Stanley D. Silsby	emergency firearm (U. S. Air Force IMP)
3604142	30 Jun 69	14 Sep 71	Stanley D. Silsby	four stack cartridge magazine (U. S. Army SPIW)

M14 RIFLE HISTORY AND DEVELOPMENT

3672089	13 Aug 69	27 Jun 72	Stanley D. Silsby	large capacity magazine (U. S. Army SPIW)
3724325	24 Aug 71	03 Apr 73	Stanley D. Silsby	firearm rate reducer (M16 type)
3942901	07 Dec 73	09 Mar 76	John Arne Ingemund Ekstrand	optical dot sight
3977296	04 Dec 74	31 Aug 76	Stanley D. Silsby	firearm hydraulic buffer assembly (M16 type)
4139959	13 May 77	20 Feb 79	William J. Howard William A. Harvey	nylon resin cartridge magazine
4538371	26 Oct 82	03 Sep 85	William J. Howard	nylon resin magazine charger
4896447	30 Dec 88	30 Jan 90	Paul A. Badoni	receiver insert for cleaning (for M1 and M14)
4955812	04 Aug 88	11 Sep 90	Banford R. Hill	video target training apparatus and method (for M14)
5012604	27 Mar 90	07 May 91	Laurence B. Rogers	adjustable trigger assembly for M14 firing mechanism
5265365	09 Jan 92	30 Nov 93	Charles A. Finn	pouch and cheek piece for long gun
5367812	28 Jun 93	29 Nov 94	Peter Lautrec	gun stock extender (for M14)
5596161	12 Jul 95	21 Jan 97	Sonja Sommers	firearm muzzle flash suppressor (for M14, M16, etc.)

LEE EMERSON

6810616	22 Jul 01	02 Nov 04	Guy Tal Ran Tal	cartridge magazine loader and unloader accessory
6839998	31 Jul 03	11 Jan 05	David P. Armstrong	replacement chassis stock system for firearms (Mk 14)
8091266	29 Jun 09	10 Jan 12	George Huang	firearm maintenance multi-tool (BAD T-1)
D296178	12 Nov 85	14 Jun 88	Melvin A. Smith	fish scaler
D390302	19 Jul 96	03 Feb 98	Larry Alan Bullock	M1A/M14 rifle recoil buffer

Appendix B

The Commercial M14

The following table is not a complete accounting of serial numbers. Note that some manufacturers (7.62mm Firearms, Arms Corporation of America, Inc., Maunz Match Rifle, Smith Enterprise, Inc., and Springfield Armory, Inc.) have issued custom serial numbers to receivers. Custom serial numbers are not accounted for in this table.

Table 17: Production of Commercial M14 Rifles

U. S. Company Name on the Finished Receiver	Receiver Model Marking	Highest Known Serial Number and Comments
7.62mm Firearms (Medina, OH)	M14 NM	51004 (cast receivers start at 51000) 52254 (forged receivers start at 52000) 40012 (fourth generation forged receivers)
A. R. Sales Co. (South El Monte, CA)	Mark IV	225 receivers (200 in the serial number range 1 to 225 and 25 in the range 226 to 250)
Arms Corporation of America, Inc., Armscorp USA, Inc. JRM / Armscorp (Silver Spring and Baltimore, MD)	M14, M14 NM, M21, T44, XM25	17677 (some serial numbers preceded by A) + 20 (S prefix serial number) + 13 (WTA prefix and four digit serial number) + 111 receivers (TFL prefix followed by serial number 001 to 081 + 30 receivers between 083 and 250) + 1 (T44 model)
Entreprise Arms, Inc. (Irwindale, CA)	M14A2	1119 (serial numbers preceded by E, EA or ABNI)
Federal Ordnance, Inc. (South El Monte, CA)	CSA14, M14, M14A, M14SA, M14S	60308 + 1411 (C series prefix serial numbers made for Century Arms International) + 500 (VCE / VME series)
Fulton Armory (Savage, MD)	M14, M14 NM, M21, XM25	702 (FA00000 series) + 50 (WR000 series) + 02573 (F00000 series) + 60 (M21)
Hesse, Ltd. (St. Paul, MN)	M14H	365
H&R Gun Co. (Smith Manufacturing Co.) (Holland, OH)	Semi-Auto 7.62MM-M14	1001 to 1140 observed

LEE EMERSON

James River Armory (Halethorpe, MD)	M14 NM, M14DMR, M14F	1002 (cast receivers begin at 1000) + 0040 (forged receivers begin at 0001) + 167 (forged ROCK-OLA series) + T14025 (forged Team M14 series)
LRB Arms (LRB of Long Island, Inc.) (Bellerose and Floral Park, NY)	M14SA, M25, T44E4	71 receivers (M14SA serial numbers less than 01201) + 03663 (M14SA serial numbers 01201 and higher) + 11356 (M25 serial numbers 10001 and higher) + 99 (TFL series) + 03845 (T44E4 series)
Maunz Match Rifle (Smith Manufacturing Co.) (Holland, OH)	MODEL 77, MODEL 87	5040 (MODEL 77 serial numbers are four digits) + 3030 (MODEL 87 serial numbers) + 50 (ASU serial numbers are five digits starting at 00010)
Maunz Manufacturing, Inc. (Toledo, OH)	U. S. RIFLE	1011 (four digit serial numbers) + 10 (EX series have one or two digit serial numbers)
National Ordnance, Inc. (South El Monte, CA)	?	2
Sarco, Inc. (Stirling, NJ)	M21	2
Smith Enterprise, Inc. (Mesa and Tempe, AZ)	EBR, M-14, M-14 NM, M-21, M25	more than 176 (select fire pre-'86 FA series) + 2603 (pre-'94 ban) + 80 to 85 (post-'94 ban serial numbers starting at 5000) + 1 (M-21) + 1 (M25) + 0214 (post- '09 M-14 series) + C0003 (EBR series)
Smith Ltd. (Smith Manufacturing Co.) (Holland, OH)	M-14	280 (serial numbers are four digits) + 5 (EX series have one digit serial numbers)
Springfield Armory, Inc. (San Antonio and Devine, TX) (Geneseo, IL)	M1A, M1-A, M-1A, M15	316000 (six digit serial numbers) + 100 (Even Hundred series) + 15 (Even Thou- sand series) + 0278 (SM series) + 227 (IDF series) + 556 (WF series) + 500 (VME series) + 68 (X series) + 1 (M15) + 500 (Camp Perry series) + 1500 AR series + 1500 MC series

The following table lists the production and export quantities according to the Bureau of Alcohol, Tobacco, Firearms and Explosives. These quantities include complete rifles and separate receivers.

M14 RIFLE HISTORY AND DEVELOPMENT

Table 18: Commercial M14 Production and Export Data

Year	Armscorp USA	LRB of Long Island	Springfield Armory, Inc.	Export by Springfield Armory, Inc.
1986			1,028	
1987			2,888	
1988			4,002	
1989			9,846	
1990			9,171	
1991			12,044	
1992			4,802	
1993			6,942	
1994	3,251		13,924	
1995	289		9,068	
1996	390		9,472	
1997	6		10,124	
1998	204		5,982	16
1999	189		10,515	2
2000	206 (10 export)		9,506	69
2001	271		8,124	12
2002	732		14,627	75
2003	480		15,353	232

LEE EMERSON

2004	367		not available	
2005	387	251	11,239	241
2006	27	360	13,675	152
2007	not available	940 includes all rifles	15,676	111
2008	43 - James River Manufacturing	not available	15,117	98
2009		6,490 includes all rifles	18,977	18
2010		5,255 includes all rifles	20,463	17
2011		5,053 includes all rifles	18,791	191

Table 19: Norinco M14 Rifles Imported Into the United States

Importer, City and State	Location of Markings	Known Serial Number Range
Century Arms International - St. Albans, VT	C00079 to at least C08312 - serial number on receiver left side, M14 SPORTER NORINCO CHINA C.A.I. ST ALB VT on the receiver heel, caliber marking on the barrel C08610 - all information on the receiver left side 92XX to 185928 - 1) barrel is marked C.A.I. St. ALB.VT. 2) serial number on the receiver left side 3) model number, caliber and CHINA either on the barrel or the receiver left side	C00006 to C09036 92XX to 9914 91043 to 971XX 1815XX to 186316
CJA - Southfield, MI	receiver left side	000001 to 008108

Table 20: Poly Technologies M14 Rifles Imported Into the United States

Importer, City and State	Location of Markings	Known Serial Numbers
Keng's Firearms Specialty - Atlanta, GA	country of origin, importer name, city and state on the barrel, other information on the receiver heel	000001 to 0272X, KFS and CAI markings on barrels to at least serial number 01965, serial numbers vary from three to six digits under 00078
Century Arms International - St. Albans, VT	receiver heel	C-1245 is the highest observed serial number
IDE USA - Southfield, MI	receiver left side	02804 to 25181

Table 21: Chinese M14 Rifles Imported Into Canada

Brand	Importer	Observed Serial Number Range
Norinco	Lever Arms Service Ltd.	AL000006 to AL000844
Norinco	Century Arms International	C09036 is the highest known serial number
Norinco	Marstar Canada	0088XXX to 0092XXX
Norinco	Bell Lifestyle Products, Dark International Trading Co., Lever Arms Service Ltd., Marstar Canada	001199 to 013398 with CJA or SFLD, MI marking
Norinco	Badger Arms Supply, Bell Lifestyle Products, Marstar Canada	2009XXXX to 20098100
Norinco	Canada Ammo	2011XXXX to 20111223
Norinco	Canada Ammo	2012XXXX to 20123298
Norinco	Dominion Arms, Marstar Canada	2013XXXX to 20130814
Poly Technologies	Century Arms International	00042 to 00565X
Poly Technologies	Bell Lifestyle Products	2009XXXX to 200908XX

Table 22: U. S. Federal Firearms Licenses

Federal Firearms License Type	Description
1	Title 1 firearm dealer or gunsmith
2	Title 1 firearm dealer who is a pawnbroker
3	Curio & Relic firearm collector
6	manufacturer of non-armor piercing ammunition and reloading components
7	manufacturer of Title 1 firearms and non-armor piercing ammunition and reloading components
8	importer of Title 1 firearms and ammunition
9	Title 1 and Title 2 destructive devices dealer
10	manufacturer of Title 1 firearms, Title 2 destructive devices and non-armor piercing ammunition and reloading components
11	importer of Title 1 firearms, Title 2 destructive devices and ammunition

The following table is an *informative guide* to state and local jurisdictions in the United States of America that restrict possession, sales or transfer of M14 magazines in some manner. Obviously, any changes in the laws restricting magazine capacity degrade the usefulness of this table. This table does not address any restrictions on handgun magazines, shotgun capacity, rimfire ammunition feeding device capacity or belt fed firearm feeding device capacity. The author has made reasonable effort to be thorough and accurate but the information cannot be guaranteed. The U. S. Department of Justice BATFE Publication P5300.5 31st Edition is a very good reference on firearms laws. However, even that publication is incomplete.

Disclaimer: Firearms owners are responsible for their actions. If you are unsure of the law, consult the local law enforcement agency and/or an attorney knowledgeable in firearms laws. This is not legal advice. Consult an attorney for any legal matter.

Table 23: M14 Magazine Capacity Restrictions in the USA

Jurisdiction	Centerfire Rifle Magazine Capacity Prohibited
California	> 10 rounds sold, transferred or made after January 01, 2000
San Francisco, California	> 10 rounds
Colorado	> 15 rounds possessed after July 01, 2013
Denver, Colorado (city and county)	> 20 rounds
District of Columbia	semi-automatic firearm with a magazine > 12 rounds capacity is defined as a machine gun and thus prohibited
Connecticut	> 10 rounds possessed after April 03, 2013
Aurora, Illinois	> 15 rounds
Chicago, Illinois	> 12 rounds
Franklin Park, Illinois	> 16 rounds
Oak Park, Illinois	> 10 rounds
South Bend, Indiana	> 15 rounds
Maryland	> 10 rounds possessed after September 30, 2013
Massachusetts	> 10 rounds made after September 13, 1994
Boston, Massachusetts	> 10 rounds
New Jersey	> 15 rounds

LEE EMERSON

New York	> 10 rounds possessed after January 15, 2014
Buffalo, New York	> 5 rounds
New York City, New York	> 5 rounds
Rochester, New York	> 5 rounds
Ohio	> 30 rounds when inserted into a rifle
Philadelphia, Pennsylvania	> 16 rounds

Table 24: Retail Suppliers of USGI M14 Related Items - 1970 and 1971

Supplier	Mailing Address City and State
Al's Corral	Atlanta, GA
Arasco	South El Monte, CA
Arizona Ordnance Co.	Phoenix, AZ
Armament Advisors	Phoenix, AZ
B. H. Service	Pandora, TX
Baron's	Oak Park, MI
Bill Edwards	Atlanta, GA
Ed Agramonte	Yonkers, NY
G.F.A. Sales Co.	Plumsteadville, PA
George R. Green & Sons	Willoughby, OH
Greeley Arms Co., Inc.	Fairfield, NJ

M14 RIFLE HISTORY AND DEVELOPMENT

Jerry's Guns & Ammo	Hibbing, MN
Karl Keely	
LJZ Surplus	Belton, TX
M. C. Matthews	Snellville, GA
Morris Lawing	Charlotte, NC
Ozzie's Gun Parts	Mineral, IL
P. Michaels	Batavia, IL
Pat's Gun Shop	Columbia, SC
R. Weatherwax	Chicago, IL
Ray A. McKnight	Texarkana, TX
Rydberg	Mountain View, CA
Sarco	Stirling, NJ
Sherwood Distributors	Beverly Hills, CA
The Musket Shop	Dumfries, VA
Thomas A. Buss	Springdale, PA
Tom Forrest	San Diego, CA

A M14 type rifle collector will often ask when his rifle was made. The information below was gathered in an attempt to help M14 type rifle owners answer that question. Use of the letter "X" in the serial number denotes that the specific digit was not revealed by the owner. In all cases, the serial number and month and year information was obtained from either the original FFL or the owner by way of a factory shipping tag, original purchase receipt or journal notes or by contacting the manufacturer. In the tables below, "purchased" means the month and year the original retail buyer paid for the receiver or rifle and "delivered" means the month and year the original FFL received the rifle or

receiver from the manufacturer. The term "shipped" refers to the month and year the receiver or rifle was shipped from the manufacturer to the original FFL. Unless otherwise noted, each serial number was shipped as a complete rifle from the manufacturer to the best knowledge of the author.

Table 25: Springfield Armory, Inc.

Receiver Serial Number	Month and Year	Comments
000065	12/71	sold as a receiver
000172	04/72	sold as a barreled receiver
000214	04/72	sold as a barreled receiver
000567	12/72	
000708	02/73	
001695	12/73	
001727	01/74	sold as a receiver
001977	04/74	
001988	04/74	sold as a barreled receiver
002127	04/74	sold as a barreled receiver
002167	09/74	sold as a barreled receiver
002168	09/74	sold as a barreled receiver
002282	09/74	sold as a barreled receiver
002283	09/74	sold as a barreled receiver
002284	09/74	sold as a barreled receiver
002293	09/74	sold as a barreled receiver
002709	11/74	sold as a receiver, lowest known Illinois serial number
002734	04/75	sold as a rifle, Illinois
002770	07/75	sold as a rifle, Illinois
002774	11/74	sold as a receiver, Illinois
002808	11/74	sold as a receiver, Illinois
002831	02/75	sold as a rifle, Texas marked barrel
002867	05/74	sold as a rifle, Texas

M14 RIFLE HISTORY AND DEVELOPMENT

002874	05/74	sold as a rifle, Texas
002923	11/74	sold as a receiver, Illinois
002979	11/74	sold as a receiver, Illinois
002985	12/74	sold as a receiver
002990	10/74	sold as a barreled receiver, Texas
002992	10/74	sold as a barreled receiver, Texas
002995	10/74	sold as a barreled receiver, Texas
002996	10/74	sold as a barreled receiver, Texas
002998	10/74	sold as a barreled receiver, Texas
003109	10/74	sold as a barreled receiver, Texas
003124	10/74	sold as a receiver, Texas
003129	10/74	sold as a barreled receiver, Texas
003139	10/74	sold as a barreled receiver, Texas
003140	10/74	sold as a barreled receiver, Texas
003142	10/74	sold as a receiver, Texas
003159	10/74	sold as a receiver, Texas
003210	10/74	sold as a receiver, Texas
003217	10/74	sold as a receiver, Texas
003270	11/74	sold as a receiver, Illinois
003306	10/74	sold as a receiver, Texas
003322	01/75	sold as a receiver
0034XX	01/75	sold as a barreled receiver
00356X	04/75	verified with Springfield Armory, Inc.

LEE EMERSON

003719	09/75	verified with Springfield Armory, Inc.
004140	11/75	sold as a receiver, verified with Springfield Armory, Inc.
004340	11/75	verified with Springfield Armory, Inc.
004357	12/75	
004379	04/76	sold as a receiver
0066XX	10/76	sold as a receiver
007297	06/77	
007600	09/77	
008893	08/78	
008977	10/78	
009991	01/79	
009334	02/79	
009586	10/78	sold as a receiver
009690	05/78	
010849	08/79	sold as a receiver
011714	11/79	
012027	12/79	
0125XX	02/80	
012788	04/80	
013000	10/74	sold as a barreled action, highest Texas serial number, stamped out of sequence
013195	05/80	
013308	05/80	
013853	06/80	
014095	06/80	sold as a receiver
014233	07/80	
014619	08/80	

M14 RIFLE HISTORY AND DEVELOPMENT

014806	09/80	
015516	10/80	
016206	01/81	
017912	05/81	sold as a receiver
018096	06/81	
018483	06/81	
019598	09/81	subsequent legal conversion to select fire
020528	11/81	
020676	11/81	
021075	02/82	
021499	03/82	sold as a select fire model
021941	04/82	
022186	06/82	
022482	07/82	
024095	12/82	
024740	03/83	
025939	07/83	
028260	11/83	
028342	12/83	
029284	02/84	
029390	03/84	
030036	04/84	
030061	05/84	sold as a select fire model
030310	05/84	sold as a receiver
031359	01/85	sold as a receiver
031892	11/84	
032315	11/84	sold as a receiver
032672	01/85	
032951	12/84	sold as a receiver
033283	02/85	

LEE EMERSON

033847	03/85	
034299	05/85	
034651	06/85	
035037	09/85	sold as a receiver
036600	12/85	sold as a barreled receiver
036945	12/85	
037343	11/86	
037405	01/86	sold as a barreled receiver
037830	02/86	sold as a receiver
038076	05/86	
038607	04/86	sold as a select fire model
039524	10/86	
039619	12/86	
040216	01/87	
040555	03/87	
041005	03/87	sold as a receiver
041509	06/87	
043208	10/87	
045083	05/88	
045336	09/88	sold as a receiver
045377	05/88	sold as a receiver
045515	07/88	
045911	06/88	
046069	09/88	sold as a Super Match M1A with Shaw Combat stock
046254	10/88	
047122	12/88	
047317	01/89	
047824	03/89	
048204	03/89	

M14 RIFLE HISTORY AND DEVELOPMENT

050000	12/89	
050073	07/89	
050438	07/89	
050885	09/89	
051166	09/89	
051519	10/89	sold as a receiver
051753	10/89	
052122	11/89	
052724	12/89	
053096	12/89	
053554	01/90	
053815	01/90	
054507	03/90	
054999	02/90	
055258	03/90	
055298	04/90	
055491	05/90	
057106	05/90	
058009	06/90	
059194	08/90	
059761	09/90	
060736	10/90	sold as a receiver
060887	11/90	
060890	10/90	
061026	11/90	
061320	10/90	
061388	11/90	
062340	01/91	
062380	01/91	
062672	09/91	

LEE EMERSON

062680	08/91	
0630XX	03/91	
0635XX	03/91	
0640XX	05/91	
064872	11/91	sold as a rear lugged Super Match rifle
064880	12/91	sold as a rear lugged receiver
065323	10/91	
066290	10/91	sold as a folding stock M1A-A1 model
066425	10/91	sold as a receiver
067852	12/91	
066871	10/91	sold as a receiver
068177	01/92	
068281	03/92	
068540	03/92	
068978	04/92	sold as a receiver
069101	04/92	sold as a receiver
069457	05/92	
069860	07/92	
070005	07/92	
070795	10/92	
072074	03/93	
072253	05/93	
072562	04/93	sold as a receiver
072680	05/93	
073468	07/93	
074131	08/93	sold as a receiver
074641	09/93	
075704	11/93	

M14 RIFLE HISTORY AND DEVELOPMENT

075874	12/93	
076322	01/94	
076392	01/94	
077987	02/94	
078191	04/94	
078206	04/94	
078839	03/94	
079085	03/94	
079266	04/94	
079836	04/94	
079844	04/94	
080377	05/94	
081246	06/94	M1A-A1 model AA9110
081435	06/94	
081586	07/94	sold as a rear lugged receiver
082619	07/94	
082817	08/94	
084091	09/20/94	
084383	10/94	
084469	09/94	sold as a receiver
084627	09/94	
0847XX	10/94	
084859	09/94	sold as a receiver
08493X	10/94	sold as a receiver
085735	09/94	
085992	11/94	
087166	02/95	
088149	02/95	
088936	03/95	
090354	03/95	

LEE EMERSON

092371	07/95	
092426	06/95	sold as a M1A-A1 model
093976	12/95	
094058	01/96	
094551	01/96	
095137	02/96	
096025	03/96	
096866	05/96	
097333	05/96	
097345	08/96	
098053	10/96	
098669	10/96	
098991	11/96	
100222	02/97	
101255	03/97	lowest observed receiver with J series pour lot number
101718	04/97	
101945	05/97	
102570	05/97	
103355	06/97	
104850	08/97	
106880	10/97	
107826	11/97	
108873	01/98	
109159	02/98	
109770	03/98	sold as a rear lugged M21
110125	03/98	
110232	03/98	
110583	04/98	
111434	05/98	

M14 RIFLE HISTORY AND DEVELOPMENT

113002	09/98	
113667	11/98	
114084	01/99	
114614	12/98	
115296	02/99	
116733	04/99	
117255	05/99	
117369	06/99	sold as a barreled receiver
118284	06/99	
118401	08/99	
118861	07/99	
120709	09/99	
121590	11/99	
121948	11/99	
122961	12/99	
123035	12/99	
124046	01/00	sold as a barreled receiver
124132	01/00	
124998	02/00	
125899	03/00	
126142	03/00	
126461	04/00	
127335	04/00	
128222	06/00	
129095	07/00	
129313	07/00	
130055	10/00	
130724	12/00	sold as a rear lugged Super Match rifle
130974	12/00	
131290	12/00	

LEE EMERSON

131585	11/00	
131957	02/01	
132810	03/01	
133090	04/01	
133405	05/01	
133605	03/01	
133665	03/01	
134855	07/01	
135551	08/01	
136425	10/01	
136732	10/01	
137075	11/01	
137546	11/01	sold as a receiver
137777	11/01	
139015	01/02	
139506	01/02	
140898	03/02	
141575	03/02	
142118	04/02	
142243	04/02	
143123	05/02	
143583	05/02	
143978	06/02	
144999	06/02	
145288	07/02	
146246	08/02	
147042	09/02	
148064	11/02	
148380	10/02	
148934	10/02	

M14 RIFLE HISTORY AND DEVELOPMENT

148998	11/02	
149004	11/02	
149106	11/02	
149063	10/02	
149645	12/02	
150156	12/02	sold as a receiver
150506	12/02	sold as a receiver
150555	12/02	sold as a receiver
150686	12/02	
151496	01/03	
151707	01/03	
152377	02/03	
152451	02/03	
152750	04/03	
153789	04/03	
152956	03/03	
155359	04/03	
155865	04/03	
156121	05/03	
156569	07/03	
157036	07/03	
157128	07/03	
157704	06/03	
157735	06/03	
160942	11/03	
161034	12/03	
161068	11/03	
161112	12/03	
161246	12/03	

LEE EMERSON

161920	01/04	
161737	12/03	
161920	01/04	
162053	01/04	
162664	03/04	
162708	02/04	one of the first M1A SOCOM models
162961	03/04	
163386	04/04	
164618	05/04	
164758	05/04	
164935	06/04	
165375	07/04	
165774	07/04	exported to the Netherlands
165787	07/04	
166719	08/04	
166784	08/04	
166912	09/04	
167417	09/04	
169375	12/04	
169858	12/04	
170157	01/05	
170616	02/05	
171127	02/05	
171275	01/05	sold as a receiver
171450	03/05	
172203	03/05	
173180	06/05	
173559	05/05	

M14 RIFLE HISTORY AND DEVELOPMENT

174514	05/05	
175045	06/05	
175450	06/05	
175830	07/05	
176067	08/05	
176167	07/05	
176635	07/05	
177998	09/05	
178046	10/05	
178216	09/05	
178745	11/05	
178800	09/05	
178898	10/05	
179887	11/05	
181429	12/05	
182201	01/06	
182867	01/06	
183075	03/06	
183335	02/06	
185270	04/06	
185394	05/06	
185796	04/06	
186793	05/06	
187500	06/06	
188946	07/06	
189219	07/06	
190814	09/06	
191506	09/06	
191530	10/06	exported to the Netherlands
192257	09/06	

LEE EMERSON

192573	09/06	
192880	10/06	
193999	11/06	
194804	12/06	
195312	12/06	
197242	03/07	
199310	03/07	
199322	04/07	
199983	04/07	
200668	05/07	
200971	05/07	
201344	09/07	
202527	06/07	
203567	07/07	
204907	08/07	
205659	08/07	
207121	10/07	
207703	10/07	
207738	09/07	
208909	11/07	
210737	12/07	
211528	12/07	
212210	01/08	
212326	02/08	
213387	03/08	
213954	03/08	
215294	03/08	
215395	04/08	
215445	05/08	
216351	04/08	

M14 RIFLE HISTORY AND DEVELOPMENT

218144	06/08	
220922	07/08	
22127X	09/08	
224119	11/08	
224473	11/08	
2263XX	01/09	
227131	01/09	
227819	02/09	
229994	03/09	
230112	08/00	
231477	06/09	
233045	06/09	
234948	07/09	
235717	07/09	
237322	08/09	
237632	09/09	
240483	11/09	
241552	11/09	
242864	01/10	
2459XX	02/10	
246XXX	09/01	2001 production
247859	03/10	
249194	04/10	
253341	06/10	
256208	08/10	
257168	09/10	
257435	09/10	
2613XX	11/10	
262611	12/10	
268607	03/11	

LEE EMERSON

269575	04/11	
270146	04/11	
271683	06/11	
27278X	06/11	
274070	07/11	
274397	08/11	
276967	10/11	sold as a receiver
278830	10/11	
282409	03/12	
282981	02/12	
284637	03/12	
289024	05/12	
290028	06/12	
293538	09/12	
2991XX	11/12	
3014XX	01/13	
302999	02/13	
3037XX	02/13	
304342	03/13	
3054XX	04/13	
308707	04/13	
3122XX	06/13	
313221	06/13	
SM0117	09/91	
SM0162	10/91	
IDF026	05/99	
IDF042	04/99	
IDF067	07/99	
WF027X	12/02	

M14 RIFLE HISTORY AND DEVELOPMENT

Table 26: Smith Enterprise, Inc.

Receiver Serial Number	Manufacture	Month and Year	Comments
0012XX	investment cast		
001339	investment cast		
001691	investment cast		
001705	investment cast		
001779	investment cast		
001798	investment cast	09/88 purchase	sold as a receiver
001799	investment cast	09/88 purchase	sold as a receiver
001802	investment cast		sold as a receiver
00185X			built in 1986
001915	billet machined	01/88 purchase	sold as a receiver, rear lugged
001923	billet machined		double lugged
001933	billet machined		sold as a receiver, rear lugged
001940	billet machined		
001984	investment cast		rear lugged
001985	billet machined		
001999	billet machined	08/88 purchase	sold as a receiver
002010	billet machined		
002025	investment cast		sold as a semi-auto M14K
002099	investment cast		made no later than 1988
1002100		06/91 delivered	sold as a receiver
1002102		06/91 delivered	sold as a receiver
002111	investment cast		double lugged, marked M-14 NM
1002113	investment cast		
002115	investment cast	1990 production	sold as a semi-auto M14K
002122	investment cast		sold as a receiver, rear lugged
1002122	investment cast		sold as a receiver, rear lugged
1002128	investment cast		sold as a receiver, rear lugged

LEE EMERSON

002160	investment cast		double lugged
002197	investment cast		
002198	investment cast		
002243	billet machined		double lugged, marked M25
002281	billet machined		rear lugged
002289	billet machined		rear lugged
002292	billet machined		rear lugged
002300	billet machined	12/92 delivered	sold as a receiver
002326	billet machined		sold as a rear lugged receiver
002371	billet machined		
002380	billet machined	12/92 delivered	sold as a receiver
002381	billet machined	12/92 delivered	sold as a receiver
002439	billet machined		double lugged receiver
002504	billet machined	1991 production	double lugged receiver
002513	billet machined		sold as a rear lugged receiver
002556	billet machined		
002584	billet machined		
002585	billet machined		sold as a receiver
00258X	billet machined	03/94 manufacture	rear lugged
002603	billet machined		rear lugged, highest observed pre-'94 ban serial number
5019	investment cast	07/96 delivered	sold as a receiver
5027	investment cast	07/96 delivered	sold as a receiver
5031	investment cast	09/96 delivered	sold as a receiver
5032	investment cast	09/96 delivered	sold as a receiver
5049	investment cast	07/97 delivered	sold as a receiver
5050	investment cast	07/97 delivered	sold as a receiver
5063	investment cast	10/98 delivered	sold as a receiver
5065	investment cast	10/98 delivered	sold as a receiver
5071	investment cast	05/99 delivered	sold as a receiver

M14 RIFLE HISTORY AND DEVELOPMENT

5074	investment cast	07/99 delivered	sold as a receiver
5075	investment cast	07/99 delivered	sold as a receiver
1200720			NFA post-ban dealer sample select fire
0001 through 0010	billet machined	09/10 manufacture	
0011 through 0030	billet machined	06/11 manufacture	
C001 through C0003	billet machined	07/11 manufacture	

Table 27: Federal Ordnance, Inc.

Receiver Serial Number	Month and Year	Comments
22XX	02/26/87 per factory tag	USGI parts
232X		USGI parts
3058		USGI parts imported from Israel
344X	05/19/88 per factory tag	USGI parts
394X		USGI parts imported from Israel
46XX		USGI parts including H&R barrel
4894	04/89 FFL delivery to original owner	USGI parts including Winchester barrel
677X	11/17/89 per factory tag	USGI parts
7010	12/89 original owner purchase	USGI parts
7089	06/89 original owner purchase	USGI parts
8042		USGI parts
824X	02/01/90 on receiver	USGI parts
8877		USGI parts
8896	04/16/90 per factory tag	USGI parts

LEE EMERSON

9337		Chinese parts
20440		Chinese parts
205XX		Chinese parts
21136		Chinese parts
21200		Chinese parts
21464	02/26/91 per factory tag	Chinese parts
227XX		Chinese parts
23111	05/91 per factory tag	Chinese parts
50127	08/26/91 per factory tag	Chinese parts
502XX	09/13/91 per factory tag	Chinese parts
50396		Chinese parts
60308		highest observed serial number

Table 28: Enterprise Arms, Inc.

Receiver Serial Number	Month and Year	Comments
E00154	04/96 delivered to FFL	sold as a receiver
E00328	01/99 delivered to FFL	sold as a receiver
E00390	12/96 delivered to FFL	sold as a receiver
E00422	04/97 delivered to FFL	sold as a receiver

M14 RIFLE HISTORY AND DEVELOPMENT

Table 29: Armscorp

Receiver Serial Number	Month and Year	Comments
S003022 - S003036		stainless steel receiver
A003051	10/87 delivered to FFL	sold as a receiver
A003095	06/88 delivered to FFL	sold as a receiver
A003145	<i>The Outdoor News</i> 02/88	service grade rifle
A003283	02/88 delivered to FFL	sold as a receiver
A003290	11/88 purchase	sold as a receiver
A003309	02/88 delivered to FFL	sold as a receiver
A003337	02/88 delivered to FFL	sold as a receiver
A003912	04/89 purchase	
A004280	06/89 delivered to FFL	sold as a receiver
A005039	08/90 delivered to FFL	sold as a receiver
A00607X	10/90 barrel installation	
A006502	05/91 purchase	sold as a receiver
A0070XX	03/92 purchase	
0071XX	01/91 purchase	
007250	08/91 purchase	sold as a receiver
10370	05/94 delivered to FFL	sold as a receiver
10451	04/93 manufacture	
10646	09/94 delivered to FFL	sold as a receiver
115XX	07/94 manufacture	sold as a complete rifle
11999	08/94 purchase	sold as a receiver
151XX	05/99 purchase	
15759	07/99 delivered to FFL	sold as a receiver
15906	01/00 manufacture	
16602	06/02 purchase	sold as a receiver
16621	06/02 purchase	sold as a receiver
16633	07/02 purchase	sold as a receiver
1664X	07/02 purchase	sold as a receiver
17011	07/03 manufacture	

LEE EMERSON

17013	07/03 manufacture	
1708X	11/03 purchase	
17096	12/03 purchase	sold as a barreled receiver
1728X	07/06 purchase	sold as a rear lugged XM25 receiver
17396	05/06 purchase	sold as a barreled receiver
17498	10/06 purchase	sold as a receiver
17615	01/08 manufacture	
17674	02/08 manufacture	sold as a receiver
17675	02/08 manufacture	sold as a receiver
17729		sold as a receiver, marked Highlander Security Spofford, NH
7	09/92 shipped to FFL	sold as a receiver marked 5.56 MM M14 NM
MALONEY	10/93	personal rifle of Charles W. Maloney
WTA0001 through WTA0013	07/06 shipped to West Texas Armory	shipped as receivers

Table 30: Fulton Armory

Receiver Serial Number	Month and Year	Comments
FA0101 to FA0110	02/03 to 04/03 manufactured	
FA0240	11/03 purchase	
FA0550	08/05	
FA0701	12/06 delivered	
F02573	12/12 delivered	sold as a rear lugged receiver

M14 RIFLE HISTORY AND DEVELOPMENT

F03102	12/13 delivered	sold as a receiver
--------	-----------------	--------------------

Table 31: LRB Arms

Receiver Serial Number	Month and Year	Comments
X00101	12/02	sold as a receiver
X00104	12/02	sold as a receiver
X00109	01/03	replacement receiver for seized MKS M14-A-1 receiver
00104	04/03 purchase	sold as a receiver
01001	10/03 purchase	sold as a receiver
01011	09/03 purchase	sold as a receiver
01012	09/03 purchase	sold as a receiver
01018	09/03 purchase	sold as a barreled receiver
0102X	11/04 purchase	sold as a barreled receiver
01038	09/03 purchase	sold as a receiver
01210	10/03 purchase	sold as a receiver
01211	09/03 purchase	sold as a receiver
01217	10/03 purchase	
01227		highest observed dot matrix serial number
01237	01/05 built into rifle at LRB	lowest observed die stamp serial number
01263	09/06 built into rifle at LRB	
01275	01/04 shipped to FFL	sold as a barreled receiver
01278	09/06 built into rifle at LRB	
01281	08/06 purchase	sold as a complete rifle
0128X	01/06 built into rifle at LRB	
0129X	01/05 shipped to FFL	
0129X	08/06 built into rifle at LRB	
01301	09/06 built into rifle at LRB	
01304	10/04 purchase	sold as a barreled receiver

LEE EMERSON

0131X	09/04 purchase	sold as a receiver
01318	05/04 purchase	sold as a rear lugged receiver
0132X	09/04 purchase	sold as a receiver
01339	05/04 shipped to FFL	sold as a receiver
0134X	02/06 built into rifle at LRB	
01364	07/04 purchase	sold as a receiver
01367	09/06 built into rifle at LRB	
0138X	08/06 shipped to FFL	sold as a complete rifle
01385	09/04 shipped to FFL	sold as a receiver
01386	09/04 shipped to FFL	sold as a receiver
01408	12/04 shipped to FFL	sold as a receiver
01437	01/05 purchase	sold as a receiver
01444	01/05 purchase	sold as a receiver
01445	01/05 purchase	sold as a receiver
01451	02/05 delivered	sold as a barreled receiver
01494	03/05 shipped to FFL	
01498	02/05 delivered	sold as a barreled receiver
0151X	03/05 purchase	sold as a barreled receiver
01531	05/05 shipped to FFL	sold as a barreled receiver
01533	03/05 shipped to FFL	sold as a receiver
01534	05/05 delivered	sold as a barreled action
01537	04/05 shipped to FFL	sold as a barreled receiver
01545	04/05 built into rifle at LRB	
01548	05/05 shipped to FFL	sold as a receiver
01550	05/05 purchase	sold as a receiver
01555	03/06 purchase	sold as a complete rifle
01584	01/06 purchase	sold as a complete rifle
0159X	09/05 purchase	
01606	09/05 built into rifle at LRB	
01612	07/05 delivered	sold as a receiver

M14 RIFLE HISTORY AND DEVELOPMENT

01629	09/05 purchase	sold as a barreled receiver
0164X	12/05 built into rifle at LRB	
01645	05/05 purchase	sold as a rear lugged receiver
01646	03/06 built into rifle at LRB	
01652	11/05 purchase	sold as a rear lugged receiver
01659	09/06 built into rifle at LRB	
0166X	01/06 built into rifle at LRB	
01665	09/06 built into rifle at LRB	
01668	11/05 built into rifle at LRB	
01705	06/06 built into rifle at LRB	
01707	06/06 built into rifle at LRB	
01711	06/06 purchase	sold as a receiver
01724	08/06 built into rifle at LRB	
01732	10/06 built at LRB	sold as a barreled receiver
01738	11/06 delivered	sold as a receiver
01739	11/06 shipped to FFL	sold as a receiver
01750	10/06 delivered	sold as a barreled receiver
01783	11/06 built into rifle at LRB	
01808	12/06 shipped to FFL	sold as a receiver
01824	12/06 built into rifle at LRB	
01827	12/06 built into rifle at LRB	
01833	01/07 built into rifle	
01844	01/07 built into rifle at LRB	
01846	04/07 built at LRB	sold as a barreled receiver
01854	03/07 shipped to FFL	sold as a rear lugged receiver
01866	02/07	sold as a rear lugged receiver
01873	05/07 built into rifle at LRB	
01885	05/07 shipped to FFL	sold as a receiver

LEE EMERSON

01886	05/07 shipped to FFL	sold as a receiver
02111	08/07 shipped to FFL	sold as a receiver
02112	08/07 shipped to FFL	sold as a receiver
02129	08/07 built into rifle at LRB	
02138	09/07 shipped to FFL	
02149	09/07 shipped to FFL	sold as a receiver
02168	09/07 built into rifle at LRB	
02169	09/07 shipped to FFL	sold as a barreled receiver
02200	11/07 purchase	sold as a barreled receiver
02201	09/07 purchase	sold as a barreled receiver
02207	10/07 purchase	sold as a receiver
02220	11/07 shipped to FFL	sold as a barreled receiver
02264	11/07	sold as a rear lugged receiver
02295	11/07	sold as a receiver
02313	11/07 shipped to FFL	sold as a barreled receiver
02325	01/08 built into rifle at LRB	
02345	12/07 shipped to FFL	sold as a barreled receiver
02363	03/08 built into rifle at LRB	
02408	05/08 built into rifle at LRB	
02454	10/08 built into rifle at LRB	
02539	01/09 shipped to FFL	sold as a barreled receiver
02618	11/09 shipped to FFL	sold as a receiver
02676	09/09 shipped to FFL	sold as a barreled receiver
02754	07/10 built into rifle at LRB	
02836	06/10 shipped to FFL	sold as a receiver
02876	08/10 shipped to FFL	sold as a barreled receiver
02881	08/10 shipped to FFL	sold as a barreled receiver
02882	08/10 shipped to FFL	sold as a receiver
02890	10/10 shipped to FFL	sold as a rear lugged receiver

M14 RIFLE HISTORY AND DEVELOPMENT

03033	04/11 purchase	sold as a receiver
03076	09/11 built into rifle	
10012	12/06 purchase	
10045	02/07 built into rifle at LRB	
10046	02/07 built into rifle at LRB	
10049	04/07 built into rifle at LRB	
10056	03/07 built into rifle at LRB	
10065	06/07 shipped to FFL	sold as a receiver
10066	06/07 shipped to FFL	sold as a receiver
10085	06/07 built into rifle at LRB	
10149	04/07 manufactured	
10153	06/07 shipped to FFL	sold as a barreled receiver
10194	08/07 rifle built at LRB	
10306	08/08 delivered	sold as a double lugged receiver
10308	08/08 delivered	sold as a double lugged receiver
10329	08/08 built into rifle at LRB	
10356	10/08 shipped to FFL	sold as a barreled receiver
10390	11/08 shipped to FFL	
10411	12/08 built into rifle at LRB	
10415	11/08 shipped to FFL	
10417	11/08 shipped to FFL	
10418	11/08 shipped to FFL	sold as a receiver
10505	03/10 shipped to FFL	sold as a receiver
10537	12/09 shipped to FFL	sold as a receiver
10538	12/09 shipped to FFL	sold as a receiver
11356	09/13 shipped to FFL	sold as a receiver

Table 32: 7.62mm Firearms

Receiver Serial Number	Month and Year	Comments
52010	05/10 manufacture	receiver
52020	05/10 manufacture	receiver
52041	06/10 manufacture	receiver
52042	06/10 manufacture	receiver

Springfield Armory, Inc. began using stock numbers by 1984. Stock numbers were indicated on the end of the factory shipping box. The designator M1A-A1 was the model number for 18 " barreled M1A rifles from 1981 until 1997. If the factory installed a California compliant muzzle brake on a model that was available with a flash suppressor, the letters CA were added at the end of the stock number, e.g., MA9102CA. The change to a muzzle brake became mandatory for M14 type rifles sold in California after December 31, 1999. M1A rifles were assembled with molybdenum-chromium alloy steel barrels unless otherwise noted. The following tables list M1A rifle and related item stock numbers used by Springfield Armory, Inc. over the years. **Note that most of the rifle models, parts and accessories are currently not available and have not been available since 1990.** This information is presented for historical purposes.

Table 33: Springfield Armory, Inc. M1A Rifle Stock Numbers

Stock Number	Model M1A Description	Year(s) Available
Receiver	stripped	1971 through 1983
Standard	usually assembled with a USGI chromium plated barrel, USGI or commercial stock	1971 through 1983
Match Grade	standard contour National Match barrel, bedded wood stock	1971 through 1976
National Match	standard contour National Match barrel, bedded wood stock	1978 through 1983
Super Match	heavyweight barrel, bedded wood stock	1975 through 1983
M1A-A1 Assault	folding stock, 18 " barrel	1981 through 1983
M1A Combat	Shaw standard walnut stock with metal butt plate or Shaw E2 walnut stock with rubber butt pad	1982
M1AE2 Standard	M14E2 stock, standard contour barrel	1973 through 1974, 1978 through 1983
M1AE2 National Match	M14E2 bedded stock, National Match barrel	1978 through 1983
M1AE2 Super Match	M14E2 bedded stock, heavyweight barrel	1978 through 1983
Even Hundred Edition		1989
Even Thousand Edition		1991
Sport Master		1991
Vietnam War Commemorative		1998

LEE EMERSON

MA92NRAC	Camp Perry Limited Edition	2007 through 2008
AA9101	18 " barrel, USGI wood stock	1984 through 1986, 1996
AA9102	18 " barrel, commercial walnut stock	1986 through 1988, 1990 through 1999, 2003
AA9103	18 " barrel, oversized walnut stock	1987 through 1990
AA9104	18 " barrel, oversized brown or camouflage fiberglass stock	1987 through 1989
AA9104	18 " barrel, black or mossy oak fiberglass stock, flash suppressor	2002 through 2003
AA9105	18 " barrel, fancy walnut stock	1987 through 1988
AA9106	18 " barrel, black synthetic stock, flash suppressor	November 1994 through 1996, 2003
AA9108	18 " barrel, birch M14E2 stock	1987 through 1988
AA9109	18 " barrel, walnut M14E2 stock	1987 through 1988
AA9110	18 " barrel, folding stock	1984 through 1989, 1993 through 1994
AA9115	18 " barrel, Shaw standard walnut stock	1987 through 1990
AA9116	18 " barrel, Shaw E2 walnut stock	1987 through 1989
AA9116	18 " barrel, wood laminate stock	1996 through 1998
AA9117	18 " barrel, camouflage synthetic stock	1987 through 1992, 1996, 2004 through 2010
AA9122	Scout Squad, 18 " barrel, commercial walnut stock, muzzle brake	1996 through 2013

M14 RIFLE HISTORY AND DEVELOPMENT

AA9124	Scout Squad, 18 " barrel, mossy oak synthetic stock, muzzle brake	2002 through 2013
AA9126	Scout Squad, 18 " barrel, black synthetic stock, muzzle brake	1996 through 2013
AA9127	Scout Squad, 18 " barrel, black wood laminate stock	1996
AA9129	Scout Squad, 18 " barrel, green polymer stock, muzzle brake	2010 through 2012
AA9625	SOCOM 16 with green polymer stock	2009 through 2013
AA9626	SOCOM 16 with black synthetic stock	2004 through 2013
AA9627	SOCOM II with second generation black synthetic stock and standard cluster rail	2005 through 2013
AA9628	SOCOM 16 Urban (2005 and 2006 production) and SOCOM II Urban Camo (2007 and later production) with synthetic stock and standard cluster rail	2005 through 2011
AA9629	SOCOM II with black synthetic stock and extended cluster rail	2007 through 2013
MA9101	collector edition with standard contour barrel and USGI wood stock	1984 through 1986, 2006
MA9102	standard with commercial walnut stock	1984 through 2013
MA9102CA	standard with commercial walnut stock and muzzle brake	2000 through 2013
MA9103	standard with oversized match stock	1984 through 1990
MA9103	collector edition with USGI chromium plated barrel and USGI birch stock	2002 through 2003

LEE EMERSON

MA9104	standard with oversized brown or camouflage fiberglass stock	1984 through 1989
MA9104	standard with mossy oak synthetic stock	2003 through 2013
MA9104CA	standard with mossy oak synthetic stock and muzzle brake	2003 through 2013
MA9105	standard with fancy walnut stock	1984 through 1988
MA9106	standard with black synthetic stock	1993 through 2013
MA9106CA	standard with black synthetic stock and muzzle brake	2000 through 2013
MA9108	standard with birch M14E2 stock	1984 through 1988
MA9109	standard with walnut M14E2 stock	1984 through 1988
MA9109	standard with green polymer stock	2009 through 2013
MA9109CA	standard with green polymer stock	2009 through 2013
MA9110	standard with folding stock	1984 through 1990
MA9115	standard with Shaw standard walnut stock	1984 through 1990
MA9115	standard with brown wood laminate stock	1996
MA9116	standard with Shaw E2 walnut stock	1984 through 1989
MA9116	standard with black wood laminate stock	1996 through 2000
MA9117	standard with woodland camouflage fiberglass stock	1984 through 1992, 1996
MA9118	standard with commercial walnut stock - .243 Winchester	1984 through 1986
MA9118	basic with bipod, muzzle stabilizer and black fiberglass stock	1996

M14 RIFLE HISTORY AND DEVELOPMENT

MA9119	standard with brown USGI fiberglass stock	1985 through 1988, 1992
MA9120	M14 Vietnam Commemorative U.S. Army	1987
MA9121	M14 Vietnam Commemorative U. S. Marine Corps	1987
MA9201	loaded standard with USGI stock	1996 through 1997
MA9202	loaded standard with commercial walnut stock	1996 through 1998
MA9203	Gold Series, Douglas heavyweight barrel with oversized walnut stock	1986
MA9204	Gold Series, Douglas heavyweight barrel with aramid stock	1986
MA9206	loaded standard with black fiberglass stock	1996 through 1997
MA9215	standard with Shaw standard walnut stock and Harris bipod	1984 through 1986
MA9216	standard with Shaw E2 walnut stock and Harris bipod	1984 through 1986
MA9221	loaded standard with collector USGI stock	1999 through 2000
MA9222	loaded standard with commercial walnut stock	1999 through 2013
MA9222CA	loaded standard with commercial walnut stock and muzzle brake	2000 through 2013
MA9225	loaded standard with wood laminate stock	
MA9226	loaded standard with black synthetic stock	1999 through 2013

LEE EMERSON

MA9226CA	loaded standard with black synthetic stock and muzzle brake	2000 through 2013
MA9229	loaded standard with green polymer stock	2009 through 2013
MA9229CA	loaded standard with green polymer stock	2009 through 2013
MA9253	Gold Series, Hart stainless steel heavyweight barrel with oversized walnut stock	1986
MA9254	Gold Series, Hart stainless steel heavyweight barrel with aramid stock	1986
MA9402	standard with National Match barrel, National Match sights, and commercial walnut stock	1996
MA9771	IDF model with sniper scope	1999
MA9781	IDF model with night vision scope	1999
MA9801	loaded standard with walnut USGI stock and stainless steel National Match medium weight barrel	1996 through 1997
MA9802	select fire	1984 through 1987
MA9802	loaded standard with commercial walnut stock and stainless steel National Match medium weight barrel	1996
MA9806	loaded standard with black fiberglass stock and stainless steel National Match medium weight barrel	1996 through 1997
MA9821	loaded standard with collector USGI stock and stainless steel National Match medium weight barrel	1999 through 2000

M14 RIFLE HISTORY AND DEVELOPMENT

MA9822	loaded standard with commercial walnut stock and stainless steel National Match medium weight barrel	1999 through 2013
MA9822CA	loaded standard with commercial walnut stock, stainless steel National Match medium weight barrel, and muzzle brake	2000 through 2012
MA9825	loaded standard with laminate wood stock and stainless steel National Match medium weight barrel	1999
MA9826	loaded standard with black synthetic stock and stainless steel National Match medium weight barrel	1999 through 2013
MA9826CA	loaded standard with black synthetic stock, stainless steel National Match medium weight barrel and muzzle brake	2000 through 2013
MA9827 and MA9827CA	loaded standard with black synthetic stock, stainless steel National Match medium weight barrel and Vltor cluster rail (muzzle brake for MA9827CA)	2006 through 2012
MA9829	loaded standard with green polymer stock and stainless steel National Match medium weight barrel	2009 through 2011
MA9851	collector edition with stainless steel barrel and USGI wood stock	1998 through 2000
MA9900	receiver	1984 through 2010
MA9903	rear lugged receiver	1989 through 2004
NA9102	National Match with commercial walnut stock (standard contour barrel before 1992, medium weight barrel from 1992 onward)	1984 through 2013

LEE EMERSON

NA9102CA	National Match with commercial walnut stock and muzzle brake	2000 through 2013
NA9103	National Match with oversized wood stock	1984 through 1990
NA9104	National Match with aramid or oversized fiberglass stock	1984 through 1990
NA9105	National Match with fancy walnut stock	1984 through 1988
NA9108	National Match with birch M14E2 stock	1984 through 1988
NA9109	National Match with walnut M14E2 stock	1984 through 1988
NA9110	National Match with folding stock	1984 through 1989
NA9115	National Match with Shaw standard walnut stock	1984 through 1990
NA9116	National Match with Shaw E2 walnut stock	1984 through 1989
NA9118	National Match with commercial walnut stock - .243 Winchester	1984 through 1986
NA9119	National Match with commercial walnut stock and 18 " barrel	1985 through 1990
NA9215	National Match with Shaw standard walnut stock and Harris bipod	1984 through 1986
NA9216	National Match with Shaw E2 walnut stock and Harris bipod	1984 through 1986
NA9802	National Match with stainless steel National Match medium weight barrel	1999 through 2013
NA9802CA	National Match with stainless steel National Match medium weight barrel and muzzle brake	2000 through 2013

M14 RIFLE HISTORY AND DEVELOPMENT

SA9102	Super Match with commercial walnut stock	1984 through 1986
SA9102	Super Match with oversized commercial walnut stock	1987 through 2013
SA9102CA	Super Match with oversized commercial walnut stock and muzzle brake	2000 through 2013
SA9103	Super Match with oversized commercial walnut stock	1984 through 1986
SA9104	Super Match with aramid or oversized fiberglass stock	1984 through 1990
SA9105	Super Match with fancy walnut stock and hand guard	1984 through 1988
SA9108	Super Match with birch M14E2 stock	1984 through 1988
SA9109	Super Match with walnut M14E2 stock	1984 through 1988
SA9110	Super Match with folding stock	1984 through 1989
SA9115	Super Match with Shaw standard walnut stock and Douglas heavyweight barrel	1984 through 1990
SA9116	Super Match with Shaw E2 walnut stock and Douglas heavyweight barrel	1984 through 1989
SA9118	Super Match with commercial walnut stock - .243 Winchester	1984 through 1990
SA9119	Super Match with commercial walnut stock and 18 " barrel	1985 through 1990
SA9121	M21 with Douglas heavyweight barrel	1990, 1995 through 2013
SA9121CA	M21 with Douglas heavyweight barrel	2000 through 2013

LEE EMERSON

SA9131	M21 with Krieger stainless steel heavyweight barrel	2002 through 2013
SA9131CA	M21 with Krieger stainless steel heavyweight barrel and muzzle brake	2013
SA9215	Super Match with Shaw standard walnut stock, heavyweight barrel and Harris bipod	1984 through 1986
SA9216	Super Match with Shaw E2 walnut stock, heavyweight barrel and Harris bipod	1984 through 1986
SA9502	M25 with Krieger molybdenum-chromium alloy steel heavyweight barrel or Krieger stainless steel heavyweight barrel	2001 through 2009
SA9802 and SA9802CA	Super Match with oversized commercial walnut stock and Douglas stainless steel heavyweight barrel (muzzle brake for SA9802CA)	1999 through 2013 2000 through 2013
SA9804 and SA9804CA	Super Match with black McMillan stock and Douglas stainless steel heavyweight barrel (muzzle brake for SA9804CA)	1999 through 2013 2000 through 2013
SA9805 and SA9805CA	Super Match with camouflage McMillan stock and Douglas stainless steel heavyweight barrel (muzzle brake for SA9805CA)	1999 through 2013 2000 through 2013

Most of the M1A rifle models, parts and accessories listed in the tables above and below have not been available since 1990. Springfield Armory, Inc. will upgrade M1A rifles returned by the customer at additional cost. These services include accurizing and changing barrels, stocks, parts and rail mounts.

Table 34: Springfield Armory, Inc. M1A Related Items Stock Numbers

Stock Number	Item Description	Comments
AA0101	.308 short A1 standard barrel	
AA0313	flash suppressor for M1A-A1 Bush rifle	
AA0510	front sight, 18 " barrel	
AA0722	hand guard, vented fiberglass, brown USGI	
BA0101	.243 standard barrel	
BN0101	.243 National Match barrel	
BP4000	butt plate complete kit	
BS0101	.243 Super Match Douglas barrel	
BS0807	fancy burley walnut stock with hand guard, without hardware	
BS5807	fancy burley walnut stock with hand guard, with hardware	
CA0701	rear sling swivel	
CA0702	butt plate machine screw	
CC5010	combination tool, with cleaning rod sections and patch tip	
CC5011	oiler	
CO0405	extractor	
CO0406	extractor spring	
CO0407	extractor plunger	

LEE EMERSON

CO0501	elevation knob assembly	
CO0502	windage knob assembly	
CO0504	windage knob washer	
CO0505	rear sight base	
CO0507	rear sight aperture	
CO0508	windage knob wing nut	
CO0509	windage knob spring	
CO0514	rear sight cover	
CO0601	trigger and sear assembly	
CO0602	hammer	
CO0603	hammer spring	
CO0604	hammer spring plunger	
CO0605	hammer spring housing	
CO0606	hammer pin	
CO0607	trigger pin	
CO0608	safety	
CO0701	hand guard clip	
CO5001	rear sight cover, plastic	
CO5005	sling, nylon, adjustable, padded camouflage	
CO5006	sling, nylon, adjustable, padded black	

M14 RIFLE HISTORY AND DEVELOPMENT

CO5007	sling, nylon	
CO5008	sling, canvas	
CO5009	sling, leather, U. S. military specification, 1.25 " wide	
CO5010	winter trigger	
CO5011	winter safety	
CO5012	trigger shoe with wrench	
CO5013	winter trigger safety kit	
CO5014	leather sling keeper, 1.25 " wide	
CR0101	USGI chromium plated barrel	
EB0812	USGI M14E2 birch stock without hardware	
EB5812	USGI M14E2 birch stock with hardware	
EW0813	USGI M14E2 walnut stock without hardware	
EW5813	USGI M14E2 walnut stock with hardware	
FA5811	folding stock with hardware	
FB0718	fiberglass butt stock plate screw	
FB0720	fiberglass butt stock nut	
FB0721	fiberglass butt plate retainer	
FB0805	fiberglass stock without hardware	

LEE EMERSON

FB5805	fiberglass stock with hardware	
FC0723	hand guard, vented black fiberglass with crinkle finish	
FC0724	hand guard, solid black fiberglass with crinkle finish	
FC0801	reconditioned USGI camouflage fiberglass stock and hand guard set without hardware	
FC0802	reconditioned USGI brown fiberglass stock and hand guard set without hardware	
FC5801	reconditioned USGI camouflage fiberglass stock and hand guard set with hardware	
FC5802	reconditioned USGI brown fiberglass stock and hand guard set with hardware	
FC0803	black fiberglass stock and hand guard set without hardware	
FC5803	black fiberglass stock and hand guard set with hardware	
FS0712	front sling swivel	
FS0713	front sling swivel bracket rivets	
FS0714	front sling swivel washer	
FU0715	stock ferrule	
	scope, A.R.T., choice of 4 X or 6 X, matte finish, with lens covers	1978 - 1980, made by Burris, presumably the "A.R.T. III" scope

M14 RIFLE HISTORY AND DEVELOPMENT

GE5001	scope, A.R.T. IV, 3 to 9 X, matte finish, with lens covers	1978 - 1994, made by Burris
GE5002	scope covers, A.R.T. IV	
GE5005	aiming device / coach's sight	
GE5017	bipod, Parker-Hale, adjustable	
GE5018	scope, A.R.T. IV, 3 to 9 X, blued finish, with lens covers	1987
GE5045	second generation M1A t-shirt	
GE5055	tie clasp, with miniature M14 in rhodium and polished gold	1988 - 1990
GE5056	hat pin or jacket pin, with miniature M14 in rhodium and polished gold	1988 - 1990
GE5065	tie clasp, with miniature M14 in rhodium and polished gold	1987
GE5066	hat pin or jacket pin, with miniature M14 in rhodium and polished gold	1987
GE5068	scope rings, 30 mm	
GE5084	USGI rifle grease, 1 pound can	
GE5099	presentation case, walnut, glass lid, antique brass hardware	1988 - 1990
GE5101	adjustable nylon cheek piece	
GI0801	USGI stock without hardware	
GI5801	USGI stock with hardware	
HC0806	heavy competition stock without hardware	

LEE EMERSON

HC5806	heavy competition stock with hardware	
KN5003	M6 bayonet and scabbard	
KS0809	oversized competition fiberglass stock without hardware, brown or camouflage	
KS5809	oversized competition fiberglass stock with hardware, brown or camouflage	
MA0101	.308 standard barrel, commercial	
MA0102	7mm-08 standard barrel	
MA0201	cartridge clip guide	
MA0202	cartridge clip guide pin	
MA0203	bolt lock	
MA0204	bolt lock pin	
MA0205	bolt lock spring	
MA0206	connector lock	
MA0207	connector lock pin	
MA0301	operating rod guide	
MA0302	operating rod guide pin	
MA0303	front band	
MA0304	gas cylinder	
MA0306	spindle valve	
MA0307	spindle valve pin	

M14 RIFLE HISTORY AND DEVELOPMENT

MA0308	spindle valve spring	
MA0309	gas piston	
MA0310	gas cylinder lock	
MA0311	gas cylinder plug	
MA0312	flash suppressor nut	
MA0313	flash suppressor	
MA0315	operating rod	
MA0316	operating rod spring	
MA0317	operating rod spring guide	
MA0401	bolt	
MA0402	bolt roller	
MA0403	bolt roller clip	
MA0404	firing pin	
MA0405	ejector spring	
MA0406	firing pin, chromium plated	
MA0408	ejector	
MA0510	front sight, standard	
MA0512	front sight screw	
MA0513	flash suppressor setscrew	
MA0601	trigger housing	

LEE EMERSON

MA0602	trigger guard	
MA0603	safety spring	
MA0604	magazine latch	
MA0605	magazine latch spring	
MA0606	magazine latch pin	
MA0722	hand guard, solid fiberglass	
MA0723	hand guard, brown	
MA0725	hand guard, black	
MA4GENAM	scope mount, fourth generation, alloy aluminum	first available in 2010
MA5001	scope mount, thumbscrew	1978 - 1990, intended for the A.R.T. scopes, presumably the "Second Generation" scope mount
MA5002	muzzle cover, plastic	
MA5003	bayonet and scabbard	same as KN5003
MA5004	match sight kit	
MA5005	bipod, height adjustable	
MA5006	magazine, 10 round	
MA5007	field manual, FM 23-8	
MA5008	technical manual, TM 9-1005-223-35	
MA5009	cleaning kit	

M14 RIFLE HISTORY AND DEVELOPMENT

MA5010	scope mount, first generation, without rings	1975 - 1995
MA5011	scope rings, 1 "	
MA5012	muzzle stabilizer	
MA5013	extractor, ruptured shell, .308 caliber	
MA5014	pliers, flash suppressor nut	
MA5015	bipod, M2	
MA5016	bipod, Harris	
MA5017	magazine, 20 round	
MA5018	magazine, 5 round	
MA5019	magazine, 5 round sporter	fits flush with stock
MA5020	magazine pouch, double	
MA5021	magazine pouch, single	
MA5022	cartridge clip	
MA5023	cartridge clip guide / magazine charging guide	1984 - 1990
MA5023	magazine, 20 round, export / law enforcement	post-1994, duplicate stock number
MA5024	technical manual, TM 9-1005-223-12P	
MA5025	technical manual, TM 9-1005-223-12	
MA5026	technical manual, USAMTU accurizing procedures	

LEE EMERSON

MA5027	marksmanship manual, ROTCM-14530	
MA5028	USGI M14E2 sling, new	
MA5028	scope mount, fourth generation, steel	first available in 2010, duplicate stock number
MA5029	muzzle and rear sight cover set	
MA5029	blank firing attachment	duplicate stock number
MA5038	scope mount, third generation	1986 - 2009
MA5040	M76 grenade launcher	1985
MA5047	scope mount, A. R. M. S. # 18	1988 - 1990
MA5049	muzzle brake	
MA5050	muzzle brake with installation kit, California legal	
MA5051	magazine, 15 round	
MA5056	scope mount, M1A Scout Squad barrel	
MA5059	magazine pouch, M1956	
MA5060	gas cylinder lock wrench	
MA5065	gadget	stock liner disassembly tool and multipurpose screwdriver
MA5066	flash suppressor alignment tool	
MA5068	extractor, ruptured shell	
MA6006	complete M1A firing mechanism	

M14 RIFLE HISTORY AND DEVELOPMENT

MA6007	butt plate assembly	
MI5051	grenade launcher sight and jig	
MS5010	front sight, NM 0.072 "	1988
NA0101	.308 National Match barrel	standard contour before 1996, medium weight since 1996
NA0102	7mm-08 National Match barrel	
NA0103	.308 National Match medium weight stainless steel barrel	1999
NA0304	National Match gas cylinder	
NA0317	National Match operating rod spring guide	
NM0101	National Match medium weight barrel	1994
NM0510	front sight, NM 0.072 "	1987
NX0802	commercial walnut stock without hardware	
NX0808	Super Match oversized walnut stock without hardware	
NX5802	commercial walnut stock with hardware	
NX5803	M21 adjustable walnut sniper stock with hardware	
NX5804	commercial walnut stock with longer pull	
NX5805	National Match military specification walnut stock	

LEE EMERSON

NX5806	sportsman walnut stock with longer pull and rubber recoil pad	
NX5808	Super Match oversized walnut stock with hardware	
PA1001	poster, exploded view, 25 " x 38 " , black and white	
RK1000	repair kit, general	
RK1004	repair kit, bolt	
RK1006	repair kit, firing mechanism	
S50810	Shaw standard stock without hardware	1984 - 1990
S55810	Shaw standard stock with hardware	1982 - 1990
S55820	Shaw standard stock with hardware and Harris bipod	1982 - 1990
S60810	Shaw E2 walnut stock without hardware	1984 - 1989
S65810	Shaw E2 walnut stock with hardware	1982 - 1989
S65820	Shaw E2 walnut stock with hardware and Harris bipod	1982 - 1986
SA0101	.308 Douglas heavyweight barrel	first available in 1978
SA0102	7mm-08 Douglas heavyweight barrel	
SA0201	.308 Krieger heavyweight barrel	
SA0301	.308 Krieger heavyweight stainless steel barrel	
SK0502	National Match windage knob	

M14 RIFLE HISTORY AND DEVELOPMENT

SK0505	National Match rear sight base, standard threads	
SK0507	National Match hooded aperture	
SK0509	National Match ball bearing	
SL0716	stock liner	
SL0717	stock liner screw	
SM0101	.308 short A1 Super Match barrel	
SM6006	M25 / Dale Rader adjustable trigger group	
SS0101	.308 Hart heavyweight stainless steel barrel	
WA0723	hand guard, walnut	
WS0711	butt plate wood screw	

Appendix C

All Things Small and Wonderful

Table 35: M14 Type Rifle Barrel Lengths

Rifle Builder	Length, contour, rate of twist, number of grooves and chromium plated?	Comments
Chinese	22 ", standard, 1:12 four groove, yes	Norinco and Poly Technologies, 31.3 ounces
Commercial	22 ", heavy, 1:10, 1:11, or 1:12, four or six groove, no	M14 SSR and Mk 14 Mod 2 (1:10), match grade, Barnett, Douglas, Krieger Barrels (53.4 ounces), Wilson Arms, Shilen, Obermeyer, Hart
Commercial	22 ", medium, 1:10, 1:11, four groove, no	match grade, Barnett, Douglas, Krieger Barrels, Wilson Arms, etc.
Commercial	22 ", medium, 1:12, four groove, no	Krieger Barrels, stainless steel, USMC M14 DMR pattern with slight changes to accommodate commercial receivers
Commercial	22 ", medium, 1:11, four groove, yes	Criterion Barrels (Wolfe Modified)
Commercial	22 ", medium, 1:11, four groove, no	Criterion Barrels (Wolfe Modified), stainless steel, 50.4 ounces
Commercial	22 ", standard, 1:10, four groove, no	Wolfe Modified
Commercial	22 ", standard	rack grade, Krieger Barrels, discontinued as of March 2008
Fulton Armory, LRB Arms	22 ", standard, 1:10 or 1:12, four, no	Wilson Arms, Criterion Barrels (1:12), Krieger (1:10)
Fulton Armory, LRB Arms	22 ", standard, 1:12, four, yes	Criterion Barrels

LEE EMERSON

LRB Arms	22 ", standard, 1:12, four, yes	Wilson Arms (2004 production)
G. A. Precision	22 ", heavy, 1:10, no	M62-R1, Badger Barrels, stainless steel
LRB Arms	22 ", medium, 1:10, six groove, yes	Criterion Barrels
LRB Arms	22 ", medium, 1:11, four groove, yes	Criterion Barrels, DMR contour, 2009 production barrels marked 7790190
Smith Enterprise, Inc.	22 ", medium, 1:10, four groove, no	M21A5, Wilson Arms, chromium-molybdenum alloy steel, M118LR chambered, SEI part number 2025, 2.73 pounds
Smith Enterprise, Inc.	22 ", medium, 1:10, four groove, no	M21A5, Krieger Barrels, stainless steel, M118LR chambered
Smith Enterprise, Inc.	22 ", standard, 1:10, four groove, no	M21A5, chromium-molybdenum alloy steel, M118LR chambered, SEI part number 2028, 33.3 ounces
Springfield Armory, Inc.	22 ", standard, 1:12, six groove, no	Wilson Arms blanks, standard M1A model
Springfield Armory, Inc.	22 ", medium, 1:11, six groove, no	loaded standard and National Match M1A models
Taiwan	22 "	T57, State Arsenal
U. S. Marine Corps	22 ", medium, 1:12, four groove, no	M14 DMR and M39 EMR, Kreiger Barrels, stainless steel, gas port not drilled per request of the U. S. Marine Corps
U. S. Marine Corps	22 ", medium, 1:11, 5 R groove, no	M14 DMR, Rock Creek, stainless steel
USGI	22 ", standard, 1:12 four groove, yes	M14, M14 T, M14 EBR-RI, USGI part number 7790190, 30.7 ounces
USGI	22 ", standard, 1:12, four groove, yes	M14 NM, USGI part number 7791173

M14 RIFLE HISTORY AND DEVELOPMENT

USGI	22 ", standard, 1:12, four groove, no	M14 NM, USGI part number 7791362
USGI	22 ", medium, 1:12, four groove, no	M14 NM, USGI part number 9345206
USGI	22 ", heavy, usually 1:12, four groove, no	M14 NM, USGI part number 9349847
LRB Arms	19 ", medium, 1:12, four groove, no	Criterion Barrels
Chinese	18.5 ", standard, 1:12, four groove, yes	On some rifles exported in 2010 and later
Commercial	18.5 ", standard, 1:10, four groove, no	Wolfe Modified
Commercial Bush	18.5 ", standard, 1:10, four groove, no	Criterion Barrels
Commercial Bush	18.5 ", medium, 1:10, 1:11, or 1:12, four groove, no	Krieger Barrels, chromium-molybdenum alloy steel or stainless steel
Commercial Bush	18.5 ", heavy, 1:10, 1:11 or 1:12, four groove, no	Krieger Barrels
Fulton Armory, LRB Arms	18.5 ", standard, 1:12, four groove, no	Fulton Armory Bush, LRB Arms Tanker, supplied by Criterion Barrels
Fulton Armory, LRB Arms	18.5 ", standard, 1:12, four groove, yes	Fulton Armory Bush, LRB Arms Tanker, supplied by Criterion Barrels
LRB Arms	18.5 ", medium, 1:10, six groove, yes	LRB Arms Tanker, supplied by Criterion Barrels
NSWC Crane	18 ", standard, 1:11, six groove, no	Mk 14 Mod 0 and 1, supplied by Springfield Armory, Inc.
Smith Enterprise, Inc.	18 ", standard, 1:10, four groove, yes	M118LR chambered, SEI part number 2027, only six installed on civilian rifles, 1.4 pounds

LEE EMERSON

Smith Enterprise, Inc.	18 ", medium, 1:10, four groove, no	M14SE and Mk 14 SEI, supplied by Wilson Arms, M118LR chambered, SEI part number 9345-MK14, only three installed on civilian rifles
Springfield Armory, Inc.	18 ", standard, 1:11, six groove, no	M1A Bush and Scout Squad models, Wilson Arms blanks, machined by Springfield Armory, Inc.
Norinco	17.625 ", standard, 1:12, four groove, yes	Imported by Gun Parts Corp., 27.6 ounces
Smith Enterprise, Inc.	17.625 ", medium, four groove, no	Bush rifle conversion and initial M14 EBR models, limited number installed on civilian rifles
Springfield Armory, Inc.	16.25 ", standard, 1:11, six groove, no	SOCOM M1A models
Fulton Armory	16 ", standard, 1:10, no	Criterion Barrels
RD Systems	16 ", standard, 1:11.27, five groove, no	SOPMOD M14, supplied by Mike Rock
Smith Enterprise, Inc.	16 ", standard, 1:10, four groove, no	M118LR chambered
Harrington & Richardson, Inc.	15.5 ", standard, 1:12, four groove, yes	Guerilla Gun, barrel shortened by subcontractor
Smith Enterprise, Inc. and LaFrance Specialties	13.5 ", standard, 1:12, four groove, yes	M14K
Smith Enterprise, Inc. and LaFrance Specialties	13.5 ", medium, 1:10, four groove, no	M14K, blank supplied by Douglas

Table 36: Composition of USGI Barrels

Element	Resulphurized AISI 4150 Alloy Steel	Chromium-Molybdenum-Vanadium Alloy Steel
carbon	0.47 to 0.55 %	0.41 to 0.49 %
manganese	0.70 to 1.00 %	0.60 to 0.90 %
phosphorus	0.040 % maximum	0.040 % maximum
sulfur	0.05 to 0.09 %	0.040 % maximum
silicon	0.20 to 0.35 %	0.20 to 0.35 %
chromium	0.80 to 1.15 %	0.80 to 1.15 %
molybdenum	0.15 to 0.25 %	0.30 to 0.40 %
vanadium	none	0.20 to 0.30 %

Table 37: Properties of Walnut, Birch and Cherry

Material Property	Black Walnut	Yellow Birch	Cherry
density (lb/ft ³)	40	43	36
specific gravity	0.59	0.62	0.54
Janka hardness (pounds)	1010	1260	950
modulus of elasticity (psi)	1,790,000	2,010,000	1,665,000
bending strength (psi)	14,800	16,600	13,520
shearing strength (psi)	1,370	1,880	1,700
compression parallel to the grain - maximum crushing strength (psi)	7,680	8,170	7,865

Table 38: U. S. Military M14 Publications

Subject	Number or Title
M14 - match conditioning procedures	Accurized National Match M-14 Rifle "M-14 (MTU-NM)" TI-02648A-25/10C (1968, 1970, and 1976 editions)
T44E4 - operator's manual	SA-NM11-2612

LEE EMERSON

M14 and M15 rifles - operator's and maintenance manual	Special Text 7-179
M14 rifle - factory quality assurance inspection	ORDP-608-R-SA1
M14 rifle - operator's and organizational maintenance manual with parts and tools list	TM 9-1005-223-12P
M14 rifle - operator's and organizational maintenance manual	TM 9-1005-223-12
M14, M14E2 and M14A1 rifle - operator's manual	FM 23-8
M14 - parts list	SL-4-02648A
M14 and M2 bipod - operator's and organizational maintenance manual	TM 9-1005-223-12
M14 and M2 bipod - operator's and organizational maintenance manual	TM 9-1005-223-12
M14 and M14E2 and M2 bipod - operator's and organizational maintenance manual	TM 9-1005-223-12
M14 and M14A1 - marksmanship training	FM 23-8 FM 23-16 FM 23-71
M14 NM - factory inspection procedure	SA-SIP-7790476
M14 and M14A1 and M2 bipod - organizational maintenance manual	TM 9-1005-223-20
M14 NM and M14 M - operator's and organizational maintenance manual with parts and tools list	TM 9-1005-223-12P
M14 and M14A1 and M2 bipod - direct support through depot maintenance manual	TM 9-1005-223-35
XM21 or M21 - operator's manual	TC 23-14 DTM 9-1005-221-10 FM 23-10 Appendix B

M14 RIFLE HISTORY AND DEVELOPMENT

M14 - organizational maintenance manual	SW 370-BK-MMI-20
M14 SSR - operator's manual	SW 370-BG-OPI-010
M14 DMR - operator's manual	TM 02648C-10/1
Mk 14 Mod 0 - operator's manual	SW 370-A2-OPI-010
M14 and M2 bipod - depot maintenance manual	DMWR 9-1005-223
M14 and M14A1 and M2 bipod - operator's manual	TM 9-1005-223-10
M14 and M14A1 and M2 bipod - organizational maintenance manual	TM 9-1005-223-20
M14 DMR - organizational and intermediate maintenance manual with parts and tools list	TM 02648C-24&P/2
M14 and M2 bipod - direct support through general support maintenance manual	TM 9-1005-223-34
M14 and M2 bipod - direct support through general support maintenance manual	TM 9-1005-223-34
M14 and M14A1 and M2 bipod - direct support through general support maintenance manual	TM 9-1005-223-34
M14 DMR - building procedures	TM 02648C-35/10
M14 - manual of arms	FM 22-5 FM 3-21.5 Appendix C
M14 EBR-RI - maintenance manual	Supplement to TM 9-1005-223-10
M39 EMR - operator's manual	TM 11473A-OR/1
M39 EMR - organizational maintenance manual	TM 11473A-IN/2

Table 39: U. S. Military Publications for M14 Related Items

Accessory	Number or Title	Issue Date dd/mm/yy or mm/yy
M4, M5, M6 and M7 bayonets with M8A1 scabbard - operator through depot maintenance manual with parts and tools list	TM 9-1005-237-15P	12/18/64
M6 and M7 bayonets with M10 scabbard - organizational and direct support maintenance manual with parts and tools list	TM 9-1005-237-23&P	11/18/86
M6, M7 and M9 bayonets with M10 scabbard - organizational and direct support maintenance with parts and tools list	TM 9-1005-237-23&P	01/11/93
M7A3 and M76 grenade launchers and M15 sight - operator through general support maintenance manual with parts and tools list	TM 9-1005-234-14P	10/06/67
Sionics, Inc. M14 SS-1 sound suppressor	Operation and Maintenance Manual for the Noise and Flash Suppressor Assembly M14 SS-1	M14 NM - not available XM21 - 12/69
Small Arms Field Maintenance Shop Set (FSN 4933-754-0664)	SM 9-4-4933-A13	
Basic Small Arms Field Maintenance Tool Kit (FSN 4933-775-0366)	SM 9-4-4933-E04	
Small Arms Repairman's Tool Kit (FSN 5180-357-7770)	SM 9-4-5180-A57	

Table 40: U. S. Military Publications for M14 Optical Sights

Optical Sight	Number or Title	Issue Date dd/mm/yy or mm/yy
XM21 Adjustable Ranging Telescope	Adjustable Ranging Telescope (ART) Mounted on the Match Conditioned 7.62 mm M-14 Rifle	09/68
AN/PAS-4 - operation and maintenance manual for Varo, Inc. model	TM 5-1090-200-15	02/09/62 Change 1 05/06/63 Change 2 06/08/64
AN/PAS-4 - Varo, Inc. model maintenance manual with parts and tools list	TM 5-1090-200-25P, Model 9903	01/22/62
AN/PAS-4 - operation, maintenance and overhaul manual for Polan Industries model	Operation, Maintenance and Overhaul Manual, Model P-155	
AN/PVS-1 - operator's manual	TC 23-11	11/66
AN/PVS-1 - organizational through general support maintenance manual with parts and tools list	TM 11-5855-236-24P	12/71
AN/PVS-2, 2A and 2B - operator's manual	TM 11-5855-203-10	08/29/74 Change 1 04/13/76
AN/PVS-2 - operator through direct support maintenance manual	TM 11-5855-203-13	04/10/68

LEE EMERSON

AN/PVS-3 and AN/PVS-3A - operator's manual	TM 11-5855-209-10	12/28/67 Change 1 06/21/69 Change 2 05/19/70 Change 5 in effect
AN/PVS-3 and AN/PVS-3A - organizational and direct support maintenance manual	TM 11-5855-209-23	02/20/68 Change 5 in effect
AN/PVS-3 and AN/PVS-3A - general support and depot maintenance manual with parts and tools list	TM 11-5855-209-40P	04/18/72
AN/PVS-2, 2A, 3 and 3A - procedure for determining serviceability	TB 11-5800-212-24	08/20/73
AN/PVS-4 - operator's manual	TM 11-5855-213-10	12/31/76 09/13/85 (reprinted in 1990) 02/01/93
AN/PVS-4 - organizational and direct support maintenance manual with parts and tools list	TM 11-5855-213-23&P	06/01/93
AN/PAQ-4 - operator's manual	TM 11-5855-261-10	05/28/81
AN/PAQ-4 - organizational and direct support maintenance manual	TM 11-5855-261-23	10/21/81
AN/PAQ-4 - organizational and direct support maintenance manual with parts and tools list	TM 11-5855-261-23P	10/23/81
AN/PAQ-4A - operator's and organizational maintenance manual with parts and tools list	TM 11-5855-297-12&P	09/15/90 Change 1 in effect

M14 RIFLE HISTORY AND DEVELOPMENT

AN/PAQ-4B and AN/PAQ-4C - operator's and organizational maintenance manual with parts and tools list	TM 11-5855-301-12&P	05/15/00
AN/PEQ-2A - operator's and organizational maintenance manual with parts and tools list	TM 11-5855-308-12&P TM 10271A-23&P/2	05/15/00
AN/PVS-10 - operator's and organizational maintenance manual with parts and tools list	TM 11-5855-303-12&P	03/01/03
AN/PVS-14 - operator's manual	TM 11-5855-306-10 TM 10271A-10/1A	06/01/00
AN/PVS-14 - organizational and direct support maintenance manual with parts and tools list	TM 11-5855-306-23&P TM 10271A-23&P/2	06/01/00

Table 41: Material Selection for USGI M14 Parts

USGI M14 Rifle Part	Specified Material
barrel (parts 7790190, 7791362, 9345206 and 9349847)	chromium-molybdenum-vanadium or 4150 resulphurized alloy steel heat treated to 30 to 35 HRC
bolt	8620H alloy steel
bolt lock	8620 alloy steel for wrought material and precision casting
bolt lock spring	QQ-W-470 wire steel
bolt roller	ASTM A681 tool steel
bolt roller retaining ring	ASTM A228 steel wire
burr, M14A1 stock	1045, 1050 or 1055 carbon steel spheroidized annealed
butt plate	aluminum per QQ-A-250
bushing, M14A1 stock swivel rear	1018 through 1022 carbon steel per QQ-S-634
butt plate cap	7075 T6 alloy aluminum
butt plate cap pin	1050 through 1095 carbon steel
butt plate flapper, M14	.17 to .24 carbon content steel drawing quality per QQ-S-698

LEE EMERSON

butt plate flapper, M14A1	1060 or 1065 carbon steel
butt plate hinge block	6061 alloy aluminum
butt plate hinge spring	QQ-W-470 wire steel
butt plate screw nut retainer	1050 through 1070 carbon steel
butt swivel	1018 through 1022 or 1141 carbon steel
cartridge clip guide	4140 or 8620 alloy steel
connector	8645, 8740, or 8742 alloy steel heat treated to 36 to 41 HRC
connector lock	1018 carbon steel
ejector	1060 carbon steel with fracture grain size 7 or finer
ejector spring	ASTM A228 cold drawn high carbon music spring wire
extractor	8645 or 8740 alloy steel grain size 7 or finer
extractor spring	QQ-W-470 wire steel
extractor spring plunger	1060 through 1095 carbon steel
firing pin, third version	8640 or 8645 or 8740 spheroidized alloy steel with complete chromium plating
flash suppressor, late	4140 alloy steel for wrought material 4140 alloy steel with carbon content 0.43 to 0.53 % for precision casting
flash suppressor nut	8640, 8642, 8645, 8740 or 8742 alloy steel austenitic grain size 5 to 8
front band	1035 or 1050 carbon steel heat treated to 30 to 35 HRC
front sight	heat treated to 42 to 45 HRC: 8640, 8740 or 4150 alloy steel for wrought material or 4140 alloy steel with carbon content was 0.43 to 0.53 % for precision casting
front sight screw, early version	steel heat treated to 36 to 43 HRC
front sight screw, late version	steel heat treated to 36 to 45 HRC
gas cylinder	416 stainless steel with contents of 0.50 % or less in copper, 0.04 % or less in phosphorus, and 12.00 to 13.50 % in chromium

M14 RIFLE HISTORY AND DEVELOPMENT

gas cylinder lock	4150 alloy steel
gas cylinder plug	416 stainless steel heat treated to 32 to 40 HRC
gas piston	originally 416 stainless steel but later changed to 420 stainless steel with no more than 0.5 % copper content 440 stainless steel for M21A5 gas pistons
grommet, M14A1 stock	rubber composition
hammer	8620H alloy steel austenite grain size 5 or smaller and heat treated to 80 to 83 HRA hardness
hammer pin	1060 through 1080 carbon steel
hammer spring	ASTM A228 cold drawn high carbon music spring wire
hammer spring housing	1112, 1117 or 1212 carbon steel
hammer spring plunger	1112, 1117 or 1020 carbon steel
hand grip, M14A1 stock	rubber coating
hand grip block, M14A1 stock	8640 alloys steel
magazine body (tube)	1050 spheroidize annealed drawing quality carbon steel and heat treated to 71 to 76 HRA hardness
magazine filler (late version)	cold rolled steel heat treated to No. 4 temper per QQ-S-698
magazine floor plate	ASTM A109 carbon steel (no more than 0.25 % carbon) and heat treated to 71 to 76 HRA hardness
magazine follower and stop	Federal Specification QQ-S-698 drawing quality carbon steel and heat treated to file hard
magazine latch	8615 alloy steel for wrought material and 8620H alloy steel for precision casting, heat treated to file hard
magazine latch spring	QQ-W-470 wire steel
magazine spring	ASTM A228 cold drawn high carbon music spring wire

LEE EMERSON

operating rod	8645H alloy steel (Gun Quality) with austenite grain size 7 or finer for the handle portion 8645H or 8742H for the tube portion Both portions heat treated to 40 to 46 HRC
operating rod guide	4140, 8640, 8645 or 8740 alloy steel
operating rod spring	17-7 precipitation hardening stainless steel wire
operating rod spring guide (solid USGI version)	forged 8640 or 8645 alloy steel and heat treated to 40 to 45 HRC
operating rod spring guide (USGI version with holes)	stamped 8640 or 8645 alloy steel and heat treated to 40 to 45 HRC
rear sight aperture	1141 carbon steel forging or 1040 carbon steel seamless tubing
rear sight base	1141 carbon steel heat treated to 45 to 50 HRC
rear sight cover	1055 or 1065 carbon steel austenitic grain size 5 or finer
rear sight elevation dog retainer	number 3 temper (quarter hard) carbon steel per QQ-S-698 or ASTM A109
rear sight elevation knob	1016 through 1020 or 1117 carbon steel or 8615 alloy steel
rear sight elevation pinion	1037 or 1141 carbon steel
rear sight nut	1141 carbon steel
rear sight nut lock	ASTM A109 carbon steel
rear sight spring	1095 carbon steel spheroidize annealed
rear sight windage knob	1022 or 1117 carbon steel
recoil pad, M14A1 stock	synthetic rubber molded over ASTM A109 sheet steel
recoil pad plug, M14A1 stock	synthetic rubber
safety	1021 carbon steel for wrought material 8620 alloy steel with 0.08 to 0.18 % carbon content or 1020 for precision casting
safety spring	ASTM A504 wire steel

M14 RIFLE HISTORY AND DEVELOPMENT

screw, M14 stock upper butt	1018, 1020 or 1117 carbon steel per ASTM A108
screw, M14A1 stock hand grip screw (late version)	1020 carbon steel per ASTM A108
screw, M14A1 stock recoil pad lower	1018 to 1020 or 1117 carbon steel
screw, M14A1 stock recoil pad upper	1018, 1020 or 1117 carbon steel per ASTM A108
sear	8620 alloy steel except sulfur content is 0.035 to 0.050 % with austenite grain size 5 to 8
sear release	8615 alloy steel for wrought material 8620 alloy steel except 0.10 to 0.20 % carbon content for precision casting
selector shaft	1141 carbon steel or 8645 alloy steel
selector shaft lock	1025, 1117 or 1118 carbon steel heat treated to file hard
small arms sling strap, 1986 design	bulked nylon webbing Type II
spindle valve	440A stainless steel
spindle valve spring	302 or 304 stainless steel
stock ferrule	ASTM A619 drawing quality steel
stock ferrule, National Match	ASTM A109 drawing quality steel
stock liner screw	1035, 1040, 1137 or 1141 carbon steel
swivel, M14A1 stock front	1018 to 1022 or 1141 carbon steel per ASTM A108
swivel, M14A1 stock rear	1018 to 1022 or 1141 carbon steel per ASTM A108
swivel bracket, M14 stock	ASTM A366 or ASTM A109 dead soft temper carbon steel
swivel loop, M14 stock	1018 to 1022 carbon steel per ASTM A108, A575 or A576
trigger	8620 alloy steel except sulfur content is 0.035 to 0.050 % with austenite grain size 5 or finer
trigger guard	1060 or 1065 carbon steel

trigger housing	1141 carbon steel with austenitic grain size 7 or finer
-----------------	---

The earliest and latest observed dates of manufacture noted for the items in Table 25 were either found by firsthand examination or through photographs of the original packaging. A single entry for an item indicates only one date observed so far.

Table 42: Observed Manufacture Dates for USGI M14 Rifle Items

USGI Contract Item - Spare Part or Tool	Earliest Observed Date of Packaging	Last Observed Date of Packaging
AN/PVS-4 carrying case		September 1990
barrel, chromium plated	December 1960	February 1983
barrel, NM lightweight	April 1966	June 1985
barrel, NM medium weight	1983	1992
barrel, NM heavyweight	May 1984	April 1993
barrel cleaning rod patch tip		March 1967
barrel reflector		April 1966
bolt with roller	July 1969	March 1970
bolt lock	March 1962	December 1966
bolt lock pin		1963
bolt roller		October 1967
bolt roller retainer		December 1967
bolt roller retaining ring pliers		November 1965
bore reflector		April 1966
broken shell extractor	October 1959	July 1961
cartridge clip guide		December 1971 (arsenal rewrap)
case, cleaning kit rod section	February 1966	May 1968
chamber brush, black ratchet	June 1960	May 1970
cleaning rod section	January 1967	August 1984
combination tool	March 1961	March 1968 (contract) December 1974 (arsenal rewrap)

M14 RIFLE HISTORY AND DEVELOPMENT

connector assembly	August 1963	October 1967
connector lock		November 1964
connector lock pin		March 1996
ejector assembly	December 1960	July 1967
extractor spring assembly		November 1964
extractor (late design)		January 1965
firing pin, first version		December 1961
firing pin, third version	June 1967	October 1969
flash suppressor	January 1961	July 1970
flash suppressor nut	March 1961	July 1961
flash suppressor nut setscrew		March 1978
flash suppressor nut wrench		May 1962
front band	December 1961	December 1972 (arsenal rewrap)
front sight screw		October 1966
gas cylinder	September 1961	November 1969
gas cylinder lock	April 1962	May 1966
gas cylinder plug	November 1960	June 1966
gas piston (non-coated)	February 1962	October 1967 (contract) June 1972 (arsenal rewrap)
gas piston (coated)	July 1993	September 1995
hammer	March 1963	September 1974 (arsenal rewrap)
hammer spring	August 1966	May 1981 (U. S. Navy contract)
hand guard assembly, solid	May 1964	August 1967
lubricant case		October 1961
M2 aiming device		February 1965
M2 bandoleer	July 1966	October 1989
M2 bipod	December 1963	March 1968

LEE EMERSON

M3 breech shield		June 1973
M5 winter trigger	December 1962	January 1968
M6 bayonet	April 1962	December 1968
M6 bayonet grip, left side	December 1966	April 1967
M6 bayonet grip, right side	August 1964	July 1966
M12 blank firing attachment, all versions	October 1964	June 1973
M14E2 muzzle stabilizer modification kit		July 1967
M14E2 stock modification kit		April 1968
M76 grenade launcher	July 1961	August 1961
M151 vehicle M14 rifle mounting kit	May 1967	November 1969
M1907 leather sling	May 1963	May 1995
M1956 canvas magazine pouch	September 1959	September 1969
M1961 canvas magazine pouch	FY1962 contract	FY1967 contract
M1961 individual equipment belt		FY1967 contract
M1967 nylon magazine pouch for the M14	FY1970 contract	FY1972 contract
M35 truck M14/M16 dual rifle mounting kit		October 1987
magazine	1959	July 2005
magazine latch	February 1960	December 1963
operating rod	July 1961	October 1986
operating rod guide	November 1959	June 1967
operating rod spring	January 1962	March 1966
operating rod spring guide	March 1961	July 1967
rear sight aperture, standard	April 1963	September 1964
rear sight aperture, National Match hooded		January 1967
rear sight base	February 1962	April 1976 (arsenal rewrap)
rear sight cover		July 1962
rear sight elevation knob and spindle	April 1962	November 1965 (M1 knob)
rear sight windage knob	February 1962	April 1963

M14 RIFLE HISTORY AND DEVELOPMENT

safety	January 1962	June 1969
safety spring	March 1961	July 1969
selector spring	April 1961	May 1963
selector switch	October 1960	March 1967
sling swivel		March 1968
small arms sling, fabric	April 1964	1975 contract
spindle valve	January 1962	August 1969
stock, fiberglass		January 1968
stock, National Match, 9352638		November 1988
stock subassembly, National Match, 11010282		August 1966
stock ferrule, National Match		December 1990
stock repair screws, large		May 1965
stock screw, wood upper butt		January 1968
trigger and sear assembly	March 1961	March 1966
trigger guard	October 1960	January 1968 (contract) March 1968 (arsenal rewrap)
trigger housing	April 1962	October 1967

Table 43: Subcontractors to USGI Contractors

Company	Subcontractor to	Known parts made or support rendered as a subcontractor
20th Century Manufacturing (Chicago, IL)	Harrington & Richardson	
A & M Tool and Die Co., Inc. (Southbridge, MA)	Harrington & Richardson	
A. A. Brunell Electroplating (Worcester, MA)	Harrington & Richardson	

LEE EMERSON

Aber Machine & Tool Corp. (East Templeton, MA)	Harrington & Richardson	
Allied Manufacturing Co., Inc. (Worcester, MA)	Harrington & Richardson	tooling support
American Twist Drill Company (Detroit, MI)	Harrington & Richardson	
American Walnut (Kansas City, KS)	Harrington & Richardson	
Associated Engineers (Springfield, MA)	Harrington & Richardson	
Atwood Vacuum Machine Co. (Rockford, IL)	Springfield Armory	magazine
B. F. Goodrich Co. (Watertown, MA)	Harrington & Richardson	
Bay State Tool & Machine (Springfield, MA)	Harrington & Richardson	
Bemis & Call (Springfield, MA)	Harrington & Richardson	
Bird & Sons (Walpole, MA)	Harrington & Richardson	
Birken Manufacturing Co. (Hartford, CT)	Harrington & Richardson	
Booker & Wallestad (Minneapolis, MN)	Harrington & Richardson	
Borg-Warner (Rockford, IL)	Olin Mathieson Chemical Corporation Springfield Armory	magazine
Bostitch, Inc. (East Greenwich, RI)	Harrington & Richardson	unknown parts

M14 RIFLE HISTORY AND DEVELOPMENT

Botwink Brothers (Worcester, MA)	Harrington & Richardson	
Bristol Spring Manufacturing Co. (Plainville, CT)	Harrington & Richardson	
Brookfield Machine & Tool (West Brookfield, MA)	Harrington & Richardson	tooling support
Brown & Sharpe Manufacturing Co. (Providence, RI)	Harrington & Richardson	
Bruce Machine and Engineering, Inc. (Peabody, MA)	Springfield Armory	windage knob
Brunswick Sports Products Co. (Los Angeles, CA)	Olin Mathieson Chemical Corporation	magazine
Casting Engineers (Chicago, IL)	Harrington & Richardson	
Chandler & Farquhar Company (Boston, MA)	Harrington & Richardson	
Chemical Corporation (Springfield, MA)	Harrington & Richardson	
Chenard Machine (Worcester, MA)	Harrington & Richardson	
Cincinnati Milling (Cincinnati, OH)	Harrington & Richardson	
Conetta Manufacturing Co. Inc. (Stamford, CT)	Harrington & Richardson	
Continental Screw Company (New Bedford, MA)	Harrington & Richardson	

LEE EMERSON

CPP	Springfield Armory	NM windage knob
Dearborn Gage (Garden City, MI)	Harrington & Richardson	
Detroit Broach & Machine (Rochester, MI)	Harrington & Richardson	
Dougherty Tool Co. (Southboro, MA)	Harrington & Richardson	unknown parts
Druge Brothers Manufacturing Co. (Oakland, CA)	TRW	windage knob
Dunbar Brothers (a division of Associated Spring Corp.) (Bristol, CT)	Harrington & Richardson	
Eagle Tool (Iron Mountain, MI)	Harrington & Richardson	
Eastern Machine & Tool Co. (Worcester, MA)	Harrington & Richardson	tooling support
Elastic Stop Nut (Union, NJ)	Harrington & Richardson	
Elbro Tool Co., Inc. (Cherry Valley, MA)	Harrington & Richardson	tooling support
Excell-o Corporation (Greenville, OH)	Harrington & Richardson	
Falls Machine Screw Co. (Chicopee, MA)	Harrington & Richardson	
Federal Products Corp. (Providence, RI)	Harrington & Richardson	
G. E. Prentice Company (Kensington, CT)	Harrington & Richardson	

M14 RIFLE HISTORY AND DEVELOPMENT

General Tire & Rubber Co. (Marion, IN)	Harrington & Richardson	fiberglass stock
George F. Blake (Worcester, MA)	Harrington & Richardson	
Granger Contracting Company (Worcester, MA)	Harrington & Richardson	
Greenfield Tap & Die (Greenfield, MA)	Harrington & Richardson	
H. Sacks & Sons, Inc. (Brookline, MA)	Harrington & Richardson Springfield Armory	M14 stock for Springfield Armory
Hartford Gage Co. (West Hartford, CT)	Harrington & Richardson	
Hartford Machine Screw Co. (Hartford, CT)	Harrington & Richardson	
Hesse Machine & Mfg. Co., Inc. (Boston, MA)	Harrington & Richardson	unknown parts
Hesse Machine & Mfg. Co., Inc. (Boston, MA)	Olin Mathieson Chemical Corporation	magazine latch
Heywood-Wakefield Co. (Gardner, MA)	Harrington & Richardson	unknown parts
Hoppe Tool (Springfield, MA)	Harrington & Richardson	
Hurley Manufacturing Company (New Hartford, CT)	Harrington & Richardson	
Ikonen Tool & Die Co. (Templeton, MA)	Harrington & Richardson	
Illinois Tool Works (Chicago, IL)	Harrington & Richardson	

LEE EMERSON

Industrial Research (Holyoke, MA)	Harrington & Richardson	
John Bath Co. (Worcester, MA)	Harrington & Richardson	tooling support
Jones & Lamson Machine Co. (Springfield, VT)	Harrington & Richardson	
Kennametal, Inc. (Windsor Locks, CT)	Harrington & Richardson	
Killeen Machine & Tool Co. (Worcester, MA)	Apex Metal Stamping, Springfield Armory, Harrington & Richardson	magazine for Apex Metal Stamping and Springfield Armory, magazine and butt plate assembly for Harrington & Richardson
Kingsbury Machine Tool Corp. (Keene, NH)	Harrington & Richardson	
Krueger-Barnes Corp. (Detroit, MI)	Harrington & Richardson	
La Pointe Machine Tool Co. (Hudson, MA)	Harrington & Richardson	
Leesona Corp. (Providence, RI)	Harrington & Richardson	
Letts Drop Forge (Detroit, MI)	Harrington & Richardson	
Lundquist Tool & Mfg. Co. (Worcester, MA)	Harrington & Richardson Olin Mathieson Chemical Corporation	operating rod spring guide
Manchester Tool & Design (Manchester, CT)	Harrington & Richardson	
Massachusetts Steel Treat (Worcester, MA)	Harrington & Richardson	

M14 RIFLE HISTORY AND DEVELOPMENT

Mechanical Components Corporation	Craft Metal Corporation	gas cylinder
Mercury Tool & Machine (Aston, PA)	Rock Island Arsenal	operating rod
Michigan Machine & Broach (Detroit, MI)	Harrington & Richardson	
Middlesex Paper Tube (Lowell, MA)	Harrington & Richardson	
Millbury Engineering Co. Inc. (Millbury, MA)	Harrington & Richardson	unknown parts and tooling support
Mite Corporation (New Haven, CT)	Harrington & Richardson	
Moore Drop Forge Co. (Springfield, MA)	Harrington & Richardson	
Morrow Manufacturing Company (North Kingston, RI)	Harrington & Richardson	
Morse Twist Drill (New Bedford, MA)	Harrington & Richardson	
MXR	Springfield Armory, possibly Olin Mathieson Chemical Corporation	safety
National Rivet & Manufacturing Co. (Waupun, WI)	Harrington & Richardson	
New Haven Clock and Watch Co. (New Haven, CT)	TRW	elevation knob and spindle assembly
North Machinery Sales (South Boston, MA)	Harrington & Richardson	

LEE EMERSON

Ober Tool & Die Company, Inc. (Everett, MA)	Harrington & Richardson	
Olson Manufacturing Co. (Worcester, MA)	Harrington & Richardson	
P & O Machine Co. (Brockton, MA)	Harrington & Richardson	
Packaging Service (Agawam, MA)	Harrington & Richardson	
Perry Packaging (Boston, MA)	Harrington & Richardson	
Pilot Company (Hartford, CT)	Harrington & Richardson	
Pioneer Tool Co. (West Springfield, MA)	Harrington & Richardson	
Pratt & Whitney Co. (West Hartford, CT)	Harrington & Richardson	
Precision Products (Chicopee, MA)	Harrington & Richardson	
Rathbone Corporation (Palmer, MA)	Harrington & Richardson	
Rhode Island Tool Co. (Providence, RI)	Harrington & Richardson	
Rochester Manufacturing Co., Inc. (Rochester, NY)	Harrington & Richardson Springfield Armory	magazine
S. E. Overton Co. (South Haven, MI)	TRW	wood stock
Saco-Lowell (Saco, ME)	Springfield Armory, Harrington & Richardson	gas cylinder

M14 RIFLE HISTORY AND DEVELOPMENT

Scoville Manufacturing Co. (Waterbury, CT)	Harrington & Richardson	
Sheffield Corporation (Dayton, OH)	Harrington & Richardson	
Sime Control Company (Chicago, IL)	Harrington & Richardson	
Simonds Machine Company (Southbridge, MA)	Harrington & Richardson	
Southern Gage (Erin, TN)	Harrington & Richardson	
Southern Screw Company (Statesville, NC)	Harrington & Richardson	
Stanley Industrial Components (Forestville, CT)	Harrington & Richardson	
Stanley-Humason (Forestville, CT)	Olin Mathieson Chemical Corporation	front band, safety spring
Star Gage Company (Springfield, MA)	Harrington & Richardson	
Sterling Sales (North Grafton, MA)	Harrington & Richardson	
Storms Drop Forging Co. (Springfield, MA)	Harrington & Richardson	receiver and other part forgings
Swank, Inc. (Attleboro, MA)	Olin Mathieson Chemical Corporation	selector lock
Textile Machine Works (Reading, PA)	Harrington & Richardson	bolt
The Connecticut Spring Corp. (Farmington, CT)	Harrington & Richardson	

LEE EMERSON

The Franklin Screw Machine Co. (Hartford, CT)	Harrington & Richardson	
The Hanson & Whitney Co. (Hartford, CT)	Harrington & Richardson	
The Torrington Company (Torrington, CT)	Harrington & Richardson	gas cylinder
Thomas Smith Co. (Worcester, MA)	Harrington & Richardson	
Triple X Sales (Westboro, MA)	Harrington & Richardson	
Union Hardware & Metal Company (Los Angeles, CA)	Springfield Armory, Olin Mathieson Chemical Corporation	magazine
Union Twist Drill Co. (Athol, MA)	Harrington & Richardson	
United Engineers, Inc. (Springfield, MA)	Harrington & Richardson	
Unity Machine & Tool (Philadelphia, PA)	Harrington & Richardson	
Varsity Manufacturing Co. (West Springfield, MA)	Harrington & Richardson	
W. J. Shannon Trucking Co. (Worcester, MA)	Harrington & Richardson	
Wachusett Corrugated Corp. (Worcester, MA)	Harrington & Richardson	
Waltham Precision Instrument (Waltham, MA)	Harrington & Richardson	
Westfield Gage Co. (Westfield, MA)	Harrington & Richardson	

M14 RIFLE HISTORY AND DEVELOPMENT

Westinghouse Electric (East Springfield, MA)	Harrington & Richardson, Olin Mathieson Chemical Corporation	magazine
Wetzel Tool Co. (East Hartford, CT)	Harrington & Richardson	
Wico Electric Co. (a division of Eltra Corp.) (West Springfield, MA)	Harrington & Richardson, TRW	elevation knob
Wico Electric Co. (West Springfield, MA)	TRW	windage knob
Worcester Tool & Die Co., Inc. (Worcester, MA)	Harrington & Richardson	tooling support
Wright Manufacturing Co. (Worcester, MA)	Harrington & Richardson, TRW	windage knob, bar stock blank for selector (H&R)

The following is a list of known contractors and government facilities that have produced USGI M14 parts. The individual entity is listed first followed by any identifying marks or Commercial and Government Entity (CAGE) Code and what parts the contractor is known to have made.

Table 44: USGI Contractors for M14 Rifle Items

USGI Contractor	Identifying Marks or CAGE Code	M14 Parts or Accessories Made
A. F. Machine & Tool Co., Inc. (Inglewood, CA)	64406	windage knob
A-1 Sewing Contractors, Inc. (St. Louis, MO)	0NZ21	M1967 nylon dual magazine pouch for the M14
Adkins Wood Products Corp. (Ozone Park, NY)		two button fabric envelope
Advanced CNC Manufacturing, Inc. (Largo, FL)	1YDC9	gas piston

LEE EMERSON

Adventure Line Mfg. Co. Inc. (Parsons, KS)		M11 small arms storage rack
Aerial Cutlery (Marinette, WI)	Aerial	M6 bayonet
Airtronic Services Inc. Medical/ Aviation Division (Elk Grove Village, IL)	1C5Q6	flash suppressor
Allied Precision Products, Inc. (Dunedin, FL)	24249	NM windage knob
Anco Machine Co. (Huntsville, AL)	3V055	ejector and ejector spring
Anniston Army Depot (Anniston, AL)	AAD	walnut M14E2 stock
Apex Metal Stamping Co., Inc. (Brooklyn, NY)	A, APEX	M14E2 stock fore grip mount, M14E2 stock butt plate bracket, gas piston, cartridge clip
Argo Development Corporation (Inwood, NY)	ARGODEVCORP, 17808	M14E2 stock rubber butt pad
Associated Spring, Inc. (Bristol, CT)	AO	cartridge clip
Associated Spring, Inc. - Barnes- Gibson-Raymond Division (Plymouth, MI)	BGR	cartridge clip
Atwood Vacuum Machine Co. (Rockford, IL)	AV, 70523	magazine
Badger Ordnance (North Kansas City, MO)	0WXH8	M14 DMR, M39 EMR and USN Mk 14 Mod 0 scope rings

M14 RIFLE HISTORY AND DEVELOPMENT

Barlow Metal Stamping, Inc. (Bristol, CT)	9M944	NM wood stock ferrule
Bearse Manufacturing Co.		M15 grenade launcher sight carrying case
Bellmore Johnson Tool Co. (Hamden, CT)		sear release
Bells Chapel Machine & Tool (Atkins, AR)	3BDS2	safety
Benrus Watch Co. (Waterbury, CT)		third version firing pin
Beta Engineering, Inc. (Arlington, TX)	33436	operating rod guide
BHM Corporation (Monagup Valley, NY)	BHM CORP, 29763	gas cylinder plug wrench
Bondhus Corporation (Monticello, MN)	5SUT6	M14 EBR-RI, M14 EBR-RI NM, M14 T, M39 EMR, Mk 14 Mod 0 and Mk 14 Mod 2 multi-tools
Borg-Warner (Rockford, IL)	BW, BRW, BRW S-1, BRW B-2	magazine
Bray Oil Company (Los Angeles, CA)		general purpose lubricating oil, LSA oil
Brookfield Precision Tool (Brookfield, MA)	BKFLD PREC TL, 0DF66	operating rod spring guide, scope mount, gas piston, scope mount adapter for AN/PVS-4, Navy special flash suppressor, sound suppressor
Bruce Machine and Engineering, Inc. (Peabody, MA)	BME, 02481	windage knob, NM windage knob
Bruce Machine and Engineering (Dearborn, MI)		gas piston
Brunswick Sports Products Co. (Los Angeles, CA)	UHC, 14530	magazine

LEE EMERSON

Canadian Arsenals, Ltd. (Long Branch, ON)	CA, C A L	standard contour NM barrel, birch M14E2 stock
Carleton Mfg. Co. (Carleton, MI)		cleaning rod section case with spacer
Cathey Enterprises, Inc. (Brownwood, TX)	8K916	M1907 leather sling
Chase Bag Co.		M2 bandoleer (observed dates September 1967 to November 1969)
Check-Mate Industries, Inc. (Wyandanch, NY)	C.M.I., 1M291	ten round and twenty round magazine
Clifton Automatic Screw Machine Co. (Erie, PA)		gas cylinder plug
Clipper International Corp. (Detroit, MI)		M14E2 stock modification kit
Columbus Milpar and Manufacturing Co. (Columbus, OH)	MILPAR COL, 16689	complete M6 bayonet, M6 bayonet left side grip
Comerford Mfg. Co. (Anaheim, CA)	COM	late version magazine filler
Conetta Mfg. Co. (Stamford, CT)		trigger and sear assembly
Continental Air Supply Co. (Fort Worth, TX)		M8A1 scabbard restraining lace
Continental Fabricators Corp. (Brooklyn, NY)		operating rod spring guide
Cooper Precision Manufacturing (Oak Ridge, TN)	1JHX1	DMR barrel

M14 RIFLE HISTORY AND DEVELOPMENT

Connetec Company, Inc. (Irvine, CA)	0EFR2	front band, safety, and trigger and sear assembly
Craft Metal Corp. (Warren, MI)		gas cylinder (prime contractor)
Crawford Development & Mfg. Co. (Tucson, AZ)		cleaning rod section
Curtis Industries, Inc. (Southfield, MI)		M14 combination tool
Del Jet Engineering and Mfg. Corp. (City of Industry, CA)		M1/M14 bolt disassembly and assembly tool
Del-Con Supply Co. (Fort Worth, TX)		M14 wood stock upper butt screw
Delta-X Corporation (Morrisville, PA)	33950	NM/2A rear sight base
Dennison Machine Tool Co., Inc. (Hickory, NC)	DM, 96567	hammer
Do Well Mfg. Co., Inc.	27471	M14E2 stock fore grip
Douglas Barrels, Inc. (Charleston, WV)	0K789	NM barrel
DPMS, Inc. (Saint Cloud, MN)	40554	trigger housing
Druge Brothers Manufacturing Co. (Oakland, CA)	DRC, 72757	windage knob, elevation knob

LEE EMERSON

E C T Corporation (Fayetteville, NC and Kinston, NC)	ECT CORP, 26946	M1967 nylon magazine pouch for the M14
East Moline Metal Products (East Moline, IL)	EMMPCO	M12 blank firing attachment, M3 breach shield
Eastern Canvas Products (Corozal, PR)		M1956 magazine web pouch
Eastern Canvas Products (Haverhill, MA)	08501	M1961 magazine web pouch
Eltra Corporation (West Springfield, MA)		elevation knob and pinion assembly
Enrex Corporation (Sterling Heights, MI)	ENREX, 0BTD4	NM windage knob
Ever Tite Manufacturing Co.		front sight
Exar Industries, Inc. (Reading, PA)	0B0K6	front sight
Farmer Supply & Tool Mfg. Corp. (Denver, CO)		M2 bipod marked 7790688
Fiel Mfg. Co., Inc. (New York, NY)		rifle butt pocket and strap assembly
Fine Manufacturing, Inc. (Lodi, NJ)	0SAR6	operating rod
Focus Hope Companies, Inc. (Detroit, MI)	00P13	ejector and ejector spring

M14 RIFLE HISTORY AND DEVELOPMENT

Ford Radio & Mica Corp. (Brooklyn, NY)	R.F.M.	late version magazine filler
Frazier Manufacturing Co.	FZR	elevation knob, windage knob
Freehold Manufacturing Assembly Co., Inc. (Little Silver, NJ)	2S308	connector lock pin
G. G. Green Enterprises, Inc. (West Warren, PA)	G.G.M.	cartridge clip
G. G. Greene Metal Stamping Co. (West Warren, PA)	G.G.G., G.G. GREENE, 26194	cartridge clip, late version magazine filler
Gar-Let Mfg. Co., Inc. (Old Forge, PA)		M11 small arms storage rack
General Automatic Corp. (Oakland, CA)		bolt roller
General Cutlery, Inc. (Fremont, OH)	20014	M10 scabbard
General Tire & Rubber Co. (Marion, IN)	89341	M14 fiberglass reinforced plastic stock
George Senn, Inc. (Philadelphia, PA)		rifle bore cleaner
Globe Union, Inc. Ignition Division (West Springfield, MA)		elevation knob and spindle
Gramercy Machine Corp. (Freeport, NY)		M5 winter trigger

LEE EMERSON

Greene Metal Products, Inc. (then Harrison Township, MI)	OLKH0 later 4M107	bore straightness plug gage
Guenther Mfg. Co., Inc. (Buchanan, NY)		trigger guard
H. Sacks & Sons, Inc. (Brookline, MA)	S under half-lozenge	M14, M14 NM (7791174 and 11010263) and M14A1 birch stocks
Harrington & Richardson (Rochdale and Worcester, MA)	H, H R, H&R, HRA, H&R Arms Co., H&R D	bolt lock, chromium plated barrel, extractor spring assembly, flash suppressor, flash suppressor nut, front band, gas cylinder, gas cylinder lock, gas cylinder plug, gas piston, hammer, operating rod, receiver, rear sight base, safety, selector switch, trigger and sear assembly, trigger guard assembly, trigger housing, M14 wood stock chamber brush
Harris Engineering, Inc. (Barlow, KY)	57215	M14 DMR, M39 EMR, Mk 14 Mod 0, M14 EBR-RI, M14 EBR-RI NM, and M14 T bipods
Hart Rifle Barrels, Inc. (Lafayette, NY)	0FMZ6	NM barrel
Hauser Products, Inc. (Chicago, IL)	1Z803	M10 scabbard
Heckethorn Mfg. Co. (Dyersburg, TN)		M1961 magazine web pouch
Hertzberg & Son, Inc. (Middletown, NY)		M14 chamber brush

M14 RIFLE HISTORY AND DEVELOPMENT

Hesse Machine & Mfg. Co., Inc. (Boston, MA)	H, 21935	blank firing attachment, flash suppressor, magazine latch
Holiday Mfg. Co. (likely Grand Island, NE)		lubricant case
Imperial Knife Company (Providence, RI)	Imperial, 74846	M6 bayonet, M10 scabbard
Industrial Home For The Blind (Brooklyn, NY)	83268	soft nylon weave small arms sling
J P Manufacturing		late version magazine filler
James Ippolito & Company (Bridgeport, CT)	96458	NM rear sight base
Kanvas King, Inc. (Los Angeles, CA)		M1961 magazine web pouch
Killeen Machine & Tool (Worcester, MA)	KMT CO., K8, 92983	magazine (ten and twenty round), operating rod spring guide, safety, late style trigger guard, standard M14 stock butt plate flapper
Kingspoint Manufacturing Co., Inc. (Fayetteville, NC)		M2 bandoleer, M1967 nylon dual magazine pouch for the M14, M1907 sling
Kisatchie Machine Works (Forest Hill, LA)	1TE83	M39 EMR bipod lock
Krieger Barrels, Inc. (Richfield, WI)	0DCS1	DMR and NM barrels
LPR Precision Parts & Tools Co. (Farmingdale, NY)	LPR	NM windage knob

LEE EMERSON

La Crosse Garment Mfg. Co., Inc. (Mauston, WI)		M1956 magazine web pouch
Lady Mac Corset Co., Inc. (Buffalo, NY)	18331	M14A1 cleaning kit pouch
Lexington Industries, Inc. (Port Sanilac, MI)		M151 vehicle mounting kit for M14 and M16 rifles
Lufkin Industries (Lufkin, TX)	stylized Lufkin	cartridge clip, elevation knob, windage knob
Lundquist Tool and Mfg. Co. (Worcester, MA)	74010	early version operating rod spring guide
L W Schneider, Inc. (Princeton, IL)	50481	M14 NM sling swivel assembly (part number 9352716)
Made Rite Tool Co. (Holyoke, MA)	13455	NM windage knob
Mathewson Tool Co. (New Haven and later Orange, CT)	26097	early (T44E4 design) walnut stock, magazine, M14E2 stock butt plate bracket, M14E2 stock rubber butt pad, M14E2 muzzle stabilizer modification kit
McMillan Fiberglass Stocks, Inc. (Phoenix, AZ)	0LB99	DMR and NM stocks
Mechanical Components Corporation (Glendale, CA)	27454	gas cylinder
Mercury Tool & Machine (Aston, PA)	24411	operating rod
Metal Craft Co. (Detroit, MI)		M151 vehicle mounting kit for M14 rifle

M14 RIFLE HISTORY AND DEVELOPMENT

Metal Industries, Inc. (Amarillo, TX)		broken shell extractor
Mill-Rose Company (Mentor, OH)		bore brush
Milo Components, Inc. (Freeport, NY)		ruptured cartridge case extractor
Minnesota Aerospace Corp. (Anoka, MN)		M1961 individual equipment belt
National Machine & Tool Corp. (Waukegan, IL)	9W421	cleaning rod section
New Haven Clock and Watch Co. (New Haven, CT)	NHC, 76728	elevation knob and spindle
Nomura Machine (Stockton, CA)	NOA, 0NWF5	NM heavyweight barrel assembly, NM medium weight barrel
North & Judd Manufacturing Co. (New Britain, CT)	an anchor symbol	small arms sling metal hardware
Novelty Products Co. (New York, NY)	NOV PROD CO, NOV PROD	M2 bandoleer (observed dates of July 1966 to April 1969)
O K Tool & Die Co. (Williamstown, NJ)		bore reflector
Olin Mathieson Chemical Corporation (New Haven, CT)	OM, W-W, Winchester, 66118	bolt, chromium plated barrel, flash suppressor, gas cylinder, hammer, M14 wood stock, magazine, operating rod, receiver, safety, rear sight aperture, rear sight base, trigger and sear assembly, sear release, trigger housing, ammunition
Ontario Knife Co. (Franklinville, NY)	2V376	M10 scabbard

LEE EMERSON

P. T. E. Inc. (then Hicksville, NY)	26546	NM 0.0520 " hooded aperture assembly
Peninsular Chemical Products Co. (Detroit, MI)		spindle valve
Pennsylvania Working Home for the Blind (Philadelphia, PA)	PWH, TWB, 86465	M8A1 scabbard
Precision Gage Co., Inc. (Chicago, IL)		gas cylinder plug gage
Precision Products, Inc. (Chicopee, MA)		ejector assembly, hammer spring housing
Prospect Mfg. & Engineering Co. (Taylor Center, MI)		M14 combination tool, cleaning rod section
Pyle Machine Co., Inc. (Fort Worth, TX)	4G848	NM operating rod guide
R. M. Hollingshead Corporation (Hanover, NJ)		general purpose lubricating oil
Raubar Manufacturing Co. (Detroit, MI)		cleaning rod section
Reinhart Fajen, Inc. or R F Acquisition, Inc. (Warsaw, MO)	77742, 3T616	NM stock
Rochester Manufacturing Co., Inc. (Rochester, NY)	HR-R, <u>R</u>	magazine

M14 RIFLE HISTORY AND DEVELOPMENT

Rock Island Arsenal (Rock Island, IL)	19204	walnut M14E2 stock, operating rod, M10 scabbard
Romark Industries, Inc. Military Systems Division (Babylon, NY)	25507	NM windage knob
Roselle Precision Products, Inc. (Berkeley Heights, NJ)		connector lock
S. E. Overton Co. (South Haven, MI)	O	wood stock
Saco-Lowell later Maremont Corporation (Saco, ME)	SAK, 26978	chromium plated barrel, standard, medium and heavy contour NM barrel, third version firing pin, gas cylinder, gas piston, and operating rod
Sage International, Ltd. (Oscoda, MI)	0Y503, 1NUY9	M14 EBR, M39 EMR and Mk 14 stock and accessories
Scott Products, Inc. (New Baltimore, MI)	2W003	gas piston
Screwtech, Inc.		flash suppressor nut setscrew
Seaboard Mfg Laboratories, Inc. (Philadelphia, PA)		rifle bore cleaner
Seymour Products Co. (Seymour, CT)	SEY, SEMCO, 86951	cartridge clip, early and late version magazine filler, M2 bandoleer
SGW (Olympia, WA)	SGW, 4S779	NM barrel
Sheffield Corp.		M14 fiberglass reinforced plastic stock
Sigma Manufacturing Industries, Inc. (Bronx, NY)	0CXJ6	safety

LEE EMERSON

Singer Hosiery Mills, Inc. (Thomasville, NC)		M1961 magazine web pouch
Sloane M Mfg. Co. (Chelsea, MA)		cleaning kit rod section case with spacer
Sloane M Mfg. Co. (New Prague, MN)		hard nylon weave small arms sling
Smith Enterprise, Inc. (Tempe, AZ)	SEI, 3A5E1	connector lock, extended bolt lock, flash hider, gas cylinder, gas cylinder lock, gas cylinder lock front sight, gas piston, hammer, hammer pin, hammer spring, muzzle brake, NM rear sight assembly, NM and standard front sights, operating rod, operating rod spring, operating rod spring guide, scope mounts, sound suppressors, stock rails, trigger pin and 30 mm scope rings
Southwest Grease & Oil Co., Inc. (Kansas City, MO)		semi-fluid lubricant
Spec Tool Co. (Pico Rivera, CA)		operating rod guide
Spiral Tool Co. (then Woodside, NY)	02108	M14A1 butt plate assembly
Springfield Armory (Springfield, MA)	S A, Springfield Armory, 19205	all rifle parts and all magazine parts
SPS Co.		bolt lock pin
Stanley-Humason, Inc.		front band, safety spring
Sterling Tool & Mfg. Co. (Chicopee Falls, MA)		magazine latch
Stewart Iron Works (Covington, KY)	SWK, 82664	windage knob
Structurlite Plastics Corp. (Hebron, OH)		solid fiberglass hand guard assembly

M14 RIFLE HISTORY AND DEVELOPMENT

Sunshine Makers, Inc. (Huntington Beach, CA)	1Z575	cleaning compound for the Mk 14 Mod 0
Swaim Machine Co., Inc. (Scottsboro, AL)	8T985	operating rod guide
Swank, Inc. (Attleboro, MA)		selector lock
Textile Machine Works (Wyomissing, PA)	HRT	bolt
TRW, Inc. (Cleveland, OH)	TRW	bolt, connector, flash suppressor, gas cylinder, gas piston, hammer, magazine, operating rod, rear sight base, receiver, safety, trigger housing, chromium plated barrel, and standard contour NM barrel
Tong Industries (Republic of Korea)	88 T I, 89 T I, 90 T I and T I	safety (numerals indicate year of manufacture), windage knob
Torrington Co. (Torrington, CT)		gas cylinder
Tri-Technologies Inc. (Mount Vernon, NY)	06MA8	front sight, operating rod, trigger and sear assembly
Union Hardware & Metal Company (Los Angeles, CA)	U H C (in a semi-circle), 78988	magazine
Unknown # 1	3JP	rear sight cover
Unknown # 2 - possibly Apex Metal Stamping Co., Inc. (Brooklyn, NY)	A ₁ , A3	cartridge clip
Unknown # 3	raised letter A	safety
Unknown # 4 - possibly J&D Tool Company	AN	M6 bayonet

LEE EMERSON

Unknown # 5	raised lettering ATW	part number 7790837 M2 bipod left leg shaft assembly
Unknown # 6 - possibly Ballard Pool & Cue or Milton Bradley Co.	B	wood stock
Unknown # 7	raised lettering BKS	part number 7790837 M2 bipod left leg shaft assembly
Unknown # 8	BST2	NM/2A rear sight base
Unknown # 9 - possibly County Machine & Tool	COUNTY MACH	M14E2 stock butt plate base
Unknown # 10	CPP	NM windage knob
Unknown # 11	CTX	magazine follower
Unknown # 12	italicized D	sear release
Unknown # 13	E. T. & D.	M14E2 stock hinged butt plate bracket assembly
Unknown # 14	GMI	NM windage knob
Unknown # 15	H A, H B	safety
Unknown # 16	HR C, HR F	hammer
Unknown # 17	HR E	safety
Unknown # 18	HR-N, OM-N	trigger housing
Unknown # 19	MHRA, MXR	safety
Unknown # 20	MKB	NM windage knob
Unknown # 21	N. E. INC.	M14E2 stock rubber butt pad and fore grip
Unknown # 22	raised letter O	safety
Unknown # 23	ROBER HT-B, ROBER HT-D	safety
Unknown # 24	S. T. & D.	M14E2 stock hinged butt plate bracket assembly
Unknown # 25	TOMCO	NM windage knob
Unknown # 26	VIZ/WD, WD	M8A1 scabbard

M14 RIFLE HISTORY AND DEVELOPMENT

Victory Plastics Company (Hudson, MA)	V.P. CO., 96126	M8A1 scabbard
Viz Manufacturing Co. (Philadelphia, PA)	VIZ, 41226	M8A1 scabbard
Watervliet Arsenal (Watervliet, NY)		bolt, cartridge clip guide
Wayne Novelty Corporation (Decatur, IN)		field maintenance gage case
Weather Manufacturing Co.	W inside a hexagon with an arrow through the base of the W	windage knob
Westinghouse Electric (East Springfield, MA)	W, <u>W</u>	magazine
Wico Electric Co. (West Springfield, MA)	WCE	elevation knob, windage knob
Worden Specialty & Machine Tool Co. (Plymouth, MI)	12408	combination tool
Wright Manufacturing Co. (Worcester, MA)	HRA-W, WRIGHT	windage knob, NM windage knob
Wyandotte Tool Co. (Wyandotte, MI)		rear sight cover
Yankee Hill Machine Company, Inc. (then Northampton, MA)	3D540	front sight and screw, bolt roller retaining ring pliers

Table 45: USGI M14 Rifle Items with Part Number Markings

USGI Part	Part Number
barrel, chromium plated	7790190
barrel, National Match, standard contour	7791362
barrel, National Match, medium weight contour	9345206
barrel, National Match, heavyweight contour	9349847
blank firing attachment, M12, third version	7793000
bolt subassembly without the roller	7790185
bolt subassembly with the roller	7790186
breech shield, M3	7790929
cleaning rod case	7267754
field maintenance gage case	7799702
gas cylinder	7790902
hammer	5546008
lubricant case	7790995
magazine filler (late version)	7791154
M14 stock hinge inlet protector	7791050
M14 stock hinge transition piece	7790914
M14E2 muzzle stabilizer	7791661
M14E2 muzzle stabilizer	11686521
M14E2 stock	5910438
M14E2 stock butt pad	7791673
M14E2 shoulder rest plate	7791683
M14E2 stock hinged butt plate bracket assembly	7792062
M2 bipod	7790688 or 7790833
M5 winter trigger	7790808
M6 bayonet left side grip	7267653
M6 bayonet right side grip	7267652
M76 grenade launcher latching handle assembly	7790900
M84 scope carrying case	7631596

M14 RIFLE HISTORY AND DEVELOPMENT

muzzle protector	7790232
operating rod	7267064
operating rod handle protector	7790231
rear sight base, NM 2/A	7791571
rear sight protector	7791358
receiver	7790189
stock, National Match walnut	7791174
stock, National Match oversized walnut	9352638
stock, National Match birch	11010263
stock subassembly, National Match walnut	11010282
trigger housing	7267030
XM21 ART scope carrying case	11729637

Spare M14 parts were packaged in the following manner:

Table 46: USGI M14 Rifle Parts and Accessories Packaging

USGI Part or Accessory	Manner of Packaging
AN/PVS-2 carrying case	one per transparent heat-sealed plastic bag
barrel	one per black cardboard tube
barrel cleaning rod patch tip	ten wrapped with vapor barrier paper
barrel reflector	twenty per cardboard box
bayonet	one per cardboard box inside sealed plastic bag
blank firing attachment and breech shield	one pair per cardboard box
bolt with roller	individually wrapped with vapor barrier paper or five individually wrapped inside a vapor barrier pack
bolt lock	one per heat-sealed pack
bolt lock pin	100 inside cheese cloth wrapper
bolt roller	five per heat-sealed pack
bolt roller retainer	five per heat-sealed pack
bolt roller retaining ring pliers	one inside foil wrap inside sealed clear plastic

LEE EMERSON

bore reflector	twenty per cardboard box
cartridge clip guide	one per heat-sealed pack
chamber brush	ten per cardboard box with each inside a cardboard sleeve
cleaning rod section	ten per package
combination tool	one per heat-sealed pack or cardboard box or black cardboard tube
connector assembly	one per sealed clear plastic pack
connector lock	five per heat-sealed pack
connector lock pin	one per transparent heat-sealed plastic bag (1990s production)
ejector assembly	two per heat-sealed pack
elevation knob and spindle	twenty per black cardboard tube
extractor spring and plunger	twenty per heat-sealed pack
firing pin	two per heat-sealed pack or cellophane bag, twenty twin packs per black cardboard tube
flash suppressor	one per black cardboard tube or heat sealable wrap
flash suppressor nut	ten per black cardboard tube
flash suppressor nut wrench	one per heat-sealed pack
front band	one per heat-sealed pack
front sight screw	100 per box
gas cylinder	two per black cardboard tube and five tubes per box or two inside cheese cloth wrapper
gas cylinder lock	one per heat-sealed pack
gas cylinder plug	five per heat-sealed pack with cardboard sleeve around the threads or five per heat-sealed pack wrapped in a single piece of vapor barrier paper
gas piston	one per heat-sealed pack or transparent heat-sealed plastic bag
lubricant case	72 per cardboard box
hammer spring	fifty per paper and / or plastic bag with oil sprayed on the parts (1981 production)

M14 RIFLE HISTORY AND DEVELOPMENT

M2 aiming device	one per cardboard box
M2 bipod modification kit	one kit wrapped in foil inside a sealed cheese cloth wrapper
M5 winter trigger (with or without safety)	one wrapped in foil paper inside cardboard tube inside heat-sealed pack
M6 bayonet	one per cardboard box inside transparent heat-sealed plastic bag
M6 bayonet grip, left or right	ten per cardboard box inside transparent heat-sealed plastic bag
M14A1 stock without hardware	ten per carton
M76 grenade launcher	one per cardboard tube
M151 vehicle mounting kit	one per cardboard box
M1907 small arms sling	one per heat-sealed transparent plastic bag
M35 truck mounting kit	one per cardboard box
magazine	one or four per heat-sealed pack or two per cardboard sleeve with outer plastic wrap (1960s production) and blue plastic bag (1990 and later production)
magazine latch	one per heat-sealed pack
operating rod	two per black cardboard tube (1960s production) and transparent heat-sealed plastic bag (1980s production)
operating rod guide	one per heat-sealed pack
operating rod spring	two per heat-sealed pack
operating rod spring guide	one per heat-sealed pack or ten per cardboard tube
rear sight aperture, National Match hooded	one per heat-sealed pack
rear sight base	one per heat-sealed pack
rear sight cover	twenty per black cardboard can
rear sight elevation knob and spindle	cardboard tube
rear sight windage knob	twenty per black cardboard tube
safety	one per heat-sealed pack

LEE EMERSON

safety spring	one per heat-sealed pack or 100 per box
selector spring	one per heat-sealed pack, twenty per black cardboard can
selector switch	one per heat-sealed pack
selector switch and spring	one set per cellophane bag (1960s production)
sling swivel, rear	one per heat-sealed pack
small arms sling, nylon	one per heat-sealed pack
spindle valve	ten per heat-sealed pack or 100 per cardboard can
stock, National Match (9352638)	one per transparent heat-sealed plastic bag (1980s production)
stock ferrule, National Match	one per heat-sealed pack (1990s production)
stock repair screws	twenty per transparent heat-sealed plastic bag
stock screw, wood, upper butt	one per heat-sealed pack
stock subassembly, National Match (11010282)	ten per cardboard box
swab holder	ten per envelope
trigger and sear assembly	two per heat-sealed pack
trigger guard	one per heat-sealed pack
trigger housing (with magazine catch, spring and pin)	one per heat-sealed pack

Table 47: Chinese M14 Rifle Part Markings

Chinese Rifle Part	Identifying Marks
barrel	KFS and CAI importer markings for Poly Technologies and CAI markings for some Norinco rifles, occasionally a single digit number or letter under the hand guard
bolt	may have numbers electro-penciled on the top or bottom
elevation knob	counterfeit W C E
flash suppressor	electro-penciled or stamped number
hammer	no markings
hand guard	silver painted bottom with counterfeit DT25
operating rod	may have electro-penciled numbers and the connector notch shape is different from USGI design

M14 RIFLE HISTORY AND DEVELOPMENT

trigger housing	five or six electropenciled numbers
windage knob	counterfeit W C E

The following *incomplete* timeline of contractors has been developed from observations made while opening new-in-wrap genuine USGI M14 magazines.

Table 48: Timeline of USGI Magazine Contractors

Production Year(s)	USGI M14 Magazine Manufacturer
1959	Union Hardware & Metal Company
1961	Atwood Vacuum, Brunswick Sports Products, Rochester Manufacturing (for Harrington & Richardson), Westinghouse Electric
1962	Borg-Warner Spring Division, Brunswick Sports Products, Olin-Mathieson Chemical Corporation, Westinghouse Electric
1963, 1965, 1966	Killeen Machine & Tool Co.
1967, 1968 and 1969	Borg-Warner Spring Division
1970	Killeen Machine & Tool Co.
1985, 1990	Check-Mate Industries
1996 and 1997	Check-Mate Industries
2004 through 2011	Check-Mate Industries

Much of the information in Appendix C was compiled by Thomas A. Buss in 1971. It is reproduced here with his permission. Mr. Buss was the M1A collector extraordinaire and a weekend military surplus parts dealer in the 1970s. His passion was the M14 rifle. At one time or another, he owned 165 stripped and barreled M1A receivers and complete rifles. His 117 page volume written from 1971 to 1977, *The M14 Collector's Manual*, the 1971 to 1976 Ohio Gun Collector Association newsletters, the mathematical graph of his personal M1A collection, and other personal notes provide precious insight into the early days of the commercial M14 and M14 parts collecting. In March 1973, he assembled the first known shortened barrel commercial M14 rifle. He regularly chatted with Melvin Smith

at gun shows. Mr. Buss interviewed Dave Mathewson and Winchester employees in 1971 to retrieve records and items left over from the T44 and M14 projects. He was given uninhibited access to all areas of the Springfield Armory Museum in 1975 and took notes and photographs of what he saw. Tom Buss was a significant resource for R. Blake Stevens in the writing of *U.S. Rifle M14 from John Garand to the M21*.

Thomas Buss married, had four children, and was later divorced. In the 1970s, he was employed as an engineer by Westinghouse Electric. He was involved in the design and technical support of the U. S. Navy S5W nuclear submarine propulsion plant main coolant pumps. In retirement, he lived in a beach front studio apartment in Madeira Beach, Florida. Living with heart disease and diabetes in his waning years, Mr. Buss was befriended by an advanced collector and significant contributor to this work, the late James Mason, who later passed in November 2009. A lucid encyclopedia of knowledge on the M14, Mr. Buss corresponded with and was interviewed by the author in 2006. To the end, he provided interesting and previously unknown information on the M14. Thomas A. Buss passed away quietly in June 2008 while visiting his sister in Orlando, Florida.

In the tables below, FSN means Federal Stock Number and NSN denotes National Stock Number.

Table 49: Barrel and Receiver Group Items

Description	Part Number	FSN or NSN	Comments
M14 Rifle	7267000	1005-00-283-7695 1005-00-770-3559	original drawing dated March 1955
M14 Rifle with equipment	8413866	1005-00-589-1271	equipment includes sling, four magazines, combination tool and cleaning kit
M14 JROTC		1005-00-283-7695	demilitarized for JROTC issue
M14 Rifle Group A (Port Security)		1005-LL-H18-7614 (NSN issued by the U. S. Navy)	U. S. Navy issue, double lugged receiver, fiberglass stock, heavyweight match grade barrel

M14 RIFLE HISTORY AND DEVELOPMENT

M14 Rifle Group B (Match Rifle)		1005-LL-H18-7615 (NSN issued by the U. S. Navy)	U. S. Navy issue, rear lugged receiver, wood or fiberglass stock, heavyweight match grade barrel
M14 Sniper Kit		1005-01-106-8975	U. S. Navy issue, includes sling, two magazines, scope and mount, cleaning kit, and aluminum carrying case
M14 M Rifle	7790485	1005-678-9829	issued with sling and magazine
M14 M Rifle with equipment	5910842	1005-00-678-9829	part number as listed in TM 9-1005-223-12P February 23, 1968, issued with sling and magazine
M14 NM Rifle	7790476 9386974	1005-00-678-9828	drawings originally dated April 1959 and September 1984 respectively
M14 NM Rifle with equipment	5910841	1005-00-678-9828	part number as listed in TM 9-1005-223-12P February 23, 1968, issued with sling and magazine
M14 NM Rifle with M84 scope		1005-937-8777	
M14A1 Rifle without bipod and sling	11010000		

LEE EMERSON

M14A1 Rifle with equipment	11010108	1005-00-072-5011	original drawing dated January 07, 1964, issued with sling, magazine and bipod
M14E2 Rifle with equipment	8427044		
M14 DMR Rifle	98003A0000	1005-01-458-6235	U. S. Marine Corps issue
M14 SMUD with equipment	EOD-M14	1005-01-255-3311	U. S. Air Force issue, issued with telescope sight, scope mount and padded carry case
M14	HGM14SEMI	1005-01-494-4169	U. S. Air Force issue, Honor Guard semi-automatic only
M14 SSR		1005-LL-L99-5690 (NSN issued by the U. S. Navy)	U. S. Navy issue
M14 T		1005-LL-L99-7853	U. S. Coast Guard
M21 Rifle with equipment	9386973 11838704	1005-00-179-0300	original drawing 9386973 dated September 1984, issued with telescope sight, scope mount, sling, magazine, and cleaning kit
M25 (Sniper Rifle M14)		1005-LL-L99-5690 (NSN issued by the U. S. Navy)	replaced by the Mk 11 Mod 0
M39 EMR		1005-01-553-5196	U. S. Marine Corps issue

M14 RIFLE HISTORY AND DEVELOPMENT

Mk 14 Mod 0		1005-01-525-7718 1005-01-531-7324	U. S. Navy issue
Mk 14 Mod 1		1005-LL-L99-7972	U. S. Navy issue
elevation knob assembly	7267099	1005-628-9047 5355-00-628-9047	calibratred in meters, original drawing dated July 1958
elevation knob lock washer	11010359 MS 35335-31		original drawing dated September 1965
elevation knob indexing dog assembly	11010362		original drawing dated September 1965
elevation knob screw blank	7267096		original drawing dated July 1958
elevation knob indexing dog	7267097		original drawing dated July 1958
elevation knob	7267098		original drawing dated July 1958
elevation pinion assembly	11010363	1005-999-3399 5355-00-999-3399	original drawing dated September 1965
windage knob assembly	7312737	1005-731-2737 5355-00-731-2737	original drawing dated December 1944
windage knob nut	7312726		original drawing dated December 1944
windage knob nut lock	7312731		original drawing dated December 1944

LEE EMERSON

windage knob spring	7312732		original drawing dated December 1944
windage knob assembly, National Match	7790386	1005-649-9275 5355-00-649-9275	original drawing dated November 1958
windage knob, National Match	7790358		original drawing dated November 1958
rear sight aperture	6008868	1005-00-600-8868	original drawing dated August 1937
rear sight aperture, ghost ring			Mk 14 Mod 0 and 1, M14 T, 0.125 ", XS Sight Systems
rear sight base	5546001	1005-00-554-6001	original drawing dated August 1937
rear sight base, National Match	7791341	1005-875-6281	marked NM/2, undercut for hooded aperture
rear sight base, National Match	7791571	1005-754-6799 5340-00-754-6799	marked NM/2A, original drawing dated November 1963
rear sight cover	6008872	1005-00-600-8872	original drawing dated August 1937
rear sight eyepiece, National Match	7791131		marked 595, 0.0595 " peep hole original drawing dated December 1961
rear sight eyepiece assembly, National Match	7791132		original drawing dated December 1961

M14 RIFLE HISTORY AND DEVELOPMENT

rear sight aperture assembly, National Match	7791133	1005-864-2926 1005-00-864-2926	0.0595 " peep hole, original drawing dated December 1961
rear sight eyepiece, National Match	7791281		marked 520, 0.0520 " peep hole, alternate design
rear sight aperture assembly, National Match	7791282	1005-864-2928 1005-00-864-2928	0.0520 " peep hole, alternate design
rear sight aperture, National Match	7791134		original drawing dated December 1961
rear sight eyepiece spring, National Match	7791135		two coil springs, original drawing dated December 1961
rear sight eyepiece ball bearing, National Match	MS 19060-1		two required
rear sight eyepiece spring, National Match	7791136		one cone disk spring, original drawing dated December 1961
rear sight eyepiece retaining ring, National Match	MS 16624-18		
rear sight assembly, NM	2061		M21A5, Smith Enterprise, Inc.
selector shaft pin	96906-16562-107 MS 16562-107	5315-051-6891 5315-00-051-6891	interchangeable with the spindle valve pin and connector pin, 5/64 " diameter x 3/8 " long

LEE EMERSON

selector lock	7267172	1005-587-8420 1005-00-587-8420	M14, M14 M, M14 NM, M21, M25, Mk 14 Mod 1 and 2, M14 DMR, M39 EMR, M14 EBR-RI, M14 EBR-RI NM, original drawing dated October 1954
selector switch	7267071	1005-587-8408 3040-00-587-8408	M14 (optional), M14A1, Mk 14 Mod 0, M14 T, original drawing dated October 1954
selector shaft spring	7267081	1005-587-8415 5360-00-587-8415	standard for M14A1, optional for M14 in lieu of selector lock, original drawing dated September 1954
selector shaft	7267072	1005-587-8409 3040-00-587-8409	original drawing dated October 1954
sear release	7790192	1005-628-9053 1005-00-628-9053	original drawing dated July 1958
gas cylinder plug	7267053	1005-00-587-8400	original drawing dated October 1954
gas cylinder plug	2076		USAF Mk 14 Mod 0, Mk 14 Mod 2, M14 EBR-RI NM, Smith Enterprise, Inc.
gas cylinder piston	7267047	1005-00-587-8398	original drawing dated October 1954

M14 RIFLE HISTORY AND DEVELOPMENT

gas cylinder piston	2075		M21A5, USAF Mk 14 Mod 0, Mk 14 Mod 2, M14 EBR-RI NM, Smith Enterprise, Inc.
gas cylinder piston, National Match	9352724		gas piston with axial groove, original drawing dated June 1982
flash suppressor setscrew	7790300 MS 51976-16	5305-042-6426 5305-01-221-3230	late version, full dog point, make from 6-40 x 0.25 " setscrew, tip is 0.092 " diameter x 0.070 " long, original drawing dated July 1958
flash suppressor nut	7267039	1005-00-587-8394	original drawing dated November 1954
flash hider	FH762KM14		Mk 14 Mod 1, Surefire, LLC
flash suppressor	7267088		early version
flash suppressor	7791053	1005-545-1573 1005-00-545-1573	late version, original drawing dated September 1960
flash suppressor, National Match	9352718	1005-01-267-2093	M14 NM, M21, M25, M14 EBR-RI, M14 EBRRRI NM, original drawing dated June 1982
flash suppressor, M14 DMR	98003A1001	1005-01-471-3532	M14 DMR, M39 EMR

LEE EMERSON

flash hider	2000V		M21A5, Mk 14 Mod 0 and 2, Smith Enterprise, Inc.
muzzle brake	2001		M14 T, Smith Enterprise, Inc.
front sight	11-2166-580-1		Mk 14 Mod 0 and 1, M14 T, XS Sight Systems
front sight, National Match	7791122	1005-00-980-5203	M14 NM, M21, M14 DMR, M39 EMR, marked NM 062, original drawing dated November 1961
front sight, standard	7790233		early version
front sight, standard	7791445	1005-084-8435 1005-00-084-8435	late version, original drawing dated October 1962
front sight screw	96906-35460-3 MS 35460-3	5305-655-9483 5305-00-655-9483	early version, # 6 - 40 NF x ½ " long socket cap screw, 3/32 " socket, phosphate coating
front sight screw	11010298	5305-00-921-6155	late version, # 6 - 40 NF x ½ " long socket cap screw, 7/64 " socket, phosphate coating, original drawing dated November 1964

M14 RIFLE HISTORY AND DEVELOPMENT

front sight screw	MS 16998-11	5305-983-6650	late version, # 6 - 40 NF x ½ " long socket cap screw, 7/64 " socket, cadmium plated
gas cylinder lock	7790188	1005-00-628-9051	original drawing dated July 1958
gas cylinder lock	2011		M21A5, Smith Enterprise, Inc.
gas cylinder lock	2013		Mk 14 Mod 0 and 1, Smith Enterprise, Inc.
gas cylinder	7267013		early version with no lip
gas cylinder	7790902	1005-790-8766 1005-00-790-8766	late version with lip, original drawing dated March 1960
gas cylinder	2071		M21A5, USAF Mk 14 Mod 0, Mk 14 Mod 2, M14 EBR-RI NM, Smith Enterprise, Inc.
gas cylinder and band assembly, National Match	9352725		M14 NM, original drawing dated June 1982
gas cylinder and band assembly	98003A1002	1005-01-472-3924	M14 DMR, M39 EMR
spindle valve pin	96906-16562-107 MS 16562-107	5315-051-6891 5315-00-051-6891	interchangeable with the selector shaft pin and connector pin, 5/64 " diameter x 3/8 " long
spindle valve pin	MS 171401		M14 DMR

LEE EMERSON

spindle valve (gas cutoff valve)	7267604	1005-00-587-8421	original drawing dated December 1954
spindle valve spring	7267605	1005-587-8422 5360-00-587-8422	original drawing dated December 1954
front band	7267001	1005-587-8375 1005-00-587-8375	original drawing dated September 1954
operating rod guide pin	MS 16562-130		first version
operating rod guide pin	96906-51923-465 MS 51923-465	5315-00-923-9440	1/8 " diameter x 3/4 " long
operating rod guide pin	96906-51923-291 MS 51923-291	5315-00-993-3247	1/8 " diameter x 3/4 " long
operating rod guide	7267025	1005-587-8385 1005-00-587-8385	original drawing dated October 1954
operating rod guide, National Match	9349846	1005-01-258-7919	original drawing dated March 1982
bolt lock pin	96906-16562-124 MS 16562-124	5315-00-839-0897	3/32 " diameter x 1 " long
bolt lock	7267034	1005-00-587-8390	original drawing dated December 1954
extended bolt lock	2003		M21A5, Mk 14 Mod 0, 1 and 2, M14 T, Smith Enterprise, Inc.
bolt lock spring	7267074	1005-587-8411 5360-00-587-8411	original drawing dated September 1954

M14 RIFLE HISTORY AND DEVELOPMENT

connector lock pin	7267042	5315-00-587-8396	original drawing dated August 1954
connector lock	7267035	5315-00-587-8391	original drawing dated September 1954
cartridge clip guide pin	96906-16562-120 MS 16562-120	5315-051-8636 5315-00-051-8636 5315-00-058-6065	3/32 " diameter x 9/16 " long
cartridge clip guide	7790184	1005-628-9049 1005-00-628-9049	original drawing dated July 1958
barrel, chromium plated	7790190	1005-628-9052 1005-00-628-9052	original drawing dated July 1958
barrel and receiver assembly	7790191		chromium plated barrel, original drawing dated July 1958
barrel and receiver assembly, National Match	9352636		original drawing dated May 1982
receiver lug	9352637	1005-01-267-2167	original drawing dated January 1986
barrel, National Match	7791173		chromium plated standard contour, original drawing dated December 1961
barrel, National Match,	7791362	1005-00-018-3255	non-plated standard contour, original drawing dated December 1961

LEE EMERSON

barrel and receiver assembly, National Match	7791363		receiver with non-plated standard contour barrel
barrel, National Match	9345206	1005-01-120-4513	non-plated medium weight contour, original drawing dated June 1981
barrel, National Match	9349847		non-plated heavyweight contour, original drawing dated March 1982
barrel assembly, National Match	9362529	1005-01-272-0970	non-plated heavyweight contour barrel with operating rod guide, original drawing dated March 1982
barrel, M14 DMR	98003A1220	1005-01-522-9955	M14 DMR, non-plated medium weight contour barrel
barrel, M39 EMR	98003A1220	1005-01-556-7367	M39 EMR, non-plated medium weight contour barrel
receiver	7790189	1005-628-9052	original drawing dated July 1958

Table 50: Bolt Assembly Items

Description	Part Number	FSN or NSN	Comments
bolt	7790185		original drawing dated July 1958
bolt with roller	7790186	1005-00-628-9050	original drawing dated July 1958
bolt assembly	7790187		original drawing dated July 1958
bolt roller	7267065	1005-00-587-8405	original drawing dated September 1954
bolt roller retaining ring (bolt roller retainer)	7267059	1005-00-587-8402	original drawing dated September 1954
extractor, early	5546003	1005-554-6003 1005-00-554-6003	M1/early M14 extractor
extractor, early modified	5546003	1005-554-6003 1005-00-554-6003	early M14 extractor with field modification (1/64 " of the bottom corner of the claw filed away)
extractor, late	7791578	1005-953-9504 1005-00-953-9504	late M14 extractor, original drawing dated October 1954, design changed to late style in March 1963
extractor, M14 DMR	98003A1231	1005-01-472-3098	M14 DMR
extractor spring	6008886	5360-00-600-8886	original drawing dated August 1937

LEE EMERSON

extractor spring plunger	5013671	1005-00-501-3671	original drawing dated August 1937
extractor spring with plunger	6008618	1005-600-8618 5340-00-600-8618	original drawing dated August 1937
ejector	7267014		original drawing dated June 1954
ejector spring	7267959		original drawing dated September 1955
ejector with spring	7267015	1005-00-587-8381	original drawing dated June 1954
firing pin	7267043	1005-587-8397	first version, non-plated, original drawing dated August 1954
firing pin	7791417	1005-962-8344 1005-00-962-8344	second version, chromium plated tip, original drawing dated April 1962
firing pin	11686413	1005-00-921-5248	third version, 100 % chromium plated, original drawing dated October 1965

Table 51: Operating Rod Group Items

Description	Part Number	FSN or NSN	Comments
connector assembly	7267012		early style with slot for the connector lock
connector assembly	7790424	1005-678-9824 3040-00-678-9824	original drawing dated April 1959
connector assembly	98003A1004	1005-01-472-3121	M14 DMR
connector pin	96906-16562-107 MS 16562-107	5315-051-6891 5315-00-051-6891	interchangeable with spindle valve pin and selector shaft pin, 5/64 " diameter x 3/8 " long
connector plunger	7790426	1005-678-9826 5340-00-678-9826	original drawing dated April 1959
connector spring	7790427	1005-678-9827 5340-00-678-9827	original drawing dated April 1959
connector body	7790425	1005-678-9825	original drawing dated April 1959
operating rod spring guide	7267027	1005-00-587-8386	original drawing dated October 1954
operating rod spring guide, National Match	9352726		original drawing dated June 1982
operating rod spring guide	98003A1005	1005-01-472-3905	M14 DMR, M39 EMR
operating rod spring	7267079	1005-587-8413 5360-00-587-8413	original drawing dated September 1954

LEE EMERSON

operating rod spring			USAF Mk 14 Mod 0, chromium silicon alloy steel, Smith Enterprise, Inc.
operating rod	7267064	1005-00-587-8404	original drawing dated September 1954

Table 52: Firing Mechanism Items

Description	Part Number	FSN or NSN	Comments
complete firing mechanism	7790195		original drawing dated July 1958
complete firing mechanism, National Match	9354354		original drawing dated June 1982
sear	7267070		original drawing dated August 1954
sear, National Match	5546016		semi-automatic fire only, original drawing dated August 1937
trigger	5546020		original drawing dated August 1937
trigger pin	5013669	5315-501-3669 5315-00-501-3669	early version
trigger pin	7791367	5315-00-819-4501	late version, original drawing dated April 1962
sear pin	5013673		original drawing dated August 1937

M14 RIFLE HISTORY AND DEVELOPMENT

trigger and sear assembly	7267090	1005-587-8419 1005-00-587-8419	original drawing dated September 1954
trigger and sear assembly	5546026	1005-00-554-6026	M14 NM and M21, original drawing dated August 1937
trigger and sear assembly	98003A3001	1005-01-471-1810	M14 DMR
hammer spring housing	6008883	1005-00-600-8883	original drawing dated August 1937
hammer spring housing, National Match	8448292		original drawing dated May 1969
hammer spring	6008887	5360-00-600-8887	original drawing dated August 1937
hammer spring plunger	6008880	5340-00-600-8880	original drawing dated August 1937
hammer spring plunger, National Match	8448692	1005-01-154-8337	original drawing dated March 1971
hammer pin	5013668	5315-00-501-3668	0.187 " diameter x 3/4 " long under head, original drawing dated August 1937
hammer pin, hammer spring, trigger pin, connector lock	2060		M21A5, USAF Mk 14 Mod 0, Smith Enterprise, Inc.
hammer	5546008	1005-00-554-6008	original drawing dated August 1937
hammer, National Match	8448293		original drawing dated May 1969

LEE EMERSON

safety	5546015	1005-00-554-6015	original drawing dated April 1937
safety spring	7267080	5360-00-587-8414	M1 rifle clip ejector can be cut to 1.1 " length as an emergency repair, original drawing dated September 1954
trigger guard	7790194	1005-628-9054	early style with hammer stop pin
trigger guard	7790990	1005-00-587-6988	late style with bent tab, produced from May 1962 onward, original drawing dated September 1960
trigger housing assembly	7790196 8448290	1005-00-628-9055	original drawings dated July 1958 and May 1969 respectively
trigger housing	7267030		original drawing dated October 1954
magazine latch pin	MS 9047-102		early version
magazine latch pin	7791418	5315-00-994-4242	late version, original drawing dated August 1962, 0.121 " diameter x 0.640 " long
magazine latch	7267032	1005-00-587-8389	original drawing dated August 1954
magazine latch spring	7267041	1005-00-587-8395	original drawing dated August 1964

Table 53: M14 Stock and Hand Guard Items

Description	Part Number	FSN or NSN	Comments
butt stock sling swivel	6008889	1005-600-8889 1005-00-600-8889	original drawing dated August 1937
lower butt screw	6008881	5305-600-8881 5305-00-600-8881	slot drive, 0.216 " diameter x 28 NF-2A x 3.171 " long, original drawing dated August 1937
upper butt screw	6146873	1005-614-6873 5305-00-614-6873	M14A1 and wood stock with M1 rifle butt plate, original drawing dated March 1935
upper butt screw	7791036	1005-474-2754 5305-00-474-2754	0.212 " diameter, 10 threads per inch, 1.140 " grip length, 2.136 " long, for wood stock with hinged butt plate, original drawing dated August 1960
upper butt screw	7791267	5305-999-1875 5305-00-999-1875	for production reinforced fiberglass stock, original drawing dated July 1965
upper butt screw nut retainer	11010414	5340-999-1864 5340-00-999-1864	for production reinforced fiberglass stock, original drawing dated July 1965

LEE EMERSON

upper butt screw nut (10-32 threads)	7791339	5310-999-1891 5310-00-999-1891	for production reinforced fiberglass stock, 10 - 32 square nut, original drawing dated July 1965
wood stock that fits the M1 rifle butt plate	7267083 per Picatinny Arsenal CMT IG Number 38 dated 2 January 1958		T44E4 bare walnut stock
wood stock that fits the M1 rifle butt plate	7267084 per Picatinny Arsenal CMT IG Number 38 dated 2 January 1958		T44E4 walnut stock with butt plate, ferrule, front and rear sling swivels, stock liner and liner screws
wood stock assembly	7790702		M14 stock includes the front and rear sling swivels, stock liner, liner screws, ferrule and butt plate assembly
wood stock subassembly	7790810		M14 stock subassembly for 7790702, includes stock, ferrule, front sling swivel, stock liner and liner screws
wood stock, National Match	7791174		M14 NM bare stock for 7791175 and 11010282

M14 RIFLE HISTORY AND DEVELOPMENT

wood stock assembly, National Match	7791175		M14 NM stock includes front and rear sling swivels, ferrule, stock liner, liner screws and butt plate assembly, original drawing dated December 1961
wood stock subassembly, National Match	7791280		M14 NM stock subassembly for 7791175, includes front sling swivel, ferrule, stock liner and liner screws, original drawing dated December 1961
wood stock, National Match	9352638	1005-01-233-8635	M14 NM bare stock for 9392337, routed for bedding, original drawing dated May 1982
wood stock subassembly, National Match	9381706		M14 NM stock subassembly for 9392337 with front sling swivel, ferrule, and routed for bedding, original drawing dated May 1984
wood stock assembly, National Match	9392337		M14 NM stock with front and rear sling swivels, ferrule, butt plate assembly, routing and bedding, original drawing dated May 1984

LEE EMERSON

wood stock	11010262		M14 stock includes ferrule, original drawing dated June 1964
wood stock	11010263	1005-754-6462	M14 and M14 NM bare stock, original drawing dated June 1964
wood stock assembly, National Match	11010281		M14 NM stock includes front and rear sling swivels, ferrule, stock liner, liner screws, butt plate assembly, routing and bedding, original drawing dated June 1964
wood stock subassembly, National Match	11010282	1005-00-912-3711	M14 NM stock subassembly includes stock, ferrule, stock liner, liner screws and routing, replaced 7791175, original drawing dated June 1964
stock liner	7267033		early version
stock liner screw	7267063		two per wood stock, 10-32 threads, 7/16 " overall length
stock ferrule	7267017		M14 and M14A1, original drawing dated October 1954
stock ferrule	9352720	1005-01-271-1027	M14 NM stock 9392337

M14 RIFLE HISTORY AND DEVELOPMENT

stock rivet, tubular oval head	7790473 MS 16535-302		M14 wood stock, original drawing dated September 1959
stock rivet, tubular oval head	11010260 MS 16535-307	5320-01-272-5023	M14 reinforced fiberglass stock, original drawing dated June 1964
stock rivet, solid, belt	MS 35745-18		M14 NM and M21
stock rivet burr	7790474	1005-072-5381 5310-00-072-5381	original drawing dated September 1959
sling swivel bracket	7267007		original drawing dated September 1954
sling swivel loop	7267037		original drawing dated September 1954
sling swivel loop assembly	7267089	1005-00-919-7278	M14, original drawing dated September 1954
sling swivel loop assembly	9352716	1005-01-271-1029	M14 NM, original drawing dated June 1982
pin, straight, knurled	11010261		M14 reinforced fiberglass stock pin inside the butt stock, original drawing dated July 1965

LEE EMERSON

screw retaining plate	7791340		reinforced fiberglass stock plate inside the grip, original drawing dated July 1965
production reinforced fiberglass stock	11686426		original drawing dated December 1965
production reinforced fiberglass stock subassembly	11686427		stock with ferrule, original drawing dated December 1965
production reinforced fiberglass stock assembly	11686428		stock includes the butt plate, both sling swivels and ferrule, original drawing dated December 1965
production reinforced fiberglass stock subassembly	5910348	1005-00-999-1871	subassembly consists of stock, upper butt screw, nut retainer and nut
hand guard band	6008870		also known as hand guard clip, original drawing dated August 1937
hand guard assembly	7267021	1005-587-8382	walnut hand guard with metal clip
hand guard assembly	7790689	1005-690-4068	slotted fiberglass hand guard with metal clip
hand guard	7791285		solid fiberglass hand guard, original drawing dated October 1961

M14 RIFLE HISTORY AND DEVELOPMENT

hand guard, National Match	9352722		M14 NM, original drawing dated June 1982
hand guard assembly	7791286	1005-856-2108 1005-00-856-2108	solid fiberglass hand guard with metal clip, original drawing dated October 1961
hand guard assembly, National Match	9352721		M14 NM, original drawing dated June 1982
hand guard assembly, M14 DMR	98003A1008	1005-01-472-3209	

Table 54: M14 Stock Butt Plate Assembly Items

Description	Part Number	FSN or NSN	Comments
M1 butt plate assembly	5564277	1005-556-4277	for early M14 stock with M1 butt plate
M1 butt plate hinge pin	5152865	5315-515-2865	interchangeable with M14 stock butt plate door pin, 0.126 " diameter x 1.00 " long, original drawing dated March 1940
M1 butt plate plunger	5152864	1005-515-2864	for early M14 stock with M1 butt plate
M1 butt plate catch spring	5152863	1005-515-2863	for early M14 stock with M1 butt plate
M1 butt plate door	6147465	1005-614-7465	for early M14 stock with M1 butt plate

LEE EMERSON

M1 butt plate	5564283	1005-556-4283	for early M14 stock with M1 butt plate
M14 butt plate assembly	7790686	1005-690-4067 1005-00-690-4067	original drawing dated September 1959
M14 butt plate hinge pin	7790695	1005-981-1254 5310-00-981-1254	original drawing dated September 1959
M14 butt plate stop pin	7790695	1005-981-1254 1005-00-981-1254	original drawing dated September 1959
M14 butt plate	7790696		original drawing dated September 1959
M14 butt plate rest	7790697	1005-981-1255 1005-00-981-1255	also known as butt plate flapper, original drawing dated September 1959
M14 butt plate ball bearing	96906-19059-49 MS 19059-49 96906-19059-88 MS 19059-88	3110-100-6151 3110-00-100-6151	
M14 butt plate hinge spring	5013747	1005-501-3747 5360-00-501-3747	original drawing dated February 1935
M14 butt plate door pin	96906-16562-98 MS 16562-98	5315-597-5086 5315-00-597-5086	1/16 " diameter x 3/8 " long
M14 butt plate door catch	7790693	1005-981-1252 1005-00-981-1252	original drawing dated September 1959
M14 butt plate door catch spring	7790699	1005-981-1256 5360-00-981-1256	original drawing dated September 1959

M14 RIFLE HISTORY AND DEVELOPMENT

M14 butt plate catch pin	5152865	5315-515-2865 5315-00-515-2865	original drawing dated March 1940
M14 butt plate door plunger	7790698		original drawing dated September 1959
M14 butt plate door	7790692		original drawing dated September 1959
M14 hinge block	7790691		original drawing dated September 1959
M14 butt plate assembly	7790700		original drawing dated September 1959
M14 hinge transition piece	7790914		black soft rubber filler block that allows use of the M1 rifle butt plate on a standard M14 stock, not the same as the hinge inlet protector part number 7791050

Table 55: M14E2/M14A1 Stock Assembly Items

Description	Part Number	FSN or NSN	Comments
stock assembly	7791671		M14E2
stock assembly	11686528		M14A1, original drawing dated April 1966
stock	11686526		M14A1, original drawing dated April 1966

LEE EMERSON

stock liner plate	7790200		
stock liner	7790202		
stock liner assembly	7790201		late version
stock liner screw	7267063		two required, 10-32 threads, 7/16 " overall length
recoil pad plug	7791674	1005-072-5386 1005-00-072-5386	two required, lusterless black color, original drawing dated September 1963
lower recoil pad screw	7791676	1005-072-5388 5305-00-072-5388	original drawing dated September 1963
butt stock sling swivel bushing	11010047	1005-072-5379 5325-00-072-5379	original drawing dated October 1963
butt stock sling swivel	11010046	1005-072-5378	original drawing dated October 1963
upper recoil pad screw	7791677	1005-072-5389 5305-00-072-5389	original drawing dated September 1963
recoil pad	7791673	1005-072-5385 1005-00-072-5385	early version made of natural rubber, late version made of synthetic rubber to minimize deterioration from oil and cleaning liquids, lusterless black color, original drawing dated September 1963

M14 RIFLE HISTORY AND DEVELOPMENT

butt plate bracket screw	6146873	1005-614-6873 5305-00-614-6873	two required, original drawing dated March 1935
butt plate flapper assembly	7791678	1005-072-5390 1005-00-072-5390	original drawing dated September 1963
butt plate flapper pin	7791682	1005-016-2624 5315-00-016-2624	original drawing dated September 1963
butt plate flapper (shoulder rest plate)	7791683		original drawing dated September 1963
butt plate bracket	7791680		
butt plate bracket pin	7791681		
butt plate bracket assembly	7792062		original drawing dated September 1963
hand grip rubber bumper	11010048	1005-072-5380	for early stock burr version, four required
hand grip rubber bumper or grommet	11686524	5325-904-9303 5340-00-904-9303	for late stock burr version, four required, original drawing dated April 1966
hand grip screw	7791675	1005-072-5380	for early stock burr version, two required
hand grip screw	11686523	5305-956-3401 5305-00-956-3401	for late stock burr version, two required, original drawing dated April 1966

LEE EMERSON

hand grip lock washer	96906-35335-32 MS 35335-32 or MS 35335-46	5310-596-7691 5310-00-596-7691	for early stock burr version, two required, No. 10 screw size
hand grip lock washer	96906-35336-21 MS 35336-21	5310-194-9209 5310-00-194-9209	for late stock version burr, two required
stock assembly burr	7790474	1005-072-5381 5310-00-072-5381	early stock version burr, two required, original drawing dated September 1959
stock assembly burr	11686522	1005-951-3254 1005-00-951-3254	late stock version burr (backing plate), one required, original drawing dated April 1966
hand grip assembly	11010044	1005-072-5377 1005-00-072-5377	original drawing dated October 1963
hand grip latch assembly	11010045		
upper hand grip pin	96906-39086-205 MS 39086-205 or MS 16562-143	5315-00-836-0643 5315-00-846-5998	3/16 " diameter x 7/8 " long
hand grip subassembly	7791672	1005-016-2623	original drawing dated October 1963
lower hand grip pin	96906-39086-211 MS 39086-211 or MS 16562-147	5315-269-4080 5315-00-269-4080	0.187 " diameter x 1.750 " long
hand grip locking pin	11010002		

M14 RIFLE HISTORY AND DEVELOPMENT

hand grip locking spring	11010003		nine coils
pin for hand grip locking pin and spring	MS 16562-95 or MS 39086-50	5315-00-845-7021	1/16 " diameter x 3/16 " long
hand grip body	11010050		rubber coated aluminum
hand grip	11010001		original drawing dated October 1963
front sling swivel pin	96906-39086-202 MS 39086-202 or MS 51923-252	5315-050-1233 5315-00-050-1233	3/16 " diameter x 1/2 " long
front sling swivel	6008890	1005-600-8890 1005-00-600-8890	original drawing dated August 1937
hand grip block	11010004	1005-016-2621 1005-00-016-2621	original drawing dated October 1963
stock subassembly	7791679	1005-072-5391	M14E2 stock subassembly includes stock, stock liner and liner screws
stock subassembly	11686527		M14A1 stock subassembly includes stock, ferrule, stock liner and liner screws, original drawing dated April 1966
stock	5910438	1005-999-4200 1005-00-999-4200	M14E2 stock

LEE EMERSON

M14E2/M14A1 sling	11010038	1005-072-5376 1005-00-072-5376	64.5 " long, original drawing dated October 1963, essentially a M1918 Browning Automatic Rifle sling with an extra standard sling hook
M14E2/M14A1 sling keeper assembly	8436759	5340-01-006-5806	
M14E2/M14A1 sling assembly	7149752		
M14E2/M14A1 hook assembly	7136183		two required

Table 56: M14 DMR Stock Assembly Items

Description	Part Number	FSN or NSN	Comments
cheek rest, adjustable	98003A2104	1005-01-470-6741	
stock	98003A2101		McMillan Fiberglass Stocks M2A model
escutcheon	98003A2002	1005-01-470-9632	
stock ferrule	9352720	1005-01-271-1027	
bipod mounting stud	98003A2003	5307-01-472-3395	
front sling swivel screw	98003A2004	5305-01-472-3539	two required
front sling swivel, M14 DMR	98003A2001	1005-01-472-4551	

M14 RIFLE HISTORY AND DEVELOPMENT

rear sling swivel	6008889	1005-00-600-8889	
cheek rest screw	98003A2105	5305-01-472-3465	two required
rear sling swivel screw	98003A2005	5305-01-533-0561	
butt pad spacing (butt pad spacer)	98003A2103	1005-01-470-7112	two available, ½ "
butt pad spacing (butt pad spacer)	98003A2107	1005-01-470-7122	two available, ¼ "
butt pad	98003A2102	1005-01-470-7096	
butt plate screw (screw, machine, rear butt plate)	98003A2106	5305-01-470-7017	two required

Table 57: Sage International Stock Assembly Items

Description	Part Number	FSN or NSN	Comments
stock assembly	B009039 or M14ALCS		butt stock with rails, pad and cheek rest, Mk 14 Mod 0, M39 EMR, M14 EBR-RI, M14 T
stock assembly	B009044 or M14ALCS/CV		receiver extension tube, Mk 14 Mod 1
stock assembly	M14ALCS/CVFS		fixed synthetic butt stock, California compliant
stock assembly	M14ALCS/CV16FS		fixed synthetic M16 style butt stock
stock assembly	M14ALCS/PMRI		M14 EBR-RI NM

LEE EMERSON

stock assembly	M14ALCS-HB		heavyweight barrel
stock assembly	M14ALCS/CV-HB		heavyweight barrel
stock assembly	M14ALCS/CVFS-HB		heavyweight barrel
stock assembly	M14ALCS/PMRI-HB		heavyweight barrel, Mk 14 Mod 2
butt stock assembly	M14ALCS-BS		M14ALCS
butt stock assembly	M14ALCS/CV-BS		M14ALCS/CV
butt stock assembly	M14ALCS/CVFS-BS		M14ALCS/CVFS
butt stock assembly	M14ALCS/PMRI-BS		M14ALCS/PMRI
butt stock assembly	CTR FDE		Mk 14 Mod 1, Magpul
recoil pad	90217		Speedfeed, not compatible with part number 90995 or M14BEK
stock chassis	90900	1005-01-556-3221	
top cover	90901	1005-01-557-1574	standard profile barrel
butt stock strut assembly	90903	1005-01-576-2489	M14ALCS, Mk 14 Mod 0
butt stock main body assembly	90904		M14ALCS

M14 RIFLE HISTORY AND DEVELOPMENT

pistol grip	90905	1005-01-556-3029	Mk 14 Mod 0, M39 EMR, M14 T, hard plastic, discontinued by Sep 2010
vertical grip assembly	90906 or M14VFG	1005-01-593-1008	Mk 14 Mod 0, M14 EBR-RI, M14 T
vertical grip assembly	BGV-MK46 FDE		Mk 14 Mod 1, TangoDown
fore grip (hand guard)	90907	1005-01-556-6680	single piece, black or tan
cheek rest	90908	1005-01-556-2248	
cheek rest	PTS CTR FDE		Mk 14 Mod 1, Magpul, 1.25 " riser
elevator cheek rest support	90909		
recoil pad	90910	1005-01-556-2252	Pachmayr
butt plate spacer	90911	1005-01-556-2241	M39 EMR
elevator cheek rest lock wrench	90912	1005-01-556-2233	
chassis sling attachment plate	90913	1005-01-556-3209	
sling mount	RMFL-125	1005-01-589-7062	Mk 14 Mod 2, Blue Force Gear, two required
chassis operating rod guide	90914	1005-01-556-3234	early version has one dot on face - NF thread screws late version has two dots on face - NC thread screws

LEE EMERSON

bottom rail	90915	1005-01-556-3241	
left side rail	90916	1005-01-556-4442	
right side rail	90917	1005-01-556-4682	
rail cover	4373CB		Mk 14 Mod 0, M14 T, quantity of two, Falcon Industries
rail cover	BP-4 FDE		Mk 14 Mod 1, quantity of two, TangoDown
rail cover	BP-4K 2PANEL FDE		Mk 14 Mod 1, TangoDown
rail cover	4373BK		Mk 14 Mod 2, quantity of two, Falcon Industries
stock lock bar return spring	90918	5360-01-556-3082	
pistol grip mounting screw	90919	5305-01-556-3212	
pistol grip mounting screw lock washer	90920	5310-01-556-3215	
pistol grip mounting screw flat washer	90921	5310-01-556-7123	
cheek rest mounting screw	90922	5305-01-556-2601	two required
recoil pad mounting screw	90923	5305-01-556-2386	two required
elevator lock screw	90924	5305-01-556-2388	

M14 RIFLE HISTORY AND DEVELOPMENT

elevator lock nut	90925	5310-01-556-2588	
butt stock strut stop screw	90926	5305-01-556-2598	two required
butt stock secondary mounting screw	90927	5305-01-556-7027	
butt stock secondary mounting screw flat washer	90928	5310-01-556-7095	
butt stock primary mounting screw	90929	5305-01-556-7094	
butt stock primary mounting screw flat washer	90930	5310-01-556-7097	
operating rod guide screw	90931		three required, early version - ¼ " x 28 x ½ " NF button head late version - ¼ " x 20 x ½ " NC button head
top cover attachment screw	90932	5305-01-556-6993	six required on standard profile top covers, 10-24 x ½ " socket head
bottom rail screw	90933	5305-01-556-7017	four required
side rail screw	90934	5305-01-556-7022	four required
front sling attachment	90935	1005-01-556-7292	
front sling attachment back plate	90936	1005-01-556-6839	

LEE EMERSON

screw	90937	5305-01-556-6992	two required
barrel tensioning screw	90938		¼ " x 20 x ½ " flat point
barrel tensioning screw lock screw	90939		8-32 x ¼ " cut point
fore grip screw (hand guard screw)	90940	5305-01-556-7020	two required, ¼ " x 20 x ½ " NC button head
butt stock butt plate weldment assembly	90941	5340-01-556-2191	
butt stock strut rod	90942	1005-01-556-2199	two required
butt stock strut mounting screw	90943	5305-01-556-2592	four required
butt stock sling attaching wire	90944	1005-01-556-2104	
collapsible butt stock main body weldment	90945	1005-01-556-2615	
lock bar	90946	1005-01-556-3009	
lock bar actuating bolt	90947	1005-01-556-2946	
lock bar thumb release lever	90948	1005-01-556-2955	
lock bar return spring retaining cup	90949	1005-01-556-3016	
lock bar thumb release lever tension spring	90950	5360-01-556-3076	

M14 RIFLE HISTORY AND DEVELOPMENT

vertical grip body	90951		
vertical grip tensioning knob assembly with attaching rod	90952		
vertical grip cur clip	90953		
elevator cheek rest support weldment assembly	90954	1005-01-556-2244	
elevator cheek rest plunger stop screw	90955	5305-01-556-2610	
front band spacer ring	90956	5365-01-556-6852	M39 EMR
Picatinny rail section adapter screw	90957		
front band spacer ring	90958	5365-01-556-6990	
front band spacer ring	90959	5365-01-556-6988	M39 EMR
front band spacer ring	90560	5365-01-556-6990	M39 EMR
front band spacer ring	90561	5365-01-556-6991	M39 EMR
fore grip (hand guard)	90967		two piece, tan
top cover	90987		M39 EMR, medium weight profile barrel

LEE EMERSON

top cover	90988	1005-01-556-3239	medium weight profile barrel with 1.25 " milled off for Smith Enterprise scope mount
top cover	90901-A or 90990	1005-01-577-2089	standard profile barrel with 1.25 " milled off Smith Enterprise scope mount
butt extension kit	M14BEK		M39 EMR, includes 90995 (1), 91734 (2) and 90928 (4)
butt extension plate	90995		M39 EMR, adds 1 " length to M14 ALCS stock
butt pad extension screw	91734		M39 EMR, two required
vertical adjustable butt extension kit	M14VABEK/ALCS		adds 1.5 " vertical height and 1.5 " length, M14ALCS
vertical adjustable butt extension kit	M14VABEK/PMRI		Mk 14 Mod 2, adds 1.5 " vertical height and 1.5 " length, M14ALCS/PMRI
stripper clip sight base	B009042 or M14SCSB		Mk 14 Mod 0, M14 T
Picatinny rail section adapter for vertical fore grip	B009047 or M14APRS		mounts to bottom of fore grip (hand guard)
detachable cantilevered sight base	B009053 or M14DCSB	1005-01-596-4872	M14 EBR-RI

M14 RIFLE HISTORY AND DEVELOPMENT

pistol grip	M14ERGO		Mk 14 Mod 2, M14 EBR-RI, M14 EBR-RI NM, replaced 90905
pistol grip	BG-16 FDE		Mk 14 Mod 1, TangoDown
full auto cutout cover	M14FACC		
Picatinny rails engraved with numbers	M14REN		quantity of four
monopod rail for butt stock with mounting screws	MPR1 or PMRI-MR		M14ALCS/PMRI
sling attachment	PMRI-FR		Mk 14 Mod 2, M14ALCS/PMRI

Table 58: Twenty Round Magazine Items

Description	Part Number	FSN or NSN	Comments
magazine assembly	7790183	1005-628-9048 1005-00-628-9048	original drawing dated June 1958
magazine base	7790182		original drawing dated June 1958
magazine spring	7267078		original drawing dated October 1954
magazine follower	7267018		original drawing October 1954
magazine follower assembly	7267019		original drawing dated October 1954

LEE EMERSON

magazine follower stop	7267085		original drawing dated October 1954
magazine tube	7790197		original drawing dated June 1958
magazine latch plate	7791098		original drawing dated June 1958

Table 59: M2 Bipod Items

Description	Part Number	FSN or NSN	Comments
M2 bipod assembly	7790688	1005-711-6202 1005-00-711-6202	original drawing dated March 1960, some bipods are stamped 7790833
pivot plunger pin	96906-16562-96 MS 16562-96	5315-282-3642 5315-00-282-3642	two required, 1/16 " diameter x ¼ " long
pivot plunger pin	7790820	1005-772-6361 5930-00-772-6361	two required, original drawing dated March 1960
pivot plunger spring	7790824	1005-772-6365 5360-00-772-6365	two required, original drawing dated March 1960
pivot plunger	7792846	1005-740-0053 5340-00-740-0053	two required, original drawing dated February 1961
leg plunger pin	96906-16562-99 MS 16562-99	5315-514-2358 5315-00-514-2358	two required, 1/16 " diameter x 7/16 " long
leg extension plunger	7790836		two required, original drawing dated March 1960

M14 RIFLE HISTORY AND DEVELOPMENT

leg extension spring	7790838	1005-897-6156 5360-00-897-6156	two required, original drawing dated March 1960
leg extension plunger housing	7790841		two required
shaft stop pin	96906-39086-88 MS 39086-88	5315-839-2327 5315-00-839-2327	two required, 1/8 " diameter x 3/8 " long
leg screw	MS 16997-9	5305-978-9342 5305-00-978-9342	February 1967 revision, 4-40 threads x 1/4 " long, two required
leg screw nut	MS 35649-244	5310-167-1376 5310-00-167-1376	February 1967 revision, 4-40 threads hex head nut, two required
right leg assembly	7790822	1005-772-6363 1005-00-772-6363	original drawing dated March 1960
right shaft assembly	7790840		original drawing dated March 1960
right leg extension assembly	7790839		original drawing dated March 1960
right leg extension shoe (pad)	7790844		
right leg extension tube	7790845		
left leg assembly	7790821	1005-772-6362 1005-00-772-6362	original drawing dated March 1960
left shaft assembly	7790837		original drawing dated March 1960

LEE EMERSON

left leg extension assembly	7790835		original drawing dated March 1960
left leg extension tube	7790843		
left leg extension shoe (pad)	7790842		
head assembly	7791106		original drawing dated November 1960
cotter pin	MS 24665-149		early version, used for bipod without swivel
cotter pin	96906-24665-151 MS 24665-151	5315-815-1405 5315-00-815-1405	late version, 1/16 " x 3/8 " long
head assembly pin	7791104	5315-474-4115 (cancelled by adoption of the long pin 7791669)	original drawing dated November 1960, short pin that won't allow installation of the sling swivel, 0.217 " diameter, 1.041 " effective length, 1.25 " nominal length, 0.078 " cotter pin hole diameter
head assembly pin	7791669	1005-072-5383 5315-00-072-5383	original drawing dated September 1963, long pin that will allow installation of the sling swivel, 0.217 " diameter, 1.326 " effective length, 1.53 " nominal length, 0.078 " cotter pin hole diameter

M14 RIFLE HISTORY AND DEVELOPMENT

bipod sling swivel	7791670	1005-072-5384 1005-00-072-5384	original drawing dated September 1963
left jaw	7791102	1005-474-4116 1005-00-474-4116	original drawing dated November 1960, the jaws were improved in the period 1966 to 1967
right jaw assembly	7791107	1005-474-4118 1005-00-474-4118	original drawing dated November 1960
self-locking bolt	7791103	5306-474-4114	original drawing dated November 1960, 5/16 " diameter - 24 UNF x 3/4 " long self-locking hex head bolt with nylon insert
right jaw	7791101		original drawing dated November 1960, the jaws were improved for better grip in the period 1966 to 1967
welded head assembly	7792847		original drawing dated February 1961

Table 60: Organizational Maintenance Items

Description	Part Number	FSN or NSN	Comments
fabric envelope, two button	7228907	1005-722-8907 1005-00-722-8907	3 " x 4 7/8 "
flash suppressor nut wrench	7790315	4933-652-9949	predecessor to 7790493
flash suppressor nut pliers	7790493	4933-690-3497 5120-00-690-3497	6 ¼ " overall length
gas cylinder lock wrench	2017		M21A5, Mk 14 Mod 2, Smith Enterprise, Inc.
ruptured case extractor	7790352	4933-652-9950 4933-00-652-9950	
barrel reflector	7265789	1005-786-5789 1005-00-786-5789	early version
barrel reflector	7790138	4933-628-9700 4933-00-628-9700	late version
M2 aiming device	6174998	1005-617-4998	
M15 sighting device	7160903	6910-716-0903 6910-00-716-0903	cardboard, 3 ½ " x 7 "
M63 dummy cartridge	7553706		training device
brush, artist	96906-16840 MS 16840	8020-244-0153 8020-00-244-0153	7/16 " wide x 1 1/8 " long
brush, cleaning	96906-16746-29 MS 16746-29	7920-205-2401 7920-00-205-2401	1 1/16 " diameter x 2 7/8 " long
brush, camel hair		7920-00-205-0565	M14 DMR

M14 RIFLE HISTORY AND DEVELOPMENT

brush, cleaning	8448462	1005-00-494-6602	M14 DMR, Mk 14 Mod 0
carbon removing compound		6850-00-965-2332	P-C-111 and others
cleaning compound solvent (rifle bore cleaner)		6850-224-6656 6850-00-224-6656	MIL-PRF-372, 2 ounces can
cleaning compound solvent (rifle bore cleaner)		6850-224-6657 6850-00-224-6657	MIL-PRF-372, 8 ounces can
cleaning compound solvent (rifle bore cleaner)		6850-224-6658 6850-00-224-6658	MIL-PRF-372, 1 quart can
cleaning compound solvent (rifle bore cleaner)		6850-224-6663 6850-00-224-6663	MIL-PRF-372, 1 gallon can
cleaning compound solvent		6850-01-381-4401	Mk 14 Mod 0, Skysol 100
cleaning compound solvent		7930-01-342-5316	Mk 14 Mod 0, Simple Green, 5 gallon container
cleaning compound solvent		7930-01-306-8369	Mk 14 Mod 0, Simple Green, 1 gallon container
cleaning compound solvent		7930-01-342-5317	Mk 14 Mod 0, Simple Green, 24 ounce bottle
bore cleaner	MC702		Mk 14 Mod 2, Shooter's Choice, 2 ounce bottle
bore cleaner	MC7128		Mk 14 Mod 0, Shooter's Choice, 1 gallon tin

LEE EMERSON

gun grease	G10CC		Mk 14 Mod 0 and Mod 2, Shooter's Choice, 10 ml syringe
abrasive cloth		5350-221-0872 5350-00-221-0872	9 " wide x 11 " long, 42-C-20420-50
fluorescent coating compound		8010-811-1845 8010-00-811-1845	red orange, 1 quart can, MIL-P-21563 No. 633
dry cleaning solvent		6850-281-1985 6850-00-281-1985	1 gallon can, PS661
grease, automotive and artillery		9150-01-197-7693	14 ounce cartridge, MIL-PRF-10924-G
grease, rifle		9150-00-248-3480 (replaced by 9150-00-754-0063)	2.5 cm ³ plastic container with yellow cap, MIL-G-46003-A
grease, rifle	8448693	9150-754-0063 9150-00-754-0063	original drawing dated March 1971, 1 pound can, see latest edition of QPL-46003 for current qualified product
linseed oil, raw		8010-221-0611 8010-00-221-0611	1 gallon can, TT-L-00215
lubricating oil, general purpose		9150-273-2389 9150-00-273-2389	4 ounces can, PL Special
lubricating oil, general purpose		9150-231-6689 9150-00-231-6689	1 quart can, PL Special
lubricating oil, semi-fluid	8436792	obsolete	2 ounces flat oval bottle, MIL-L-46000C

M14 RIFLE HISTORY AND DEVELOPMENT

lubricating oil, weapons		9150-00-292-9689	1 quart can, for below zero degrees operations
cleaner, lubricant and preservative		9150-01-102-1473	M14 DMR, ½ ounce bottle
cleaner, lubricant and preservative		9150-01-054-6453	Mk 14 Mod 0, 1 pint bottle, MIL-PRF-63460
cleaner, lubricant and preservative		9150-01-079-6124	Mk 14 Mod 0, 4 ounce bottle
cleaner, lubricant and preservative		9150-01-053-6688	Mk 14 Mod 0, 1 gallon can
bedding compound			M14 DMR, Marine-Tex, gray, 1 pound
clay, modeling		7510-00-275-2679	M14 DMR, 1 pound
mold release compound		8030-01-064-4951	M14 DMR, can
shim stock			M14 DMR
paper, lens		6640-00-663-0832	M14 DMR, pack of 50 sheets
rag, wiping	DDD-R-30	7920-00-205-1711	50 pound bale, cotton, A-A-2522
swab, small arms cleaning	5019316	1005-00-288-3565	2 ½ " x 2 ½ ", cotton, 1 pack
acetone		6810-00-223-2739	M14 DMR, 1 quart

Table 61: Direct Support Maintenance Items

Description	Part Number	FSN or NSN	Comments
tool and gage set for direct, general and depot maintenance	8421895	4933-647-3703 4933-00-647-3703	7.62 MM Rifle, M14 Series
field maintenance gage case	7799702	4933-678-9830 5220-00-678-9830	maple box
breech bore field reject gage	7274761	4933-647-3697 5220-00-647-3697	limit 0.310 ", marked top line - RIFLE 7.62 MM, M14 second line - BREECHBORE
field test gage bolt	7274799	4933-647-3699 5220-00-647-3699	0.615 " right lug, 0.575 " left lug
head space field reject gage	7274790	4933-647-3698 5220-00-647-3698	limit 1.6455 "
gas piston snap gage	7274757	4933-647-3695 5220-00-647-3695	NO-GO, 0.4968 " piston diameter
gas cylinder plug gage	7274755	4933-647-3693 5220-00-647-3693	NO-GO, 0.5009 " piston hole diameter
firing pin protrusion gage	7274736	4933-345-6122 5220-00-345-6122	0.044 " minimum, 0.060 " maximum
firing pin hole plug gage	7458406	4933-917-1067 5220-00-917-1067	NO-GO, 0.083 " maximum
flash suppressor alignment tool	7799705	4933-856-2561 4933-00-856-2561	
flash suppressor nut pliers	7790493	4933-690-3497 5120-00-690-3497	

M14 RIFLE HISTORY AND DEVELOPMENT

bolt roller retaining ring pliers	7799723	4933-563-0436 5120-00-563-0436	
hex head wrench, 7/64 "		5120-889-2162 5120-00-889-2162	for late front sight screw part number 11010298
head space gages	7274746	5220-00-921-6054	set of nine gages, 1.630 " to 1.638 ", USMC M14 DMR
3/8 " combination open end and socket end wrench			USMC M14 DMR
gas cylinder lock tool (wrench)			locally fabricated, USMC M14 DMR intermediate level item
Dremel ^(R) Moto-Tool kit		5120-01-014-6856	USMC M14 DMR
test fixture, measuring, trigger pull	7274758	4933-00-647-3696	USMC M14 DMR

Table 62: General Support (Depot) Maintenance Items

Description	Part Number	FSN or NSN	Comments
bolt assembly and disassembly tool	7144859	4933-00-714-4859	M1 tool adapted to the M14
bolt assembly and disassembly tool	7791607	4933-00-055-5996	M1 and M14 variants, organizational and intermediate level item for the USMC M14 DMR
small arms shop set		4933-754-0664 4933-00-754-0664	reference SM 9-4-4933-A13
small arms repairman's tool kit		5180-754-0640	pre-'62 tool kit
small arms repairman's tool kit		4933-357-7770 5180-00-357-7770	twenty-seven items added to 5180-754-0640, adopted January 1962, reference SM 9-4-5180-A57
tool set, direct and general support maintenance, basic small arms	8426358	4933-775-0366 1015-00-775-0366	reference SM 9-4-4933-E04
tool set, depot maintenance	8432422	4933-930-5598	7.62 MM Rifle, M14 Series
head space gage	7274780	4933-916-9271 5220-00-916-9271	1.6355 "
head space gage	7274782	4933-916-9275 5220-00-916-9275	1.6375 "
head space gage	7274786	4933-069-8676 5220-00-069-8676	1.6415 "

M14 RIFLE HISTORY AND DEVELOPMENT

head space reamer assembly	24-013863	4933-809-7980	
head space reamer assembly crank handle	10-013069	4933-105-2835	
barrel and receiver assembly disassembling fixture	10-013027	4933-439-6089	
bolt and roller assembly grease fitting adapter	10-013635	4933-450-6725 4933-00-450-6725	
bolt and roller assembly assembling and disassembling fixture	10-016057	4933-439-6088 4933-00-439-6088	
firing mechanism assembling fixture	443448	4933-439-6090 4933-00-439-6090	
gas cylinder piston hole plug gage	8440826	5220-437-1152 5220-00-437-1152	NO-GO, 0.5009 " piston hole diameter
gas port alignment plug gage	11015316	4933-916-9188 5220-00-916-9188	
bore straightness drop plug gage	11015416	4933-916-9189 5220-00-916-9189	
targeting jack gage	6511841	4933-916-9193 4993-00-916-9193	
GO relationship of storage holes to butt plate plug gage	7271641	4933-916-9194 5220-00-916-9194	
torque testing gage	7271792	4933-916-9196 5220-00-916-9196	

LEE EMERSON

receiver and trigger housing clamping surfaces flush pin gage	7799742	4933-916-9341 5220-00-916-9341	
operating rod spring length gage	7799743	4933-916-9360 5220-00-916-9360	
extractor assembly length gage	7799744	4933-916-9362 6695-00-916-9362	
ejector assembly length gage	7799745	4933-916-9365 5220-00-916-9365	
hammer spring length gage	7799747	4933-916-9444 5220-00-916-9444	
rear sight aperture length gage	7799746	4933-916-9437 5220-00-916-9437	
connector assembly straightness gage	7799748	4933-916-9464 5220-00-916-9464	
barrel alignment gage	7799749	4933-916-9468 6695-00-916-9468	
selector slot location gage	7799750	4933-916-9487 5220-00-916-9487	
firing pin intrusion flush pin gage	7799751	4933-916-9527 5220-00-916-9527	
adjustment snap gage	7479462	4933-917-1068 5220-00-917-1068	MIL-STD-118
barrel and receiver assembling fixture	7799718	4933-937-4068 4933-00-937-4068	
fixed open end wrench	10-012952	5120-156-8735 5120-00-156-8735	

M14 RIFLE HISTORY AND DEVELOPMENT

facing cutter	7799721	4933-937-4069 5110-00-937-4069	
bolt face firing pin hole plain cylindrical plug gage	7458398	5220-745-8398 5220-00-745-8398	NO-GO, 0.083 " maximum diameter, MIL-STD-111
chamfer tool (field)	7799719	5220-00-937-4536	also known as a profile gage
proof firing cover	7273975	4933-838-5472	for depot rebuild program only
firing stand	7273901	4933-916-9207 4933-00-916-9207	for depot rebuild program only
target, 1000 inch	8448435	6920-240-9349	roll of 500
target, M14 rifle	11686842	6920-021-2477	for depot rebuild program only, roll of 500 targets per box, original drawing dated November 1966
adjustable base assembly	7692125		support level not available
timer cycle gage	7273920		support level not available
trigger pull gage	7274758	4933-00-647-3696	support level not available
bolt lock pin removal tool	improvised		see drawing at TM 9-1005-223-35 July 1968 page 6
flash suppressor seating tool	improvised		see drawing at TM 9-1005-223-35 July 1968 page 7

LEE EMERSON

stock liner screw wrench	improvised		
M15 grenade launcher sight drill jig	improvised		see drawing at TM 9-1005-223-35 July 1968 page 7, use mild steel or aluminum
firing mechanism assembly and disassembly fixture	improvised		
protector, rear sight	7791358	1005-00-441-8807	
protector, operating rod handle	7790231	1005-00-875-9765	
protector, muzzle	7790232	1005-00-875-9766	

Table 63: Procurement Substitutions - Interchangeable Items

Description	FSN or NSN	Identical to the M14 item?	Comments
M1 elevation pinion assembly		not suitable	early style with small screw and smooth face marked battle range
M1 elevation pinion assembly	1005-731-2738	no but suitable	calibrated in yards
M1 windage knob		not suitable	early style with winged lock nut
M1 windage knob	1005-731-2737	yes	original drawing dated December 1944

M14 RIFLE HISTORY AND DEVELOPMENT

M1 rear sight aperture	1005-600-8868	yes	original drawing dated August 1937
M1 rear sight cover	1005-600-8872	yes	original drawing dated August 1937
M1 rear sight base	1005-564-6001	yes	original drawing dated August 1937
M1 extractor	1005-554-6003	no but suitable	early M14 extractor
M1 extractor spring w/plunger	1005-600-8618	yes	original drawing dated August 1937
M1 trigger pin	5315-501-3669	no but suitable	early M14 trigger pin
M1 trigger pin	1005-819-4501	yes	on 1964 DCM list
M1 trigger and sear assembly	1005-554-6026	no but suitable	for semi-automatic fire only
M1 sear		no but suitable	for semi-automatic fire only
M1 sear pin		yes	original drawing dated August 1937
M1 trigger		yes	original drawing dated August 1937
M1 hammer spring housing	1005-600-8883	yes	original drawing dated August 1937
M1 hammer spring	1005-600-8887	yes	original drawing dated August 1937
M1 hammer spring plunger	1005-600-8880	yes	original drawing dated August 1937
M1 hammer pin	5315-501-3668	yes	original drawing dated August 1937
M1 hammer		dimensionally identical	World War II production marked C46008, original drawing dated August 1937

LEE EMERSON

M1 hammer	1005-554-6008	dimensionally identical	1950s production marked D5546008, original drawing dated August 1937
M1 safety	1005-554-6015	yes	original drawing dated April 1937
M1 hand guard band		yes	original drawing dated August 1937
M1 lower butt stock screw	5305-600-8881	yes	original drawing dated August 1937
M1 butt stock sling swivel	1005-600-8889	yes	original drawing dated August 1937
M1 small butt plate screw	1005-614-6873	early M14 and M14A1	also available from M1903, can be used on standard M14 stock by plugging hole, original drawing dated March 1935
M1 butt plate assembly	1005-556-4277	early M14 only	can be used on standard M14 by using hinge transition piece 7790914 or equivalent
NM front sight			marked NM 062, original drawing dated November 1961
NM rear sight base	1005-875-6281	yes	marked NM/2, original drawing dated December 1961
NM rear sight base	1005-754-6799	yes	marked NM/2A, original drawing dated November 1963
NM windage knob	1005-649-9275	yes	original drawing dated November 1958
hooded rear sight aperture	1005-864-2926	yes	0.0595 " diameter

M14 RIFLE HISTORY AND DEVELOPMENT

hooded rear sight aperture	1005-864-2928	yes	0.0520 " diameter
NM rear sight aperture	1005-348-8654	yes	0.0595 " diameter, part number 7268109
NM rear sight aperture	1005-348-8655	yes	0.0520 " diameter, part number 7268110
M1907 leather sling	1005-00-714-1245	yes	series of original drawings dated November 1950, part number 7141245
small arms sling, cotton web	1005-00-654-4058	yes	olive drab, last contract circa 1966, part number 6544058
small arms sling, hard nylon weave	1005-00-714-5320	no but suitable	issued for use in the Republic of Viet Nam, introduced about 1969, part number 7145320
small arms sling, soft nylon weave	1005-00-167-4336	no but suitable	first produced in 1973, part number 8448770
small arms sling	1005-01-216-4510	no but suitable	originally dated January 1986, two metal loops but no clasp, part number 12624561
M1 rifle cleaning rod case	1005-716-2792	no	M1 case made of light cloth with integral tab, M14 case of heavy cloth with sewn on tab
M10 cleaning rod handle assembly		no	part number 7266115
M10 cleaning rod section		yes	drawing number D7162920
bore brush	1005-556-4174	yes	drawing number C5564174

swab holder		yes	
barrel reflector	4933-726-5788	no	
M15 grenade launcher sight drill jig	1005-00-731-0066	no	part number 7310066, M1903 and M1 rifles, the jig holes are located too high for the M14
M1 stock ferrule sling swivel	1005-600-8890	M14A1 only	

Table 64: Accessories for Various USGI M14 Rifles

Description	Part Number	FSN or NSN	Comments
bipod	98003A2200	1005-01-472-3902	M14 DMR, Harris Bipods, model S-L
bipod	180-MZ-091		M21A5, Smith Enterprise, Inc.
bipod	S-BRM	1005-01-511-7758	M39 EMR, M14 T, Harris Bipods
bipod	1A2-BRM		Mk 14 Mod 0, Harris Bipods
bipod	1A2-L		M14 EBR-RI, M14 EBR-RI NM, Harris Bipods
bipod	ACB-4 FDE		Mk 14 Mod 1, TangoDown
bipod	BT10-LW17		Mk 14 Mod 2, B&T Industries
bipod adapter	98060	1005-01-468-0350	M39 EMR and Mk 14 Mod 0, M14 EBR-RI, M14 EBR-RI NM, Knight's Armament

M14 RIFLE HISTORY AND DEVELOPMENT

bipod adapter	LT-130		M14 T, LaRue Tactical
bipod lock	875	1005-01-511-9944	M39 EMR, Kisatchie Machine Works
blind bag	247261		Mk 14 Mod 2, Caldwell
cartridge clip (stripper clip)	7790130	1305-00-914-7912	M14, M14A1, five round capacity, originally drawn January 1958
cartridge clip spring	7790131		
cartridge clip shoe	7790132		
chamber brush	7790463	1005-633-7165 1005-690-8441 1005-00-690-8441	The FSN was changed between 1960 and January 1963 but the reason is not known. The part number did not change.
cheek rest, strap on	2021		M21A5, Smith Enterprise, Inc.
cleaning kit	308-6	1005-01-451-5119	M14 DMR, M39 EMR, Mk 14 Mod 0, 1, and 2, M14 EBR-RI, M14 EBR-RI NM, M14 T, Otis Products, Inc.
cleaning kit, optics	81-9238		Mk 14 Mod 2, Crimson Trace
cleaning kit pouch		8465-926-6768 8465-00-926-6768	M14A1

LEE EMERSON

bore snake, .30 caliber	24015		Mk 14 Mod 0 and 2, M14 T, Hoppes
cleaning rod, coated	D30C24		Mk 14 Mod 2, J. Dewey
cleaning rod guide	2052		Mk 14 Mod 2, Smith Enterprise, Inc.
cleaning rod case with spacer	7267754	1005-650-4510 1005-00-650-4510	cloth case with sewn on tab, four USGI versions made
cleaning rod section	7266109	1005-726-6109 1005-00-726-6109	four required
cleaning rod swab holder	7266110	1005-726-6110 1005-00-726-6110	3.5 " overall length
M14 combination tool	7790769	4933-00-768-0211	FSN listed as 4933-768-2011 in TM 9-1005-223-34
M14 EBR-RI multi-tool	13026063	5110-01-576-6136	M14 EBR-RI, M14 EBR-RI NM, Bondhus
M39 EMR multi-tool	784285	1005-01-559-1342	Bondhus
Mk 14 EBR multi-tool	67255281	MSC	Mk 14 Mod 0, M14 T, Bondhus
Mk 14 EBR multi-tool	853485		Mk 14 Mod 2, Bondhus
Mk 14 EBR multi-tool	736540		Mk 14 Mod 2, Bondhus
gas cylinder plug wrench	7267693		pre-'61 cleaning kit item, 3/8 " box end twelve point, 2 5/8 " overall length, 15 degree offset handle

M14 RIFLE HISTORY AND DEVELOPMENT

combination tool			pre-'61 cleaning kit item, three pieces
oiler case			pre-'61 cleaning kit item
grease cup			pre-'61 cleaning kit item
chamber brush	7267713		pre-'61 cleaning kit item, no ratchet mechanism
M1 cleaning kit case	7162792	1005-716-2792 1005-00-716-2792	lighter cloth material than 7267754 and has an integral tab
cleaning rod swab holder	6147417	1005-614-7417 1005-00-614-7417	pre-'61 cleaning kit item, 3 "
lubricant case	7790995	1005-791-3377 1005-00-791-3377	two compartment plastic case
magazine filler (late version)	7791154	1005-00-052-4336	commonly known as magazine charger guide, original drawing dated February 1961
M2 bandoleer		1305-00-984-1125	M14, M14A1
M3 bipod with carrying case	8445081	1005-890-2609 1005-00-890-2609	M16 accessories
M3 bipod	8448457	1005-992-6676 1005-00-992-6676	M16 accessory, sometimes used on the M14 in the Republic of Viet Nam, Colt Industries part number 62122
M3 bipod carrying case	2-2-246	1005-999-2430 3040-00-999-2430	
M3 breech shield	7790929		
M5 winter trigger kit	5910520	1005-777-1369 1005-00-777-1369	M14

LEE EMERSON

M5 winter trigger assembly	7790808	1005-775-0364 1005-00-775-0364	M14, original drawing dated May 15, 1961
M5 winter trigger cam	7791209		
M5 winter trigger hinge	7791212		
M5 winter trigger pin	7791208		two required
M6 bayonet	7267616	1005-00-722-3097	original drawing dated January 24, 1955
M6 bayonet with M10 scabbard	8427015	1005-00-014-0369	original drawing dated February 25, 1964
M6 bayonet blade assembly	7267649		original drawing dated January 24, 1955
M6 bayonet left track	7267647		
M6 bayonet right track	7267646		
M6 bayonet blade	7267650		
M6 bayonet wedge	7266544		two required
M6 bayonet track rivet	7266542		two required
M6 bayonet guard	7267651		
M6 bayonet sleeve	7266541		
M6 bayonet plate	7266538		
M6 bayonet spring	7267645		original drawing dated January 24, 1955, steel music wire per QQ-W-470, conical compression, 8.5 coils, 0.55 " free length, plain ends, right hand or left hand twist

M14 RIFLE HISTORY AND DEVELOPMENT

M6 bayonet latching lever	7267648		original drawing dated January 24, 1955, AISI 1060 carbon steel per QQ-S-640
M6 bayonet pin	586077		early version
M6 bayonet pin	MS 16562-125	5315-00-058-6077	late version
M6 bayonet right side grip	7267652	1005-333-3577 1005-00-333-3577	original drawing dated January 24, 1955, thermosetting molding plastic, semi-dull black
M6 bayonet left side grip	7267653	1005-333-3578 1005-00-333-3578	original drawing dated January 24, 1955, thermosetting molding plastic, semi-dull black
M6 bayonet screw	7266548	5305-00-726-6548	two required, early version
M6 bayonet screw	11010078	5305-00-051-3609	original drawing dated December 06, 1963, two required, late version, effective with D7267616 Revision F dated December 1969, 6-32 UNC-2A x 0.75 " long, interchangeable with M4, M5, M5A1 and M7 bayonet screw
M8A1 scabbard	7268112	1095-00-508-0339	
M8A1 scabbard restraining lace	7267136	1005-300-5378 1005-00-300-5378	
M10 scabbard	8448476	1095-00-223-7164	
M11 small arms storage rack	8429990	1095-897-8755 1095-00-897-8755	original drawing dated October 1961, M1 and M14 rifles

LEE EMERSON

M12 blank firing kit	5910570	1005-00-893-0902	
M12 blank firing attachment	7793000		third version
sound suppressor	M14 SS-1		XM21, Sionics, Inc.
sound suppressor	2080	1005-LL-L99-7965	M21A5, Smith Enterprise, Inc.
sound suppressor	762K-DE		Mk 14 Mod 1, Surefire, LLC
sound suppressor and tool pouch	3005		M21A5, Smith Enterprise, Inc.
trigger shoe	V2 EBR		Mk 14 Mod 2, X-treme Shooting Products, LLC
M15 grenade launcher sight	5750053	1005-049-9428 1005-00-344-6156	
M15 sight body	7310096		
M15 sight level assembly	7310097		
M15 sight level assembly screw	7310093		two required
M15 sight bracket screw	7310095		two required
M15 sight stock plate	7311859		
M15 sight tapping screw	7310009		two required
M15 grenade launcher sight carry case	7160198	1005-716-0198 1005-00-716-0198	canvas pouch with two snap buttons
T140 and M76 grenade launcher	7267617	1005-722-3098 1005-00-722-3098	M14, MIL-STD-1266 dated March 23, 1961
M76 grenade launcher with equipment	5910536	1005-778-8812 1005-00-778-8812	M14
M151 vehicle mounting kit		2590-045-9611 (cancelled)	early version for M14 rifle

M14 RIFLE HISTORY AND DEVELOPMENT

M151 vehicle mounting kit	11630529	2540-763-7348 1095-00-763-7348	late version for M14 and M16 rifles
XM152 winter trigger assembly	11010283	1005-919-9915	
M35 truck dual rifle mounting kit	12301044	2540-01-223-0041	M14 or M16
muzzle stabilizer assembly			M14 (USAIB) only, 1962 design, first version
muzzle stabilizer assembly	7791661	1005-072-5382	M14E2, original drawing dated September 1963, second version
muzzle stabilizer assembly	11686521	1005-930-0806 1005-00-930-0806	M14A1, original drawing dated April 1966, final version
muzzle stabilizer yoke pin	7791664	5315-929-0862 5315-00-929-0862	
muzzle stabilizer yoke washer	7791668	5310-962-0873 5310-00-962-0873	0.098 " ID x 0.315 " OD x 0.060 " thick flat washer
muzzle stabilizer yoke assembly	11686520	1005-951-3232 1005-00-951-3232	
muzzle stabilizer yoke screw	11686519	5305-956-3127 5306-00-956-3127	¼ " diameter - 28 UNF x 1.215 " long hex head bolt
muzzle stabilizer yoke nut	7791663	5310-953-6340 5310-00-953-6340	¼ " diameter - 28 UNF x 0.270 " thick hex nut
muzzle stabilizer yoke	11686517		
muzzle stabilizer stop	11686518	1005-951-3056 1005-00-951-3056	
muzzle stabilizer	7791667		

LEE EMERSON

rifle butt pocket and strap assembly		8465-782-2779, 8465-00-782-2779	nylon webbing carrier to attach a M14 rifle to an ALICE ruck sack, U. S. Army Quartermaster Corps item
M84 scope carrying case	7631596	1240-00-763-1596	marked MRT on the inside of the flap
ART TEL scope carrying case	11729637	1240-179-4192	waterproof 6061 T6 alloy aluminum or fiberglass container
ART II scope carrying case	5888-160	1240-01-152-2922	Leatherwood Industries, Inc.
AN/PAS-4 scope		1090-797-8217 5855-00-797-8217	Varo model 9903, 4.5 X, total weight 13 pounds
AN/PAS-4 scope		1090-990-0701 5855-00-990-0701	Polan Industries model P-155, 4.5X, total weight 13 pounds
AN/PVS-1 scope	6060	5855-087-2942 5855-00-087-2942	Electro-Optical Systems, Inc., 4X magnification, 18.5 " long, 3.375 " wide, weight 6 pounds
AN/PVS-2 scope		5855-832-9223 5855-00-832-9223	4X magnification, 17.5 " long, 3.5 " wide, weight 6 pounds, AN/PVS-2A and AN/PVS-2B models were also fielded, - 2B model features automatic control for light brightness
AN/PVS-3 scope		5855-832-9341 5855-00-832-9341	4X magnification, 13.5 " long, 3.5 " wide, 5.75 " high, weight 3 pounds, automatic light brightness control

M14 RIFLE HISTORY AND DEVELOPMENT

AN/PVS-3A scope		5855-156-4992 5855-00-156-4992	4X magnification, automatic light brightness control
AN/PVS-4 scope		5855-00-629-5334	4X magnification, 9.5 " long, 4.5 " wide, 3.8 pounds weight
boresight assembly	SC-D-614644	5855-00-937-7706	AN/PVS-1, 2, and 3
scope mount	SC-D-607130		AN/PVS-1, 2, and 3
AN/PVS-4 carrying case		5855-00-832-6525	
AN/PAQ-4 infrared aiming light		5855-01-107-5925	Mk 14 Mod 0
AN/PAQ-4A infrared aiming light		5855-01-312-5160	Mk 14 Mod 0
AN/PAQ-4B infrared aiming light		5855-01-361-1362	Mk 14 Mod 0
AN/PAQ-4C infrared aiming light		5855-01-398-4315	Mk 14 Mod 0
AN/PEQ-2A target illuminator		5855-01-447-8992	Mk 14 Mod 0
AN/PVS-10 day and night scope		5855-01-410-8979	M14 DMR
AN/PVS-14 night scope		5855-01-432-0524	
AN/PVS-22 night scope mount	2009		M21A5, Smith Enterprise, Inc., U. S. Army safety certified
AN/PVS-27 night scope		5855-01-547-9489	Mk 14 Mod 2
optical scope (sight, telescopic)	9349352	1240-01-107-9068	M21, original drawing dated November 1981
optical scope	98003A0020	1240-01-470-6548	M14 DMR, 10X
optical scope	PRM8541	1240-01-533-1854	M39 EMR, Premier Reticles

LEE EMERSON

optical scope	Mark 4, 67095		USN Mk 14 Mod 0, Leupold & Stevens, Inc., 1.5-5X
optical scope	Mark 4		USN Mk 14 Mod 0, Leupold & Stevens, Inc., 3.5-10X
optical scope	Mark 4, 67940		USAF Mk 14 Mod 0, Leupold & Stevens, Inc., 3.5-10X
optical scope	NXS		Mk 14 Mod 1, Nightforce Optics, Inc., 2.5-10X24 mm
optical scope	NXS		Mk 14 Mod 2, Nightforce Optics, Inc., 3.5-10X50 mm MIL-DOT with ZeroStop
optical scope	Mark 4, 51850		M14 EBR-RI, M14 EBR-RI NM, Leupold & Stevens, Inc., 3.5-10X
optical scope	PM Short Dot		M14 T, Schmidt & Bender, 1.1-4X
optical scope	MS02 black		Mk 14 Mod 1, Trijicon, Inc., 7 MOA
scope mount	18	1240-01-316-0055	Atlantic Research Marketing Systems, Inc., MIL-STD-1913
scope mount	2006	1005-01-506-5750 5855-01-506-5750	M21A5, M39 EMR, USAF Mk 14 Mod 0, Smith Enterprise, Inc., U. S. Navy safety certified, MIL-STD-1913, 5.38 " long
scope mount	2008	1005-01-533-8160	Smith Enterprise, Inc., U. S. Army safety certified, MIL-STD-1913, 7.0 " long

M14 RIFLE HISTORY AND DEVELOPMENT

scope mount	2005	1005-01-535-4430	Smith Enterprise, Inc., MIL-STD-1913, Trijicon, Inc. sight compatible
scope mount	98003A1100	1005-01-556-7363	M39 EMR, optical platform interface
scope mount	LT-139		M14 T, LaRue Tactical
scope mount	LT-608		Mk 14 Mod 1, LaRue Tactical
scope mount, red dot sight	35101P01		Mk14 Mod 1, Wilcox Industries Corp.
scope mount screw	98003A1105		M14 DMR, M39 EMR
scope ring (assembly, ring, telescopic sight)	98003A0030	1005-01-470-7458	M14 DMR, Badger Ordnance, two required
scope ring	306-29		USN Mk 14 Mod 0, Badger Ordnance, two required
scope ring	7008	1005-01-535-4374	USAF Mk 14 Mod 0, Smith Enterprise, Inc., two required
scope ring	7018	1005-01-535-4423	M21A5, Smith Enterprise, Inc., two required
scope ring	A107		Mk 14 Mod 2, Nightforce Optics, Inc., two required
scope ring	A118		Mk 14 Mod 1, Nightforce Optics, Inc., two required
scope ring	61049		M14 EBR-RI, M14 EBR-RI NM, Leupold & Stevens, Inc., two required
scope ring	LT-139		M14 T, LaRue Tactical

LEE EMERSON

scope ring	306-75	1005-01-537-8618	M39 EMR, Badger Ordnance, two required
scope ring mount	SIMRAD B0634	2540-01-544-9232	M39 EMR, SPA Defense
scope ring screw (screw, cap)	MS 16995-18B	5305-00-145-0713	M14 DMR, eight required, M39 EMR, ten required
scope ring upper half (cap, ring)	98003A0033	1005-01-470-9060	M14 DMR and M39 EMR, two required
scope ring lower half (ring, base)	98003A0031	1005-01-470-9065	M14 DMR and M39 EMR, two required
scope ring nut	98003A0036	5310-01-472-3851	M14 DMR and M39 EMR, two required
scope ring washer	DOD-W-63474/3	5310-01-360-4766	M14 DMR and M39 EMR, two required
scope ring clamp	98003A0034	1005-01-470-9595	M14 DMR and M39 EMR, two required
sling, M1907	2023		M21A5, Smith Enterprise, Inc.
sling, M60		1005-00-312-7177	Mk 14 Mod 2
sling, rifle	TAS-M14		Mk 14 Mod 0, M14 T, Buffer Technologies
sling, rifle	FNH-ESS		Mk 14 Mod 2, 1.25 " wide
transport case	1750-000-110	6760-01-491-2838	M39 EMR, Pelican
transport case	DC-M14		Mk 14 Mod 0, Eagle Industries
transport case	DC-M14-EBR-KH		Mk 14 Mod 2, Eagle Industries
transport case	IM3300-X0000		Mk 14 Mod 2, Pelican
weapons record book		0000-00-005-9811	Mk 14 Mod 0
weapons record book		7610-LL-LN9-8954	Mk 14 Mod 2

M14 RIFLE HISTORY AND DEVELOPMENT

XM152 winter trigger kit	5910322		M14A1 only
--------------------------	---------	--	------------

Table 65: Comparison of USGI Multi-tools

Tool	Mk 14 Mod 0	Mk 14 Mod 2	M39 EMR	M14 EBR-RI
gas system cleaning bits		X	X	X
3/8 " box end wrench		X	X	X
1/2 " socket wrench		X	X	X
flat tip screwdriver	X	X	X	X
0.050 " hex wrench	X			
1/16 " hex wrench	X			
5/64 " hex wrench	X	X	X	X
3/32 " hex wrench	X	X		X
3 mm hex wrench				X
1/8 " hex wrench	X	X	X	
1/8 " Torx wrench	X	X		X
5/32 " hex wrench	X	X		X

LEE EMERSON

5/32 " ball end hex wrench			X	
3/16 " ball end hex wrench	X		X	

Table 66: Repair Items

Description	Part Number	FSN or NSN	Comments
combination tool spring pin	MS 16562-98	5315-597-5086 5315-00-597-5086	1/16 " diameter x 3/8 " long
combination tool screwdriver blade	7790786	4922-780-1982 5120-00-780-1982	0.220 " wide x 0.527 " long
enamel, walnut stock touch up		8010-145-0042 8010-00-145-0042	number 21089, 1 gallon can
M5 winter trigger kit screw	7791231		two required, wood screw with partially threaded shaft, TM 9-1005-223-12 January 1963
M5 winter trigger kit thread forming tapping screw	7791415	5305-990-6435 5305-00-990-6435	two required, wood screw with fully threaded shaft, TM 9-1005-223-34 August 1972
M5 winter trigger kit retaining hinge washer	7791237	1005-010-5022 5340-00-010-5022	
M5 winter trigger kit lever	7791211		
M5 winter trigger kit safety	7790903	1005-778-0580 1005-00-778-0580	

M14 RIFLE HISTORY AND DEVELOPMENT

stock repair screw, large	5233523	5315-523-3523 5315-00-523-3523	half-hard brass, 3/32 " diameter x 2 7/16 " long, for repair of wood stock FSN 1005-754-6462
stock repair screw, small	7190954	5315-719-0954 5315-00-719-0954	half-hard brass, 1/16 " diameter x 2 " long, for repair of wood stock FSN 1005-754-6462

The U. S. Army Ordnance Corps at Raritan Arsenal promulgated an Instructor Guide on the M14 (T44E4) Rifle on January 02, 1958. This guide, CMT-IG Number 38 Notes on Rifle Caliber 7.62MM M14 (T44E4), included physical data, a general description and a list of T44E4 parts and required spare parts. M14 parts production did not start until December 1958. Some of the associated drawings, including the M14 receiver, had not yet been drawn. The following is a list of T44E4 parts and the numbers of spare parts for maintenance of 100 rifles from CMT-IG Number 38 and Springfield Armory Notes on Development Type Materiel Report Number SA-NM11-2612 dated June 17, 1955.

Table 67: T44E4 Rifle Parts and Recommended Spare Parts

Ordnance Drawing Number	T44E4 Part Description	Number of Spare Parts for Maintenance of 100 Rifles
BCTX2.2 (147457)	full dog point set socket screw	10
BEAX1 (138534)	lock tooth type washer	
BFSX2.1 (586045)	selector shaft pin	2
BFSX2.1 (586062)	spindle valve pin	50
BFSX2.1 (586064)	spring pin	2
BFSX2.1 (586072)	bolt lock pin	10
BFSX2.1 (586081)	magazine latch pin	9

LEE EMERSON

BFSX2.1 (586085)	pin	20
BMCX1.3 (135285)	(2) truss head rivet	10
B5013668	hammer pin	4
B5013669	trigger pin	4
B5013671	extractor spring plunger	
A5013673	sear pin	
B5152863	butt plate plunger spring	
B5152864	butt plate plunger	
A5152865	butt plate cap pin	
D5546001	rear sight base	2
F5546003	extractor	8
D5546020	trigger	
D5564277	butt plate	
D5564283	butt plate assembly	
B6008618	extractor spring assembly	15
D6008868	rear sight aperture	4
B6008870	hand guard band (clip)	
C6008872	rear sight cover	2
B6008880	hammer spring plunger	2
C6008881	long butt plate screw	2

M14 RIFLE HISTORY AND DEVELOPMENT

C6008883	hammer spring housing	2
B6008886	extractor spring	
B6008887	hammer spring	5
C6008889	butt swivel	2
B6146873	small butt plate screw	2
D6147465	butt plate cap	
D7267001	front band	5
F7267002	barrel	6
F7267003	bolt body	
B7267004	bolt with roller	6
D7267005	bolt assembly	
B7267007	front swivel bracket	
D7267011	connector bar	
D7267012	connector assembly	8
D7267013	gas cylinder	4
C7267014	ejector	
B7267015	ejector assembly	12
B7267017	stock ferrule	
D7267018	magazine follower	
C7267019	magazine follower and stop assembly	

LEE EMERSON

D7267020	hand guard	
D7267021	hand guard assembly	10
D7267022	trigger guard	
D7267023	trigger guard and stop assembly	4
B7267024	connector spring guide	
C7267025	operating rod guide	4
C7267027	operating rod spring guide	10
C7267028	packet charger guide	2
F7267029	operating rod handle	
F7267030	trigger housing	
D7267031	trigger and latch housing assembly	4
C7267032	magazine latch	5
C7267033	stock liner	
C7267034	bolt lock	5
B7267035	connector lock	10
C7267036	gas cylinder lock	4
B7267037	front swivel loop	
D7267038	magazine assembly	1000
B7267039	flash suppressor nut	5
B7267041	magazine latch spring	5

M14 RIFLE HISTORY AND DEVELOPMENT

B7267042	connector lock pin	10
C7267043	firing pin	20
D7267047	gas piston	4
B7267050	connector plate	
C7267051	magazine floor plate	
C7267053	gas cylinder plug	4
F7267056	receiver	
F7267057	barrel and receiver assembly	
D7267058	sear release	5
B7267059	bolt roller retainer	10
B7267063	(2) stock liner screw	8
D7267064	operating rod assembly	8
B7267065	bolt roller	10
D7267066	safety	2
D7267067	front sight screw	2
D7267070	sear	
C7267071	selector switch	5
C7267072	selector shaft	5
D7267073	front sight	2
B7267074	bolt lock spring	5

LEE EMERSON

B7267076	connector spring	
C7267078	magazine spring	
B7267079	operating rod spring	5
B7267080	safety spring	5
B7267081	selector spring	5
F7267083	stock	
F7267084	stock assembly with butt plate	10
B7267085	magazine follower stop	
F7267088	flash suppressor	5
C7267089	front swivel assembly	2
C7267090	trigger and sear assembly	4
D7267091	magazine tube	
B7267092	operating rod tube	
C7267172	selector shaft lock	5
C7267604	spindle valve	5
B7267605	spindle valve spring	10
B7267959	ejector spring	
D7267963	hammer	4
B7312633	hammer stop	
C7312725	indexing dog	

M14 RIFLE HISTORY AND DEVELOPMENT

C7312726	rear sight nut	
B7312727	dog retainer	
B7312728	rear sight nut retainer	
B7312729	rear sight screw retainer	
C7312730	rear sight screw	2
C7312731	rear sight lock nut	
C7312732	rear sight spring	
C7312733	indexing dog assembly	
D7312734	elevating knob	
D7312735	windage knob	
D7312736	elevating pinion	
D7312737	windage knob assembly	4
D7312738	elevating pinion assembly	4

Table 68: T12 Bayonet Parts

Part Name	Drawing Number
blade assembly	C7267649
lever	D7267648
pin	BFSX 2.1 (586077)
grip, left hand	D7267653
grip, right hand	D7267652

LEE EMERSON

screw (two required)	A7266548
spring	B7267645

Table 69: T140 and M76 Grenade Launcher Parts

Part Name	Drawing Number
grenade launcher assembly, T140 and M76	F7267617
sleeve spring, T140	B7267659
handle, T140 or tube and hinge assembly, M76	C7267660
plunger, T140 and M76	C7267661
sleeve assembly, T140	C7267666
long (hinge) pin, T140	B7267669
latch spring, T140 and M76	B7267691
short (latch) pin, T140	B7267692
latching handle assembly, M76	C7790900
short (latch) pin, M76	MS 16562-96

Table 70: T6 Auxiliary Winter Trigger Parts

Part Name	Drawing Number
actuator assembly	B7267640
lever	D7267643
support	C7267639
spring	C7267638
pivot	B7267637
winter trigger assembly	

Table 71: T44E5 Rifle Parts and Recommended Spare Parts

Ordnance Drawing Number	T44E5 Part Description	Number of Spare Parts for Maintenance of 100 Rifles
D6008869	rear sight aperture	4
SA-C-24043	front band	5
SA-F-34831	barrel	6
C7267028	packet charger guide	2
B7267035	connector lock	10
B7267042	connector lock pin	10
BFXS2.1 (586064)	spring pin	2
F7267056	receiver	
D5546001	rear sight base	2

LEE EMERSON

D7267005	bolt assembly	
D7267004	bolt and roller assembly	6
F7267003	bolt	
B7267059	bolt roller retainer	10
B7267065	bolt roller	10
B7267015	cartridge ejector assembly	12
C7267014	cartridge ejector	
B7267077	cartridge ejector spring	
F5546003	extractor	8
C7267043	firing pin	20
B6008618	extractor spring and plunger assembly	15
B5013671	extractor spring plunger	
B6008886	extractor spring	
D7267012	connector assembly	8
D7267011	connector bar	
D7267024	connector spring guide	
B7267050	connector plate	
B7267076	connector spring	
C6008872	rear sight cover	2
SA-C-24048	gas cylinder	4

M14 RIFLE HISTORY AND DEVELOPMENT

	hand guard and band assembly	10
B6008870	rear hand guard band	
SA-C-24050	hand guard	
D7267023	trigger and stop guard assembly	4
D7267022	trigger guard	
B7312633	hammer stop	
SA-B-34122	operating rod guide	4
C7267027	operating rod spring guide	10
D5546008	hammer	4
C6008883	hammer spring housing	2
D7267031	trigger and latch housing assembly	4
F7267030	trigger housing	
C7267032	magazine latch	5
BFSX2.1 (586081)	spring pin	9
B7267041	magazine latch spring	5
D7312737	rear sight windage knob assembly	4
D7312735	rear sight windage knob	
C7312731	rear sight lock nut	
C7312726	rear sight nut	

LEE EMERSON

B7312728	rear sight nut retainer	
C7267034	bolt lock	5
SA-B-24054	gas cylinder lock	4
C7267172	selector shaft lock	5
D7267038	magazine assembly	1000
C7267019	magazine and stop follower assembly	
D7267018	magazine follower	
B7267085	follower stop	
C7267051	magazine floor plate	
C7267078	magazine spring	
D7267091	magazine tube	
SA-B-31699	stabilizer nut	5
B5013668	hammer pin	4
BFSX2.1 (586072)	spring pin	10
BFSX2.1 (586045)	spring pin	2
BFSX2.1 (586070)	spring pin	20
B5013669	trigger pin	4
D7312738	rear sight elevating pinion assembly	4
C7312733	indexing dog assembly	
C7312725	indexing dog	

M14 RIFLE HISTORY AND DEVELOPMENT

B7312729	rear sight screw retainer	
C7312730	rear sight screw	2
BEAX1 (138534)	lock tooth type washer	
D7312734	rear sight elevating knob	
D7312736	rear sight elevating pinion	
D7312727	dog retainer	
D7312732	rear sight spring	
D7267047	piston	4
C7267053	gas cylinder plug	4
B6008880	hammer spring plunger	2
D7267058	sear release	5
D7267064	operating rod assembly	8
F7267029	operating rod handle	
B7267092	operating rod tube	
D7267066	safety	2
D7267067	front sight screw	2
SA-B-31946	stabilizer nut lock screw	10
C7267071	selector	5
C7267072	selector shaft	5
D7267073	front sight	2

LEE EMERSON

B7267074	bolt lock spring	5
B6008887	hammer spring	4
B7267079	operating rod spring	5
B7267080	safety spring	5
B7267081	selector spring	5
SA-F-33598	heavy barrel stock assembly	10
SA-A-24049	stock ferrule	
SA-C-34120	stock liner	
SA-D-32057	butt hinge plate assembly	
D6147465	butt plate cap	
A5152865	butt plate cap pin	
SA-C-32056	butt plate assembly	
B5152864	butt plate plunger	
B5152863	butt plate plunger spring	
SA-C-32055	shoulder rest plate	
SA-A-33364	shoulder rest hinge pin	
CCAX1 (104918)	ball	
SA-A-33974	setscrew	
A5013747	shoulder rest spring	
C6008881	long butt plate screw	2

M14 RIFLE HISTORY AND DEVELOPMENT

B6146873	small butt plate screw	2
C6008889	butt swivel	2
BMCX1.3 (106886)	truss head rivet	10
SA-B-38554	left side stock screw	4
SA-B-38555	right side stock screw	4
SA-F-34119	stock	
C7267089	front swivel assembly	2
B7267007	front swivel bracket	
B7267037	front swivel loop	
SA-D-31921	flash suppressor	5
C7267090	trigger and sear assembly	4
A5013673	sear pin	
D7267070	sear	
D5546020	trigger	

U. S. Army Technical Manual 9-1005-223-35 July 1968 lists the maximum parts quantity allowed at the Direct Support (DS), General Support (GS) and Depot Maintenance levels.

Table 72: M14 Rifle Spare Parts Allowance for 100 Rifles

M14 Rifle Part	DS 30 Days for 100 Rifles	GS 30 Days for 100 Rifles	Depot Maintenance for 100 Rifles
magazine	6	4	15
hand guard assembly	2	2	20
small arms sling	2	2	
trigger pin	2	2	12
trigger and sear assembly	2	2	6
hammer spring housing	2	2	6
ejector spring	2	2	12
hammer spring plunger	2	2	4
hammer pin	2	2	8
hammer	2	2	12
safety	2	2	10
safety spring	2	2	12
trigger guard	2	2	12
trigger housing assembly	2	2	6
magazine latch pin	2	2	100
magazine latch	2	2	6
magazine latch spring	2	2	6
stock subassembly	2	2	20

M14 RIFLE HISTORY AND DEVELOPMENT

upper butt stock screw	2	2	6
stock nut retainer	2	2	12
stock nut	2	2	12
lower butt stock screw	2	2	12
butt swivel	2	2	6
hinged butt plate assembly	2	2	12
butt plate hinge pin			24
butt plate stop pin			24
butt plate rest (flapper)			10
butt plate ball bearing			10
butt plate hinge spring			10
butt plate door pin			10
butt plate door catch			10
butt plate door catch spring			10
connector assembly	2	2	6
connector pin	2	2	300
connector plunger			12
connector spring			12
operating rod spring guide	2	2	6
operating rod spring	2	2	24

LEE EMERSON

operating rod	2	2	8
extractor	2	2	24
ejector with spring	2	2	24
extractor spring plunger	2	2	12
firing pin	2	2	48
bolt	2	2	12
bolt roller	2	2	24
bolt roller retainer	2	2	24
elevation knob and pinion assembly	2	2	20
windage knob	2	2	24
rear sight aperture	2	2	6
rear sight cover	2	2	6
rear sight base	2	2	6
selector shaft lock	2	2	6
selector switch	2	2	6
selector shaft spring	2	2	6
selector shaft	2	2	10
sear release	2	2	6
gas cylinder plug	2	2	20
gas piston	2	2	6

M14 RIFLE HISTORY AND DEVELOPMENT

flash suppressor setscrew	2	2	24
flash suppressor nut	2	2	12
flash suppressor	2	2	20
front sight screw	2	2	12
front sight	2	2	12
gas cylinder lock	2	2	12
gas cylinder	2	2	12
spindle valve	2	2	6
spindle valve spring	2	2	24
front band	2	2	10
operating rod guide pin	2	2	100
operating rod guide	2	2	6
bolt lock pin	2	2	100
bolt lock	2	2	6
bolt lock spring	2	2	20
connector lock pin	2	2	100
connector lock	2	2	6
cartridge clip guide pin	2	2	100
cartridge clip guide	2	2	5
barrel			20

The U. S. Army Combat Developments Command Experimentation Command tested several U. S. and Soviet made small arms from October 22, 1965 to February 21, 1966 at Fort Ord, CA. This field experiment was designed to determine the reliability and fire effectiveness of these weapons. The malfunction rate for the 120 M14 rifles used in the experiment was 0.63 per 1000 rounds fired. As part of data collected, the replacement of M14 rifle parts was kept track of. The data in the table below is reproduced from the final report. The number of mean rounds fired between part replacement was 4,372 for all M14 rifles used in the experiment. For the sixty-nine M14 rifles that did require a new part, the mean number of rounds fired between replacement was 2,908. Notes: a) RIBPR = Round Interval Between Parts Replacement b) total rounds fired = 327,903

Table 73: M14 Rifle Parts Replacement

Parts Replaced	RIBPR 1 to 1000	RIBPR 1000 to 2000	RIBPR 2001 to 3000	RIBPR 3001 to 4000	RIBPR 4001 to 5000	RIBPR 5001 to 6000	Total Each Part
extractor		3	4				7
firing pin (non-chrome)			10	11	4		25
butt plate		3	1				4
bolt			1	1			2
stock assembly		1	1				2
pinion assembly			1	1			2
ejector		1	5				6
bolt roller		2					2
windage knob			1				1
bolt (lock) pin		4					4
trigger pin			1				1
straight pin		1	1				2

M14 RIFLE HISTORY AND DEVELOPMENT

front sight setscrew			1				1
selector		1	1				2
gas piston		1					1
gas cylinder plug			1				1
retainer pin			1				1
hammer spring		1					1
rear sight aperture			1				1
bolt lock			1				1
front sight		1					1
rear sight base			1				1
operating rod spring guide		1					1
miscellaneous unidentified parts		1	3	1			5
Totals	0	21	36	14	4	0	75
Rifles firing within round interval	120	120	96	34	11	2	

In the 1965-66 Fort Ord field experiment, the M14E2 automatic rifle was also extensively tested for reliability and fire effectiveness. The malfunction rate for sixty-four M14E2 rifles tested was 0.47 per 1000 rounds fired. Replacement of M14E2 rifle parts was kept track of during the test. The data in the table below is reproduced from the final report. The number of mean rounds fired between part replacement was 7,017 for all seventy M14E2 rifles used in the experiment. For the eighteen M14E2 rifles that did require a new part, the mean number of rounds fired between replacement was 1,929. Notes: a) RIBPR =

Round Interval Between Parts Replacement b) total rounds fired = 140,346

Table 74: M14E2 Rifle Parts Replacement

Parts Replaced	RIBPR 1 to 1000	RIBPR 1000 to 2000	RIBPR 2001 to 3000	RIBPR 30001 to 4000	RIBPR 4001 to 5000	Total Each Part
muzzle stabilizer (second version)	3					3
trigger pin	2					2
windage knob		1				1
gas cylinder	1					1
extractor	1			1		2
gas piston	1					1
bolt	2					2
rear (front?) sight setscrew	1					1
stock assembly		1				1
butt plate			1			1
firing pin	2					2
bolt lock	1					1
retainer pin	1					1
miscellaneous unidentified parts	1					1
Totals	16	2	1	1		20

M14 RIFLE HISTORY AND DEVELOPMENT

Rifles firing within round interval	70	61	35	9	3	
-------------------------------------	----	----	----	---	---	--

Bibliography

U. S. Government Documents and Media

Armed Forces Network. "Countering Snipers, Iraq." U. S. Army Specialist Samantha Szesciorka: January 22, 2007.

CECOM Historical Office. "A History of the United States Army Communications-Electronics Command (CECOM)." Fort Monmouth, New Jersey: March 1990.
www.monmouth.army.mil/cecom/pae/historian/updates/13.htm

Code of Federal Regulations Title 27 www.gpoaccess.gov/ecfr/

Commandant, U. S. Marine Corps. "Contact Ambush." 16 mm film converted to DVD. Department of the Navy: 1966. National Technical Information Service AVA04620VNB1.

Commander In Chief Pacific. *Commander In Chief Pacific Command History 1966 Volume 1*. FPO San Francisco 96610: June 03, 1967.

Commander In Chief Pacific. *Commander In Chief Pacific Command History 1968 Volume 1*. FPO San Francisco 96610: May 08, 1969.

Commander In Chief Pacific. *Commander In Chief Pacific Command History 1969 Volume 2*. FPO San Francisco 96610: 1970.

Commander Marine Corps Systems Command Quantico, VA message dated 311914Z Aug 10.

Defense Logistics Services Center. *Federal Supply Code for Manufacturers, United States and Canada*. Defense Logistics Agency. Battle Creek, MI: 1988.

Department of Agriculture. *Income Opportunities in Special Forest Products*. Forest Service Agriculture Information Bulletin 666: May 1993.

Department of Defense. *MIL-L-46000C Lubricant, Semi-fluid (Automatic Weapons)*. February 25, 1987.

Department of Defense. *MIL-PRF-10924G Grease, Automotive and Artillery*. September 24, 1998.

Department of Defense. *MIL-PRF-14107D Lubricating Oil, Weapons, Low Temperature*. October 20, 2000.

Department of Defense. *MIL-PRF-63460E Lubricant, Cleaner and Preservative for Weapons and Weapons Systems*. March 15, 2006.

Department of Defense. *MIL-STD-171E Department of Defense Manufacturing Process Standard Finishing of Metal and Wood Surfaces*. 23 June 1989.

Department of Defense. *MIL-STD-1913 Dimensioning of Accessory Mounting Rail for Small Arms Weapons*. February 03, 1995.

Department of Defense. *MIL-STD-3004A with Change 1 Quality Surveillance For Fuels, Lubricants, and Related Products*. April 15, 2004.

Department of Defense. *QPL-63460-32 Military Qualified Products List of Products Qualified under Performance Specification MIL-PRF-63460 Cleaner, Lubricant and Preservative for Weapons and Weapons Systems*. July 28, 2006.

Department of Defense. *QPL-46003-10 Military Qualified Products List of Products Qualified under Performance Specification MIL-G-46003 Grease, Rifle*. March 02, 1992.

Department of Justice. *NCIC 2000 Code Manual*. Washington, DC: December 2000.

Department of Justice, Bureau of Alcohol, Tobacco, Firearms, and Explosives. *Annual Firearms Manufacturing and Export Report*. Washington, DC: 1998 through 2011.

Department of Justice, Bureau of Alcohol, Tobacco, Firearms, and Explosives. Letter to Lee E. Emerson. Martinsburg, WV: May 21, 2007.

Department of Justice, Bureau of Alcohol, Tobacco, Firearms, and Explosives. "Open Letter To Federally Licensed Firearms Importers and Registered Importers of U.S. Munitions Import List Articles." July 13, 2005.

Department of Justice, Bureau of Alcohol, Tobacco, Firearms, and Explosives. "Revised Open Letter To Federally Licensed Firearms Importers and Registered Importers of U.S. Munitions Import List Articles." August 12, 2005.

Department of Justice, Bureau of Alcohol, Tobacco, Firearms, and Explosives. *State Laws and Published Ordinances 30th ATF Publication Edition P5300.5*. Office of Enforcement Programs and Services, Firearms Programs Division: December 2010.

Department of War. *TB 9X-115 War Department Technical Bulletin: Preliminary Instructions - Rifle, Cal. .30, T20E2*. Washington, DC: June 28, 1945.

Department of the Air Force, Air Force Materiel Command. Supplement 1 dated 23 August 2004 to Air Force Instruction 36-2226 of 26 February 2003. Wright-Patterson Air Force Base, OH.

Department of the Army. "Be Your Own Inspector The M14 Rifle." *PS Magazine The Preventative Maintenance Monthly* December 1961: 2-12.

Department of the Army. "Everything You Always Wanted To Know About Bayonet-Knives And Scabbards But Were Too Shy To Ask." *PS Magazine The Preventative Maintenance Monthly*.

Department of the Army. Historical Summary: FY 1980 Chapter 11 Research, Development, and Acquisition. www2.army.mil/cmh-pg/books/DAHSUM/1980/ch11.htm

Department of the Army. Historical Summary: FY 1981 Chapter 11 Research, Development, and Acquisition. www2.army.mil/cmh-pg/books/DAHSUM/1981/ch11.htm

Department of the Army. Memorandum for the Undersecretary of the Army: Treasury Department Opinion Concerning M14M Rifle Sale. Office of the General Counsel. Washington, DC: March 20, 1978.

Department of the Army. *MIL-C-43681A(GL) Military Specification Case, Maintenance Equipment, Small Arms, M14A1*. 18 July 1973.

M14 RIFLE HISTORY AND DEVELOPMENT

Department of the Army. *MIL-S-11595D Military Specification Steel, Bars and Blanks (Under 2 Inches In Diameter) For Barrels of Small Arms Weapons*. January 03, 1966.

Department of the Army. *SC 1305/30-IL Ammunition and Explosives: Classes 1305 through 1330*. July 29, 1977.

Department of the Army. *Small Arms Weapon Systems Analysis: A Review and Evaluation*. Office of the Chief of Staff. June 1967.

Department of the Army. *U. S. RIFLE, CAL. 7.62 MM M-14*. T. F. 9 2970: 1960.

Department of the Army, Aberdeen Research and Development Center. *Technical Report No. 1 M16 Rifle System Reliability and Quality Assurance Evaluation*. Aberdeen Proving Ground, MD: July 1968.

Department of the Army, ARDEC. *MIL-S-45921A Military Specification Stock, Gun, Shoulder: Assembly w/o Butt Plate, Fiberglass Reinforced, Plastic (Premix) (For Rifle, 7.62MM: M14)*. 22 June 1993.

Department of the Army, Armament Research, Development & Engineering Center. Technical Data Package List: 726700:19205. Picatinny, NJ: July 18, 2006.

Department of the Army, Armament Research, Development & Engineering Center. Technical Data Package List: 9386973:19200. Picatinny, NJ: July 18, 2006.

Department of the Army, Army Infantry School. *Special Text 7-179 U.S. Rifles, 7.62-MM, M14 and M15*. Fort Benning, GA: December 1958.

Department of the Army, Army Materials & Mechanics Research Center. *MIL-C-13924C Coating, Oxide, Black, for Ferrous Metals*. Watertown, MA: 9 June 1980.

Department of the Army, Army Materials & Mechanics Research Center. *MIL-C-13924C Amendment 1 Coating, Oxide, Black, for Ferrous Metals*. Watertown, MA: 30 September 1987.

Department of the Army, Army Materials & Mechanics Research Center. *MIL-W-12332A(MR) Military Specification Welding, Resistance, Spot, Seam, and Projection For Fabricating Assemblies of Low-Carbon Steel*. Watertown, MA: 14 December 1964.

Department of the Army, Army Pictorial Center. *Weapons of the Infantry*. T.F. 3893: 1967.

Department of the Army, Combat Developments Command. *Rifle Evaluation Study (U)*. December 20, 1962.

Department of the Army, Combat Developments Command Experimentation Command. *Small Arms Weapon Systems Field Experiment*. Fort Ord, CA: May 10, 1966.

Department of the Army, Corps of Engineers. *EM 1110-2-1424 Engineering and Design Lubricants and Hydraulic Fluids*. Washington, DC: February 28, 1999.

Department of the Army, General Equipment Test Activity. *Engineering Test of Carrier, Combination Tool and Cleaning Material for Rifle, 7.62MM, M14E2 Final Report*. Fort Lee, VA: August 1966.

Department of the Army, Headquarters. *Army Regulation 920-25*. Washington, DC: February 08, 1965.

Department of the Army, Headquarters. *FM 3-21.5 Drill and Ceremonies*. Washington, DC: July 2003. www.adtdl.army.mil/cgi-bin/atdl.dll/fm/3-21.5/toc.htm

Department of the Army, Headquarters. *FM 7-8 Infantry Rifle Platoon and Squad*. Washington, DC: April 22, 1992.

Department of the Army, Headquarters. *FM 22-5 Drill and Ceremonies*. Washington, DC: December 08, 1986.

Department of the Army, Headquarters. *FM 23-8 U. S. Rifle 7.62-MM M14*. Washington, DC: December 1959.

Department of the Army, Headquarters. *FM 23-8 U.S. Rifle 7.62MM, M14 and M14E2*. Washington, DC: May 1965.

Department of the Army, Headquarters. *FM 23-8 M14 and M14A1 Rifles and Rifle Marksmanship*. Washington, DC: 15 April 1974.

Department of the Army, Headquarters. *FM 23-10 Sniper Training*. Appendix B M21 Sniper Weapon System. Washington, DC: 17 August 1994. www.globalsecurity.org/military/library/policy/army/fm/23-10/Appb.htm

Department of the Army, Headquarters. *FM 23-16 Automatic Rifle Marksmanship*. Washington, DC: June 1965.

Department of the Army, Headquarters. *FT 7.62-A-2 with Change 1 Firing Tables Gun, Machine, 7.62MM, M60 on Mount, Machine Gun, 7.62MM, M122 and Rifle, 7.62MM, M14*. Washington, DC: October 30, 1964.

Department of the Army, Headquarters. *MWO 9-1005-223-30/1 M14A1 Muzzle Stabilizer*. Washington, DC: April 08, 1968.

Department of the Army, Headquarters. *TB 9-1005-223-30/3 Rifle, 762-MM, M14: Storage Compartment for Flash Suppressor Alignment Tool*. Washington, DC: March 05, 1962.

Department of the Army, Headquarters. *TM 9-1005-223-10 Operator's Manual for Rifle, 7.62-MM, M14, W/E; M14A1, W/E; M2 Rifle Bipod*. Washington, DC: March 1972.

Department of the Army, Headquarters. *TM 9-1005-223-12 Operation and Organizational Maintenance 7.62-mm Rifle M14*. Washington, DC: October 1959.

Department of the Army, Headquarters. *TM 9-1005-223-12 Operator and Organizational Maintenance Manual 7.62-mm Rifle M14 and Rifle Bipod M2*. Washington, DC: May 1961.

Department of the Army, Headquarters. *TM 9-1005-223-12 Operator and Organizational Maintenance Manual 7.62-MM Rifle M14 and Rifle Bipod M2*. Washington, DC: January 1963.

Department of the Army, Headquarters. *TM 9-1005-223-12 Operator and Organizational Maintenance Manual with Repair Parts and Special Tools List for Rifles, M14 and M14E2, and Bipod, Rifle, M2* Washington, DC: 8 February 1965.

Department of the Army, Headquarters. *TM 9-1005-223-12P Operator's and Organizational Maintenance Repair Parts and Special Tool Lists for Rifle, 7.62-mm, M14 (National Match) and Rifle, 7.62-mm, M14 (M)*. Washington, DC: 23 February 1968.

Department of the Army, Headquarters. *TM 9-1005-223-20 Organizational Maintenance Manual including Repairs and Special Tools Lists. Rifle, 7.62-mm, M14, W/E, Rifle 7.62-mm, M14A1, W/E. Bipod, Rifle, M2*. Washington DC: August 1972.

Department of the Army, Headquarters. *TM 9-1005-223-34 7.62-MM Rifle M14 and Rifle Bipod M2*. Washington, DC: 7 September 1961.

Department of the Army, Headquarters. *TM 9-1005-223-34 Direct Support and General Support Maintenance Manual Including Repair Parts and Special Tools Lists (Including Depot Maintenance Repair Parts and Special Tools) Rifle, 7.62-mm, M14, W/E, Rifle, 7.62-mm, M14A1, W/E, Bipod, Rifle, M2*. Washington, DC: 2 August 1972.

Department of the Army, Headquarters. *TM 9-1005-223-35 Direct Support, Central Support, and Depot Maintenance Manual Including Repair Parts and Special Tools List: Rifle, 7.62-MM: M14, W/E Rifle, 7.62-MM: M14A1, W/E Bipod, Rifle: M2*. Washington, DC: July 1968.

Department of the Army, Headquarters. *TM 9-1005-319-10 Operator's Manual W/ Components List Rifle, 5.56-MM, M16A2 W/E (1005-01-128-9936)*. Washington, DC: August 1986 with Change 3 dated May 01, 1994.

Department of the Army, Headquarters. *TM 9-1305-201-20&P Organizational Maintenance Manual (Including Repair Parts and Special Tools List) for Small Arms Ammunition to 30 Millimeter Inclusive (FSC 1305)*. Washington, DC: October 1981.

Department of the Army, Headquarters. *TC 23-14 Sniper Training and Employment*. Washington, DC: 14 June 1989.

Department of the Army, Headquarters. *FM 23-10 Sniper Training*. Washington, DC: 17 August 1994.

Department of the Army, Headquarters. *TM 43-0001-27 Army Ammunition Data Sheets Small Caliber Ammunition*. Washington, DC: Change 6 December 06, 2002.

Department of the Army, Materiel Command. *Technical Report 68-4 M14 Rifle Cost Analysis Report*. Washington, DC: October 1968.

Department of the Army, Office of the Adjutant General. *Lessons Learned, Headquarters, 2^d Infantry Division*. Washington, DC: May 15, 1970.

Department of the Army, Office of the Adjutant General. *Lessons Learned, Headquarters, 3^d Howitzer Battalion, 6th Artillery*. Washington, DC: November 01, 1966.

Department of the Army, Office of the Adjutant General. *Lessons Learned, Headquarters, 5th Battalion, 2^d Artillery*. Washington, DC: April 20, 1970.

Department of the Army, Office of the Adjutant General. *Lessons Learned, Headquarters, 89th Military Police Group*. Washington, DC: August 15, 1966.

Department of the Army, Ordnance Corps. *Infantry and Aircraft Weapons Division Report On Test of Blank-Firing Attachments For The 7.62-MM, M14 Rifle and M60 Machine Gun Report No. DPS-234*. Aberdeen Proving Ground, Development and Proof Services: May 1961.

Department of the Army, Ordnance Corps. *Instructor Guide CMT-IG Number 38*. Preventive Maintenance Agency, Raritan Arsenal, Metuchen, NJ: 2 January 1958.

Department of the Army, Ordnance Corps. *MIL-G-46003(Ord) Grease, Rifle*. August 21, 1961.

Department of the Army, Ordnance Corps. *ORDP-608-R-SA1 Rifle, 7.62-MM, M14*. Springfield Armory, Springfield, MA: April 1959.

Department of the Army, Ordnance Corps. *SA-SIP-7790476 Rifle, U.S. 7.62-MM, M14 National Match*. Springfield Armory, Springfield, MA: January 1966.

Department of the Army, Test & Evaluation Command. *USATECOM Project No. 8-5-0400-04 Small Arms Weapons Study USAIB Project No. 3110*. Fort Benning, FA: December 1965.

Department of the Army, Test & Evaluation Command. *APG Report No. APG-MT-5746 Final Report Technical Feasibility Test of M16A1E1 Rifle*. Aberdeen Proving Ground, MD: February 1983.

Department of the Army, United States Army Infantry Center Directorate for Combat Developments Small Arms Division and Armament Research Development & Engineering Center. *Project Manager Soldier Weapons Soldier Weapons Assessment Team Report 6-03 Operation Iraqi Freedom*. Soldier Weapons Assessment Team - Iraq: July 31, 2003.

Department of the Army, Watertown Arsenal Laboratories. *Assessment of 9310 Steel for Carburized Components in M14 Rifles*. Watertown, MA: July 1962.

Department of the Army, Watertown Arsenal Laboratories. *Mechanical and Metallurgical Properties of Carburized 8620H Steel For M14 Rifle Components*. Watertown, MA: November 1961.

Department of the Army, Weapons Command. Letter to Mr. H. A. Shephard, President, TRW from Major General Nelson M. Lynde, Jr. April 11, 1963.

Department of the Army, Weapons Command. *MIL-G-46003A(WC) Grease, Rifle*. Rock Island Arsenal, Rock Island, IL: December 31, 1976.

Department of the Army, Weapons Command. *MIL-R-45012E Military Specification Rifle, 7.62MM: M14*. 6 January 1971.

Department of the Army, Weapons Command. *MIL-R-45979 Military Specification Rifle, 7.62MM: M14, National Match*. 24 September 1976.

Department of the Army, Weapons Command. *MIL-STD-1270A(WC) Patching Of Wood Stocks For The 7.62MM, M14, and M14E2 Rifles*. 26 August 1966.

Department of the Navy. FY 2006 President's Budget. <http://public.secnav.navy.mil/fy07.nsf/Welcome?openframeset>

Department of the Navy. FY 2007 President's Budget. <http://public.secnav.navy.mil/fy07.nsf/Welcome?openframeset>

Department of the Navy, Naval Surface Warfare Center. *SW370-A2-OPI-010 Operator's Manual for Rifle, 7.62MM Mk14 Mod 0, Enhanced Battle Rifle (EBR)*. Crane, Indiana: October 01, 2002.

Department of the Navy. *SECNAV INSTRUCTION 5060.22*. May 26, 1981.

Department of the Navy, United States Marine Corps. *MCO P5060.20 Marine Corps Drill and Ceremonies Manual*. Washington, DC: May 05, 2003.

Department of the Navy, United States Marine Corps. *TM 02648C-24&P/2 U.S. Marine Corps Technical Manual Organization and Intermediate Maintenance Manual, including repair parts and special tools lists for Rifle, 7.62-MM, M14, DMR W/E*. Quantico, VA: July 2000.

Department of the Treasury Bureau of Alcohol, Tobacco and Firearms. *Firearms Identification for Law Enforcement Officers*. Department of the Treasury/ Internal Revenue Service/ATFD Publication 674 (8-70).

Department of the Treasury Bureau of Alcohol, Tobacco and Firearms. *Identification of Firearms Within the Purview of the National Firearms Act*. Department of the Treasury/ ATF P 5300.1 (1-75).

Department of the Treasury Bureau of Alcohol, Tobacco and Firearms. Letter to Mr. Martin Pearl from Edward M. Owen, Jr. Washington, DC: August 21, 1980.

Department of the Treasury Bureau of Alcohol, Tobacco and Firearms. Letter to Mr. Lloyd Hahn from Edward M. Owen, Jr. Washington, DC: June 08, 1994.

Department of the Treasury Bureau of Alcohol, Tobacco and Firearms. Letter to Mr. Lloyd Hahn from Naomi L. Rubarts. Washington, DC: March 22, 1995.

Department of the Treasury Internal Revenue Service Revenue Ruling 58-417 http://www.cs.cmu.edu/afs/cs/usr/wbardwell/public/nfalist/rr_58417.txt

Department of the Treasury Office of Public Affairs. "Treasury Prohibits Importation Of Certain Semiautomatic Assault Rifles RR-2347." Washington, DC: April 06, 1998. www.ustreas.gov/press/releases/rr2347.htm

Gaskill, Gerald. "Navy Small Arms Program Status & Way Ahead JSSAP." Naval Surface Warfare: 15 May 2006.

General Services Administration Federal Supply Service. *QQ-C-320B Federal Specification Chromium Plating (Electrodeposited)*. Washington, DC: June 17, 1974.

Intrec, Inc. for Defense Advanced Research Projects Agency. "The Evaluation of Small Arms Effectiveness Criteria, Volumes I and II." May 1975.

Kay, Bruce F. *An Analysis of The Infantry's Need For An Assault Submachine Gun. Thesis for Master of Military Art and Science.* U. S. Army Command and General Staff College, Fort Leavenworth, KS: June 10, 1977.

National Archives & Records Administration. Record Group 338: Records of the U. S. Army Commands. NWME Electronic and Special Media Records Services Division National Archives at College Park 8601 Adelphi Road College Park, MD 20740.

Naval Surface Warfare Center. *Initial Test / Acceptance Sheet - Rifle, 7.62mm M14 - USCG.* October 2005.

Panda, J. F. *Investment Cast Components for SPIW Report No. SA-TR11-4002.* Springfield Armory: Springfield, MA, July 27, 1966.

Presidential Documents. Executive Order 12850 of May 28, 1993. Federal Register Vol. 58 No. 103 June 1, 1993.

Project Manager's Weekly Significant Action Report. Project: Rifles. 8 February Thru 12 February 1965.

Project Manager's Weekly Significant Action Report. Project: Rifles. 10 -14 June 1968.

Project Manager's Weekly Significant Action Report. Project: Rifles. 18 - 22 November 1968.

SAA Pamphlet. *Cartridge, 7.62mm, NATO, Ball, Duplex, M198.* July 1967.

SAA Pamphlet. *Cartridge, 7.62mm, Inert Loaded, M172.* July 1967.

Springfield Armory. "Development of M14 Rifle to Match Grade." Memo from Chief, Project Coordinating Board to Chief, Engineering Division: July 01, 1960.

Springfield Armory. "Development of M14 Rifle to Match Grade." Memo from Chief, Engineering Division to Assistant for Plans & Programs: July 06, 1960.

Springfield Armory. *Historical Development of the M14 Rifle 1945 - 1961.* Springfield, MA: 1961.

Springfield Armory. *Investigation of Problems Related to M14 Rifle Failures.* Springfield, MA: May 08, 1961.

Springfield Armory. *Nondestructive Inspection of Receivers for 7.62mm M14 Rifle by Electromagnetic Methods SA-TR19-1505.* Springfield, MA: April 06, 1961.

Springfield Armory. *Properties and Methods of Nondestructive Testing of Receivers for 7.62MM M14 Report SA-TR19-1506.* Springfield, MA: November 07, 1961.

Springfield Armory. *SA-TN11-1094.* Springfield, MA: December 16, 1957.

Springfield Armory. *SA-TR11-2643 Evaluation of Pretreatment Processes And Long-Term Storage On Magazine Spring For The M14, 7.62MM, Rifle.* Springfield, MA: February 01, 1966.

Springfield Armory. *SA-TR19-1507 Properties and Methods of Nondestructive Testing of Bolts for 7.62mm M14 Rifles.* Springfield, MA: January 04, 1962.

M14 RIFLE HISTORY AND DEVELOPMENT

- Springfield Armory Research and Development. *Notes On Development Type Materiel Rifle. Caliber .30, T44E4 Report SA-NM11-2612*. Springfield, MA: June 17, 1955.
- Springfield Armory Research and Development. *Notes On Development Type Materiel Rifle. Caliber 7.62MM, T44E5 (M15) Report SA-NM11-2617*. Springfield, MA: March 27, 1958.
- Springfield Armory Research and Engineering. *Engineering Development and Operational Characteristics of Rifle, 7.62mm, M14E2*. Springfield, MA: December 18, 1963.
- U. S. Army. Fact Sheet Infantry Weapons No. 2 January 1972 M6 Bayonet
- U. S. Army Arctic Test Center. *Service Test of Lubricants For M14 and M16A1 Rifles Under Arctic Winter Conditions*. APO Seattle 98733: April 08, 1968.
- U. S. Army Center for Army Lessons Learned. *The Modern Warrior's Combat Load Dismounted Operations in Afghanistan April - May 2003*. Task Force Devil Combat Arms Assessment Team.
- U. S. Army Combat Developments Command. *Rifle Evaluation Study*. Declassified excerpts. 20 Dec 1962.
- U. S. Army Human Engineering Laboratories. *Small Arms Use in Viet Nam: M14 Rifle and .45-Caliber Pistol*. Aberdeen Proving Ground, MD: January 1967.
- U. S. Army Human Engineering Laboratories. *Technical Memorandum 1-65 Auditory and Acoustical Evaluation of Several Shoulder Rifles*. Aberdeen Proving Ground, MD. January 1965.
- U. S. Army Human Engineering Laboratory. *Comparison of Three Shooting Techniques In The Daylight Employment of Tracer*. Aberdeen Proving Ground, MD: August 1973.
- U. S. Army Infantry School. *Characteristics of Infantry Weapons WW101*. Fort Benning, GA: June 1965 and July 1967 printings.
- U. S. Army Infantry School, Headquarters. *Rifle Squad and Platoon Evaluation Program 22 May 61 - 31 July 61*. Fort Benning, GA: November 13, 1961.
- U. S. Army Limited Warfare Laboratory. *Installation and Operation Manual For The Adjustable Ranging Telescope (ART) Mounted On The Match Conditioned 7.62MM M-14 Rifle*. Aberdeen Proving Ground, MD: September 1968.
- U. S. Army Materiel Command. *1967 National Match Rifles U.S. Cal. 7.62MM M14 and U.S. Cal. .30, M1 and National Match Ammunition*. Washington, DC: 1967.
- U. S. Army Weapons Command, Headquarters. *DTM 9-1005-221-10 Rifle, 7.62-MM, XM21, Sniper W/Adjustable Ranging Telescope and Mount With Equipment (1005-179-0300)*. Rock Island, IL: November 1969.
- U. S. Army Weapons Command, Headquarters. *DMWR 9-1005-223 U. S. Army Weapons Command Depot Maintenance Work Requirements for Overhaul of the Rifle, 7.62MM, M14 and Bipod, Rifle, M2*. Rock Island, IL: October 1971.

U. S. Army Weapons Command Quality Assurance Directorate. *Fatigue Behavior of Thick-Walled Cylinders (7.62 MM Rifled Specimens)*. Watervliet Arsenal: Watervliet, NY, June 1972.

U. S. Army Weapons Command Science & Technology Laboratory Research & Engineering Directorate. *Arctic Test For Small Arms Lubricants (Winter 1966-1967)*. Rock Island, IL: February 1969.

U. S. Marine Corps, Headquarters. "A Chronology of the United States Marine Corps, 1965-1969 Volume IV." Compiled by Gabrielle M. Neufeld, Historical Division: 1971.

U. S. Marine Corps. *Technical Instruction TI-02648A-15/6 Cleaning Prior To Firing Rifle, 7.62 MM, M14*. Headquarters U. S. Marine Corps. Washington, DC: November 19, 1962.

U. S. Marine Corps. *Technical Instruction TI-02648A-25/10B Match Condition Procedures M14, Rifle, 7.62MM*. Headquarters U. S. Marine Corps. Washington, DC: 27 November 1972.

U. S. Marine Corps. *The Rifle Basic Marksmanship Series MH 10582 C*. Combat Pictorial Branch: 1970.

United States. *Military Specification Training Aid, Rifle, M-14 Mockup, Two To One Scale Device 3F44 MIL-T-82390 (TD)*. US Government Printing Office: 3 November 1969.

United States v. One Harrington & Richardson Rifle, Model M-14, 7.62 Caliber Serial No. 85279 (U. S. C. A. Sixth Circuit, No. 03-2106, June 09, 2004)

United States v. One U. S. (TRW) 7.62mm M-14 National Match Rifle, Serial No. 1453711, 1980 WL 95647 (S. D. Ohio, May 20, 1980)

United States v. One TRW, Model M14, 7.62 Caliber Rifle, Serial Number 1488973 From William K. Alverson (U. S. C. A. Sixth Circuit, No. 04-5082, March 20, 2006)

United States v. TRW Rifle 7.62x51mm Caliber, One Model 14 Serial 593006 (U. S. C. A. Ninth Circuit, No. 04-16049, May 05, 2006)

United States Army Infantry Board. *Report of Project No 2920 Service Test of Plastic Stocks For Rifle, 7.62mm, M14*. Fort Benning, GA: September 29, 1961.

United States Army Marksmanship Unit. *Accurized National Match M-14 Rifle "M-14 (MTU-NM)"*. Fort Benning, GA.

United States Army Vietnam, Headquarters. *Pamphlet Number 750-11 M14 Rifle Preventive Maintenance*. APO San Francisco 96307: February 01, 1967.

United States House of Representatives. Violent Crime Control and Law Enforcement Act of 1994 H. R. 3355

United States Senate. *Report by Preparedness Investigating Subcommittee of the Committee on Armed Services United States Senate Under the Authority of S. Res. 43 (87th Cong., 1st Sess.) on The M-14 Rifle Program*. Government Printing Office, Washington, DC: 1961.

Vanderhoff, John A., Anthony J. Kotlar and Richard B. Peterson. *Technical Report BRL-TR-2873 CARS Temperature Measurements In the Muzzle Flash Region of a 7.62 MM Rifle*. US Army Ballistic Research Laboratory: Aberdeen Proving Ground, MD, November 1987.

Watertown Arsenal Laboratories. *Photoelastic Stress Analysis of 7.62MM M-14 Rifle Bolt*. Watertown Arsenal Laboratories, MA: August 1961.

Books and Media about the M14 Type Rifle

Buss, Thomas A. *The M14 Collector's Manual*. Self-published: Springdale, PA, 1971 with updates to September 14, 1977.

Duff, Scott A. and CWO John M. Miller. *The M14 Owner's Guide and Match Conditioning Instructions*. Scott A. Duff Publications: Export, PA, 1996.

Dunlap, Robert. *M1 Garand M1A Rifles - American Gunsmithing Institute*. Approximately 90 minutes: VHS and DVD.

Iannamico, Frank. *The Last Steel Warrior U.S. M14 Rifle*. Moose Lake Publishing, LLC: Henderson, NV, 2005.

Kuhnhausen, Jerry. *The U. S. .30 Caliber Gas Operated Service Rifles A Shop Manual Volumes I & II*. VSP Publishers: McCall, Idaho, 1995.

Kuleck, Walt and Clint McKee. *The M14 Complete Assembly Guide*. Scott A. Duff Publications: Export, PA, 2006.

Luppino, Art. *Center X M1A/M14 Maintenance & Cleaning for Improved Accuracy*. Lenny Magill Productions: San Diego, CA, 1992. Approximately 120 minutes: VHS and DVD.

Poyer, Joe. *The M-14 Type Rifle A Sporter's and Collector's Guide*. North Cape Publications: Tustin, CA, 1997.

Senich, Peter R. *The Long-Range War Sniping In Vietnam*. Paladin Press: Boulder, CO, 1994.

Senich, Peter R. *The One-Round War: USMC Scout-Snipers in Vietnam*. Paladin Press: Boulder CO, 1996.

Skennerton, Ian D., Producer. *7.62mm U.S. M14 RIFLE*. Ray Riling Arms Books: Philadelphia, PA, 2005.

Smith Enterprise, Inc. *M21A5 C-IED / M14SE Rifle Powerpoint Presentation And Other SEI Offerings, Videos & Pictures*. 2008 Compact Disc.

Stevens, R. Blake. *U.S. Rifle M14 from John Garand to the M21 Revised Second Edition*. Collector Grade Publications: Cobourg, Ontario, Canada, 1991.

Other Books

Askeland, Donald R. *The Science and Engineering of Materials Third Edition*. PWS Publishing Company: Boston, 1994.

Bellavia, David and John R. Bruning. *House To House*. Pocket Star Books: New York, 2007.

- Bowden, Mark. *Black Hawk Down A Story of Modern War*. Penguin Books: New York, 1999.
- Culbertson, John J. *Operation Tuscaloosa: 2nd Battalion, 5th Marines at An Hoa, 1967*. Airtime Publications, 2002.
- Cunningham, Gary M. *American Military Bayonets of the 20th Century*. Scott A. Duff Publications: Export, PA, 1996.
- Daughterty, Leo J. and Gregory Louis Mattson. *Nam A Photographic History*. Michael Friedman Publishing Group, Inc.: New York, 2001.
- DeGarmo, E. Paul, J. Temple Black and Ronald A. Kohser. *Materials and Processes in Manufacturing 7th Edition*. Macmillan Publishing Company: New York, 1988.
- Drez, Ronald J. and Douglas Brinkley. *Voices of Courage The Battle for Khe Sanh, Vietnam*. Bulfinch Press: New York, 2005.
- Duff, Scott A. and David C. Clark (Editor). *The M1 Garand, World War II: History of development and production, 1900 through 2 September 1945 2nd Edition*. Scott A. Duff Publications: Export, PA, 1996.
- Durant, Michael J. with Steven Hartov. *In The Company of Heroes*. New American Library: New York, 2003.
- Ezell, Edward C. *Small Arms of the World 6th Edition*. Stackpole Books: Mechanicsburg, PA, 1960.
- Ezell, Edward C. *Small Arms of the World 11th Edition*. Stackpole Books: Mechanicsburg, PA, 1977.
- Ezell, Edward C. *The Great Rifle Controversy*. Stackpole Books: Harrisburg, PA, 1984.
- Ezell, Edward C. *The Search For A Lightweight Rifle: The M14 and M16 Rifles*. Doctoral dissertation, Case Western University: June 1969.
- Faas, Horst and Tim Page, Ed. *Requiem*. Random House: New York, 1997.
- Fjestad, Steven P. *Blue Book of Gun Values Twenty-Eighth Edition*. Blue Book Publications, Inc.: Minneapolis, MN, 2007.
- Fuller, Stephen L. *United States Martial and Collectors Arms*. Military Arms Research Service: San Jose, CA, 1977.
- Glenn, Russell W., Ed. *Capital Preservation: Preparing for Urban Operations in the 21st Century*. Rand Corporation: Santa Monica, CA, 2001.
- Griffiths, Philip Jones. *Vietnam Inc.* Phaidon Press Inc.: New York, 2001 reprint of the 1971 edition.
- Hardin, Jr., Albert Nolan. *The American Bayonet*. Riling and Lenz: Philadelphia, PA, 1964.
- Henderson, Charles W. *Marine Sniper: 93 confirmed kills*. Stein and Day: New York, 1986.
- Hildreth, Ray and Charles W. Sasser. *Hill 488*. Pocket Books: New York, 2003.

- Houze, Herbert G. *Winchester Repeating Arms Company Its History & Development From 1865 to 1981*. Krause Publications: Iola, WI, 1994 and 2004.
- Jacques, Maurice J. and Major Bruce H. Norton. *Sergeant Major, U. S. Marines*. Ballantine Books: New York, 1995.
- Jarrett, William S., Ed. *Shooter's Bible 1987 Edition No. 78*. Stoeger Publishing Company: South Hackensack, NJ, 1986.
- Jones, Denny A. *Principles and Prevention of Corrosion Second Edition*. Prentice Hall, Inc.: Upper Saddle River, NJ, 1996.
- Kugler, Ed. *Dead Center*. Ivy Books: New York, 1999.
- Lawrence, Richard Russell, Ed. *The Mammoth Book of Special Ops*. Carrol & Graf Publishers: New York, 2006.
- Lewis, Jack, Lt. Col. USMC (retired), Editor. *The Gun Digest Book of Assault Weapons*. Chapter 11 Springfield's SAR-48. Sheldon Factor / DBI Books: Northbrook, IL, 1986.
- McJunkin, James N. and Max D. Crace. *Visions of Vietnam: Drawings and Photographs of the Vietnam War*. Presidio Press: Novato, CA, 1983.
- Murphy, Edward F. *Semper Fi Vietnam From Da Nang To The DMZ Marine Corps Campaigns, 1965-1975*. Presidio Press: Novato, CA, 1997.
- Palmer, Helen. *Do You Know What I Am Going To Do Next Saturday?* Random House: New York, 1963.
- Party, Boston T. *Boston's Gun Bible*. Javelin Press: Ignacio, CO, 2004.
- Pegler, Martin and Ramiro Bujeiro. *The Military Sniper Since 1914*. Osprey Publishing: Oxford, United Kingdom, 2001.
- Pfarrer, Chuck. *Warrior Soul The Memoir of a Navy SEAL*. Random House: New York, 2004.
- Piedmont, John P., Lt. Col. USMCR. *Det One U. S. Marine Corps U. S. Special Operations Command Detachment, 2003-2006*. U. S. Marine Corps History Division: Washington, DC, 2010.
- Rayle, Roy E. *Random Shots Episodes in the Life of a Weapons Developer Fourth Edition*. Merriam Press: Bennington, VT, 2008.
- Smith, Joseph E. (Editor). *Small Arms of the World*. Stackpole Books: Harrisburg, PA, 1996.
- Stevens, R. Blake and Edward C. Ezell. *The Black Rifle M16 Retrospective*. Collector Grade Publications: Cobourg, Ontario, Canada, 1994.
- Unknown. *United States Army Training Center Infantry Fort Jackson South Carolina Company D Tenth Battalion Second Brigade*. Albert Love Enterprises, Inc.: Atlanta, GA, 1965.
- Vetter, Jr., Lawrence C. *Never Without Heroes Marine Third Reconnaissance Battalion in Vietnam, 1965-70*. Ivy Books: New York, 1996.

Walter, John. *Rifles of the World 2nd Edition*. Krause Publications: Iola, WI, 1998.

Warner, Ken (Editor). *Gun Digest 1985/39th Annual Edition*. DBI Books, Inc.: Northfield, IL, 1984.

West, Bing. *The Village*. Pocket Books: New York 2003.

Magazines and Newspapers

Adams, Chad. "Springfield's SOCOM II The Most Modern, Modular M1A." *American Rifleman* January 2006: 45-47, 64.

Andrews, Dave, et al. "Smith M-14 National Match Rifle." *American Rifleman* July 1991: 48-50.

Armed Forces of the Philippines. "Military bares plot to undermine Arroyo." *The Manila Times* September 21, 2007. www.manilatimes.net/national/2007/sept/21/yehey/metro/20070921met1.html

Askins, Charles, Colonel. "New War + New Guns = New Training!" *Guns & Ammo* August 1966.

Ayoob, Massad. "21st Century Battle Rifle Springfield Armory's SOCOM-II Moves The Concept Forward." *GUNS* August 2006.

Ayoob, Massad. "Passive firing pin locks: are they really necessary?" *Guns* August 2005. http://findarticles.com/p/articles/mi_m0BQY/is_8_51/ai_n14694932

Ayoob, Massad. "The Magnificent M14." *Guns & Ammo Combat Tactics* Volume Four Number Two Fall 2006: 112 -125.

Beckstrand, Tom. "The M14 and Our Designated Marksmen." *Guns & Ammo Combat Arms* 2010: 64-67.

Beecher, William. "Fantastic New Weapons That May Replace It!" *Guns & Ammo* November 1963: 31, 32, 59, 61, 62, 65, 66.

Benson, Jim. "Fed Ord M14SA Rifle." *American Survival Guide* September 1988: 8-10, 66.

Benson, Jim. "M14-K Gun." *American Survival Guide* October 1990: 24, 65.

Benson, Jim. "M1A Rifle." *American Survival Guide* November 1987: 22-25, 51.

Benson, Jim. "M1A-A1." *American Survival Guide* December 1990: 24-25, 62.

Benson, Jim. "M21 Rifles." *American Survival Guide* June 1996: 24-25, 78-79.

Benson, Jim. "Super Match M1A Rifle." *American Survival Guide* February 1990: 56-58.

Berger, Matt. "Springfield Socom 16 .308." *Guns & Weapons for Law Enforcement*, October 2005: 66-70, 72-74.

Birkinshaw, Jack. "Local Firm Searches World for Guns." *Independent Star-News* (Pasadena, CA) August 16, 1959.

Brown, Robert K. "Automatic Ranging Telescopic Sight-The Leatherwood ART." *Guns* November 1974.

- Bruce, Robert. "M14 vs. M16 in Vietnam." *Small Arms Review* April 2002: 20-23.
- Bruce, Robert. "Precision Shooting In The Global War On Terror." *Small Arms Review* February 2006: 50-60.
- Bruce, Robert. "VC / NVA Weapons Photo Album." *Small Arms Review* March 2004: 87.
- Canfield, Bruce N. "The M14: John Garand's Final Legacy." *American Rifleman* August 2002: 48-55, 95.
- Cerojano, Teresa. "Philippine Army "Pre-Empts" New Plot." *Associated Press* September 21, 2007. www.newsday.com/news/nationworld/world/wire/sns-ap-philippines,0,5917195.story
- Clark, Bob. "Fabian Brothers: DTA MIL/BRAKE." *American Survival Guide* September 1986: 43.
- Clarke, John R. "Accurizing Service Rifles." *American Rifleman* February 1987: 28-29, 72-73.
- Cole, Jr., Albert A. "Early Problems With The M14 Rifle." *American Rifleman* February 1993: 34-35, 79.
- Cole, Jr., Albert A. "The First M1As." *American Rifleman* August 1990: 32-33, 80.
- Cox, Matthew. "Marksmen issued better rifles in Afghanistan." *Army Times* March 22, 2010: 20-22.
- Crawford, Zac. "Might As Well Jump." *Coast Guard* August 2004: 12-17.
- Cutshaw, Charlie. "Enhanced Battle Rifle .308." *Special Weapons for Military & Police 2005 Gun Buyers Annual Presents #34*: 38-43.
- Cutshaw, Charlie. "Sandbox Ready Mark 14 Mod 0 Enhanced Battle Rifle." *S.W.A.T.* March 2011: 76-81.
- Davis, Carl J. "The M14 National Match Rifle." *American Rifleman* August 1964: 33-36.
- Davis, W. C. "7.62 mm. Elevation Table." *American Rifleman* June 1968: 77.
- Dickey, Pete. "Identifying Modern Military Rifles." *American Rifleman* January 1987: 36-39.
- Emerson, Ashley. "Springfield SOCOM Another American Classic?" *S.W.A.T.* April 2004: 56-59.
- Erfurth, Herbert J. "Shooting the New Army Rifle." *Guns* July 1958: 12-15, 49-50.
- Escobar, Mike. "Homing In On The Range." *Soldier of Fortune* November 2005: 38-39.
- Fortier, David M. "Springfield Armory's Loaded M1A." *M1 Magazine* March 2010: 74-77.
- Fortier, David M. "Springfield's M1A SOCOM .308." *Shooting Times Gun Guide 2006 Buyer's Guide*: 24, 26.
- Fortier, David M. and Gus Norcross. "The M21 Sniper Rifle." *M1 Magazine* March 2010: 28-35.

- Garavaglia, Louis A. "Snipers in Vietnam Also Need Firepower." *American Rifleman* January 1968: 18-20.
- Gauthier, Joseph H. "Arms Company Boosts Shipments." *The Evening Gazette* (Worcester, MA) June 22, 1961.
- Gourley, Scott. "Navy SEALs to get new rifles." *Jane's Defence Weekly* 17 March 2006.
- Gourley, Scott R. "U S Marines Antiterrorism Task Force Special weapons and tactics of this new elite brigade." *Popular Mechanics* January 2003.
- Hackathorn, Ken. "Make Mine M14 RDF's Strong Right Arm?" *Soldier of Fortune* July 1982: 36-41.
- Hacker, Rick. "JAE-100 G2." *Guns & Ammo Combat Arms* 2010: 94-96, 98.
- Hackworth, David H. and Eilhys England. "Hopeless to Hardcore Snipers Part II." *Soldier of Fortune* August 2002: 58.
- Hall, Jeffrey. "Extreme Cold Weather Testing." *S.W.A.T.* April 1986: 30-33.
- Hantke, Paul. "The SOCOM Special Customizing the Springfield M1A for special operators." *Gun World* May 2005: 48-55.
- Harris, C. E. "National Board approves heavy M14 NM barrel." *American Rifleman* July 1975: 27.
- Harris, C. E. "Retesting The M14 Lookalike." *American Rifleman* January 1981: 40-43.
- Harrison, E. H. "7.62 mm. Duplex Cartridge." *American Rifleman* January 1974: 62.
- Harrison, E. H. "Army Sniper Rifle." *American Rifleman* December 1969: 82.
- Harrison, E. H. "Blank Attachment." *American Rifleman* January 1963: 64.
- Harrison, E. H. "'New Service Rifle.'" *American Rifleman* June 1957: 15-21.
- Harrison, E. H. "Overhead Fire Ammunition." *American Rifleman* November 1969: 92.
- Harrison, E. H. "Plastic Stocks for the M14." *American Rifleman* November 1968: 40.
- Harrison, E. H. "The M14 National Match Rifle." *American Rifleman* May 1966: 46-49.
- Heter, E. W. "M14 NM Barrel." *American Rifleman* April 1966: 61.
- Howe, Walter J. and E. H. Harrison. "Making the M14 Rifle." *American Rifleman* February 1963: 13-20.
- Howe, Walter J. and E. H. Harrison. "The M14 Rifle." *American Rifleman* October 1961: 17-27.
- Hundley, Kris. "Inquiry targets SOCom Deal." *St. Petersburg Times* St. Petersburg, FL. January 19, 2007. www.sptimes.com/2007/01/19/Hillsborough/Inquiry_targets_SOCom.shtml
- Iannamico, Frank. "In search of.....The U.S. Rifle, M14." *Small Arms Review* June 2005: 29-33.
- Iannamico, Frank. Ed. "The Life and Times of Burton "Bob" Brenner Part 6." *Small Arms Review* November 2009: 43-50.

- James, Garry. "The Chinese Gun Connection." *Guns & Ammo Annual 1989*: 102-107.
- Johansen, Herbert O. "Army's New Rifle Is a Machine Gun, Too." *Popular Science* February 1959: 157-161.
- Johnston, Gary Paul. "7.62mm NATO Reising: M14 'Shorty'." *Assault Rifles*: 74-76, estimated 1987.
- Johnston, Gary Paul. "H&R Simulator: The Rimfire M14." *Assault Rifles*: 96-98, estimated 1987.
- Johnston, Gary Paul. "The Army's New Sniper Rifle." *Soldier of Fortune* August 21, 2007. www.military.com/forums/0,15240,146717,00.html?ESRC=dod-b.nl
- Johnston, Gary Paul. "The M14 Today." *Soldier of Fortune* March 2008: 50-52, 54.
- Johnston, Gary Paul. "The Ultimate M1A." *Shooting Illustrated* January 2012: 26-31, 60.
- Karwan, Chuck. "Diehard Defender The Specialized M14." *American Rifleman* September 2007: 68-72, 74, 76, 106.
- Karwan, Chuck. "'In Country' With the M14." *American Rifleman* August 2002: 60-61, 88-90.
- Keefe, Mark A. "Opening Shot Back On The Line." *American Rifleman* March 2007: 24.
- Kemps, Don J. and Jack Prucha. "Shooting Out an M1 Barrel." *GCA Journal* Summer 2013: 15-16.
- Kokalis, Peter G. "M14 Rebirth of an American Classic." *Soldier of Fortune* June 1986: 64-67.
- Kokalis, Peter G. "The M14 Reborn Crazy Horse and the Romanian Option." *Shotgun News* December 05, 2005: 20-22, 24, 26.
- Kuleck, Walter J., Ph.D. "Specialized M14s in Service Today." *American Rifleman* September 2007: 74, 76.
- Landay, Jonathan S. "U.S. buys weapons from indicted company." Knight Ridder Newspapers wire story dated April 27, 2005. www.realcities.com/mlid/krwashington/
- Langham, Robert. "TSRA Rifle Team Teaches Army Squad Designated Marksmen at Camp Bullis." *TSRA Sportsman* May / June 2004: 10-11. www.tsrapac.org/Vol_36_3.pdf
- Lardner, Richard. "Inquiry Has State Defense Contractor In Sights." *The Tampa Tribune* Tampa, FL. January 19, 2007. www.tbo.com/news/nationworld/MGBKT3744XE.html
- Larson, Doug. "Down and Dirty with Springfield's SOCOM 16." *Guns & Ammo Annual 2007*: 60 - 62, 64, 66.
- Leicht, Paul W. "Reflections in the Objective Lens Marine Snipers Rotate Home." *Soldier of Fortune* June 2005: 20-22.
- Macaleese, David. "Through The Crosshairs And Into The Desert Jordan's Elite Unit Sniper Training Course." *Special Operations Report* Issue Number 9: 30-32, 34, 36-38, 40-42, 44, 46-47.

- Mananghaya, James. "AFP says it has uncovered new destabilization plot." *The Philippine Star* September 21, 2007. www.philstar.com/index.php?p=60&type=2&sec=24&act=view&aid=20070920196
- Mananghaya, James. "6 officers relieved over coup plot - AFP." *The Philippine Star* September 22, 2007. www.philstar.com/index.php?Headlines&p=49&type=2&sec=24&aid=20070921169
- Mananghaya, James. "AFP destroys rebel guns." *The Philippine Star* September 22, 2007. <http://uw.abs-cbnnews.com/storypage.aspx?StoryId=93460>
- Martin, Derrick and Barrett Tillman. "Ask Derrick." *Precision Shooting* February and April 1998.
- Mason, James D. "The Springfield Armory M1A." *Guns* January 1976.
- Martone, Andrea. "A Time To Also Honor Our Soldiers In Iraq and Afghanistan." *The Port Washington Sentinel* Port Washington, NY. June 17, 2005: 4.
- McElrath, Daniel T. "M1A, The M14's Successful Sibling." *American Rifleman* August 2002: 56-59, 93, 95.
- McLean, Edward T. "Arsenal." *Vietnam* June 1991: 10, 62-63.
- Mendenhall, Monty. "Chinese Thompson SMG." *Small Arms Review* January 2005: 26-28.
- Miller, George. "Gorton Machine May Change Manufacture of Small Arms." *Racine Journal Times* March 07, 1960.
- Norcross, Gus. "M14 Maintenance and Inspection." *Shotgun News* August 06, 2007: 30-32.
- Norrell, James O. E. "U S Military Optics "A New Perspective on Combat."" *American Rifleman* June 2003: 52, 80-81.
- Owens, Franklin. "Army Lab Adds ART to Sniping." *American Rifleman* May 1969: 47.
- Pae, Peter. "Physicist Dean Wooldridge, Co-founder of Aerospace TRW, Dies." *Los Angeles Times*: Obituaries. September 22, 2006.
- Palmer, Hugh. "Armcorp M14 Tests Reported." *The Outdoor News* February 1988.
- Palmer, Hugh. "Chinese M-14 look-alikes maybe unsafe." *The Outdoor News* December 1993.
- Palmer, Hugh. "New M-14 Improved Has Fewer Problems Than Early One." *The Outdoor News* October 1986.
- Palmer, Hugh. "Springfield Armory National Match M1A evaluated." *The Outdoor News* March 1987.
- Palmer, Hugh. "Super Match M1A Good But Not Good Enough." *The Outdoor News* January 1988.
- Pelletier, Fred. "Springfield Armory's M1A." *Shooters Journal* September 1980: 38-39, 58.

- Pence, Arthur. "Exploded Views: The M1A Rifle." *American Rifleman* September 1980: 48-49.
- Petty, Charles E. "Kimber's New .22 Rifles." *Guns* January 2001. http://findarticles.com/p/articles/mi_m0BQY/is_1_47/ai_67717289
- Pikula, Sam. "K-Gun." *American Survival Guide* November 1997: 22-23, 91.
- Pikula, Sam. "Smith Enterprises." *American Survival Guide* January 1997: 76-77.
- Plaster, John L. "New Life For An Old Warhorse." *American Rifleman* March 2011: 64-65, 84-87.
- Poole, Eric R. "Inside Rock Island." *Guns & Ammo Combat Arms* 2011: 16-21.
- Poole, Eric R. "The New Battle Standard." *M1 Magazine* March 2010: 84-89.
- Pushies, Fred. "Smith Enterprises's Crazy Horse M21A5 7.62x51mm." *Special Weapons For Military & Police* April 2009: 56-59.
- Rathbun, Frank F. "Replacing the Browning Automatic Rifle is the new modification of the . . . M-14." *Guns* September 1964: 27, 48.
- Raynor, Kenneth C. "M1A Rifle Velocities." *American Rifleman* July 1974.
- Roberts, Jr., J. B. "Why Are Service Rifle Scores Improving?" *American Rifleman* March 1982: 42-45, 80.
- Rodriguez, Greg. "Modernizing The M1A." *Guns & Ammo Combat Arms* 2010: 82-87.
- Schogol, Jeff. "Last sailors trading in their M-14s." *Stars and Stripes* Pacific Edition July 26, 2007.
- Schreier, Jr., Konrad F. "The New U.S. Army M21 Sniper Rifle." *Guns & Ammo* June 1975: 38, 82.
- Sears, Robert N. "National Match Barrels." *American Rifleman* August 1975.
- Shotgun News* P. O. Box 1790 Peoria, IL 61656 February 2, 2004: 42.
www.shotgunnews.com
- Sheetz, Brian C. "30 Years of Service To Shooters." *American Rifleman* November 2007: 70-72, 74, and 76.
- Shyne, Michael. "SAR at the War Remnants Museum Ho Chi Minh City, Vietnam." *Small Arms Review* April 2002: 26-28.
- Slack, Donovan. "Even small localities got big guns." *The Boston Globe* June 15, 2009.
www.boston.com/news/local/massachusetts/articles/2009/06/15/
- Smith, Clint. "M1A A Rifle For Close Spaces or Far Places." *Guns* July 2004: 71-75.
- Smith, David C. "Jet Parts Producer Tackles Delay-Ridden M-14 Rifle Project." *The Wall Street Journal* February 19, 1962.
- Smith, Matt. "Interview with Tim LaFrance of LaFrance Specialties." *Small Arms Review* August 2002: 87-89.

- Spaulding, Dave. "New Navy M-14 EBR 7.62x51mm." *Special Weapons for Military & Police 2005 Gun Buyers Annual Presents #36*: 62-67.
- Springfield Armory. *Armorer* September 1967: 1-12.
- Staff Evaluation. "Armscorp M14." *American Survival Guide* November 1990: 46.
- Staff Report. "McMillan M1A." *M1 Magazine* March 2010: 16-19.
- Staff Report. "The M14 Service Rifle Is Getting The Boot." *Guns & Ammo* November 1963: 30, 33, 57.
- Stanley, John. *The Arizona Republic*: June 15, 2000.
- Stone, David. "American Sniper in Israel." *Soldier of Fortune* March 2002: 26.
- Syvret, Paul and Rob Maccoll (photographer). "Flying eco-warriors keep the pigs at bay." *The Courier Mail* April 14-15, 2007: 1, 8-9.
- Thompson, Jim. "Armscorp M-14." *American Survival Guide* December 1986: 56-57, 72.
- Trivedi, Hitesh K, et al. "Next generation lubrication system for weapons." *Tribology Letters* Volume 10 Number 4, 2001: 229-235.
- Tyson, Ann Scott. "Weight of Combat Gear Is Taking Toll." *Washington Post* February 01, 2009: A03.
- Unknown. Advertisement for Rosen Public Auction. *Long Beach Press Telegram* October 30, 1966: C4.
- Unknown. "Arsenal Aids Small Arms Drive." *Albany Knickerbocker-News* February 28, 1961.
- Unknown. "Arsenal Gets \$2,000,000 Small Arms Assignments." *Troy Times Record* February 14, 1961.
- Unknown. "Dedicate M14 Production New Army Rifles Roll Off Line At Winchester." *Shooting Times* November 1960: 15.
- Unknown. "Dope Bag: Data and Comment: New S&K Insta-Mount." *American Rifleman* January 1975: 58.
- Unknown. "Dope Bag: M14 Rifle." *American Rifleman* May 1960 65-66.
- Unknown. "Dope Bag: Norinco M14 Rifle Sporter." *American Rifleman* May 1992: 53-54.
- Unknown. "First M1A Match A Success." *American Rifleman* January 2008: 42.
- Unknown. "Guerrilla Gun Is Developed Locally." *The Evening Gazette* (Worcester, MA) December 10, 1962.
- Unknown. "M-14 Won't Disappear Instantly." *Army Times* January 16, 1974.
- Unknown. "New Arms Flow to Hot Spots." *Boston Sunday Advertiser* September 30, 1962.
- Unknown. "New Army Rifle." *Worcester Daily Telegram* May 03, 1957.
- Unknown. "Smith Arms International." *American Survival Guide* August 1994: 15.

Unknown. "The Evolution of The M14 To The M62-R1." *Special Operations Report* Issue Number 9: 48-49.

Unknown. "The M14: Boon Or Blunder?" *Gun World* June 1963: 18-18.

Unknown. Untitled news article citing a Department of Defense press release dated January 30, 1960. *American Rifleman* March 1960: 27.

von Benedikt, Joseph. "Scope Your M1A." *M1 Magazine* March 2010: 52-57.

Waite, M. D. "The M1A: Good News for Target Shooters." *American Rifleman* March 1974: 36-37.

Weller, Jac. "U. S. Rifles Do the Job in Vietnam." *American Rifleman* November 1968: 18-21.

Whittington, Thomas. "Scoring a Bull's Eye in a Blur." *Armada International* 2008: Issue 6.

Williams, Mason. "New Springfield Armory Rifle!" *Guns Illustrated* 1975: 51-53.

Wilson, Chuck. "Iron Curtain Rifles Boosting His Sales." *Independent* (Pasadena, CA) December 06, 1955.

Online Sources

1911forum.com "The Importance of Proper Lubrication." August 18, 2001. <http://forums.1911forum.com/showthread.php?t=1231>

1982 Lebanon War http://en.wikipedia.org/wiki/1982_Lebanon_War

1st Battalion 22nd Infantry <http://1-22infantry.org>

10th Special Forces Group (United States) http://en.wikipedia.org/wiki/10th_Special_Forces_Group

199th Light Infantry Brigade D Troop 17th Cav <http://members.aol.com/dtrp17cav/index.htm>

25th Aviation Battalion <http://25thaviation.org/history/id734.htm>

3rd U.S. Infantry Regiment "The Old Guard." www.globalsecurity.org/military/agency/army/3inf-rgt.htm

44MAG Distributing, LLC P. O. Box 3321 Harbor, OR 97415 www.44mag.com

4th Marine Expeditionary Brigade (Anti-Terrorism) www.4meb.usmc.mil

4th Marine Expeditionary Brigade (Antiterrorism) www.globalsecurity.org/military/agency/usmc/4meb.htm

5th Infantry Regiment www.bobcat.ws/history1970.htm

7.62mm Firearms Medina, OH www.762mmfirearms.com

A Brief History of Army Arsenals. U. S. Army Materiel Command Historical Office <http://www.amc.army.mil/amc/ho/studies/arsenals.html>

Accro-Met, Inc. Monroe, NC 28110 www.accromet.com

Accuracy Speaks, Inc. 3960 North Usery Pass Road Mesa, AZ 85207
www.accuracyspeaks.com

Accuracy Systems, Inc. 44 Republican Road Edgefield, SC 29824 <http://ruger-mini-14-firearms.com>

Ace Ltd. USA P. O. Box 430 Winchester, KY 40391 www.riflestocks.com

Ace Wire Spring & Form Company "Compression Springs." 1105 Thompson Avenue
McKees Rocks, PA 15136 www.acewirespring.com

Accuracy International www.ketmer.com/ai/index

Accuracy International www.wikipedia.org

Accuracy International, Ltd. www.accuracyinternational.com

Adams, Kevin. 7.62 x 51 MM NATO Stripper Clips http://homepages.ihug.co.nz/~kevin_a/

Adco Firearms, LLC 6616 Monroe Street Sylvania, OH 43560 www.adcofirearms.com

Advanced Armament Corporation 1434 Hillcrest Road Norcross, GA 30093
www.silencertalk.com/2007/762-SD.pdf

AIM Sports, Inc. 5095 Walnut Grove Avenue San Gabriel, CA 91776
www.aimsportsinc.com

Aimpoint Inc. 14103 Mariah Court Chantilly, VA 20151 www.aimpoint.com

Airsoft. <http://en.wikipedia.org/wiki/Airsoft>

Allen, Darren M. and Bruce Edwards. "Vt-bound assault rifles apparently legal." *Rutland Herald* April 29, 2004. www.globalsecurity.org/org/news/2004/040429-legal-arms.htm

Allied Armament, Inc. 55948 Columbia River Highway Scappoose, OR 97056
www.alliedarmament.com

Alphacasting, Inc. 391, Ste-Croix St-Laurent, Quebec, Canada H4N 2L3
www.alphacasting.com

Alpharubicon. "M-14." <http://everything2.com/index.pl?node=M-14M14> Maunz
www.alpharubicon.com/leo/m14maunz.htm

Amega Ranges, Inc. www.amegaranges.com/cgi-bin/shop.pl/SID=1110680448.22073/page=index.html

American Backyard Forum. www.ambackforum.com

American Grenade Guide. <http://members.shaw.ca/dwlynn/yank/usid.htm>

Ameriglo, LLC 5579B Chamblee Dunwoody Road Suite 214 Atlanta, GA 30338
www.ameriglo.com

Amoskeag Auction. "114. Remington Prototype M-14 Training Rifle from the Remington Arms Co. Collection." July 30, 2011 auction. www.amoskeagauction.com/84/114.html

AMS Machine P. O. Box 102 West End, NC 27376 www.amsmachine.net

Anderson, Gary. "Army Marksmanship Unit Inducts New Hall of Fame Members." The First Shot CMP On-line Magazine: November 2004. www.odcmp.org

Anonymous. "Historical Genocide: The Demilitarization Program of Small Arms at Anniston Army Depot." 1995. www.jouster.com January 3, 2009 7:58 PM.

Arizona Expert Arms 663 W. 2nd Avenue Suite 12 Mesa, AZ 85210 www.azexarms.com

Arlington National Cemetery. www.arlingtonnationalcemetery.org/ceremonies/sentinelstou.html

Armalite, Incorporated P. O. Box 299 745 S. Hanford Street Geneseo, IL 61254 www.armalite.com

Armed Forces Journal Shoot-Out Weapons Specs www.armedforcesjournal.com/blackwater/analysis8.html

Armscorp USA 4424 John Avenue Baltimore, MD 21227 www.armscorpusa.com

Army Equipment and Technical Publications. www.army.mil/usapa/tech/EM_0065_1.html

Army Equipment and Technical Publications. www.army.mil/usapa/tech/EM_0163_1.html

Army Property. Rifle, 7.62mm, M14-Series, Various LINs and NSNs. www.armyproperty.com/Equipment-Info/M14.htm

Arrowhead Industries 1662 E. M-68 Hwy Afton, MI 49705 <http://arrowheadind.com>

Art Armes. <http://artarmes.com>

ASM International. "Surface Hardening of Steels: Understanding the Basics." 2002. www.asminternational.org

AssaultWeb discussion board www.assaultweb.net

Association of Graduates USMA. Stanley C. Pace / Distinguished Graduate Award. <http://www.aogusma.org/aog/awards/DGA/01cit/pace.htm>

Atlantic Research Marketing Systems, Inc. 230 West Center Street West Bridgewater, MA 02379 www.armsmounts.com

Arizona Response Systems 16014 West Remuda Drive Surprise, AZ 85387 www.arizonaresponsesystems.com

Armor Holdings Inc. Company 13386 International Parkway Jacksonville, FL 32218 www.break-free.com

Arsenal Military Sales rue des Allies 19B-7120 Rouveroy, Belgium www.amsmilitaria.com

Auction Arms. www.auctionarms.com

AWC Systems Technology P. O. Box 41938 Phoenix, AZ 85080 www.awcsystemtech.com

B&G Manufacturing. "Corrosion Resistance." 3067 Unionville Park P. O. Box 904 Hatfield, PA 19440 www.bgmfg.com/corrosion_resistance.htm

B.Jones Sights 5115 E. Edgemont Avenue Phoenix, AZ 85008 www.bjonessights.com

Badger Arms Supply 508 Main Street Melfort, SK www.badgerarmssupply.com

Badger Barrels, Inc. P. O. Box 417 8330-196 Avenue Bristol, WI 53104
www.badgerbarrelsincl.com

Badger Ordnance 1209 Swift Street North Kansas City, MO 64116
www.badgerordnance.com

Bain, Mr. "The M21 and M25 Sniper Weapon Systems." www.snipercountry.com/article7.html

Balay Rehabilitation Center. Chronology of the Pikit Crisis. www.hrnow.org/monitor/ids2003_0312_02.htm

Balay Rehabilitation Center. Notes on the Mindanao Crisis. www.hrnow.org/monitor/ids2003_0506_01.htm

Baldwin, Kadina. "Soldiers issued enhanced M14s." *The Fort Campbell Courier* September 13, 2012. www.fortcampbellcourier.com/news/article_f4b8f4a0-fde0-11e1-a69b-0019bb2963f4.html

Bales, Steven J. "How Surface Treatments Keep Molds Operating Longer." Gardner Publications, Inc.: June 05, 2001. www.moldmakingtechnology.com/articles/010605.html

Bane, Gene. "Jack Paar in Berlin." *Stars and Stripes* September 07, 1961.
www.stripes.com/photoday/paar/

Bardwell, James, Esq. "FAQ on National Firearms Act Weapons." www.cs.cmu.edu/afs/cs/usr/wbardwel/public/nfalist/nfa_faq.txt

Bardwell, James, Esq. "Modifying Semi-Automatic Firearms or "What can I do to my SKS rifle?"" www.titleii.com/Bardwell/semi_auto_faq.txt

Barska 1721 Wright Avenue La Verne, CA 91750 www.barska.com

Bassett Machine P. O. Box 615 Dripping Springs, TX 78620 www.bassettmachine.com

Battenfeld Technologies, Inc. 5885 W. Van Horn Tavern Road Colombia, MO 65203
www.battenfeldtechnologies.com/fajen/

Battle Arms Development, Inc. P. O. Box 92742 Henderson, NV 89009
www.battlearmsdevelopment.com

Battle Comp Enterprises, LLC 101 South Hickey Blvd Suite A455 South San Francisco, CA 94080 www.battlecomp.com

Battle Rifles discussion board www.BattleRifles.com

Beirut Timeline www.warriorsinc.com/BTimeLine.cfm

Bell and Carlson 101 Allen Road Dodge City, KS 67801 www.bellandcarlson.com

Bell Lifestyle Products, Inc. 3164 Peppermill Court Mississauga, ON
www.belllifestyleproducts.com

Best Made Designs, LLC 1601 W. 15th Street Monahans, TX 79756
www.specopsbrand.com

Big-ordnance.com. "United States Grenades." <http://www.big-ordnance.com/grenades/grenades1.htm>

Bits of Pieces #5B Tilbury Center 7621 Vantage Way Delta, BC V4G 1A6 <http://bitsofpieces.com>

BlackHawk Products Group 4850 Brookside Court Norfolk, VA 23502
www.blackhawkindustries.com

Blackrose Tactical Vancouver, BC www.Blackrose-Tactical.com

Bob Babcock photographs <http://c22inf.bravepages.com/babcockpageone.htm>

Boise Cascade P. O. Box 50 Boise, ID 83728 www.bc.com

Bolger, Daniel P., Major. "Scenes from an Unfinished War: Low-Intensity Conflict in Korea, 1966-1968." <http://www-cgsc.army.mil/carl/resources/csi/Bolger/bolger.asp>

Booser, E. R., Consultant, Vero Beach, Fla. and M.M. Khonsari, Louisiana State University. "Systematically Selecting the Best Grease For Equipment Reliability". *Machinery Lubrication Magazine*. January 2007. www.machinerylubrication.com/article_printer_friendly.asp?articleid=970

Bourdon Forge Company, Inc. 99 Tuttle Road Middletown, CT 06457
www.bourdonforge.com

Bowers Board <http://subguns.biggerhammer.net/>

Boyd's' Gunstock Industries, Inc. 25376 403rd Avenue Mitchell, SD 57301
www.boydboys.com

Brian in Afghanistan <http://anysoldier.com/brian/Afghanistan/>

Brief History of The Winchester Repeating Arms Company. www.thckk.org/winchester-hist.html

Brownells, Inc. www.brownells.com

Bry Coat Inc. 207 Vollmer Avenue P. O. Box 1976 Oldsmar, FL 34677 www.brycoat.com

BTP Arms 1282 Smallwood Drive West # 105 Waldorf, MD 20603
www.keepshooting.com

Buffer Technologies P.O. Box 105047 Jefferson City, MO 65110 www.buffertech.com

Bureau of Alcohol, Tobacco, Firearms and Explosives. "Identification of Firearms within the Purview of the National Firearms Act." www.atf.gov/docs

Bureau of Alcohol, Tobacco, Firearms and Explosives www.atf.treas.gov/firearms

Burlington Engineering, Inc. 220 W. Grove Avenue Orange, CA 92865
www.burlingtoneng.net

Butterly, Nick. "Split-second difference between life and death." *The West Australian* January 24, 2011. au.news.yahoo.com/thewest/a/-/wa/8699757/split-difference-between-life-and-death/

C. J. Weapons Accessories P. O. Box 104801 Jefferson City, MO 65110
www.cjweapons.com

C S GunWorks P. O. Box 580113 Elk Grove, CA www.csgunworks.com

California Business Portal. www.sos.ca.gov/business

Canada Ammo www.canadaammo.com

Canada Firearms Centre Frequently Asked Questions www.cfc-ccaf.gc.ca/faq/default_e.asp

CanadianGunnutz.com www.canadiangunnutz.com

Carbide Depot, Inc. "Coefficient for Static Friction of Steel." 119B Citation Court Birmingham, AL 35209 www.carbidedepot.com/forumlas-frictioncoefficient.htm

Carley, Larry. "Automatic Transmission Fluid." <http://www.aa1car.com/library/atf.htm>

Cathy Rankin www.cathyrankin.com

Cedarland. "The Lebanese War." www.cedarland.org/war.html

Century International Arms Inc. 430 South Congress Avenue Suite 1 Delray Beach, FL 33445 www.centuryarms.com

Century Spring Corporation "Technical FAQs." 222 East 16th Street Los Angeles, CA 90015 www.centuryspring.com

Champion's Choice 201 International Boulevard La Vergne, TN 37086

Charles W. Maloney, B.F.A., M.F.A. Gunning Arts, Inc. Catonsville, MD www.charliemaloney.com

Charley's Surplus Sales 317 West Main Street Ada, OK 74820 <http://members.cox.net/charleyssurplus/>

Check-Mate Industries, Inc. 77 Mount Avenue Wyandanch, NY 11798 www.checkmateindustries.com

Chemicator Products, Inc. Plastilube Material Safety Data Sheet. July 20, 2000. P. O. Box 2385 Huntington Park, CA 90255

China North Industries. www.softwar.net/norinco.html

China Poly Group Corporation. <http://en.poly.com.cn> Beijing, China

Chinese Kalashnikov Reference Guide. www.chicom47.net

Choate Machine & Tool, Inc. 116 Lovers Lane P. O. Box 218 Bald Knob, AR 72010 www.riflestock.com

Civilian Marksmanship Program. *CMP Competition Rules 11th Edition*. www.odcmp.com

Clapp, Wiley. "The M14/M1A Completes Four Decades of Service." www.galleryofguns.com/shootingtimes/Articles

Clark, Eileen. "The Passion of Marty Fajen." www.nrapublications.org/woman's%20outlook/spotlight.asp

Clark Custom Guns, Inc. 336 Shootout Lane Princeton, LA 71067 www.clarkcustomguns.com

Classic Jonny Quest.com www.classicjq.com

Cline Tool and Service Company 1415 E. 19th Street Newton, IA 50208
www.clinetool.com

Clint Fowler Rifles Barboursville, VA www.m1-m1a-ar15.com

Clyde Armory 165 Ben Burton Road # D Athens-Bogart, GA 30622 www.policeguns.com

Clymer Manufacturing Company 1645 West Hamlin Road Rochester Hills, MI 48309
www.clymertool.com

CM Manufacturing www.cmmanufacturing.com

Cobb, Ralph E. M5, M6, and M7 Bayonets & Foreign Copies. www.worldbayonets.com

Cole Distributing P. O. Box 247 Scottsville, KY 42164 www.coledistributing.com

Collecting Lithuanian Firearms. www.freeexistence.org/lith.html

Collimated light. http://en.wikipedia.org/wiki/Collimated_light

Commerce Business Daily. www.cbd-net.com/index.php/search/show/593721

Commerce Business Daily. www.cbd-net.com/index.php/search/show/597926

Consistency, Penetration and National Lubricating Grease Institute (NLGI) Numbers
[www.engineersedge.com/lubrication/
consistency_penetration_national_lubricating_grease_institute_nlgi_numbers.htm](http://www.engineersedge.com/lubrication/consistency_penetration_national_lubricating_grease_institute_nlgi_numbers.htm)

Contras [http://en.wikipedia.org/wiki/Contra_\(guerrillas\)](http://en.wikipedia.org/wiki/Contra_(guerrillas))

Crane, David. "21st Century M14/M1A Battle Rifle: Meet the Troy Modular Chassis System (MCS)." Defense Review: January 07, 2008. www.defensereview.com

Crane, David. "SRSS Bulldog762 Bullpup M14/M1A Battle Rifle Goes To Combat: SpecOps Tests Bulldog's Bite." Defense Review: November 29, 2009.
www.defensereview.com

Crane, David. "SRSS Bulldog 762 Bullpup M14/M1A Battle Rifle (7.62mm) Range Session." Defense Review: September 22, 2008. www.defensereview.com

Crazy Horse (TM) Rifles www.crazyhorserifles.com

Creedmoor Sports 167 Creedmoor Way Anniston, AL 36205 www.creedmoorsports.com

Culver, Dick. Refinishing Techniques for Military Rifle Stocks. [www.jouster.com/Bulletin/
refinishing.htm](http://www.jouster.com/Bulletin/refinishing.htm)

Culver, Dick. The Rationale for Linseed Oil vs. Tung Oil. [www.jouster.com/Bulletin/
TUNG.htm](http://www.jouster.com/Bulletin/TUNG.htm)

Culver Shooting Page Lane's Tips www.jouster.com/lanestips

Cunningham, Grant. "Lubrication 101." www.grantcunningham.com/lubricants101.html

Custom Rifle Slings by JHW 5214 Woodlawn Drive Harrisburg, PA 17109
www.slingsbyjhw.com

D. D. Ross Company Medina, OH 44256 www.ddross.com

Daisy Outdoor Products. P. O. Box 220 Rogers, AR 72757 www.daisy.com

Daniel, Eric. "Me and my M-14." kitup.military.com/2007/06/me_and_my_m14.html

Dark International Trading Company / R K Custom Guns www.darkinternational.com

Dasan Machineries Co., Ltd. 798-5, Yongarm-ri, Bongdong-eup, Wanju-gun, Jeollabuk-do, Korea <http://dasan21.en.ec21.com>

Dave Manson Precision Reamers 8200 Embury Road Grand Blanc, MI 48439 <http://mansonreamers.com>

David I. "D. I." Boyd II. www.militarymarksmanship.org/tapsboyd.htm

Davis, Ian. "Disposal of Surplus Weapons in OSCE." www.smallarmssurvey.org/copublications/DisposalofsurplusweaponsinOSCE/01OSCE_USA.pdf

Dealers: Firearms and Accessories Accessory Manufacturers http://www.webcom.com/gun_guy/dealers.htm

Defense Logistics Agency www.dla.mil/history/history.htm

Defense Logistics Agency Law Enforcement Support Office https://pubweb.drms.dla.mil/cmis/Section1033/weapon_req.htm

Defense Logistics Information Service https://www.webflis.dlis.dla.mil/WEBFLIS/ASPscripts/pub_search_bsm.aspx

Delta 14 Chassis Inc. P. O. Box 20370 Ferndale, MI 48220 www.delta14chassis.com

Delta P Design, Inc. P. O. Box 245 Walterville, OR 97489 www.deltapdesign.com

Deluxe Reading. http://en.wikipedia.org/wiki/Topper_Toys

Dlask Arms Corporation 202B - 1546 Derwent Way Delta, BC, Canada V3M 6M4 www.dlaskarms.com

Dogfight Ink Fine Arts Sales and Design Services. www.dogfightink.com/m14.html

Douglas Barrels, Inc. 5504 Big Tyler Road Charleston, West Virginia 25313 www.benchrest.com/douglas/

Douglas, Dwayne. "How to Prevent Seizing and/or Galling of Wear Plates, Slides And Core Pins." Gardner Publications, Inc.: June 05, 2006. www.moldmakingtechnology.com/articles/060605.html

Dow Arms Room - Tactical Rifles 19250 Highway 301 Dade City, FL 33523 www.tacticalrifles.net

DPMS - Panther Arms 3312 12th Street SE St. Cloud, MN 56304 www.dpmsinc.com

Dragon Models USA www.dragonmodelsusa.com

Drying Oils www.wikipeida.com

Dunnigan, James. "New U. S. Army Sniper Rifle." Strategy Page: May 09, 2007. <http://www.strategypage.com/dls/articles/20075912343.asp>

Dupage Trading Company P. O. Box 1274 Chandler, AZ 85244 www.dupagetrading.com

eBay www.ebay.com

E&L Mfg., Inc. 4177 Riddle By-Pass Road Riddle, OR 97469 www.brasscatchers.com

E. I. du Pont de Nemours and Company, Inc. www.dupont.com/teflon/coatings/typical_props.html

Eaton Detroit Spring, Inc. "Spring Tech 101." 1555 Michigan Avenue Detroit, MI 48216 www.eatonsprings.com

Eberlestock USA, LLC P. O. Box 862 Boise, ID 83701 <http://eberlestock.com/index.html>

Ecrimesa Avda. Parayas, s/n Apdo. correos no. 402 Santander 39080 Spain www.ecrimesa.com

Electronic Arts, Inc. www.eagames.com/official/battlefield/vietnam/us/home.jsp

Elite Firearms 7600 Old U. S. Highway 45 Boaz, KY 42027 www.eliteguns.com

Ellwood Epps Sporting Goods Highway 11 Orillia, Ontario, Canada www.ellwoodepps.com

EN3: Introduction to Engineering and Statics. Department of Engineering Brown University <http://www.engin.brown.edu/courses/en3/Notes/Statics/friction/friction.htm>

Endoshoji Co., Ltd. Tokyo, Japan <http://www.endoshoji.com/model-guns/page035.html>

Entreprise Arms, Inc. 15861 Business Center Drive Irwindale, CA 91706 www.entreprise.com

Expat Intelligence. <http://www.expaintelligence.com/expat-new-zealand.shtml>

Experimental TRW LMR - Low Maintenance Rifle (USA) <http://www.militaryphotos.net/forums/archive/index.php/t-90162.html>

Ezell, Virginia Hart. "Navy SEALs Choose Knights SR25 Rifle." *National Defense* October 2000. www.nationaldefensemagazine.org/issues/2000/Oct/Navy_SEALS.htm

Fabbrica d' Armi Pietro Beretta S.p.A. www.beretta.com

Fabsports Canada www.fabsports.ca

FAS Military Analysis Network. "M16A2 5.56mm Semiautomatic Rifle." <http://www.fas.org/man/dod-101/sys/land/m16.htm>

FBO Daily by Loren Data Corporation [www.fbodaily.com/cbd/archive/1998/07\(July\)/28-Jul-1998/](http://www.fbodaily.com/cbd/archive/1998/07(July)/28-Jul-1998/)

FBO Daily by Loren Data Corporation www.fbodaily.com/archive/2004/08-August/28-Aug-2004/FBO-00655629.htm

FBO Daily by Loren Data Corporation www.fbodaily.com/archive/2007/10-October/03-Oct-2007/FBO-01426043.htm

Federation of American Scientists. New People's Army. www.fas.org/irp/world/para/npa.htm

Feliciano, Roberto, Lieutenant Colonel PN(M) (MNSA) (RES). The Philippine Marine Corps Scout Sniper Program: Continuing Relevance and Development into the 21st Century. www.navy.mil.ph/digest.html

FFL Types There is NO SUCH THING as a Class 3 Weapon By: Circuits of AR15.com.
www.quarterbore.com/nfa/class3.htm

Fisher Enterprises P. O. Box 7486 Tempe, AZ 85281 www.fishersuppressors.com

Fiske Brothers Refining Co. Lubriplate 130-A Material Safety Data Sheet. January 01, 1985. 129 Lockwood Street Newark, NJ 07105 <http://hazard.com/msds/f2/bfn/bfnlc.html>

Fiske Brothers Refining Co. Lubriplate RG-62-A Material Safety Data Sheet. March 01, 1996. 129 Lockwood Street Newark, NJ 07105 <http://hazard.com/msds/f2/cbq/cbqlf.html>

Fiske Brothers Refining Co. Lubriplate RG-62-A Material Safety Data Sheet. January 01, 1999. 129 Lockwood Street Newark, NJ 07105 <http://hazard.com/msds/f2/cky/ckyft.html>

Florida Gun Works 8306 Mills Drive Box 571 Miami, FL 33183 www.floridagunworks.com

Ford Motor Company Dearborn, MI www.ford.com

Forster Precision Products 310 E. Lanark Avenue Lanark, IL 61046
www.forsterproducts.com/Pages/gages.htm

Fort Dix, N.J. www.dix.army.mil

Francis Conway. *Las Cruces Sun-News* May 03, 2011. www.legacy.com/obituaries/lcsun-news/obituary.aspx?n=francis-conway&pid=150756824

Frankford Arsenal Alumni Home Page www.frankfordarsenal.org

Fred's P. O. Box 629 Ramseur, NC 27316 www.fredsm14stocks.com

Free Jose Maria Sison! <http://rwor.org/a/100/Sison-arrest-en.html>

Free Republic. "Weapons Lube Issued by Army May be Costing Lives in Iraq." November 18, 2003. www.freerepublic.com/focus/f-news/1024494/posts

Friction Factors www.roymech.co.uk/Useful_Tables/Tribology/co_of_frict.htm

FTI, Inc. 8 Vreeland Road Florham Park, NJ 07932 www.tetraproducts.com

Full Canopy Armory, LLC 9860 Mesquite Loop Flagstaff, AZ 86004
www.fullcanopyarmory.com

Fulloflead's Great Rust Experiment! December 09, 2002. <http://www.bladeforums.com/forums/archive/index.php/t-233147.html>

Fulton Armory 8725 Bollman Place # 1 Savage, MD 20763 www.fulton-armory.com

Funding Universe. Brunswick Corporation. www.fundinguniverse.com/company-histories/Brunswick-Corporation-company-History.html

GG&G 3602 East 42nd Stravenue Tucson, AZ 85713 www.gggaz.com

Gary Cunningham's Bayonet Point's www.usmilitaryknives.com/bayo_points_7.htm

Gary Cunningham's Bayonet Point's www.usmilitaryknives.com/bayo_points_9.htm

Gary Cunningham's Bayonet Point's www.usmilitaryknives.com/bayo_points_18.htm

Gemini Technologies, Inc. P. O. Box 140618 Boise, ID 83714 www.gem-tech.com

M14 RIFLE HISTORY AND DEVELOPMENT

General Dynamics - Ordnance and Tactical Systems - Canada - History.
www.snctec.com/html/en/about/history.php

G. A. Precision 1141 Swift Street North Kansas City, MO 64116 www.gaprecision.net

Georgia Precision Shooter's Supply 317 North Frontage Road Forsyth, GA 31029
www.georgiaprecision.com

Glenn Eugene Nelson March 19, 1935 - February 17, 2007 Columbus, GA. *Ledger-Enquirer*: February 17, 2007. www.legacy.com/ledger-enquirer/Obituaries

Global Defense Initiatives, Inc. 4019 Goldfinch Street Suite 3 San Diego, CA 92103
www.gdiengineeredolutions.com

Global Tactical Supply, LLC and Dennys Gun 2001 Clay Street North Kansas City, MO 64116 www.globaltactical.com

Gloria Material Technology Corporation 35 Hsin Chung RD Hsin-Ying, Taiwan
www.gmtc.com.tw

Goodwin, Liz. "Fighting drugs and border violence at Arizona's Organ Pipe Cactus National Monument: What about the ranger's M14 rifle, Yogi?" Yahoo News The Ticket Blog February 28, 2012. news.yahoo.com/blogs/ticket/fighting-drugs-border-violence-arizona-organ-pipe-cactus-132342614.html

Gourley, Scott R. "New Equipment." *Army Magazine* November 2003. www.ausa.org/www/armymag.nsf

Gourley, Scott. "One Shot." *Military Training Technology* December 01, 2002 Volume 7 Issue 8. www.mt2-kmi.com/archive_article.cfm?DocID=206

Gray-Syracuse, Inc. 901 E. Genesee Street Chittenango, NY 13037
www.graysyracuse.com

Grease (lubricant). http://en.wikipedia.org/wiki/Grease_%28lubricant%29

Grease Ready Reference Glossary by Lubrizol www.lubrizol.com/GreaseReference/glossary.asp

Greases. www.boucherandjones.com/grease.htm

Griffin & Howe, Inc. 340 W. Putnam Avenue Greenwich, CT 06830 www.griffinhowe.com

Guenther, Lalita. "Soldiers try out new rifle." *Paraglide* September 03, 2009.
www.paraglideonline.net/090309_focus1.html

Gun Broker. www.gunbroker.com

Gun World M14 Rifles - Outlined www.gun-world.net-usa-r-m14-m14type.htm

Guns America www.gunsamerica.com

Guns Recovered at Brach Davidian Compound <http://usgovinfo.about.com/blwacoguns.htm>

H & M Metal Processing. 1414 Kenmore Blvd Akron, OH 44314 www.blacknitride.com

Hacker, Rick. "M14." *Shooting Illustrated* December 15, 2011.
www.shootingillustrated.com/index.php/18268/m14/#comment-3701

Hale, Timothy. "Squad Designated Marksmanship Training with the M14 EBR." Shottimes.net February 14, 2012. www.shottimes.net/2012/02/squad-designated-marksmanship-training.html

Half MOA Specialties 6431 Harper Mill Road Harrisonburg, VA 24471 www.halfoma.us

Hanita Cutting Tools. "Coating: titanium nitride TiN." 51 Commerce Street Springfield, NJ 07081 www.hanita.com/hanita_protected/tec00002.htm

Hardwood Information Center. www.hardwoodcouncil.com

Harris, Ed. "Re: CLP Break Free -- what is it?" August 11, 1990. http://yarchive.net/gun/break_free_clp.html

Harris Bipods. www.harrisbipods.com

Hays, Kirk. "Re: machine oil." September 30, 1996. <http://yarchive.net/gun/lubricants.html>

Hell's Half Acre: A Vietnam Page Ammunition Pouches <http://hometown.aol.com/rtoartilleryfo/ammo.html>

Heritage Arms, Inc. 1631 P Road Loma, CO 81524 www.heritage-arms.com

Hill Country Leather. www.hillcountryleather.com/

Historical Political Events for June 26. http://perspicuity.net/cgi/disp_day.cgi?06&26&1999

Historical Political Events for March 14. http://perspicuity.net/cgi/disp_day.cgi?03&14&1999

Historical Political Events for May 19. http://perspicuity.net/cgi/disp_day.cgi?05&19&1999

Historical Political Events for October 22. http://perspicuity.net/cgi/disp_day.cgi?10&22&1999

Historical Political Events for September 13. http://perspicuity.net/cgi/disp_day.cgi?09&13&1999

Hoover's. "Springfield Armory, Inc." www.hoovers.com/Springfield-Armory/--ID__115240--/global-company-information-180factsheetform.xhtml?cm_ven=PAID&cm_cat=GGL&cm_pla=TCK&cm_ite=springfield_armory_inc

Hughes-Wilson, John and Adrian Wilkinson. "Safe and Efficient Small Arms Collection and Destruction Programmes: A Proposal for Practical Technical Measures." United Nations Development Programme Emergency Response Division: New York, July 2001.

HUM 90 Tour of Duty Pages. www.hum90.com

Iannamico, Frank. "U. S. Rifle M14." Machine Gun News 1995. www.machinegunbooks.com/m14sample.html

Idaho State Police. Planning, Grants and Research. <http://www.isp.state.id.us/pgr/>

Illinois Highpower. www.illinoishighpower.org/general_highpower_info/faq.htm#where

M14 RIFLE HISTORY AND DEVELOPMENT

Innovative Industries, LLC. P. O. Box 558 Warren, MI 48090
www.innovativeindustriesllc.com

International Ammunition Association. <http://cartridgecollectors.org/forum/>

International Lubricant Corporation. "Rifle Grease Material Safety Data Sheet."
September 08, 1992. <http://hazard.com/msds/f2/bnr/bnrqx.html>

Israeli Special Forces Sniping and Sharpshooting. www.geocities.com/mazanga9/IDF/IDFSnipingSharpshootingPhoto1.htm

J. Allen Enterprises 21520-G Yorba Linda Boulevard # 175 Yorba Linda, CA 92887
www.jae100.com

James River Armory 3601 Commerce Drive Suite 110 Halethorpe, MD 21227
www.jamesriverarmory.com

Jeep Name Origin. <http://members.aol.com/brimiljeep/WebPages/JeepNamePage.html#B/OLiteGuard>

Jet Suppressors 1904 N. FM 1069 Aransas Pass, TX 78336 <http://jetsuppressors.com>

Jimmie E. Howard. http://en.wikipedia.org/wiki/Jimmie_E._Howard

Jing An China. www.worldsecurity-index.com/details.php?id=3917

John F. Dugan Memorial Page. www.jmlavelle.com/gunnel/dugan.htm

John M. Olin. http://en.wikipedia.org/wiki/John_M._Olin

John M. Olin Foundation. http://en.wikipedia.org/wiki/John_M._Olin_Foundation

John Masen Company 1305 Jelmak Street Grand Prairie, TX 75050
www.johnmasen.com

Johnson, Steve. NordArm's M14 Picatinny Rail With Integrated Bipod.
www.thefirearmblog.com/blog/2013/10/14/nordarms-m14-picatinny-rail-integrated-bipod/

JP Enterprises, Inc. P. O. Box 378 Hugo, MN 55038 www.jp rifle.com

Juggernaut Tactical, Inc. P. O. Box 745 Twin Peaks, CA 92391 www.jtactical.com

Jungle Toy 1503 Marlborough Avenue Riverside, CA 92507 www.airsoft128.com/xcart/customer/product.php?productid=34538&cat=0&page=1

Justice Technology Information Network www.nlectc.org/equipment/1033.html

J. V. Precision Machine Company 71 Cogwheel Lane Seymour, CT 06483
www.jvprecision.net

Karsten's Custom Camo. www.imageseek.com/karsten

Keng's Firearms Specialty, Inc. 875 Wharton Drive, S.W. P. O. Box 44405 Atlanta, GA 30336 www.versapod.com

Kimber Mfg., Inc. 1 Lawton Street Yonkers, NY 10705 www.kimberamerica.com

Klare, Michael and David Andersen. "A Scourge of Guns The Diffusion of Small Arms and Light Weapons in Latin America." www.fas.org/asmp/library/scourge/Titlepg.pdf

Kolbe, Geoffrey. "The Making Of A Rifled Barrel." www.border-barrels.com/articles/bmart.htm

Krebs Custom, Inc. 1000 Rand Road Wauconda, IL 60084 <http://www.krebscustom.com/index.html>

Krieger Barrels, Inc. 2024 Mayfield Road Richfield, WI 53076 www.kriegerbarrels.com

Lamothermic Precision Investment Casting Corporation 391 Route 12 Brewster, NY 10509 www.lamothermic.com

Larry Burrows: Vietnam – The Digital Journalist <http://digitaljournalist.org/issue0302/>

LaRue Tactical 850 County Road 177 Leander, TX 78641 www.laruetactical.com

Latham, Gary (Algoma Steel, Inc.). "Does the Squeaky Wheel Get the Grease?" www.uvlm.com/PDFS/case_study.pdf

Law Enforcement Support Office. www.dla.mil/j-3/leso/

LAW483 Enterprises P. O. Box 2892 Weatherford, TX 76086 www.m14riflestocks.com

Leapers, Inc. 37250 Plymouth Road Livonia, MI 48150 www.leapers.com

Lebanese Civil War 1983 - 1984 www.1stbusinesslebanon.com/civilwar/civil3.html

Lee Spring Company 1462 62nd Street Brooklyn, NY 11219 http://www.globalspec.com/FeaturedProducts/Detail/LeeSpring/Stock_Compression_Springs/29889/0

Lenny Magill Publications 4585 Murphy Canyon Road Sand Diego, CA 92123 www.GunVideo.com

Les Tam Slings leslietam@aol.com

Lever Arms Service Ltd. 2131 Burrard Street Vancouver, BC Canada V6J3H7 www.leverarms.com

Light Rifles. www.scs.wsu.edu/~pbourque/riflelt.htm#g2a

Lightfighter Tactical. www.lightfighter.com

Lightforce USA 1040 Hazen Lane Orofino, ID 83544 www.nightforceoptics.com

Lincoln. www.lincoln.com/lifestyle/heritage.asp?year=1970

Lincoln Continental Owners Club Pacific Northwest Region Snohomish, WA www.lincoln-club.org

Long Mountain Outfitters, LLC www.longmountain.com/movieguns/RedDawn

Lothar Walther Postfach 1125 D-89551 Konigsbronn www.lothar-walther.de

Louis Marx and Company. http://en.wikipedia.org/wiki/Louis_Marx_and_Company

LRB of Long Island, Inc. 32 Cherry Lane Floral Park, NY 11001 www.lrbarms.com

Lubricant Test Conducted by S.T.A.T.E. Members. Maryland State Police: January 25, 1991. <http://www.militec1.com/marylandpolice2.pdf>

Luxembourg Defence Technologies www.luxdeftec.com

M14 RIFLE HISTORY AND DEVELOPMENT

Lyman Products Corporation 475 Smith Street Middletown, CT 06457
www.lymanproducts.com

M-14 Parts and Armorer Services www.m-14parts.com

M1Surplus.com P. O. Box 2828 Big Bear City, CA 92314 www.m1surplus.com

M10 Scabbard. www.m4bayonets.com/scabbards/m10.html

M14 Mag Bag Sumrall, MS www.m14magbag.com

M14 Rifle. Internet Movie Firearms Database. www.imfdb.org/index.php/M14_Rifle

M14 Spring Guides A Short History of their Evolution Sadlak Industries, LLC 712 Bread & Milk Street Unit 7 Coventry, CT 06238 www.sadlak.com

M14-M1AHeaven.com <http://www.m14-m1aheaven.com/index.php>

M14HDW.US www.m14hdw.us

M14L1. www.ginklai.net/view/44/m14l1.html

M39 Enhanced Marksman Rifle. www.wikipedia.org

M89SR. www.israeli-weapons.com/weapons/small_arms/m89sr/M89SR.html

MacRae's Blue Book. [www.macraesbluebook.com/search/
company.cfm?company=456273](http://www.macraesbluebook.com/search/company.cfm?company=456273)

Magblock, LLC www.magazineblocks.com

maglula Ltd. P. O. Box 302 Rosh Ha'ayin 48103 Israel www.maglula.com

Magna-Matic Corporation W4599 County Road IW Waldo, WI 53093 www.magna-matic.com

Magpul Industries Corporation P. O. Box 17697 Longmont, CO 80308 www.magpul.com

Magwedge.com www.magwedge.com

Malay, Ricardo S. "Now it can be told: '71 NPA arms deal with China failed."
www.inq7.net/nat/2203/dec/11/text/nat_5-1p.htm

Malcolm Cooper. http://en.wikipedia.org/wiki/Malcolm_Cooper

Manual of arms. http://en.wikipedia.org/wiki/Manual_of_arms

Marine Corps JROTC www.mcjrotc.org

Marine Corps News. "Depot DIs supervise JROTC drill meet." Lance Corporal Dorian Gardner, May 12, 2006. [www.marines.mil/marinelink/mcn2000.nsf/lookupstoryref/
20065121345](http://www.marines.mil/marinelink/mcn2000.nsf/lookupstoryref/20065121345)

Marine Medium Helicopter Squadron 365 in Vietnam. www.angelfire.com/de/HMM365V

Marksmanship Awards. www.usnst.org/awards.htm

Marksmanship Medal. http://en.wikipedia.org/wiki/Marksmanship_Medal

Marksmanship Ribbon. http://en.wikipedia.org/wiki/Marksmanship_Ribbon

Marstar Canada, Inc. Rural Route # 1 Vankleek Hill, Ontario Canada K0B 1R0
www.marstar.ca

Martir, Jonathan C., Lieutenant Colonel PM(M) (GSC). "Marine Operations - Liguasan Marsh." Video: June 05, 2003. www.navy.mil.ph/Dloads/index.html

Maryland Department of Assessments and Taxation. www.dat.state.md.us

MatWeb. "ASTM A228." www.matweb.com

Maunz Match Rifles, LLC P O Box 104 Maumee, OH 43537 www.maunzmatchrifles.com

McDonald, Eric V. and Todd Caldwell. "Geochemical and Physical Characteristics of Iraqi Dust and Soil Samples." State of Nevada Desert Research Institute Division of Earth and Ecosystem Sciences www.dees.dri.edu/Projects/tcald_GPCIDSS.htm

McFarlane Toys. www.spawn.com

McCann Industries 132 South 162nd Spanaway, WA 98387 www.mccannindustries.com

McMillan Fiberglass Stocks, Inc. 1638 W. Knudsen Drive Suite 101 Phoenix, AZ 85027 www.mcmfamily.com

MD Labs – XF7. www.maxpedition.com/product/product_xf7.htm

MD Labs XF7 Lubricant 8333 Pecos Drive # 4 Prescott Valley, AZ 86314 www.madxf7.com/

MD Labs XF7 Weapon Lube www.tacticalforums.com/cgi-bin/tacticalubb/ultimatebb.cgi?ubb=get_topic;f=7;t=001338

Metal Suppliers Online. www.suppliersonline.com/propertypages/8620.asp

Michaelis, Dean. "M25 Development History." www.snipersparadise.com/articles/M25dev.htm

Mid-West Spring and Stamping 1404 Joliet Road Suite C Romeoville, IL 60446 www.mwspring.com/materials.html

Midwest Industries, Inc. 833 West College Avenue Waukesha, WI 53186 <http://www.midwestindustriesinc.com>

Military Bayonets: M-6 http://www.olive-drab.com/od_edged_weapons_bayonet_m6.php

Militec, Inc. "Grease MSDS." 11828 Pika Drive Waldorf, MD 20602 www.militec1.com/greasemsds1.html

Militec, Inc. "The Only Synthetic-Based Metal Conditioner: Proven Technology for Today's Soldier and Marine. National Defense Industrial Association Small Arms Systems Division Annual Conference June 9-12, 1997. www.militec1.com/techoverview1.html

Millett 9200 Cody Overland Park, KS 66214 www.millettsights.com

Minelli S.p.A. www.minelligroup.it

Minnick, Fred. "Lethal Snipers Lead the Way." www.defendamerica.mil//articles/mar2004/a031604a.html

Model Guns http://www.modelguns.co.uk/m14_rifle.htm

Monroig, Armando, Sergeant. "Military Police Help Train Iraqi Police." U. S. Army

M14 RIFLE HISTORY AND DEVELOPMENT

National Guard, 5th Mobile Public Affairs Detachment: January 01, 2007.
www.agreaterfreedom.com

Montgomery, Rebecca. "AMC Deputy Chief of Staff on Target with M14 Enhanced Battle Rifle." TACOM LCMC Rock Island Public Affairs: June 26, 2008. <http://www.army.mil/news/2008/06/26/10394-amc-deputy-chief-of-staff-on-target-with-m14-enhanced-battle-rifle/>

Motor Oil. http://en.wikipedia.org/wiki/Motor_oil

Msgt Maze. www.msgt-maze.com

Muscle Products Corporation. MSDS for PL-10 Grease. 752 Kilgore Road Jackson Center, PA 16133 www.customfuelcatalyst.com/grease.html

Muscle Products Corporation. Product Data Sheet for PL-10 Grease. <http://www.mpc-home.com/data/data-PL-10.pdf>

MWG Company. 10651 S.W. 185 Terrace Miami, FL 33157 http://www.mwgco.com/thestore/NATIONAL_MAGAZINES.html

National Firearms Owners Association. www.nfaoa.org

National Rifle Association. Getting Started - High Power Rifle Competition.
www.nrahq.org/compete/highpower.asp

National Rifle Association. "Winners of New NRA/Springfield Armory M1A Rifle Match Take Home \$25,000 in Cash and Prizes." www.nra.org/Article.aspx?id=9322

National Shooting Sports Foundation 11 Mile Hill Road Newtown, CT 06470
www.nssf.org

Naval Surface Warfare Center 300 Highway 361 Crane, IN 47522-5001
www.crane.navy.mil

New Century NcStar, Inc. formerly New Century Science & Technology, Inc. 18031 Cortney Court City of Industry, CA 91748 previously at 10302 Olney Street El Monte, CA 91731 www.ncstar.com

New Data on Murder of Lumumba http://www.africawithin.com/lumumba/murder_of_lumumba.htm

New People's Army. www.philippinerevolution.org/npa/index.shtml

Nicolaus Associates P. O. Box 875 Jefferson, GA 30549 www.nicolausassociates.com

Nightforce Optics, Inc. 336 Hazen Lane Orofino, ID 83544 www.nightforceoptics.com

Nioa Trading 128 Buchanan Road Banyo, Queensland, Australia 4014 www.nioa.net.au

NISAT www.nisat.org/export_laws-regs%20linked/usa/overview.htm

NISAT www.nisat.org/export_laws-regs%20linked/usa/surplus_light_arms_and_ammunition.htm

NISAT www.nisat.org/weapons%20pages%20linked/US/m14_rifle.htm

Non-Environmentally Hazardous Items Approved for Local Sale Sorted by NSN <http://www.drms.dla.mil/newenv/html/documents/nonenvhzbysn.pdf>

Norinco 12A Guang An Men Nan Jie P. O. Box 2932 Beijing, China 100053
www.norinco.com.cn

Norrell Manufacturing 13529 Saddle Hill Drive Little Rock, AR 72212 www.molyresin.com

Norinco Armsports Co., Ltd. 12A Guang An Men Nan Jie P. O. Box 2932 Beijing, China
100053 www.norincosports.cn

North Eastern Arms www.northeasternarms.com

Northridge International, Inc. 1026 Arroyo Avenue San Fernando, CA 91340
www.northridgeinc.com

Northrup Grumman Corporation Electro-Optical Systems 3414 Herrmann Drive Garland,
TX 75041 www.es.northropgrumman.com/es/eos/PDF_Data_Sheets/M845.pdf

Northwest Territorial Mint 2505 South 320th Street Suite 110 Federal Way, WA 98003
www.nwtmint.com

NTI. "Poly Technologies Corporation." www.nti.org/db/china/baoli.htm

Numrich Gun Parts Corporation 226 Williams Lane West Hurley, NY 12491
www.gunpartscorp.com

O'Connor, Patrick. "GEN 3 SRSS BullDog 762 BullPup M14/M1A 7.62mm NATO Rifle/
Carbine Chassis/Stock System for Urban Tactical Operations, including Vehicle Ops
(Review and Photos!)." Defense Review: September 14, 2010. www.defensereview.com

Olin Online 501 Merritt Seven Norwalk, CT 06856 www.olin.com/about/history.asp

Olive-Drab Soldier's Web Gear: Vietnam and Recent [www.olive-drab.com/
od_soldiers_gear_vietnam_webgear.php](http://www.olive-drab.com/od_soldiers_gear_vietnam_webgear.php)

Omni Tech Partners, Inc. 110 Kountz Lane Freeport, PA 16229
www.omnitechpartners.com

OneSixthWarriors BHD Michael Durant, Randy Shughart & Gary Gordon Tribute
discussion thread. <http://www.onesixthwarriors.com/forum/showthread.php?t=20145>

OPS, Inc. P. O. Box 377 Shingletown, CA 96088 www.opsinc.us

Oregon Secretary of State http://egov.sos.state.or.us/br/pkg_web_name_srch_inq.login

Orion 7 Enterprises, Inc. P. O. Box 1592 Rocky Point, NY 11778 www.m1garand.com

Otis Products, Inc. Laura Street P. O. Box 582 Lyons Falls, NY 13368 www.otisgun.com

Pacific Canvas & Leather Co., Inc. P. O. Box 291909 Phelan, CA
www.pacificcanvasandleather.com

Pacific Tool and Gauge, Inc. White City, OR www.pacifictoolandgauge.com

Paladin Republic Armory www.paladinrepublic.com

Parallax. <http://en.wikipedia.org/wiki/Parallax>

Parkerizing. <http://en.wikipedia.org/wiki/Parkerizing>

People's Armed Police www.answers.com/topic/people-s-armed-police

Philippine Marine Corps. Cutting Edge The First 50 Years of The Philippine Marines. 2000. www.navy.mil.ph/Dloads/index.html

Philippine Navy. Tides of Change The Philippine Navy Looks Back A Hundred Years and Peers Into The Next Century. 1998. www.navy.mil.ph/Dloads/index.html

Philippine Revolution Web Central. Updates on the 36th year of the NPA Developments in the work of the New People's Army. www.philippinerevolution.org/cgi-bin/npa/updates.pl

Photobetty. "Before You – Dickey Chapelle." www.photobetty.com/dickey_chapelle/15.htm

Physics and Astronomy Online. www.physlink.com/Reference/FrictionCoefficients.htm

Pineo, Paul F. and Lora Lumpe. Recycled Weapons American Exports of Surplus Arms, 1990-1995 A Study by the Arms Sales Monitoring Project of the Federation of American Scientists. May 1996. www.fas.org/asmp/library/publications/recycle.htm

Planet Battlefield www.planetbattlefield.com/bfv/game

Plastilube <http://65.213.72.112/tds/docs/PLASTILUBE-EN.PDF>

Polytetrafluoroethylene <http://en.wikipedia.org/wiki/Teflon>

Potteiger, Jarrod (Noria Corporation). "Step-by-Step Grease Selection." *Machinery Lubrication Magazine*. September 2005.

Potterfield, Larry W. "Letter from Fajen CEO." www.webcom.com/gun_guy/fajen.htm

President's Hundred Tab http://en.wikipedia.org/wiki/President's_Hundred_Tab

Program Executive Office Soldier <https://peosoldier.army.mil>

ProMag Industries 10654 South Garfield Avenue South Gate, CA 90280
www.promagindustries.com

Promethium. www.infoplease.com

Quantico Arms & Tactical Supply, Inc. 253 Potomac Avenue Quantico, VA 22134
www.quanticoarms.com

Rauch Tactical www.rauchtactical.com

Rawles, James Wesley. The M14 Magazine / M1A Magazine FAQ. www.rawles.to/M14%20Magazine_FAQ.html

Recoil Reduction Technologies, LLC P. O. Box 894 Mandeville, LA 70470
www.nokick.com

Red dot sight. http://en.wikipedia.org/wiki/Red_dot_sight

Reese Surplus, Inc. 25132 Ridge Road Colona, IL 61241 www.reesesurplus.com

Reflex Suppressors Joensuu, Finland <http://guns.connect.fi/rs/general.html>

Results of the 1973 Church Committee Hearings, on CIA misdeeds, and the 1984 Iran/Contra Hearings [http://home.netcom.com/~ncoic/cia_info.htm#Paramilitary Operations](http://home.netcom.com/~ncoic/cia_info.htm#Paramilitary_Operations)

Retroland. Johnny Eagle. www.retroland.com/pages/retropedia/toys/item/2595/

Ricca, William J. "Grenade Launchers and Associated Equipment." www.billricca.com/glpq.htm

Ricca, William J. "Military Training Aids-Double Size Trainers (2X)." www.billricca.com/trainers_2x.htm

Ricca, William J. "Numbers, Numbers, Numbers. . . ." www.billricca.com/Number_Article.htm

Ricca, William J. "The M10 Cleaning Rod, Its Development and Evolution To the M14." <http://www.billricca.com/m10page.htm>

Ricca, William J. "The M76 Grenade Launcher and Some Its Predecessors." www.billricca.com/m76_gren_launcher.htm

Ricca, William J. "US Small Arms Storage Racks." www.billricca.com/prod041.htm
Rifles. www.angelfire.com/art/enchanter/blast.html

Rivera, Melissa and Aaron C. Davenport. "Airborne Use of Force." *The Coast Guard Proceedings of the Marine Safety & Security Council* Spring 2006. www.uscg.mil/proceedings/Spring06/SPRING%2006/Article%20PDFs/AirborneUseofForce.pdf

Rock Creek Barrels 101 Ogden Avenue Albany, WI 53503 www.rockcreekbarrels.com

Rocketto, Hap. A Short History of the Distinguished Shooter Program. May 01, 2006. www.odcmp.com/Competitions/Distinguished_History.pdf

Rogue M14HDW www.athenswater.com/Rogue_M14_HDW.html

Ron Brown Custom Slings P. O. Box 5181 Fitzgerald, GA 31750
www.servicerifleslings.com

Rooster33 P. O. Box 1034 5658 Vedder Road Chilliwack, British Columbia, Canada V2R 3N7 <http://whamocamo.bizland.com/rooster33/>

Run Guns 140 N. Western Avenue Route 31 Unit B Carpentersville, IL 60110
www.rguns.net

Russell, Michael. Oil Finishes for Wood - Which One? <http://ezinearticles.com/?Oil-Finishes-for-Wood---Which-One?&id=192572>

Russell, Steven D. Tung & Linseed Oils. www.sydneywoodturners.com/au/site/articles/finishing/oils.html

S & J Hardware www.sjhardware.com

S.O. Tech 5290 West Washington Boulevard Los Angeles, CA 90016
www.specopsech.com

Saga of the Sage www.athenswater.com/M1A_Scout_Squad_EBR.htm

SAGE Chopmod EBR CQB Review: Trimming weight from the Beast!
www.tacticalworks.ca

Sage Enhanced Battle Rifle. "USCG SAGE EBRM14T / PROJECT COMPLETE." <http://sageebr.com/2011/07/05/uscg-sage-ebrm14-t--project-complete.aspx>

Sage International, Ltd. 3391 East Eberhardt Street Oscoda, MI 48750
www.sageinternationalltd.com/si/index.html

Sage International Enhanced Battle Rifle Chassis Review www.tacticalworks.ca

Sarco, Inc. P. O. Box 98 323 Union Street Stirling, NJ 07980 www.sarcoinc.com

Sardius M26 sniper rifle. <http://translate.google.com/translate?hl=en&sl=zh-CN&u=http://www.gun-world.net/isreal/tci/m26.htm&sa=X&oi=translate&resnum=8&ct=result&prev=/search%3Fq%3DNehemiah%2BSirkis%26hl%3Den>

Satern Custom Machining 320 West 5th Avenue North Estherville, IA 51334
www.saternmachining.com

Saturday, October 22, 1967: March on the Pentagon <http://home.sandiego.edu/~hbarns/1967.htm>

Sawmill Creek Woodworkers Forums www.sawmillcreek.org

Scarface <http://www.scarface-usmc.org>

Schneider, Jim. "Relatives sue Intratec, Hell-Fire, USA Magazines." *Shooting Industry* October 1994. http://findarticles.com/p/articles/mi_m3197/is_n10_v39/ai_16373708

SecurityArms.com www.securityarms.com

Sellars, John R. "Some Memories of My Career." www.aiaa-my aerospace.org/rhttp/stories/sellars_career.pdf

Seneca Wire & Manufacturing Company 319 South Vine Street Fostoria, OH 44830
www.senecawire.com

Shilen Rifles, Inc. P. O. Box 1300 Ennis, TX 75120 www.shilen.com

Shinsung Industrial Co. 38-6, Gueok-ri, Yongjin-myeon, Wanju-gun, Jeollabuk-do, Korea
www.shinsungrifle.com

Shooters Den 7025 Whitewater Drive Jacksonville, OR 97530 www.tedbrownrifles.com

ShootingSight, LLC 607-600 Redna Terrace Cincinnati, OH 45215
www.shootingsight.com

Short Rifle Stock Systems, Inc. www.shortrifles.com

Silencer Talk. www.silencertests.com

Single Base Smokeless Powder MSDS. IMR Powder Company http://avogadro.chem.iastate.edu/MSDS/smokeless_powder.htm

Sison, Jose Maria. http://en.wikipedia.org/wiki/Jose_Maria_Sison

Skelton, Bart. "Short. . .With An Attitude." *Guns and Ammo* July 2005.
www.gunsandammomag.com/long_guns/socom_012306/

Smith Enterprise, Inc. 1701 West 10th Street # 14 Tempe, AZ 85281
www.smithenterprise.com

Smith Enterprise, Inc. "MD Labs XF7 Weapon Lube Material Safety Data Sheet."
www.smithenterprise.com

Smith Enterprise, Inc. "Smith Enterprise Upgrades Battle-Worn Sound Suppressors for Silver Star Recipient in the 82nd Airborne." smithenterpriseinc.blogspot.com July 28, 2013.

Sniper Country discussion board <http://www.snipercountry.com/HotTips/RifleSelectAR10M1A.htm>

Sniper Rifles www.poultorp.dk/df/sniper.html

Southwest Petro-Chem Div Witco Chemical Corporation. Rifle Grease Material Safety Data Sheet. November 01, 1990. <http://hazard.com/msds/f2/bfn/bfnlb.html>

SparrowHawk Stocks 12580 Main Road East Marion, NY 11939
www.sparrowhawk14.com

Specter Gear 1107 E. Douglas Visalia, CA 93292 www.spectergear.com

Speedlock CS Springs www.zediker.com/books/ar15/zbay2.html#cssprings

Springfield Armory, Inc. 420 West Main Street Geneseo, IL 61254 www.springfield-armory.com

Springfield Armory National Historic Site. www.rediscover.com/spring.htm

Springfield Technical Community College. www.stcc.edu

SSI Manufacturing Technologies Corporation 675 Emmett Street Bristol, CT 06010
www.ssimanufacturing.com

Stamped Out Identification Tag Specialists. <http://stampedout.net/odds-004-nsn.html>

State of California. www.sos.ca.gov/business

State of Illinois. www.ilsos.gov/corporatellc

Steelhawk Airsoft 18232 E. Gale Avenue City of Industry, CA 91748 <http://steelhawkairsoft.com>

Stitchery of West Virginia. www.m1acheekpad.com

Stone Axe Engineering. www.stoneaxeengineering.com

Stonecipher, Kent. "M14 Enhanced Battle Rifle - Rock Island (M14EBR-RI)." Oklahoma City Firearms Examiner: June 25, 2010. www.examiner.com

Stonecipher, Kent. "Squad Designated Marksman M14 rifle training at Ft. Carson." Oklahoma City Firearms Examiner: May 19, 2010. www.examiner.com

Stonecipher, Kent. "The M14 Enhanced Battle Rifle at Rock Island Arsenal." Oklahoma City Firearms Examiner: July 30, 2010. www.examiner.com

Strait, Tim Warbirds Custom Guns Houston, TX www.warbirdscustomguns.com

Sturm, Ruger & Co., Inc. Lacey Place Southport, CT 06890 www.ruger.com

Sturmgewehr.com discussion board www.sturmgewehr.com

Sun Valley MCJROTC. www.svmcjrrotc.org/forums/

Suppressed Tactical Weapons, Inc. 6911 Bill Poole Road Rougemont, NC 27572
www.stwibs.com/About_STW/M4_3L/M14_Suppressor/m14_suppressor.html

Surefire, LLC 18300 Mount Baldy Circle Fountain Valley, CA 92708 www.surefire.com

T65, T86 and T91 assault rifle (Taiwan). <http://world.guns.ru/assault/as82-e.htm>

Tac Pro, Inc. 1136-3 Centre Street P. O. Box 428 Thornhill, ON L4J 3M8
www.tacpro.com

Tactical Assault Gear, Inc. 600 Palm Avenue Suite # 225 Imperial Beach, CA 91932
www.tacticalassaultshop.com

Tactical Forums. "USMC M14." January 05, 2002. www.tacticalforums.com/ubb/Forum50/HTML/000087.html

Tactical Forums. "Weapons lube costing lives in Iraq." November 19, 2003. [www.http://www.tacticalforums.com/cgi-bin/tacticalubb/ultimatebb.cgi?ubb=get_topic;f=1;t=001324](http://www.tacticalforums.com/cgi-bin/tacticalubb/ultimatebb.cgi?ubb=get_topic;f=1;t=001324)

Tactical Intervention Specialists 2431 Peralta Office K Oakland, CA 94607
www.tacticalintervention.com

Tactical Night Vision Company 25612 Barton Road # 328 Loma Linda, CA 92354
www.tnvc.com

Tactical Tailor 12715 Pacific Highway SW Lakewood, WA 98499 www.tacticaltailor.com

Tactical Works. P. O. Box 27020 Tuscany RPO Calgary, Alberta, Canada T3L 2Y1
www.tacticalworks.ca

Taiwanmilitary.org. <http://taiwanmilitary.org/>

Talbot 2210 East Grand Blanc Road Grand Blanc, MI 48439-8113 www.talbot.us

TangoDown 1588 Arrow Highway Unit F La Verne, CA 91750 www.tangodown.com

Tapco, Inc. P. O. Box 2408 Kennesaw, GA 30156 www.tapco.com

Tasco 9200 Cody Overland Park, KS 66214 www.tasco.com

TCI89 sniper rifles. <http://translate.google.com/translate?hl=en&sl=zh-CN&u=http://www.gun-world.net/isreal/tci/m26.htm&sa=X&oi=translate&resnum=8&ct=result&prev=/search%3Fq%3DNehemiah%2BSirkis%26hl%3Den>

Tech-SIGHTS, LLC. 904 Deer Run Drive Hartsville, SC 29550 www.tech-sights.com

Teflon. www.tuberose.com/Teflon.html

Temco Japan Co. Lt. "Bone Conduction." <http://www.temco-j.co.jp/english/boneconduction/index.html>

The American Historical Foundation The Vietnam War Commemorative M14
www.ahfrichmond.com/projectgraphics/061viet.ahf

The Amherst Depot 349 W. Dearborn Street Englewood, FL 34223 www.amherst-depot.com

The Beta Company 2137B Flintstone Drive Tucker, GA 30084 www.betaco.com

The Business Identification Number Cross-reference System. https://www.bpn.gov/bincs/begin_search.asp

The Firearm Blog. "XT98 Semi-automatic Sniper Rifle (M14 style rifle) and XT97 Pistol." www.thefirearmblog.com/blog/2011/08/23/xt98-semi-automatic-sniper-rifle-m14-style-rifle-and-xt97-pistol/

The First Shot CMP On-line Magazine <http://www.odcmp.org/0704/default.asp?page=04FSCEREMONY2>

The Gun Zone. ""Mail Call!" Archives." November 30, 2000. <http://www.thegunzone.com/let-2000.html>

The Gun Zone. "The Rules." www.thegunzone.com/therules.html

The History of Arlington National Cemetery. <http://library.thinkquest.org/2901/HISTORY.HTM>

The Israeli Special Forces Home Page. www.isayeret.com

The Kapowwe Company 32015 State Highway 249 Suite 121 Pinehurst, TX 77362 www.kapowwe.com

The M-14/M1A Firing Line discussion board www.m14tfl.com

The Philadelphia Code. <http://municipalcodes.lexisnexis.com/codes/philadelphia>

The Piping Tool Box. "Identification Tests for Stainless Steels." www.piping-toolbox.com/51_383.html

The Piping Tool Box. "Metals and Corrosion Resistance." www.piping-toolbox.com/51_49.html

The Robar Companies, Inc. 21438 North 7th Avenue Suite B Phoenix, AZ 85027 www.robarguns.com

The Saga of Hill 950. www.willpete.com/saga_of_hill_950.htm

The United States Army Marksmanship Training Unit www.usarec.army.mil/hq/amu

The Upgrade Path Inc. for M14.ca 3925 Garnet Place Victoria, BC V8P 5G7 www.m14.ca

The Vietnam Database M1956 Webbing www.thevietnam-database.co.uk/USArmy/M56webbing.htm

The Vietnam Database M1967 Webbing www.thevietnam-database.co.uk/USArmy/M67webbing.htm

The Vietnam Database USMC Webbing www.thevietnam-database.co.uk/Usmc/Mwebbing.htm

The Vietnam Files www.thevietnamfiles.com

Thermold Magazines www.thermoldmagazines.com

Thorp, T. M. "Review of Firearms Control in New Zealand." 30 June 1997. <http://teapot.usask.ca/cdn-firearms/Research/Thorpe.nz/>

Thrustline Manufacturing, Inc. 2930 Pennsylvania Avenue # 92 Ogden, UT 84401 <http://thrustlinemfg.com/index.html>

M14 RIFLE HISTORY AND DEVELOPMENT

Tiarco Chemical "Octopol Grease & Lubricant Dithiocarbamates." Dalton, GA
www.tiarco.com/Gease%20and%20Lube%20Dithiocarbamates.htm

Tim's TV Showcase <http://timvp.com/gomer.html>

Topper Deluxe Reading. 1965 Consumer Mini-Catalog. <http://users.rcn.com/ed.ma.ultranet/deluxred.htm>

Traditions Military Video www.militaryvideo.com

Treeline Enterprises www.treelinem14.com

Tremblay, Nicholas, Corporal. "Marine Corps Designated Marksmen." Marine Corps News Service: November 15, 2003. http://m3.doubleclick.net/814859/1intercept_ros224.html

Trijicon, Inc. 49385 Shafer Avenue Wixom, MI 48393 www.trijicon.com

Triple K Manufacturing Company 2222 Commercial Street San Diego, CA 92113
www.triplek.com

Tristar Sporting Arms, Ltd. 1816 Linn Street North Kansas City, MO 64116
www.tristarsportingarms.com/

Troy Industries 128 Myron Street West Springfield, MA 01089 www.troyind.com

TRW Low Maintenance Rifle. www.securityarms.com/20010315/galleryfiles/2500/2546.htm

Tuff Products www.tuffproducts.com

Turner Saddlery P. O. Box 120 Clay, AL 35048 www.turnersling.com

TV.com. www.tv.com/mail-call/show

Tyler Manufacturing & Distributing Co., Inc. P. O. Box 94845 Oklahoma City, OK 73143
www.t-grips.com

U S Armory P. O. Box 15154 Wilmington, NC 28408 www.usarmory.com

U. S. and Soviet Military Aid. www.fas.org/asmp/library/scourge/scourge-ch3.pdf

U. S. Department of State Dispatch. Bureau of Public Affairs: Volume 5 Number 22 May 30, 1994. <http://dosfan.lib.uic.edu/ERC/briefing/dispatch/1994/html/Dispatchv5no22.html>

Ultimak 2216 South Main Suite B2 Moscow, ID 83843 www.ultimak.com/M8.htm

Unertl Ordnance Company, Inc. 2900 S. Highland Drive Bldg 18 Unit C Las Vegas, NV 89109 www.unertloptics.com

United States Code www4.law.corenell.edu/uscode/

United States Environmental Protection Agency. Guide to Cleaner Technologies Alternative Metal Finishes EPA/625/R-94/007. Office of Research and Development: Washington, DC, September 1994.

United States Marine Corps Marines Equipment. www.marines.com/about_marines/marinegear.asp?format=flash

United States Patent and Trademark Office. www.uspto.gov

United States Naval Special Warfare Development Group. http://en.wikipedia.org/wiki/SEAL_Team_Six

Unknown. "NRA and Springfield Armory Launch New M1A Match." The National Rifle Association: 2007. www.nra.org/Article.aspx?id=7440

U.S. Air Force Rifle Distinguished Badge Numbers. www.afsv.af.mil/AFSports/Documents/BadgeRiflePublic.doc

U.S. Marine Corps Designated Marksman Rifle www.answers.com/main

US Marines Combined Action Platoons <http://capmarine.com>

USAR Shooting Teams Alumni Association <http://www.usarshooters.org>

USMC / Combat Helicopter Association Image Catalog Phot #3859 M-14 & M-16s, TET 68 HUE, fighting at the WALL! www.popasmoke.com

USMC / Combat Helicopter Association Image Catalog Photo #4479 Roger Mastrorillo Chu Lai 1969 www.popasmoke.com

Viet Nam Sniper. www.vietnamsniper.com

Vietnam War Guns www.vietnamwar-guns.com

Vietnam War Individual Equipment. www.vietnamgear.com/equipment.aspx?cat=8

Vltor M1A/M14 Modstock and CAS-14/Cluster Rail Handguard www.militarymorons.com/weapons/longguns.html

Vltor Weapon Systems 3735 N. Romero Road Tucson, AZ 85705 www.vltor.com

W. C. Wolff Company P. O. Box 458 / Dept. 100 Newton Square, PA 19073 www.gunsprings.com

War Rifles discussion board www.warrifles.com

WarChina.com. "The United States M14 Rifles." www.warchina.com-n19286c47.aspx

Wayne Machine Inc. No. 10 Alley 35 Lane 193 Chung-Cheng North Road Sanchung City Taipei, Taiwan 241 Republic of China <http://waynemachine.com.tw/>

Welker, David. "The Chinese Military - Industrial Complex Goes Global." The Monopoly Makers: June 1997 Volume 18 Number 6. <http://multinationalmonitor.org/hyper/mm0697.05.html>

Wenig Custom Gunstocks, Inc. 103 North Market Street Lincoln, MO 65338 www.wenig.com

West Texas Armory 10025 East CR 6400 Lubbock, TX 79403 <http://westtexasarmory.com>

Whamo Camo P. O. Box 367 Seneca, MO 64865 www.whamo-camo.com

William J. Ricca Surplus Sales P. O. Box 25 New Tripoli, PA 18066 www.billricca.com

Wilson Arms Company 97-101 Leetes Island Road Branford, CT 06405 www.wilsonarms.com

Windy City Sourcing, Inc. P. O. Box 581 Itasca, IL 60143 www.windycitysourcing.com

Winston, Julian. "Guns in New Zealand." http://julianwinston.com/guns/nz_guns.php

Woodworkers Source. www.exotic-hardwoods-northamerica.com

Wright, David. "In Darfur, Teens With Machine Guns See No End to Violence." ABC World News Tonight: May 24, 2006. <http://abcnews.go.com/WNT/>

X-PER-X, Inc. "Stainless Steels and Corrosion." 3420, boulevard, Saint-Joseph Est Montreal, Quebec, Canada H1X 1W6 www.xperx.ca/new2_a.html

X-treme Shooting Products, LLC P. O. Box 829 Milford, OH 45150 www.x-tremeshooting.com

XS Sight Systems 2401 Ludelle Fort Worth, TX 76105 www.xssights.com

Watters, Daniel. 5.56 x 45mm: 1957 - 1962 www.thegunzone.com/556dw-1.html

Watters, Daniel. 5.56 x 45mm: 1963 - 1964 www.thegunzone.com/556dw-2.html

Watters, Daniel. 5.56 x 45mm: 1965 - 1966 www.thegunzone.com/556dw-3.html

Watters, Daniel. 5.56 x 45mm: 1967 www.thegunzone.com/556dw-4.html

Watters, Daniel. 5.56 x 45mm: 1968 - 1969 www.thegunzone.com/556dw-5.html

Watters, Daniel. 5.56 x 45mm: 1970 - 1973 www.thegunzone.com/556dw-6.html

Yankee Hill Machine Co., Inc. 20 Ladd Avenue Suite 1 Florence, MA 01062 www.yankeehillmachine.com

Young Manufacturing, Inc. 3613 N. 35th Avenue Phoenix. AZ 85017 www.youngmanufacturing.net

Zahal Israeli Tactical Gear www.zahal.org

Zediker Publishing M14 Maintenance Parts One, Two and Three. www.zediker.com

Zion's Camp. <http://zionscamp.yuku.com/>

Other Sources

A. R. Sales Co. Mark IV Rifle. 1971 sales literature.

Anzivino, Scott. Personal electronic mail. February 07 and 09, 2005.

Anzivino, Scott. Personal electronic mail. August 27 and 31, 2005.

Anzivino, Scott. Telephone interview. January 30, 2005.

Armstrong, David. "M14 to MK 14 - Evolution of a Battle Rifle." National Defense Industrial Association Small Arms Symposium & Exhibition: May 7-10, 2007.

Armstrong, David. "The M14 EBR - a Continuing Evolution." National Defense Industrial Association Small Arms Symposium & Exhibition: May 14-17, 2012.

Armstrong, David. Personal electronic mail. November 20, 2004.

Armstrong, David. Personal electronic mail. April 17, 2006.

Armstrong, David. Personal electronic mail. February 26, 2007.

Armstrong, David. Personal electronic mail. April 11, 2011.

- Audette, Richard. "Project Manager Soldier Weapons Overview for the Small Arms Symposium & Exhibition." National Defense Industrial Association Small Arms Symposium & Exhibition: May 7-10, 2007.
- AWC Systems Technology. 2008 Product Catalog. P. O. Box 41938 Phoenix, AZ 85080
- Ballance, Elmer. Telephone interview. October 08, 2004.
- Bennicas, Michael. Personal electronic mail. May 05, 2004.
- Biancospino, Lou. Telephone interview. October 07, 2003 and May 08, 2009.
- Biancospino, Lou. Personal electronic mail. Various dates in 2004 and 2005.
- Biancospino, Lou. Personal discussion. April 28, 2007.
- Biancospino, Lou. Personal electronic mail. January 28, 2010.
- Bidwell, William. Personal electronic mail. December 03, 06, 07, 10, 12, 13, 14 and 22, 2007.
- Boudreau, Brian. Personal electronic mail. August 18 and 30, 2007.
- Braun, Thomas. "The M14 Rifle in Germany."
- Brenner, Burton. Personal discussion. August 28, 2008.
- Brezinski, Alan. Personal electronic mail. October 16, 2004.
- Brezinski, Alan. Telephone interview. October 16, 2004.
- Brezinski, Alan. Telephone interview. October 20, 2004.
- Brezinski, Alan. Personal electronic mail. July 31, 2006.
- Brezinski, Alan. Personal electronic mail. January 03, 2007.
- Brown, Frank L. "Critical Combat Performances, Knowledges, and Skills Required of the Infantry Rifle Squad Leader Rifle, 7.62-mm M14." The George Washington University Human Resources Research Office: December 1968.
- Brown, Frank L. "Critical Combat Performances, Knowledges, and Skills Required of the Infantry Rifle Squad Leader Rifle, 7.62-mm M14A1." The George Washington University Human Resources Research Office: December 1968.
- Brown, Ted. Personal electronic mail. May 21, 2004 and July 03, 2005.
- Brown, Ted. Personal discussion. August 06, 2004.
- Brown, Ted. Personal electronic mail. September 16 and 19, 2005.
- Brown, Ted. Personal electronic mail. December 12, 2007.
- Brown, Ted. Personal discussion. April 28, 2007.
- Buss, Thomas A. Ohio Gun Collector Association Report. Issues dated September 18, 1971 to May 09, 1976.
- Buss, Thomas A. Personal notes regarding a visit to Springfield Armory Museum March 30, 1971.

M14 RIFLE HISTORY AND DEVELOPMENT

- Buss, Thomas A. Personal notes and documents regarding Springfield Armory, Inc. January 12, 1983.
- Buss, Thomas A. Personal notes and documents regarding Springfield Armory, Inc. January 13, 1983.
- Buss, Thomas A. Personal discussion and articles examined. September 03, 2006.
- Buss, Thomas A. Personal electronic mail. March 08 and August 27, 2006.
- Button, Rick. "United States Coast Guard." Joint Services Small Arms Synchronization Team Meeting 2005 NDIA International Infantry and Joint Services Small Arms Symposium.
- Cabral, Richard. Personal discussion and product demonstration. July 13, 2010.
- Chalker, John. Personal discussion. December 05, 2005.
- Chicas, Sam. Personal electronic mail. December 21, 2007.
- Chrismon, Harold. 3421 Ave "N" Plano, TX 75074
- Civilian Marksmanship Program. Recall of M14 Rifles. Letter from Charles W. Maddox, Chairman, CMP Board of Directors dated January 08, 2007.
- Collins, Chick. Personal electronic mail. June 22, 2007.
- Controlled Thermal Technology, Inc. 2617 West Cypress Street Phoenix, AZ 85009 Certification of Conformance CTT Job # BB36063. April 16, 2008.
- Coogan, Mike. Private correspondence. June 22 and 26, 2006.
- Corcoran, Ken. Telephone discussion. February 02, 2007.
- Crist, Stanley C. Personal electronic mail. June 17, 20, and 21, 2006.
- Davis, Dick. Personal discussion. February 12, 2004.
- Davis, Todd. Personal electronic mail. April 11, 2009.
- Deguzman, James. Personal electronic mail. July 29, 2006.
- Dickson, David R. Personal electronic mail from Wayne Machine, Inc. August 30 and 31, 2006.
- Dow, Bruce R. Personal discussion. January 05, 2007.
- Downey, Jerry. Personal electronic mail. October 20, 2009.
- Ferren, Jason. Telephone discussion. April 01, 2003.
- Fisher, Dave. Telephone discussion. April 16, 2005.
- Fiske Brothers Refining Co. Lubriplate No. 130-A, No. 130-AA Material Safety Data Sheet. September 13, 2002. 129 Lockwood Street Newark, NJ 07105.
- Fiske Brothers Refining Co. Specification sheet for LUBRIPLATE No's. 130-A & 130-AA. 129 Lockwood Street Newark, NJ 07105
- Global Defense Initiatives, Inc. GDI Product Development History G1-OSM (Optical Sight Mount) For M14/M1A/M21/M25 Rifle Systems. April 30, 2008.

Goluzza, Frank. Personal electronic mail. December 17, 2011.

Green, Charles T. Personal electronic mail. Various dates in 2006 and 2007.

Grove, Bob. Personal electronic mail. August 08, 2004.

Halstead, Richard Paul. Personal electronic mail. December 08 and 11, 2007.

Harrington & Richardson, Inc. 320 Park Avenue Worcester, MA. The Simulator M14 cal. .22 Speeds Arms Training Lowers Costs. Sales brochure circa 1959.

Harrington & Richardson, Inc. First Northeast Commerce and Industry Exposition brochure. Date unknown.

Harrington & Richardson, Inc. *Gun Flash*. November 1962: 1-2, 5.

Harrington & Richardson, Inc. *Gun Flash*. December 1962: 1-4.

Harrington & Richardson, Inc. *Gun Flash*. April 1963.

Harrington & Richardson, Inc. The M14 Guerilla Rifle. Sales advertisement circa 1962.

Harrington & Richardson, Inc. 95th Anniversary Catalog. 1965: 32 - 33.

Harrington & Richardson, Inc. Letter in response to Thomas A. Buss letter dated January 8, 1971 regarding the M14 Simulator rifle.

Hartman, Mark. Personal interview. January 21, 2010.

Hogan, Edward M. "Ned". Telephone interview. July 16, 2006.

Hogan, Edward M. "Ned". Letter to Mel Smith dated 14 December 1969.

Hogan, Edward M. "Ned". Letter to Mel Smith dated 9 July 1970.

Hogan, Edward M. "Ned". Letter dated July 31, 2006.

Hill, Jim. Electronic mail to Art Luppino. August 16, 2007.

Huang, George. Personal discussion. September 05, 2009.

Hultman, Tim. Personal electronic mail. August 06, 2007.

Humphreville, Mark. Telephone interview. March 18, 2007.

Humphreville, Mark. Personal electronic mail. June 04 and July 24 and 25, 2007.

Humphreville, Mark. Personal electronic mail. July 19, 2009 and October 16, 2011.

Hyland, James. Personal discussion. July 21, 2005.

Ingram Custom Rifleworks, Inc. South Cariboo, British Columbia, Canada.

Karnes, Steve. Telephone interview. October 12, 2005.

Keller, George E., Ph. D. Analysis of Effectiveness of Vortex ^(R) Flash Suppressor Design on Small Arms Muzzle Flash and Blast. 2010.

Kelley, Charles W. Personal electronic mail. August 12, 2006.

Kelley, Drew. Personal discussion. January 18, 2011.

Kirotar, Heikii. Personal electronic mail. January 20 and March 23, 2008.

M14 RIFLE HISTORY AND DEVELOPMENT

Knight's Manufacturing Company 701 Columbia Boulevard Titusville, FL 32780

Kohl, Bob. Personal discussion. November 01, 2010.

Kuleck, Walter J., Ph.D. Personal electronic mail. Various dates in 2004 and 2005.

Kuleck, Walter J., Ph.D. Personal electronic mail. May 27 and June 01, 2007.

Johnson, Mike R. Personal electronic mail. August 15, 2007.

Jones, Lisa. Personal electronic mail. November 11, 2007 and May 03, 2011.

L. H. Gun Company. The M1A Civilian Rifle. 1971 sales flyer.

L. H. Gun Company. L. H. Gun Company's Springfield Armory 7.62 MM M1A. 1973 sales brochure.

Larson, Rick. Personal electronic mail. February 05, 2008.

LAW483 Tactical M14 Systems. Troy MCS Installation Instructions. P. O. Box 2892 Weatherford, TX 76087. www.LAW483.com

Lawrence, Anthony. Personal electronic mail. Various dates 2011 through 2013.

Lee, Nolan. Personal electronic mail. May 28, 2007.

Lehman, Mark. Personal electronic mail. January 05, 2007, February 11 and March 01, 2008, and January 20, February 03, March 03 and October 04, 2011.

Letson, Mike. Personal electronic mail. Various dates in 2003 and 2004.

Loyola, Edward. Personal electronic mail. January 05, 2005.

Luppino, Art. Personal electronic mail. August 16 and 20, 2007.

Madacy Entertainment Group. We Were Heroes 1st Cavalry Division (Airmobile) Vietnam DVD Set. 2002. P. O. Box 1445 St. Laurent, Quebec, Canada H4L 4Z1

Marathon Music & Video. Vietnam Combat DVD Set. 2002. P. O. Box 22738 Eugene, OR 97402

Marsh, Chuck, et al. "U.S. Navy Small Arms Ammunition Advancements." 2009 NDIA International Infantry and Joint Services Small Arms Symposium.

Mason, Jim. Personal discussion and articles examined. September 02, 2006.

Mason, Jim. Personal discussion and articles examined. January 04, 2007.

Mateiko, Mitchell. Personal electronic mail. May 11, 2012.

Mathewson Tool Company. Undated sales flyer illustrating various components fabricated. Provided by Thomas A. Buss.

Maunz, Karl. Personal discussion and personal documents and records examined February 12, 2005.

Maunz, Karl. Telephone interview. October 21, 2004.

Maunz, Karl. Telephone interview. October 28, 2004.

Maunz, Karl. Telephone interview. December 15, 2004.

Maunz, Karl. Telephone interview. January 17, 2005.

Maunz, Karl. Telephone interviews. March 11, 12 and 13, 2005.

Maunz, Karl. Telephone interview. September 01, 2005.

Maus, Art. Sherluk P. O. Box 156 Delta, OH 43515 Personal discussion. December 06, 2003. www.sherluk.com

McCann Industries. 2008 Product Catalog. 132 South 162nd P. O. Box 641 Spanaway, WA 98387

McMillan Fiberglass Stocks, Inc. 1638 W. Knudsen Drive Suite 101 Phoenix, AZ 85027. 1994 Catalog.

Metals Engineering & Testing Laboratories 2040 W. Quail Avenue Phoenix, AZ 85027. Test Report for Lab No. 048-585. April 28, 2008.

Mil-Spec Logistics, Inc. 1303 W. Buckingham Suite 103-102 Garland, TX 75040. Installation instructions for M14/M21 Scope Mount.

Mo's Competitor Supply. 34 Delmar Drive Brookfield, CT 06804

Mock, James. Personal electronic mail. July 06, 07, 13, 20, 22, 24, 26 and 27, 2008.

Mock, James. Personal electronic mail. October 16, 2008.

Mock, James. Telephone interview of Robert E. Penney. July 29, 2008.

Mock, James. Telephone interview of Robert Thomasser. July 29, 2008.

Mock, James. Telephone interview of Leo Grizzaffi. July 31, 2008.

Morey, Evan K. Metallurgical Report Laboratory Number 081-622. Metals Engineering and Testing Laboratories: Phoenix, AZ, September 14, 2011.

Morrey, Jim. Personal electronic mail. June 22 through July 07, 2005.

Nimrod Technical Specifications. Product data sheet for Nimrod 6X40 rifle scope.

Nitrex Inc. 201 E. Mayflower Avenue North Las Vegas, NV 89030. Hardness test reports for two Chinese M14 bolts. April 23 and 26, 2010.

Nitrex Inc. 201 E. Mayflower Avenue North Las Vegas, NV 89030. Crystalline structure examination report for two Chinese M14 bolts. July 07, 2010.

Olive, Jim. "Joint Service Small Arms Systems Annual Symposium." United States Coast Guard Office of Counterterrorism & Special Missions Operations: May 07, 2007.

Other Source # 12. Telephone interview. April 28, 2004.

Other Source # 18. Personal electronic mail. October 18, 2004.

Other Source # 18. Telephone interview. October 24, 2004.

Other Source # 27. Telephone interview. November 24, 2004.

Other Source # 27. Telephone interview. November 30, 2004.

Other Source # 34. Telephone interviews. August 25 and 29, 2005.

Other Source # 49. Telephone interview. January 08, 2006.

- Other Source # 75. Personal discussion. January 05, 2007.
- Owens, James. Personal documents and electronic mail. June 22 through July 02, 2005.
- Papakotos, Kostas. Personal electronic mail. May 02, 2006.
- Palmer, Bradford B. Personal discussion. February 11, 2005.
- Pimley, Rick. Personal electronic mail. Various dates in 2004, 2005 and 2006.
- Pimley, Rick. Telephone interview. October 30, 2004.
- Poly Technologies, Inc. Legend Series sales flyer. 1988
- Porter, Brent. Personal electronic mail. July 19, 2004.
- Rader, Gary. Personal electronic mail. February 11, 12, and 13, 2007.
- Rankin, Claude. Telephone interview. May 08, 2006.
- Rankin, Claude. Telephone interview. February 14, 2008.
- Rankin, Claude. Telephone interview. September 07, 2010.
- Reese, Tom. "Buyer Beware." Factory letter and product review of Poly Technologies M-14S serial number 09384. March 01, 1994
- Ricca, William J. *Technical Manuals - A History*. May 2007.
- Ricca, William J. Electronic mail. March 12, 2012.
- Ricca, William J. Personal discussion. March 12, 2005.
- Ricca, William J. Personal discussion. October 08, 2005.
- Ricca, William J. *PS Magazine The Preventive Maintenance Monthly*. Compact disc compilation of articles from 1951 to 1973. New Tripoli, PA: 2006.
- Richter, Mark. "Interoperability and Integration of Dismounted Soldier System Weapon Systems." NATO Research and Technology Organization: May 09, 2007.
- Rock, Mike. Telephone interview. November 26, 2004.
- Ruehlin, Richard. "Navy Small Arms." National Defense Industrial Association Small Arms Symposium & Exhibition: May 08, 2007.
- Ruple, Frank W. Personal electronic mail. August 01, 2005.
- Russell, John K. Personal electronic mail. July 25 and 26, 2005.
- S&K Scope Mounts RR2 Box 72E Sugar Grove, PA 16350
- Sadlak, Mike. Personal discussion and company documents examined February 11, 2005.
- Sadlak, Mike. Personal electronic mail. January 09, 2005 and January 21, 2011.
- Sadlak, Mike. Telephone interview. June 21, 2004.
- Sadlak, Mike. Telephone interview. November 19, 2004.
- Sadlak, Mike. Telephone interview. November 26, 2004.

Sadlak, Mike. Telephone interview. December 10, 2004.

Sage International, Ltd. 2011 MSRP / Agency Price List.

Sage International, Ltd. M14ALCS/MP-EBR. January 2010.

Shannon, Dave. Telephone interview. March 05, 2007.

Shapiro, Jeff. Telephone interview. February 13, 2005.

Shearer, Donnie L. Personal electronic mail. October 02, 2004.

Shearer, Donnie L. Viet Nam Combat Photographs of the M14. January 27, 2006.

Shelton, Matt. Personal electronic mail. August 15, 2007.

Smith, Neal. Telephone interview. September 06, 2006.

Smith, Ron. Company documents examined February 18, April 09, and October 28, 2004 and March 20, 2012.

Smith, Ron. Personal discussions. January 26, February 18, 2004, April 09 and October 28, 2004.

Smith, Ron. Personal discussions. February 03 and October 29, 2008.

Smith, Ron. Personal discussion. March 08, 2009.

Smith, Ron. Personal discussion. April 14 and May 31, 2011.

Smith, Ron. Telephone interviews. April 17 and October 27, 2004.

Smith, Ron. Telephone interviews. May 25 and October 23, 2005.

Smith, Ron. Telephone interviews. March 18, August 04, and November 06, 2006.

Smith, Ron. Telephone interviews. March 05 and 22, June 27 and July 23, 2007.

Smith, Ron. Telephone interviews. February 06, March 29, and May 07, 2008.

Smith, Ron. Telephone interview. June 07, 2013.

Smith, William. Telephone interview. FTI, Inc. 8 Vreeland Road Florham Park, NJ 07932
March 02, 2007.

Smith Arms, International 1994 Catalog 1701 West 10th Street Tempe, AZ 85281

South Central Research Corporation P. O. Box 660 Katy, TX 77492

Sprey, Pierre M. "Evaluating Weapons: Sorting the Good from the Bad." The Pentagon Labyrinth: 10 Short Essays To Help You Through It. Center for Defense Information World Security Institute: February 2011.

Springfield Armory, Inc. Letter to Mario J. Gravina dated October 15, 2004. 420 West Main Street Geneseo, IL 61254

Springfield Armory, Inc. 1976, 1978 - 1981, 1983 - 1990, 1992 - 1996, 2000, 2002, 2004, and 2011 Retail Price Lists. 420 West Main Street Geneseo, IL 61254

Springfield Armory, Inc. 1989 Parts and Accessories Brochure. 420 West Main Street Geneseo, IL 61254.

M14 RIFLE HISTORY AND DEVELOPMENT

Springfield Armory, Inc. 1978, 1981, 1984, 1986 - 1990, 1992 - 1996, 2000, 2002 and 2004 -2011 Product Catalogs. 420 West Main Street Geneseo, IL 61254

St Paul, Jeff. Personal electronic mail. January 05, 2007.

Stenzel, Aimee, Ed. "Firearms Production In America 2002 Edition." Violence Policy Center. Washington, DC: 2003.

Stutesman, Dave. Personal electronic mail. August 03, 2006.

Sung, Paul S. Shinsung Industries Co., Ltd., USA Sierra Imports Company 40 Westpark Drive Daly City, CA 94105. Personal interview. January 21, 2010.

Tamilo, Douglas A. "Project Manager Soldier Weapons Briefing." National Defense Industrial Association Small Arms Symposium & Exhibition: May 23-26, 2011.

Thomas, Chris. Personal interview. January 21, 2010.

Thomasser, Robert. Telephone interview. August 06, 2008.

Todd, Richard. Personal electronic mail and photographs. December 28 and 29, 2011.
Tooltech 20 Church Street Oxford, MI 48371

Toms, Greg. Personal electronic mail. August 01 and 02, 2006.

Toms, Greg. Personal electronic mail. August 16, 2007.

Triple K Manufacturing Company. 2007-2008 Product Catalog. 2222 Commercial Street San Diego, CA 92113.

Troy Industries, Inc. 2005 Modular Weapon Systems Catalog 17 Main Street Lee, MA 01238

Troy Industries, Inc. 2010 Catalog West Springfield, MA 01089

Troy Industries, Inc. Sopmod-201 parts diagram. March 29, 2007.

TRW. Company documents. Various dates in 1962, 1963 and 1964. Provided by Thomas A. Buss.

TRW. "M-14 Order Makes TRW Top Rifle Producer." Friendly Forum newsletter. October 12, 1962. Provided by Thomas A. Buss.

TRW. "TRW Wins M-14 Match Rifle Contract." Friendly Forum newsletter. April 10, 1964. Provided by Thomas A. Buss.

TRW Systems Group. 5.56mm Low Maintenance Rifle. Redondo Beach, CA: 1973.

Tuttle, Art H. "The Marine Corps Enlightened M1 Hammer." August 08, 1984.

Unknown. "Meeting Our Suppliers; Walt Wolff, Jr., W. C. Wolff Co." Brownells, Inc.

Unknown. Printable M14 Magazine. <https://www.dropbox.com/s/yb2inpdhvdw16fv/M14%20Magazine%20V2.rar>

Unknown. Telescope / Auto-Ranging ART II Operation Manual. Provided by Jim Mason.

Watters, Daniel E. Personal electronic mail. March 22 and April 02, 2008.

Watters, Daniel E. Personal electronic mail. September 02, 2009.

Wozny, Douglas K. Personal electronic mail. August 17, 2008.

Young, Kevin. Personal electronic mail. December 30, 2004 and September 11, 2013.

Youngson, Chris. Personal interview. January 21, 2010.

Yost, John. "50th Annual Joint Services Small Arms Section Symposium and Exhibition."
May 11, 2004.

Yu, Scott. Personal electronic mail. June 22, 2005.

Zakreski, Larry. M14 Clinic FAQ. December 03, 2007.

Zimmerman, Kim. Telephone interview. November 02, 2004.

"Ollis salus populi suprema lex esto" - Cicero, *De Legibus*